

1 DRAFT 1.6
2 Geneva, May 17, 2012
3 CERN report
4 ECFA report
5 NuPECC report
6 LHeC-Note-2011-003 GEN



A Large Hadron Electron Collider at CERN

Report on the Physics and Design
Concepts for Machine and Detector

LHeC Study Group



To be submitted for publication

¹³ The Kandinsky painting is taken from a talk on gluon saturation and 5D black hole duality as presented
¹⁴ at the first CERN-ECFA-NuPECC Workshop on the LHeC held at Divonne near to CERN in September
¹⁵ 2008 [1].

Abstract

17 The physics programme and the design are described of a new electron-hadron collider, the LHeC, in which
18 electrons of 60 to possibly 140 GeV collide with LHC protons of 7000 GeV. With an ep design luminosity
19 of about $10^{33} \text{ cm}^{-2}\text{s}^{-1}$, the Large Hadron Electron Collider exceeds the integrated luminosity collected at
20 HERA by two orders of magnitude and the kinematic range by a factor of twenty in the four-momentum
21 squared, Q^2 , and in the inverse Bjorken x . The physics programme is devoted to an exploration of the
22 energy frontier, complementing the LHC and its discovery potential for physics beyond the Standard Model
23 with high precision deep inelastic scattering (DIS) measurements. These are projected to solve a variety of
24 fundamental questions in strong and electroweak interactions. The LHeC thus becomes the world's cleanest
25 high resolution microscope, designed to continue the path of deep inelastic lepton-hadron scattering into
26 unknown areas of physics and kinematics. The physics programme also includes electron-ion (eA) scattering
27 into a $(Q^2, 1/x)$ range extended by four orders of magnitude as compared to previous lepton-nucleus DIS
28 experiments. The LHeC may be realised either as a ring-ring or as a linac-ring collider. Optics and beam
29 dynamics studies are presented for both versions, along with technical design considerations on the interaction
30 region, magnets, cryogenics, RF, civil engineering and further components. A design study is also presented
31 of a detector suitable to perform high precision DIS measurements in a wide range of acceptance using
32 state-of-the art detector technology, which is modular and of limited size enabling its fast installation. The
33 detector includes tagging devices for electron, photon, proton and neutron detection near to the beampipe.
34 The LHeC is designed to be built and operated while the LHC runs. It is a major opportunity for progress
35 in particle physics and further exploits the investment made in the LHC.



36 LHeC Study Group

37 J.L. Abelleira Fernandez^{10,15}, C.Adolphsen³⁹, S.Alekhin^{40,11}, A.N.Akai⁰¹, H.Aksakal³⁰, P.Allport¹⁷, J.L.Albacete³⁷,
38 V.Andreev²⁵, R.B.Appleby²³, E.Arikan³⁰, N.Armesto³⁸, G.Azuelos²⁶, M.Bai⁴⁷, D.Barber^{11,17,23}, J.Bartels¹²,
39 J.Behr¹¹, O.Behnke¹¹, S.Belyaev¹⁰, I.BenZvi⁴⁷, N.Bernard¹⁶, S.Bertolucci¹⁰, S.Bettoni¹⁰, S.Biswal³², J.Blumlein¹¹,
40 H.Boettcher¹¹, H.Braun⁴⁸, S.Brodsky³⁹, A.Bogacz²⁸, C.Bracco¹⁰, O.Bruening¹⁰, E.Bulyak⁰⁸, A.Bunyatian¹¹,
41 H.Burkhardt¹⁰, I.T.Cakir⁵⁴, O.Cakir⁵³, R.Calaga⁴⁷, E.Ciapala¹⁰, R.Ciftci⁰¹, A.K.Ciftci⁰¹, B.A.Cole²⁹, J.C.Collins⁴⁶,
42 J.Dainton¹⁷, A.De.Roeck¹⁰, D.d’Enterria¹⁰, A.Dudarev¹⁰, A.Eide⁴³, R.Enberg⁵⁸, E.Eroglu⁴⁵, K.J.Eskola¹⁴,
43 L.Favart⁰⁶, M.Fitterer¹⁰, S.Forte²⁴, P.Gambino⁴², H. García Morales¹⁰, T.Gehrmann⁵⁰, C.Glasman²², R.Godbole²⁷,
44 B.Goddard¹⁰, T.Greenshaw¹⁷, A.Guffanti⁰⁹, V.Guzey²⁸, C.Gwenlan³⁴, T.Han³⁶, Y.Hao⁴⁷, F.Haug¹⁰, W.Herr¹⁰,
45 B.Holzer¹⁰, M.Ishitsuka⁴¹, M.Jacquet³³, B.Jeanneret¹⁰, J.M.Jimenez¹⁰, H.Jung¹¹, J.M.Jowett¹⁰, H.Karadeniz⁵⁴,
46 D.Kayran⁴⁷, F.Kocac⁴⁵, A.Kilic⁴⁵, K.Kimura⁴¹, M.Klein¹⁷, U.Klein¹⁷, T.Kluge¹⁷, G.Kramer¹², M.Korostelev²³,
47 A.Kosmicki¹⁰, P.Kostka¹¹, H.Kowalski¹¹, D.Kuchler¹⁰, M.Kuze⁴¹, T.Lappi¹⁴, P.Laycock¹⁷, E.Levichev³¹,
48 S.Levonian¹¹, V.N.Litvinenko⁴⁷, A.Lombardi¹⁰, C.Marquet¹⁰, B.Mellado⁰⁷, K.H.Mess¹⁰, A.Milanese¹⁰, S.Moch¹¹,
49 I.I.Morozov³¹, Y.Muttoni¹⁰, S.Myers¹⁰, S.Nandi²⁶, P.R.Newman⁰³, T.Omori⁴⁴, J.Osborne¹⁰, Y.Papaphilippou¹⁰,
50 E.Paoloni³⁵, C.Pascaud³³, H.Paukkunen³⁸, E.Perez¹⁰, T.Pieloni¹⁵, E.Pilicer⁴⁵, B.Pire⁵⁵, A.Polini⁰⁴, V.Ptitsyn⁴⁷,
51 Y.Pupkov³¹, V.Radescu¹³, S.Raychaudhuri²⁷, L.Rinolfi¹⁰, R.Rohini²⁷, J.Rojo²⁴, S.Russenschuck¹⁰, C.A.Salgado³⁸,
52 K.Sampe⁴¹, R.Sassot⁵⁷, E.Sauvan¹⁹, M.Sahin⁰¹, U.Schneekloth¹¹, T.Schoerner Sadenius¹¹, D.Schulte¹⁰,
53 A.N.Skrinsky³¹, W.Smith²⁰, H.Spiesberger²¹, A.M.Stasto⁴⁶, M.Strikman⁴⁶, M.Sullivan³⁹, B.Surrow⁰⁵, S.Sultansoy⁰¹,
54 Y.P.Sun³⁹, L.Szymanowski⁵⁶, I.Tapan⁴⁵, P.Taels⁰², E.Tassi⁵², H.Ten.Kate¹⁰, J.Terron²², H.Thiesen¹⁰, L.Thompson²³,
55 K.Tokushuku⁴⁴, R.Tomás García¹⁰, D.Tommasini¹⁰, D.Trbojevic⁴⁷, N.Tsoupas⁴⁷, J.Tuckmantel¹⁰, S.Turkoz⁵³,
56 K.Tywoniuik¹⁸, G.Unel¹⁰, J.Urakawa⁴⁴, P.VanMechelen⁰², A.Variola³⁷, R.Veness¹⁰, A.Vivoli¹⁰, P.Vobly³¹,
57 R.Wallny⁵¹, S.Wallon⁵⁹, G.Watt¹⁰, G.Weiglein¹², C.Weiss²⁸, U.A.Wiedemann¹⁰, U.Wienands³⁹, F.Willeke⁴⁷,
58 B.-W.Xiao⁴⁶, V.Yakimenko⁴⁷, A.F.Zarnecki⁴⁹, F.Zimmermann¹⁰, R.Zlebcik⁶⁰, F.Zomer³³

59 ⁰¹ *TOBB University of Economics and Technology, Ankara, Turkey*

60 ⁰² *University of Antwerpen, Belgium*

61 ⁰³ *Univeristy of Birmingham, UK*

62 ⁰⁴ *University of Bologna, Italy*

63 ⁰⁵ *Massachusetts Institute of Technology, MIT, Boston, USA*

64 ⁰⁶ *IHE Brussels, Belgium*

65 ⁰⁷ *Harvard University, Cambridge, USA*

66 ⁰⁸ *Charkow National University, Ukraine*

67 ⁰⁹ *Freiburg University, Germany*

68 ¹⁰ *CERN, Geneva, Switzerland*

69 ¹¹ *DESY, Hamburg, Germany*

70 ¹² *University of Hamburg, Germany*

71 ¹³ *University of Heidelberg, Germany*

72 ¹⁴ *Jyväskylä University, Finland*

73 ¹⁵ *EPFL, Lausanne, Switzerland*

74 ¹⁶ *University of California in Los Angeles, UCLA, USA*

75 ¹⁷ *University of Liverpool, UK*

76 ¹⁸ *University of Lund, Sweden*

77 ¹⁹ *LAPP, Annecy, France*

78 ²⁰ *University of Madison, Wisconsin, USA*

79 ²¹ *University of Mainz, Germany*

80 ²² *University of Madrid, Spain*

81 ²³ *University of Manchester/Cockcroft Institute, UK*

82 ²⁴ *INFN Milano, Italy*

83 ²⁵ *LPI Moscow, Russia*

84 ²⁶ *University of Montreal, Canada*

85 ²⁷ *Tata Institute, Mumbai, India*

86 28 *Jefferson Laboratory, USA*
87 29 *Columbia University, New York, USA*
88 30 *Nigde University, Turkey*
89 31 *Budker Institute of Nuclear Physics SB RAS, Novosibirsk, 630090 Russia*
90 32 *Orissa University, India*
91 33 *Orsay, LAL, France*
92 34 *University of Oxford, UK*
93 35 *University of Pisa, Italy*
94 36 *University of Pittsburgh, USA*
95 37 *IPhT Saclay, France*
96 38 *University of Santiago de Compostela, Spain*
97 39 *SLAC, Stanford Linear Accelerator Centre, Stanford, USA*
98 40 *Serpukhov Institute, Russia*
99 41 *Tokyo Institute of Technology, Japan*
100 42 *University of Torino and INFN Torino, Italy*
101 43 *NTNU, Trondheim, Norway*
102 44 *KEK, Tsukuba, Japan*
103 45 *Uludag University, Turkey*
104 46 *Pennsylvania State University, USA*
105 47 *Brookhaven National Laboratory, BNL, USA*
106 48 *Paul Scherrer Institute, Villigen, Switzerland*
107 49 *Faculty of Physics, University of Warsaw, Poland*
108 50 *University of Zurich, Switzerland*
109 51 *ETH Zurich, Switzerland*
110 52 *INFN Gruppo Collegato di Cosenza and Universita della Calabria, Italy*
111 53 *University of Ankara, Turkey*
112 54 *SANAEM Ankara, Turkey*
113 55 *CPHT, École Polytechnique, CNRS, 91128 Palaiseau, France*
114 56 *National Center for Nuclear Research (NCBJ), Warsaw, Poland*
115 57 *Universidad de Buenos Aires, Buenos Aires, Argentina*
116 58 *Uppsala University, Sweden*
117 59 *Laboratoire de Physique Théorique, Université Paris XI, Orsay, France*
118 60 *Charles University, Praha, Czech Republic*

Preface

120 Preparations for new, big machines take time. The idea of an electron-proton (ep) collider in the LEP-LHC
 121 tunnel was discussed as early as 1984 [2], at the first LHC workshop at Lausanne. This was the time when
 122 the first ever built ep collider, HERA, was approved by the German government. HERA was a machine of
 123 about 30 GeV electron beam energy and nearly 1 TeV proton beam energy, a combination of a warm dipole
 124 electron ring with a superconducting dipole proton ring, in a 6 km circumference tunnel. The machine
 125 started operation 8 years after its approval. It reached luminosities of $10^{31} \text{ cm}^{-2} \text{ s}^{-1}$ in its first phase of
 126 operation which were increased by about a factor of 4 in the subsequent, upgraded configuration. HERA
 127 never attempted to collide electrons with deuterons nor with ions.

128 The realisation of HERA at DESY had followed a number of attempts to realise ep interactions in
 129 collider mode, mainly driven by the unforgettable Bjoern Wiik: since the late 1960s, he and his colleagues
 130 had considered such machines and proposed to probe the proton's structure more deeply with an ep collider
 131 at DORIS [3], later at PETRA (PROPER) [4] and subsequently at the SPS at CERN (CHEEP) [5]. Further
 132 ep collider studies were made for PEP [6], TRISTAN [7] and also the Tevatron (CHEER) [8].

133 In 1990, at a workshop at Aachen, the combination of LEP with the LHC was discussed, with studies [9–
 134 11] on the luminosity, interaction region, a detector and the physics as seen with the knowledge of that
 135 time, before HERA. Following a request of the CERN Science Policy Committee (SPC), a brief study of
 136 the ring-ring ep collider in the LEP tunnel was performed [12] leading to an estimated luminosity of about
 137 $10^{32} \text{ cm}^{-2} \text{ s}^{-1}$.

138 At the end of the eighties it had been anticipated that there was a possible end to the increase of the
 139 energy of ep colliders in the ring-ring configuration, because of the synchrotron radiation losses of an electron
 140 ring accelerator. The classic SLAC fixed target ep experiment had already used a 2 mile linac. For ep linac-
 141 ring collider configurations, two design sketches considering electron beam energies up to a few hundred
 142 GeV were published, in 1988 [13] and in 1990 [14]. As part of the TESLA linear collider proposal, an option
 143 (THERA) was studied [15] to collide electrons of a few hundred GeV energy with protons and ions from
 144 HERA. Later, in 2003, the possibility was evaluated to combine LHC protons with CLIC electrons [16]. It
 145 was yet realised, that the bunch structures of the LHC and CLIC were not compliant with the need for high
 146 luminosities.

147 In September 2007, the SPC again asked whether one could realise an ep collider at CERN. Some of us
 148 had written a paper [17] in the year before, that had shown in detail, for the first time, that a luminosity of
 149 $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$ was achievable. This appeared possible in a ring-ring configuration based on the “ultimate”
 150 LHC beam, with $1.7 \cdot 10^{11}$ protons in bunches 25 ns apart. Thanks to the small beam-beam tune-shift, it was
 151 found to be feasible to simultaneously operate pp in the LHC and ep in the new machine, which in 2005 was
 152 termed the Large Hadron Electron Collider (LHeC) [18]. Thus it appeared possible to realise an ep collider
 153 that was complementary to the LHC, just as HERA was to the Tevatron. The integrated luminosity was
 154 projected to be $O(100) \text{ fb}^{-1}$, a factor of a hundred more than HERA had collected over its lifetime of 15
 155 years.

156 It was clear that with a centre-of-mass energy of about $\sqrt{s} \simeq 1.5 \text{ TeV}$ an exciting programme of deep
 157 inelastic scattering (DIS) measurements at the energy-frontier was in reach. This would comprise searches
 158 and analyses for physics beyond the Standard Model, novel measurements in QCD and electroweak physics
 159 to unprecedented precision, as well as DIS physics at such low Bjorken x , that all the known laws of parton

160 and gluon interactions would have to be modified to account for non-linear parton interaction effects. It had
161 also been realised that the kinematic region, in terms of negative four-momentum-transfer squared, Q^2 , and
162 $1/x$, accessed in lepton-nucleus interactions could be extended by 4 orders of magnitude using the ion beams
163 of the LHC. A salient theme of the LHeC therefore is the precise mapping of the gluon field, over six orders
164 of magnitude in Bjorken x , in protons, neutrons and nuclei, with unprecedented sensitivity.

165 In the autumn of 2007, (r)ECFA and CERN invited us to work out the LHeC concept to a degree,
166 which would allow one to understand its physics programme, evaluate the accelerator options and their
167 technical realisation. The detector design should be affordable and capable of realising a high precision,
168 large acceptance experimental programme of deep inelastic scattering at the energy frontier. The electron
169 beam energy range was set to be between about 50–150 GeV. The wall plug power consumed for the electron
170 beam was limited to 100 MW.

171 For the installation of the LHC it had been decided to remove LEP from the tunnel and to re-use the
172 injector chain. To realise an ep collider based on the LHC, a new electron accelerator has to be built. The
173 following report details two solutions for the chosen default electron beam energy of $E_e = 60$ GeV. One option
174 is to build and install a new ring, with modern magnet technology, on top of the LHC, using a new 10 GeV
175 injector. Alternatively, one can build a “linac”, actually two 10 GeV superconducting linacs in a racetrack
176 configuration. By employing energy recovery techniques, this configuration could provide the equivalent of
177 about 1 GW available power and reach $10^{33} \text{ cm}^{-2}\text{s}^{-1}$ luminosity. The genuine linac would be of about the
178 same length as the one used for the discovery of quarks at SLAC [19,20], the Q^2 , however, with which parton
179 interactions were studied at the LHeC exceeded that from 1969 by a factor of nearly 10^5 .

180 It was agreed early on to devote a few years to the report, also because none of the people involved
181 could work anything near to full time for this endeavour. Three workshops were held in 2008-2010, that
182 annually assembled about a hundred experts on theory, experiment and accelerator to develop the LHeC
183 design concepts. The project was presented annually to ECFA and in 2008 to ICFA, see [21]. In view
184 of the unique electron-ion scattering programme of the LHeC, the design effort became also supported by
185 NuPECC, and the LHeC is now part of the NuPECC roadmap for European nuclear physics as released in
186 2010 [22]. Following an intermediate report to the Science Policy Committee of CERN, in July 2010, the
187 SPC considered the LHeC “an option for a future project at CERN”.

188 In August 2011, a first complete draft of this conceptual design report was handed to more than twenty
189 experts on various aspects of the physics and technology of the LHeC, which CERN had invited to referee
190 the project and scrutinize its motivation and its design. The report has been completed following often close
191 interactions with the referees and due consideration of their observations.

192 The LHeC by its nature is an upgrade of the LHC. It substantially enriches the physics harvest related to
193 the gigantic investment in the LHC. Whatever the outcome of the searches at the LHC for physics beyond
194 the Standard Model turns out to be, an ep collider operating at the energy frontier is guaranteed to deepen
195 the understanding of TeV scale physics and thus will support the development of the theory of elementary
196 particles and their interactions.

197 The LHeC needs the LHC proton and ion beams to be operational and so the design is made for syn-
198 chronous pp and ep operation, as well as AA and eA , including deuterons. Should the LHC eventually be
199 upgraded to even higher beam energy, beyond 7 TeV per beam [23], or a new proton collider be built, it
200 would open an even higher energy reach for ep also. There certainly is a future for deep inelastic scattering
201 at the energy frontier. It is herewith envisaged to begin with the LS3 shutdown of the LHC, in the early
202 twenties, likely leading into further decades. As Frank Wilczek put it, “one of the joys of our subject is the
203 continuing of our culture that bridges continents and generations” [24].

204 Our science is driven by curiosity, by theoretical expectations, sometimes too great, but also by experiment
205 and technology, and the authors of this study therefore hope that the LHeC may be given the chance to
206 contribute to the common efforts of our community for a deeper understanding of nature.

207
208 Max Klein (Chair of the LHeC Steering Committee)

Contents

209

210	I Introduction	14
211	1 Lepton-Hadron Scattering	16
212	1.1 Development and Contributions	16
213	1.2 Open Questions	17
214	2 Design Considerations	22
215	2.1 DIS and Particle Physics	22
216	2.2 Synchronous pp and ep operation	22
217	2.3 Choice of Electron Beam Energy	23
218	2.4 Detector Constraints	25
219	2.5 Two Electron Beam Options	25
220	2.6 Luminosity and Power	26
221	3 Executive Summary	29
222	II Physics	30
223	4 Precision QCD and Electroweak Physics	31
224	4.1 Inclusive Deep Inelastic Scattering	31
225	4.1.1 Cross Sections and Structure Functions	31
226	4.1.2 Neutral Current	32
227	4.1.3 Charged Current	35
228	4.1.4 Cross Section Simulation and Uncertainties	36
229	4.1.5 Longitudinal Structure Function $\mathbf{F_L}$	40
230	4.2 Determination of Parton Distributions	44
231	4.2.1 QCD Fit Ansatz	44
232	4.2.2 Valence Quarks	45
233	4.2.3 Strange Quarks	48
234	4.2.4 Top Quarks	48
235	4.3 Gluon Distribution	53
236	4.4 Prospects to Measure the Strong Coupling Constant	55
237	4.4.1 Status of the DIS Measurements of α_s	55
238	4.4.2 Simulation of α_s Determination	56
239	4.5 Electron-Deuteron Scattering	58
240	4.6 Charm and Beauty production	60
241	4.6.1 Introduction and overview of expected highlights	60
242	4.6.2 Total production cross sections for charm, beauty and top quarks	63
243	4.6.3 Charm and Beauty production in DIS	64
244	4.6.4 Intrinsic Heavy Flavour	68

245	4.6.5	D^* meson photoproduction study	68
246	4.7	High p_t jets	71
247	4.7.1	Jets in ep	71
248	4.7.2	Jets in γA	76
249	4.8	Total photoproduction cross section	77
250	4.9	Electroweak physics	79
251	4.9.1	The context	79
252	4.9.2	Light Quark Weak Neutral Current Couplings	81
253	4.9.3	Determination of the Weak Mixing Angle	82
254	4.9.4	Summary	88
255	5	Physics at High Parton Densities	89
256	5.1	Physics at small x	89
257	5.1.1	High energy and density regime of QCD	89
258	5.1.2	Status following HERA data	96
259	5.1.3	Low- x physics perspectives at the LHC	103
260	5.1.4	Nuclear targets	106
261	5.2	Prospects at the LHeC	110
262	5.2.1	Strategy: decreasing x and increasing A	110
263	5.2.2	Inclusive measurements	110
264	5.2.3	Exclusive Production	115
265	5.2.4	Inclusive diffraction	135
266	5.2.5	Jet and multi-jet observables, parton dynamics and fragmentation	147
267	5.2.6	Implications for ultra-high energy neutrino interactions and detection	160
268	6	New Physics at High Energy	163
269	6.1	New Physics in inclusive DIS at high Q^2	163
270	6.1.1	Quark substructure	163
271	6.1.2	Contact Interactions	165
272	6.1.3	Kaluza-Klein gravitons in extra-dimensions	168
273	6.2	Leptoquarks and leptogluons	168
274	6.2.1	Phenomenology of leptoquarks in ep collisions	168
275	6.2.2	The Buchmüller-Rückl-Wyler Model	169
276	6.2.3	Phenomenology of leptoquarks in pp collisions	170
277	6.2.4	The Contact Term Approach	171
278	6.2.5	Current status of leptoquark searches	171
279	6.2.6	Sensitivity on leptoquarks at LHC and at LHeC	172
280	6.2.7	Determination of LQ properties	172
281	6.2.8	Leptoquarks as R-parity violating squarks	179
282	6.2.9	Leptogluons	179
283	6.3	Excited leptons and other new heavy leptons	179
284	6.3.1	Excited Fermion Models	180
285	6.3.2	Simulation and Results	181
286	6.4	New physics in boson-quark interactions	183
287	6.4.1	An LHeC-based γp collider	184
288	6.4.2	Anomalous Single Top Production at the LHeC Based γp Collider	184
289	6.4.3	Excited quarks in γp collisions at LHeC	187
290	6.4.4	Quarks from a fourth generation at LHeC	187
291	6.4.5	Diquarks at LHeC	188
292	6.4.6	Quarks from a fourth generation in Wq interactions	188
293	6.5	Sensitivity to a Higgs boson	188
294	6.5.1	Higgs production at LHeC	189

295	6.5.2	Observability of the signal	189
296	6.5.3	Probing Anomalous HWW Couplings at the LHeC	192

297 **III Accelerator** **198**

298	7	Ring-Ring Collider	199
299	7.1	Baseline Parameters and Configuration	199
300	7.2	Baseline Parameters and Configuration	200
301	7.3	Geometry	200
302	7.3.1	General Layout	200
303	7.3.2	Electron Ring Circumference and e-p Synchronization	200
304	7.3.3	Idealized Ring	201
305	7.3.4	Bypass Options	202
306	7.3.5	Bypass Point 1	203
307	7.3.6	Bypasses Point 5	203
308	7.3.7	Matching Proton and Electron Ring Circumference	203
309	7.4	Layout and Optics	204
310	7.4.1	Arc Cell Layout and Optics	204
311	7.4.2	Insertion Layout and Optics	204
312	7.4.3	Bypass Layout and Optics	205
313	7.4.4	Chromaticity Correction	205
314	7.4.5	Working Point	206
315	7.4.6	Aperture	206
316	7.5	Layout	220
317	7.5.1	Beam Separation Scheme	221
318	7.5.2	Crossing Angle	223
319	7.5.3	Beam Optics and Luminosity	225
320	7.6	Design Requirements	226
321	7.6.1	Detector Coverage and Acceptance	226
322	7.6.2	Lattice Matching and IR Geometry	227
323	7.7	High Luminosity IR Layout	228
324	7.7.1	Parameters	228
325	7.7.2	Layout of the Electron Lattice	228
326	7.7.3	Separation Scheme	229
327	7.8	High Acceptance IR Layout	229
328	7.8.1	Parameters	229
329	7.8.2	Layout	231
330	7.8.3	Separation Scheme	232
331	7.9	Comparison of the two Layouts	232
332	7.9.1	Crab Cavities	233
333	7.10	Long Straight Section	234
334	7.10.1	Dispersion	234
335	7.10.2	Geometry	234
336	7.10.3	Electron Optics in the LSS	235
337	7.10.4	Synchrotron Radiation	235
338	7.10.5	LHC Integration	236
339	7.11	The Non-Colliding Proton Beam	237
340	7.11.1	Design Elements	237
341	7.11.2	Solution	238
342	7.11.3	Summary	240
343	7.12	Synchrotron radiation and absorbers	241

344	7.12.1	Introduction	241
345	7.12.2	High Luminosity	243
346	7.12.3	High Detector Acceptance	249
347	7.13	Beam-beam effects in the LHeC	256
348	7.13.1	Head-on beam-beam effects	256
349	7.13.2	Long range beam-beam effects	259
350	7.14	Performance as an electron-ion collider	260
351	7.14.1	Heavy nuclei, e-Pb collisions	260
352	7.14.2	Electron-deuteron collisions	261
353	7.15	Spin polarisation – an overview	262
354	7.15.1	Self polarisation	262
355	7.15.2	Suppression of depolarisation – spin matching	265
356	7.15.3	Higher order resonances	265
357	7.15.4	Calculations of the e^\pm polarisation in the LHeC	266
358	7.15.5	Spin rotator concepts for the LHeC	268
359	7.15.6	Further work	269
360	7.15.7	Summary	270
361	7.16	Integration and machine protection issues	271
362	7.16.1	Space requirements	271
363	7.16.2	Impact of the synchrotron radiation on tunnel electronics	277
364	7.16.3	Compatibility with the proton beam loss system	277
365	7.16.4	Space requirements for the electron dump	278
366	7.16.5	Protection of the p-machine against heavy electron losses	278
367	7.16.6	How to combine the Machine Protection of both rings?	279
368	7.17	LHeC Injector for the Ring-Ring option	279
369	7.17.1	Injector	279
370	7.17.2	Required performance	280
371	7.17.3	Source, accumulator and acceleration to 0.6 GeV	281
372	7.17.4	10 GeV injector	282
373	8	Linac-Ring Collider	284
374	8.1	Basic Parameters and Configurations	284
375	8.1.1	General Considerations	284
376	8.1.2	ERL Performance and Layout	285
377	8.1.3	Polarization	293
378	8.1.4	Pulsed Linacs	293
379	8.1.5	Higher-Energy LHeC ERL Option	295
380	8.1.6	γ -p/A Option	295
381	8.1.7	Summary of Basic Parameters and Configurations	297
382	8.2	Interaction region	297
383	8.2.1	Layout	298
384	8.2.2	Optics	298
385	8.2.3	Modifications for γ p or γ -A	305
386	8.2.4	Synchrotron radiation and absorbers	305
387	8.3	Linac Lattice and Impedance	312
388	8.3.1	Overall Layout	312
389	8.3.2	Linac Layout and Lattice	314
390	8.3.3	Beam Break-Up	320
391	8.3.4	Imperfections	332
392	8.3.5	Touschek Scattering	333
393	8.4	Performance as a Linac-Ring electron-ion collider	333
394	8.4.1	Heavy nuclei, e-Pb collisions	333

395	8.4.2	Electron-deuteron collisions	333
396	8.5	Polarized-Electron Injector for the Linac-Ring LHeC	334
397	8.6	Spin Rotator	336
398	8.6.1	Introduction	336
399	8.6.2	LHeC Spin Flipper Options	336
400	8.6.3	Polarimetry	339
401	8.6.4	Conclusions and Outlook for the Spin Control	340
402	8.7	Positron Options for the Linac-Ring LHeC	340
403	8.7.1	Motivation	340
404	8.7.2	LHeC Linac-Ring e^+ Requirements	342
405	8.7.3	Mitigation Schemes	342
406	8.7.4	Cooling of Positrons	343
407	8.7.5	Production Schemes	345
408	8.7.6	Conclusions on Positron Options for the Linac-Ring LHeC	350
409	9	System Design	351
410	9.1	Magnets for the Interaction Region	351
411	9.1.1	Introduction	351
412	9.1.2	Magnets for the ring-ring option	351
413	9.1.3	Magnets for the linac-ring option	352
414	9.2	Accelerator Magnets	358
415	9.2.1	RR option, dipole magnets	358
416	9.2.2	RR option, quadrupole magnets	361
417	9.2.3	LR option, dipole magnets	366
418	9.2.4	LR option, quadrupole magnets	366
419	9.2.5	LR option, corrector magnets for the two 10 GeV linacs	370
420	9.3	Ring-Ring RF Design	371
421	9.3.1	Design Parameters	371
422	9.3.2	Cavities and klystrons	371
423	9.4	Linac-Ring RF Design	374
424	9.4.1	Design Parameters	374
425	9.4.2	Layout and RF powering	375
426	9.4.3	Arc RF systems	377
427	9.5	Crab crossing for the LHeC	377
428	9.5.1	Luminosity Reduction	379
429	9.5.2	Crossing Schemes	379
430	9.5.3	RF Technology	379
431	9.6	Ring Ring option power converters	381
432	9.6.1	Overview	381
433	9.6.2	Powering considerations	381
434	9.6.3	Power converter topologies	381
435	9.6.4	Main power converters	382
436	9.6.5	Insertion and by-pass quadrupole power converters	384
437	9.6.6	Power converter infrastructure	385
438	9.7	Linac-Ring option power converters	385
439	9.7.1	Overview	385
440	9.7.2	Powering considerations	385
441	9.7.3	Linac quadrupole and corrector power converters	385
442	9.7.4	Recirculation main power converters	387
443	9.7.5	Power converter infrastructure	387
444	9.7.6	Conclusions on power converters	388
445	9.8	Vacuum	389

446	9.8.1	Vacuum requirements	389
447	9.8.2	Synchrotron radiation	390
448	9.8.3	Vacuum engineering issues	392
449	9.9	Beam Pipe Design	397
450	9.9.1	Requirements	397
451	9.9.2	Choice of Materials for beampipes	397
452	9.9.3	Beampipe Geometries	397
453	9.9.4	Vacuum Instrumentation	399
454	9.9.5	Synchrotron Radiation Masks	400
455	9.9.6	Installation and Integration	400
456	9.10	Cryogenics	401
457	9.10.1	Ring-Ring Cryogenics Design	401
458	9.10.2	Linac-Ring Cryogenics Design	405
459	9.10.3	General Conclusions Cryogenics for LHeC	407
460	9.11	Beam Dumps and Injection Regions	409
461	9.11.1	Injection Region Design for Ring-Ring Option	409
462	9.11.2	Injection transfer line for the Ring-Ring Option	411
463	9.11.3	60 GeV internal dump for Ring-Ring Option	414
464	9.11.4	Post collision line for 140 GeV Linac-Ring option	416
465	9.11.5	Absorber for 140 GeV Linac-Ring option	417
466	9.11.6	Energy deposition studies for the Linac-Ring option	417
467	9.11.7	Beam line dump for ERL Linac-Ring option	418
468	9.11.8	Absorber for ERL Linac-Ring option	420
469	10	Civil Engineering and Services	421
470	10.1	Overview	421
471	10.2	Location, Geology and Construction Methods	421
472	10.2.1	Location	421
473	10.2.2	Land Features	423
474	10.2.3	Geology	423
475	10.2.4	Site Development	423
476	10.2.5	Construction Methods	424
477	10.3	Civil Engineering Layouts for Ring-Ring	424
478	10.4	Civil Engineering Layouts for Linac-Ring	427
479	10.5	Summary	427
480	11	Project Planning	431
481	IV	Detector	437
482	12	Detector Requirements	438
483	12.1	Requirements on the LHeC Detector	438
484	12.1.1	Installation and Magnets	438
485	12.1.2	Kinematic reconstruction	440
486	12.1.3	Acceptance regions - scattered electron	441
487	12.1.4	Acceptance regions - hadronic final state	444
488	12.1.5	Acceptance at the High Energy LHC	446
489	12.1.6	Energy Resolution and Calibration	446
490	12.1.7	Tracking Requirements	448
491	12.1.8	Particle Identification Requirements	450
492	12.1.9	Summary of the Requirements on the LHeC Detector	450

493	13 Central Detector	452
494	13.1 Basic Detector Description	452
495	13.1.1 Baseline Detector Layout	457
496	13.1.2 An Alternative Solenoid Placement - Option B	459
497	13.2 Magnet Design	462
498	13.2.1 Magnets configuration	462
499	13.2.2 Detector Solenoid	462
500	13.2.3 Detector integrated e-beam bending dipoles	466
501	13.2.4 Cryogenics for magnets and calorimeter	466
502	13.2.5 Twin Solenoid System	469
503	13.3 Tracking Detector	469
504	13.3.1 Tracking Detector - Baseline Layout	469
505	13.3.2 Performance	470
506	13.3.3 Tracking detector design criteria and possible solutions	470
507	13.4 Calorimetry	480
508	13.4.1 The Barrel Electromagnetic Calorimeter	480
509	13.4.2 The Hadronic Barrel Calorimeter	482
510	13.4.3 Endcap Calorimeters	484
511	13.5 Calorimeter Simulation	484
512	13.5.1 The Barrel LAr Calorimeter Simulation	485
513	13.5.2 The Barrel Tile Calorimeter Simulation	486
514	13.5.3 Combined Liquid Argon and Tile Calorimeter Simulation	487
515	13.5.4 Lead-Scintillator Electromagnetic Option	487
516	13.5.5 Forward and Backward Inserts Calorimeter Simulation	490
517	13.6 Calorimeter Summary	501
518	13.7 Muon Detector	501
519	13.7.1 Muon detector design	502
520	13.7.2 The LHeC muon detector options	504
521	13.7.3 Forward Muon Extensions	505
522	13.7.4 Muon Detector Summary	506
523	13.8 Event and Detector Simulations	507
524	13.8.1 Pythia6	507
525	13.8.2 1 MeV Neutron Equivalent	509
526	13.8.3 Nearest Neighbor	511
527	13.8.4 Cross Checking	511
528	13.8.5 Future Goals	514
529	14 Forward and Backward Detectors	516
530	14.1 Luminosity Measurement and Electron Tagging	516
531	14.1.1 Options	517
532	14.1.2 Use of the Main LHeC Detector	517
533	14.1.3 Dedicated Luminosity Detectors in the tunnel	518
534	14.1.4 Small angle Electron Tagger	518
535	14.1.5 Summary and Open Questions	521
536	14.2 Polarimeter	522
537	14.2.1 Polarisation from the scattered photons	523
538	14.2.2 Polarisation from the scattered electrons	523
539	14.3 Zero Degree Calorimeter	523
540	14.3.1 ZDC detector design	524
541	14.3.2 Neutron Calorimeter	524
542	14.3.3 Proton Calorimeter	526
543	14.3.4 Calibration and monitoring	527

544	14.4 Forward Proton Detection	527
545	V Summary	530
546	15 Appendix	564
547	15.1 Scientific Advisory Committee	564
548	15.2 Steering Committee	565
549	15.3 Working Group Convenors	566
550	15.4 CERN Referees	567

551

Part I

552

Introduction

553 The present document is a detailed presentation of the physics, the accelerator options and a detector design
554 comprising the LHeC project. It has been developed under the auspices and with support of CERN, ECFA
555 and NuPECC, between 2008 and now. The paper is organised as follows:

556 In the introduction, **Chapter I**, cornerstones of deep inelastic scattering and the main considerations
557 for the design of the LHeC are summarised. The emphasis is on adding a 60 GeV energy electron beam
558 to the existing proton and ion beams of the LHC, in a manner which foresees the simultaneous *ep* and
559 *pp* operation for the realisation of a luminous DIS programme while minimising the interference with the
560 LHC. The introduction contains an executive summary of this report (which will be added before its final
561 publication).

562 **Chapter II** presents major, selected subjects, with related simulation studies and theoretical consider-
563 ations, in order to sketch the physics programme of the LHeC. These subjects are grouped into three areas:
564 high precision QCD and electroweak physics, the physics of high parton densities at low Bjorken x and in
565 nuclei and finally the potential for searches for phenomena beyond the standard model and its relation to
566 the LHC. It is clear that it has rarely been possible, fortunately, to accurately predict nor to fully simulate
567 the physics of a new machine at much enlarged energies. The subjects here presented are neither supposed
568 to cover the complete field as it is known today. For a new laboratory of particle physics as the LHeC
569 represents, however, a broad view must be taken to what it comprises most likely.

570 **Chapter III** is devoted to the accelerator design studies presenting the ring-ring and linac-ring concepts,
571 optics etc and in a third section the various technical systems which often are common to both accelerator
572 options. The emphasis here is on an understanding of the main challenges and characteristics of both options
573 and not on discussing their relative merits. The accelerator chapter is concluded with separate sections on
574 the civil engineering and a tentative time schedule for the realisation of the LHeC within the next about ten
575 years.

576 **Chapter IV** presents the design considerations for a detector with its challenging central part and further
577 systems to tag forward nucleons and backward scattered electrons and photons, including a study for a high
578 precision measurement of the lepton beam polarisation. The salient feature of the detector baseline design
579 is its silicon tracker surrounded by an electromagnetic liquid argon calorimeter inside a superconducting coil
580 which uses a tile hadron calorimeter for the flux return.

581 The present version of this document (as of July 2011) does not yet contain summary sections. These
582 will be added in the fall when the referee process ended and corresponding updates of this document ¹ are
583 completed. One can not exclude today that this process, also in the light of the rapid increase in LHC
584 luminosity, leads to revisions of not only details of the present draft report. The main characteristics of this
585 *ep* collider, however, its high luminosity and its high cms energy, beyond a TeV, are on firm ground as they
586 are achieved with the unique hadron beams of the LHC. The LHeC technologies require prototyping and
587 preparations but essentially they are at hand which makes the LHeC a realistic opportunity.

588 This report has been organised jointly by a steering group and convenors for the various physics, accel-
589 erator and detector parts of the design. It was accompanied by a scientific advisory committee. The present
590 draft is handed to 24 referees nominated by the CERN directorate for a detailed evaluation of the design
591 and its corresponding update. The composition of these groups is listed in the **Appendix** of the paper.
592 Some members of the steering group, many of the convenors and various members of the advisory committee
593 have made direct scientific contributions to the LHeC design as presented here. They therefore also appear
594 among the authors of this study which are representing a group of about 150 physicists and engineers from
595 50 institutes.

596 It is for the coming phase of the LHeC design to begin its technical development, beyond the initial
597 prototyping of magnets, and to form the appropriate international collaborations, both for the accelerator
598 and the detector.

¹An estimate is underway of the cost of the detector and the accelerator options which will be made available to CERN when available. For a rough cost estimate, an order of magnitude guess, which will be sufficient for most of the purposes, it may suffice to state that the cost of the LHeC is expected to be comparable with the cost of LEP or the XFEL while the detector cost will be a fraction only of the cost of CMS or ATLAS.

Chapter 1

Lepton-Hadron Scattering

1.1 Development and Contributions

It is almost exactly 100 years since the birth of the scattering experiment as a means of revealing the structure of matter. Geiger and Marsden's experiment [25] and its interpretation by Rutherford [26] set the scene for a century of ever-deeper and more precise resolution of the constituents of the atom, the nucleus and the nucleon. Lepton-hadron scattering has played a crucial role in this exploration over the past 55 years. The finite radius of the proton of about 1 fm was first established through elastic electron-proton scattering experiments [27]. Later, through deep inelastic electron proton scattering at Stanford [19, 20], proton structure was understood in terms of quarks, still the smallest known constituents of matter. With the discovery of Bjorken scaling of the proton structure function $F_2(x, Q^2)$, its quark model interpretation, and the subsequent discovery of scaling violation in support of asymptotic freedom [28, 29], deep inelastic scattering (DIS) became a field of fundamental theoretical importance [30] to the understanding of the strong interaction. Precise measurements of the parton momentum distributions of the nucleon became a major testing ground for the selection and development of Quantum Chromodynamics (QCD) [31] as the appropriate theory of the strong interaction. Prior to these developments, the theory of strong interactions was of merely phenomenological nature, built around S matrix theory and general amplitude features and various concepts such as Regge, bootstrap or further models [32].

Quantum Chromodynamics is a Yang-Mills gauge theory, in which the interaction between confined quarks proceeds via coloured gluon exchange. With improved resolution, as provided by increased Q^2 , quarks can be resolved as quarks radiating gluons, whilst gluons may split into quark-antiquark pairs or, due to the non-abelian nature of the underlying gauge field theory, into pairs of gluons [33–35]. The development of QCD calculations beyond leading order [36, 37] is one of the most remarkable recent achievements of particle physics theory supported by experiment. It leads to a consistent description of all perturbatively accessible hadron observables in DIS (and beyond), as has recently been established over the kinematic range accessible to HERA [38]. This includes the unexpected observation of deep inelastic diffractive scattering at HERA, according to which in a significant fraction of violent DIS interactions the proton remains intact, an exchange of vacuum quantum numbers which often is termed “Pomeron exchange”.

Despite previous successes, many fundamental areas of QCD have not been verified experimentally, with instantons [39] as only one example. Even the classic areas related to quarks and gluons have not been exploited as required for limited precision, range and variation of initial conditions. Meanwhile the theory underlying DIS experiences further fundamental developments. Four-dimensional conformal field theory is seen to be related to superstring theory in the anti-de Sitter space in ten dimensions, which relates the $N = 4$ supersymmetric pomeron to the graviton in this space [40]. The evolution of partons is expected to obey different laws than explored hitherto at HERA when at small x their interactions have to be damped for the restoration of unitarity, see [41] for a review.

Particle physics in the past could profit very much from the complementarity of hadron-hadron, DIS and

The 10-100 GeV Energy Scale [1968-1986]




Figure 1.1: Key results of the exploration of the 10 – 100 GeV energy scale in hadron-hadron (top), deep inelastic (bottom left) and e^+e^- scattering (bottom right). These and further important results selected the $SU(2)_L \times U(1)$ and QCD as the appropriate theories for the electroweak and the strong interaction, respectively, of leptons and quarks transmitted by the photon, the W^\pm , Z bosons and gluons.

636 e^+e^- experiments. Key observations were made in all three areas, and the overlap in physics coverage was
 637 used to achieve confidence in new and precision results. This is sketched in Figure 1.1 for the experiments of
 638 the seventies and eighties, which resulted in the birth of the Standard Model. Fig. 1.2 illustrates this for the
 639 experiments of the nineties until now, when the Tevatron, HERA and the SLC/LEP machines determined
 640 the progress in the exploration of particle physics at the energy frontier accessed with colliders. The present
 641 report deals with the reasons and possibility to extend deep inelastic scattering experimentation into an
 642 unexplored range of our knowledge for which the LHC at CERN provides the rare and single opportunity
 643 for the next decades ahead. Simultaneous LHC and LHeC operation would put the ep part of the TeV scale
 644 triangle, as shown in Figure 1.3, on a firm ground.

645 1.2 Open Questions

646 For a project as the LHeC one needs to understand which fundamental properties of nature it promises to
 647 deal with and which possibly specific questions it is expected to answer.

648 The Standard Model of particle physics contains a remarkable, but unexplained, symmetry between
 649 quarks and leptons [42], with three generations, in each of which two quarks and two leptons are embedded.
 650 It was pointed out long ago [43] that it appears somewhat artificial that the basic building blocks of matter
 651 share the electromagnetic and the weak interactions but differ in their sensitivity to the strong interaction.
 652 Many theories which unify the quark and lepton sectors, such as models based on the E6 gauge group [44],
 653 R -parity violating supersymmetry and left-right symmetric extensions of the Standard Model [45], predict
 654 new resonant states with both lepton and baryon numbers, usually referred to as leptoquarks (LQ). In the
 655 technicolour theory, leptoquarks are bound states of technifermions [46, 47]. Although some of the specific
 656 theories have not been supported by experiment, the search for leptoquarks has been a prime motivation for
 657 high energy scattering, especially DIS experiments. The limits for leptoquark states as of the time of EPS11
 658 from the LHC leave the possibility of new LQ states at around 1 TeV mass open while the absence of large

659 missing energy may be seen as being compliant with RPV SUSY states in which there is no LSP. An LHeC,
 660 in combination with the existing LHC programme, can extend this search into a previously unexplored mass
 661 region, with the prospect of deciphering the leptoquark quantum numbers.

662 No analytic proof yet exists that QCD should exhibit the property of colour confinement, though it
 663 is reasonable to assume that it is a consequence of gluon dynamics, as reflected for example in popular
 664 hadronisation models [48] and Monte Carlo simulations on the lattice. Studying the behaviour of gluons
 665 under new extreme conditions and contrasting the conditions under which the proton stays intact with those
 666 in which it is destroyed may help to shed light on the precise mechanism at work.

667 The search for the Higgs boson, which explains the masses of the electroweak bosons, and for the origin
 668 of electroweak symmetry breaking is currently the central focus of particle physics and is expected to be
 669 principally resolved within the near future by the ATLAS and CMS experiments. If there exists a Higgs
 670 particle at masses around 130 GeV, the determination of its properties becomes an important issue. The
 671 LHeC, due to its clean initial state and the absence of pile-up, has an interesting potential to accurately
 672 determine the Higgs particle coupling to $b\bar{b}$, and to also investigate the quartic self-coupling of the scalar
 673 doublet, from the HWW vertex, which provides direct insight into the nature of electroweak symmetry
 674 breaking.

675 The question of hadronic mass deserves similar exploration. The mass of baryons is almost entirely due to
 676 strong interaction field energy, generated through quark and gluon vacuum condensates the self-interaction
 677 of gluons in a manner which is not yet well understood. It may be accessible through a more detailed
 exploration of QCD dynamics.




Figure 1.2: Key results of the exploration of the Fermi energy scale in $p\bar{p}$ (top), deep inelastic (bottom left) and e^+e^- scattering (bottom right) with the energy frontier colliders, the Tevatron, HERA and the SLC/LEP, respectively. These and further important results established the Standard Model of particle physics with six types of quarks and leptons in three families, and the development of higher order precision calculations used for the prediction of the top quark and the Higgs mass, based mainly on e^+e^- scattering results, and for the understanding of the partonic contents of the proton to NNLO pQCD, based mainly on the results from HERA and previous DIS fixed target experiments.

678

679 The salient theme of physics with the LHeC is the mapping of the gluon field. This is achieved with
 680 precision measurements of the evolution of structure functions over an unprecedented range of $\ln Q^2$. It

681 relates inclusive ep DIS with jets and heavy flavour, it concerns the unexplored role of the gluon in nuclei
 682 and in deeply virtual Compton scattering. The gluon field is central to QCD but not directly measurable. It
 683 may exhibit spots of maximum density (hot spots) and it may also disappear (cold spots) as it does towards
 684 low Q^2 and x , and possibly at the scaling point near $x \simeq 0.2$ [49]. Knowing the gluon means understanding
 685 the origin of baryonic matter, the production of the Higgs boson and of other new particles and not least
 686 important understanding Quantum Chromodynamics.

687 The study of deep inelastic ep scattering is important for the investigation of the nature of the Pomeron
 688 and Odderon, which are Regge singularities of the t -channel partial waves $f_j(t)$ in the complex plane of the
 689 angular momentum j . The Pomeron is responsible for a growth of total cross sections with energy. The
 690 Odderon describes the behaviour of the difference of the cross sections for particle-particle and particle-
 691 antiparticle scattering which obey the Pommeranchuk theorem. In perturbative QCD, the Pomeron and
 692 Odderon are the simplest colorless reggeons (families of glueballs) constructed from two and three reggeized
 693 gluons, respectively. Their wave functions satisfy the generalized BFKL equation. In the next-to-leading
 694 approximation the solution of the BFKL equation contains an infinite number of Pomerons and to verify
 695 this prediction of QCD one needs to increase the energy of colliding particles. In the N=4 supersymmetric
 696 generalization of QCD, in the t'Hooft limit of large N_c , the BFKL Pomeron is equivalent to the reggeized
 697 graviton living in the 10-dimensional anti-de-Sitter space. Therefore, the Pomeron interaction describing
 698 the screening corrections to the BFKL predictions, at least in this model, should be based on a general
 699 covariant effective theory being a generalization of the Einstein-Hilbert action for general relativity. Thus,
 700 the investigation of high energy ep scattering could be interesting for the construction of a non-perturbative
 701 approach to QCD based on an effective string model in high dimensional spaces.

702 The strong coupling constant α_s decreases as energy scales increase, in contrast to the energy dependence
 703 of the weak coupling and the fine structure constant. It appears possible in SUSY theories that the three
 704 constants approach a common value at energies of order 10^{15} GeV. The distinctions we make between the
 705 electromagnetic, weak and strong interactions may merely be a consequence of the low energy scale at which
 706 we live. The possible grand unification of the known interactions has been one of the major goals of modern
 707 particle physics theory and experiment. Progress in this area requires that we know α_s , by far the most
 708 poorly constrained of the fundamental couplings, much more accurately than is currently the case. The
 709 LHeC promises a factor of ten reduction in the uncertainty on α_s based on a major renewal and extension
 710 of the experimental and the theoretical basis of the physics of deep inelastic scattering.

711 After quarks were discovered, a distinction was soon made between valence and sea quarks [50]. However,
 712 it was not until the high energy colliding beam configuration of HERA became available that the rich partonic
 713 structure of the proton was fully realised. Despite the resulting fast development of our knowledge of the
 714 parton distribution functions (PDFs) in the proton, there are still many outstanding important questions
 715 regarding the quark contents of the nucleon. These regard for example: i) the unresolved question of whether
 716 sea quarks and anti-quarks have the same momentum distributions; ii) the clarification of the role of heavy
 717 quarks in QCD, including the search for their intrinsic states [51], the precision measurement of the b quark
 718 density or, owing to the huge reach in Q^2 , the novel exploration of top production in DIS and the transition
 719 of top from a heavy to a light quark, for $Q^2 \gg m_t^2$; iii) the partonic structure of the neutron which is to be
 720 resolved over many orders of magnitude in $1/x$, as HERA had no deuteron data taken, and the assumption
 721 of isospin symmetry, which relates the neutron down-quark distribution to the proton up-quark distribution.
 722 Modern fits of PDFs use quite a number of symmetry assumptions and exploit parameterisations which are
 723 to be questioned and overcome by a new basis for the PDF determinations which the LHeC uniquely provides
 724 as it constrains all quark distributions, $u_v, d_v, u, \bar{u}, d, \bar{d}, s, \bar{s}, c, b$ and likely t and \bar{t} over an unprecedented
 725 range of x and Q^2 . The LHeC will put the whole PDF related physics on new, much firmer ground. That
 726 is crucial for searches for physics beyond the standard model. It also is necessary for high precision tests of
 727 the electroweak theory, as for the ultimate measurement of the mass of the W boson [52] as a test for the
 728 validity of the SM, especially the relation to the masses of the top quark and the Higgs boson.

729 The structure of the neutron at low $x \leq 0.01$ in the DIS region is experimentally unknown. With
 730 no data on the scattering of leptons from heavy ions with colliding beam kinematics, the knowledge of the
 731 modifications to nucleon parton densities when they are bound inside nuclei, rather than free, is also restricted

732 to high x values. This is reflected in a lack of detailed understanding of shadowing phenomena, particularly
733 for the gluon density and a corresponding lack of knowledge of the initial state of heavy ion collisions at LHC
734 energies. The mechanism of shadowing at low x can be tested for the first time via Gribov's fundamental
735 relation to diffraction and also via measurements with different light nuclei. Antishadowing at larger x [53]
736 may possibly be non-universal and flavour specific. Nuclear corrections at large x may be dealt with in eD
737 scattering at the LHeC by tagging the spectator nucleon and reconstructing its momentum well enough to
738 account for the so far disturbing effects of Fermi motion. This promises to overcome the uncertainty from
739 nuclear corrections which has been an obstacle for decades in the understanding of nucleon structure and
740 represents a formidable experimental task, see e.g. [53] for a recent study. Parton distributions in nuclei,
741 for $x \lesssim 0.01$, presently are based in HERA's proton data convoluted with theoretical expectations. With
742 the LHeC they will be determined down to almost 10^{-6} and largely flavour separated. It is unknown what
743 will be found from an experimental point of view, and it is critical for the understanding of the quark gluon
744 plasma.

745 There are various fundamental properties predicted in QCD which have never been resolved or even tested
746 so far and which will become accessible with the LHeC. While ordinary quark distributions correspond to
747 an incoherent sum of squared amplitudes, a new approach has been developed, which uses quark amplitudes
748 and Generalised Parton Distributions (GPDs) to understand proton structure in a new, three-dimensional
749 way [54,55]. Our understanding of GPDs is limited by the relative paucity of experimental data on exclusive
750 DIS channels. The emission of partons is assumed in PDF fits to be governed by the linear DGLAP evolution
751 equations, an approximation to a full solution to QCD, in which parton cascades are ordered in transverse
752 momentum. There are good reasons to believe that the DGLAP approximation is insufficient to describe
753 the Q^2 evolution of low x partons, even within the x range to which the LHC rapidity plateau corresponds.
754 Inclusive DIS and jet data in an extended low x kinematic regime are required to resolve this situation.

755 The rapid rise of the proton gluon density as x decreases cannot continue indefinitely. At x values
756 within the reach of LHeC ep and eA scattering, a transition takes place from the currently known DIS
757 regime in which the proton behaves as a dilute system to a new low x domain in which parton densities
758 saturate and the proton approaches a 'black disk' limit [56]. This latter region represents a fundamentally
759 new regime of strong interaction dynamics, for which a rich phenomenology has developed, but where the
760 detailed mechanisms and the full consequences are not yet known. Experimental data at sufficiently low x
761 with scales which are large enough to allow a partonic interpretation are required in order to test the models
762 and fully understand the behaviour of partons at high densities. The so well known DGLAP evolution at low
763 x is to break and non-linear evolution equations will determine the parton distributions, for which various
764 untested predictions exist.

765 The high precision and range of the LHeC DIS measurements provide many further opportunities for
766 explorations of fundamental interest. With the ep initial state any new phenomenon singly produced can be
767 investigated with particular sensitivity, as for example the possibility for excited leptons to exist. Variation
768 of beam charge and polarisation lead to resolve quantum numbers of new, so-called contact interactions, of
769 scale up to about 50 TeV, and to novel precision measurements of the scale dependence of the weak mixing
770 angle around the Z pole.

771 Despite its huge success in describing existing high energy data, the Standard Model is known to be in-
772 complete, not only due to the absence of an experimentally established mechanism for electroweak symmetry
773 breaking. As the exploitation of the TeV energy regime and the high luminosities of the LHC era develop
774 further, a full understanding requires to challenge the existing theory through new precision measurements,
775 as broad in scope as possible, with initial states involving leptons as well as quarks and gluons. The LHeC
776 will not just answer some of the currently outstanding questions but represents the opportunity to build a
777 new laboratory for particle physics which owing to its specific configuration, its enlarged DIS energy range
778 and unprecedented precision will accompany the LHC, and possibly built pure lepton machines, in exploring
779 the next layer of the high energy frontier physics.

The TeV Scale [2010-2035..]




Figure 1.3: The exploration of the TeV energy scale has begun with the LHC. The present document describes one of its compliments, a new TeV scale ep and eA collider, while intense work is continuing on the development of concepts for new e^+e^- and possibly $\mu^+\mu^-$ colliders. While each of the new machines has exciting standard model programmes to pursue with higher precision and range, physics beyond the SM has been elusive at the moment this report is released and 1 fb^{-1} of 7 TeV cms LHC data have been analysed within a very short time for the EPS11 conference at Grenoble.

Chapter 2

Design Considerations

The following sections describe briefly which general considerations have determined the LHeC design as presented in this report. Major changes to the underlying assumptions would naturally require an appropriately changed variation of the design.

2.1 DIS and Particle Physics

Deep inelastic scattering experiments with charged leptons may be classified as low energy, medium and high energy experiments. The pioneering low energy DIS experiment, which discovered quarks, was performed at SLAC. Classic medium energy experiments were the BCDMS and the NMC experiments at CERN, while HERA, the first ep collider ever built, had pushed the DIS energy reach to the Fermi scale. This allowed the field of deep inelastic scattering to develop as part of the energy frontier particle physics, complementary to the Tevatron and LEP. In all three areas, the field of DIS is considering upgrade projects with the 12 GeV upgrade at Jlab, the medium energy colliders at Jlab and/or BNL, possibly fixed target further neutrino experiments and the LHeC.

The LHeC provides the only realistic possibility for an energy frontier ep programme in the coming probably three decades. Owing to the LHC, there is one opportunity to complement the TeV scale pp machine with a TeV energy ep collider, besides a pure lepton collider in this energy range. It took about 30 years for HERA, LEP and the Tevatron to be built, operated and analysed. The exploration of the TeV energy scale is subject to similar time horizons.

2.2 Synchronous pp and ep operation

The intense, energetic hadron beams of the LHC provide the unique possibility to realise a luminous experimental programme of deep inelastic scattering at TeV energies. The LHeC is therefore by its nature an upgrade to the LHC, which gives it its site and in a way determines its dimensions too. The first design consideration builds on the assumption that the LHC still runs in pp mode when an electron beam becomes operational. This has several implications:

- The construction of the LHeC has to be completed in the coming about 10 years.
- The design has to be adapted for synchronous pp and ep (and AA and eA) operation, as with magnets in the IR to steer three beams and with civil engineering and detector modularity requirements to be compliant with the LHC operation and upgrade programme.
- The synchronous operation of pp and ep allows to collect a high integrated luminosity, with the goal of a total of order 100 fb^{-1} , and makes the most efficient use of both the proton beams and the electron beam installation too.

812 It can not realistically be assumed today, that the ep physics would commence only when the pp program
813 was finished because several key LHC components have a limited lifetime, which is nowadays estimated to
814 be about 20 years. Planning for an ep run after the pp program finishes therefore implies a significant risk
815 of additional cost for the project due to a substantial consolidation effort in the LHC.

816 The LHeC can be thought and it is designed to accompany the proton and the ion physics programme
817 of the LHC in its high luminosity phase, now assumed to begin in 2023.

818 2.3 Choice of Electron Beam Energy

819 The centre of mass energy squared of an ep collider is $s = 4E_e E_p$. It determines the maximum four-
820 momentum transfer squared, Q^2 , between the electron and the proton because $Q^2 = sxy$, where x is the
821 fraction of four momentum of the proton carried by the struck parton while y is the inelasticity of the
822 scattering process which in the laboratory frame is the relative energy transfer, with $0 < x, y \leq 1$.

823 HERA has operated with a proton beam energy of $E_p = 0.92$ TeV and an electron (and positron) beam
824 energy of $E_e = 27.5$ GeV. With Sokolov-Ternov build-up times of about half an hour, the electron beam
825 became polarised and mean polarisations of up to 40% were achieved. HERA has not accelerated any
826 hadron beam other than protons. The LHeC has to surpass these parameters significantly for a unique and
827 exciting programme to be pursued.

828 The LHeC can use an up to 7 TeV energy proton beam. For this design study the electron beam energy
829 is set to 60 GeV. This implies that the gain in s , or Q^2 at fixed (x, y) , as compared to HERA will be a
830 factor of 16.6, or about 4 in \sqrt{s} . The real gain in range of Q^2 and x will even be larger as with the superior
831 luminosity even the highest Q^2 values and x close to 1 become accessible. The kinematic range of the LHeC
832 as compared to HERA at low x and at high Q^2 is illustrated in Fig. 2.1.


833 The choice of a default $E_e = 60$ GeV for this design report is dictated by physics and by practical
834 considerations:

- 835 • New physics has been assumed to appear at the TeV energy scale. At the time of completion of this
836 report, the LHC has excluded much of the sub-TeV physics beyond the Standard Model (SM) but
837 leaves the possibility open of resonant lepton-parton states with masses of larger than about 500 GeV,
838 for which the LHeC would be a particularly suitable machine with a range of up to $M \lesssim \sqrt{s}$.
- 839 • High precision QCD and electroweak physics require a maximum range in $\ln Q^2$ and highest Q^2 ,
840 respectively. The unification of electromagnetic and weak forces takes place at $Q^2 \simeq M_Z^2$ which is much
841 exceeded by the LHeC energies. Part of the electroweak physics requires lepton beam polarisation.
- 842 • The discovery of gluon saturation requires to measure at typical values of small $x \simeq 10^{-5}$ with $Q^2 \gg$
843 M_p^2 , where M_p is the mass of the proton. The choice of energies ensures this discovery at the LHeC in
844 the DIS region, both in ep and in eA .
- 845 • Energy losses by synchrotron radiation, $\propto E_e^4$, both in the ring and the return arcs for the linac, can be
846 kept at reasonable levels, in terms of the power, P , needed to achieve high luminosity and the radius
847 of the racetrack return arcs for the linac too.

848 It so appears that 60 GeV is an appropriate and affordable choice. It yet is well possible that the 60 GeV
849 may not be the final value of the electron beam energy, especially if the LHC would find non-SM physics
850 just above the now chosen energy range. The design therefore also considers a dedicated high energy beam
851 of 140 GeV as an option, which yet has not been worked out to any comparable detail ¹.

¹Such a large E_e would also fit better to a future HE LHC, when about 16 TeV proton beam energy might become available in the yet much farther future, as that would keep the $e - p$ beam energy asymmetry tolerable.

LHeC - Low x Kinematics



LHeC - High Q^2 Kinematics




Figure 2.1: Kinematics of ep scattering at the LHeC at low x (top) and high Q^2 (bottom). Solid (dotted) curves correspond to constant polar angles θ_e (θ_h) of the scattered electron (hadronic final state). The polar angle is defined with respect to the proton beam direction. Dashed (dashed-dotted) curves correspond to constant energies E'_e (E_h) of the scattered electron (hadronic final state). The shaded (green) area illustrates the region of kinematic coverage in neutral current scattering at HERA. The energy and angle isochrone lines are discussed in the detector design chapter in detail.

2.4 Detector Constraints

One easily recognises, in Fig. 2.1, that the asymmetry of the electron and proton beam energies poses severe constraints to the detector design: i) the “whole” low Q^2 and low x physics requires to measure the electron, of energy $E'_e \lesssim E_e$, scattered in backward direction between about 170° and 179° , and ii) the forward scattered final state, of energy comparable to E_p , needs to be reconstructed down to very small angles in order to cover the high x region in a range of not too extreme Q^2 .

The current detector design considers an option to have split data taking phases, like HERA I and II, with different interaction region configurations, a high acceptance phase, covering $1^\circ - 179^\circ$, at reduced luminosity and a high luminosity phase, of acceptance limited to $8^\circ - 172^\circ$. In the course of the study, however, an optics was found for the high acceptance configuration with only a factor of two reduced luminosity. It is likely, therefore, that the TDR will lead to a unification of these configurations and correspondingly weakened demands on the modularity of the inner detector region.

Synchronous ep and pp operation implies that at least one of the four IPs, currently occupied by experiments, will have to be free'd for an LHeC detector. It was decided to use for this report IP2 as an example site and to limit the study of bypasses, in the ring option, to IP1 and IP5. There has often been a discussion about the need for two detectors and ambitious detector push-pull concepts are discussed for the Linear Collider. For the LHeC this would imply a major overhead of cost and delay in construction time. The detector envisaged here will be challenging but also be based on known technology. Truly independent reconstruction, simulation and analysis software teams using one common facility may lead to sufficient confidence when it comes to crucial and most precise results.

2.5 Two Electron Beam Options

It was shown a few years ago [17] that an electron beam in the LHC tunnel would allow to achieve an outstanding luminosity of about $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$ in ep interactions for both electrons and positrons. It is obvious, however, that while such a ring may be built without any major technical obstacle, installing it on top of the LHC magnet ring would be a non-trivial engineering task. For this reason it was decided to consider besides this “ring-ring (RR)” option also a “linac-ring (LR)” configuration, with a linear electron accelerator tangential to the LHC. For the comparison of RR and LR options, E_e was kept the same 60 GeV. The ring may extend to somewhat higher energies, while only a Linac would allow to exceed 100 GeV E_e largely. The potential for higher energy is not the only, and possibly not the dominant reason for considering a linac-ring collider. Important other benefits include the potential for higher electron current than assumed in the LHeC baseline design and thus higher luminosity, and a construction time that can overlap with LHC running.

This report presents all major components and considerations for both the RR and the LR configuration. A choice between the two configurations is envisaged soon after the appearance of the CDR. It is important to consider that the RR configuration delivers high electron and positron luminosity, with difficulties for high polarisation, while the LR configuration has a high potential for polarised electrons, but difficulties to deliver an intense positron beam, yet offering also a photon beam option. The electrical power required for a ring-ring collider at constant beam current increases with the fourth power of energy, while for a linac-ring collider the increase is roughly linear as long as the synchrotron radiation in the return arcs remains a small fraction of the total. Also, for higher electron energies in the ring the polarization greatly decreases, whereas for the linac solution the polarization is independent of beam energy. A choice of one over the other option has primarily to be based on physics but as well technical, cost and further considerations, which is why considerable effort had been spent to develop both options to the required detail. No attempt is made in the report to favour one over the other configuration. In the period of this design study both options came into a very fruitful interaction and occasional competition which nicely boosted both designs.

2.6 Luminosity and Power

The relation of the luminosity, power and energy differs for the RR and the LR configurations. In the case of the ring accelerator, as for HERA, the luminosity for matched beams is determined by the number of protons per bunch (N_p), the normalised proton beam emittance (ϵ_p), the x, y coordinates of the proton beam beta function values at the interaction point ($\beta_{x,y}$) and the electron beam current (I_e) as

$$L = \frac{N_p \cdot \gamma}{4\pi e \epsilon_p} \cdot \frac{I_e}{\sqrt{\beta_{px} \beta_{py}}}, \quad (2.1)$$

with $\gamma = E_p/M_p$. The design luminosity assumes the so-called ultimate proton beam parameters for $E_p = 7$ TeV with $1.7 \cdot 10^{11}$ protons per bunch and $\epsilon_p = 3.8 \mu\text{m}$. It is interesting to note that already the first year of operating the LHC has indicated that smaller emittance values are in reach and the bunch intensities have exceeded 10^{11} , for 50 ns spacing. Eq. 2.1 then corresponds to

$$L = 8.2 \cdot 10^{32} \text{cm}^{-2} \text{s}^{-1} \cdot \frac{N_p 10^{11}}{1.7} \cdot \frac{m}{\sqrt{\beta_{px} \beta_{py}}} \cdot \frac{I_e}{50 \text{mA}}, \quad (2.2)$$

where the electron beam current is given by

$$I_e = 0.35 \text{mA} \cdot P_{\text{SR}}[\text{MW}] \cdot \left(\frac{100}{E_e[\text{GeV}]} \right)^4. \quad (2.3)$$

Consequently one needs to minimize the β functions and gains linearly with P and like E_e^4 when decreasing the electron beam energy. With $\beta_{x(y)} = 1.8(0.5)$ m, see the optics section, one obtains a typical value of $10^{33} \text{cm}^{-2} \text{s}^{-1}$ luminosity for $E_e = 60$ GeV with 30 MW of synchrotron-radiation power. The dependence of $L(E, P)$ is shown in Fig. 2.2 (top) for the RR configuration. While with the matching requirement for each E_e an evaluation would have to be done of the β functions, one yet recognises that the RR option has a great potential to indeed achieve very high luminosities, even exceeding $10^{33} \text{cm}^{-2} \text{s}^{-1}$ if E_e was a bit lowered and P somewhat enlarged.

For this design report on the LHeC the wall-plug power limit was set to 100 MW, about one fifth of what one is considering for CLIC, for example. With a 10 years running period at such a high luminosity and N_p probably enlarged, one can consider an integrated luminosity for the LHeC of $O(100) \text{fb}^{-1}$ a realistic perspective in simultaneous operation with the LHC. This is two orders of magnitude more than HERA delivered. That is necessary for exploiting the high Q^2 and large x boundaries. It means that the whole low Q^2 physics program, with the exception of rare processes as DVCS and subject to trigger acceptance considerations, may yet be pursued in a rather short period of time.

A linear electron beam colliding with a storage ring proton beam was considered quite some time ago [13]. Its luminosity, for head-on collisions, can be obtained from the following relation [14], similar to Eq. 2.1

$$L = \frac{N_p \cdot \gamma}{4\pi e \epsilon_p} \cdot \frac{I_e}{\beta^*}, \quad (2.4)$$

which scales as

$$L = 8 \cdot 10^{31} \text{cm}^{-2} \text{s}^{-1} \cdot \frac{N_p 10^{11}}{1.7} \cdot \frac{0.2m}{\beta^*} \cdot \frac{I_e}{1 \text{mA}}, \quad (2.5)$$

where the electron beam current is given by

$$I_e = mA \cdot \frac{P_b[\text{MW}]}{(1 - \eta)E_e[\text{GeV}]}. \quad (2.6)$$

Here η denotes the efficiency of the energy recovery process, defined in terms of beam power at the collision point with and without recovery, $P_{b,er}$ and $B_{b,0}$, respectively, for the same wall-plug power, as $\eta \equiv 1/(1 - P_{b,0}/P_{b,er})$. It is easy to see that a pulsed linac without recovery is short by an order of magnitude in the

928 luminosity to the RR configuration, even for an ambitious β^* value of 0.1 m, which is introduced in the LR
929 section. With energy recovery, however, and an efficiency above 90 % as is expected to be realistic for the
930 LHeC case, one obtains luminosities of similar value as in the RR case, see Fig. 2.2. The energy recovery
931 linac (ERL) operates the cavities in CW mode at moderate gradients of typically 20 MV/m.

932 The recovery of energy requires a racetrack geometry of the linac with return arcs, or possibly two linacs
933 of opposite orientation as was originally considered [57]. This introduces synchrotron radiation losses as a
934 parameter of concern to the LR configuration also. With the design here proposed, the arcs have a bending
935 radius of 764 m, which leads to a LR accelerator of about 9 km length, which is one third of the LHC
936 circumference, and requires a small compensation stage for the energy losses in the arcs.

937 A straight high energy, pulsed linac is also considered, which at $E_e = 140$ GeV, reaches a luminosity of
938 about $5 \cdot 10^{31}$, the design value of the HERA upgrade phase. One can also contemplate about stages of ERL
939 returns, which provide much higher luminosities in this case, as is briefly demonstrated in this report too.
940 This machine would require a 40-MW beam dump, the design for which has been scaled from the 10-MW
941 dump proposed for the ILC.




Figure 2.2: Estimated luminosity, in units of $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$, for the RR configuration (top) and the LR energy recovery configuration (bottom), displayed as a function of the electron beam energy with the beam power as a parameter, see text.

Chapter 3

Executive Summary

The current version of the CDR, as of early August 2011, is for the referees as listed at the end of the draft to be evaluated. The authors are aware that various aspects of the project and the draft deserve a bit more attention prior to releasing the design report to the public. This concerns for example due consideration of the potential of the ring accelerator to reach higher than the here assumed 60 GeV beam energy, a further pass through physics and detector considerations and certainly various editorial finesses. The referee process will no doubt lead to further improvements and clarifications. The parameter table 3.1 given here may serve as a first overview for what the LHeC project as currently understood comprises. A genuine executive summary will be

For the linac technology. With the limit of present

electron beam	RR	LR	LR ^{*)}	proton beam	RR	LR
e- energy at IP[GeV]	60	60	140	bunch pop. [10 ¹¹]	1.7	1.7
luminosity [10 ³² cm ⁻² s ⁻¹]	13	10	0.4	tr.emitt.γ _{x,y} [μm]	3.75	3.75
polarization [%]	40	90	90	spot size σ _{x,y} [μm]	30, 16	7
bunch population [10 ⁹]	20	1.0	1.5	β* _{x,y} [m]	1.8,0.5	0.1
e- bunch length [mm]	10	0.3	0.3	bunch spacing [ns]	25	25
bunch interval [ns]	25	25	50			
transv. emit. γ _{x,y} [mm]	0.58, 0.29	0.05	0.1			
rms IP beam size σ _{x,y} [μm]	30, 16	7	7			
e- IP beta funct. β* _{x,y} [m]	0.18, 0.10	0.12	0.14			
full crossing angle [mrad]	1	0	0			
geometric reduction H _{hg}	0.75	0.91	0.94			
repetition rate [Hz]	-	-	10			
beam pulse length [ms]	-	-	5			
ER efficiency	-	94%	-			
average current [mA]	131	6.4	0.27			
tot. wall plug power[MW]	100	100	100			



RR= Ring – Ring LR =Linac –Ring

Ring: with 1° as baseline : L/2
Linac: clearing gap: L*2/3

*) pulsed, but high energy ERL not impossible

Figure 3.1: Parameters of the LHeC in the ring-ring and the linac-ring version as considered in the current report. The LHC proton beam parameters correspond to the “ultimate beam” configuration, to which even the current operation is already close, as with the emittance, β*, the 50 ns bunch spacing and also the number of protons per bunch. The report has also parts for electron-deuteron and electron-ion scattering.

954

Part II

955

Physics

Chapter 4

Precision QCD and Electroweak Physics

This chapter elucidates the physics prospects which are related to high precision measurements with the LHeC to test and develop QCD and the electroweak theory. Section 4.1 presents inclusive deep inelastic scattering and consists of three parts: NC and CC cross sections and structure functions, the simulation of NC and CC data sets including estimates for the expected systematic uncertainties, and the simulation of LHeC precision measurements of the longitudinal structure function F_L . The LHeC is the first DIS experiment which is able to completely unfold the quark contents of the nucleon. Section 4.2 introduces assumptions for the QCD fit, used for illustrating the expected gain in precision at the LHeC as compared to HERA, BCDMS and precision W charge asymmetry data from the LHC. Results are then presented first for the determination of the valence quark and the strange quark distributions, which are also compared with the current information as contained in modern PDF determinations. A dedicated part is written for top quark physics at the LHeC as at very high Q^2 , t and \bar{t} production in DIS become a new subject of research. Sections 4.3 and 4.4 discuss in detail the expected precision measurements of the gluon distribution and of the strong coupling constant, respectively. Section 4.5 motivates the measurements with electron-deuteron scattering which extend current experimental knowledge on the structure of the neutron (and the deuteron) by nearly four orders of magnitude in Q^2 and $1/x$. Section 4.6 introduces the measurements of the charm and beauty densities. Owing to the much extended range, higher energy (cross section) and dedicated Silicon tracking, high precision measurements of the c and b densities will be provided for the development of the QCD theory of heavy quarks and for the description of new phenomena which may be expected to be related especially to the b density, as the production of the Higgs particle in MSSM SUSY. Sections 4.7 illustrates the precision QCD tests that can be performed at the LHeC with jets in the final state, respectively. With the enlarged energy, new measurements of the total photoproduction cross sections can be performed as are discussed in Section 4.8. The Chapter is concluded with the electroweak physics Section 4.9 which focusses on the precision measurements of the light weak NC quark couplings and on the scale dependence of the electroweak mixing angle, as can be determined from polarisation asymmetries in NC and the NC/CC cross section ratio.

4.1 Inclusive Deep Inelastic Scattering

4.1.1 Cross Sections and Structure Functions

The scattering amplitude for electron-proton scattering is a product of lepton and hadron currents times the propagator characteristic of the exchanged particle, a photon or Z_0 in neutral current scattering, a W^\pm in charged current scattering. The inclusive scattering cross section therefore is given by the product of two

989 tensors,

$$\frac{d^2\sigma}{dx dQ^2} = \frac{2\pi\alpha^2}{Q^4 x} \sum_j \eta_j L_j^{\mu\nu} W_j^{\mu\nu}, \quad (4.1)$$

990 where j denotes the summation over γ , Z_0 exchange and their interference for NC, and $j = W^+$ or W^-
 991 for CC. The leptonic tensor $L_j^{\mu\nu}$ is related to the coupling of the electron with the exchanged boson and
 992 contains the electromagnetic or the weak couplings, such as the vector and axial-vector electron- Z_0 couplings,
 993 v_e and a_e , in the NC case. This leptonic part of the cross section can be calculated exactly in the standard
 994 electroweak $U_1 \times SU_2$ theory. The hadronic tensor, however, describing the interaction of the exchanged
 995 boson with the proton, can only be reduced to a sum of structure functions, $F_i(x, Q^2)$, but not be fully
 996 calculated. Conservation laws reduce the number of basic structure functions in unpolarised ep scattering to
 997 $i = 1 - 3$. In perturbative QCD the structure functions are related to parton distributions f *via* coefficient
 998 functions C

$$[F_{1,3}, F_2] = \sum_i \int_0^1 [1, z] \frac{dz}{z} C_{1,2,3}\left(\frac{x}{z}, \frac{Q^2}{\mu_r^2}, \frac{\mu_f^2}{\mu_r^2}, \alpha_s(\mu_r^2)\right) \cdot f_i(z, \mu_f^2, \mu_r^2), \quad (4.2)$$

999 where i sums the quark q , anti-quark \bar{q} and gluon g contributions and $f_i(x)$ is the probability distribution of the
 1000 parton of type i to carry a fraction x of the proton's longitudinal momentum. The coefficient functions
 1001 are exactly calculable but depend on the factorisation and renormalisation scales μ_f and μ_r . The parton
 1002 distributions are not calculable but have to be determined by experiment. Their Q^2 dependence obeys
 1003 evolution equations. A general factorisation theorem, however, has proven the parton distributions to be
 1004 universal, i.e. to be independent of the type of hard scattering process. This makes deep inelastic lepton-
 1005 nucleon scattering a most fundamental process: the parton distributions in the proton are measured best
 1006 with a lepton probe and may be used to predict hard scattering cross sections at, for example, the LHC. The
 1007 parton distributions are derived from measurements of the structure functions in NC and CC scattering, as
 1008 is discussed below.

1009 4.1.2 Neutral Current

1010 The neutral current deep inelastic ep scattering cross section, at tree level, is given by a sum of generalised
 1011 structure functions according to

$$\frac{d^2\sigma_{NC}}{dx dQ^2} = \frac{2\pi\alpha^2 Y_+}{Q^4 x} \cdot \sigma_{r,NC} \quad (4.3)$$

$$\sigma_{r,NC} = \mathbf{F}_2 + \frac{Y_-}{Y_+} \mathbf{xF}_3 - \frac{y^2}{Y_-} \mathbf{FL}, \quad (4.4)$$

1012 where the electromagnetic coupling constant α , the photon propagator and a helicity factor are absorbed in
 1013 the definition of a reduced cross section σ_r , and $Y_{\pm} = 1 \pm (1-y)^2$. The functions \mathbf{F}_2 and \mathbf{xF}_3 depend on
 1014 the lepton beam charge and polarisation (P) and on the electroweak parameters as [58]

$$\begin{aligned} \mathbf{F}_2^{\pm} &= F_2 + \kappa_Z (-v_e \mp P a_e) \cdot F_2^{\gamma Z} + \kappa_Z^2 (v_e^2 + a_e^2 \pm 2P v_e a_e) \cdot F_2^Z \\ \mathbf{xF}_3^{\pm} &= \kappa_Z (\pm a_e + P v_e) \cdot x F_3^{\gamma Z} + \kappa_Z^2 (\mp 2v_e a_e - P(v_e^2 + a_e^2)) \cdot x F_3^Z. \end{aligned} \quad (4.5)$$

1015 In the on-mass shell \overline{MS} scheme the propagator function κ_Z is given by the weak boson masses (M_Z , M_W)

$$\kappa_Z(Q^2) = \frac{Q^2}{Q^2 + M_Z^2} \cdot \frac{1}{4 \sin^2 \Theta \cos^2 \Theta} \quad (4.6)$$

1016 with the weak mixing angle $\sin^2 \Theta = 1 - M_W^2/M_Z^2$. In the hadronic tensor decomposition [59] the structure
 1017 functions are well defined quantities. In the Quark Parton Model (QPM) the longitudinal structure function

1018 is zero [60] and the two other functions are given by the sums and differences of quark (q) and anti-quark
 1019 (\bar{q}) distributions as

$$\begin{aligned} (F_2, F_2^{\gamma Z}, F_2^Z) &= x \sum (e_q^2, 2e_q v_q, v_q^2 + a_q^2)(q + \bar{q}) \\ (xF_3^{\gamma Z}, xF_3^Z) &= 2x \sum (e_q a_q, v_q a_q)(q - \bar{q}), \end{aligned} \quad (4.7)$$

1020 where the sum extends over all up and down type quarks and $e_q = e_u, e_d$ denotes the electric charge of up-
 1021 or down-type quarks. The vector and axial-vector weak couplings of the fermions ($f = e, u, d$) to the Z_0
 1022 boson in the standard electroweak model are given by

$$v_f = i_f - e_f 2 \sin^2 \Theta \quad a_f = i_f \quad (4.8)$$

1023 where $e_f = -1, 2/3, -1/3$ and $i_f = I(f)_{3,L} = -1/2, 1/2, -1/2$ denotes the left-handed weak isospin charges,
 1024 respectively. Thus the vector coupling of the electron, for example, is very small, $v_e = -1/2 + 2 \sin^2 \Theta \simeq 0$,
 1025 since the weak mixing angle is roughly equal to $1/4$.

1026 At low Q^2 and low y the reduced NC cross section, Eq.4.3, to a very good approximation is given by
 1027 $\sigma_r = F_2(x, Q^2)$. At $y > 0.5$, F_L makes a sizeable contribution to $\sigma_{r,NC}$. In the DGLAP approximation of
 1028 perturbative QCD, to lowest order, the longitudinal structure function is given by [61]

$$F_L(x) = \frac{\alpha_s}{4\pi} x^2 \int_x^1 \frac{dz}{z^3} \cdot \left[\frac{16}{3} F_2(z) + 8 \sum e_q^2 \left(1 - \frac{x}{z}\right) z g(z) \right], \quad (4.9)$$

1029 which at low x is dominated by the gluon contribution. A measurement of F_L requires a variation of the
 1030 beam energy.

1031 Two further structure functions can be accessed with cross section asymmetry measurements, in which
 1032 the charge and/or the polarisation of the lepton beam are varied. A charge asymmetry measurement, with
 1033 polarisation values P_{\pm} of the e^{\pm} beam, determines the following structure function combination

$$\sigma_{r,NC}^+(P_+) - \sigma_{r,NC}^-(P_-) = -\kappa_Z a_e (P_+ + P_-) \cdot F_2^{\gamma Z} + \frac{Y_-}{Y_+} \kappa_Z a_e \cdot [2xF_3^{\gamma Z} + (P_+ - P_-) \kappa_Z a_e x F_3^Z] \quad (4.10)$$

1034 neglecting terms $\propto v_e$ which can be easily obtained from Eq.4.5. If data are taken with opposite polarisation
 1035 and charge, the asymmetry represents a measurement of the difference of quark and anti-quark distributions
 1036 in NC, see Eq.4.7. In contrast to what is often stated, the charge asymmetry is a parity conserving quantity
 1037 $\propto a_e a_q$. Assuming symmetry between sea and antiquarks, it is a direct measure of the valence quarks,
 1038 $xF_3^{\gamma Z} = 2u_v + d_v$ in ep . This function was measured for the first time in μ^{\pm} Carbon scattering by the
 1039 BCDMS Collaboration [62] at large $x > 0.2$ and for Q^2 of about 50 GeV^2 . With the LHeC, for the first
 1040 time, high precision measurements of xF_3 in NC become possible as is demonstrated in Sect.4.2.2. These
 1041 will access the valence quarks at low $x \lesssim 0.001$ for the first time in direct measurements.

1042 A genuine polarisation asymmetry measurement, keeping the beam charge fixed, according to eqs.4.3
 1043 and 4.5 determines a similar combination of $F_2^{\gamma Z}$ and $xF_3^{\gamma Z}$

$$\frac{\sigma_{r,NC}^{\pm}(P_L) - \sigma_{r,NC}^{\pm}(P_R)}{P_L - P_R} = \kappa_Z [\mp a_e F_2^{\gamma Z} + \frac{Y_-}{Y_+} v_e x F_3^{\gamma Z}] \simeq \mp \kappa_Z a_e F_2^{\gamma Z} \quad (4.11)$$

1044 neglecting again the term $\propto v_e$. The product $a_e F_2^{\gamma Z}$ is proportional to combinations $a_e v_q$ and thus a direct
 1045 measure of parity violation at very small distances.

1046 The structure function $F_2^{\gamma Z}$ accesses a new combination of quark distributions and is measurable for the
 1047 first time, and with high precision, at the LHeC, see Fig.4.1, in which the result is shown of its possible
 1048 measurement. The remarkable precision on $F_2^{\gamma Z}$ illustrates the huge potential in precision and range which
 1049 the LHeC brings. For the study of electroweak effects one clearly desires to have the maximum beam energy
 1050 and polarisation available as the comparison of the two results for different beam conditions but the same
 1051 luminosity in Fig.4.1 shows.

1052 The polarisation asymmetry also permits a high precision measurement of the weak mixing angle at
 1053 different Q^2 values, below and to much higher values than M_Z^2 , at which $\sin^2 \Theta$ was precisely measured at
 1054 LEP and the SLC, see Sect.4.9.3.




Figure 4.1: Simulation of the measurement of the γZ interference structure function $F_2^{\gamma Z}$, shown as a function of x for a typical high Q^2 value, for two LHeC configurations ($E_e = 60$ GeV and $P = \pm 0.4$, left) and ($E_e = 140$ GeV and $P = \pm 0.9$, right). The proton beam energy is 7 TeV and the luminosity assumed is 10 fb^{-1} per polarisation state. This function is a measure for parity violation and provides additional information on the quark distributions as it is proportional to $e_q v_q$ to be compared with e_q^2 in the lowest order function F_2 . Shown are statistical uncertainties only. The systematic uncertainty can be expected to be small as in the asymmetry many effects cancel and because at the LHeC such asymmetries are large, and the polarisation possibly controlled at the per mille level, as is discussed in the technical part of the CDR.

1055 4.1.3 Charged Current

1056 The inclusive polarised charged current $e^\pm p$ scattering cross section can be written as

$$\frac{d^2\sigma_{CC}^\pm}{dx dQ^2} = \frac{1 \pm P}{2} \cdot \frac{G_F^2}{2\pi x} \cdot \left[\frac{M_W^2}{M_W^2 + Q^2} \right]^2 Y_+ \cdot \sigma_{r,CC}. \quad (4.12)$$

1057 The reduced charged current cross section, analogous to the NC case Eq. 4.3, is a sum of structure function
1058 terms

$$\sigma_{r,CC}^\pm = W_2^\pm \mp \frac{Y_-}{Y_+} xW_3^\pm - \frac{y^2}{Y_+} W_L^\pm. \quad (4.13)$$

1059 In the on-mass shell scheme, the Fermi constant G_F is defined, see for example [63], using the weak boson
1060 masses as

$$G_F = \frac{\pi\alpha}{\sqrt{2}M_W^2 \sin^2\theta(1 - \Delta r)} \quad (4.14)$$

1061 with $\sin^2\theta = 1 - M_W^2/M_Z^2$ as above. The higher order correction term Δr can be approximated [64] as
1062 $\Delta r = 1 - \alpha/\alpha(M_Z) - 0.0094(m_t/173\text{GeV})^2/\tan^2\theta$, and thus introduces a dependence of the DIS cross section
1063 on the mass of the top quark. The choice of G above allows the CC cross section, Eq. 4.12, to be rewritten
1064 as

$$\frac{d^2\sigma_{CC}^\pm}{dx dQ^2} = \frac{1 \pm P}{2} \cdot \frac{2\pi\alpha^2 Y_+}{Q^4 x} \cdot \kappa_W^2 \cdot \sigma_{r,CC}, \quad (4.15)$$

1065 with

$$\kappa_W(Q^2) = \frac{Q^2}{Q^2 + M_W^2} \cdot \frac{1}{4\sin^2\theta}, \quad (4.16)$$

1066 which is convenient for the consideration of NC/CC cross section ratios.

1067 In the QPM (where $W_L^\pm = 0$), the structure functions represent beam charge dependent sums and
1068 differences of quark and anti-quark distributions and are given by

$$W_2^+ = x(\bar{U} + D), \quad xW_3^+ = x(D - \bar{U}), \quad W_2^- = x(U + \bar{D}), \quad xW_3^- = x(U - \bar{D}). \quad (4.17)$$

1069 Using these equations one finds

$$\sigma_{r,CC}^+ \sim x\bar{U} + (1-y)^2 xD, \quad (4.18)$$

$$\sigma_{r,CC}^- \sim xU + (1-y)^2 x\bar{D}. \quad (4.19)$$

1070 Combined with Equation 4.5, which approximately reduces to

$$\begin{aligned} \sigma_{r,NC}^\pm &\simeq [c_u(U + \bar{U}) + c_d(D + \bar{D})] + \kappa_Z[d_u(U - \bar{U}) + d_d(D - \bar{D})] \\ c_{u,d} &= e_{u,d}^2 + \kappa_Z(-v_e \mp Pa_e)e_{u,d}v_{u,d} \quad d_{u,d} = \pm a_e a_{u,d} e_{u,d}, \end{aligned} \quad (4.20)$$

1071 one finds that the NC and CC cross section measurements at the LHeC determine the complete set U, D, \bar{U}
1072 and \bar{D} , i.e. the sum of up-type, of down-type and of their anti-quark-type distributions. Below the b quark
1073 mass threshold, these are related to the individual quark distributions as follows

$$U = u + c \quad \bar{U} = \bar{u} + \bar{c} \quad D = d + s \quad \bar{D} = \bar{d} + \bar{s}. \quad (4.21)$$

1074 Assuming symmetry between sea quarks and anti-quarks, the valence quark distributions result from

$$u_v = U - \bar{U} \quad d_v = D - \bar{D}. \quad (4.22)$$

1075 4.1.4 Cross Section Simulation and Uncertainties

1076 The LHeC extends the kinematic range as compared to HERA in the negative momentum transfer squared
 1077 Q^2 from a maximum of about 0.03 to 1 TeV² and towards low x , e.g. for $Q^2 = 3 \text{ GeV}^2$, from about $4 \cdot 10^{-5}$
 1078 to $2 \cdot 10^{-6}$. The projected increase of integrated luminosity by a factor of 100 allows to also extend the
 1079 kinematic range at large x , in charged currents, from practically about 0.4 to 0.8. Due to the enlarged
 1080 electron beam energy E_e the range of high inelasticity $y \simeq 1 - E'_e/E_e$ should extend closer to 1. A reduced
 1081 noise in the calorimeters may allow to reach lower values of y than at HERA, also because the hadronic y
 1082 is determined as the sum over $E - p_z$ divided by twice the with the LHeC enhanced electron beam energy.
 1083 Very recently it has been observed by H1 that the reconstruction of the hadronic final state with jets rather
 1084 than the full sum of hadronic energy depositions allows to control better the region of low y , i.e. scattering
 1085 close to the beam pipe. At the LHeC these jets are extremely energetic and one would expect, subject to
 1086 detailed simulation studies at a later stage of the project, that kinematic reconstruction for values of y down
 1087 to 0.001 or even below could be trusted.

1088 While the extensions of kinematic coverage and improvements of statistical precision are impressive,
 1089 an estimate of the impact of LHeC NC and CC cross section measurements on derived quantities such as
 1090 structure functions and parton distributions requires to also estimate the expected systematic measurement
 1091 accuracy as may be achieved with the detector described in Chapter 13 below. In the following the assump-
 1092 tions and simulation results are presented for the NC and the CC cross sections, which are subsequently
 1093 used in QCD fit and other analyses throughout this report.

1094 The systematic uncertainties of the DIS cross sections have a number of sources, which at HERA have
 1095 broadly been classified as uncorrelated and correlated across bin boundaries. For the NC case, the uncor-
 1096 related sources, apart from data and Monte Carlo statistics, are a global efficiency uncertainty, due to for
 1097 example tracking or electron identification errors, photoproduction background, calorimeter noise and radi-
 1098 ative corrections. The correlated uncertainties result from imperfect energy scale and angle calibrations. In
 1099 the classic kinematic reconstruction methods used here, and described in Sect. 12.1 one uses the scattered
 1100 electron energy E'_e and polar angle θ_e complemented by the energy of the hadronic final state E_h ¹. The
 1101 correlated errors are due to scale uncertainties of the electron energy E'_e and of the hadronic final state
 1102 energy E_h . There are also systematic errors due to an uncertainty of the measurement of the electron polar
 1103 angle θ_e . The assumptions used in the simulation of pseudodata are summarised in Table 4.1.

1104 In the absence of a detailed detector simulation at this stage, the systematic NC cross uncertainties due
 1105 to E'_e , θ_e and E_h are calculated, following [65], from the derivatives of the NC cross section in the chosen bins
 1106 taking into account the Jacobians where needed. The results have been compared, for the HERA kinematics,
 1107 with the H1 MC simulation of systematic errors [66] and found to be in very good agreement for all three
 1108 sources. The resulting error depends much on the kinematics. At low Q^2 , for example, the systematic cross
 1109 section error due to the uncertainty of θ_e rises because of $\delta Q^2/Q^2 = \delta E'_e/E'_e \oplus \tan(\theta_e/2) \cdot \delta\theta_e$ while at high
 1110 Q^2 it is negligible. Low Q^2 is the backward region, of large electron scattering angles with respect to the
 1111 proton beam direction.

1112 A particular challenge is the measurement at large x because the cross section varies as $(1-x)^c$, with
 1113 $c \simeq 3$, and thus the relative error is amplified $\propto 1/(1-x)$ as x approaches 1. At high x the hadronic final
 1114 state is scattered into the forward detector region where the energy calibration becomes challenging. The
 1115 calculated correlated NC cross section errors are illustrated in Figs. 4.2 and 4.3 for $Q^2 = 2$ and 20000 GeV²,
 1116 respectively. In the detector chapter these calculations have been taken to define approximate requirements
 1117 on the scale calibrations in the different detector regions. An example for the resulting cross section
 1118 measurement is displayed in Fig. 4.4 for low x and in Fig. 4.5 for large x .

¹Basically one determines Q^2 best with the electron kinematics and determines x from $y = Q^2/sx$. At large y the inelasticity is essentially measured with the electron energy $y \simeq 1 - E'_e/E_e$. At low y one has $y = E_h \sin^2(\theta_h/2)/E_e$ with the hadronic final state energy E_h and angle θ_h which results in $\delta y/y \simeq \delta E_h/E_h$ to good approximation. There have been various refined methods proposed to determine the DIS kinematics, as the double angle method or the so-called sigma method. For the estimate of the cross section uncertainty behaviour as functions of Q^2 and x , however, the simplest method using Q_e^2, y_e at large y and Q_e^2, y_h at low y is transparent and accurate enough within better than a factor of two. In much of the phase space, moreover, it is rather the uncorrelated efficiency or further specific errors than the kinematic correlations, which dominate the cross section measurement accuracy.




Figure 4.2: Neutral current cross section errors, calculated for $60 \times 7000 \text{ GeV}^2$, as result from scale uncertainties of the scattered electron energy $\delta E'_e/E'_e = 0.1\%$, of its polar angle $\delta\theta_e = 0.1 \text{ mrad}$ and the hadronic final state energy $\delta E_h/E_h = 0.5\%$, at low $Q^2 = 2 \text{ GeV}^2$ and correspondingly low x .




Figure 4.3: Neutral current cross section errors, calculated for $60 \times 7000 \text{ GeV}^2$ unpolarised e^-p scattering, as result from scale uncertainties of the scattered electron energy $\delta E'_e/E'_e = 0.1\%$, of its polar angle $\delta\theta_e = 0.1 \text{ mrad}$ and the hadronic final state energy $\delta E_h/E_h = 0.5\%$, at large $Q^2 = 20000 \text{ GeV}^2$ and correspondingly large x . Note that the characteristic behaviour of the relative uncertainty at large x , i.e. to diverge $\propto 1/(1-x)$, is independent of Q^2 , i.e. persistently observed at $Q^2 = 200000 \text{ GeV}^2$ for example too.




Figure 4.4: Simulated neutral current, inclusive reduced cross section measurement, for an integrated luminosity of 10 fb^{-1} , in unpolarised e^-p scattering at $E_e = 60$ and $E_p = 7000 \text{ GeV}$. The DIS cross section is measurable at unprecedented precision and range. The uncertainty is about or below 1% and thus not visible on this plot. Departures from the strong rise of the reduced cross section, $\sigma_r \simeq F_2$, at very low x and Q^2 are expected to appear due to non-linear gluon-gluon interaction effects in the so-called saturation region.




Figure 4.5: Simulated neutral current, inclusive reduced cross section measurement, for an integrated luminosity of 10 fb^{-1} , in unpolarised e^-p scattering at $E_e = 60$ and $E_p = 7000 \text{ GeV}$. The DIS cross section is measurable at unprecedented precision and range. Plotted is the total uncertainty which, where visible at high x and Q^2 , is dominated by the statistical error. Similar data sets are expected with different beam polarisations and charges, and in CC scattering, for $Q^2 \geq 100 \text{ GeV}^2$. The strong variations of σ_r with Q^2 , as at $x = 0.25$, are due to the effects of Z exchange as is discussed and illustrated subsequently.

source of uncertainty	error on the source or cross section
scattered electron energy scale $\Delta E'_e/E'_e$	0.1 %
scattered electron polar angle	0.1 mrad
hadronic energy scale $\Delta E_h/E_h$	0.5 %
calorimeter noise (only $y < 0.01$)	1-3 %
radiative corrections	0.5%
photoproduction background (only $y > 0.5$)	1 %
global efficiency error	0.7 %

Table 4.1: Assumptions used in the simulation of the NC cross sections on the amount of uncertainties from various sources. These assumptions correspond to the typical or best of what was achieved in the H1 experiment. Note that in the cross section measurement the energy scale and angular uncertainties are relative to the Monte Carlo and not to be confused with resolution effects which determine the purity and stability of binned cross sections. The total cross section error due to these uncertainties, e.g. for $Q^2 = 100 \text{ GeV}^2$, is about 1.2, 0.7 and 2.0 % for $y = 0.84, 0.1, 0.004$.

1119 For the CC case, a similar simulation was done, albeit with less numeric effort. An illustration of the
1120 high precision and large range of the inclusive CC cross section measurements is presented in Fig. 4.6. The
1121 systematic cross section error, based on the H1 experience, was set to 2% and for larger $x > 0.3$ a term
1122 was added to allow the error to rise linearly to 10% at $x = 0.9$. For both NC and CC cross sections
1123 the statistical error is given by the number of events but limited to 0.1% from below. With these error
1124 assumptions a number of data sets was simulated, both for NC and CC, which is summarised in Table 4.2.
1125 The energies of these sets had been chosen prior to the final baseline energy choice. For the simulation of
1126 the F_L measurement, described below, a separate set of beam energies is considered.

1127 4.1.5 Longitudinal Structure Function F_L

1128 The inclusive, deep inelastic electron-proton scattering cross section at low Q^2 ,

$$\frac{d^2\sigma}{dx dQ^2} = \frac{2\pi\alpha^2 Y_+}{Q^4 x} [F_2(x, Q^2) - f(y) \cdot F_L(x, Q^2)], \quad (4.23)$$

1129 is defined by two proton structure functions, F_2 and F_L with $y = Q^2/sx$, $Y_+ = 1 + (1-y)^2$ and $f(y) = y^2/Y_+$.
1130 The two functions reflect the transverse and the longitudinal polarisation state of the virtual photon probing
1131 the proton structure, i.e. $F_T = F_2 - F_L$ and F_L , respectively. The positivity of the transverse and longitudinal
1132 cross sections requires $0 \leq F_L \leq F_2$. Since for most of the kinematic range the y dependent factor $f(y)$ is
1133 very small, there follows that F_L causes in most of the kinematic range only a small correction to the reduced
1134 cross section, which is governed by F_2 , apart from the regio of maximum y . At small x , the inelasticity is
1135 given as $y \simeq 1 - E'_e/E_e$. Therefore, in order to extract F_L , DIS has to be measured extremely accurately
1136 at small scattered lepton energies, which is a question of how large E_e is, how to trigger and how to control
1137 the background from particle production at low energies. A variation of the beam energies is required to
1138 separate the two functions measured at the same x and Q^2 by variation of $y = Q^2/sx$.

1139 A first measurement of F_L at low x at HERA has recently been performed by the ZEUS Collaboration [67]
1140 and by the H1 Collaboration [68]. For the study of the gluon distribution at lowest x , the H1 data are crucial
1141 as only H1 has measured F_L below Q^2 of about 10 GeV^2 owing to their backward detector constellation
1142 upgraded in the nineties. The F_L measurement at HERA was performed towards the end of the accelerator
1143 operation and could only extend over a period of three months with about 10 pb^{-1} of integrated luminosity
1144 spent at two reduced proton beam energies, 450 and 565 GeV, besides the nominal 920 GeV. The H1 result is
1145 consistent with pQCD predictions. The ratio $R = F_L/(F_2 - F_L)$ has been found to be independent of x and
1146 Q^2 at 20% accuracy, i.e. $R = 0.26 \pm 0.05$ [68]. This interesting relation deserves a more precise investigation
1147 and may break when the region of saturation is entered at lower x than HERA could access.




Figure 4.6: Reduced charged current cross sections with statistical uncertainties corresponding to 1 fb^{-1} electron (top data points, red) and positron (lower data points, blue) proton scattering at the LHeC, The curves are determined by the dominant valence quark distributions, u_v for e^-p and d_v for e^+p . In the simulation the lepton polarisation is taken to be zero. The valence-quark approximation of the reduced cross section is seen to hold at $x \geq 0.3$. A precise determination of the u/d ratio up to large x appears to be feasible at very high Q^2 .

Set	E_e/GeV	E_N/TeV	N	L^+/fb^{-1}	L^-/fb^{-1}	Pol
A	20	7	7	1	1	0
B	50	7	7	50	50	0.4
C	50	7	7	1	1	0.4
D	100	7	7	5	10	0.9
E	150	7	7	3	6	0.9
F	50	3.5	7	1	1	0
G	50	2.7	7	0.1	0.1	0.4
H	50	1	7	-	1	0

Table 4.2: Conditions for simulated NC and CC data sets for studies on the LHeC physics. Here, A defines a low electron beam energy option which is of interest to reach lowest Q^2 because Q_{min}^2 decreases $\propto E_e^{-2}$; B is the standard set, with a total luminosity split between different polarisation and charge states. C is a lower luminosity version which was considered in case there was a need for a dedicated low/large angle acceptance configuration, which according to more recent findings could be avoided since the luminosity in the restricted acceptance configuration is estimated, from the β functions obtained in the optics design, to be half of the luminosity in the full acceptance configuration; D is an intermediate energy linac-ring version, while E is the highest energy version considered, with the luminosities as given. It is likely that the assumptions for D and E on the positron luminosity are a bit optimistic. However, even with twenty times lower positron than electron luminosity one would have 0.5 fb^{-1} , i.e. the total HERA luminosity equivalent available in option D for example. F is the deuteron and G the lead option; finally H was simulated for a low proton beam energy configuration as is of interest to maximise the acceptance at large x .

1148 The LHeC will extend this initial measurement by using higher luminosities and dedicated detector
1149 conditions into a much enlarged kinematic range. Since the LHeC is supposed to run synchronously with the
1150 LHC, the simulation presented here has been made with reduced electron beam energies keeping the proton
1151 beam energy untouched. The following set of energies and integrated luminosities: (60, 1), (30, 0.3), (20,
1152 0.1) and (10, 0.05) (GeV, fb^{-1}). Note that the F_L measurement requires to also have data with the opposite
1153 beam charge in order to be able to reliably subtract the non DIS background which at high y is substantial.
1154 This has not been simulated here.

1155 In the low x studies below a similar simulation was used for which the luminosity assumptions were
1156 similar but a set of reduced proton beam energies was considered. The advantage of lowering E_p is that the
1157 maximum y for all beam energy configurations can be high, e.g. 0.95 for $E_e = 60 \text{ GeV}$. When E_e is lowered
1158 instead, one has to accept a lower y_{max} as below a few GeV of energy the background is too high for a
1159 reliable measurement to be performed. The results of both F_L simulations, with reduced E_e or E_p , come
1160 out to be very similar.

1161 The result of the simulation study is shown in Fig. 4.7. The technique applied is the conventional separa-
1162 tion of F_2 and F_L by fitting a straight line to the various reduced cross section data points at fixed Q^2 and
1163 x with $f(y)$ as the parameter and separating the uncorrelated from the correlated systematic uncertainties
1164 which partially cancel in such an analysis. The expected accuracy on F_L is typically 4% at Q^2 of 3.5 GeV^2
1165 or 7% at Q^2 of 25 GeV^2 at a number of points in x , with mainly similar contributions from the calculated
1166 correlated and the assumed uncorrelated systematic uncertainties, and less due to statistics which yet starts
1167 to become important for $Q^2 \geq 100 \text{ GeV}^2$. The LHeC thus will provide the first precision measurement of
1168 $F_L(x, Q^2)$ ever, in a region where the behaviour of the gluon density ought to change significantly and new,
1169 non-linear laws for parton evolution should emerge.

1170 A related measurement of prime interest is the determination of F_L in diffraction, as is discussed below.
1171 A pioneering measurement of F_L^D has been performed by H1 (-cite when published in July-).




Figure 4.7: Simulated measurement of the longitudinal structure function $F_L(x, Q^2)$ at the LHeC (red closed circles) from a series of runs with reduced electron beam energy, see text. The inner error bars denote the statistical uncertainty, the outer error bars are the total errors with the additional uncorrelated and correlated systematic uncertainties added in quadrature. The blue squares denote the recently published result of the H1 Collaboration, plotting only the x averaged results as the more accurate ones, see [68]. The LHeC extends the measurement towards low x and high Q^2 (not fully illustrated here) with much improved precision.

4.2 Determination of Parton Distributions

Despite a series of deep inelastic scattering experiments with neutrinos, electrons and muons using stationary targets and with HERA, despite the addition of some Drell Yan data, the knowledge of the quark distributions in the proton is still limited. It often relies on pQCD analyses using various assumptions on the Bjorken x dependence of the PDFs and their symmetries. The LHeC has the potential to put the PDF knowledge on a qualitatively and quantitatively new and superior basis. This is due to the kinematic range, huge luminosity, availability of polarised electron and positron beams, as of proton and deuteron beams, and to the anticipated very high precision of the cross section measurements as has been discussed above.

The LHeC has the potential to provide crucial constraints and many determinations of parton distributions completely or rather independently of the conventional QCD fitting techniques. For example, the valence quarks can be measured up to high x , and all heavy quarks be determined from dedicated c and b tagging analyses with unprecedented precision. Therefore, the then evolving QCD fits based on real LHeC data will be set-up with a massively improved and better constrained input data base. Their eventual effect is thus not easy to simulate now, it yet may be illustrated based on the currently used procedures.

The striking potential of the determination of the quark and gluon distributions will be discussed and illustrated below. For the various PDFs, the current knowledge is illustrated with a series of plots based on the world's best PDF determinations available today. Simulations of essentially direct quark distribution measurements, as for the charm quark, will be shown. Moreover, a consistent set of standard QCD fits has been performed using the simulated LHeC and further data which is first described in what follows. This is used to illustrate the effect the inclusive NC and CC data from the LHeC are expected to have on the PDF uncertainties.

Currently extensive work is being performed to test and further constrain PDFs with Drell-Yan scattering data from the LHC. This naturally focusses on the Z and W^\pm production and decay. While such tests are undoubtedly of interest, they require an extremely high level of precision as at scales $Q^2 \simeq M_{W,Z}^2$ any effect due to PDF differences at smaller scales is washed out by the overriding effect of quark-antiquark pair production from gluon emission, below the valence quark region. The present QCD fit results also use a set of simulated $W^+ - W^-$ asymmetry data of ultimate precision in order to be able to estimate the effect the Drell-Yan data will have besides the LHeC in the determination of the PDF's.

4.2.1 QCD Fit Ansatz

NLO QCD fits are performed in order to study the effect of the (simulated) LHeC data on the PDF knowledge. Fits are done using the combined HERA data published and so available to date (HERA I), adding BCDMS proton data as the most accurate fixed target structure function set of importance at high x , simulated precision $W^+ - W^-$ asymmetry LHC data, using the LHeC data alone and in combination. In the fits, for the central values of the LHeC data, the Standard Model expectation is used, smeared within the uncorrelated, Gaussian distributed uncertainties and taking into account the correlated uncertainties as well.

The procedure used here is adopted from the HERA QCD fit analysis [38]. The QCD fit analysis to extract the proton's PDFs is performed imposing a $Q_{min}^2 = 3.5 \text{ GeV}^2$ to restrain to the region where perturbative QCD can be assumed to be valid. The fits are extended to lowest x for systematic uncertainty studies, even when at such low x values non-linear effects are expected to appear.

The fit procedure consists first in parametrising PDFs at a starting scale $Q_0^2 = 1.9 \text{ GeV}^2$, chosen to be below the charm mass threshold. The parametrised PDFs are the valence distributions xu_v and xd_v , the gluon distribution xg , and the $x\bar{U}$ and $x\bar{D}$ distributions, where $x\bar{U} = x\bar{u}$, $x\bar{D} = x\bar{d} + x\bar{s}$. This ansatz is natural to the extent that the NC and CC inclusive cross sections determine the sums of up and down quark distributions, and their antiquark distributions, as the four independent sets of PDFs, which may be transformed to the ones chosen if one assumes $u_v = U - \bar{U}$ and $d_v = D - \bar{D}$, i.e. the equality of anti- and sea quark distributions of given flavour.

The following standard functional form is used to parameterise them

$$xf(x) = Ax^B(1-x)^C(1+Dx+Ex^2), \quad (4.24)$$

1219 where the normalisation parameters (A_{uv}, A_{dv}, A_g) are constrained by quark counting and momentum sum
 1220 rules.

1221 The parameters $B_{\bar{U}}$ and $B_{\bar{D}}$ are set equal, $B_{\bar{U}} = B_{\bar{D}}$, such that there is a single B parameter for
 1222 the sea distributions, an assumption the validity of which will be settled with the LHeC. The strange quark
 1223 distribution at the starting scale is assumed to be a constant fraction of \bar{D} , $x\bar{s} = f_s x\bar{D}$, chosen to be $f_s = 0.31$.
 1224 In addition, to ensure that $x\bar{u} \rightarrow x\bar{d}$ as $x \rightarrow 0$, $A_{\bar{U}} = A_{\bar{D}}(1 - f_s)$. The D and E are introduced one by
 1225 one until no further improvement in χ^2 is found. The best fit resulted in a total of 10 free parameters [38],
 1226 while fits with a tested set of 14 parameters lead to very similar results. As discussed above this will change
 1227 considerably when the LHeC data become available and more flexible parameterisations and methods can
 1228 be tested. This has been studied to some extent in the simulation for α_s presented below.

1229 The PDFs are then evolved using DGLAP evolution equations [69] at NLO in the \overline{MS} scheme with the
 1230 renormalisation and factorisation scales set to Q^2 using standard sets of parameters as for $\alpha_s(M_Z)$. These,
 1231 as well as the exact treatment of the heavy quark thresholds, are of no significant influence for the estimates
 1232 of the PDF uncertainties to which the subsequent analysis is only directed. The experimental uncertainties
 1233 on the PDFs are determined using the $\Delta\chi^2 = 1$ criterion.

1234 4.2.2 Valence Quarks

1235 The knowledge of the valence quark distributions, both at large and at low Bjorken x , as derived in the
 1236 current world data QCD fit analyses is amazingly limited, as is illustrated in Fig. 4.8 from a comparison of
 1237 the leading determinations of PDF sets. This has to do, at high x , with the limited luminosity, challenging
 1238 systematics rising $\propto 1/(1-x)$ and nuclear correction uncertainties, and, at low x , with the smallness of the
 valence quark distributions as compared to the sea quarks. The impressive improvement expected from the




Figure 4.8: Ratios (to MSTW08) and uncertainty bands of valence quark distributions, at $Q^2 = 1.9 \text{ GeV}^2$, for most of the available recent PDF determinations. Top: up valence quark; down: down valence quark; left: logarithmic x , right: linear x .

1239 LHeC is demonstrated in Fig. 4.9. As can be seen, the uncertainty of the down valence quark distribution at,
 1240

1241 for example, $x = 0.7$ is reduced from a level of 50 – 100 % to about 5 %. The up valence quark distribution is
 1242 better known than d_v , because it enters with a four-fold weight in F_2 , due to the electric quark charge ratio
 1243 squared, a big improvement yet is also visible. These huge improvement effects at large x are a consequence
 1244 of the high precision measurements of the NC and the CC inclusive cross sections, which at high x tend to
 1245 $4u_v + d_v$ and u_v (d_v) for electron (positron) scattering, respectively. At HERA the luminosity and range had
 1246 not been high enough to allow a similar measurement as will be possible for the first time with the LHeC.
 1247 This is illustrated in Fig. 4.10 which compares recent results of the ZEUS Collaboration, on the CC cross
 section with the LHeC simulation.




Figure 4.9: Uncertainty of valence quark distributions, at $Q^2 = 1.9 \text{ GeV}^2$, as resulting from an NLO QCD fit to HERA (I) alone (green, outer), HERA and BCDMS (crossed), HERA and LHC (light blue, crossed) and the LHeC added (blue, dark). Top: up valence quark; down: down valence quark; left: logarithmic x , right: linear x .

1248

1249 Access to valence quarks at low x can be obtained from the $e^\pm p$ cross section difference as introduced
 1250 above:

$$\sigma_{r,NC}^- - \sigma_{r,NC}^+ = 2 \frac{Y_-}{Y_+} (-a_e \cdot k x F_3^{\gamma Z} + 2v_e a_e \cdot k^2 x F_3^Z). \quad (4.25)$$

1251 Since the electron vector coupling, v_e , is small and k not much exceeding 1, to a very good approximation the
 1252 cross section difference is equal to $-2kY_- a_e x F_3^{\gamma Z} / Y_+$. In leading order pQCD this “interference structure
 1253 function” can be written as

$$x F_3^{\gamma Z} = 2x [e_u a_u (U - \bar{U}) + e_d a_d (D - \bar{D})], \quad (4.26)$$

1254 with $U = u + c$ and $D = d + s$ for four flavours. The $x F_3^{\gamma Z}$ structure function thus provides information
 1255 about the light-quark axial vector couplings (a_u , a_d) and the sign of the electric quark charges (e_u , e_d).
 1256 Equivalently one can write

$$x F_3^{\gamma Z} = 2x [e_u a_u (u_v + \Delta_u) + e_d a_d (d_v + \Delta_d)]. \quad (4.27)$$




Figure 4.10: Reduced charged current e^+p scattering cross section versus Bjorken x for different polarisations $\pm P$ and values of Q^2 . Closed points: LHeC simulations for 10 fb^{-1} ; open points: ZEUS measurements based on the full HERA statistics of about 0.15 fb^{-1} per polarisation state. Note that the reduced CC cross section at fixed x and Q^2 contains an explicit dependence on the beam energy via the ratio of inelasticity dependent factors Y_-/Y_+ , which is at the origin of the simulated and measured cross section differences apparent at lower x .

1257 In the naive parton model as in conventional perturbative QCD, it is assumed that the differences $\Delta_u =$
 1258 $(u_{sea} - \bar{u} + c - \bar{c})$ and $\Delta_d = (d_{sea} - \bar{d} + s - \bar{s})$ are zero ². Inserting the SM charge and axial coupling values
 1259 one finds

$$xF_3^{\gamma Z} = \frac{x}{3}(2u_v + d_v + \Delta) \quad (4.28)$$

1260 with $\Delta = 2\Delta_u + \Delta_d$. Neglect of Δ leads to a sum rule [70], which in leading order is

$$\int_0^1 xF_3^{\gamma Z} \frac{dx}{x} = \frac{1}{3} \int_0^1 (2u_v + d_v) dx = \frac{5}{3}. \quad (4.29)$$

1261 The $xF_3^{\gamma Z}$ structure function thus is determined by the valence quark distributions and predicted to be only
 1262 very weakly depending on Q^2 . Fig. 4.11 shows a simulation of $xF_3^{\gamma Z}$ and its comparison with the so far most
 1263 accurate measurement from HERA. With such a high precision interesting tests are possible of the relation
 1264 of $xF_3^{\gamma Z}$ to xW_3 , which should only differ by the weak couplings involved in NC and CC.

1265 4.2.3 Strange Quarks

1266 The strange quark distribution $s(x, Q^2)$ has been very difficult to measure. In DIS some information is
 1267 obtained from di-muon production in neutrino-nucleon scattering. Often s is linked to the behaviour of the
 1268 sea quarks. Recently the HERMES Collaboration, from kaon multiplicities, derived an unusual behaviour of
 1269 the strange quark density as compared to previous analyses [71]. Some hints for a difference between the s
 1270 and \bar{s} distributions have been discussed. The existing information on the sum of the strange and anti-strange
 1271 quark distributions is plotted in Fig. 4.12. Obviously there is no real understanding of the strange quark
 1272 distribution in the proton available. This will change with the LHeC. Here s and \bar{s} may be very well measured
 1273 as a function of x and Q^2 from the $W^+s \rightarrow c$ and $W^-\bar{s} \rightarrow \bar{c}$ processes, i.e. with charmed quark tagging
 1274 in CC DIS using electron and positron beams, respectively. The precision for s which may be obtained is
 1275 illustrated in Fig. 4.13. Accurate measurements may be obtained for the first time ever. The simulation of
 1276 \bar{s} obviously leads to the same picture such that over a wide kinematic range possible differences between s
 1277 and \bar{s} may be established.

1278 4.2.4 Top Quarks

1279 The top is the heaviest of the quarks. It decays before hadrons are formed. It has not been explored in
 1280 DIS yet because the cross sections at HERA have been too small [72]. This is different at the LHeC where
 1281 top in charged currents is produced with a cross section of order 5 pb as can easily be estimated from the
 1282 LO calculation of Wb scattering. At the LHeC therefore, for the first time, one can study top quarks in
 1283 deep inelastic scattering. Positron (electron) proton charged current scattering provides a clear distinction
 1284 between top (anti-top) quark production in Wb to t fusion. The rates of this process are very high, as is
 1285 illustrated as a function of Q^2 in Fig. 4.14. Besides the rates and the charge tag it is notable that the
 1286 absence of pile-up and underlying event effects, characteristic for LHC measurements, provide comfortable
 1287 conditions for top quark physics at the LHeC.

1288 Due to its large mass, the top quark may very well play a role in the mechanism of electroweak symmetry
 1289 breaking (EWSB) both in the Standard Model as well as BSM physics. In the Standard Model, a precise
 1290 measurement of single top production in DIS (see for example [73]) is sensitive to the b quark content of
 1291 the proton. In a BSM EWSB scenario, the top quark will couple to the new physics sector and give rise to
 1292 anomalous production modes. The LHeC is expected to provide competitive sensitivity to flavor changing
 1293 neutral currents (FCNC) especially anomalous $tu\gamma$ and tuZ couplings.

1294 In the SM, top is produced dominantly in gluon-boson fusion at $x \lesssim 0.1$. In CC this leads to a top-beauty
 1295 final state while in NC this gives rise to pair produced top-antitop quarks, with a cross section of order 10

²However, in non-perturbative QCD there may occur differences, for example between the strange and anti-strange quark distributions, for which there are some hints in DIS neutrino nucleon di-muon data and corresponding QCD fit analyses, see below.




Figure 4.11: Simulation of the LHeC measurement of the interference structure function $xF_3^{\gamma^Z}$ from unpolarised $e^\pm p$ scattering with 10fb^{-1} luminosity per beam (blue, closed points) compared with the HERA II data as obtained by H1 (preliminary, green triangles) and by ZEUS (red squares) with about 0.15fb^{-1} luminosity per beam charge. The H1 x values are enlarged by 10% of their given values for clarity. One should notice that any significant deviation of sea from anti-quarks, see Eq. 4.27, would cause $xF_3^{\gamma^Z}$ at low x to not tend to zero. The top plot shows an average of $xF_3^{\gamma^Z}$ over Q^2 projected to a chosen Q^2 value of 1500GeV^2 exploiting the fact that the valence quarks are approximately independent of Q^2 . The lower plot is a zoom into the high x region.




Figure 4.12: Sum of the strange and anti-strange quark distribution as embedded in the NLO QCD fit sets as noted in the legend. Left: $s + \bar{s}$ versus Bjorken x at $Q^2 = 1.9 \text{ GeV}^2$; right: ratio of $s + \bar{s}$ of various PDF determinations to MSTW08. In the HERAPDF1.0 analysis (green) the strange quark distribution is assumed to be a fixed fraction of the down quark distribution which is conventionally assumed to have the same low x behaviour as the up quark distribution, which results in a small uncertainty of $s + \bar{s}$.




Figure 4.13: Simulated measurement of the strange quark density with the LHeC. Closed (open) points: tagging acceptance down to 10° (1°).




Figure 4.14: Charged current event rates for unpolarised e^-p (left) and e^+p (right) scattering in which \bar{t} and t is produced, respectively. Squares: inclusive CC rate vs. Q^2 ; triangles: charm production from W_s fusion; closed circles: top production from Wb fusion, estimated in a massless heavy flavour treatment. The rates are calculated for the default beam energies for 10 fb^{-1} of integrated luminosity. The errors are only statistical.

1296 times lower than in CC [72]. The electron beam charge distinguishes top and anti-top quark production in
 1297 CC. Thus a unique SM top physics program can be performed at the LHeC. This includes the consideration
 1298 of a top-quark density which at very high scales may be considered “light”. Recently a six-flavour variable
 1299 number scheme has been proposed [74], limited so far to leading order, in which it is predicted that the
 1300 top contribution to proton structure has an on-set much below the threshold of its production in a massless
 1301 scheme. This is illustrated in Fig. 4.15. Due to the very high Q^2 and statistics, the LHeC opens top quark
 PDF physics as a new field of research.




Figure 4.15: Parton momentum fractions as a function of Q^2 in a novel six-flavour variable number scheme (CFNS), solid curves, and in the massless scheme, dashed curves. At HERA one has observed beauty and charm production already below the conventional threshold of $\sqrt{Q^2} = m_Q$. The scheme of [74] suggests that there is a very early onset of top with measurable rates already at Q^2 values of only about one tenth of $m_t^2 \simeq 3 \cdot 10^4 \text{ GeV}^2$. With the LHeC the 'PDF' top physics is expected to commence.

1302

1303 Top, including anomalous couplings, has been considered for the CDR initially [75], based on some
 1304 ANOTOP and PYTHIA studies at generation level. With a detector now simulated in GEANT4 and in
 1305 the light of the first top results provided by the LHC experiments [76], as well as further prospects, the CC
 1306 and NC top physics at the LHeC deserves a more detailed study. This shall include an analysis about the
 1307 possible precision measurement of the top (and anti) top quark mass, which at the LHC may be determined
 1308 with an accuracy of 1 GeV and possibly be better in *ep*. Independently of whether one soon finds the SM
 1309 Higgs particle or it remains elusive, a high precision measurement of m_t is of prime importance.

4.3 Gluon Distribution

There are many fundamental reasons to understand the gluon distribution and the gluon interactions deeper than hitherto. Half of proton’s momentum is carried by gluons. Gluon self-interaction is responsible for the creation of baryonic mass. The Higgs particle, should it exist, is predominantly produced by gluon-gluon interactions. The rise of the gluon density towards low Bjorken x must be tamed for unitarity reasons: there is a new phase of hadronic matter to be discovered, in which gluons interact non-linearly while α_s is smaller than 1.

The LHeC, with precision and range of the most appropriate process (DIS) to explore $xg(x, Q^2)$, will pin down the gluon distribution much more accurately than could be done before. This primarily comes from the extension of range and precision in the measurement of $\partial F_2/\partial \ln Q^2$ which at small x is a measure of xg . The inclusive NC and CC measurements together provide a fully constrained data base for the determination of the quark distributions, which strongly constrains xg . The addition of precision measurements of F_L , discussed above and used in the small x chapter of this document, will unravel the saturating behaviour of xg . High precision measurements of boson-gluon fusion to heavy quark pairs will provide a complementary basis for understanding the gluon and its parton interactions.

The peculiarity of the gluon density is that it is defined and observable only in the context of a theory. Moreover, a crude data base and correspondingly rough fit ansatz can screen local deviations from an otherwise preferred smooth behaviour. It has yet not been settled whether there are gluonic “hot” spots in the proton or not. An example for possible surprises is provided by the analysis [49], in which Chebyshev polynomials have been used to parameterise the parton distributions in contrast to more conventional forms as in Eq. 4.24. Inspection of the gluon distribution obtained there reveals that it seems to be vanishing at $x \simeq 0.2$, i.e. at the point, in which scaling holds for $F_2(x, Q^2)$, which one might term a “cool” spot in the proton. Much more is still to be learned about the gluon, even when one is disregarding the yet to be explored role of the gluon in the theory of generalised and of unintegrated parton distributions.

The current knowledge of the gluon distribution in the proton is astonishingly limited as becomes clear from Fig. 4.16 showing the world determinations, and their uncertainties, of $xg(x, Q^2)$ at a typical initial, low scale, and from Fig. 4.17 expressing this information with ratios to one of the PDF sets. At low x and Q^2 most but not all of the PDF sets predict xg to be of valence like type with very large uncertainties for x below a few times 10^{-4} . At large x inclusive DIS has difficulties to pin down xg because the evolution of valence quarks as non-singlet quantities in QCD is not directly coupled to the gluon and very weak. Yet, even the information from jets, used in some of the PDF sets, does not lead to a clear understanding of xg at large x as is illustrated too. In fact, there is a tendency of obtaining a smaller xg at large x from HERA (I) data alone, see Fig. 4.16, as compared to the other determinations, albeit with large uncertainties.

The determination of xg is predicted to be radically improved with the LHeC precision data which extend up to lowest x near to 10^{-6} and large $x \geq 0.7$. The result of the QCD fit analysis for xg as described above in Sect. 4.2.1 is shown in Fig. 4.18. One observes a dramatic improvement at low x , as must be expected from the extension of the kinematic range, but also at high x , as is attributed to the high x precision measurements of the NC and CC cross sections. At $x = 0.7$, for example, the predicted experimental uncertainty of xg is 5%, which is about ten times more accurate than the results of MSTW08 or of the HERA fit indicate.

It is worth noting that the uncertainties considered here are restricted to those related to the genuine cross section measurement errors. There are further uncertainties, as discussed e.g. in [38], related to the difficulty of parameterising the PDFs and choosing the optimum solution in such a fit analysis. These will be also considerably reduced with the LHeC extended data base. Moreover, this analysis is not making use of the plethora of extra information on xg , which the LHeC will provide with F_L , $F_2^{c,b}$ and jet cross section measurements. The understanding of the gluon and its interactions is a primary task of the LHeC and undoubtedly a new horizon in strong interaction physics will be opened.




Figure 4.16: Gluon distribution and uncertainty bands, at $Q^2 = 1.9 \text{ GeV}^2$, for most of the available recent PDF determinations. Left: logarithmic x , right: linear x .




Figure 4.17: Ratios to MSTW08 of gluon distribution and uncertainty bands, at $Q^2 = 1.9 \text{ GeV}^2$, for most of the available recent PDF determinations. Left: logarithmic x , right: linear x .




Figure 4.18: Relative uncertainty of the gluon distribution at $Q^2 = 1.9 \text{ GeV}^2$, as resulting from an NLO QCD fit to HERA (I) alone (green, outer), HERA and BCDMS (crossed), HERA and LHC (light blue, crossed) and the LHeC added (blue, dark). Left: logarithmic x , right: linear x .

4.4 Prospects to Measure the Strong Coupling Constant

The precise knowledge of $\alpha_s(M_Z^2)$ is of instrumental importance for the correct prediction of the electro-weak gauge boson production cross sections and the Higgs boson cross section at Tevatron and the LHC [77]. Independently of such applications, the accurate determination of the coupling constants of the known fundamental forces is of importance in the search for their possible unification within a more fundamental theory. Among the coupling constants of the forces in the Standard Model, the strong coupling α_s exhibits the largest uncertainty, which is currently of the size of $\sim 1\%$. Any future improvement of this accuracy, along with the consolidation of the genuine central value, is one of the central issues of contemporary elementary particle physics. It demands deep experimental and theoretical efforts to obtain the required precision and especially to handle all essential systematic effects.

Experimentation at the LHeC will allow to measure the strong coupling constant $\alpha_s(M_Z^2)$ at much higher precision than hitherto, both from the scaling violations of the deep inelastic structure functions, as will be demonstrated below, and using ep multiple jet cross sections. For the final inclusion of jet data in global pdf analyses, both from ep and from hadron colliders, their description at NNLO is required. At the LHeC, similar to HERA, the measurement of the ep jet cross sections will form important data samples³ for the measurement of $\alpha_s(M_Z^2)$.

Subsequently, a brief account will be given on the status and the complexity of determining α_s in DIS, followed by a presentation of the study of the α_s measurement uncertainty with the inclusive NC and CC data from the LHeC.

4.4.1 Status of the DIS Measurements of α_s

During the last 35 years the strong coupling constant has been measured with increasing accuracy in lepton-nucleon scattering in various experiments at CERN, FERMILAB and DESY. The precision, which has been reached currently, requires the description of the deep-inelastic scattering structure functions at $O(\alpha_s^3)$ [36, 78, 79].

³These are presented below but have not been used in this document for a determination of the strong coupling constant. One knows of course that the use of jet data in DIS helps resolving the α_s - xg correlation, especially at large x , and consequently leads to a significant reduction of the uncertainty on the coupling constant. This, however, tends to also change the central value. The LHeC as will be shown below determines α_s to permille precision already in inclusive scattering. Comparison with precise values from jets can be expected to shed light on the yet unresolved question as to whether there is a theoretical or systematic effect which leads to different values in inclusive DIS and jets or not.

	$\alpha_s(M_Z^2)$	
BBG	$0.1134^{+0.0019}_{-0.0021}$	valence analysis, NNLO [80]
GRS	0.112	valence analysis, NNLO [81]
ABKM	0.1135 ± 0.0014	HQ: FFNS $N_f = 3$ [82]
ABKM	0.1129 ± 0.0014	HQ: BSMN-approach [82]
JR	0.1124 ± 0.0020	dynamical approach [83]
JR	0.1158 ± 0.0035	standard fit [83]
MSTW	0.1171 ± 0.0014	[84]
ABM	0.1147 ± 0.0012	FFNS, incl. combined H1/ZEUS data [85]
BBG	$0.1141^{+0.0020}_{-0.0022}$	valence analysis, N ³ LO [80]
world average	0.1184 ± 0.0007	[86]

Table 4.3: Recent NNLO and N³LO determinations of the strong coupling $\alpha_s(M_Z)$ in DIS world data analyses.

As is well known [87], though also questioned [88], the fits at NLO exhibit scale uncertainties for both the renormalization and factorization scales of $\Delta_{r,f}\alpha_s(M_Z^2) \sim 0.0050$, which are too large to cope with the experimental accuracy of $O(1\%)$. Therefore, NNLO analyses are mandatory. In Table 1 recent NNLO results are summarised. NNLO non-singlet data analyses have been performed in [80,81]. The analysis [80] is based on an experimental combination of flavor non-singlet data referring to $F_2^{p,d}(x, Q^2)$ for $x < 0.35$ and using the respective valence approximations for $x > 0.35$. The $\bar{d} - \bar{u}$ distributions and the $O(\alpha_s^2)$ heavy flavor corrections were accounted for. The analysis could be extended to N³LO effectively due to the dominance of the Wilson coefficient in this order [78] if compared to the anomalous dimension, cf. [80,89]. This analysis led to an increase of $\alpha_s(M_Z^2)$ by $+0.0007$ if compared to the NNLO value.

A combined singlet and non-singlet NNLO analysis based on the DIS world data, including the Drell-Yan and di-muon data, needed for a correct description of the sea-quark densities, was performed in [82]. In the fixed flavor number scheme (FFNS) the value of $\alpha_s(M_Z^2)$ is the same as in the non-singlet case [80]. The comparison between the FFNS and the BMSN scheme [90] for the description of the heavy flavor contributions induces a systematic uncertainty $\Delta\alpha_s(M_Z^2) = 0.0006$. One should note that also in the region of medium and lower values of x higher twist terms have to be accounted for within singlet analyses to cover data at lower values of Q^2 . Moreover, systematic errors quoted by the different experiments usually cannot be combined in quadrature with the statistical errors, but require a separate treatment. The NNLO analyses [83] are statistically compatible with the results of [80–82], while those of [84] yield a higher value.

In [85] the combined H1 and ZEUS data were accounted for in an NNLO analysis for the first time, which led to a shift of $+0.0012$. However, running quark mass effects [91] and the account of recent F_L data reduce this value again to the NNLO value given in [82]. Other recent NNLO analyses of precision data, as the measurement of $\alpha_s(M_Z^2)$ using thrust in high energy e^+e^- annihilation data [92,93], result in $\alpha_s(M_Z^2) = 0.1153 \pm 0.0017 \pm 0.0023$, resp. $0.1135 \pm 0.0011 \pm 0.0006$. Also the latter values are lower than the 2009 world average [86] based on NLO, NNLO and N³LO results.

4.4.2 Simulation of α_s Determination

Since nearly twenty years, the α_s determination in DIS is dominated by the most precise data from the BCDMS Collaboration, which hint to particularly low values of $\alpha_s(M_Z) \simeq 0.113$ [94] and exhibit some peculiar systematic error effects, when compared to the SLAC data and in the pQCD analyses as are discussed in [95,96]. Recent analyses seem to indicate that the influence of the BCDMS data is limited, which, however, is possible only when jet and nuclear fixed target data, extending to very low Q^2 , are used. Jet data sometimes tend to increase the value of α_s and certainly introduce extra theoretical problems connected with hadronisation effects in non-inclusive measurements. The use of fixed target data poses problems due to the uncertainty of corrections from higher twists and from nuclear effects, because what is required is an extraordinary precision if indeed one wants to unambiguously determine the strong coupling

case	cut [Q^2 in GeV^2]	α_s	\pm uncertainty	relative precision in %
HERA only (14p)	$Q^2 > 3.5$	0.11529	0.002238	1.94
HERA+jets (14p)	$Q^2 > 3.5$	0.12203	0.000995	0.82
LHeC only (14p)	$Q^2 > 3.5$	0.11680	0.000180	0.15
LHeC only (10p)	$Q^2 > 3.5$	0.11796	0.000199	0.17
LHeC only (14p)	$Q^2 > 20.$	0.11602	0.000292	0.25
LHeC+HERA (10p)	$Q^2 > 3.5$	0.11769	0.000132	0.11
LHeC+HERA (10p)	$Q^2 > 7.0$	0.11831	0.000238	0.20
LHeC+HERA (10p)	$Q^2 > 10.$	0.11839	0.000304	0.26

Table 4.4: Results of NLO QCD fits to HERA data (top, without and with jets) to the simulated LHeC data alone and to their combination. Here 10p or 14p denotes two different sets of parametrisations, one, with 10 parameters, the minimum parameter set used in [38] and the other one with four extra parameters added as has been done for the HERAPDF1.5 fit. The central values of the LHeC based results are obviously of no interest. The result quoted as relative accuracy includes all the statistical and the systematic error sources taking correlations as from the energy scale uncertainties into account.

constant in DIS. These problems have been discussed in detail above, and recently also in presentations by MSTW [97] and in a phenomenological study of the NNPDF group [98].

The question, of how large α_s is, remains puzzling, as has been discussed at a recent workshop [99] and requires a qualitatively and quantitatively new level of experimental input if one wants to progress in DIS.

Following the description of the simulated LHeC data (Sec. 4.1.4) and the QCD fit technique (Sec. 4.2.1) a dedicated study has been performed to estimate the accuracy of an α_s measurement with the LHeC. In the fits, for the central values of the LHeC data, the SM expectation is used smeared within the above uncertainties assuming their Gaussian distribution and taking into account correlated uncertainties as well.

The QCD fit results are summarised in Tab. 4.4. The first two lines give the result of a fit to the HERA I data. One observes that the inclusion of DIS jet data reduces the uncertainty, by a factor of two, but it also increases the central value by more than the uncertainty. The LHeC alone, in sole inclusive DIS, reaches values of better than 0.2% which when complemented with HERA data reaches a one per mille precision. From inspecting the results one finds that enlarging the Q^2 minimum still leads to an impressive precision, as of two per mille in the LHeC plus HERA case, at values which safely are in the DIS region. A Q^2 cut of for example 10 GeV^2 excludes also the lowest x region in which non-linear gluon interaction effects may require to change the evolution equations.

It is obvious that the sole experimental uncertainty, while impressive and promising indeed, is not the only problem in such a complex analysis. That requires all relevant parameters to be correspondingly tuned and understood. For example, the charm mass has to be known at the 10 MeV level to allow an α_s uncertainty of one per mille. The question of the uncertainty of the renormalisation and factorisation scales and their effect on α_s will be posed newly and higher than NNLO approximations of pQCD appear to be necessary. However, as mentioned above there already exist first N³LO results.

From an experimental and phenomenological point of view it appears extremely exciting that with the LHeC the α_s determination in DIS will be put on much more solid grounds, by the high precision and unprecedented kinematic range and but also by the resulting full constraints on the complete set of parton distributions, of light and heavy quarks, often by direct measurements, which hitherto had to be parameterised in an often crude way.

In view of the importance of this result, this analysis has been performed independently twice with separately generated NC and CC pseudodata under somewhat different assumption, albeit using the same simulation program, and using different versions of the QCD fit program. The results obtained before [100] are in good agreement with the numbers presented here.

1445 It is finally worth noting that there is an interest to measure α_s also based on non-singlet quantities. The
 1446 LHeC data provide high precision information both on the valence quarks and also on the proton-neutron
 1447 structure function difference. The accuracy expected from such measurements has not been estimated.

1448 4.5 Electron-Deuteron Scattering

1449 The structure of the deuteron and of the neutron are experimental unknowns over most of the kinematic
 1450 region of deep inelastic scattering. The last time lepton-deuteron scattering was measured occurred in the
 1451 fixed target μD experiments at CERN [101–103], while it had only been considered at HERA [104–106].
 1452 The LHeC so extends the range of these measurements by nearly four orders of magnitude in Q^2 and $1/x$,
 1453 which gives rise to a most exciting programme in QCD and in experimental physics.

1454 DIS and Partons

1455 Electron-deuteron scattering complements ep scattering in that it makes possible accurate measurements of
 1456 neutron structure in the new kinematic range accessed by the LHeC. In a collider configuration, in which
 1457 the hadron “target” has momentum much larger than the lepton probe, the spectator proton can be tagged
 1458 and its momentum measured with high resolution [104]. The resulting neutron structure function data are
 1459 then free of nuclear corrections which have plagued the interpretation of deuteron data, especially at larger
 1460 x , until now [107]. At low x , for the first time, since diffraction is related to shadowing, one will be able to
 1461 control the shadowing corrections ⁴ at the per cent level of accuracy as is also discussed below.

1462 Accurate en cross section measurements will resolve the quark flavour decomposition of the sea, i.e. via
 1463 isospin symmetry, unfolding \bar{u} from \bar{d} contributions to the rise of $F_2^p \propto x(4\bar{u} + \bar{d})$ towards low x , and, from
 1464 the full set of $e^\pm p$ and $e^\pm n$ charged current cross section data, a full unfolding of the flavour content of the
 1465 nucleon. For the study of the parton evolution with Q^2 , the measurement of $F_2^N = (F_2^p + F_2^n)/2$ is crucial
 1466 since it disentangles the evolution of the non-singlet and the singlet contributions. Down to x of about 10^{-3}
 1467 the W^+/W^- LHC data will also provide important information on the up-down quark distributions, albeit
 1468 at high Q^2 . With ep , eD and W^+/W^- data, the low x sea will be resolved for the first time, as all the low
 1469 x light quark information from HERA has been restricted to F_2^p only.

1470 A special interest in high precision neutron data at high Q^2 arises from the question of whether there
 1471 holds charge symmetry at the parton level, as has been discussed recently [109]. It may be studied in the
 1472 charged current ep and eD reactions, using both electrons and positrons, by measuring the asymmetry ratio

$$R^- = 2 \frac{W_2^{-D} - W_2^{+D}}{W_2^{-p} + W_2^{+p}}, \quad (4.30)$$

1473 which is directly sensitive to differences of up and down quark distributions in the proton and neutron,
 1474 respectively, which conventionally are assumed to be equal. With the prospect of directly measuring the
 1475 strange and anti-strange quark asymmetry in $e^\pm p$ CC scattering and of tagging the spectator proton and
 1476 thus eliminating the Fermi motion corrections in eD , such a measurement becomes feasible at the LHeC. It
 1477 requires high luminosity of order 1 fb^{-1} in eD scattering.

1478 QED corrections and photon PDFs of the proton and neutron

The LHeC offers the unique opportunity to include $\mathcal{O}(\alpha)$ corrections to parton evolution by measuring the
 photon parton distributions, $\gamma^{p,n}(x, Q^2)$, of the proton and the neutron. The most direct measurement is to
 observe wide-angle scattering of the photon by the electron beam. To be specific, the processes $eN \rightarrow e\gamma X$
 where the final state electron and photon are produced with equal and opposite large transverse momentum.

⁴For light nuclei, nuclear shadowing is dominated by the scattering off two nucleons. Since the probability of such double collisions is primarily determined by nuclear geometry, the A -dependence (though not the absolute value) of shadowing in light nuclei ($A \leq 12$) is not sensitive to details of the dynamics. Consequently, one can extract the nuclear shadowing correction for electron-deuteron scattering with a small uncertainty (well below 1 the electron-carbon and electrondeuteron cross sections [108]).




Figure 4.19: Uncertainty of the d/u ratio as a function of x from a QCD fit to H1 and BCDMS data (outer band, blue), to the LHeC proton data (middle band, yellow) and the combined simulated proton and deuteron data from the LHeC (inner band, green). In these fits the constraint of u and d to be the same at low x has been relaxed.

The subprocess is then simply QED Compton scattering, $e\gamma \rightarrow e\gamma$, and the cross sections are obtained by the convolution [?]

$$\frac{d\sigma(eN \rightarrow e\gamma X)}{dx^\gamma} = \gamma^{p,n}(x^\gamma, \mu^2) \hat{\sigma}(e\gamma \rightarrow e\gamma).$$

If the photon is produced with transverse energy E_T^γ and pseudorapidity η^γ in the LHeC laboratory frame, then

$$x^\gamma = \frac{E_T^\gamma E_e \exp(\eta^\gamma)}{2E_p E_e - E_T^\gamma E_p \exp(-\eta^\gamma)},$$

1479 where E_e and E_p are the energies of the electron and proton beams respectively. At HERA only a single
 1480 measurement of the $ep \rightarrow e\gamma X$ cross section was made (for $x_\gamma \sim 0.005$), with a large uncertainty [?]. Also, a
 1481 first estimate of $\gamma^{p,n}(x, Q^2)$ PDFs was performed in [?].

1482 Such measurements at the LHeC will be considerably more precise and will allow an investigation of
 1483 whether the $\mathcal{O}(\alpha)$ contributions have a sizeable effect, in comparison to the $\mathcal{O}(\alpha_s^2)$ NNLO QCD terms, in
 1484 a complete QED-modified DGLAP evolution, including QED terms in the input. Even if they are found
 1485 to have a small effect, they necessarily lead to a precise determination of the isospin violations $u^p \neq d^n$ and
 1486 $u^n \neq d^p$. Recall that it was these isospin violations, together with $s \neq \bar{s}$, which explained away the NuTeV
 1487 $\sin^2\theta_W$ anomaly. Of course, ideally, for precision physics we should anyway use QED-modified partons which
 1488 include $\gamma^{p,n}(x, Q^2)$.

1489 Hidden Colour

1490 In nuclear physics nuclei are simply the composites of nucleons. However, QCD provides a new perspective
 1491 [110, 111]. Six quarks in the fundamental 3_C representation of $SU(3)$ color can combine into five
 1492 different color-singlet combinations, only one of which corresponds to a proton and neutron. The deuteron
 1493 wavefunction is a proton-neutron bound state at large distances, but as the quark separation becomes

1494 smaller, QCD evolution due to gluon exchange introduces four other “hidden color” states into the deuteron
1495 wavefunction [112]. The normalization of the deuteron form factor observed at large Q^2 [113], as well as
1496 the presence of two mass scales in the scaling behavior of the reduced deuteron form factor [110], sug-
1497 gest sizable hidden-color Fock state contributions in the deuteron wavefunction [114]. The hidden-color
1498 states of the deuteron can be materialized at the hadron level as $\Delta^{++}(uuu)\Delta^-(ddd)$ and other novel quan-
1499 tum fluctuations of the deuteron. These dual hadronic components become important as one probes the
1500 deuteron at short distances, such as in exclusive reactions at large momentum transfer. For example, the
1501 ratio $d\sigma/dt(\gamma d \rightarrow \Delta^{++}\Delta^-)/d\sigma/dt(\gamma d \rightarrow np)$ is predicted to increase to a fixed ratio 2 : 5 with increasing
1502 transverse momentum p_T . Similarly, the Coulomb dissociation of the deuteron into various exclusive chan-
1503 nels $ed \rightarrow e' + pn, pp\pi^-, \Delta\Delta, \dots$ will have a changing composition as the final-state hadrons are probed
1504 at high transverse momentum, reflecting the onset of hidden-color degrees of freedom. The hidden color
1505 of the deuteron can be probed at the LHeC in electron deuteron collisions by studying reactions such as
1506 $\gamma^*d \rightarrow npX$ where the proton and neutron emerge in the target fragmentation region at high and opposite
1507 p_T . In principle, one can also study DIS reactions $ed \rightarrow e'X$ at very high Q^2 where $x > 1$. The production
1508 of high p_T anti-nuclei at the LHeC is also sensitive to hidden color-nuclear components.

1509 4.6 Charm and Beauty production

1510 4.6.1 Introduction and overview of expected highlights

1511 In this section it is shown that the measurements of charm and beauty production at LHeC provide high
1512 precision pQCD tests and are crucial to improve the knowledge of the proton structure. Historically the
1513 HERA charm and beauty studies extended by large amount results from previous fixed target experiments.
1514 This allowed a great advancement in the understanding of the dynamics of heavy quark production. The
1515 LHeC is the ideal machine for a further extension of similar historic importance because a higher centre
1516 of mass energy and a much larger integrated luminosity compared to HERA are available. On top of this
1517 the heavy flavour measurements will greatly benefit from the advanced detector design at LHeC with high
1518 precision (Silicon or similar) trackers all over the place. At HERA the tagging was restricted to central
1519 rapidities and effective efficiencies⁵ of only 0.1% (1%) for charm (beauty) were reached. At LHeC efficiencies
1520 of 10% (50%) should be possible for charm (beauty) and a large rapidity range can be covered from the very
1521 backward to the very forward regions. Before further elucidating the great measurement prospects the next
1522 paragraph introduces the main heavy quark production processes, the relevant pQCD theoretical schemes
1523 and some related open questions.

1524 In leading order, heavy quarks are produced in ep collisions via the Boson Gluon Fusion (BGF) process
1525 shown in Figure 4.20 on the left. This process provides direct access to the gluon density in the proton.
1526 BGF type processes dominate DIS scattering towards lower x , due to the large gluon density. In the high Q^2
1527 limit, the events with charm and beauty quarks are expected to account for $\sim 36\%$ and $\sim 9\%$ of the BGF
1528 processes and hence contribute significantly to inclusive DIS. On the theoretical side, the description of heavy
1529 quark production in the framework of perturbative QCD is complicated due to the presence of several large
1530 scales like the heavy quark masses, the transverse momentum p_T of the produced quarks and the momentum
1531 transfer Q^2 . Different calculation schemes have been developed to obtain predictions from pQCD. At low
1532 scales p_T (or Q^2) the fixed-flavour number scheme (FFNS) [115–117] is expected to be most appropriate
1533 where the quark masses are fully accounted for. At very high scales the NLO FFNS scheme predictions
1534 are expected to break down since large logarithms $\ln(p_T^2/m^2)$ are neglected that represent collinear gluon
1535 radiations from the heavy quark lines. These logarithms can be resummed to all orders in the alternative
1536 zero-mass variable flavour number (ZM-VFNS) [118–121] schemes. Here the charm and beauty quarks are
1537 treated above kinematic threshold as massless and appear also as active sea quarks in the proton, as depicted
1538 in figure 4.20 in the sketch on the right. Most widely used are nowadays the so-called generalised
1539 variable flavour number schemes (GM-VFNS) [122, 123]. These mixed schemes converge to the massive and

⁵The effective efficiency takes the background pollution into account. It is defined as the efficiency of an equivalent background free sample with the same signal precision as that obtained in the data.

1540 massless schemes at low and high kinematical scales, respectively, and apply a suitable interpolation in the
 1541 intermediate region. However, the exact modelling of the interpolation and in general the treatment of mass
 1542 dependent terms in the perturbation series are still a highly controversial issue among the various theory
 1543 groups. The different treatments have profound implications for global PDF fits and influence the fitted
 1544 densities of gluons and other quark flavours in the proton. This has direct consequences for many important
 1545 cross section predictions at LHC, for instance for Z and W production. The value of the mass of the charm
 1546 quark is also an important uncertainty in the predictions. In the determinations of m_c we have to distinguish
 1547 between the pole mass and the running mass. Fits to the present data have been performed using both as
 1548 free parameters. First, Ref. [?] used the pole mass as a free parameter and finds $m_c = 1.45$ GeV at NLO
 1549 and 1.26 GeV at NNLO. Alternatively, Ref. [91] use the running mass and finds $m_c(m_c) = 1.26$ GeV at
 1550 NLO and 1.01 GeV at NNLO. Typically the uncertainties quoted in these results are about $\pm 10\%$. After the
 1551 conversion from the pole to the running mass these values obtained by the two analyses are quite compatible
 1552 with each other. Clearly, LHeC data are required to improve the perturbative stability and to increase the
 1553 precision in our knowledge of m_c .

1554 The following main physics highlights are expected for heavy quark production measurements at LHeC:

- 1555 • *Massive vs Massless scheme:* At HERA the charm and beauty production data were found to be well
 1556 described by the NLO FFNS scheme calculations over the whole accessible phase space, up to the
 1557 highest p_T and Q^2 scales. An LHeC collider would allow to extend these studies to a much larger
 1558 kinematical phase space and thus to map the expected transition to the massless regime. Further
 1559 improvements in the determination of the charm quark mass and in the tuning of the GM-VFNS
 1560 schemes are possible and will have strong impacts on global PDF fits.
- 1561 • *Gluon density determination:* At HERA the recorded charm data provide already some interesting
 1562 sensitivity to the gluon density in the proton. However due to the small tagging efficiencies the
 1563 precisions are far below those obtained from the scaling violations of F_2 or those from jet data. At
 1564 LHeC this situation will highly improve and it will be possible to probe the gluon density via the BGF
 1565 process down to proton momentum fractions $x_g \leq 10^{-5}$, where it is currently not well known.

1566 At such low values of x_g a fixed-order perturbative computation becomes unreliable. It is then necessary
 1567 to resum both evolution equations and hard matrix elements. In fact, heavy quark production is the first
 1568 process for which all-order small x resummed terms were computed, and the high-energy factorization,




Figure 4.20: Left: Leading order Boson Gluon Fusion (BGF) diagram for charm and beauty production in ep -collisions. Right: Sketch of the leading order process in the massless approach where charm and beauty quarks are treated as massless sea quarks in the proton.

on which the whole of perturbative small- x resummation is based, was proven in this context [124,125]. Heavy quark production at the LHeC, with its high precision, energy and extended kinematic coverage, would thus provide an ideal setting for tests of high-energy factorization and small x resummation.

In this context it is also interesting to note that in the BGF process one can reach for charm production much smaller x_g values than with flavour inclusive jets since experimentally one can tag charm quarks with small transverse momenta. The studies of heavy flavour production sensitive to the gluon density can be done both in DIS and in the photoproduction kinematic regime.

- *Charm and beauty densities in the proton:* In general the measurements of the structure functions F_2^{cc} and F_2^{bb} are of highest interest for theoretical analyses of heavy flavour production in ep collisions. These structure functions are describing the parts of F_2 which are due to events with charm or beauty quarks in the final state. At sufficiently high $Q^2 \gg m_c^2, m_b^2$, the two structure functions can be directly related to effective densities of charm and beauty quarks in the proton, This can be used for predictions of many interesting processes at LHC with charm or beauty quarks in the initial state. For instance, as discussed in [126], in the minimal supersymmetric extension of the standard model the production of the neutral Higgs boson A is driven by $b\bar{b} \rightarrow A$ and for the calculation of this process the PDF uncertainties dominate over the theoretical uncertainties of the perturbative calculation. At HERA the measurements of F_2^{bb} barely reached the necessary high Q^2 regime and only with modest precision. Huge phase space extensions and precision improvements will be possible at LHeC.
- *Intrinsic charm component:* Since long it has been suggested [51,127–129] that the proton wave function might contain an intrinsic charm component $uudcc$. This would show up mainly at large $x > 0.1$. Unfortunately at HERA this large x region could not be studied mainly due to the limited detector acceptance in the forward region. Due to the even larger boost in the forward direction at LHeC the situation is also not easy there. However, with a forward tracking acceptance down to small polar angles there could be a chance to study this effect, in particular with the planned proton low energy runs.
- *Strange/antistrange densities:* Events with charm quarks in the final state can be also used as a tool for other purposes. The strange and antistrange quark densities in the proton can be analysed via the charge current process $sW \rightarrow c$, where the charm quark is tagged in the event. At HERA this was impossible due to the small cross sections, but at LHeC the cross sections for CC reactions are much higher and as noted before the other experimental conditions (luminosities, detector) will greatly improve. This leads to the first and precise measurement of both the strange and the anti-strange quark densities as is demonstrated in Sect. 4.2.
- *Electroweak physics:* There are intriguing possibilities for LHeC electroweak physics studies with charm and beauty quarks in the final state. For example one should be able to do a lepton beam polarisation asymmetry measurement for neutral current events, where the scattered quark is tagged as a beauty quark. This will provide direct access to the axial and vector couplings of the beauty quark to the Z boson. Similar measurements are possible for charm.

In summary the measurements of charm and beauty at an LHeC will be extremely useful for high precision pQCD tests, in particular for the understanding of the treatment of mass terms in pQCD, to improve the knowledge of the proton PDFs: directly for g, c, b, s, \bar{s} densities and indirectly also for u and d . Furthermore they provide a great potential for electroweak physics. At the time when the LHeC will be operated, the pQCD theory calculations are expected to have advanced considerably. In particular there is hope that full massive scheme NNLO calculations of order $o(\alpha_s^3)$ will be available by then. These will allow theory to data comparisons for heavy flavour production in ep collisions with unprecedented precision.

In the following subsections several dedicated simulation studies are presented which illustrate some of the expected highlights. First total cross sections are presented for various processes involving charm, beauty and also top quarks in the final state, showing that LHeC will be a genuine *multi heavy flavour factory*. Then the expected measurements of the structure functions F_2^{cc} and F_2^{bb} are discussed and compared to the

1617 existing HERA data. Next a study is presented of the possibility to measure intrinsic charm with dedicated
 1618 low proton energy runs. Finally predictions for differential charm hadron production cross sections in the
 1619 photoproduction kinematic regime are presented and compared to HERA, demonstrating the large phase
 1620 space extension.

1621 4.6.2 Total production cross sections for charm, beauty and top quarks

1622 This section presents total cross sections for various heavy quark processes at LHeC (with 7 TeV proton
 1623 beam energy) as a function of the lepton beam energy. Predictions are obtained for: charm and beauty
 1624 production in photoproduction and DIS, the charged current processes $sW \rightarrow c$ and $bW \rightarrow t$ and top quark
 1625 pair production in photoproduction and DIS. For comparison the flavour inclusive charged current total
 1626 cross section is also shown. Table 4.5 lists the generated processes, the used Monte Carlo generators and the
 selected parton distribution functions. The resulting cross sections are shown in Figure 4.21. For comparison

Process	Monte Carlo	PDF
Charm γp Beauty γp tt γp	PYTHIA6.4 [130]	CTEQ6L [131]
Charm DIS Beauty DIS tt DIS	RAPGAP3.1 [132]	CTEQ5L [133]
CC e^+p CC e^-p $sW \rightarrow c$ $\bar{s}W \rightarrow \bar{c}$ $bW \rightarrow t$ $\bar{b}W \rightarrow \bar{t}$	LEPTO6.5 [134]	CTEQ5L
tt DIS	RAPGAP 3.1	CTEQ5L

Table 4.5: Used generator programmes for the predictions of total cross sections at LHeC, shown in Figure 4.21. For all processes with top quarks the top mass was set to a value of 170 GeV. For both photoproduction (labelled as γp) and DIS only direct photon processes were generated and no reactions with resolved photons. The Q^2 ranges of the generated data are $Q^2 < 1 \text{ GeV}^2$ for photoproduction with PYTHIA, $Q^2 > 2 \text{ GeV}^2$ for DIS with RAPGAP and $Q^2 > 4 \text{ GeV}^2$ for the processes with LEPTO.

1627 also the predicted cross sections for the HERA collider (with 920 GeV proton energy) are presented. The
 1628 cross sections at LHeC are typically about one order of magnitude larger compared to HERA. Attached to
 1629 the right of the plot are the number of events that are produced per 10 fb^{-1} of integrated luminosity. For
 1630 instance for charm more than 10 billion events are expected in photoproduction and for beauty more than
 1631 100 million events. In DIS the numbers are typically a factor of five smaller. The strange and antistrange
 1632 densities can be probed with some hundred thousands of charged current events with charm in the final state.
 1633 The top quark production is dominated by the single production in the charged current reaction with beauty
 1634 in the initial state and about one hundred thousands tops and a similar number of antitops are expected.
 1635 In summary the LHeC will be the first ep collider which provides access to all quark flavours and with high
 1636 statistics.
 1637

Total cross sections in ep collisions




Figure 4.21: Total production cross section predictions for various heavy quark processes at the LHeC (with 7 TeV proton energy), as a function of the lepton beam energy. The following processes are covered: charm and beauty production in photoproduction ($Q^2 < 1 \text{ GeV}^2$) and DIS ($Q^2 > 2 \text{ GeV}^2$), the charged current processes $sW \rightarrow c$ and $bW \rightarrow t$ and top pair production in photoproduction and DIS. The flavour inclusive charged current total cross section is also shown. All predictions are taken from Monte Carlo simulations, some details can be found in Table 4.5. For comparison also the predicted cross sections at HERA (with 920 GeV proton energy) are shown.

1638 4.6.3 Charm and Beauty production in DIS

1639 This section presents predictions for charm and beauty production in neutral current DIS, for Q^2 values
 1640 of at least a few GeV^2 . The predictions are given for the structure functions $F_2^{c\bar{c}}$ and $F_2^{b\bar{b}}$ which denote
 1641 the contributions from charm and beauty events to F_2 . As explained in section 4.6.1 the two structure
 1642 functions are of large interest for theoretical analyses. Experimentally they are obtained by determining the

1643 total charm and beauty cross sections in two-dimensional bins of x and Q^2 . The LHeC projections shown
 1644 here were obtained with the Monte Carlo programme RAPGAP [132] which generates charm and beauty
 1645 production with massive leading order matrix elements supplemented by parton showers. The proton Parton
 1646 Distribution Function set CTEQ5L [133] were used and the heavy-quark masses were set to $m_c = 1.5$ GeV
 1647 and $m_b = 4.75$ GeV, respectively. In general at HERA the RAPGAP predictions are known to provide a
 1648 reasonable description of the measured charm and beauty DIS production data. The RAPGAP data were
 1649 generated for an LHeC collider scenario with 100 GeV electrons colliding with 7 TeV protons. The statistical
 1650 uncertainties have been evaluated such that they correspond to an integrated data luminosity of 10 fb^{-1} . All
 1651 studies were done at the parton level, hadronisation effects were not taken into account. Tagging efficiencies
 1652 of 10% for charm quarks and 50% for beauty quarks have been assumed, respectively. These efficiencies are
 1653 about a factor 100 larger compared to the effective efficiencies (including the dilution due to background
 1654 pollution) at HERA which may look surprisingly but is explainable. At HERA the charm quarks were tagged
 1655 either with full charm meson reconstruction or with inclusive secondary vertexing of charm hadron decays.
 1656 The first method suffered from very small branching ratios of suitable decay channels. The second technique
 1657 which was also used for the beauty tagging was affected by a large pollution from light quark background
 1658 events due to the limited detector capabilities to separate secondary from primary vertices. At LHeC one
 1659 can expect a much better secondary vertex identification and thus a very strong background reduction. It is
 1660 difficult to predict exactly how much background pollution will remain at LHeC, so for the purpose of this
 1661 simulation study it was completely neglected. Systematic uncertainties were also neglected for the studies
 1662 presented here. From the experiences at HERA the total systematic uncertainties for charm and beauty
 1663 cross sections in the visible ranges can be expected to be of similar size as the statistical ones.

1664 Figures 4.22 and 4.23 show the resulting RAPGAP predictions at LHeC for the structure functions F_2^{cc}
 1665 and F_2^{bb} , respectively, compared to recent measurements [135] from HERA. The data are shown as a function
 1666 of x for various Q^2 values. The Q^2 values were chosen such that they cover a large fraction of the specific
 1667 values for which HERA results are available. Some further values demonstrate the phase space extensions
 1668 at LHeC. The projected LHeC data are presented as points with error bars which (where visible) indicate
 1669 the estimated statistical uncertainties. For the open points the detector acceptance is assumed to cover the
 1670 whole polar angle range. For the grey shaded and black points events are only accepted if at least one charm
 1671 quark is found with polar angles $\theta_c > 2^0$ and $\theta_c > 10^0$, respectively. The selected results from HERA are
 1672 shown as triangles with error bars indicating the total uncertainty. The HERA F_2^{cc} results in Figure 4.22
 1673 are those of a recent weighted average [135] of almost all available measurements from H1 and ZEUS. In a
 1674 large part of the covered phase space these results are already rather accurate, with precisions between 5%
 1675 and 10%. The overlaid LHeC projections show a vast phase space increase to lower and larger x and also
 1676 to much higher Q^2 values. In the kinematic overlap region the expected statistical precisions at LHeC are
 1677 typically a factor ~ 40 better than at HERA which can be easily explained by the 20 times larger integrated
 1678 luminosity and the ~ 100 times better tagging efficiency. For the smaller x not covered by HERA the
 1679 precision even improves at LHeC due to the growing cross sections driven by the rise of the gluon density.
 1680 The best statistical precisions in the LHeC simulation are observed at smallest x values and small Q^2 and
 1681 reach down to 0.01%. As seen in the simulation (not shown here) the LHeC F_2^{cc} data provide access to the
 1682 the gluon density in the BGF process down to proton momentum fractions $x_g \sim 10^{-5}$. The LHeC data can
 1683 also provide an substantial extension to higher x compared to HERA where the measurements reached x
 1684 values of a few percent. As evident from the simulated points with different polar angle cuts this necessitates
 1685 an excellent forward tagging of charm quarks. In any case values of $x > 0.1$ should be accessible in the
 1686 medium and large Q^2 domain.

1687 Figure 4.23 show the RAPGAP predictions at LHeC for F_2^{bb} . Also shown are the results from the H1
 1688 analysis [136] based on inclusive secondary vertex tagging. Clearly these results and similar ones (not shown)
 1689 from ZEUS are not very precise, the typical total uncertainties are 20-50%. Again, the LHeC F_2^{bb} projections
 1690 demonstrate a vast phase space increase, similar as for charm. The best statistical precisions obtained at
 1691 LHeC for F_2^{bb} are seen in the simulation towards low x and small and medium Q^2 and reach down to 1
 1692 permille. The measurements at LHeC will enable a precision mapping of beauty production from kinematic
 1693 threshold to large Q^2 . In the context of the generalised variable flavour number schemes (GM-VFNS) this




Figure 4.22: F_2^{cc} projections for LHeC compared to HERA data [135], shown as a function of x for various Q^2 values. The expected LHeC results obtained with the RAPGAP MC simulation are shown as points with error bars representing the statistical uncertainties. The dashed lines are interpolating curves between the points. For the open points the detector acceptance is assumed to cover the whole polar angle range. For the grey shaded and black points events are only accepted if at least one charm quark is found with polar angles $\theta_c > 2^0$ and $\theta_c > 10^0$, respectively. For further details of the LHeC simulation see the main text. The combined HERA results from H1 and ZEUS are shown as triangles with error bars representing their total uncertainty.




Figure 4.23: F_2^{bb} projections for LHeC compared to HERA data [136] from H1, shown as a function of x for various Q^2 values. The expected LHeC results obtained with the RAPGAP MC simulation are shown as points with error bars representing the statistical uncertainties. The dashed lines are interpolating curves between the points. For the open points the detector acceptance is assumed to cover the whole polar angle range. For the grey shaded and black points events are only accepted if at least one beauty quark is found with polar angles $\theta_b > 2^\circ$ and $\theta_b > 10^\circ$, respectively. For further details of the LHeC simulation see the main text. The HERA results from H1 are shown as triangles with error bars representing their total uncertainty.

1694 will allow to study in detail the onset of the beauty quark density in the proton and to compare it to the
 1695 charm case. As mentioned in section 4.6.1, for high $Q^2 \gg m_b^2$ the F_2^{bb} results can be directly interpreted

1696 in terms of an effective beauty density in the proton. The measurement of this density is of large interest
 1697 because it can be used to predict beauty quark initiated processes at the LHC. As visible in the figure,
 1698 HERA covers only a small phase space in this region and with moderate precision. However, at LHeC the
 1699 prospects for measuring F_2^{bb} in this region are very good.

1700 4.6.4 Intrinsic Heavy Flavour

1701 It is usually assumed, for example in fits of parton distributions, that the charm and bottom quark distri-
 1702 butions in the proton structure only arise from gluon splitting $g \rightarrow Q\bar{Q}$. However, the proton light-front
 1703 wavefunction contains *ab initio* intrinsic heavy quark Fock state components such as $|uudc\bar{c}\rangle$ > [51,127–129].
 1704 Intrinsic charm and bottom may explain the origin of high x_F open-charm and open-bottom hadron pro-
 1705 duction, as well as the single and double J/ψ hadroproduction cross sections observed at high x_F . The
 1706 factorization-breaking nuclear $A^\alpha(x_F)$ dependence of hadronic J/ψ production cross sections may also be
 1707 explained.

1708 Some past phenomenological studies [137] have shown that at large x and low scale (just above charm
 1709 threshold) the intrinsic component might be several times larger than the intrinsically generated one. Ne-
 1710 glecting a significant large x intrinsic component may also lead to an incorrect assesment of the large x gluon
 1711 distribution.⁶

1712 The LHeC could establish the phenomenology of intrinsic heavy flavours, and in particular charm, at
 1713 large x . In addition to DIS measurements, one can test the charm (and bottom) distributions at the LHeC
 1714 by measuring reactions such as $\gamma p \rightarrow cX$ where the charm jet is produced at high p_T in the reaction $\gamma c \rightarrow cg$.

1715 In order to access the charm and bottom distributions towards larger Bjorken x , it is required to tag
 1716 heavy flavour production in the forward direction. As this is difficult in the asymmetric electron-proton
 1717 beam energy configuration such a measurement can favourably be done with a reduced proton beam energy.
 1718 Approximately, as may be derived from Eq. 12.8, the small hadronic scattering angle, θ_h , is obtained from
 1719 the relation, $\theta_h^2 \simeq 2\sqrt{Q^2}/E_p x$. Therefore a reduction by a factor of 7 of the proton beam energy E_p enhances
 1720 x by 7 at fixed Q^2 and θ_h . One also notices that large x is reached at fixed θ_h and E_p only at high Q^2 . The
 1721 attempt to access maximum x thus requires to find an optimum of high luminosity, to reach high Q^2 , and
 1722 low proton beam energy, to access large x . Fig. 4.24 shows a simulated measurement of the charm structure
 1723 function for $E_p = 1$ TeV and a luminosity of 1 fb^{-1} . The two curves illustrate the difference between CTEQ66
 1724 PDF sets with and without an intrinsic charm component, based on [137]. The actual amount of intrinsic
 1725 charm may be larger than in the CTEQ attempt, it may also be smaller. One so finds that a reliable detection
 1726 of an intrinsic heavy charm component at the LHeC may be possible, but will be a challenge for forward
 1727 charm detection and requires high luminosity. The result yet may be rewarding as it would have quite some
 1728 theoretical consequences as sketched above. It would be obtained in a region of high enough Q^2 to be able
 1729 to safely neglect any higher twist effects which may mimic such an observation at low energy experiments.

1730 4.6.5 D^* meson photoproduction study

1731 A study is presented of D^* meson photoproduction at the LHeC. It illustrates the large phasespace extension
 1732 to higher charm quark transverse momenta at LHeC compared to HERA; this will allow stringent tests of
 1733 the treatment of heavy quark mass dependent terms in pQCD. The study is based on NLO predictions in the
 1734 so-called general-mass variable-flavour-number scheme (GM-VFNS) [122,123] for 1-particle inclusive heavy-
 1735 meson production. Both direct and resolved photon contributions are taken into account. The cross section
 1736 for direct photoproduction is a convolution of the proton PDFs, the cross section for the hard scattering
 1737 process and the fragmentation functions FF for the transition of a parton to the observed heavy meson.

⁶In [138] a novel mechanism for inclusive and diffractive Higgs production $pp \rightarrow pHp$ is proposed, in which the Higgs boson carries a significant fraction of the projectile proton momentum. The production mechanism is based on the subprocess $(Q\bar{Q})g \rightarrow H$ where the $Q\bar{Q}$ in the $|uudQ\bar{Q}\rangle$ intrinsic heavy quark Fock state of the colliding proton has approximately 80% of the projectile protons momentum. A similar mechanism could produce the Higgs at large $x_F \sim 0.8$ in $\gamma p \rightarrow HX$ at the LHeC based on the mechanism $\gamma(Q\bar{Q}) \rightarrow H$ since the heavy quarks typically each carry light-cone momentum fractions $x \sim 0.4$ when they arise from the intrinsic heavy quark Fock states $|uudQ\bar{Q}\rangle$ of the proton.




Figure 4.24: Simulation of measurement of the charm structure function at large x , see text. The errors are statistical, taking tagging and background efficiencies into account. The tagging efficiency for charm quarks was assumed to be 10% and the amount of background was estimated to be $0.01 \cdot N_{ev}$, where N_{ev} refers to the total number of expected NC events in the respective (Q^2, x) bin. Solide line: CTEQ66c predictions, including an intrinsic charm component, dashed line: ordinary CTEQ6m.

1738 For the resolved contribution, an additional convolution with the photon PDFs has to be performed. For
 1739 the photoproduction predictions at the ep -colliders HERA and LHeC, the calculated photon proton cross
 1740 sections are convoluted with the photon flux using the Weizsaecker-Williams approximation.

1741 In the GM-VFNS approach the large logarithms $\ln(p_T^2/m^2)$, which appear due to the collinear mass
 1742 singularities in the initial and final state, are factorized into the PDFs and the FFs and summed by the
 1743 well known DGLAP evolution equations. The factorization is performed following the usual $\overline{\text{MS}}$ prescrip-
 1744 tion which guarantees the universality of both PDFs and FFs. At the same time, mass-dependent power
 1745 corrections are retained in the hard-scattering cross sections, as in the FFNS. For the photon PDF the
 1746 parametrization of Ref. [139] with the standard set of parameter values is used and for the proton PDF the
 1747 parametrization CTEQ6.5 [140] of the CTEQ group. For the FFs the set Belle/CLEO-GM of Ref. [141] is
 chosen. Various combinations of beam energies are studied. To compare with the situation at HERA, as




Figure 4.25: The p_T -differential cross section for the production of D^* mesons at LHeC for different beam energies integrated over rapidities $|\eta| \leq 2.5$, for the low- p_T range $5 \text{ GeV} \leq p_T \leq 20 \text{ GeV}$ (left) and for the high- p_T range $20 \text{ GeV} \leq p_T \leq 50 \text{ GeV}$ (right). The curves from bottom to top correspond to the combinations of beam energies as indicated in the figure. The lowest curves are showing the cross sections at the HERA beam energies.

1748 a reference, the values $E^p = 920 \text{ GeV}$ and $E^e = 27.5 \text{ GeV}$ for proton and electron energies, respectively,
 1749 are also included. Numerical results of the study are shown in Fig. 4.25. The higher centre-of-mass energies
 1750 available at the LHeC lead to a considerable increase of the cross sections as compared to HERA. Obvi-
 1751 ously one can expect an increase in the precision of corresponding measurements and much higher values of
 1752 p_T , as well as higher values of the rapidity η , will be accessible. Since theoretical predictions also become
 1753 more reliable at higher p_T , measurements of heavy quark production constitute a promising testing ground
 1754 for perturbative QCD. One may expect that the experimental information will contribute to an improved
 1755 determination of the (extrinsic and intrinsic) charm content of the proton and the charm fragmentation
 1756 functions.
 1757




Figure 4.26: Rapidity distribution of the cross section for the production of D^* mesons at LHeC for different beam energies integrated over the low- p_T range $5 \text{ GeV} \leq p_T \leq 20 \text{ GeV}$ (left) and the high- p_T range $20 \text{ GeV} \leq p_T \leq 50 \text{ GeV}$ (right). The curves from bottom to top correspond to the combinations of beam energies as indicated in the figure. The lowest curves are showing the cross sections at the HERA beam energies.

4.7 High p_t jets

4.7.1 Jets in ep

The study of the jet final states in lepton-proton collisions allows the determination of aspects of the nucleon structure which are not accessible in inclusive scattering. Moreover, jet production allows for probing predictions of QCD to a high accuracy. Depending on the virtuality of the exchanged photon, one distinguishes processes in photoproduction (quasi-real photon) and deep inelastic scattering.

The photoproduction cross section for di-jet final states can be studied in different kinematical regions, thereby covering a wide spectrum of physical phenomena, and probing the structure of the proton and the photon. Two-jet production in deep inelastic scattering is a particularly sensitive probe of the gluon distribution in the proton and of the strong coupling constant α_s . Both processes allow the study of potentially large enhancement effects in di-jet and multi-jet production.

Jet production in photoproduction proceeds via the direct processes, in which the quasi-real photon interacts as a point-like particle with the partons from the proton, and the resolved processes, in which the quasi-real photon interacts with the partons from the proton via its partonic constituents. The parton distributions in the quasi-real photon are constrained mostly from the study of processes at e^+e^- colliders, and are less well-determined than their counterparts in the proton. In both the direct and the resolved process, there are two jets in the final state at lowest-order QCD. The jet production cross section is given in QCD by the convolution of the flux of photons in the electron (usually estimated via the Weizacker-Williams

1776 approximation), the parton densities in the photon, the parton densities in the proton and the partonic cross
 1777 section (calculable in pQCD). Therefore, the measurements of jet cross sections in photoproduction provide
 1778 tests of perturbative QCD and the structure of the photon and the proton.

1779 Owing to the large size of the cross section, photoproduction of di-jets can be used for precision physics
 1780 in QCD. A measurement at LHeC could improve upon previous HERA results and enter into a much larger
 1781 kinematical region. In measurements made by the ZEUS collaboration, the available photon-proton centre-of-
 1782 mass energy ranged from 142 to 293 GeV, and jets of a transverse energy of up to 90 GeV could be observed.
 1783 By comparing the measured cross section with the theoretical prediction in NLO pQCD, a value of $\alpha_s(M_Z)$
 1784 was extracted with a total uncertainty of $\pm 3\%$ and the running of α_s was tested over a wide range of E_t^{jet} in
 1785 a single measurement. The limiting factors in this measurement were the theoretical uncertainty inherent
 1786 to the NLO prediction (which could be improved by computing NNLO corrections to jet photoproduction)
 and the experimental systematic uncertainty in the detector energy calibration.




Figure 4.27: PYTHIA predictions for photoproduction cross section at HERA and for three LHeC scenarios.

1787 Another motivation for making new photoproduction experiments is to improve the knowledge of the
 1788 parton content of the photon. At present, most information on the photon structure is inferred from the
 1789 collision of quasi-real photons with electrons at e^+e^- colliders, resulting in a decent determination of the
 1790 total (charge weighted) quark content of the quasi-real photon. Its gluonic content, and the quark flavour
 1791 decomposition are on the other hand only loosely constrained. Improvements to the photon structure are of
 1792 crucial importance to physics studies at a future linear e^+e^- collider like the ILC or CLIC. Such a collider,
 1793 operating far above the Z -boson resonance, will face a huge background from photon-photon collisions.
 1794 This background can be suppressed only to a certain extent by kinematical cuts. Consequently, accurate
 1795 predictions of it (which require an improved knowledge of the photon's parton content) are mandatory for
 1796 the reliable interpretation of hadronic final states at the ILC or CLIC. Several parametrizations of the parton
 1797 distributions in the photon are available. They differ especially in the gluon content of the photon. For the
 1798




Figure 4.28: Parton level predictions for the inclusive transverse energy distribution in photoproduction.

1799 studies presented here, the GRV-HO parametrization [142] is used as default.

1800 The photoproduction studies performed at LHeC were done for three different electron energy scenarios:
 1801 $E_e=50$, 100 and 150 GeV. In all cases, the proton energy was set to 7 TeV. PYTHIA MC samples of
 1802 resolved and direct processes were generated for these three scenarios. Jets were searched using the k_t -
 1803 cluster algorithm in the kinematic region of $0.1 < y < 0.9$ and $Q^2 < 1 \text{ GeV}^2$. Inclusive jet cross sections
 1804 were done for jets of $E_t^{\text{jet}} > 15 \text{ GeV}$ and $3 < \eta^{\text{jet}} < 3$. Figure 4.27 shows the PYTHIA MC cross sections
 1805 as functions of y for the three scenarios plus the corresponding cross section for the HERA regime. It can
 1806 be seen that the LHeC cross sections are one to two orders of magnitude larger than the cross section at
 1807 HERA.

1808 The full study was complemented with fixed-order QCD calculations at order α_s and α_s^2 using the
 1809 program by Klasen et al. [143] with the CTEQ6.1 sets for the proton PDFs, GRV-HO sets for the photon
 1810 PDFs, $\alpha_s(M_Z) = 0.119$ and the renormalisation and factorisation scales were set to the transverse energy of
 1811 each jet.

1812 Figure 4.28 shows the inclusive jet cross sections at parton level as functions of E_t^{jet} for the three en-
 1813 ergy scenarios for the PYTHIA res+dir (red dots), PYTHIA resolved (blue triangles) and PYTHIA direct
 1814 (pink triangles) together with the predictions from the NLO (solid curves) and LO (dashed curves) QCD
 1815 calculations. The calculations predict a sizeable rate for E_t^{jet} of at least up to 200 GeV. Resolved processes
 1816 dominate at low E_t^{jet} , but the direct processes become increasingly more important as E_t^{jet} increases. The
 1817 PYTHIA cross sections (which have been normalised to the NLO integrated cross section) agree well in shape
 1818 with the NLO calculations. Investigating the η^{jet} distribution, we find that resolved processes dominate in
 1819 the forward region, while direct processes produce more central jets.

1820 Figure 4.29 show the inclusive jet cross sections at parton level as functions of E_t^{jet} (on the left) and
 1821 η^{jet} (on the right) for the PYTHIA resolved+direct (symbols) and the predictions from the NLO (solid
 1822 curves) and LO (dashed curves) QCD calculations together for the three energy scenarios. For comparison,
 1823 the calculations for the HERA regime are also included. It is seen that the cross sections at fixed E_t^{jet}
 1824 increase and that the jets tend to go more backward as the collision energy increases. The much larger
 1825 photon-proton centre-of-mass energies that could be available at LHeC provide a much wider reach in E_t^{jet}




Figure 4.29: Dijet distributions in photoproduction as function of the jet transverse energy (left) and of the jet rapidity (right) for different LHeC energies compared to the HERA kinematic range.

1826 and η^{jet} compared to HERA.

1827 Hadronisation corrections for the cross sections shown were investigated. The corrections are predicted
 1828 to be quite small, below +5% for the chosen scenarios. Since the hadronisation corrections are very small,
 1829 the features observed at parton level remain unchanged.

1830 Inclusive-jet and dijet measurements in deep-inelastic scattering (DIS) have since long been a tool to
 1831 test concepts and predictions of perturbative QCD. Especially at HERA, jets in DIS have been thoroughly
 1832 studied, and the results have provided deep insights, giving for example precise values for the strong coupling
 1833 constant, α_s and providing constraints for the proton PDFs.

1834 An especially interesting region for such studies has been the regime of large (for HERA) Q^2 values of, for
 1835 example, $Q^2 > 125 \text{ GeV}^2$. In this regime, the theoretical uncertainties, especially those due to the unknown
 1836 effects of missing higher orders in the perturbative expansion, are found to be small. Recently, both the H1
 1837 and ZEUS collaborations have published measurements of inclusive-jet and dijet events in this kinematic
 1838 regime.

1839 An extension of such measurements to the LHeC is interesting for two reasons: First, the provided high
 1840 luminosity will allow measurements in already explored kinematic regions with still increased experimental
 1841 precision. Second, the extension in centre-of-mass energy, \sqrt{s} , and thus in boson virtuality, Q^2 , and in jet
 1842 transverse energy, $E_{T,jet}$, will potentially allow to study pQCD at even higher scales, extending the scale
 1843 reach for measurements of the strong coupling or the precision of the proton PDFs at large values of x .

1844 To explore the potential of such a measurement, we investigated DIS jet production for the following LHeC
 1845 scenario: proton beam energy 7 TeV, electron beam energy 70 GeV and integrated luminosity 10 fb^{-1} . The
 1846 study concentrates on the phase space of high boson virtualities Q^2 , with event selection cuts $100 < Q^2 < 500$
 1847 000 GeV^2 and $0.1 < y < 0.7$, where y is the inelasticity of the event. Jets are reconstructed using the k_T
 1848 clustering algorithm in the longitudinally invariant inclusive mode in the Breit reference frame. Jets were
 1849 selected by requiring: a jet pseudorapidity in the laboratory of $-2 < \eta_{lab} < 3$, a jet transverse energy in the
 1850 Breit frame of $E_{T,jet}^{\text{Breit}} > 20 \text{ GeV}$ for the inclusive-jet measurement and jet transverse energies in the Breit
 1851 frame of 25(20) GeV for the leading and the second-hardest jet in the case of the dijet selection.

1852 For inclusive-jet production we study cross sections in the indicated kinematic regime as functions of

1853 Q^2 , x_{Bj} , $E_{T,jet}^{Breit}$ and η_{jet}^{lab} , the jet pseudorapidity in the laboratory frame. For dijet production, studies are
 1854 presented as functions of Q^2 , the logarithm of the proton momentum fraction ξ , $\log_{10} \xi$, the invariant dijet
 1855 mass M_{jj} , the average transverse energy of the two jets in the Breit frame, $\overline{E_{T,jet}^{Breit}}$, and of half of the absolute
 1856 difference of the two jet pseudorapidities in the laboratory frame, η' .

1857 For the binning of the observables shown here, the statistical uncertainties for the indicated LHeC inte-
 1858 grated luminosity can mostly be neglected, even at the highest scales. The systematic uncertainties were
 1859 assumed to be dominated by the uncertainty on the jet energy scale which was assumed to be known to 1%
 1860 or 3% (both scenarios are indicated with different colours in the following plots), leading to typical effects on
 1861 the jet cross sections between 1 and 15%. A further relevant uncertainty is the acceptance correction that is
 1862 applied to the data which was assumed to be 3% for all observables.

1863 The theoretical calculations were performed with the DISENT program [144] using the CTEQ6.1 proton
 1864 PDFs [131, 145]. The central default squared renormalisation and factorisation scales were set to Q^2 . The
 1865 theory calculations for the LHeC scenario were corrected for the effects of hadronisation and Z^0 exchange
 1866 using Monte Carlo data samples simulated with the LEPTO program [134].

1867 Theoretical uncertainties were assessed by varying the renormalization scale up and down by a factor
 1868 2 (to estimate the potential effect of contributions beyond NLO QCD), by using the 40 error sets of the
 1869 CTEQ6.1 parton distribution functions, and by varying α_s using the CTEQ6AB PDF [146]. The dominant
 1870 theory uncertainty turned out to be due to the scale variations, resulting in effects of a few to up to 20%
 1871 or more, for example for low values of Q^2 or, for the case of the dijet measurement, for low values of the
 1872 invariant dijet mass, M_{jj} , or the logarithm of momentum fraction carried into the hard scattering, $\log_{10} \xi$.

1873 Note that for the inclusive-jet results also the predictions for a HERA scenario with almost the same
 1874 selection are shown in order to indicate the increased reach of the LHeC with respect to HERA. The only
 1875 change is a reduction in centre-of-mass energy to 318 GeV and a reduced Q^2 reach, $125 < Q^2 < 45\,000$ GeV².
 1876 The HERA predictions shown were also corrected for hadronisation effects and the effects of Z^0 exchange.

1877 Figure 4.30 shows the inclusive jet cross section as function of Q^2 and of the jet transverse energy
 1878 in the Breit frame, while Figure 4.31 shows the dijet cross section as function of Q^2 and of $\xi = x_{Bj}(1 +$
 1879 $M_{jj}^2/Q^2)$. The top parts of the figures show the predicted cross sections together with the expected statistical
 1880 and (uncorrelated) experimental systematic uncertainties as errors bars. The correlated jet energy scale
 1881 uncertainty is indicated as a coloured band; the inner, yellow band assumes an uncertainty of 1%, the outer,
 1882 blue band one of 3%. Also shown as a thin hashed area are the theoretical uncertainties; the width of the
 1883 band indicates the size of the combined theoretical uncertainty. In case of inclusive-jet production, also the
 1884 predictions for HERA are indicated as a thin line.

1885 The bottom parts of the figures show the relative uncertainties due to the jet energy scale (yellow band
 1886 for 1%, blue band for 3%), the statistical and uncorrelated experimental systematic uncertainties as inner
 1887 / outer error bars, and the combined theoretical uncertainties as hashed band. The inner part of this band
 1888 indicates the uncertainty due to the variation of the renormalisation scale.

1889 The inclusive-jet cross section as function of Q^2 shows a typical picture: In most region of the phase
 1890 space, the uncertainties are dominated by the theory uncertainties, and here mainly by the renormalisation
 1891 scale uncertainty. The typical size of experimental uncertainties is of the order of 10%, with larger values
 1892 in regions with low relevant scales — i.e. low invariant dijet masses, low jet transverse energies or low Q^2
 1893 values. The theoretical uncertainties are typically between 5 and 20%, with partially strong variations over
 1894 the typical range of the observable in question.

1895 A comparison with the HERA predictions for inclusive-jet production shows that the LHeC cross sections
 1896 is typically larger by 1 to 3 orders of magnitude. The dijet final state allows for a full reconstruction of the
 1897 partonic kinematics, and can thus be used to probe the parton distribution functions in Q^2 and ξ . It can
 1898 be seen that a measurement at LHeC covers a large kinematical range ranging down to $\xi \approx 10^{-3}$ and up to
 1899 $Q^2 = 10^5$ GeV². Potentially limiting factors in an extraction of parton distribution functions are especially
 1900 the jet energy scale uncertainty on the experimental side and missing higher order (NNLO) corrections on the
 1901 theory side. The jet energy scale uncertainty can be addressed by the detector design and by the experimental
 1902 setup of the measurement. NNLO corrections to dijet production in deep inelastic scattering are already
 1903 very much demanded by the precision of the HERA data, their calculation is currently in progress [147, 148].




Figure 4.30: Predicted LHeC results for inclusive jet production as function of Q^2 and of E_T in the Breit frame. Predictions for HERA results are also shown.

1904 In summary, jet final states in photoproduction and deep inelastic scattering at the LHeC promise a wide
 1905 spectrum of new results on the partonic structure of the photon and the proton. They allow for precision tests
 1906 of QCD by independent determinations of the strong coupling constant over a kinematical range typically
 1907 one to two orders of magnitude larger than what was accessible at HERA. The resulting parton distributions
 1908 will have a direct impact for precision predictions at the LHC and a future linear collider.

1909 4.7.2 Jets in γA

1910 For photoproduction in eA collisions, jets provide an abundant yield of high-energy probes of the nuclear
 1911 medium. The expected cross sections have been computed using the calculations in [149,150], for an electron
 1912 beam of 50 GeV colliding with the LHC beams. For the nuclear case the same integrated luminosity (2 fb^{-1})
 1913 was assumed per nucleon as for ep . Only jets with $E_{T,jet} > 20 \text{ GeV}$ are considered, and for the distribution
 1914 in $E_{T,jet}$ the pseudorapidity acceptance is $|\eta_{jet}| < 3.1$, corresponding to $5^\circ < \theta_{jet} < 175^\circ$ in polar angle. The
 1915 simulations use the Weizsäcker-Williams photon flux from the electron with the standard option in [149,150].
 1916 The chosen photon, proton and nuclear modified PDFs are taken from GRV-HO [151], CTEQ6.1M [145] and
 1917 EPS09 [152], respectively - see Subsec. 5.1.4 for explanations on the nuclear modifications of PDFs. The
 1918 renormalization and factorization scales are taken to be $\mu_R = \mu_F = \sum_{jets} E_{T,jet}/2$ and the inclusive k_T jet
 1919 algorithm [153] is used with $D = 1$. The statistical uncertainty in the computation (i.e. in the Monte Carlo
 1920 integration) is smaller than 10 % for all results shown. This large statistical uncertainty is reached only
 1921 for the largest $E_{T,jet}$, with much smaller uncertainties at lower values of E_T . No attempt has been made
 1922 to estimate the uncertainties due to the choices of photons flux, photon or proton parton densities, scales
 1923 or jet algorithms (see [154,155] for such considerations at HERA). The issues of background subtraction,
 1924 experimental efficiencies in the jet reconstruction or energy calibration have also yet to be addressed. The




Figure 4.31: Predicted LHeC results for dijet production as function of Q^2 and of ξ .

1925 only uncertainty studied thus far is that due to the nuclear parton densities, which is extracted in the EPS09
 1926 framework [152] using the Hessian method.

1927 The results are shown in Fig. 4.32. One observes that yields of around 10^3 jets per GeV are expected
 1928 with $E_{T,jet} \sim 95$ (80) GeV in ep (ePb), for $|\eta_{jet}| < 3.1$ and the considered integrated luminosity of 2 fb^{-1} per
 1929 nucleon. The effects of the nuclear modification of parton densities and their uncertainties are smaller than
 1930 10 %. The two-peak structure in the η_{jet} -plot results from the sum of the direct plus resolved contributions,
 1931 each of which produce a single maximum, located in opposite hemispheres. Positive η_{jet} values are dominated
 1932 by direct photon interactions, whereas negative η_{jet} values are dominated by contributions from resolved
 1933 photons.

1934 4.8 Total photoproduction cross section

1935 Due to the $1/Q^4$ propagator term, the LHeC ep cross section is dominated by very low Q^2 quasi-real photons.
 1936 With a knowledge of the effective photon flux [156], measurements in this kinematic region can be used to
 1937 obtain real photoproduction (γp) cross sections. The real photon has a dual nature, sometimes interacting
 1938 in a point-like manner and sometimes interacting through its effective partonic structure, resulting from
 1939 $\gamma \rightarrow q\bar{q}$ and higher multiplicity splittings well in advance of the target [157, 158], the details of which are
 1940 fundamental to the understanding of QCD evolution.

1941 The behaviour of the total photoproduction cross section at high energy is a topic of a major interest.
 1942 It is now firmly established experimentally that all hadronic cross sections rise with centre of mass energy
 1943 for large energies. The Froissart-Martin bound has been derived for hadronic probes. It therefore remains
 1944 to be seen whether this bound is applicable to γp scattering. For example in Refs. [159, 160] it has been
 1945 argued that the bound for real photon-hadron interactions should be of a different functional form, namely
 1946 $\ln^3 s$. This would imply that the universality of the asymptotic behaviour of hadronic cross sections does




Figure 4.32: Predictions for the inclusive jet distribution in photoproduction, differential in $E_{T\text{jet}}$ (left) and η_{jet} (right) for $e(50)+p(7000)$ (blue, top lines), $e(50)+\text{Pb}(2750)$ without nuclear modification of the parton densities (black lines), and $e(50)+\text{Pb}(2750)$ with EPS09 nuclear modification of the parton densities (red lines for the central value and bands for the uncertainty coming from the nuclear modification factors). See the text and the legends on the plots for further details of the calculations and kinematic cuts. In both plots, the axis on the left corresponds to the cross section in μb , while the axis on the right provides the number of jets expected for an integrated luminosity of 2 fb^{-1} per nucleon, per unit of $E_{T\text{jet}}$ (η_{jet}) in the plot on the left (right).

not hold. Therefore the measurement of the total photoproduction cross section at high energies will bring an important insight into the problems of universality of hadronic cross sections, unitarity constraints, the role of diffraction and the interface between hard and soft physics.

In Fig. 4.33, available data on the total cross section are shown [64, 161–163]⁷, together with a variety of models. More specifically, the dot-dashed black line labelled ‘FF model GRS’ is a minijet model [165], the yellow band labelled ‘Godbole et al.’ is an eikonalized minijet model with soft gluon resummation [165] with the band defined by different choices of the parameters in the model, the red solid line labelled ‘Block & Halzen’ is based on a low energy parametrization of resonances joined with Finite Energy Sum Rules and asymptotic $\ln^2 s$ -behaviour [166, 167], and the dashed blue line labelled ‘Aspen model’ is a QCD inspired model [168].

The theoretical predictions diverge at energies beyond those constrained by HERA data, where cross sections were obtained by tagging and measuring the energies of electrons scattered through very small angles in dedicated calorimeters located well down the beampipe in the outgoing electron direction [161, 162]. As discussed in Chapter 14, the most promising location for similar small angle electron detectors at the LHeC is in the region around 62 m from the interaction point, which could be used to tag scattered electrons in events with $Q^2 < 0.01 \text{ GeV}^2$ and $y \sim 0.3$. This naturally leads to measurements of the total photoproduction cross section at γp center-of-mass energies $W \sim 0.5\sqrt{s}$. The measurements would be strongly limited by systematics. In the absence of a detailed simulation of an LHeC detector these uncertainties are hard to estimate. For the simulated data in Fig. 4.33, uncertainties of 7% have been assumed, matching the precision of the H1 and ZEUS data. This would clearly be more than adequate to distinguish between many of the available models. The HERA uncertainties were dominated by the invisible contributions from diffractive channels in which the diffractive masses were too small to leave visible traces in the main detector. If detector acceptances to 1° are achieved at the LHeC, better precision is expected to be possible.

4.9 Electroweak physics

4.9.1 The context

Precision electroweak measurements at low energy have played a central role in establishing the Standard Model (SM) as the theory of fundamental interactions. More recently, measurements at LEP, SLD, and the Tevatron have confirmed the SM at the quantum level, verifying the existence of its higher-order loop contributions. The sensitivity of these contribution to virtual heavy particles has allowed for an estimate of the mass of the top quark prior to its actual discovery in 1995 by the CDF and DØ Collaborations. Now that the determination of the top mass at the Tevatron has become quite accurate, reaching the 1% level, and M_W is known with an error of 23 MeV, electroweak precision measurements imply significant constraints on the mass of the last missing piece of the SM, the Higgs boson. The current situation has been analysed for instance in [169, 170] taking into account the results of direct searches for the Higgs boson at LEP-2 and the Tevatron, which currently exclude a SM Higgs boson with mass lower than 114 GeV or in a narrow window around 160 GeV. At 95% CL, if the SM is correct, the Higgs boson must soon be found with mass below 155 GeV either at the Tevatron or at the LHC.

Electroweak precision measurements are also very effective in constraining the possible extensions of the SM. In general, the observed good quality of the SM fit disfavors new physics at an energy scale of $O(100 \text{ GeV})$ that modifies the Higgs mechanism in a drastic way. On the other hand, the fit does present a few interesting deviations at the level of $2\text{--}3\sigma$. There is a significant tension between the FB asymmetry of $Z \rightarrow b\bar{b}$ measured at LEP, which favors a heavy Higgs, and the LR asymmetry in $Z \rightarrow \ell\bar{\ell}$ and the W mass, which both favors a very light Higgs. Unfortunately, the present determination of M_H depends largely on these conflicting information, whose origin could be either statistical or rooted in new physics around the corner [171]. Another plausible $\sim 3\sigma$ hint of physics beyond the SM, without Higgs implications, is the discrepancy between the measured magnetic anomalous moment of the muon and its SM prediction [172].

⁷The recent results by ZEUS [164] refer only to the energy behavior of the cross section in the range $194 < W < 296 \text{ GeV}$, but do not provide absolute values.




Figure 4.33: Simulated LHeC measurements of the total photoproduction cross section with $E_e = 50$ GeV or $E_e = 100$ GeV, compared with previous data and a variety of models (see text for details). This is derived from a similar figure in [165].

1993 It is unlikely that operating experiments will change significantly the above picture of electroweak precision
1994 measurements. The Tevatron and LHC will marginally improve the current precision on the top mass
1995 and reach a combined 15 MeV uncertainty on M_W , while LHCb might be able to achieve an interesting ac-
1996 curacy in the measurement of $\sin^2 \theta_W$ [173,174]. Two experiments at Jefferson Lab, Q-weak [175] and (later)
1997 MOLLER [176], will measure the weak mixing angle from parity violation in ep and e^-e^- scattering at low
1998 energy: these are interesting measurements complementary to the existing ones; MOLLER, in particular,
1999 may eventually reach an accuracy similar to that of LEP. It is widely expected that either the Higgs boson
2000 or further new physics will be discovered at the LHC, if not both. This is the context in which precision
2001 electroweak measurements at LHeC are set.

2002 The electroweak measurements possible at LHeC are of the kind performed at HERA (see [177,178] for
2003 an overview). However, they will greatly benefit from the higher energy and larger luminosity, as well as from
2004 highly polarized lepton beams, and therefore also include processes, as single standard model or anomalous
2005 top quark production, which were impossible to study in ep before.

2006 A first class of measurements involves polarized charged currents (CC) only. They include a verification
2007 of the left-handedness of CC from the polarization dependence of the CC cross-section. At HERA this has
2008 led to a bound on possible right-handed currents, expressed in terms of the mass of a right-handed W_R boson
2009 that couples to quarks with the same strength as the SM one. While the HERA result, $M_{W_R} > 210$ GeV
2010 at 95% CL, can be significantly improved at the LHeC, low-energy flavour bounds and direct searches for
2011 W type new bosons at the LHC are more sensitive. It yet is interesting to verify the universality of space-
2012 and timelike interactions and thus to determine the propagator mass from the CC cross section through its
2013 Q^2 dependence, $\propto (M_W^2/(M_W^2 + Q^2))^2 \phi(x, Q^2)$. At the LHeC, the HERA W propagator mass uncertainty
2014 value may be improved by a factor of 10 to about 150 MeV.




Figure 4.34: Determination of the vector and axial NC couplings of the light quarks at LEP, CDF, HERA and LHeC. - plot to be updated.

4.9.2 Light Quark Weak Neutral Current Couplings

The LHeC will be able to measure the neutral current couplings of the light quarks at unprecedented precision. As can be seen in Fig. 4.34, LEP has been able to constrain only an ambiguous combination of them as the couplings enter as squares in pure weak NC reactions.

DIS experiments with polarized electron and positron beams can completely disentangle the vector and axial couplings of up and down type light quarks. As illustrated in Fig.4.34, the preliminary results by ZEUS and H1 have improved on the LEP determination in the case of the up quarks [178–180]. Very recent D0 results, obtained from the Z/γ^* forward-backward asymmetry in the electron channel, somewhat improve on HERA constraints [181]. However, a simultaneous determination of the four light quark couplings, based on a luminosity of 5 fb^{-1} with D0, still gives uncertainties of order $0.1 - 0.2$, which are an order of magnitude less precise than the expected DIS result at the LHeC.

The sensitivity of the LHeC to the light quark NC couplings has been studied with a QCD fit to the simulated data, in which the PDFs and the NC quark couplings are simultaneously determined. Here the electron couplings are fixed, as they are very precisely measured at LEP and SLD. The expected resolution for scenario D of LHeC is hardly visible on the scale of Fig. 4.34. A comparison among the various LHeC scenarios can be found in Fig. 4.35 The accuracy on the vector and axial vector couplings of the u , d quarks ranges, in the best possible scenario, between 1 and 4%, with an improvement wrt HERA by a factor 10 to 40. A better determination of the light quark NC couplings will particularly constrain New Physics models that modify significantly the light quark NC couplings, without affecting the well-measured lepton and heavy quark couplings. It is not easy to realize such an exotic scenario in a natural way, although family non-universal (leptophobic) Z' models (see for instance [182,183] and refs. therein), R-parity violating supersymmetry (see [184] for a review) and leptoquarks [185] can in principle succeed. LHeC could therefore accurately test a spectrum of interesting new physics models. A specific linear combination of the light quark NC vector couplings (v_u and v_d) might be measured at the per cent level by the QWeak Collaboration [175]. Their results, combined with existing precise measurements of Atomic Parity Violation and DIS, could




Figure 4.35: Determination of the vector and axial NC couplings of the light quarks at LHeC, comparison different scenarios.

2040 provide a percent determination of v_u and v_d [186] and test the same kind of models, but it will not probe
 2041 the axial quark couplings.

2042 4.9.3 Determination of the Weak Mixing Angle

2043 Cross Section Asymmetries and Ratios

2044 The LHeC is a unique facility for electroweak physics because of the very high luminosity, high measurement
 2045 precision and the extreme range of momentum transfer Q^2 . Fig. 4.36 illustrates the reach and the size of
 2046 the electroweak effects in NC scattering. Depending on the charge and polarisation of the electron beam,
 2047 the contributions from γZ interference and pure Z exchange become comparable to or even exceed the
 2048 photon exchange contribution, i.e. of F_2 , which has dominated hitherto all NC DIS measurements. With the
 2049 availability of two charge and two polarisation states, of neutral and charged current measurements, proton
 2050 and isoscalar targets, a unique menu becomes available for testing the electroweak theory. For example,
 2051 one can very precisely measure light quark weak neutral current couplings, discussed above. One can also
 2052 test the universality of $\gamma - g$ and $Z - g$ fusion by extracting the heavy quark (c , b) contributions from γZ
 2053 interference. A remarkable measurement illustrated in the following regards the energy dependence of the
 2054 weak mixing angle $\sin^2 \Theta$.

2055 Tests of the electroweak theory in DIS require to simultaneously control the parton distribution effects.
 2056 With the outstanding data base from the LHeC, joint QCD and electroweak fits become possible to high
 2057 orders perturbation theory. Cross section asymmetries and ratios can also be used to determine electroweak
 2058 parameters. Particularly useful examples are polarisation and charge asymmetries and also NC to CC cross
 2059 section ratios.

2060 In NC scattering, the polarisation asymmetry

$$A^\pm = \frac{1}{P_R - P_L} \cdot \frac{\sigma_{NC}^\pm(P_R) - \sigma_{NC}^\pm(P_L)}{\sigma_{NC}^\pm(P_R) + \sigma_{NC}^\pm(P_L)} \quad (4.31)$$




Figure 4.36: Simulated measurement of the neutral current DIS cross section (closed points) with statistical errors for 10 fb^{-1} shown as a function of Q^2 for different values of Bjorken x . The different curves represent the contributions of pure photon exchange (red), γZ interference (green) and pure Z exchange (blue) as prescribed in Eq. 4.5. Note the high precision of the reduced cross section measurement up to large x and Q^2 .

2061 served for the decisive confirmation of the left handed weak neutral current doublet structure as was predicted
 2062 by the GWS theory in 1979 [187]. The size of the electroweak asymmetries is given by the relative amount
 2063 of Z to photon exchange $O(10^{-4}Q^2/\text{GeV}^2)$, i.e. it becomes of order 1 at high Q^2 at the LHeC.

2064 To a good approximation the asymmetry measures the structure function ratio

$$A^\pm \simeq \mp \kappa_Z a_e \frac{F_2^{\gamma Z}}{(F_2 + \kappa_Z a_e Y_- x F_3^{\gamma Z} / Y_+)} \simeq \mp \kappa_Z a_e \frac{F_2^{\gamma Z}}{F_2}. \quad (4.32)$$

2065 Thus A^+ is expected to be about equal to $-A^-$ and to be only weakly dependent on the parton distributions.
 2066 The product of the axial coupling of the electron and the vector coupling of the quarks, inherent in $F_2^{\gamma Z}$,
 2067 determines the polarisation asymmetry to be parity violating. A measurement of A^\pm provides a unique and
 2068 precise measurement of the scale dependence of the weak mixing angle, as is discussed below (Sect. 4.9.3).
 2069 At large x the polarisation asymmetry provides an NC measurement of the d/u ratio of the valence quark
 2070 distributions, according to

$$A^\pm \simeq \pm \kappa \frac{1 + d_v/u_v}{4 + d_v/u_v}. \quad (4.33)$$

2071 Further asymmetries of NC cross sections have been discussed in [58].

2072 The neutral-to-charged current cross-section ratio

$$R^\pm = \frac{\sigma_{NC}^\pm}{\sigma_{CC}^\pm} = \frac{2}{(1 \pm P)\kappa_W^2} \cdot \frac{\sigma_{r,NC}^\pm}{\sigma_{r,CC}^\pm} \quad (4.34)$$

2073 is of interest for electroweak physics too as will be demonstrated below. At very high $Q^2 \gg M_Z^2$ and
 2074 neglecting terms in the NC part proportional to v_e it becomes approximately equal to

$$R^\pm \simeq \frac{2a_e^2}{(1 \pm P)\cos^2\theta} \cdot \frac{Y_+ F_2^Z - Y_- P x F_3^Z}{Y_+ W_2^\pm + Y_- x W_3^\pm} \quad (4.35)$$

2075 which reveals the striking similarity of the neutral and charged weak interactions at high energies. One may
 2076 further consider, for example, a quantity which is the eN analogon to the Paschos-Wolfenstein relation [188]
 2077 in νN scattering

$$A_{NCC} = \frac{\sigma_{NC}^+ - \sigma_{NC}^-}{\sigma_{CC}^+ - \sigma_{CC}^-}. \quad (4.36)$$

2078 The very high luminosity and Q^2 range of the LHeC as compared even to HERA will open a completely
 2079 new era of electroweak physics in DIS.

2080 Measurement of the Weak Mixing Angle

2081 Further tests of the SM at the quantum level and indirect searches for new physics require ultimate precision.
 2082 Such corrections occur in the factor $1 - \Delta r$, see Eq. 4.14, which depends on the top mass, logarithmically
 2083 on the Higgs mass and possibly on new, heavy particles. A measurement of the weak mixing angle, $\sin^2\theta$,
 2084 to 0.01 % precision should fix the Higgs mass to 5 % accuracy. The so far most precise measurements of
 2085 $\sin^2\theta$ have been performed at the Z pole in e^+e^- scattering, using the very high statistics, at LEP, and
 2086 in the case of the SLC, the large beam polarisation of 75 % too. The LHeC has the potential to measure
 2087 weak asymmetries and cross section ratios at, below and beyond the M_Z scale by precisely measuring their
 2088 dependence on $\sqrt{Q^2}$.

2089 The accuracy estimated for $\sin^2\theta$ depends on its definition. The electroweak theory has three independent
 2090 parameters. For the subsequent study, as in a similar study of H1 [179], the values of α and M_Z are fixed,
 2091 which are best known, M_Z to 0.002 %. For the estimate of the sensitivity to electroweak effects as the third
 2092 parameter here $\sin^2\theta$ is chosen, which is used, together with α and M_Z to calculate G and M_W and also

2093 occurs in the weak neutral current couplings⁸. This way both the NC and the CC cross sections are sensitive
 2094 to $\sin^2 \theta$. Equivalently one could have expressed all parameters using α , M_Z and M_W , and determine M_W .
 2095 Due to the relation $\sin^2 \theta = 1 - M_W^2/M_Z^2$, the error of such an indirect measurement of M_W is

$$\Delta M_W = \frac{M_W \delta \sin^2 \theta}{2 \sin^2 \theta}, \quad (4.37)$$

2096 i.e. a one permille accuracy on $\sin^2 \theta$ corresponds to $\Delta M_W = 40 \text{ MeV}$.

2097 A simulation is done of the NC and CC cross sections depending on the lepton beam charges and
 2098 polarisations based on the formulae presented above. This allows to build a variety of asymmetries and
 2099 cross section ratios and derive their sensitivity to the weak mixing angle. An example is illustrated in
 2100 Fig. 4.37. Here the polarisation asymmetry (left) and the NC/CC ratio (right) are calculated for different
 2101 values of $\sin^2 \Theta$ using two recent sets of leading order parton distributions, CTEQ6LL and MSTW08. The
 2102 measurement accuracy of $\sin^2 \Theta$ has a statistical, a polarisation, a systematic and a pdf uncertainty. One
 2103 derives that the statistical precision is about 0.1 % for the NC asymmetry A^- and even 0.05 % for the NC/CC
 2104 ratio R^- for e^-p scattering with an assumed polarisation of -0.8 and a luminosity of 10 fb^{-1} for default
 2105 beam energies.

2106 At this early stage of consideration one may not present a full error study. However, a few first con-
 2107 siderations are in order: The high luminosity and large Q^2 range move the electroweak physics at this ep
 2108 machine to the level of highest accuracy demands. Most of the systematic errors cancel in asymmetry and
 2109 ratio measurements. A 0.1 % electron energy scale uncertainty, as has been achieved with H1, for example,
 2110 translates at the LHeC to a 0.15 % change of A^- and a negligible change of R^- . This measurement samples
 2111 data in a region of very high cross section accuracy and can exclude the highest x region where uncertainties
 2112 grow like $1/(1-x)$. The desired level of polarisation measurement is obviously about a permille, which seems
 2113 to be possible as is discussed in the detector chapter.

2114 The requirements for A^- and R^- are different. The asymmetry A^- requires frequent changes of the
 2115 polarisation to control the time dependence of the measurement. It measures essentially a ratio of the
 2116 structure functions $F_2^{\gamma Z}/F_2$ and therefore it is rather insensitive to uncertainties related to the parton
 2117 distributions. In fact, one observes in Fig. 4.37 that the predictions of the two PDF sets considered differ
 2118 by less than the statistical uncertainty for A^- . The NC/CC ratio R is less sensitive to time drifts as the
 2119 NC and CC data are taken simultaneously. Its statistical power is highest, as had already been noticed for
 2120 HERA [189]. It yet is sensitive to the PDFs. For the two sets of PDFs considered here, an about two per cent
 2121 difference is calculated of the R^- ratios. This would spoil the extraction of $\sin^2 \Theta$. The high sensitivity of R
 2122 to the mixing angle can only be employed when the PDFs are much better known than so far. This, however,
 2123 is one of the major goals of the LHeC physics programme and large improvements are to be expected as
 2124 is discussed in Sec. 4.2. The potential of measuring $\sin^2 \Theta$ from NC/CC ratios is observed to be particular
 2125 striking. However, for the evaluation of the scale dependence of $\sin^2 \Theta$ below, the results derived from A^-
 2126 are used due to its much smaller PDF sensitivity.

2127 The mixing angle, similar to α_s , is predicted to vary strongly as a function of the scale μ , which in DIS
 2128 is precisely known and given as $\sqrt{Q^2}$. This dependence results from higher order loop effects as calculated
 2129 in [190]. Precise measurements to per mille uncertainty were performed at the Z pole by SLC and LEP
 2130 experiments. Recent low energy experiments have provided measurements of $\sin^2 \Theta$ at very low Q^2 as from
 2131 the parity violation asymmetry due to polarisation conjugation in Moeller scattering at $Q^2 = 0.026 \text{ GeV}^2$
 2132 by the E158 experiment. At scale values of about 5 GeV the NuTeV Collaboration has determined the
 2133 mixing angle which for some time created a substantial experimental and theoretical effort when it appeared
 2134 to be above the theoretical expectation by a few standard deviations. Explanations of this ‘‘anomaly’’
 2135 included variations of the strange quark density, effects from QED or nuclear corrections. An ultraprecise
 2136 measurement of $\sin^2 \Theta$ is envisaged, yet still at $\mu = M_Z$, if a new Z_0 factory was built.

2137 The current measurements are summarised in Fig. 4.38. The plot also contains projected $\sin^2 \Theta$ uncer-
 2138 tainty values from the LHeC, as listed in Table 4.6, which result from simulations of the parity violation

⁸An interesting test is also to fix α , M_Z and G and to determine derived electroweak parameters as M_W or $\sin^2 \Theta$ for precision consistency checks in the search for deviations from the SM. Such a study has not been undertaken so far for the LHeC.




Figure 4.37: Simulated measurement of the polarisation NC cross section asymmetry A^- (left), in per cent for $P = \pm 0.8$, and the ratio of neutral-to-charged current cross sections, $R = NC/CC$ (right), for $P = -0.8$, for different values of $\sin^2 \theta$. The errors are statistical for luminosities of 10 fb^{-1} per beam for polarised electron scattering for $E_e = 60 \text{ GeV}$ and the nominal 7 TeV proton beam. The closed (open) symbols show the simulation for the CTEQ6LL (MSTW08) leading order parameterisations of the parton distributions. The average Q^2 is 1300 GeV^2 for the NC asymmetry A^- , while for the ratio R the average CC Q^2 is about 9500 GeV^2 . Consequently, the mean x in NC and CC differs by a factor of 6, which is at the origin of the large differences in R between the two PDF set predictions.




Figure 4.38: Dependence of the weak mixing angle on the energy scale μ , taken from [64]. Four simulated points have been added based on the estimated measurement accuracy using the polarisation asymmetry A^- binned in intervals of $\sqrt{Q^2}$, see text.

Type	Q_1	P_1	Q_2	P_2	$\delta s(A_{12})$	$\delta s(R_1)$	$\delta s(R_2)$
e^- Polarisation Conjugation	-1.	-0.8	-1.	0.8	0.00026	0.00009	0.00024
e^+ Polarisation Conjugation	+1.	-0.8	+1.	0.8	0.00027	0.00040	0.00015
e^- Low P Conjugation	-1.	-0.4	-1.	0.4	0.00052	0.00010	0.00015
Charge Conjugation $P=0$	+1.	0.	-1.	0.	0.01600	0.00019	0.00012
Charge Conjugation $P=\mp 0.8$	+1.	-0.8	-1.	0.8	—	0.00040	0.00024
Charge Conjugation $P=\pm 0.8$	+1.	+0.8	-1.	-0.8	0.00790	0.00015	0.00009
e^- PC Low $Q^2 \sim 300 \text{ GeV}^2$	-1.	-0.8	-1.	0.8	0.00068	0.00029	0.00083
e^- PC Med $Q^2 \sim 1500 \text{ GeV}^2$	-1.	-0.8	-1.	0.8	0.00027	0.00012	0.00029
e^- PC High $Q^2 \sim 22000 \text{ GeV}^2$	-1.	-0.8	-1.	0.8	0.00044	0.00071	0.00055
e^- PC vHigh $Q^2 \sim 130000 \text{ GeV}^2$	-1.	-0.8	-1.	0.8	0.00170	0.00460	0.00200

Table 4.6: Estimated accuracies of the weak mixing angle, $\delta \sin^2 \Theta$ from simulated measurements of the NC asymmetry and the NC/CC cross section ratio for different beam charge and polarisation conditions.

2139 asymmetry A^- in polarised e^-p scattering, for scales between about 10 and 400 GeV. Due to the high statis-
2140 tics nature of the DIS NC process, the variation of $\sin^2 \Theta$ as a function of $\sqrt{Q^2}$ can be measured for a large
2141 range of $\sqrt{Q^2}$. At low scales the range limited by the sensitivity to the Z exchange effects and at high scales
2142 by the kinematic limit and luminosity. It may deserve a study to understand to how low values of Q^2 the
2143 asymmetry A^- can be determined in a meaningful measurement, which is related to time drifts, polarisation
2144 flip times etc. and likely can only be answered with real data. It is to be noted that previous and planned
2145 fixed target experiments measure this asymmetry at extremely small values of Q^2 as compared to the range
2146 of the LHeC.

2147 From the range considered here, with $Q^2 > 300 \text{ GeV}^2$, it can be concluded, see Fig. 4.38, that the expected
2148 measurement accuracy would lead to a decisive test of the scale dependence of $\sin^2 \Theta$.

2149 4.9.4 Summary

2150 This chapter has described how the LHeC can make an enormous improvement in our knowledge of the
2151 partonic structure of the proton and neutron, in precision, in kinematic scope and in the types of partons
2152 explored. The knowledge of PDFs is an essential ingredient in extracting physics from all high energy
2153 colliders involving nucleon beams. Up to now the global PDF analyses have been based on a pure DGLAP
2154 approach, which has been able to satisfactorily describe all DIS and related hard scattering data, albeit with
2155 limited precision and kinematic scope. However, the kinematic reach of the LHeC takes us into a low x
2156 domain where, for sure, the pure DGLAP approach will be insufficient and novel physics effects will be able
2157 to be explored. Our present understanding and expectations of this domain will be the subject of Chapter
2158 6.

Chapter 5

Physics at High Parton Densities

In Chapter 4, the opportunities offered by the LHeC to perform precision QCD studies were discussed in detail. Such studies have been done, until now, within the framework of standard, fixed-order perturbation theory and collinear factorization, which is valid when momentum scales are sufficiently hard and when the hadron can be described as a dilute set of partons. On the other hand, the parton densities extracted from HERA data exhibit a strong rise towards low x at fixed Q^2 , indicating that the proton becomes increasingly densely packed. There are also compelling theoretical reasons to believe that collinear factorization should break down with increasing energies and sizes of the hadron. The low x regime of proton structure thus represents an exciting and largely unexplored territory whose dynamics are those of a densely packed partonic system. From very general considerations, it is clear that the increasing parton densities cannot continue undamped throughout the region of LHeC sensitivity. Non-linear evolution must eventually become relevant and the parton densities must ‘saturate’. The LHeC offers the unique possibility of observing these highly non-perturbative dynamics at sufficiently large Q^2 values for weak coupling methods to be applied, suggesting the exciting possibility of a parton-level understanding of the collective properties of QCD. In this chapter we explore these possibilities in detail, addressing possible methods by which LHeC data might be used to establish the existence of this new high parton density regime of QCD and to explore its properties.

5.1 Physics at small x

5.1.1 High energy and density regime of QCD

Introduction

Quantum Chromodynamics [31] is the fundamental theory of strong interactions that has been extensively tested in the last 39 years. Still, many open questions remain to be solved. One of them, which can be addressed at high energies, is the transition between the regimes in which the strong coupling constant is either large or small - the so-called *strong* and *weak coupling* regimes. In the former, standard perturbation theory techniques are not applicable and exact analytical results are not yet within the reach of current knowledge. Therefore various models, *effective* theories, whose parameters cannot yet be derived from QCD, or numerical lattice computations, have to be employed. One example of such an effective theory which has been used through the years and actually predates QCD, is the Regge-Gribov [191–193] theory.

The weak coupling regime has been well tested in high-energy experiments through a selected class of measurements - often referred to as *hard processes* - where weak and strong coupling effects can be cleanly separated. There exists a well-defined theoretical concept which has been derived from first principles and probed in the weak coupling regime, namely the collinear factorization theorem (for a comprehensive review see [194] and references therein). It allows a separation of the cross sections involving hadrons into: (i) parts that can be computed within perturbation theory, corresponding to the cross section for parton scattering, and (ii) pieces which cannot be calculated using weak coupling techniques, but whose evolution

with momentum scales is still perturbative. The latter are universal, process-independent distributions that either characterize the partonic content of the hadron - *parton densities* on which we will mainly focus the discussion - or the eventual projection of partons onto hadrons. Together with their corresponding (DGLAP) linear evolution equations [33–35], they have been used to describe experimental data to a high accuracy. Examples include total DIS cross sections, the production of jets with large transverse momenta and final states with heavy quarks, see the analysis and discussion in Chapter 4.

In recent years high-energy experiments have become sensitive to kinematic regions in which the coupling is small but the factorization assumption may no longer be valid. We will refer to this region as the high parton density domain, or simply the dense regime. As an example, several HERA DIS measurements at small longitudinal momentum fractions x , where parton densities are large, indicate deviations from the behavior expected within the standard collinear factorization. Similarly, hadronic or nuclear collisions involving partons with small values of x may also show such deviations. At the same time, cross sections grow rapidly with decreasing x , so contributions from these regions dominate hadronic cross sections in sufficiently high-energy scattering. Experiments sensitive to this kinematic region thus provide a way to test QCD in the new regime where the parton densities become very large and highly novel effects are expected. As has historically always been the case for the exploration of parton densities, the most promising approach is lepton-nucleon scattering, exploiting the point-like, non-strongly interacting nature of the lepton probe to take ‘snapshots’ of the hadronic structure with deeply sub-femtoscopic resolution.

From a theoretical viewpoint, this situation offers both opportunities and challenges. The fact that, at small- x , there is no abrupt transition between the dilute and dense regimes, allows the use of techniques which, while still being weak coupling, go beyond those employed in the dilute limit. The usual parton multiplication processes have to be supplemented by processes in which partons recombine - thus adding non-linear terms to the evolution equations [195]. There are deep theoretical questions arising in this new dense partonic regime of QCD. At high energies the scattering amplitudes are close to the unitarity limit. Unitarity is violated when the linear regime is extrapolated to very high energies, so the dynamics of QCD beyond the linear dilute regime has to be such that unitarity is fulfilled. The generic expectations are that the dynamical mechanism responsible for the fulfillment of unitarity is that accountable for the taming of parton densities due to recombination effects - this phenomenon is generically referred to as parton *saturation*. Theoretical calculations [196–199] in the limit of high energies support these expectations. Furthermore, the experimental exploration of this transition region where the standard perturbative description based on collinear factorization and linear evolution equations requires large corrections, provides new possibilities of further understanding the strong coupling regime.

Deep inelastic lepton-hadron scattering has already been shown to address these questions in the most efficient manner. It provides the cleanest way of measuring the parton densities, including the small- x region in which the transition between the dilute and dense regimes of QCD should occur within the weak coupling region where calculations can be done. Approaching this transition region from the dilute side by decreasing x or by increasing the number of nucleons in the target, one should observe features which cannot be understood within the framework of linear QCD evolution equations but, using more elaborate tools (non-linear evolution equations) can still be analyzed in terms of weak coupling techniques. Within the standard framework of the leading-twist linear QCD evolution equations (DGLAP) the parton densities are predicted to rise at small x , and this rise has been seen very clearly at HERA. This rise should eventually be tamed by the novel, nonlinear effects leading to parton saturation. In hadron-hadron scattering it is a unitarity bound that limits the growth of the total cross sections as a function of energy. As a result, according to Froissart and Martin [200, 201], total cross sections are bounded according to

$$\sigma_{\text{tot}} \leq \text{const.} \ln^2 s/s_0, \quad (5.1)$$

where s_0 is a typical hadronic scale, and the dimensionful coefficient ‘const.’ is governed by the range of the strong interaction. This bound comes from two fundamental assumptions. The first is that the amplitude for the scattering at fixed value of impact parameter¹ is bounded by unity and the second is the

¹The impact parameter in a scattering process between two collinear particles is the perpendicular distance between the centres of the particles.

2241 finite range of the strong interaction. The bound on the amplitude has a simple physical interpretation in
 2242 terms of a situation where the probability for the interaction becomes very high, so the target (or more
 2243 precisely the interaction region) becomes completely absorptive. This situation is usually referred to as a
 2244 *black disk* regime. The description of this regime is very challenging theoretically and it is expected that
 2245 new phenomena will occur which are direct manifestations of a new state of QCD which is characterized
 2246 by a high parton density [56, 202]. The LHeC will uniquely offer the possibility of exploring the transition
 2247 towards this new state of dense QCD matter, as it can pursue a two-pronged approach: high center-of-mass
 2248 energy, extending the kinematic range to lower x , and the possibility of deep inelastic scattering off heavy
 2249 nuclei.

2250 In the rest of this introductory section, we will present different approaches that are currently under
 2251 discussion to describe the high-energy regime of QCD. We will recall the ideas that lead from linear evolution
 2252 equations to non-linear ones. On the former, we will discuss both cases in which the evolution equations
 2253 are computed within fixed-order perturbation theory (the DGLAP evolution equations) and where they
 2254 include some kind of resummation - thus going beyond any fixed order in the perturbative expansion in the
 2255 QCD coupling constant. The most famous example is the Balitsky-Fadin-Kuraev-Lipatov (BFKL) equation
 2256 [203, 204]. Concerning the latter, non-linear evolution leads to the phenomenon of saturation of partonic
 2257 densities in the hadron or nucleus. We will briefly review the realizations of saturation of parton densities
 2258 both at strong coupling and, mainly, at weak coupling. We will end by discussing the importance of diffractive
 2259 observables and of the use of nuclear targets for the investigation of the small- x behavior of the hadron or
 2260 nucleus wave function.

2261 Beyond DGLAP evolution

2262 In DIS the structure function $F_2(x, Q^2)$ is proportional to the total cross section σ_{tot} for the scattering of a
 2263 virtual photon on a hadron h , $\gamma^* h \rightarrow X$. The growth of F_2 at small x translates into the rise of σ_{tot} as a
 2264 function of the energy of the virtual photon-hadron system. Although the Froissart-Martin bound, derived
 2265 for hadron-hadron scattering, cannot be applied to a process involving a virtual photon, direct calculations
 2266 based on the evaluation of the QCD diagrams demonstrate unambiguously that, at small x , large corrections
 2267 exist and need to be resummed. These corrections suppress the leading-twist results and there is no doubt
 2268 that, for F_2 , the rise with $1/x$ predicted by DGLAP is modified by contributions which are not included
 2269 in the framework of leading-twist linear evolution equations. The corrections which become numerically
 2270 important in the small- x limit are also important for the restoration of the unitarity bound, as mentioned
 2271 previously. As a result of these modifications parton saturation is reached for sufficiently large energies or
 2272 small values of Bjorken- x .

2273 In deep inelastic electron-proton scattering, the virtual photon emitted by the incoming electron interacts
 2274 with partons inside the proton whose properties are specified by the kinematics of the photon. In particular,
 2275 the effective transverse size of the partons is (roughly) inversely proportional to the square root of the
 2276 virtuality of the photon, $\langle r_T^2 \rangle \sim 1/Q^2$. The deep inelastic cross section, parametrized through parton
 2277 densities, thus *counts* the numbers of quarks and gluons per unit of phase space. For sufficiently large
 2278 photon virtualities Q^2 and not too small x , the improved QCD parton model works well because the partons
 2279 forming the hadron, on the distance scale defined by the small photon, are in a dilute regime, and they
 2280 interact only weakly. This is a direct consequence of the property of asymptotic freedom, which makes the
 2281 strong coupling constant small. This diluteness condition is not satisfied if the density of partons increases.
 2282 This happens if either the number of partons increases (large structure function) or the interaction between
 2283 the partons becomes strong (large α_s). The former situation is realized at small x , the latter for small
 2284 photon virtuality Q^2 which sets the scale of the strong coupling $\alpha_s(Q^2)$. This simple qualitative argument
 2285 shows that corrections to the standard QCD parton picture can be described in terms of quarks and gluons
 2286 and their interactions as long as Q^2 is not too small ($\alpha_s(Q^2) \ll 1$) and the gluon density is large (small
 2287 x). Combining these two conditions one arrives at the picture shown in Fig. 5.1: there is an approximately
 2288 diagonal line in the $\ln Q^2 - \ln 1/x$ plane below which the parton distributions are dilute, and the standard
 2289 QCD parton picture applies. In this regime linear evolution equations provide the correct description of
 2290 parton dynamics. In the vicinity of the line, non-linear QCD corrections become important, and above the




Figure 5.1: Schematic view of the different regions for the parton densities in the $\ln Q^2 - \ln 1/x$ plane. See the text for comments.

2291 line partons are in a high-density state. The division between the two regimes is usually defined in terms of a
 2292 dynamically generated ‘saturation scale’, growing with decreasing x and, in the case of nuclei, with increasing
 2293 mass number. Within this picture one easily understands which type of corrections can be expected. Once
 2294 the density of gluons increases sufficiently, it becomes probable that, prior to their interaction with the
 2295 photon, gluons undergo recombination processes.

2296 Resummation at low x

2297 As already mentioned in Sec. 4.6.1, the generic challenges that the small- x region bears in QCD are inherently
 2298 related to the divergence of the gluon number density with decreasing values of x . It is well known that the
 2299 deep-inelastic partonic cross sections and parton splitting functions receive large corrections in the small- x
 2300 limit due to the presence of powers of $[\alpha_s \log x]$ to all orders in the perturbative expansion [33, 125, 203–205].
 2301 It thus suggests dramatic effects from logarithmically enhanced corrections, so the success of fixed order NLO
 2302 perturbation theory at HERA has been very hard to explain in regions where x becomes small. Recently,
 2303 hints have been found that indeed the quality of the DGLAP fits tends to deteriorate systematically in
 2304 the region of small x and Q^2 [38, 206]. Direct calculations at next-to-leading logarithmic accuracy in the
 2305 BFKL framework were performed [207, 208], and showed a slow convergence of the perturbative series in
 2306 the high-energy, or small- x regime. Therefore, generically one expects deviations from fixed-order DGLAP
 2307 evolution in the small- x and small- Q regime which call for a resummation of higher orders in perturbation
 2308 theory.

2309 Extensive analyses have been performed in the last few years [209–214], which indeed point to the
 2310 importance of resummation to all orders. Resummation should embody important constraints like kinematic
 2311 effects, momentum sum rules and running coupling effects.

2312 Several important questions arise here, such as the relation and interplay of the resummation and the
 2313 non-linear effects, and possibly the role of resummation in the transition between the perturbative and non-
 2314 perturbative regimes in QCD. Precise experimental measurements in extended kinematic regions are needed
 2315 to explore the deviations from standard DGLAP evolution and to quantify the role of the resummation at
 2316 small x .

2317 **Saturation in perturbative QCD**

2318 The original approach to implement unitarity and rescattering effects in high-energy hadron scattering was
 2319 developed by Gribov [56,192,215]. The models based on this non-perturbative Regge-Gribov framework are
 2320 quite successful in describing existing data on inclusive and diffractive ep and eA scattering (see e.g. [216,217]
 2321 and references therein). However, they lack solid theoretical foundations within QCD.

2322 On the other hand, attempts have been going on for the last 30 years to implement parton rescattering
 2323 or recombination² in perturbative QCD in order to describe its high-energy behaviour. In the pioneering
 2324 work in [195,218], a non-linear evolution equation in $\ln Q^2$ was proposed to provide the first correction to the
 2325 linear equations. A non-linear term appeared, which was proportional to the local density of color charges
 2326 seen by the probe (the virtual photon).

2327 An alternative, independent approach was developed in [219], where the amplitudes for diffractive pro-
 2328 cesses in the triple Regge limit were calculated. This resulted in the extraction of the triple Pomeron vertex
 2329 in QCD at small x , which is responsible for the non-linear term in the evolution equations.

2330 Later on these ideas were further developed to include all corrections enhanced by the local parton density,
 2331 to constitute what is called the Color Glass Condensate (CGC) [196–199,220–227] (see also the most recent
 2332 developments in [228–231]). The CGC provides a non-perturbative, but weak-coupling, realization of parton
 2333 saturation ideas within QCD. The linear limit of the basic CGC equation is the BFKL equation, which is
 2334 the linear evolution equation derived in the high-energy limit. As illustrated in Fig. 5.1, the evolution in the
 2335 $\ln Q^2 - \ln 1/x$ plane is driven by both linear equations: along $\ln Q^2$ for DGLAP and along $\ln 1/x$ for BFKL.

2336 The basic framework in which saturation ideas are discussed is illustrated in Fig. 5.2. One is considering
 2337 the hadron wave function at high energy. Its partonic components can be separated into those partons with
 2338 a large momentum fraction x and those with small x . The large- x components form dilute systems and
 2339 provide color sources for the corresponding small- x components. Due to multiple splittings of the small- x
 2340 gluons, a dense system is eventually formed. One can then construct within this formalism an evolution
 2341 equation for the gluon correlators in the hadron wave function which is a renormalization group equation
 2342 with respect to the rapidity separating large- and small- x partons. This renormalization procedure assumes
 2343 perturbative gluon emissions from the large- x partons which imply a redefinition of the source at each step
 2344 in rapidity.

2345 The mean field version of the CGC evolution equations, the Balitsky-Kovchegov (BK) equation [198,199],
 2346 provides a non-linear evolution equation for the so-called unintegrated gluon densities. These distributions,
 2347 unlike the standard integrated densities, contain the information about the transverse momenta of the
 2348 partons. They naturally appear in the theoretical formulations of small- x physics. A detailed description of
 2349 these distributions as well as the prospects of their precise determination at the LHeC through a variety of
 2350 processes are discussed in Subsec. 5.2.5.

2351 It turns out that the BK approach results in a gluon density which, for a fixed resolution of the probe,
 2352 is saturated for small longitudinal momentum fractions x , whereas at large values of x , the non-linear
 2353 term is negligible. The separation between these two limits is given by a dynamically generated saturation
 2354 momentum $Q_s(x)$ which increases with decreasing x (c.f. Fig. 5.1), and therefore saturation is determined
 2355 by the condition $Q < Q_s(x)$. Then, for large energies or small x , the system is in a dense regime of high
 2356 gluon fields (thus non-perturbative) but the typical gluon momentum, $\sim Q_s$, is large (thus the coupling
 2357 constant which determines gluon interactions is weak). The qualitative behavior of the saturation scale with
 2358 energy and nuclear size can be argued as follows. The transition from a dilute to a dense regime occurs
 2359 when the packing factor (in this case, the product of the density of gluons per unit transverse area times the
 2360 gluon-gluon cross section) becomes of order unity i.e.

$$\frac{A \times xg(x, Q_s^2)}{\pi A^{2/3}} \times \frac{\alpha_s(Q_s^2)}{Q_s^2} \sim 1 \implies Q_s^2 \sim A^{1/3} Q_0^2 \left(\frac{1}{x}\right)^\lambda, \quad (5.2)$$

2361 where the growth of the gluon density at small x in the dilute system has been approximated by a power
 2362 law, $xg(x, Q^2) \sim x^{-\lambda}$, logarithms are neglected and the nucleus is considered a simple superposition of

²Note that the rescattering and recombination concepts correspond to the same physical mechanism viewed in the rest frame and the infinite momentum frame of the hadron, respectively.




Figure 5.2: Illustration of saturation ideas. The hadron is moving very fast to the right, and its wave function contains many partonic components. Specifically, it includes partons with both large and small fractions of its longitudinal momentum x . The former are in a dilute regime and their lifetimes are very large, while the latter become densely packed due to multiple splitting and are short-lived (the length of the horizontal lines represents the extent of the lifetimes of the hadron fluctuations). Thus, the hard large x partons act as a frozen source for the dynamics of the soft ones. The photon with virtuality Q^2 is moving to the left and it constitutes a probe of the hadron wave function with a spatial resolution proportional to $1/Q$.

2363 independent nucleons. The exponent $\lambda \simeq 0.3$ can be derived from QCD and is broadly consistent with data
 2364 from HERA. The scale Q_0^2 can only be determined by experiment.

2365 The BK equation was derived under several simplifying assumptions such as the scattering of a dilute
 2366 projectile on a dense target, a large number of QCD colours and the absence of correlations in the target.
 2367 At present, the discussion is concentrated on how to overcome these difficulties [228, 232, 233]. Possible
 2368 phenomenological implications [234–236] are being considered. Also, the proposed relation between high-
 2369 energy QCD and Statistical Mechanics [232, 237] is under investigation.

2370 In the CGC formalism, the resummed terms are those enhanced by the energy and by the local density
 2371 of partons, and the saturation scale depends on the matter (colour charge) density at the impact parameter
 2372 probed by the virtual photon. For a nucleus, the nuclear size plays the role of an enhancement factor, see
 2373 Eq. (5.2), in a manner which is analogous to impact parameter scanning. Therefore, it is expected that when
 2374 scanning the impact parameter from the center to the periphery of the hadron at high energy, one should go
 2375 from a non-linear to a linear regime. Analogously, non-linear effects will become more important for large
 2376 nuclei than for smaller ones or for nucleons. Thus, a study of the variation of parton densities with impact
 2377 parameter and with the nuclear size, will provide an exacting test of our ideas on parton saturation.

2378 The importance of diffraction

2379 It was observed at HERA that a substantial fraction, about 10%, of deep inelastic interactions are diffractive
 2380 events of the type $ep \rightarrow eXp$. These are events in which the interacting proton stays intact, despite the
 2381 inelasticity of the interaction. Moreover, the proton appears well separated from the rest of the hadronic
 2382 final state X by a large rapidity gap. The events otherwise look similar to normal deep inelastic events.

2383 Diffraction has been extensively analyzed at HERA, with a variety of measurements as functions of x , Q^2
 2384 and the fractional proton energy loss $x_{\mathbb{P}}$, as well as more differential analyses which include the dependence




Figure 5.3: Illustration of the transverse profile of the hadron as explored by a virtual photon at impact parameter b .

2385 on the squared four-momentum transfer t . Physically, for the diffractive event to occur, there must be an
 2386 exchange of a coherent, color neutral cluster of partons (a quasi-particle) which leaves the interacting proton
 2387 intact. This color neutral cluster is often called the *pomeron*, and it can be characterised via a factorisation
 2388 theorem [238] by a set of partonic densities analogous to those for the proton or nucleus. At lowest order,
 2389 the QCD realisation of the pomeron is a pair of gluons [239, 240], which leads to enhanced sensitivity to
 2390 saturation phenomena compared to the single gluon exchange in the bulk of non-diffractive processes.

2391 There are strong theoretical indications that diffraction is closely linked with the phenomenon of partonic
 2392 saturation. From a wide range of calculations, mostly based on the so-called dipole model, see for example
 2393 [241, 242], it is known that diffractive DIS events involve softer effective scales than non-diffractive events
 2394 at the same Q^2 . Thus, the exploration of diffractive phenomena offers a unique window to analyze both
 2395 the relevance of non-linear effects and the transition between perturbative and non-perturbative dynamics
 2396 in QCD.

2397 The LHeC will provide a widely extended kinematic coverage for diffractive events. In addition to the
 2398 enhanced sensitivity to saturation effects through the basic 2-gluon exchange, their study at the LHeC will
 2399 allow the extraction of diffractive parton densities for a larger range in Q^2 than at HERA, and will thus
 2400 provide crucial tests of parton dynamics and flavour decomposition in diffraction as well as of the factorization
 2401 theorems. The high energy involved also enables the production of diffractive states with large masses which
 2402 could include W and Z bosons as well as states with heavy flavours or even exotic states with quantum
 2403 numbers 1^- .

2404 Of particular importance is the exclusive diffractive production of vector mesons, for which differential
 2405 measurements as a function of squared four-momentum transfer, t , are most easily performed. It has been
 2406 demonstrated that in this case, information about the momentum transfer of the cross section can be trans-
 2407 lated into the dependence of the scattering amplitude on impact parameter. As a result, a profile in impact
 2408 parameter of the interaction region, illustrated in Fig. 5.3, can be extracted. The precise determination of
 2409 the dynamics governing the high parton density regime requires a detailed picture of the spatial distribu-
 2410 tion, in impact parameter space, of partons in the interaction region. By selecting small impact parameter
 2411 values (large t), it is possible to probe the regions of highest parton density, where the onset of saturation
 2412 phenomena should most readily occur. One can then extract the value of the saturation scale as a function
 2413 of energy and impact parameter.

2414 Even less differential measurements of the diffractive production of vector mesons can provide valuable
 2415 information about parton dynamics and non-linear effects. For example, the measurement of the energy
 2416 dependence of the diffractive cross section for the photoproduction of J/ψ mesons at the LHeC can distinguish
 2417 between different scenarios for parton evolution and thus explore parton saturation to a greater accuracy
 2418 than ever before.

2419 The importance of nuclei

2420 Studying lepton-nucleus collisions is an important ingredient of the LHeC low x programme for several
2421 reasons. Most obviously, as discussed in sections 5.1.4 and 5.2.2, the nuclear structure functions and parton
2422 densities are basically unknown at small x . This is an issue which is becoming increasingly problematic in
2423 interpreting ultra-relativistic heavy ion collision data from RHIC and the LHC, as discussed in Subsec. 5.1.4.
2424 The main reason for this lack of knowledge comes from the rather small area in the $\ln Q^2 - \ln 1/x$ plane
2425 covered by presently available experimental data, see Fig. 5.4. Current theoretical and phenomenological
2426 analyses [243] point to the importance of non-linear dynamics in DIS off nuclei at small and moderate Q^2 and
2427 small x , which needs to be tested experimentally. In this respect, a relation exists, as reviewed in Sec. 5.2.4,
2428 between diffraction in lepton-proton collisions and the small- x behavior of nuclear structure functions. This
2429 relation relies on only basic properties of Quantum Field Theory and its verification provides stringent tests
2430 of our understanding of the strong interaction.

2431 Non-linear effects in parton evolution are enhanced by increasing the density of partons. Such an increase
2432 can be achieved (see Fig. 5.5) either by increasing the energy of the collision (decreasing x), or by increasing
2433 the nuclear mass number A . The latter can be accomplished by either using the largest nuclei possible, or
2434 by selecting subsets of collisions with small impact parameters b (i.e. more central collisions) between the
2435 relatively light nuclei and the virtual photon, such that more nucleons are involved. The ideal situation
2436 would be to map out the dependence of the saturation scale on x , b and A as fully as possible (see Eq. (5.2)).
2437 This is a key observable in formulations which resum multiple interactions and result in parton saturation.
2438 As such it must be checked in experiment in order to clearly settle the mechanism underlying non-linear
2439 parton dynamics.

2440 Beyond inclusive variables, measurements of diffractive observables in lepton scattering from nuclei have
2441 never been obtained previously and the uncertainties in current theoretical predictions are very large. Inclu-
2442 sive and exclusive diffraction measurements in lepton-nucleus collisions at the LHeC will offer a completely
2443 new testing ground for our ideas on nuclear structure at small x and on parton saturation and non-linear
2444 dynamics in QCD.

2445 5.1.2 Status following HERA data

2446 As discussed in the previous Section, in the low- x region a high parton density can be achieved in DIS
2447 and various novel phenomena are predicted. Ultimately, unitarity constraints become important and a
2448 ‘black disk’ limit is approached [215], in which the cross section reaches the geometrical bound given by the
2449 transverse proton or nucleus size. When α_s is small enough for quarks and gluons to be the right degrees of
2450 freedom, parton saturation effects are therefore expected to occur within the theoretically controllable weak
2451 coupling regime. In this small- x limit, many striking observable effects are predicted, such as Q^2 dependences
2452 of the cross sections which differ fundamentally from the usual logarithmic variations, and diffractive cross
2453 sections approaching 50% of the total [244]. This fairly good phenomenological understanding of the onset of
2454 unitarity effects is, unfortunately, not very quantitative. In particular, the precise location of the saturation
2455 scale line in the DIS kinematic plane (see Fig. 5.1) is to be determined experimentally. The search for parton
2456 saturation effects has therefore been a major issue throughout the lifetime of the HERA project.

2457 Although no conclusive saturation signals have been observed in parton density fits to existing HERA
2458 data, various hints have been obtained, for example, by studying the change in fit quality as low- x and Q^2
2459 data are progressively omitted, in the NNPDF [206, 245] and HERAPDF [38] analyses (see below).

2460 A more common approach is to fit the data to dipole models [241, 242, 246, 247], which are applicable at
2461 very low Q^2 values beyond the range in which quarks and gluons can be considered to be good degrees of
2462 freedom. The typical conclusion [247] is that HERA data in the perturbative regime exhibit at best weak
2463 evidence for saturation. However, when data in the $Q^2 < 1 \text{ GeV}^2$ region are included, models which include
2464 saturation effects are quite successful in the description of the wide variety of experimental data.

2465 The ‘geometric scaling’ [248] feature of the HERA data (Fig. 5.6left) reveals that, to a good approxima-
2466 tion, the low- x cross section is a function of a single combined variable $\tau = Q^2/Q_s^2(x)$, where $Q_s^2 = Q_0^2 x^{-\lambda}$ is
2467 the saturation scale, see Eq. (5.2). This parameterisation works well for scattering off both protons and ions,




Figure 5.4: Kinematical coverage of the LHeC in the $\ln Q^2 - \ln 1/x$ plane for nuclear beams, compared with existing nuclear DIS and Drell-Yan experiments.




Figure 5.5: Schematic view of the different regions for the parton densities in the $\ln 1/x - \ln A$ plane, for fixed Q^2 . Lines of constant occupancy of the hadron are parallel to the diagonal line shown. See the text for further comments.

2468 as shown in Fig. 5.6right [248,249]. Geometric scaling is observed not only for the total γ^*p cross section,
 2469 but also for other, more exclusive observables in γ^*p collisions [250,251] and even in hadron production in
 2470 proton-proton collisions at the LHC [252] and nucleus-nucleus collisions at RHIC [249]. This feature supports
 2471 the view (Subsec. 5.1.1) of the cross section as being invariant along lines of constant ‘gluon occupancy’.
 2472 When viewed in detail (Fig. 5.6), there is a change in behaviour in the geometric scaling plot near $\tau = 1$,
 2473 which has been interpreted as a transition to the saturation region shown in Fig. 5.1. However, data with
 2474 $\tau < 1$ exist only at very low, non-perturbative, Q^2 values to date, precluding a partonic interpretation. Also,
 2475 the fact that the scaling extends to large values of τ which characterize the dilute regime, has prompted
 2476 theoretical explanations of this phenomenon which do not invoke the physics of saturation [253].

2477 Dipole models

2478 As mentioned previously, one of the interesting observations at HERA is the success of the description of
 2479 many aspects of the experimental data within the framework of the so-called dipole picture [196,254,255] with
 2480 models that include unitarisation or saturation effects [256,257]. These models are based on the assumption
 2481 that the relevant degrees of freedom at high energy are colour dipoles. Dipole models in DIS are closely
 2482 related to the Good-Walker picture [258] previously developed for soft processes in hadron-hadron collisions.
 2483 In DIS, dipoles are shown to be the eigenstates of high-energy scattering in QCD, and the photon wave
 2484 function can be expanded onto the dipole basis.

2485 The dipole factorization for the inclusive cross section in DIS is illustrated in Fig. 5.7. It differs from
 2486 the usual picture of the virtual photon probing the parton density of the target in that here the partonic
 2487 structure of the probed hadron is not evident. Instead, one chooses a particular Lorentz frame where the
 2488 photon fluctuates into a quark-antiquark pair with a transverse separation r and at impact parameter b with
 2489 respect to the target. For sufficiently small $x \ll (2m_N R_h)^{-1}$, with m_N the nucleon mass and R_h the hadron
 2490 or nuclear radius, the lifetime of the $q\bar{q}$ fluctuation is much longer than the typical time for interaction with
 2491 the target. The interaction of the $q\bar{q}$ dipole with the hadron or nucleus is then described by a scattering
 2492 matrix $S(r, b; x)$ such that $|S(r, b; x)| < 1$. The unitarity constraints can be incorporated naturally in this
 2493 picture [259] by the requirement that $|S(r, b; x)| \geq 0$, with $S(r, b; x) = 0$ corresponding to the black disk




Figure 5.6: (left) Geometric scaling plot [248], in which low x data on the γ^*p cross section from HERA and E665 are plotted as a function of the dimensionless variable τ (see text). The cross sections are scaled by $\sqrt{\tau}$ for visibility. (right) Geometric scaling plot showing cross sections for electron scattering off nuclei as well as off protons [249].

2494 limit. Integrating $1 - S(r, b; x)$ over the impact parameter b one obtains the dipole cross section $\sigma^{q\bar{q}}(r, x)$,
 2495 which depends on the dipole size and the energy (through the dependence on $x = x_{Bj}$). The transverse size
 2496 of the partons probed in this process is roughly proportional to the inverse of the virtuality of the photon
 2497 Q^2 . This statement is most accurate in the case of a longitudinally polarized photon, while in the case of a
 2498 transversely polarized one, the distribution of the probed transverse sizes of dipoles is broadened due to the
 2499 so-called aligned jet configurations.

2500 At small values of the dipole size, such that $r \ll 1/Q$, the dipole cross section can be shown to be related
 2501 to the integrated gluon distribution function

$$\sigma^{q\bar{q}}(r, x) \sim r^2 \alpha_s(C/r^2) xg(x, C/r^2), \quad (5.3)$$

2502 where C is a constant. In this regime, where r is small, the dipole cross section is small and consequently
 2503 the amplitude is far from the unitarity limits. With increasing energy the dipole cross section grows and
 2504 saturation corrections must be taken into account in order to guarantee the unitarity bound on $S(r, b; x)$.
 2505 The transition region between the two limits is characterised by the saturation scale $Q_s(x)$. Several models
 2506 [241, 246, 260] have been proposed which successfully describe the HERA data on the structure function F_2 .

2507 Once the dipole cross section has been constrained by the data on the inclusive structure functions, it
 2508 can be used to predict, with almost no additional parameters, the cross sections for diffractive production at
 2509 small x . Inclusive diffraction has been computed within the dipole picture in [242], and exclusive diffraction
 2510 of vector mesons in [261, 262]. One of the interesting aspects of these models is that they naturally lead
 2511 to a constant ratio of the diffractive to total cross sections as a function of energy [242]. In models with
 2512 saturation this is related to the fact that the saturation scale provides a natural x -dependent cut-off and




Figure 5.7: Schematic representation of dipole factorisation at small x in DIS. The virtual photon fluctuates into a quark-antiquark pair and subsequently interacts with the target. All the details of the dynamics of the interaction are encoded in the dipole scattering amplitude.

2513 gives the same leading-twist behavior for inclusive and diffractive cross sections. As a result the ratio of
 2514 inclusive to diffractive cross sections is almost constant as a function of the energy.

2515 In spite of the fact that this approach has been able to successfully describe inclusive data and predict
 2516 diffraction at small values of x , there is still important conceptual progress to be made. Certainly there
 2517 are important hints from dipole models about the nature of the perturbative–non-perturbative transition in
 2518 QCD. Nevertheless, dipole models should be rather regarded as effective phenomenological approaches. As
 2519 such they only parametrize the essential dynamics at small x . For instance, the transverse impact parameter
 2520 dependence of the dipole scattering amplitude $S(r, b; x)$ is very poorly constrained. Indeed, it is possible
 2521 simultaneously to describe F_2 and F_2^D with a rather wide range of impact parameter dependences. On the
 2522 theoretical side, it has not been possible so far to fully predict the realistic profile of the interaction region in
 2523 transverse size. It is therefore of vital importance to measure accurately the t -dependencies of the diffractive
 2524 cross sections in an extended kinematic range to pin down the impact parameter distribution of the proton
 2525 at high energies.

2526 Hints of deviations from fixed-order linear DGLAP evolution in inclusive HERA data

2527 As discussed in previous sections, the experimental data on the inclusive structure functions F_2 and F_L
 2528 measured at HERA have been successfully described - with $\chi^2/d.o.f. \sim 1$ - by fits which use linear fixed-order
 2529 DGLAP evolution, see e.g. [38, 68, 131, 133, 263–269]. The current status of the calculations is fixed order at
 2530 next-to-next-to-leading accuracy. On the other hand, see Subsec. 5.1.1, there are several theoretical reasons
 2531 to expect that at small x and/or at small Q^2 the fixed-order DGLAP framework needs to be extended.
 2532 Possible relevant phenomena predicted by perturbative QCD are linear small- x resummation, non-linear
 2533 evolution and parton saturation or other higher-twist effects. Although the exact kinematic regime in which
 2534 these effects should become important remains unclear, it is evident that at some point they will lead to
 2535 deviations from fixed-order DGLAP evolution. Therefore, an important question is whether these deviations
 2536 are already present in HERA data. Several analyses have been performed which aimed to address this
 2537 question.

2538 In one analysis [247], HERA $F_2(x, Q^2)$ data are subjected to three fits in the framework of a dipole model.
 2539 In one of the fits, the parameterisation of the dipole cross section does not contain saturation properties,
 2540 whereas in the other two, saturation effects are included using two rather different models [246, 247]. All
 2541 three dipole fits are able to describe the HERA data adequately in the perturbative region $Q^2 \geq 2 \text{ GeV}^2$.
 2542 However, a clear preference for the models containing saturation effects becomes evident when data in the




Figure 5.8: Left plot: the kinematic coverage of the data used in the NNPDF2.0 analysis, indicating the different choices of A_{cut} used to probe deviations from DGLAP. Right plot: the diagonal χ^2_{diag} evaluated in kinematic slices corresponding to the different A_{cut} cuts, where χ^2_{diag} has been computed using both the reference NNPDF2.0 fit without kinematic cuts (yellow line) and the NNPDF2.0 with the maximum $A_{\text{cut}} = 1.5$ cut (red line).

range $0.045 < Q^2 < 1 \text{ GeV}^2$ are added [247]. Similar conclusions are drawn when the same dipole cross section models are applied to various less inclusive observables at HERA [270]. These observations provide an intriguing hint that saturation effects may already be present in HERA data. However, due to the non-perturbative nature of the low Q^2 kinematic region in which the effects appear, there is no clear interpretation in terms of perturbative QCD degrees of freedom and firm conclusions cannot be drawn on the existence and nature of parton recombination effects.

In another analysis [206], possible indications of deviations from linear DGLAP evolution were discussed. It was based on an unbiased PDF analysis of the inclusive HERA data. Here we present briefly an updated version of this study which uses the most precise inclusive DIS data to date, the combined HERA-I dataset [38] in the framework of the global NNPDF2.0 fitting framework. The key idea is to perform global fits only in the large- x , large- Q^2 region, where NLO DGLAP is expected to be reliable. This way one can determine *safe* parton distributions which are not contaminated by possible non-DGLAP effects. These PDFs are then evolved backwards into the potentially *unsafe* low- x and low- Q^2 kinematic region, and are used to compute physical observables, which are compared with data. A deviation between the predicted and observed behavior in this region can then provide a signal for effects beyond NLO DGLAP.

The PDFs were determined within the *safe* kinematic region in which $Q^2 \geq A_{\text{cut}} \cdot x^{-\lambda}$, where $\lambda = 0.3$ and A_{cut} is a variable parameter (see the left plot in Fig. 5.8 and [206] for details on the procedure). The NNPDF2.0 analysis [269] was repeated for different choices of the kinematic cuts, one for each choice of A_{cut} , and the results were compared with experimental data. As shown in Fig. 5.9, at high $Q^2 = 15 \text{ GeV}^2$ one does not see any significant deviation from NLO DGLAP. In this region all PDF sets agree with data and with one another, the only difference between them being that as A_{cut} increases the PDF uncertainty bands grow as expected due to the experimental information removed by the cuts. The situation is different at a lower $Q^2 = 3.5 \text{ GeV}^2$: the prediction obtained from the backwards evolution of the data above the cut exhibits a systematic downward trend, becoming more evident with increasing A_{cut} . These results are indicative of deficiencies in the description of HERA data at low- x and low- Q^2 by NLO DGLAP evolution³. Specifically, the NLO DGLAP approach suggests a faster evolution with Q^2 than is present in the data. To be sure that one is observing a genuine small- x effect, one needs to check that it becomes less and less relevant as x and Q^2 increase. To this aim the diagonal χ^2_{diag} was computed, see the right plot in Fig. 5.8, in different kinematic slices, both from the fit without cuts and from that with the maximum cut $A_{\text{cut}} = 1.5$.

³This problem cannot be solved by NNLO corrections which work in the opposite direction, see in this respect [267]. Also, in the HERAPDF framework [38, 68] the fit quality tends to worsen when low- Q^2 data are included. See [245] for a recent discussion and comparison with models containing non-linear dynamics.




Figure 5.9: Left: the proton structure function $F_2(x, Q^2 = 15 \text{ GeV}^2)$ at small- x , computed from PDFs obtained from the NNPDF2.0 fits with different values of A_{cut} . Right: the same but at a lower $Q^2 = 3.5 \text{ GeV}^2$ scale.

2572 The expectation is that at larger x and Q^2 the difference between the two fits becomes smaller, as deviations
 2573 from NLO DGLAP should become negligible. The data support this expectation: the contribution to the
 2574 χ^2 from the region with $A_{\text{cut}} \geq 3$ is comparable for the fits with and without cuts, in contrast to the lower x
 2575 and Q^2 region, where the χ^2 is substantially larger in the version of the fit with cuts applied. Nevertheless, it
 2576 should be noted that there is no general consensus on the origins of these effects. e.g. in [271] it is suggested
 2577 that their origin lies in bias due to the chosen initial conditions for DGLAP evolution

2578 In summary, there are hints that the low- Q^2 -low- x region covered by HERA may exhibit deviations from
 2579 fixed-order linear evolution. These hints are obtained from the success of dipole models with saturation
 2580 features to describe the experimental data in this region, and from the fact that the quality of fixed-order
 2581 DGLAP fits seems to deteriorate there. However, the region in which such effects may be present corresponds
 2582 to rather small Q^2 , preventing a clear interpretation in terms of perturbative QCD degrees of freedom. In
 2583 addition, the overall quality of the fixed-order DGLAP fits to HERA data remains high. It is therefore
 2584 premature to draw any firm conclusion on the failure of fixed-order linear evolution as the appropriate tool
 2585 to describe all HERA data. In any case, it is clear that the methods discussed in this Subsection should be
 2586 used to analyse LHeC inclusive structure function data, and would allow a detailed characterization of any
 2587 new high-energy QCD dynamics unveiled by the LHeC. If the hints in the HERA data are correct, the novel
 2588 phenomena should appear at the LHeC in a higher Q^2 perturbative region where they can be established
 2589 cleanly and understood in terms of parton dynamics.

2590 Linear resummation schemes

2591 The deviations from DGLAP evolution could be caused by higher order effects at small x and small Q
 2592 which need to be resummed to all orders of perturbation theory. As mentioned previously, the problem
 2593 of resummation at small x has been extensively studied in recent years, see for example [209–214]. It has
 2594 been demonstrated that the small- x resummation framework accounts for running coupling effects, kinematic
 2595 constraints, gluon exchange symmetry and other physical constraints. The results were shown to be very
 2596 robust with respect to scale changes and different resummation schemes. As a result, the effect of the
 2597 resummation of terms which are enhanced at small x is perceptible but moderate - comparable in size to
 2598 typical NNLO fixed order corrections in the HERA region.

2599 A major development for high-energy resummation was presented in [211], where the full small- x re-
 2600 summation of deep-inelastic scattering (DIS) anomalous dimensions and coefficient functions was obtained
 2601 including the quark contribution. This allowed for the first time a consistent small- x resummation of DIS
 2602 structure functions. These results are summarized in Fig. 5.10, taken from Ref. [211], where the K -factors

2603 for F_2 and F_L for the resummed results are compared. As is evident from this figure, resummation is quite
 2604 important in the region of low x for a wide range of Q^2 values. One observes, for example, that the fixed order
 2605 NNLO contribution leads to an enhancement of F_2 with respect to NLO, whereas the resummed calculation
 2606 leads to a suppression. This means that a truncation at any fixed order is very likely to be insufficient for
 2607 the description of the LHeC data and therefore the fixed-order perturbative expansion becomes unreliable
 2608 in the low- x region, which calls for the resummation. Furthermore, the resummation of hard partonic cross
 2609 sections has been performed for several LHC processes such as heavy quark production [272], Higgs pro-
 2610 duction [273, 274], Drell-Yan [275, 276] and prompt photon production [277, 278]. The LHC is thus likely to
 2611 provide a testing ground in the near future.

2612 We refer to the recent review in Ref. [279] as well as to the HERA-LHC workshop proceedings [280] for
 2613 a more detailed summary of recent theoretical developments in high-energy resummation.




Figure 5.10: The K -factors, defined as the ratio of the fixed-order NNLO or resummed calculation to the NLO fixed-order results for the singlet F_2 and F_L structure functions, with F_2 and F_L kept fixed for all x at $Q_0 = 2$ GeV. Results are shown at fixed $x = 10^{-2}$, 10^{-4} or 10^{-6} as a function of Q in the range $Q = 2 - 1000$ GeV with α_s running and n_f varied in a zero-mass variable flavour number scheme. The breaks in the curves correspond to the b and t quark thresholds. The curves are: fixed order perturbation theory NNLO (green, dashed); resummed NLO in the $Q_0\overline{\text{MS}}$ scheme (red, solid), resummed NLO in the $\overline{\text{MS}}$ scheme (blue, dot-dashed). Curves with decreasing x correspond to those going from bottom to top for NNLO and from top to bottom in the resummed cases.

2614 To summarise, small- x resummation is becoming a very important component for precision LHC physics,
 2615 and will become a crucial ingredient of the LHeC small- x physics program [281, 282]. The LHeC extended
 2616 kinematic range will enhance the differences between the resummed predictions and fixed-order DGLAP
 2617 calculations.

2618 5.1.3 Low- x physics perspectives at the LHC

2619 The low- x regime of QCD can also be analyzed in hadron and nucleus collisions at the LHC. The experimen-
 2620 tally accessible values of x range from $x \sim 10^{-3}$ to $x \sim 10^{-6}$ for central and forward rapidities respectively.
 2621 The estimates for the corresponding saturation scale at $x \sim 10^{-3}$, based on Eq. (5.2), result in $Q_s^2 \approx 1$ GeV²
 2622 for proton and $Q_s^2 \approx 5$ GeV² for lead.

2623 The significant increase in the center-of-mass energy and the excellent rapidity coverage of the LHC
 2624 detectors will extend the kinematic reach in the x - Q^2 plane by orders of magnitude compared to previous




Figure 5.11: Kinematic reaches in the (x, Q^2) plane covered in proton-proton (left), proton-nucleus (center) [283] and ultraperipheral nucleus-nucleus (right) [284] collisions at the LHC. Also shown are the regions studied so far in collider and fixed-target experiments. Estimates of the saturation scale for lead are also shown.

2625 measurements at fixed-target and collider energies (see Fig. 5.11). Such measurements are particularly
 2626 important in the nuclear case since, due to the scarcity of nuclear DIS data, the gluon PDF in the nucleus is
 2627 virtually unknown at fractional momenta below $x \approx 10^{-2}$ [152]. In addition, due to the dependence of the
 2628 saturation scale on the hadron transverse size, non-linear QCD phenomena are expected to play a central role
 2629 in the phenomenology of collisions involving nuclei. We succinctly review here the experimental possibilities
 2630 to study saturation physics in pp , pA and AA collisions at the LHC.

2631 Low- x studies in proton-proton collisions

2632 The LHC experiments feature detection capabilities at forward rapidities ($|\eta| \gtrsim 3$), which will allow mea-
 2633 surements of various perturbative processes sensitive to the underlying parton structure and its dynamical
 2634 evolution in the proton. The *minimum* parton momentum fractions probed in a $2 \rightarrow 2$ process with a particle
 2635 of momentum p_T produced at pseudo-rapidity η is

$$x_{min} = \frac{x_T e^{-\eta}}{2 - x_T e^{\eta}}, \quad \text{where } x_T = 2p_T/\sqrt{s}, \quad (5.4)$$

2636 i.e. x_{min} decreases by a factor ~ 10 every 2 units of rapidity. The extra e^{η} lever-arm motivates the interest in
 2637 *forward* particle production measurements to study the PDFs at small values of x . From Eq. (5.4) it follows
 2638 that the measurement at the LHC of particles with transverse momentum $p_T = 10$ GeV at rapidities $\eta \approx 5$
 2639 probes x values as low as $x \approx 10^{-5}$ (Fig. 5.11, left). Various experimental measurements have been proposed
 2640 at forward rapidities at the LHC to constrain the low- x PDFs in the proton and to look for possible evidence
 2641 for non-linear QCD effects. These include forward jets and Mueller-Navelet dijets in ATLAS and CMS [285];
 2642 and forward isolated photons [286] and Drell-Yan (DY) [287] in LHCb.

2643 Low- x studies in proton-nucleus collisions

2644 Until an electron-ion collider becomes available, proton-nucleus collisions will be the best available tool to
 2645 study small- x physics in a nuclear environment without the strong influence of the final-state medium as
 2646 expected in the AA case. Though proton-nucleus collisions are not yet scheduled at the LHC, detailed feasi-
 2647 bility studies exist [288] and strategies to define the accessible physics programme are being developed [283].
 2648 The pA programme at the LHC serves a dual purpose [283]: to provide “cold QCD matter” benchmark

measurements for the physics measurements of the AA programme without significant final-state effects, and to study the nuclear wavefunction in the small- x region. In Fig. 5.11 (center) we show how dramatically the LHC will extend the region of phase space in the (x, Q^2) plane⁴ by orders of magnitude compared with those studied at present. The same figure also shows the scarcity of nuclear DIS and DY measurements and, correspondingly, the lack of knowledge of nuclear PDFs in the regions needed to constrain the initial state for the AA programme - there is almost no information at present in the region $x \lesssim 10^{-2}$ [152].

Nuclear PDF constraints, checks of factorization (universality of PDFs) and searches for saturation of partonic densities will be performed in pA collisions at the LHC by studying different production cross sections for e.g. inclusive light hadrons [289], heavy flavour particles [290], isolated photons [291], electroweak bosons [292] and jets. Additional opportunities also appear in the so-called ultra-peripheral collisions in which the coherent electromagnetic field created by the proton or the large nucleus effectively acts as one of the colliding particles with photon-induced collisions at centre of mass energies higher than those reached in photoproduction at the HERA collider [293] (see next subsection).

At this point it is worth mentioning that particle production in the forward (proton) rapidity region in dAu collisions at RHIC shows features suggestive of saturation effects, although no consensus has been reached so far, see [294–300] and references therein. The measurements at RHIC suffer from the limitation of working at the edge of the available phase space in order to study the small- x region in the nuclear wave function. This limitation will be overcome by the much larger available phase space at the LHC.

Low- x studies in nucleus-nucleus collisions

Heavy-ion (AA) collisions at the LHC aim at the exploration of collective partonic behaviour both in the initial wavefunction of the nuclei as well as in the final produced matter, the latter being a hot and dense QCD medium (see the discussions in Subsection 5.1.4). The nuclear PDFs at small x define the number of parton scattering centers and thus the initial conditions of the system which then thermalises.

A possible means of obtaining direct information on the nuclear parton distribution functions is through the study of final state particles which do not interact strongly with the surrounding medium, such as photons [301] or electroweak bosons [292]. Beyond this, global properties of the collision such as the total multiplicities or the existence of long-range rapidity structures (seen in AuAu collisions at RHIC [302] and in pp and PbPb collisions at the LHC [303, 304]) are sensitive to the saturation momentum which at the LHC is expected to be well within the weak coupling regime [305], $Q_{\text{sat, Pb}}^2 \approx 5 - 10 \text{ GeV}^2$. CGC predictions for charged hadron multiplicities in central Pb-Pb collisions at 5.5 TeV per nucleon are $dN_{ch}/d\eta|_{\eta=0} \approx 1500\text{--}2000$ [306]. (Note that the predictions done before the start of RHIC in 2000 were 3 times higher). Recent data from ALICE [307] give $dN_{ch}/d\eta|_{\eta=0} \approx 1600$ in central Pb-Pb at 2.76 TeV per nucleon, in rough agreement with CGC expectations.

As already noted for the pA case, one of the cleanest ways to study the low- x structure of the Pb nucleus at the LHC may be via ultra-peripheral collisions (UPCs) [293] in which the strong electromagnetic fields (the equivalent flux of quasi-real photons) generated by the colliding nuclei can be used for photoproduction studies at maximum energies $\sqrt{s_{\gamma N}} \approx 1 \text{ TeV}$, that is 3–4 times larger than at HERA. In particular, exclusive quarkonium photoproduction offers an attractive opportunity to constrain the low- x gluon density at moderate virtualities, since in such processes the gluon couples *directly* to the c or b quarks and the cross section is proportional to the gluon density *squared*. The vector meson mass M_V introduces a relatively large scale, amenable to a perturbative QCD treatment. In $\gamma A \rightarrow J/\psi (\Upsilon) A^{(*)}$ processes at the LHC, the gluon distribution can be probed at values as low as $x = M_V^2/W_{\gamma A}^2 e^y \approx 10^{-4}$, where $W_{\gamma A}$ is the γA centre of mass energy (Fig. 5.11 right). Full simulation studies [284, 308] of quarkonium photoproduction tagged with very-forward neutrons, show that ALICE and CMS can carry out detailed p_T, η measurements in the dielectron and dimuon decay channels.

In summary, pp , pA and AA collisions at the LHC have access to the small- x regime, and will certainly help to unravel the complex parton dynamics in this region. However, the excellent precision of a high

⁴Asymmetric colliding systems imply a rapidity shift in the two-in-one magnet design of the LHC. This shift has been taken into account in the figure: the quoted y values are those in the laboratory frame.

energy electron-proton (ion) collider cannot be matched in hadronic collisions. The deep inelastic scattering process is much cleaner experimentally and under significantly better theoretical control. The description of hadron-hadron and heavy ion collisions in the regime of small x suffers from a variety of uncertainties, such as the question of the appropriate factorization, if any, and the large indeterminacy of fragmentation functions in the relevant kinematic region. Thus, the precise measurement of physical observables and parton densities and their interpretation in terms of QCD dynamics is only possible at an electron-hadron (ion) collider.

5.1.4 Nuclear targets

As discussed in Subsection 5.1.1, the use of nuclei offers a means of modifying the parton density both through colliding different nuclear species and by varying the impact parameter of the collision. Therefore, the study of DIS on nuclear targets is of the utmost importance for our understanding of the dynamics which control the behaviour of hadron and nuclear wave functions at small x . On the other hand, the characterization of parton densities inside nuclei and the study of other aspects of lepton-nucleus collisions such as particle production, are of strong interest both fundamentally and because they are crucial for a correct interpretation of the experimental results from ultrarelativistic ion-ion collisions. In the rest of this section we focus on these last two aspects.

Additionally, nuclear effects have to be better understood in order to improve the constraints on nucleon PDF in analyses which include DIS data with neutrino beams (e.g. [267, 269]). Due to the smallness of the cross section, such neutrino experiments use nuclear targets, so corrections for nuclear effects are a significant source of uncertainty in the extraction of parton densities even for the proton.

Comparing nuclear parton density functions

The nuclear modification of structure functions has been extensively studied since the early 70's [309, 310]. It is usually characterized through the so-called nuclear modification factor which, for a given structure function or parton density f , reads

$$R_f^A(x, Q^2) = \frac{f^A(x, Q^2)}{A \times f^N(x, Q^2)}. \quad (5.5)$$

In this equation, the superscript A refers to a nucleus of mass number A , while N denotes the nucleon (either a proton or a neutron, or their average as obtained using deuterium). The absence of nuclear effects would result in $R = 1$.

The nuclear modification factor for F_2 shows a rich structure: an enhancement ($R > 1$) at large $x > 0.8$, a suppression ($R < 1$) for $0.3 < x < 0.8$, an enhancement for $0.1 < x < 0.3$, and a suppression for $x < 0.1$ where isospin effects can be neglected. The latter effect is called shadowing [243], and is the dominant phenomenon at high energies (the kinematical region $x < 0.1$ will determine particle production at the LHC, see Sec. 5.1.3 and [311]).

The modifications in each region are believed to be of different dynamical origin. In the case of shadowing, the explanation is usually given in terms of a coherent interaction involving several nucleons, which reduces the nuclear cross section from the totally incoherent situation, $R = 1$, towards a region of total coherence. In the region of very small x , small-to-moderate Q^2 and for large nuclei, the unitarity limit of the nuclear scattering amplitudes is expected to be approached and some mechanism of unitarisation such as multiple scattering should come into play. Therefore, in this region nuclear shadowing is closely related to the onset of the unitarity limit in QCD and the transition from coherent scattering of the probe off a single parton to coherent scattering off many partons. The different dynamical mechanisms proposed to deal with this problem should offer a quantitative explanation for shadowing, with the nuclear size playing the role of a density parameter in the way discussed in Subsection 5.1.1.

At large enough Q^2 the generic expectation is that the parton system becomes dilute and the usual leading-twist linear DGLAP evolution equations should be applicable to nuclear PDFs. In this framework,

global analyses of nuclear parton densities (in exact analogy to those of proton and neutron parton densities) have been developed up to NLO accuracy [152, 312–314]. In these global analyses, the initial conditions for DGLAP evolution are parametrized by flexible functional forms but they lack theoretical motivation in terms of e.g. the dynamical mechanisms for unitarization mentioned above. On the other hand, the relation between diffraction and nuclear shadowing [56, 215] can in principle be employed to constrain the initial conditions for DGLAP evolution, as has been explored previously at both LO [217] and NLO [315]⁵ accuracy, see Subsec. 5.2.4. All nuclear PDF analyses [152, 312–314] include data from NC DIS and DY experiments, [152, 314] also use particle production data at mid-rapidity in deuterium-nucleus collisions at RHIC, and [314] CC DIS data from neutrino experiments. Error sets obtained through the Hessian method are provided in [152, 314]. Note that CC DIS data have been considered only recently [53, 314, 317]⁶ in this context.

Results from different nuclear PDF analyses performed at NLO accuracy are shown in Fig. 5.12, with the band indicating the uncertainty obtained using the error sets in [152]. In addition to the discrepancies concerning the existence of an enhancement/suppression at large x , the different approaches lead to clear differences at small x , both in magnitude and in shape⁷, usually within the large uncertainty band shown. With nuclear effects vanishing logarithmically in the DGLAP analysis, the corresponding differences and uncertainties diminish, although they remain sizable until rather large Q^2 .

These large uncertainties are due to the lack of experimental data on nuclear structure functions for $Q^2 > 2 \text{ GeV}^2$ and x smaller than a few times 10^{-2} . The constraints on the small- x gluon are particularly poor. Particle production data at mid-rapidity coming from deuterium-nucleus collisions at RHIC offer an indirect constraint on the small- x sea and glue [152, 314], but these data are bound to contain sizable uncertainties intrinsic to particle production in hadronic collisions at small and moderate scales. Therefore, only high-accuracy data on nuclear structure functions at smaller x , with a large lever arm in Q^2 , as achievable at the LHeC, will be able to substantially reduce the uncertainties and clearly distinguish between the different approaches.

Requirements for the ultra-relativistic heavy ion programs at RHIC and the LHC

The LHeC will offer extremely valuable information on several aspects of high-energy hadronic and nuclear collisions. On the one hand, it will characterize hard scattering processes in nuclei through a precise determination of initial state. On the other hand, it will provide quantitative constraints on theoretical descriptions of initial particle production in ultra-relativistic nucleus-nucleus collisions and the subsequent evolution into the quark-gluon plasma, the deconfined partonic state of matter whose production and study offers key information about confinement. Such knowledge will complement that coming from pA collisions and self-calibrating hard probes in nucleus-nucleus collisions (see [283, 301, 311, 318, 319]) regarding the correct interpretation of the findings of the heavy-ion programme at RHIC (see e.g. [320, 321] and refs. therein) and at the LHC. Beyond the qualitative interpretation of such findings, the LHeC will greatly improve the quantitative characterization of the properties of QCD extracted from such studies. The relevant information can be classified into three items:

a. Parton densities inside nuclei:

The knowledge of parton densities inside nuclei is an essential piece of information for the analysis of the medium created in ultra-relativistic heavy-ion collisions using hard probes, i.e. those observables whose yield in nucleon-nucleon collisions can be predicted in pQCD (see [301, 311, 318, 319]). The comparison between the expectation from an incoherent superposition of nucleon-nucleon collisions and the measurement in nucleus-nucleus collisions characterises the nuclear effects. However, we need

⁵In the approach in [315] predictions are provided only for sea quarks and gluons, with the valence taken from the analysis in [316].

⁶The analyses in [152, 314, 317] show the compatibility of the nuclear corrections as extracted from NC DIS, DY and particle production in dAu at RHIC, with CC DIS data on nuclear targets, while in [53] some tension is found between NC and CC DIS data.

⁷The increasing shape of the gluon ratio with decreasing x at small x and Q^2 in [314], is due to the fact that in this analysis the proton parton densities MSTW2008 [267], in which the gluon distribution becomes negative in that kinematical region, are used.




Figure 5.12: Ratio of parton densities in a bound proton in Pb to those in a free proton scaled by $A = 207$, for valence u (left), \bar{u} (middle) and g (right), at $Q^2 = 1.69$ (top) and 100 (bottom) GeV^2 . Results are shown from [312] (nDS, black dashed), [313] (HKN07, green solid), [152] (EPS09, red dotted), [315] (FGS10, blue dashed-dotted; in this case the lowest Q^2 is 4 GeV^2 and two lines are drawn reflecting the uncertainty in the predictions) and [314] (DSSZ, cyan dashed-dotted). The red bands indicate the uncertainties according to the EPS09 analysis [152].

2783 to disentangle those effects which originate from the creation of a hot medium in nucleus-nucleus
2784 collisions, from effects arising only from differences in the partonic content between nucleons and
2785 nuclei.

2786 Our present knowledge of parton densities inside nuclei is clearly insufficient in the kinematic regions of
2787 interest for RHIC and, above all, for the LHC (see [311] and Subsection 5.1.3). Such ignorance reflects
2788 in uncertainties larger than a factor 3–4 for the calculation of different cross sections in nucleus-nucleus
2789 collisions at the LHC (see Fig. 5.12 and [289]), thus weakening strongly the possibility of extracting
2790 quantitative characteristics of the produced hot medium. While the pA program at the LHC will offer
2791 new constraints on the nuclear parton densities (e.g. [283, 289]), measurements at the LHeC would be
2792 far more constraining and would reduce the uncertainties in nucleus-nucleus cross sections to less than
2793 a factor two.

2794 b. Parton production and initial conditions for a heavy-ion collision:

2795 The medium produced in ultra-relativistic heavy-ion collisions develops very early a collective behavior,
2796 usually considered as that of a thermalized medium and describable by relativistic hydrodynamics. The
2797 initial state of a heavy-ion collision for times prior to its eventual thermalization, and the thermalisation
2798 or isotropisation mechanism, play a key role in the description of the collective behavior. Such an
2799 initial condition for hydrodynamics or transport is presently modelled and fitted to data. But it
2800 should eventually be determined by a theoretical formalism of particle production within a saturation
2801 framework which embodies the both aspects: parton fluxes inside nuclei - discussed in the previous
2802 item, and particle production and evolution, eventually leading to isotropization.

2803 The CGC offers a well-defined framework in which the initial condition and thermalization mechanism
2804 can be computed from QCD, see Subsection 5.1.1 and e.g. [322] and refs. therein. Although our
2805 theoretical knowledge is still incomplete, electron-nucleus collisions offer a setup, considerably less
2806 complex than nucleus-nucleus collisions, in which these CGC-based calculations already exist and can
2807 be tested. In this way, electron-ion collisions offer a testing ground for ideas on parton production in
2808 a dense environment, which is required for a first principles calculation of the initial conditions for the
2809 collective behavior in ultra-relativistic heavy-ion collisions. The LHeC offers the possibility of studying
2810 particle production in the kinematic region relevant for experiments at RHIC and the LHC.

2811 c. Parton fragmentation and hadronization inside the nuclear medium:

2812 The mechanism through which a highly virtual parton evolves from an off-shell coloured state to a final
2813 state consisting of colourless hadrons, is still subject to great uncertainties. Electron-ion experiments
2814 offer a testing ground for our ideas and understanding of such phenomena, see [323] and refs. therein,
2815 with the nucleus being a medium of controllable extent and density which modifies the radiation and
2816 hadronization processes.

2817 The LHeC will have capabilities for particle identification and jet reconstruction for both nucleon and
2818 nuclear targets. Its kinematic reach will allow the study of partons traveling through the nucleus
2819 from low energies, for which hadronization is expected to occur inside the nucleus, to high energies
2820 with hadronization outside the nucleus. Therefore the modification of the yields of energetic hadrons,
2821 observed at RHIC⁸ and usually attributed to in-medium energy loss - the so-called jet quenching
2822 phenomenon - will be investigated. With jet quenching playing a key role in the present discussions
2823 on the production and characterisation of the hot medium produced in ultra-relativistic heavy-ion
2824 collisions, the LHeC will offer most valuable information on effects in cold nuclear matter of great
2825 importance for clarifying and reducing the existing uncertainties.

⁸LHC experiments have already observed the jet quenching phenomenon both at the level of single-particle spectra [324, 325] and through the study of jets [326–328], which will play a central role in heavy-ion physics at these energies.

5.2 Prospects at the LHeC

5.2.1 Strategy: decreasing x and increasing A

As discussed previously, in order to analyse the regime of high parton densities at small x , we propose a two-pronged approach which is illustrated in Fig. 5.5. To reach an interesting novel regime of QCD one can either decrease x by increasing the center-of-mass energy or increase the matter density by increasing the mass number A of the nucleus. In addition, we will see that diffraction, and especially exclusive diffraction, will play a special role in unravelling the new dense partonic regime of QCD.

The LHeC will offer a huge lever arm in x and also a possibility of changing the matter density at fixed values of x . This will allow us to pin down and compare the small x and saturation phenomena both in protons and nuclei and will offer an excellent testing ground for theoretical predictions. Thus, in the following, LHeC simulations of electron-proton collisions are paralleled by those in electron-lead wherever possible. For a complementary perspective on the opportunities for novel QCD studies offered by the LHeC, see [88].

5.2.2 Inclusive measurements

Predictions for the proton

The LHeC is expected to provide measurements of the structure functions of the proton with unprecedented precision, which will allow detailed studies of small- x QCD dynamics. In particular, it will be highly sensitive to departures of the inclusive observables F_2 and F_L from the fixed-order DGLAP framework, in the region of small x and Q^2 . These deviations are expected by several theoretical arguments, as discussed in detail previously.

In Fig. 5.13 we show some predictions for the proton structure functions, F_2 and F_L , in ep collisions at $Q^2 = 10 \text{ GeV}^2$ and for $10^{-6} \leq x \leq 0.01$ i.e. $F_{2(L)}(x, Q^2 = 10 \text{ GeV}^2)$. The different curves correspond to the extrapolation of models that reproduce correctly the available HERA data for the same observables in the small- x region. They are classified into two categories: those based on linear evolution approaches and those that include non-linear small- x dynamics. Among the linear approaches we include extrapolation from the NLO DGLAP fit as performed by the NNPDF collaboration [329] (solid yellow bands) and the results from a combined DGLAP/BFKL approach, which includes resummation of small- x effects [330] (black-dotted-dotted lines). The non-linear calculations shown here are all formulated within the dipole model. We distinguish two categories: those based on the eikonalization of multiple scatterings together with DGLAP evolution of the gluon distributions [260,261] (blue dashed-dotted lines) and those relying in the Color Glass Condensate effective theory of high-energy QCD scattering (red dashed lines). The latter include calculations based on solutions of the running coupling Balitsky-Kovchegov equation [331] and other more phenomenological models of the dipole amplitude without [246], or with [262] impact parameter dependence. Finally, we also include a hybrid approach, where initial conditions based on Regge theory and including non-linearities are evolved in Q^2 according to linear DGLAP evolution [216] (green dotted line). In all cases the error bands are generated by allowing variations of the free parameters in each subset of models. The green filled squares correspond to the subset of the simulated LHeC pseudodata at $Q^2 = 10 \text{ GeV}^2$ (see Subsection 4.1.4).

Clearly, the accuracy of the data at the LHeC will offer huge possibilities for discriminating between different models and for constraining the dynamics underlying the small- x region.

Constraining small- x dynamics

The potential impact of the LHeC on low x parton densities within the framework of an NLO DGLAP analysis is assessed by adding the pseudodata introduced in subsection 4.1.4 into the NNPDF fitting analysis. The pseudodata are first generated at the extrapolated central values according to the existing NNPDF fits.

The extrapolated NNPDF1.2 gluon density and its uncertainty band are shown at the starting scale for QCD evolution, $Q_0^2 = 2 \text{ GeV}^2$ in Fig. 5.14, where it can be seen that the lack of experimental constraints for $x \lesssim 10^{-4}$ leads to an explosion in the uncertainties. When the LHeC F_2 pseudodata are included in addition,




Figure 5.13: Predictions from different models for $F_2(x, Q^2 = 10 \text{ GeV}^2)$ (plot on the left) and $F_L(x, Q^2 = 10 \text{ GeV}^2)$ (plot on the right) versus x , together with the corresponding pseudodata. See the text for explanations.

2872 the uncertainties improve considerably, but remain rather large at the lowest x values, due to the lack of a
 2873 large lever-arm in Q^2 to constrain the evolution. However, when the LHeC pseudodata on the longitudinal
 2874 structure function F_L are included in addition, the additional constraints lead to a much more substantial
 2875 improvement in the uncertainties on the gluon density.

2876 As is well known from experience at HERA, the measurement of the longitudinal structure function
 2877 presents many experimental challenges and involves possibly undesirable modifications to the beam energies.
 2878 An alternative constraint on the gluon density from the charmed structure function F_2^c has therefore also
 2879 been investigated. As discussed in detail in Subsec. 4.6.1, the LHeC will offer unique precision in the
 2880 determination of the charm and beauty structure functions, extending to very small x .

2881 In Fig. 5.15 the gluon distribution function is shown, as obtained from the NNPDF2.0 analysis. The green
 2882 band corresponds to the standard analysis. The red band shows the modified analysis where additionally
 2883 F_2^c pseudodata from the LHeC are included, using a novel technique based on Bayesian reweighting [332]. It
 2884 is observed that the charmed structure function considerably improves the constraints on the gluon density
 2885 at small values of x , especially between $3 \times 10^{-5} - 10^{-2}$, provided that the scattered electron acceptance
 2886 extends to within around 1° of the beampipe. With a sufficiently good theoretical understanding, heavy
 2887 flavour production data from the LHeC may thus offer an alternative to F_L for precision constraints on the
 2888 gluon density at all but the lowest x values.

2889 Given that for all models considered in Fig. 5.13 there are significant flexibilities in the initial parametri-
 2890 sations, it is conceivable that upon suitable changes of parameters it would be possible to obtain satisfactory
 2891 fits of a wide range of models to the LHeC data. It is therefore essential to analyse in more detail the ability
 2892 of the LHeC to distinguish unambiguously between different evolution dynamics. With this aim, a PDF
 2893 analysis is performed including LHeC pseudodata which are generated using different scenarios for small- x
 2894 QCD dynamics. Pseudodata for $F_2(x, Q^2)$ and $F_L(x, Q^2)$ at small x are considered in a scenario in which
 2895 the LHeC machine has electron energy $E_e = 70 \text{ GeV}$ and electron acceptance for $\theta_e \leq 179^\circ$, for an integrated
 2896 luminosity of 1 fb^{-1} . The study is carried out in the framework of the NNPDF1.0 analysis [333] and includes
 2897 all HERA and fixed target data used in that analysis, in addition to LHeC pseudodata. The kinematics
 2898 of the LHeC pseudodata included in the fit (together with other data included in the original NNPDF1.0
 2899 analysis) are shown in Fig. 5.16. In order to avoid correlations between low x and high x data e.g. through
 2900 the momentum sum rule constraint, only LHeC pseudodata with $x < 10^{-2}$ are considered. The average total
 2901 uncertainty of the simulated F_2 pseudodata is $\sim 2\%$, while that of F_L is $\sim 8\%$.

2902 For the NNPDF fits, the input LHeC pseudodata are generated not within the DGLAP framework,




Figure 5.14: The results for the gluon distribution in the standard NNPDF1.2 DGLAP fit [329], together with the results when additionally including LHeC pseudodata for F_2 (left) and for both F_2 and F_L (right). The results are shown at the starting scale for DGLAP evolution, $Q_0^2 = 2 \text{ GeV}^2$.

2903 but rather using two different models which include saturation effects in the gluon density: the AAMS09
 2904 model [331], which is based on non-linear Balitsky-Kovchegov evolution with a running coupling, and the
 2905 FS04 dipole model [247]. Both of these models deviate significantly from linear DGLAP evolution in the
 2906 LHeC regime.

2907 The global fit using the NNPDF1.0 framework with fixed-order DGLAP evolution is repeated, now
 2908 including LHeC pseudodata generated using the scenarios including saturation effects. By assessing the quality
 2909 of the fit with saturated LHeC pseudodata included, this study tests the sensitivity to parton dynamics be-
 2910 yond fixed-order DGLAP. The conclusions are the same for both the AAMS09 and the FS04 models. The
 2911 DGLAP analysis yields an acceptable fit when only the $F_2(x, Q^2)$ LHeC pseudodata are included. This
 2912 implies that although the underlying physical theories are different, the small- x extrapolations of AAMS09
 2913 and FS04 for F_2 are sufficiently similar to DGLAP-based extrapolations for the differences to be absorbed as
 2914 modifications to the shapes of the non-perturbative initial conditions for the PDFs at the starting scale Q_0^2
 2915 for DGLAP evolution. More sophisticated analyses, based for example on sequential kinematical cuts and
 2916 backwards DGLAP evolution, as presented in Subsec. 5.1.2, could still be applied. However, it seems likely
 2917 that it will not be possible unambiguously to establish non-linear effects using LHeC data on F_2 alone.

2918 The situation is very different when data on the longitudinal structure function $F_L(x, Q^2)$ are included
 2919 in the NNPDF fit, provided the lever-arm in Q^2 is large enough for the gluon sensitivity through the Q^2
 2920 evolution of F_2 to conflict with that through F_L . The analysis based on linear DGLAP evolution fails to
 2921 reproduce simultaneously F_2 and F_L in all the Q^2 bins, and thus the overall χ^2 is very large. The effect is
 2922 illustrated in Fig. 5.17, where the best fits from the NNPDF DGLAP analysis are compared with the LHeC
 2923 F_L pseudodata generated from the AAMS09 model. This is a clear signal for a departure from fixed-order
 2924 DGLAP of the simulated pseudodata. This analysis shows that the combined use of F_2 and F_L data is
 2925 a very sensitive probe of novel small- x QCD dynamics, and that their measurement would be very likely
 2926 to discriminate between different theoretical scenarios. Using F_2^c data in place of F_L may offer a similarly
 2927 powerful means of establishing deviations from fixed-order linear DGLAP evolution at small x .

2928 Predictions for nuclei: impact on nuclear parton distribution functions

2929 The LHeC, as an electron-ion collider in the TeV regime, will have an enormous potential for measuring the
 2930 nuclear parton distribution functions at small x . Let us start by a brief explanation of how the pseudodata
 2931 for inclusive observables in $e\text{Pb}$ collisions are obtained: To simulate an LHeC measurement of F_2 in electron-
 2932 nucleus collisions, the points (x, Q^2) , generated for $e(50) + p(7000)$ collisions for a high acceptance, low




Figure 5.15: The effect on the extracted gluon distribution function of the inclusion of the LHeC pseudodata on the charmed structure function in the NNPDF global analysis. Left plot: scattered electron acceptance extending to within 10° of the beampipe. Right plot: 1° acceptance. The results are shown at the starting scale for DGLAP evolution, $Q_0^2 = 2 \text{ GeV}^2$.

2933 luminosity scenario, as explained in Subsection 4.1.4, are considered. Among them, we keep only those
 2934 points at small $x \leq 0.01$ and not too large $Q^2 < 1000 \text{ GeV}^2$ with $Q^2 \leq sx$, for a Pb beam energy of
 2935 2750 GeV per nucleon⁹. Under the assumption that the instantaneous luminosity per nucleon is the same
 2936 in ep and eA [334], the number of events is scaled by a factor $1/(5 \times 50 \times A)$, with 50 coming from the
 2937 transition from a high luminosity to a low luminosity scenario, and 5 being a crudely estimated reduction
 2938 factor accounting for the shorter running time for ions than for proton.

2939 At each point of the grid, σ_r and F_2 are generated using the dipole model of [241, 335] to get the
 2940 central value. Then, for every point, the statistical error in ep is scaled by the previously mentioned factor
 2941 $1/(5 \times 50 \times A)$, and corrected for the difference in F_2 or σ_r between the (Glauberized) 5-flavor GBW
 2942 model [335] and the model used for the ep simulation. The fractional systematic errors are taken to be
 2943 the same as for ep - as has been achieved in previous DIS experiments on nuclear targets¹⁰. An analogous
 2944 procedure is applied when obtaining the nuclear pseudodata for F_2^c and F_2^b , considering the same tag and
 2945 background rejection efficiencies as in the ep simulation.

2946 To generate LHeC F_L pseudodata for a heavy ion target, a dedicated simulation of $e + p(2750)$ collisions
 2947 has been performed, at three different energies: 10, 25 and 50 GeV for the electron, with assumed luminosities
 2948 5, 10 and 100 pb^{-1} respectively, see Subsec. 4.1.5. Then, for each point in the simulated grid, F_L values
 2949 for protons and nuclei are generated using the (Glauberized) 5-flavor GBW model [335]. The relative
 2950 uncertainties are taken to be exactly the same as in the ep simulation, as explained above.

2951 In Fig. 5.18 we show several predictions for the nuclear suppression factor, Eq. (5.5), with respect to
 2952 the proton, for the total and longitudinal structure functions, F_2 and F_L respectively, in $e\text{Pb}$ collisions at
 2953 an example $Q^2 = 5 \text{ GeV}^2$ and for $10^{-5} < x < 0.1$. Predictions based on global DGLAP analyses of existing
 2954 data at NLO: nDS, HKN07, EPS09 and DSSZ [152, 312–314], plus those from models using the relation
 2955 between diffraction and nuclear shadowing, AKST and FGS10 [217, 315], are shown together with the LHeC
 2956 pseudodata. Brief explanations on the different models can be found in Subsec. 5.1.4. Clearly, the accuracy
 2957 of the data at the LHeC will offer huge possibilities for discriminating between different models and for
 2958 constraining the dynamics underlying nuclear shadowing at small x .

2959 In order to better quantify how the LHeC would improve the present situation concerning nuclear PDFs

⁹In this document we have restricted the discussion and results to Pb because it is the presently accelerated ion at the LHC. But simulations also exist for a Ca nucleus of 3500 GeV per nucleon, and they can be easily produced for other nuclei as Ar (3150 GeV per nucleon), whose acceleration at the LHC has been discussed as part of the AA program [288].

¹⁰A significant difference in the systematics may eventually come from the different size of the QED radiative corrections for protons and nuclei, an important point which remains to be addressed in future studies.




Figure 5.16: The kinematic coverage of the LHeC pseudodata used in the present studies, together with the data already included in the reference NNPDF1.0 dataset.

2960 in global DGLAP analyses (see the uncertainty band in Fig. 5.12), nuclear LHeC pseudodata have been
 2961 included in the global EPS09 analysis [152]. The DGLAP evolution was carried out at NLO accuracy, in the
 2962 variable-flavor-number scheme (SACOT prescription) with the CTEQ6.6 [265] set for free proton PDFs as a
 2963 baseline. See [152] and references therein for further details. The only difference compared with the original
 2964 EPS09 setup is that one additional gluon parameter, x_a , has been varied (this parameter was originally
 2965 frozen in EPS09), and the only additionally weighted data set was the PHENIX data on π^0 production at
 2966 mid-rapidity [336] in dAu collisions at RHIC.

2967 Two different fits have been performed: the first one (Fit 1) includes pseudodata on the total reduced
 2968 cross section. The results of the fit are shown in Fig. 5.19 in terms of the nuclear modification factors for
 2969 the parton densities. A large improvement in the determination of sea quark and gluon densities at small x
 2970 is evident.

2971 The second fit (Fit 2) includes not only nuclear LHeC pseudodata on the total reduced cross section
 2972 but also on its charm and beauty components. These data provide direct information on the nuclear effects
 2973 on charm and beauty parton densities, which are generated mainly dynamically from the gluons through
 2974 DGLAP evolution. Thus, the inclusion of such pseudodata further improves the determination of the nuclear
 2975 effects on the gluon at small x , as illustrated in Fig. 5.20.

2976 In both Figs. 5.19 and 5.20 a sizable reduction of the uncertainties in the sea quark and gluon nuclear
 2977 parton distributions at large $x > 0.1$ can also be observed. This improvement is basically due to the
 2978 constraints imposed by sum rules and to the fact that DGLAP evolution links large and small x . Although
 2979 the study of parton distributions at large x is not the subject of this chapter, it is worth commenting
 2980 that F_2 could be measured in eA collisions at the LHeC with a statistical accuracy better than a few
 2981 percent up to $x \sim 0.6$ but for large $Q^2 > 1000 \text{ GeV}^2$. On the other hand, flavor decomposition will only
 2982 be accessible for $x < 0.1$. Therefore, the LHeC will provide additional information on the antishadowing
 2983 ($R > 1$, $0.1 < x < 0.3$) and - with less precision - on the EMC-effect ($R < 1$, $0.3 < x < 0.8$) regions. The
 2984 latter is valence-dominated and there exist data from fixed target experiments, though at much smaller Q^2 ,
 2985 so at the LHeC the validity of leading-twist DGLAP evolution will be tested.




Figure 5.17: The results for F_L obtained from the best NLO DGLAP fit to the standard NNPDF1.2 data set, together with the LHeC pseudodata for $F_2(x, Q^2)$ and $F_L(x, Q^2)$ generated with the (saturating) AAMS09 model. The fit results are compared with the input AAMS09 F_L pseudodata.

2986 Furthermore, the large lever-arm in Q^2 opens the possibility of measuring CC events in electron scattering
 2987 on nuclear targets, thus helping to improve the loose constraints on the flavour decomposition of the nuclear
 2988 parton densities coming from existing DIS and DY data. In this respect (see the comments in Subsec.
 2989 5.1.4) the LHeC may help to clarify the issue of the compatibility of the nuclear corrections extracted in
 2990 neutrino-nucleus collisions with those coming from electron- or muon-nucleus collisions¹¹.

2991 In conclusion, the precision and large lever-arm in x and Q^2 of the nuclear data at the LHeC will offer huge
 2992 possibilities for discriminating different models and for constraining the parton densities in global DGLAP
 2993 analyses. Besides measurements of the reduced cross section, data on its charm and bottom components
 2994 and on F_L will help to constrain the nuclear effects on PDFs, see e.g. the recent work in [338, 339].

2995 5.2.3 Exclusive Production

2996 Introduction

2997 Exclusive processes such as the electroproduction of vector mesons and photons, $\gamma^* N \rightarrow VN (V = \rho^0, \phi, \gamma)$, or
 2998 photoproduction of heavy quarkonia, $\gamma N \rightarrow VN (V = J/\psi, \Upsilon)$ - see Fig. 5.21 - provide information on nucleon
 2999 structure and small- x dynamics which is complementary to that obtained in inclusive measurements [244].
 3000 The exclusive production of J/ψ and ρ mesons in ep collisions and Deeply-Virtual Compton Scattering

¹¹Note that the nuclear modifications of the structure function F_2 in these two types of process are expected to differ due to the different coupling to quarks [337].




Figure 5.18: Predictions from different models for the nuclear modification factor, Eq. (5.5) for Pb with respect to the proton, for $F_2(x, Q^2 = 5 \text{ GeV}^2)$ (plot on the left) and $F_L(x, Q^2 = 5 \text{ GeV}^2)$ (plot on the right) versus x , together with the corresponding LHeC pseudodata. Dotted lines correspond to the nuclear PDF set EPS09 [152], dashed ones to nDS [312], solid ones to HKN07 [313], dashed-dotted ones to FGS10 [315], dashed-dotted-dotted ones to AKST [217] and long dashed-dotted ones to DSSZ [314] (only for F_2). The band corresponds to the uncertainty in the Hessian analysis in EPS09 [152].

3001 (DVCS, $ep \rightarrow e\gamma p$), have been particularly prominent in the development of our understanding of HERA
 3002 physics [340].

3003 Diffractive channels such as these are favourable, since the underlying exchange crudely equates to a
 3004 pair of gluons, making the process sensitive to the square of the gluon density [341], in place of the linear
 3005 dependence for F_2 or F_L . With a sufficiently good theoretical understanding of the exclusive production
 3006 mechanism, this may enhance substantially the sensitivity to non-linear evolution and saturation phenomena.
 3007 As already shown at HERA, J/Ψ production in particular is a potentially very clean probe of the gluonic
 3008 structure of the hadron [262,341]. The same exclusive processes can be measured in deep inelastic scattering
 3009 off nuclei, where the gluon density is modified by nuclear effects [342]. In addition, exclusive processes
 3010 give access to the spatial distribution of the gluon density, parametrized by the impact parameter [343]
 3011 of the collision. The correlations between the gluons coupling to the proton contain information on the
 3012 three-dimensional structure of the nucleon or nucleus, which is encoded in the Generalised Parton Densities
 3013 (GPDs). The GPDs combine aspects of parton densities and elastic form factors and have emerged as a key
 3014 concept for describing nucleon structure in QCD (see [55,344,345] for a review).

3015 Exclusive processes can be treated conveniently within the dipole picture described in Subsec. 5.1.2. In
 3016 this framework, the cross section can be represented as a product of three factorisable terms: the splitting
 3017 of an incoming photon into a $q\bar{q}$ dipole; the ‘dipole’ cross section for the interaction of this $q\bar{q}$ pair with the
 3018 proton and, in the case of vector mesons, a wave function term for the projection of the dipole onto the
 3019 meson. As discussed in Subsec. 5.1.2 the dipole formalism is particularly convenient since saturation effects
 3020 can be easily incorporated.

3021 Generalised Parton Densities and Spatial Structure

3022 At sufficiently large Q^2 the exclusively produced meson or photon is in a configuration of transverse size
 3023 much smaller than the typical hadronic size, $r_\perp \ll R_{\text{hadron}}$. As a result its interaction with the target can
 3024 be described using perturbative QCD [346]. A QCD factorisation theorem [347] states that the exclusive
 3025 amplitudes in this regime can be factorised into a perturbative QCD scattering process and certain universal
 3026 process-independent functions describing the emission and absorption of the active partons by the target,
 3027 the generalized parton distributions (GPDs).

3028 Let us briefly review (see [55,344,345] for details) the definition of GPDs and their relation to the
 3029 ordinary parton densities discussed in detail in Chapter 4. The parton distributions of the proton (or any




Figure 5.19: Ratio of parton densities for protons bound in Pb to those in a free proton, for valence u (left), \bar{u} (middle) and g (right), at $Q^2 = 1.69$ (top) and 100 (bottom) GeV^2 . The dark grey band corresponds to the uncertainty band using the Hessian method in the original EPS09 analysis [152], while the light blue band corresponds to the uncertainty obtained after including nuclear LHeC pseudodata on the total reduced cross sections (Fit 1). The dotted lines indicate the values corresponding to the different nPDF sets in the EPS09 analysis [152].

3030 other hadron) are given by the diagonal matrix elements $\langle P, \lambda | \hat{O} | P, \lambda \rangle$, where P and λ are the 4-momentum
3031 and helicity of the proton, and \hat{O} is a twist-2 quark or gluon operator. However, there is new information in
3032 the GPDs defined in terms of the off-diagonal matrix elements $\langle P', \lambda' | \hat{O} | P, \lambda \rangle$. Unlike the diagonal PDFs,
3033 the GPDs cannot be regarded as parton densities, but are to be interpreted as probability amplitudes.

3034 The physical significance of GPDs is best seen using light-cone coordinates, $z^\pm = (z^0 \pm z^3)/\sqrt{2}$, and in
3035 the light-cone gauge, $A^+ = 0$. It is conventional to define the generalised quark distributions in terms of
3036 quark operators at light-like separation, resulting in

$$F_q(x, \xi, t) = \frac{1}{2\bar{P}^+} \left[H_q((x, \xi, t) \bar{u}(P') \gamma^+ u(P) + E_q((x, \xi, t) \bar{u}(P') \frac{i\sigma^{+\alpha} \Delta_\alpha}{2m} u(P) \right] \quad (5.6)$$

3037 with $\bar{P} = (P + P')/2$ and $\Delta = P' - P$, and where we have suppressed the helicity labels of the protons
3038 and spinors. We now have two extra kinematic variables: $t = \Delta^2$, $\xi = -\Delta^+/(P + P')^+$. We see that
3039 $-1 \leq \xi \leq 1$. Similarly, we may define GPDs \tilde{H}_q and \tilde{E}_q with an additional γ_5 between the quark operators
3040 in Eq. (5.6); and also an analogous set of gluon GPDs, H_g , E_g , \tilde{H}_g and \tilde{E}_g . These definitions correspond to
3041 helicity-conserving GPDs. Analogous definitions exist for helicity-flip (transversity), chiral-odd GPDs H_T ,
3042 E_T , \tilde{H}_T , \tilde{E}_T [348].




Figure 5.20: Ratio of the gluon density for protons bound in Pb to that of a free proton at $Q^2 = 1.69 \text{ GeV}^2$. The red band corresponds to the uncertainty using the Hessian method in the original EPS09 analysis [152], while the dark brown band corresponds to the uncertainty obtained after including nuclear LHeC pseudodata on the total reduced cross sections (Fit 1), and the light blue band shows the uncertainty obtained after further including pseudodata on charm and beauty reduced cross sections (Fit 2).

3043 For $P' = P$, $\lambda' = \lambda$ the matrix elements reduce to the ordinary PDFs:

$$\begin{aligned}
 H_q(x, 0, 0) &= q(x), & H_q(-x, 0, 0) &= -\bar{q}(x), & H_g(x, 0, 0) &= xg(x), \\
 \tilde{H}_q(x, 0, 0) &= \Delta q(x), & \tilde{H}_q(-x, 0, 0) &= \Delta \bar{q}(x), & \tilde{H}_g(x, 0, 0) &= x\Delta g(x), \\
 H_T(x, 0, 0) &= \Delta_T q(x),
 \end{aligned}
 \tag{5.7}$$

3044 where Δq ($\Delta_T q(x)$) is the difference between quark densities with opposite helicities (transversities). No
 3045 corresponding relations exist for E , \tilde{E} , E_T , \tilde{H}_T , \tilde{E}_T as they decouple in the forward limit, $\Delta = 0$. For
 3046 properties of all these distributions, see the reviews [55, 344, 345].

3047 For the evolution of the GPDs, there are two types of domain: (i) the time-like domain, with $|x| < |\xi|$,
 3048 where the GPDs describe the wave functions of a t-channel $q\bar{q}$ (or gluon) pair and evolve according to
 3049 modified ERBL equations [349, 350]; (ii) the space-like domain, with $|x| > |\xi|$, where the GPDs generalise
 3050 the familiar q , \bar{q} (and gluon) PDFs and describe DVCS and exclusive vector meson production, and evolve
 3051 according to modified DGLAP equations. The splitting functions for the evolutions of GPDs are known to
 3052 NLO [351].

3053 The GPDs contain new information about proton structure and should be determined from experiment.
 3054 We can parametrise them in terms of 'double distributions' [352, 353], which reduce to diagonal PDFs as
 3055 $\xi \rightarrow 0$. With an additional physically reasonable 'Regge' assumption of no extra singularity at $\xi = 0$, GPDs
 3056 at low ξ are uniquely given in terms of diagonal PDFs to $\mathcal{O}(\xi)$ [354]. Alternatively, flexible $SO(3)$ -based
 3057 parametrisations have been used to determine GPDs from DVCS data [355].

3058 The Fourier transform of the GPDs with respect to the transverse momentum transferred to the nucleon
 3059 describes the transverse spatial distribution of partons (illustrated in Fig. 5.3) with a given longitudinal




Figure 5.21: Schematic illustration of the exclusive vector meson production process and the kinematic variables used to describe it in photoproduction ($Q^2 \rightarrow 0$) and DIS (large Q^2). The outgoing particle labelled ‘VM’, may be either a vector meson with $J^{PC} = 1^{--}$ or a photon.

3060 momentum fraction x [356–358]. The transverse spatial distributions of quarks and gluons are fundamental
 3061 characteristics of the nucleon, which reveal the size of the configurations in its partonic wave function and
 3062 allow the study of the non-perturbative dynamics governing their change with x , such as Gribov diffusion,
 3063 chiral dynamics, and other phenomena. The nucleon transverse gluonic size is also an essential input in
 3064 studies of saturation at small x . It determines the initial conditions of the non-linear QCD evolution equations
 3065 and thus directly influences the impact parameter dependence of the saturation scale for the nucleon [261,
 3066 359], which in turn predicates its nuclear enhancement [360]. Information on the nucleon transverse quark
 3067 and gluon distributions is further required in the phenomenology of high-energy pp collisions with hard
 3068 processes, including those with new particle production, where it determines the underlying event structure
 3069 (centrality dependence) in inclusive scattering [361] and the rapidity gap survival probability in hard single
 3070 diffraction [362] and central exclusive diffraction [363,364]. In view of its considerable interest, the transverse
 3071 quark/gluon imaging of the nucleon with exclusive processes has been recognized as an important objective
 3072 of nucleon structure and small- x physics.

3073 Mapping the transverse spatial distribution of quarks and gluons requires measurement of the t -dependence
 3074 of hard exclusive processes up to large values of $|t|$, of the order of 1 GeV^2 . Studies of the Q^2 -dependence
 3075 and comparisons between different channels provide crucial tests of the reaction mechanism and the uni-
 3076 versality of GPDs. Vector meson production at small x and heavy quarkonium photoproduction at high
 3077 energies probe the gluon GPD of the target, while real photon production (DVCS) involves the singlet quark
 3078 as well as the gluon GPDs. Measurements of exclusive J/ψ photo/electroproduction [365,366] and ρ^0 and
 3079 ϕ electroproduction at HERA have confirmed the applicability of the factorized QCD description through
 3080 several model-independent tests, and have provided basic information on the nucleon gluonic size in the
 3081 region $10^{-4} < x < 10^{-2}$ and its change with x [244]. Measurements of DVCS at HERA [367,368] hint that
 3082 the transverse distribution of singlet quarks may extend further than that of gluons. While these experi-
 3083 ments have given important insight into transverse nucleon structure, the interpretation of the HERA data
 3084 is limited by the low statistics which preclude a fully differential analysis. A major source of systematic
 3085 uncertainty at larger t arises from the lack of a complete separation between elastically scattered protons

3086 and proton excitations, illustrating the importance of good scattered proton detection at the LHeC.

3087 As discussed in the following, the LHeC would enable a comprehensive program of gluon and singlet
 3088 quark transverse imaging through exclusive processes, with numerous applications to nucleon structure and
 3089 small- x physics. The high statistics would permit fully differential measurements of exclusive channels, as
 3090 needed to understand the reaction mechanism. For example, measurements of the t -distributions for fixed
 3091 x differentially in Q^2 are needed to confirm the dominance of small-size configurations. The LHeC would
 3092 also push such measurements to the region $Q^2 \sim \text{few} \times 10 \text{ GeV}^2$ where finite-size (higher-twist) effects are
 3093 small and the effects of QCD evolution can be cleanly identified. Measurements of gluonic exclusive channels
 3094 ($J/\psi, \phi, \rho^0$) at the LHeC would provide gluonic transverse images of the nucleon down to $x \sim 10^{-6}$ with
 3095 unprecedented accuracy, testing theoretical ideas about diffusion dynamics in the wave function. Because
 3096 exclusive cross sections are proportional to the square of the gluon GPD (i.e. the gluon density), such
 3097 measurements would also offer new insight into non-linear effects in QCD evolution, and enable new tests of
 3098 the approach to saturation by measuring the impact parameter dependence of the saturation scale. Along
 3099 these lines, saturation effects in the exclusive vector meson production on protons and nuclei have been
 3100 studied in [342, 369–371]. Furthermore, measurements of DVCS would provide additional information on
 3101 the nucleon singlet quark size and its dependence on x . Besides its intrinsic interest for nucleon structure
 3102 and small- x physics, this information would greatly advance our theoretical understanding of the transverse
 3103 geometry of high-energy pp collisions at the LHC. We note that these exclusive measurements at the LHeC
 3104 would complement similar measurements at moderately small x ($0.003 < x < 0.2$) with the COMPASS
 3105 experiment at CERN and in the valence region $x > 0.1$ with the JLab 12 GeV Upgrade, providing a
 3106 comprehensive picture of the nucleon spatial structure.

3107 Further interesting information comes from hard exclusive measurements accompanied by the diffractive
 3108 dissociation of the nucleon, $\gamma^* N \rightarrow V + Y$ ($Y = \text{low-mass proton dissociation state}$). The ratio of inelastic to
 3109 elastic diffraction in these processes provides information on the quantum fluctuations of the gluon density,
 3110 which reveals the quantum-mechanical nature of the non-perturbative colour fields in the nucleon and can
 3111 be related to dynamical models of low-energy nucleon structure [372]. HERA results are in qualitative
 3112 agreement with such model predictions but do not permit a quantitative analysis. These measurements of
 3113 exclusive diffraction at the LHeC, and similar ones for eA collisions, would allow for detailed quantitative
 3114 studies of all these new aspects of nucleon and nuclear structure.

3115 Exclusive Production Formalism in the Dipole Approach

3116 For the exclusive production of vector mesons, a QCD factorization theorem has been demonstrated (for σ_L)
 3117 in [346]. The dipole model follows from this QCD factorization theorem in the LO approximation. Within
 3118 the dipole model, see Subsec. 5.1.2, the amplitude for the exclusive diffractive production of a particle E ,
 3119 $\gamma^* p \rightarrow Ep$, shown in Fig. 5.22(a), can be expressed as

$$3120 \mathcal{A}_{T,L}^{\gamma^* p \rightarrow E+p}(x, Q, \Delta) = i \int d^2 \mathbf{r} \int_0^1 \frac{dz}{4\pi} \int d^2 \mathbf{b} (\Psi_E^* \Psi)_{T,L} e^{-i[\mathbf{b} - (1-z)\mathbf{r}] \cdot \Delta} \frac{d\sigma_{q\bar{q}}}{d^2 \mathbf{b}}. \quad (5.8)$$

3120 Here $E = V$ for vector meson production, or $E = \gamma$ for deeply virtual Compton scattering (DVCS). In Eq.
 3121 (5.8), z is the fraction of the photon's light-cone momentum carried by the quark, $r = |\mathbf{r}|$ is the transverse
 3122 size of the $q\bar{q}$ dipole, while \mathbf{b} is the impact parameter, that is, $b = |\mathbf{b}|$ is the transverse distance from the centre
 3123 of the proton to the centre-of-mass of the $q\bar{q}$ dipole; see Fig. 5.22(a). The transverse momentum lost by the
 3124 outgoing proton, Δ , is the Fourier conjugate variable to the impact parameter \mathbf{b} , and $t \equiv (p - p')^2 = -\Delta^2$.
 3125 The forward overlap function between the initial-state photon wave function and the final-state vector meson
 3126 or photon wave function in Eq. (5.8) is denoted $(\Psi_E^* \Psi)_{T,L}$, while the factor $\exp[i(1-z)\mathbf{r} \cdot \Delta]$ originates from
 3127 the non-forward wave function [373]. The differential cross section for an exclusive diffractive process is
 3128 obtained from the amplitude, Eq. (5.8), by

$$\frac{d\sigma_{T,L}^{\gamma^* p \rightarrow E+p}}{dt} = \frac{1}{16\pi} \left| \mathcal{A}_{T,L}^{\gamma^* p \rightarrow E+p} \right|^2, \quad (5.9)$$




Figure 5.22: Parton level diagrams representing the γ^*p scattering amplitude proceeding via (a) single-Pomeron and (b) multi-Pomeron exchange, where the perturbative QCD Pomeron is represented by a gluon ladder. For exclusive diffractive processes, such as vector meson production ($E = V$) or DVCS ($E = \gamma$), we have $x' \ll x \ll 1$ and $t = (p - p')^2$. These diagrams are related through the optical theorem to inclusive DIS, where $E = \gamma^*$, $x' = x \ll 1$ and $p' = p$.

3129 up to corrections from the real part of the amplitude and from skewedness ($x' \ll x \ll 1$ for the variables
3130 shown in figure 5.22a). Taking the imaginary part of the forward scattering amplitude immediately gives
3131 the formula for the total γ^*p cross section (or equivalently, the proton structure function $F_2 = F_T + F_L$) via
3132 the optical theorem:

$$\sigma_{T,L}^{\gamma^*p}(x, Q) = \text{Im} \mathcal{A}_{T,L}^{\gamma^*p \rightarrow \gamma^*p}(x, Q, \Delta = 0) = \sum_f \int d^2\mathbf{r} \int_0^1 \frac{dz}{4\pi} (\Psi^* \Psi)_{T,L}^f \int d^2\mathbf{b} \frac{d\sigma_{q\bar{q}}}{d^2\mathbf{b}}. \quad (5.10)$$

3133 The dipole picture therefore provides a unified description of both exclusive diffractive processes and inclusive
3134 DIS at small x .

3135 The unknown quantity common to Eqs. (5.8) and (5.10) is the b -dependent dipole–proton cross section,

$$\frac{d\sigma_{q\bar{q}}}{d^2\mathbf{b}} = 2 \mathcal{N}(x, r, b), \quad (5.11)$$

3136 where \mathcal{N} is the imaginary part of the dipole–proton scattering amplitude, which can vary between zero and
3137 one, with $\mathcal{N} = 1$ corresponding to the unitarity (“black disk”) limit. The scattering amplitude \mathcal{N} encodes
3138 the information about the details of the strong interaction between the dipole and the target (proton or
3139 nucleus). It is generally parameterised according to some theoretically-motivated functional form, with the
3140 parameters fitted to data. Most dipole models assume a factorised b dependence, $\mathcal{N}(x, r, b) = T(b)\mathcal{N}(x, r)$,
3141 with $\mathcal{N}(x, r) \in [0, 1]$ and, for example, $T(b) = \Theta(R_p - b)$, so that the b -integrated $\sigma_{q\bar{q}} = (2\pi R_p^2)\mathcal{N}(x, r)$.
3142 However, the “saturation scale” is strongly dependent on impact parameter and the chosen of b -dependence
3143 must be made consistent with the t -dependence of exclusive diffraction at HERA. This matching is compli-
3144 cated by the non-zero effective “Pomeron slope” α'_p measured at HERA, which implies a correlation between
3145 the x - and b -dependences of $\mathcal{N}(x, r, b)$. Therefore, for accurate results, $\mathcal{N}(x, r, b)$ should be determined from
3146 the simultaneous description of inclusive DIS and exclusive diffractive processes.

3147 An impact-parameter-dependent saturation (“b-sat”) model [261, 262] has been shown to describe very
3148 successfully a broad range of HERA data on exclusive diffractive vector meson (J/ψ , ϕ , ρ) production and
3149 DVCS (see also the rather different approach in [374]), including almost all aspects of the Q^2 , W and t
3150 dependence with the exception of α'_p , together with the inclusive structure functions F_2 , $F_2^{c\bar{c}}$, $F_2^{b\bar{b}}$ and F_L .
3151 The “b-Sat” parameterisation is based on LO DGLAP evolution of an initial gluon density, $xg(x, \mu_0^2) =$
3152 $A_g x^{-\lambda_g} (1 - x)^{5.6}$, with a Gaussian impact parameter dependence, $T(b) \propto \exp(-b^2/2B_G)$. The dipole

3153 scattering amplitude is parametrized as

$$\mathcal{N}(x, r, b) = 1 - \exp\left(-\frac{\pi^2}{2N_c} r^2 \alpha_S(\mu^2) x g(x, \mu^2) T(b)\right), \quad (5.12)$$

3154 where the scale $\mu^2 = 4/r^2 + \mu_0^2$, $B_G = 4 \text{ GeV}^{-2}$ was fixed from the t -slope of exclusive J/ψ photoproduction
 3155 at HERA, and the other three parameters ($\mu_0^2 = 1.17 \text{ GeV}^2$, $A_g = 2.55$, $\lambda_g = 0.020$) were fitted to ZEUS
 3156 F_2 data with $x_{Bj} \leq 0.01$ and $Q^2 \in [0.25, 650] \text{ GeV}^2$ [262]. The eikonalised dipole scattering amplitude of
 3157 Eq. (5.12) can be expanded as

$$\mathcal{N}(x, r, b) = \sum_{n=1}^{\infty} \frac{(-1)^{n+1}}{n!} \left[\frac{\pi^2}{2N_c} r^2 \alpha_S(\mu^2) x g(x, \mu^2) T(b) \right]^n, \quad (5.13)$$

3158 where the n -th term in the expansion corresponds to n -Pomeron exchange; for example, the case $n = 3$ is
 3159 illustrated in Fig. 5.22(b). The terms with $n > 1$ are necessary to ensure unitarity.

3160 Simulations of LHeC Elastic J/ψ and Υ Production

3161 Due to the extremely clean final states produced, the relatively low effective x -values ($x_{\text{eff}} \sim (Q^2 + m_V^2)/(Q^2 +$
 3162 $W^2)$) and scales ($Q_{\text{eff}}^2 \sim (Q^2 + m_V^2)/4$) accessed [341, 375], and the experimental possibility of varying both
 3163 W and t over wide ranges, J/ψ photoproduction ($Q^2 \rightarrow 0$) may offer the cleanest available signature to study
 3164 the transition between the dilute and dense regimes of small- x partons. It should be possible to detect the
 3165 muons from J/ψ or Υ decays with acceptances extending to within 1° of the beampipe with dedicated muon
 3166 chambers on the outside of the experiment. Depending on the electron beam energy, this makes invariant
 3167 photon-proton masses W of well beyond 1 TeV accessible.

3168 For the analysis presented here we concentrate on the photoproduction limit, where the HERA data are
 3169 most precise due to the large cross sections and where unitarity effects are most important. Studies have
 3170 also been made at larger Q^2 [376], where the extra hard scale additionally allows a perturbative treatment
 3171 of exclusive light vector meson (e.g. ρ , ω , ϕ) production. Again, perturbative unitarity effects are expected
 3172 to be important for light vector meson production when $Q^2 \gtrsim 1 \text{ GeV}^2$ is not too large.

3173 LHeC pseudodata for elastic J/ψ and Υ photoproduction and electroproduction have been generated
 3174 using the DIFFVM Monte Carlo generator [377] under the assumption of 1° acceptance and a variety
 3175 of luminosity scenarios. The DIFFVM generator involves a simple Regge-based parameterization of the
 3176 dynamics and a full treatment of decay angular distributions. Statistical uncertainties are estimated for
 3177 each data point. Systematic uncertainties are hard to estimate without a detailed simulation of the muon
 3178 identification and reconstruction capabilities of the detector, but are likely to be at least as good as the 10%
 3179 measurements typically achieved for the elastic J/ψ at HERA.

3180 The plots in Fig. 5.23 show t -integrated predictions for exclusive J/ψ photoproduction ($Q^2 = 0$) obtained
 3181 from Eqs. (5.8) and (5.9), using the eikonalised “b-Sat” dipole scattering amplitude given in Eq. (5.12)
 3182 together with a “boosted Gaussian” vector meson wave function [262, 378]. Also shown is the single-Pomeron
 3183 exchange contribution obtained by keeping just the first ($n = 1$) term in the expansion of Eq. (5.13), such
 3184 that the scattering amplitude is linearly dependent on the gluon density, without refitting any of the input
 3185 parameters.

3186 The difference between the “eikonalised” and “1-Pomeron” predictions therefore indicates the importance
 3187 of unitarity corrections, which increase significantly with rising γp centre-of-mass energy W . The maximum
 3188 kinematic limit accessible at the LHeC, $W = \sqrt{s}$, is indicated with different options for electron beam
 3189 energies (E_e) and not accounting for the angular acceptance of the detector. The most precise HERA
 3190 data [366, 379] are overlaid, together with sample LHeC pseudodata points, assuming 1° muon acceptance,
 3191 with the errors (statistical only) given by an LHeC simulation with $E_e = 150 \text{ GeV}$. The central values of the
 3192 LHeC pseudodata points were obtained from a Gaussian distribution with the mean given by extrapolating
 3193 a power-law fit to the HERA data [366, 379] and the standard deviation given by the statistical errors
 3194 from the LHeC simulation. The plots in Fig. 5.23 show that the errors on the LHeC pseudodata are much





Figure 5.23: LHeC exclusive J/ψ photoproduction pseudodata, as a function of the γp centre-of-mass energy W , plotted on a (top) log–log scale and (bottom) linear–linear scale. The difference between the solid and dashed curves indicates the size of unitarity corrections according to the b-Sat dipole model.




Figure 5.24: LHeC exclusive Υ photoproduction pseudodata, as a function of the γp centre-of-mass energy W , plotted on a log–log scale. The difference between the solid and dashed curves indicates the size of unitarity corrections according to the b-Sat model. The b-Sat theory predictions have been scaled by a factor 2.16 to best-fit the existing HERA data.

3195 smaller than the difference between the “eikonalised” and “1-Pomeron” predictions. Therefore, exclusive
 3196 J/ψ photoproduction at the LHeC may be an ideal observable for investigating unitarity corrections at a
 3197 perturbative scale provided by the charm-quark mass.

3198 Similar plots for exclusive Υ photoproduction are shown in Fig. 5.24. Here, the unitarity corrections are
 3199 smaller than for J/ψ production due to the larger scale provided by the bottom-quark mass and therefore the
 3200 smaller typical dipole sizes r being probed. The simulated LHeC pseudodata points also have larger statistical
 3201 errors than for J/ψ production due to the much smaller cross sections. Nonetheless, the simulations indicate
 3202 that a huge improvement in kinematic range and precision is possible compared with the very sparse Υ data
 3203 from HERA [380–382].

3204 In order to achieve a satisfactory description of the experimental data on exclusive Υ photoproduction,
 3205 an additional normalization factor of ~ 2 has to be included in the dipole calculation (a similar factor is
 3206 required for other calculations using the dipole model, see for example Ref. [383]). This normalization factor
 3207 does not arise from any theoretical considerations. Therefore, the dipole model prediction for the Υ in
 3208 diffractive exclusive processes in DIS still poses significant theoretical questions which cannot be resolved
 3209 without LHeC data.

3210 The cross sections shown in Figs. 5.23 and 5.24 are integrated over $t \equiv (p - p')^2 = -\Delta^2$, where Δ is
 3211 the Fourier conjugate variable to the impact parameter \mathbf{b} . One expects that at high center-of-mass energies
 3212 (small x), saturation effects are most important close to the centre of the proton (small b), where the
 3213 interaction region is densest. This is illustrated in Fig. 5.25(a) where the b-Sat model dipole scattering
 3214 amplitude is shown as a function of b for various x values. By measuring exclusive diffraction in bins of $|t|$
 3215 one can extract the impact parameter profile of the interaction region. This is illustrated in Fig. 5.25(b)
 3216 where the integrand of Eq. (5.8) is shown for different values of t as a function of impact parameter. Clearly
 3217 for large values of $|t|$, small values of b are probed in the impact parameter profile, corresponding to the most
 3218 densely populated region, where saturation effects should be most clearly visible. Indeed, the eikonalised
 3219 dipole model of Eq. (5.12) leads to “diffractive dips” in the t -distribution of exclusive J/ψ photoproduction




Figure 5.25: (a) The imaginary part of the dipole scattering amplitude, $\mathcal{N}(x, r, b)$, as a function of the impact parameter b , for fixed values of dipole size $r = 1 \text{ GeV}^{-1}$ (typical for exclusive J/ψ photoproduction) and different x values. (b) The (r -integrated) amplitude - the integrand of Eq. (5.8) - for exclusive J/ψ photoproduction as a function of b , for $W = 300 \text{ GeV}$ and $|t| = 0, 1, 2, 3, 4 \text{ GeV}^2$.

3220 at large $|t|$ (reminiscent of the dips seen in the t -distribution of the proton-proton elastic cross section),
 3221 departing from the exponential fall-off in the t -distribution seen with single-Pomeron exchange [261]. The
 3222 HERA experiments have only been able to make precise measurements of exclusive J/ψ photoproduction at
 3223 relatively small $|t| \lesssim 1 \text{ GeV}^2$, and no significant departure from the exponential fall-off, $d\sigma/dt \sim \exp(-B_D|t|)$,
 3224 has been observed.

3225 In Fig. 5.26, LHeC pseudodata on the differential cross section $d\sigma/dt$ is shown as a function of the
 3226 energy W in different bins of t for the case of exclusive J/Ψ production. Again two different b-Sat model
 3227 scenarios are shown, with unitarisation effects and with single Pomeron exchange. Already for small values of
 3228 $|t| \sim 0.2 \text{ GeV}^2$ and low values of electron energies there is a large discrepancy between the models. The LHeC
 3229 simulated data still have very small errors in this regime, and can clearly distinguish between the different
 3230 models. The differences are of course amplified for large t and large electron beam energies. However the
 3231 precision of the data deteriorates at large t .

3232 Summarising, it is clear that the precise measurements of large- $|t|$ exclusive J/ψ photoproduction at the
 3233 LHeC would have significant sensitivity to unitarity effects.

3234 Simulations of Deeply Virtual Compton Scattering at the LHeC

3235 Simulations of the DVCS measurement possibilities with the LHeC have been made using the Monte Carlo
 3236 generator MILOU [384], in the 'FFS option', for which the DVCS cross section is estimated using the model
 3237 of Frankfurt, Freund and Strikman [385]. A t -slope of $B = 6 \text{ GeV}^{-2}$ is assumed.

3238 The $ep \rightarrow e\gamma p$ DVCS cross section is estimated in various scenarios for the electron beam energy and
 3239 the statistical precision of the measurement is estimated for different integrated luminosity and detector
 3240 acceptance choices. Detector acceptance cuts at either 1° or 10° are placed on the polar angle of the final
 3241 state electron and photon. Based on experience with controlling backgrounds in HERA DVCS measurements




Figure 5.26: Simulated LHeC measurements of the W -dependence of exclusive J/ψ photoproduction at the LHeC, differentially in bins of $|t| = 0.10, 0.20, 0.49, 1.03, 1.75$ GeV². The difference between the solid and dashed curves indicates the size of unitarity corrections according to the b-Sat dipole model. The central values of the LHeC pseudodata points were obtained from a Gaussian distribution with the mean given by extrapolating a parameterization of HERA data and the standard deviation given by the statistical errors from the LHeC simulation with $E_e = 150$ GeV. The t -integrated cross section (σ) as a function of W for the HERA parameterization was obtained from a power-law fit to the data from both ZEUS [379] and H1 [366], then the t -distribution was assumed to behave as $d\sigma/dt = \sigma \cdot B_D \exp(-B_D|t|)$, with $B_D = [4.400 + 4 \cdot 0.137 \log(W/90 \text{ GeV})]$ GeV⁻² obtained from a linear fit to the values of B_D versus W given by both ZEUS [379] and H1 [366].




Figure 5.27: Simulated LHeC measurement of the DVCS cross section multiplied by Q^4 for different x values for a luminosity of 1 fb^{-1} , with $E_e = 50 \text{ GeV}$, and electron and photon acceptance extending to within 1° of the beampipe with a cut at $P_T^\gamma = 2 \text{ GeV}$. Only statistical uncertainties are considered.

[367, 368, 386], an additional cut is placed on the transverse momentum P_T^γ of the final state photon.

The kinematic limitations due to the scattered electron acceptance follow the same patterns as for the inclusive cross section (see Subsec. 5.2.2). The photon P_T^γ cut is found to be a further important factor in the Q^2 acceptance, with measurements at $Q^2 < 20 \text{ GeV}^2$ almost completely impossible for a cut at $P_T^\gamma > 5 \text{ GeV}$, even in the scenario with detector acceptances reaching 1° . If this cut is relaxed to $P_T^\gamma > 2 \text{ GeV}$, it opens the available phase space towards the lowest Q^2 and x values permitted by the electron acceptance.

A simulation of a possible LHeC DVCS measurement double differentially in x and Q^2 is shown in Fig. 5.27 for a very modest luminosity scenario (1 fb^{-1}) in which the electron beam energy is 50 GeV , the detector acceptance extends to 1° and photon measurements are possible down to $P_T^\gamma = 2 \text{ GeV}$. High precision is possible throughout the region $2.5 < Q^2 < 40 \text{ GeV}^2$ for x values extending down to $\sim 5 \times 10^{-5}$. The need to measure DVCS therefore places constraints on the detector performance for low transverse momentum photons, which in practice translates into the electromagnetic calorimetry noise conditions and response linearity at low energies.

If the detector acceptance extends to only 10° , the P_T^γ cut no longer plays such an important role. Although the low Q^2 acceptance is lost in this scenario, the larger luminosity will allow precise measurements for $Q^2 \gtrsim 50 \text{ GeV}^2$, a region which is not well covered in the 1° acceptance scenario due to the small cross section. In the simulation shown in Fig. 5.28, a factor of 100 increase in luminosity is considered, resulting in precise measurements extending to $Q^2 > 500 \text{ GeV}^2$, well beyond the range explored for DVCS or other GPD-sensitive processes to date.

Maximising the lepton beam energy potentially gives access to the largest W and smallest x values, provided the low P_T^γ region can be accessed. However, the higher beam lepton energy boosts the final state photon in the scattered lepton direction, resulting in an additional acceptance limitation.




Figure 5.28: Simulated LHeC measurement of the DVCS cross section multiplied by Q^4 for different x values for a luminosity of 100 fb^{-1} , with $E_e = 50 \text{ GeV}$, and electron and photon acceptance extending to within 10° of the beampipe with a cut at $P_T^\gamma = 5 \text{ GeV}$. Only statistical uncertainties are considered.

3264 Further studies of this process will require a better understanding of the detector in order to estimate
 3265 systematic uncertainties. A particularly interesting extension would be to investigate possible beam charge
 3266 [367, 386] and polarisation asymmetry measurements at lower x or larger Q^2 than was possible at HERA.
 3267 With the addition of such information, a full study of the potential of the LHeC to constrain GPDs could
 3268 be performed.

3269 Accessing chiral-odd transversity GPDs in diffractive processes

3270 Transversity quark distributions in the nucleon remain among the most unknown leading-twist hadronic
 3271 observables. The four chiral-odd transversity GPDs [348], denoted H_T , E_T , \tilde{H}_T , \tilde{E}_T , offer a new way to
 3272 access the transversity-dependent quark content of the nucleon. The factorization properties of exclusive
 3273 amplitudes apply in principle both to chiral-even and to chiral-odd sectors. However, one photon or one
 3274 meson electroproduction leading-twist amplitudes are insensitive to the latter [387, 388]. At leading twist,
 3275 they can be accessed experimentally through the quasi-forward exclusive electro- or photoproduction of a
 3276 vector meson pair with a large invariant mass [389, 390]. In analogy with the virtual photon exchange
 3277 occurring in the deep inelastic electroproduction of a meson, one considers the subprocess:

$$\mathcal{P}(q_P) p(p_2) \rightarrow \rho_T(p_\rho) N'(p_{2'}) , \quad (5.14)$$

3278 of almost forward scattering of a virtual Pomeron on a nucleon, the hard scale being the virtuality $-q_P^2$
 3279 of this Pomeron. The choice of a transversely polarized vector meson $\rho_T(p_\rho)$ involves at leading twist a
 3280 chiral-odd distribution amplitude (DA), which in turn selects the chiral-odd GPDs. Let us stress that the
 3281 target needs not to be polarized for the amplitude to contain the transversity GPD. This subprocess is at




Figure 5.29: Factorization of the process $\gamma^{(*)}p \rightarrow \rho\rho N'$ in the asymmetric kinematics discussed in the text. \mathcal{P} is the hard Pomeron modeled by two gluon exchange.

work in the diffractive process

$$ep(p_2) \rightarrow e'\gamma_{L/T}^{(*)}(q) \quad p(p_2) \rightarrow e'\rho_{L,T}^0(q_\rho) \quad \rho_T(p_\rho) N'(p_{2'}) , \quad (5.15)$$

shown in Fig. 5.29. The final state may be either $\rho^0\rho^0p$ or $\rho^0\rho^+n$. We consider the kinematics where the energy of the system ($\rho_T(p_\rho) N'$) is smaller than the energy of the system ($\rho_{L,T} \rho_T$) but still large enough to justify a factorized approach (in particular much larger than baryonic resonance masses). In this regime, the amplitude is calculable consistently within the collinear factorization method, as an integral (over the longitudinal momentum fractions of the quarks) of the product of two amplitudes: the first one (the *impact factor* $J^{\gamma \rightarrow \rho^0}$) describes in the Born approximation the transition $\gamma^{(*)} \rightarrow \rho_{L,T}^0$ via two gluon exchange and the second one describes the subprocess $\mathcal{P} p \rightarrow \rho_T N'$. The fact that this latter process is closely related to the electroproduction process $\gamma^* p \rightarrow \rho N'$ allows to separate its long distance dynamics expressed through the GPDs from a perturbatively calculable coefficient function. The skewness parameter ξ is related in the usual way ($\xi \approx x_B/(2-x_B)$) to the Bjorken variable defined by the Pomeron momentum $x_B = -q_P^2/(2q_P \cdot p_2)$.

The resulting scattering amplitude $\mathcal{M}^{\gamma^* p \rightarrow \rho^0 \rho_T p}$ then receives contributions from the four chiral-odd GPDs H_T, \tilde{H}_T, E_T and \tilde{E}_T , but only the first contribution does not vanish kinematically in the forward direction. Thus, assuming that the Mandelstam variable $-t = -(p_2 - p_{2'})^2$ is sufficiently small, the transversity GPD H_T contribution dominates the amplitude which reads in the $\rho^0\rho_T^+$ case:

$$\begin{aligned} \mathcal{M}^{\gamma p \rightarrow \rho^0 \rho_T^+ n} &= \sin\theta \, 16\pi^2 W^2 \alpha_s f_\rho^T \xi \sqrt{\frac{1-\xi}{1+\xi}} \frac{C_F}{N_c (p_T^2)^2} \\ &\times \int_0^1 \frac{du \phi_\perp(u)}{u^2 \bar{u}^2} J^{\gamma \rightarrow \rho^0}(u p_T, \bar{u} p_T) \frac{H_T^{ud}(\xi(2u-1), \xi, t)}{\sqrt{2}} , \end{aligned} \quad (5.16)$$

with $H_T^{ud} = H_T^u - H_T^d$, f_ρ the ρ decay constant, $\phi_\perp(u)$ the DA of the ρ_T meson, $W^2 = (q + p_2)^2$, θ the angle between the transverse polarization vector of the target \vec{n} and the polarization vector $\vec{\epsilon}_T$ of the produced ρ_T -meson, and p_T the transverse momentum of the ρ^0 meson (see [389, 390]). Note that the squared amplitude averaged over the nucleon polarizations does not cancel, enforcing the remarkable feature of exclusive unpolarized reactions to be sensitive to the transversity GPDs.

To get an estimate of the differential cross section of this process, we use a simple meson pole model for the transversity GPD $H_T^q(x, \xi, t)$ starting with the effective interaction Lagrangian $\mathcal{L}_{\mathcal{A}NN} = \frac{g_{\mathcal{A}NN}}{2M} \bar{N} \sigma_{\mu\nu} \gamma_5 \partial^\nu A^\mu N$. This yields, identifying the axial meson as $A = b_1(1235)$,

$$H_T^{ud}(x, \xi, 0) = \frac{g_{b_1 NN} f_{b_1}^T \langle k_\perp^2 \rangle}{2\sqrt{2} M_N m_{b_1}^2} \frac{\phi_\perp^{b_1}\left(\frac{x+\xi}{2\xi}\right)}{2\xi} , \quad (5.17)$$




Figure 5.30: The differential cross section for the photoproduction (a) and electroproduction (b) of the meson pair $\rho_T^0 \rho_T^+$ as a function of ξ for (a) $p_T^2 = 2, 4$ and 6 GeV^2 and for (b) $p_T^2 = 2 \text{ GeV}^2$ and $Q^2 = 2, 4$ and 6 GeV^2 . The cross sections for the production of the meson pair $\rho_T^0 \rho_T^0$ are two times smaller.




Figure 5.31: Diagrams illustrating the different types of exclusive diffraction in the nuclear case: coherent (plot on the left) and incoherent (plot on the right). While the diagrams have been drawn for the case of exclusive vector meson production, they equally apply to an arbitrary diffractively produced state.

3305 with the average of the intrinsic transverse momentum of the quarks $\langle k_{\perp}^2 \rangle \approx 0.8 \text{ GeV}^2$. The resulting cross
 3306 sections estimated within the approximation where the Pomeron is modeled by a two gluon exchange do not
 3307 depend on the variable W^2 , but on the variable ξ . They are shown in Fig. 5.30 as a function of ξ for various
 3308 values of p_T^2 and Q^2 . The rise at small ξ comes mostly from the phase space factor. NLO corrections for
 3309 this amplitude are not known till now. The cross sections look reasonably large. The required studies on the
 3310 possibilities for detection of the final states and of the accessible kinematic range are left for the future.

3311 **Diffractive Vector Meson Production off Nuclei**

3312 Exclusive diffractive processes are similarly promising as a source of information on the gluon density in
 3313 the nucleus [342]. Quasi-elastic scattering of photons from nuclei at small x can be treated within the
 3314 same dipole model framework as for ep scattering, making the comparisons with the proton case relatively
 3315 straightforward. The interaction of the dipole with the nucleus can be viewed as a sum of dipole scatterings
 3316 off the nucleons forming the nucleus. Nuclear effects can be incorporated into the dipole cross section by
 3317 modifying the transverse gluon distribution and adding the corrections due to Glauber rescattering from
 3318 multiple nucleons [261,342]. Previous experimental data on exclusive production from nuclei exist [391,392],
 3319 but are limited in both kinematic range and precision.

3320 There is one aspect of diffraction which is specific to nuclei. The structure of incoherent diffraction with

3321 nuclear break-up ($eA \rightarrow eXY$) is more complex than with a proton target, and it can also be more informative.
 3322 In the case of a target nucleus, we expect the following qualitative changes in the t -dependence. First, the
 3323 low- $|t|$ regime of coherent diffraction illustrated in Fig. 5.31 left, in which the nucleus scatters elastically and
 3324 remains in its ground state, will be dominant up to a smaller value of $|t|$ (about $|t| = 0.05 \text{ GeV}^2$) than in
 3325 the proton case, reflecting the larger size of the nucleus. The nuclear dissociation regime (incoherent case),
 3326 see Fig. 5.31 right, will consist of two parts: an intermediate regime in momentum transfer up to perhaps
 3327 $|t| = 0.7 \text{ GeV}^2$, where the nucleus will predominantly break up into its constituent nucleons, and a large- $|t|$
 3328 regime where the nucleons inside the nucleus will also break up, implying - for instance - pion production in
 3329 the Y system. While these are only qualitative expectations, it is crucial to study this aspect of diffraction
 3330 quantitatively in order to complete our understanding of the transverse structure of nuclei.




Figure 5.32: Differential cross section for the diffractive production of J/Ψ on a lead nucleus, as a function of the momentum transfer $|t|$. The dashed-red and solid-blue lines correspond to the b-Sat model predictions for coherent production without and with saturation effects, respectively. The dotted lines correspond to the predictions for the incoherent case. The pseudodata shown for the coherent case are explained in the text.

3331 Fig. 5.32 shows the diffractive cross sections for exclusive J/Ψ production off a lead nucleus with (b-Sat)
 3332 and without (b-NonSat) saturation effects. The figure shows both the coherent and incoherent cross sections.
 3333 According to both models shown, the cross section for $t \sim 0$ is dominated by coherent production, whereas the
 3334 nuclear break-up contribution becomes dominant for $|t| \gtrsim 0.01 \text{ GeV}^2$, leading to a relatively flat t distribution.

3335 The coherent cross section exhibits a characteristic multiple-dip structure at these relatively large t values,
 3336 the details of which are sensitive to gluon saturation effects. Resolving these dips requires a clean separation
 3337 between the coherent and nuclear break-up contributions, which may be possible with sufficient forward
 3338 instrumentation. In particular, preliminary studies suggest that the detection of neutrons from the nuclear
 3339 break-up in the Zero Degree Calorimeter (Subsec. 14.3) reduces the incoherent backgrounds dramatically.
 3340 Assuming that it is possible to obtain a relatively clean sample of coherent nuclear diffraction, resolving
 3341 the rich structure at large t should be possible based on the measurement of the transverse momentum of
 3342 the elastically produced J/ψ according to $t = -p_T^2(J/\psi)$. The resolution on the t measurement is thus
 3343 related to that on the J/ψ by $\Delta t = 2\sqrt{-t} \Delta p_T(J/\psi)$, amounting to $\Delta t < 0.01 \text{ GeV}^2$ throughout the range
 3344 shown in Fig. 5.32 assuming $\Delta p_T(J/\psi) < 10 \text{ MeV}$, as has been achieved at HERA. The pseudodata for
 3345 the coherent process shown in the figure are consistent with this resolution and correspond to a modest
 3346 integrated luminosity of order 10 pb^{-1} .

3347 Independently of the large $|t|$ behaviour, important information can be obtained from the low $|t|$ region
 3348 alone. Coherent production for $t \sim 0$ can easily be related to the properties of dipole-nucleon interactions,
 3349 because all nuclear effects can be absorbed into the nuclear wave functions, such that only the average gluon
 3350 density of the nucleus enters the calculation. For this forward cross section, the exact shape of the nuclear
 3351 wave function is not important, in contrast to what happens at larger $|t|$ where the distribution reflects the
 3352 functional form of the nuclear density.

3353 Saturation effects can be studied in a very clean way using the t -averaged gluon density obtained in this
 3354 way from the forward coherent cross section. Fig. 5.33 shows this cross section for J/Ψ production as a
 3355 function of W for different nuclei. The cross section varies substantially as a function of the γ^*p centre of
 3356 mass energy W and the nuclear mass number A . It is also very sensitive to shadowing or saturation effects
 3357 due to the fact that the differential cross section at $t = 0$ has a quadratic dependence on the gluon density
 3358 and A . Due to this fact, the ratios of the cross sections for nuclei and protons are roughly proportional to the
 3359 ratios of the gluon densities squared. This has been exploited in the calculation [393] presented in Fig. 5.34,
 3360 where the nuclear modification factor R for the square of the gluon density is shown. The predictions are
 3361 consistent with those obtained from the b-Sat model (Fig. 5.33). Therefore, a precise measurement of the
 3362 J/ψ cross section around $t = 0$ is an invaluable source of information on the gluon density and in particular
 3363 on non-linear effects.

3364 Another region of interest is the measurement at larger $|t|$, $|t| \gtrsim 0.15 \text{ GeV}^2$. Here the reaction is fully
 3365 dominated by the incoherent processes in which the nucleus breaks up. The shadowing or saturation effects
 3366 should be stronger in this region than in the coherent case [360] and the shape of the diffractive cross
 3367 section should be only weakly sensitive to nuclear effects [342]. Finally, the intermediate region between
 3368 $|t| \sim 0.01 \text{ GeV}^2$ and $|t| \sim 0.1 \text{ GeV}^2$ is also very interesting because here the barely known gluonic nuclear
 3369 effects can be studied.

3370 Searching for the Odderon

3371 Exclusive processes in photoproduction and DIS offer unique sensitivity to rare exchanges in QCD. One
 3372 prominent example is that of exclusive pseudoscalar meson production, which could proceed via the exchange
 3373 of the Odderon. The Odderon is the postulated Reggeon which is the C-odd partner of the Pomeron. The
 3374 exchange of an Odderon should contribute with different signs to particle-particle and particle-antiparticle
 3375 scattering. Therefore, in the case of hadron-hadron collisions it could lead, via the optical theorem, to a
 3376 difference between proton-proton and proton-antiproton total cross sections at high energies, provided the
 3377 intercept of the Odderon is close to unity. Despite many searches, no evidence for Odderon exchange has
 3378 been found so far, see for example [394]. Nevertheless, the existence of the Odderon is a firm prediction of
 3379 high-energy QCD, for a comprehensive review see [395]. At lowest order in perturbation theory it can be
 3380 described as a system of three non-interacting gluons. In the leading logarithmic approximation in x its
 3381 evolution is governed by the Bartels-Kwieciński-Praszałowicz (BKP) equations [396–398]. Up to now, two
 3382 solutions to the BKP equations are known, one with intercept slightly below one [399] and the other with
 3383 intercept exactly equal to one [400].

3384 Several channels involving Odderon exchange are possible at the LHeC, leading to the exclusive production




Figure 5.33: Energy dependence of the coherent photoproduction of the J/Ψ on a proton and different nuclei in the forward case $t = 0$ according to the b-Sat model. The cross sections are normalized by a factor $1/A^2$, corresponding to the dependence on the gluon density squared if no nuclear effects are present.

3385 of pseudoscalar mesons, $\gamma^{(*)}p \rightarrow Cp$, where $C = \pi^0, \eta, \eta', \eta_c \dots$. Searches for the Odderon in the reaction
3386 $ep \rightarrow e\pi^0 N^*$ were performed by the H1 collaboration at HERA [401] at an average γp c.m.s energy $\langle W \rangle =$
3387 215 GeV. No signal was found and an upper limit on the cross section was derived, $\sigma(ep \rightarrow e\pi^0 N^*, 0.02 <$
3388 $|t| < 0.3 \text{ GeV}^2) < 49$ nb at the 95 % confidence level. Although the predicted cross sections for processes
3389 governed by Odderon exchange are rather small, they are not suppressed with increasing centre-of-mass
3390 energy and the large luminosities offered by the LHeC may be exactly what is required for a discovery. In
3391 addition to π^0 production, Odderon searches at the LHeC could be based on other exclusive channels, for
3392 example with heavier mesons η_c, η_b [402].

3393 It has been advocated [403] that one could devise more sensitive tests of the existence of the Odderon
3394 exchange by searching for interference effects between Pomeron and Odderon exchange amplitudes. Such an
3395 observable is the measurement of the difference between charm and anti-charm angular or energy distributions
3396 in $\gamma^* p \rightarrow c\bar{c}N^*$. Another channel is the exclusive photo or electroproduction of two pions [404–406]. Indeed
3397 a $\pi^+\pi^-$ pair may be produced both as a charge symmetric C^+ and a charge antisymmetric C^- state. The
3398 Pomeron exchange amplitude will contribute to the $C^- \pi^+\pi^-$ state, the Odderon exchange amplitude will
3399 contribute to the $C^+ \pi^+\pi^-$ state. A (mesonic) charge antisymmetric observable will select the interference
3400 of these two amplitudes. In the hard electroproduction case, one may estimate the effect through a lowest




Figure 5.34: The x dependence of the nuclear modification ratio for the gluon density squared, from nuclei to protons (rescaled by A^2), for the scale corresponding to the exclusive production of the J/Ψ . The results have been obtained from the model described in [393].

3401 order calculation where Pomeron (Odderon) exchange is calculated through the exchange of two (three)
 3402 non-interacting gluons in a colour singlet state in the t -channel, as shown in Fig. 5.35.




Figure 5.35: Feynman diagrams describing $\pi^+\pi^-$ electroproduction in the Born approximation.

3403 The impact representation of the amplitude has the form of an integral over the 2-dimensional transverse
 3404 momenta k_i of the t -channel gluons:

$$\mathcal{M}_P = -i W^2 \int \frac{d^2 k_1 d^2 k_2 \delta^{(2)}(k_1 + k_2 - p_{2\pi})}{(2\pi)^2 k_1^2 k_2^2} J_P^{\gamma^* \rightarrow \pi^+ \pi^-}(k_1, k_2) \cdot J_P^{N \rightarrow N'}(k_1, k_2), \quad (5.18)$$

$$\mathcal{M}_O = -\frac{8\pi^2 W^2}{3!} \int \frac{d^2 k_1 d^2 k_2 d^2 k_3 \delta^{(2)}(k_1 + k_2 + k_3 - p_{2\pi})}{(2\pi)^6 k_1^2 k_2^2 k_3^2} J_O^{\gamma^* \rightarrow \pi^+ \pi^-}(k_1, k_2, k_3) \cdot J_O^{N \rightarrow N'}(k_1, k_2, k_3),$$

3405 where $J_{P/O}^{\gamma^* \rightarrow \pi^+ \pi^-}$ is the impact factor for the transition $\gamma^* \rightarrow \pi^+ \pi^-$ and $J_{P/O}^{N \rightarrow N'}$ is the impact factor for the
 3406 transition of the nucleon in the initial state N into the nucleon in the final state N' .

3407 The impact factors are calculated by standard methods. An important feature of the $J_{P/O}^{\gamma^* \rightarrow \pi^+ \pi^-}$ impact
 3408 factors is the presence of the appropriate two-pion generalized distribution amplitude (GDA) [407–409]:

$$J_P^{\gamma^* \rightarrow \pi^+ \pi^-}(k_1, k_2) = -\frac{i e g^2 \delta^{ab} Q}{2 N_C} \int_0^1 dz z \bar{z} P_P(k_1, k_2) \Phi^{I=1}(z, \zeta, m_{2\pi}^2), \quad (5.19)$$

$$J_O^{\gamma^* \rightarrow \pi^+ \pi^-}(k_1, k_2, k_3) = -\frac{i e g^3 d^{abc} Q}{4 N_C} \int_0^1 dz z \bar{z} P_O(k_1, k_2, k_3) \frac{1}{3} \Phi^{I=0}(z, \zeta, m_{2\pi}^2), \quad (5.20)$$

3410 where P_P and P_O are known perturbatively calculated functions. ζ is the light-cone momentum fraction of
 3411 the π^+ in the two pion system of invariant mass $m_{2\pi}$, which is related to the polar decay angle θ of the π^+

3412 in the rest frame of the two pion system. The GDAs $\Phi^I(z, \zeta, m_{2\pi}^2)$ are non-perturbative matrix elements
 3413 containing the full strong interactions between the two pions. They are universal quantities much related to
 3414 GPDs in the meson. One must distinguish the GDA $\Phi^{I=0}$ where the pion pair is in an isosinglet state from
 3415 the GDA $\Phi^{I=1}$ where it is in an isovector state. The charge conjugation parity of the exchanged particle
 3416 selects the charge parity, hence the isospin of the emerging two-pion state: the Pomeron (Odderon) exchange
 3417 process involves the production of a pion pair in the C -odd (even) channel which corresponds to odd(even)
 3418 isospin. In the numerical studies we use a simple ansatz [410] for the generalized distribution amplitudes
 3419 $\Phi^I(z, \zeta, m_{2\pi}^2)$. A crucial point is the choice of the parametrization of the phases in the GDA's since, through
 3420 interference effects, the rapid variation of a phase shift leads to a characteristic $m_{2\pi}$ -dependence of the
 3421 asymmetry. We show on Fig. 5.36 the resulting estimate for the charge asymmetry defined as

$$A(Q^2, t, m_{2\pi}^2) = \frac{\int \cos \theta d\sigma(W^2, Q^2, t, m_{2\pi}^2, \theta)}{\int d\sigma(W^2, Q^2, t, m_{2\pi}^2, \theta)} = \frac{\int_{-1}^1 \cos \theta d \cos \theta 2 \operatorname{Re} [\mathcal{M}_P^{\gamma_L^*} (\mathcal{M}_O^{\gamma_L^*})^*]}{\int_{-1}^1 d \cos \theta [|\mathcal{M}_P^{\gamma_L^*}|^2 + |\mathcal{M}_O^{\gamma_L^*}|^2]}, \quad (5.21)$$

3422 where θ is the polar decay angle of the π^+ in the rest frame of the two pion system. In order to visualize a
 3423 rather large uncertainty in our modeling we present our results with an error band dominated by the value
 3424 of the soft coupling constant α_{soft} which we vary in the interval of $\alpha_{soft} = 0.3 - 0.7$ (see Ref. [406] for
 3425 details). While detailed studies on the possibilities for detection of the final states are left for the future,
 3426 this estimate demonstrates that the presence of the perturbative Odderon may be discovered in two pion
 electroproduction at high energy (note that the asymmetry (5.21) is independent of W^2).




Figure 5.36: The charge asymmetry defined in Eq. (5.21) as a function of the $\pi^+\pi^-$ invariant mass $m_{2\pi}$.

3427

3428 5.2.4 Inclusive diffraction

3429

3429 Introduction to Diffractive Deep Inelastic Scattering

3430

3430 Approximately 10% of low- x DIS events are of the diffractive type, $ep \rightarrow eXp$, with the proton surviving the
 3431 collision intact despite the large momentum transfer from the electron (Fig. 5.37). This process is usually
 3432 interpreted as the diffractive dissociation of the exchanged virtual photon to produce any hadronic final state
 3433 system X with mass much smaller than W and the same net quantum numbers as the exchanged photon
 3434 ($J^{PC} = 1^{--}$). Due to the lack of colour flow, diffractive DIS events are characterised by a large gap in the
 3435 rapidity distribution of final state hadrons between the scattered proton and the diffractive final state X .




Figure 5.37: Illustration of the kinematic variables used to describe the inclusive diffractive DIS process $ep \rightarrow eXp$.

3436 As discussed in Subsection 5.2.3, similar processes exist in electron-ion scattering, where they can be
 3437 sub-divided into fully coherent diffraction, where the nucleus stays intact ($eA \rightarrow eXA$) and incoherent
 3438 diffraction, where the nucleons within the nucleus are resolved and the nucleus breaks up ($eA \rightarrow eXY$, Y
 3439 being a system produced via nuclear or nucleon excitation, with the same quantum numbers as A).

3440 Theoretically, rapidity gap production is usually described in terms of the exchange of a net colourless
 3441 object in the t -channel, which is often referred to as a pomeron [411,412]. In the simplest models [413,414],
 3442 this pomeron has a universal structure and its vertex couplings factorise, such that it is applicable for
 3443 example to proton-(anti)proton scattering as well as DIS. One of the main achievements at HERA has been
 3444 the development of an understanding of diffractive DIS in terms of parton dynamics and QCD [415]. Events
 3445 are selected using the experimental signatures of either a leading proton [416–418] or the presence of a large
 3446 rapidity gap [417,419]. The factorisable pomeron picture has proved remarkably successful for the description
 3447 of most of these data.

3448 The kinematic variables used to describe diffractive DIS are illustrated in Fig. 5.37. In addition to x , Q^2
 3449 and the squared four-momentum transfer t , the mass M_X of the diffractively produced final state provides
 3450 a further degree of freedom. In practice, the variable M_X is often replaced by

$$\beta = \frac{Q^2}{Q^2 + M_X^2 - t}. \quad (5.22)$$

3451 Small values of β refer to events with diffractive masses much bigger than the photon virtuality, while values
 3452 of β close to unity are associated with small M_X values. In models based on a factorisable pomeron, β may
 3453 be interpreted as the fraction of the pomeron longitudinal momentum which is carried by the struck parton.
 3454 The variable

$$x_{\mathbb{P}} = \frac{x}{\beta} = \frac{Q^2 + M_X^2 - t}{Q^2 + W^2 - M^2}, \quad (5.23)$$

3455 with M the nucleon mass, is then interpreted as the longitudinal momentum fraction of the Pomeron with
 3456 respect to the incoming proton or ion. It also characterises the size of the rapidity gap as $\Delta\eta \simeq \ln(1/x_{\mathbb{P}})$.

Measuring Diffractive Deep Inelastic Scattering at the LHeC

Diffractive DIS (DDIS) can be studied in a substantially increased kinematic range at the LHeC, which will allow a whole new level of investigations of the factorisation properties of inclusive diffraction, will lead to new insights into low- x dynamics and will provide a subset of final states with known quantum numbers for use in searches for new physics and elsewhere.

As shown in [238], collinear QCD factorisation holds in the leading-twist approximation in diffractive DIS and can be used to define diffractive parton distribution functions for the proton or ion. That is, within the collinear framework, the diffractive structure functions [420] can be expressed as convolutions of the appropriate coefficient functions with diffractive quark and gluon distribution functions, which in general depend on all of β , Q^2 , $x_{\mathbb{P}}$ and t . The diffractive parton distribution functions (DPDFs) are physically interpreted as probabilities for finding a parton with a small fraction of the proton momentum $x = \beta x_{\mathbb{P}}$, under the condition that the proton stays intact with a final state four-momentum which is specified up to an azimuthal angle by $x_{\mathbb{P}}$ and t . The DPDFs may then be evolved in Q^2 with the DGLAP evolution equations, with β playing the role of the Bjorken- x variable. The other two variables $x_{\mathbb{P}}$ and t play the role of external parameters to the DGLAP evolution.

In various extractions using HERA DDIS data [419,421–423] the DPDFs have been found to be dominated by gluons. Proton vertex factorisation holds to good approximation, such that the DPDFs vary only in normalisation with the four-momentum of the final state proton, the normalisation being well modelled using Regge phenomenology [412].

The LHeC will offer the opportunity to study diffractive DIS in an unprecedented kinematic range. The diffractive kinematic plane is illustrated in Fig. 5.38 for two different values of the Pomeron momentum fraction, $x_{\mathbb{P}} = 0.01$ and $x_{\mathbb{P}} = 0.0001$. In each plot, accessible kinematic ranges are shown for three different electron energies in collision with the 7 TeV proton beam. Figure 5.38a corresponds to the coverage that will be possible based on leading proton detection (see Chapter 14). Figure 5.38b is more representative of the possibilities using the large rapidity gap technique (see the following). It is clear that the LHeC will have a much increased reach compared with HERA towards low values of $x_{\mathbb{P}}$, where the interpretation of diffractive events is not complicated by the presence of sub-leading meson exchanges, rapidity gaps are large and diffractive event selection systematics are correspondingly small. The range in the fractional struck quark momentum β extends by a factor of around 20 below that accessible at HERA.

Figure 5.39 further illustrates the achievable kinematic range of diffractive DIS measurements at the LHeC for the example of a 150 GeV electron beam combining large rapidity gap and proton tagging acceptance, compared with an estimation of the final HERA performance. For ease of illustration, a binning scheme is chosen in which the β dependence is emphasized and very large bins in $x_{\mathbb{P}}$ and Q^2 are taken. There is a large difference between the kinematically accessible ranges with backward acceptance cuts of 1° and 10° . Statistical uncertainties are typically much smaller than 1% for a luminosity of 2 fb^{-1} , so a much finer binning is possible, as required. The data points are plotted according to the H1 Fit B DPDF predictions [419], which amounts to a crude extrapolation based on dependences in the HERA range.

Systematic uncertainties are difficult to estimate without a detailed knowledge of the forward detectors and their acceptances. At HERA, sub-5% systematics have been achieved in the bulk of the phase space and it is likely that the LHeC could do at least as well.

The limitations in the kinematic range accessible with the large rapidity gap technique are investigated in Fig. 5.40. This shows the correlation between $x_{\mathbb{P}}$ and the pseudorapidity η_{max} of the most forward particle in the hadronic final state system X , in simulated samples with LHeC and HERA beam energies, according to the RAPGAP event generator [132]. This correlation depends only on the proton beam energy and is thus the same for all LHeC running scenarios. At HERA, a cut at $\eta_{\text{max}} \sim 3.2$ has been used to select diffractive events. Assuming LHeC forward instrumentation extending to around $\theta = 1^\circ$, a cut at $\eta_{\text{max}} = 5$ may be possible, which would allow measurements to be made comfortably up to $x_{\mathbb{P}} \sim 0.001$, with some limited sensitivity at larger $x_{\mathbb{P}}$, a region where the proton tagging acceptance takes over (see Chapter 14). The two methods are thus complementary, and offer some common acceptance in an overlap region of $x_{\mathbb{P}}$. This redundancy could be used for cross-calibration of the two methods and their systematics, as has been done at HERA.





Figure 5.38: Diffractive DIS kinematic ranges in Q^2 and β of HERA and of the LHeC for different electron energies $E_e = 20, 50, 150 \text{ GeV}$ at $x_{\text{P}} = 0.01$ (upper plot), and $x_{\text{P}} = 0.0001$ (lower plot). In both cases, 1° acceptance is assumed for the scattered electron and the typical experimental restriction $y > 0.01$ is imposed. No rapidity gap restrictions are applied.




Figure 5.39: Simulation of a possible LHeC measurement of the diffractive structure function, F_2^D using a 2 fb^{-1} sample, compared with an estimate of the optimum results achievable at HERA using the full luminosity for a single experiment (500 pb^{-1}). The loss of kinematic region if the LHeC scattered electron acceptance extends to within 10° of the beam-pipe, rather than 1° is also illustrated.




Figure 5.40: Comparison of the correlation between the rapidity gap selection variable, η_{\max} and x_{P} at HERA and at the LHeC, using events simulated with the RAPGAP Monte Carlo generator.




Figure 5.41: Simulated distributions in the invariant mass M_X according to the RAPGAP Monte Carlo model for samples of events obtainable with $x_{\mathbb{P}} < 0.05$. Left: one year of high acceptance LHeC running at $E_e = 50$ GeV compared with HERA (full luminosity for a single experiment). Right: comparison between three different high acceptance LHeC luminosity and E_e scenarios.

3508 Diffractive Parton Densities and Final States

3509 The previously unexplored diffractive DIS region of very low β is of particular interest. Here, diffractively
 3510 produced systems will be created with unprecedented invariant masses. Figure 5.41 left shows a comparison
 3511 between HERA and the LHeC in terms of the M_X distribution which could be produced in diffractive
 3512 processes with $x_{\mathbb{P}} < 0.05$ (using the RAPGAP Monte Carlo model [132]). Figure 5.41 right compares the
 3513 expected M_X distributions for one year of running at three LHeC electron beam energy choices. Diffractive
 3514 masses up to several hundred GeV are accessible with reasonable rates, such that diffractive final states
 3515 involving beauty quarks and W and Z bosons, or even exotic states with 1^- quantum numbers, could be
 3516 produced.

3517 Large improvements in DPDFs are likely to be possible from NLO DGLAP fits to LHeC diffractive
 3518 structure function data. In addition to the extended phase space in β , the extension of the kinematic range
 3519 towards larger Q^2 increases the lever-arm for extracting the diffractive gluon density and opens the possibility
 3520 of significant weak gauge boson exchange, which would allow a quark flavour decomposition for the first time.

3521 Proton vertex factorisation can be tested precisely by comparing the β and Q^2 dependences at the LHeC
 3522 at different small $x_{\mathbb{P}}$ values in their considerable regions of overlap. The production of dijets or heavy quarks
 3523 as components of the diffractive system X will allow precise testing of QCD collinear factorisation. These
 3524 processes are driven by boson-gluon fusion ($\gamma^*g \rightarrow q\bar{q}$) and thus provide complementary sensitivity to the
 3525 diffractive gluon density to be compared with that from the scaling violations of the inclusive diffractive
 3526 cross section.

3527 Diffractive final states containing charm signatures or relatively high transverse momentum dijets have
 3528 been analyzed in detail at HERA. In the DIS regime, the cross sections for these processes are reproduced
 3529 within uncertainties by calculations based on NLO DPDFs extracted from inclusive diffractive data for both
 3530 the dijet [421, 424–426] and charm [427, 428] cases. By far the limiting factor in the precision of these tests
 3531 is the large scale uncertainty on the theoretical predictions, due to the strong kinematic limitations on the




Figure 5.42: Leading order diagrams for diffractive dijet photoproduction. Diagrams (a) and (b) are examples of direct and resolved photon interactions, respectively.

3532 accessible jet transverse energies in diffraction at HERA. The situation from HERA photoproduction data is
 3533 more complex and is usually divided into direct and resolved photon contributions (figures 5.42a and 5.42b,
 3534 respectively). In the direct photon case, where the highly virtual photon has a point-like coupling, the pro-
 3535 cess is driven by photon-gluon fusion and at the current level of precision, cross sections are well predicted
 3536 using DPDFs extracted in fits to inclusive diffractive data [362, 425, 429]. In contrast, the resolved photon
 3537 case introduces sensitivity to the rich partonic structure of the quasi-real photon. It is these partons which
 3538 participate in the hard scattering sub-process producing the dijets, in a manner which resembles the situation
 3539 in hadron-hadron scattering. In this case, the possibility of additional rescatterings between the hadronic
 3540 remnants leads to a non-unit ‘survival probability’ for the rapidity gap [430–432] and a breakdown of factori-
 3541 sation. Factorisation tests have been carried out on several occasions in diffractive dijet photoproduction at
 3542 HERA, resulting in a somewhat confused situation on the size of the gap destruction effects [362, 429] and
 3543 the roles of resolved and direct contributions. Data in which the parton entering the hard scattering carries
 3544 a lower fraction x_γ of the photon momentum are required to clarify the situation, both experimentally and
 3545 theoretically.

3546 At the LHeC, much larger diffractive jet transverse momenta are measurable ($p_T \lesssim M_X/2$) in both
 3547 photoproduction and DIS. An example study is shown in Fig. 5.43, where the diffractive DIS dijet cross
 3548 section is simulated for the LHeC kinematics and acceptance, using NLOJET++ [433], with the H1 2006
 3549 Fit B DPDFs [419]. Kinematic cuts of $x_{\mathbb{P}} < 0.01$, $Q^2 > 2 \text{ GeV}^2$, $0.1 < y < 0.7$ and $\theta_e > 1^\circ$, matching the
 3550 expected LHeC detector geometry and ensuring good containment for the jets and the scattered electron. Jets
 3551 were reconstructed using the k_T algorithm with $R = 1$ and an integrated luminosity of 100 fb^{-1} is assumed.
 3552 The statistical precision remains excellent up to jet p_T values of around 40 GeV, with measurements possible
 3553 up to around 50 GeV. Theory scale variations in the range of $(0.25\mu^2, 4\mu^2)$ lead to much smaller uncertainties
 3554 than is the case in the HERA data.

3555 Diffractive dijet photoproduction at the LHeC is expected to be dominated by the resolved photon
 3556 contribution. A range of transverse momenta similar to the DIS case is accessible in photoproduction,
 3557 assuming tagging of electrons scattered through small angles as described in section 4.8. Fractional DPDF
 3558 momenta $z_{\mathbb{P}}$, and in the resolved photoproduction case, x_γ values, between one and two orders of magnitude
 3559 smaller than at HERA are typically accessible. All of these improvements will lead to a new level of precision
 3560 in tests of factorization and constraints on the diffractive gluon density in new kinematic regions from
 3561 diffractive jet production at the LHeC [434].




Figure 5.43: Simulated transverse momentum distribution of the jets in diffractive dijet production in DIS ($Q^2 > 2 \text{ GeV}^2$). The simulation was performed using NLOJET++, assuming integrated luminosity of 100 fb^{-1} and high acceptance for the scattered electron (1°). Scale uncertainties are illustrated by varying the factorization scale in the range $(0.25\mu^2, 4\mu^2)$.

3562 The simulated measurement of the longitudinal proton structure function, F_L described in subsection
 3563 4.1.5, could also be extended to extract the diffractive analogue, F_L^D . At small β , where the cross
 3564 section for longitudinally polarised photons is expected to be dominated by a leading twist contribution, an
 3565 F_L^D measurement provides further complementary constraints on the role of gluons in the diffractive PDFs.
 3566 As $\beta \rightarrow 1$, a higher twist contribution from longitudinally polarised photons, closely related to that driving
 3567 vector meson electroproduction, dominates the diffractive cross section in many models [435] and a mea-
 3568 surement to even modest precision would give considerable insight. A first measurement of this quantity has
 3569 recently been reported by the H1 Collaboration [436], though the precision is strongly limited by statistical
 3570 uncertainties. The LHeC provides the opportunity to explore it in much finer detail.

3571 In contrast to leading proton production, the production of leading neutrons in DIS ($ep \rightarrow eXn$) requires
 3572 the exchange of a net isovector system. Data from HERA have supported the view that this process is
 3573 driven dominantly by charged pion exchange over a wide range of neutron energies [437]. With the planned
 3574 emphasis on zero degree calorimetry for leading neutron measurements (see Chapter 14), LHeC data will
 3575 thus constrain the structure of the pion at much lower x and larger Q^2 values than has been possible hitherto.
 3576 Note also that the combination of rapidity gap detection and zero degree calorimetry offers the possibility
 3577 of disentangling coherent from incoherent nuclear diffraction.

3578 Diffractive DIS, Dipole Models and Sensitivity to Non-linear Effects

3579 Diffractive DIS at the LHeC will provide an opportunity to test the predictions of collinear factorisation
 3580 and the possible onset of non-linear or higher-twist effects in the evolution. Of particular importance is the
 3581 semi-hard regime $Q^2 < 10 \text{ GeV}^2$ and x as small as possible. It is possible that the non-linear saturation
 3582 regime will be easier to reach with diffractive than with inclusive measurements, since diffractive processes
 3583 are mostly sensitive to quantum fluctuations in the proton wave function that have a virtuality of order of
 3584 the saturation scale Q_s^2 , instead of Q^2 . As a result, power corrections (not the generic Λ_{QCD}^2/Q^2 corrections,
 3585 but rather the sub-class of them of order Q_s^2/Q^2) are expected to come into play starting from a higher
 3586 value of Q^2 in diffractive than in inclusive DIS. Indeed, there is already a hint of this at HERA: collinear

3587 factorization starts to fail below about 3 GeV^2 in the case of F_2 [38], while it breaks down already around
 3588 8 GeV^2 in the case of F_2^D [419]. This fact can alternatively be observed in the feature that models which
 3589 in principle should only work for small Q^2 , can in practice be used up to larger Q^2 for diffractive than for
 3590 inclusive observables (see e.g. [216]).

3591 With the sort of measurement precision for F_2^D achievable at the LHeC, it ought to be possible to
 3592 distinguish between different models, as illustrated in Fig. 5.44. For the simulated data shown here, a
 3593 conservative situation is assumed, in which the electron beam energy is 50 GeV and only the rapidity gap
 3594 selection method is used, such that the highest $x_{\mathbb{P}}$ bin is at 0.001 . H1 Fit B [419] extrapolations (as in
 3595 Fig. 5.39) are compared with the “b-sat” [261, 262] and bCGC [438] dipole models. As has been found
 3596 to be necessary to describe HERA data, photon fluctuations to $q\bar{q}g$ states are included in addition to the
 3597 usual $q\bar{q}$ dipoles used to describe inclusive and vector meson cross sections. Both dipole models differ
 3598 substantially from the H1 Fit B extrapolation. The LHeC simulated precision and kinematic range are
 3599 sufficient to distinguish between a range of models with and without saturation effects, and also between
 3600 different models which incorporate saturation.




Figure 5.44: Simulated F_2^D measurements in selected $x_{\mathbb{P}}$, β and Q^2 bins. An extrapolation of the H1 Fit B DPDF fit to HERA data is compared with two different implementations of the dipole model, both of which contain saturation effects and include $q\bar{q}g$ photon fluctuations in addition to $q\bar{q}$ ones.

Predicting nuclear shadowing from inclusive diffraction in ep

The connection between nuclear shadowing and diffraction was established a long time ago by Gribov [215]. Its key approximation is that the nucleus can be described as a dilute system of nucleons in the nucleus rest frame. The accuracy of this approximation for hadron-nucleus interactions is on the level of a few %, which reflects the small admixture of non-nucleonic degrees of freedom in nuclei and the small off-shellness of the nucleons in nuclei as compared to the soft strong interaction scale. Gribov's result can be derived using the AGK cutting rules [439] and hence it is a manifestation of unitarity [440, 441]. The formalism can be used to calculate directly cross sections of $\gamma(\gamma^*)$ -nucleus scattering for the interaction with $N = 2$ nucleons, but has to be supplemented by additional considerations to account for the contribution of the interactions with $N \geq 3$ nucleons.

In this context, nuclear PDFs at small x can be calculated [440, 441] combining unitarity relations for different cuts of the shadowing diagrams corresponding to diffractive and inelastic final states, with the QCD factorisation theorem for hard diffraction [238]. A *model-independent* expression for the nuclear PDF at fixed impact parameter b , valid for the case $N = 2$ [440], reads:

$$\begin{aligned} \Delta [xf_{j/A}(x, Q^2, b)] &= xf_{j/N}(x, Q^2, b) - xf_{j/A}(x, Q^2, b) \\ &= 8\pi A(A-1)\Re e \left[\frac{(1-i\eta)^2}{1+\eta^2} \int_x^{0.1} dx_{\mathbb{P}} \beta f_j^{D(4)}(\beta, Q^2, x_{\mathbb{P}}, t_{\min}) \right. \\ &\quad \left. \times \int_{-\infty}^{\infty} dz_1 \int_{z_1}^{\infty} dz_2 \rho_A(\vec{b}, z_1) \rho_A(\vec{b}, z_2) e^{i(z_1-z_2)x_{\mathbb{P}}m_N} \right], \end{aligned} \quad (5.24)$$

where $f_{j/A}(x, Q^2)$, $f_{j/N}(x, Q^2)$ are nuclear and nucleon PDFs respectively, $f_j^{D(4)}(\beta, Q^2, x_{\mathbb{P}}, t_{\min})$ are diffractive nucleon PDFs, $\eta = \Re e A^{diff}/\Im m A^{diff} \approx 0.17$, $\rho_A(r)$ is the nuclear matter density, and $t_{\min} = -m_N^2 x_{\mathbb{P}}^2$ with m_N the nucleon mass. Eq. (5.24) satisfies the QCD evolution equations to all orders in α_s . Numerical studies indicate that the dominant contribution to the shadowing probed by present experiments - corresponding to not very small x - comes from the region of relatively large β , for which small- x approximations which involve resummation of $\ln x$ terms are not important.

In Eq. (5.24), the interaction of different configurations of the hard probe (e.g. $q\bar{q}$, $q\bar{q}g$, vector meson resonances, ...) are encoded in $f_j^{D(4)}(\beta, Q^2, x_{\mathbb{P}}, t_{\min})$. For the case of more than $N = 2$ nucleons, there are two or more intermediate nucleon diffractive states which may be different and thus result in a different interaction between the the virtual photon and the nucleus. Therefore the interaction of the hard probe with $N \geq 3$ nucleons is sensitive to finer details of the diffractive dynamics, namely the interplay between the interactions of the hard probe with N nucleons with different cross sections. This (colour) fluctuation effect is analogous to the inelastic shadowing phenomenon for the scattering of hadrons from nuclei, with the important difference that the dispersion of the interaction cross sections for the configurations in the projectile is much smaller in the hadronic case than in DIS.

In order to estimate this effect, one should note that, experimentally, the energy dependence of hard diffraction is close to that observed for soft Pomeron dynamics (the soft Pomeron intercept $\alpha_{\mathbb{P}} \approx 1.11$) with the hard Pomeron contribution ($\alpha_{\mathbb{P}} \approx 1.25$) being a small correction. This fact indicates that hadron-like (aligned jet) configurations [442], evolved via DGLAP evolution to large Q^2 , dominate hard diffraction in DIS, while point-like configurations give an important, and increasing with Q^2 , contribution to small- x PDFs. This reduces the uncertainties in the treatment of $N \geq 3$ contributions [315, 393]. Calculations show that the difference between two extreme scenarios of colour fluctuations is $\leq 20\%$ for $A \sim 200$ and much smaller for lighter nuclei, see the two FGS10 curves in Figs. 5.12 and 5.18. Besides, fluctuations tend to reduce the shadowing somewhat compared with the approximations neglecting them [217, 440, 443, 444] (compare the FGS10 results in Fig. 5.18 left with those labelled AKST). The gluon density is more sensitive to the magnitude of fluctuations than F_2 , as can be inferred from Figs. 5.12 and 5.18 right.

Finally, the AGK technique also allows the calculation of the nuclear diffractive PDFs, see below, and fluctuations of multiplicity in non-diffractive DIS [393, 440, 445]. Both observables turn out to be sensitive to the pattern of colour fluctuations.

3644 Predictions for inclusive diffraction on nuclear targets

3645 Inclusive diffraction was first measured in DIS events in ep collisions at the HERA collider. LHeC would be
 3646 the first electron-ion collider machine, and therefore DDIS off nuclei at this machine will be a completely un-
 3647 explored territory throughout the whole kinematic domain accessed. This implies a huge discovery potential
 3648 in this field.

3649 Despite this lack of experimental information on DDIS off nuclei, we have expectations, based on our
 3650 current understanding of QCD, of how it should look. For instance, the theory of nuclear shadowing allows
 3651 us to construct nuclear diffractive PDFs for large Q^2 (see the previous item) while, within the Color Glass
 3652 Condensate framework, nuclear diffractive structure functions can be predicted at small x . Depending on
 3653 kinematics and the heavy ion species, different patterns of nuclear shadowing or antishadowing are expected
 3654 as a function of β and $x_{\mathbb{P}}$. This is just one of many examples of what should be checked with an eA collider.
 3655 Others are the impact parameter dependence introduced in the models, or the relation between nuclear
 3656 shadowing and diffraction in ep which relies on what we know on DDIS from HERA. Therefore, in the larger
 3657 kinematic domain accessible at the LHeC there are many things to discover about the structure of nuclei
 3658 with diffractive measurements.

3659 One of the main issues which needs to be established is whether the collinear, leading twist, factorization
 3660 of inclusive diffraction, proved for protons, is applicable for scattering off nuclei, and the region of its
 3661 applicability. An important question arises as to where the factorization would break down, i.e. for which
 3662 values of Q^2 and W , and whether it depends on the mass number, which would provide most important
 3663 information on the role of the higher twists in different nuclei. A related issue is whether the factorization
 3664 of the hadron vertex which is used in the proton case also holds in the nuclear case. In the analysis of the
 3665 diffractive structure functions, the Regge-type factorization is usually assumed. This factorization states
 3666 that the diffractive structure function is written as a product of the two factors: one of them is the Pomeron
 3667 structure function that depends on β and Q^2 , and the other is the Pomeron flux factor that is a function of
 3668 t and $x_{\mathbb{P}}$. The latter one is usually parametrized using a Regge form with a Pomeron intercept being close
 3669 to, albeit slightly higher than, the value obtained from soft interactions. It is currently unclear whether
 3670 such factorization would still hold in the nuclear case, and this is one of the issues that can be tested at
 3671 the LHeC. Also the range of possible parameters, like the Pomeron intercept, extracted from such analysis,
 3672 would provide important details on the nuclear dynamics.

3673 Predictions from a variety of models for nuclear coherent diffraction (see comments on the different
 3674 types of diffractive processes on nuclei in subsection 5.2.3), are shown in Figs. 5.45 and 5.46. The chosen
 3675 models here are FGS10 [393] and KLMV [446, 447]. Both plots show selected LHeC pseudodata for $x_{\mathbb{P}}F_2^D$
 3676 as a function of β in bins of Q^2 and $x_{\mathbb{P}}$. Statistical and systematic errors are added in quadrature, with
 3677 systematic errors estimated to be at the level of 5%. The models give very different predictions both in
 3678 absolute value and in their detailed dependence on $x_{\mathbb{P}}$ and Q^2 , which cannot be resolved without LHeC data.

3679 Also shown in Fig. 5.47 are predicted diffractive-to-total ratios of the structure function F_2 as a function
 3680 of W . It was demonstrated in [242] that the constancy with W of this ratio for the proton - approximately
 3681 shown by HERA data - can be naturally explained in models which include saturation effects, because in
 3682 the black disk regime the ratio of diffractive-to-total cross sections tends to a constant value. It has been
 3683 predicted that in the black disk regime this ratio (for coherent diffraction) may grow as large as 50% [448]. In
 3684 reality, it could be smaller due to the density distribution in impact parameter. Within the given energy range
 3685 the models shown in Fig. 5.47 predict a slight variation with energy. Note however the rather substantial
 3686 difference between predictions coming from the different models as well as the fact that the plot shows the
 3687 ratio of structure functions for given β and $x_{\mathbb{P}}$ and not integrated cross sections. The uncertainty in modeling
 3688 the impact parameter is one of the main sources of the discrepancies between the models. Precise LHeC
 3689 data are required for clarifying these aspects.

3690 Finally we note that, if the scattering on a nucleus at small x is dominated almost entirely by the so-called
 3691 black disk regime, then in principle dramatic effects are expected that can be revealed by studying the final
 3692 states in diffractive events [159]. As demonstrated in [56], the total virtual photon-nucleus cross section in
 3693 the black disk limit reads simply

$$\sigma_{\gamma^*A} = 2\pi R_A^2 (1 - Z_3), \quad (5.25)$$




Figure 5.45: Diffractive structure function $x_{\mathbb{P}}F_2^D$ for Pb in bins of Q^2 and $x_{\mathbb{P}}$ as a function of β . Model calculations are taken from [393].

3694 where R_A is the nuclear radius and Z_3 the charge renormalization constant due to hadrons. The coefficient
3695 $1 - Z_3$ can be computed in terms of the hadronic components of the photon wave function and related to
3696 the cross section for the annihilation of electron-positron pairs into hadrons. Since the elastic part (i.e. that
3697 due to diffraction) is half the total cross section in this regime, one can obtain from eq. (5.25) a spectrum
3698 of the diffractive masses [159] that, in the center-of-mass of the diffractively produced system, should be the
3699 same as in e^+e^- annihilation. A similar analysis for exclusive processes in this limit shows that the exclusive
3700 diffractive production cross sections on nuclei (see subsection 5.2.3) would exhibit a $1/Q^2$ behavior instead
3701 of the $1/Q^6$ behaviour expected from pQCD. This is due to the fact that a factor $1/Q^4$ which comes from
3702 the square of the cross section of the interaction of a small dipole with the target disappears in the black
3703 disk limit.

3704 5.2.5 Jet and multi-jet observables, parton dynamics and fragmentation

3705 Introduction

3706 Inclusive measurements provide essential information about the integrated distributions of partons in a
3707 proton. However, as was discussed in previous sections, more exclusive measurements are needed to pin
3708 down the essential details of the small- x dynamics. For example, a central prediction of the BFKL framework
3709 at small x is the diffusion of the transverse momenta of the emitted partons between the photon and the
3710 proton. In the standard collinear approach with integrated parton densities the information about the
3711 transverse momentum is not accessible. However, it can be recovered within a different framework which
3712 utilizes unintegrated parton distribution functions, dependent on parton transverse momentum as well as x
3713 and Q^2 . Unintegrated PDFs are natural in the BFKL approach to small- x physics. A general, fundamental
3714 expectation is that as x decreases, the distribution in transverse momentum of the emitted partons broadens,
3715 resulting in diffusion.




Figure 5.46: Diffractive structure function $x_{\mathbb{P}}F_2^D$ for Pb in bins of Q^2 and $x_{\mathbb{P}}$ as a function of β . Model calculations are based on the dipole framework [446, 447].




Figure 5.47: Ratio of the transversely polarised photon contribution to the diffractive structure function $x_p F_2^D$ to the inclusive structure function F_2 in p and Pb for fixed values of Q^2 and β as a function of the energy W . Model calculations are based on the dipole framework [446, 447].

3716 The specific parton dynamics can be tested by a number of exclusive measurements. These in turn can
 3717 provide valuable information about the distribution of transverse momentum in the proton. As discussed
 3718 in [449], for many inclusive observables the collinear approximation with integrated PDFs is completely
 3719 insufficient, and even just including parton transverse momentum effects by hand may not be sufficient to
 3720 describe many observables. In DIS, for example, processes needing unintegrated distributions include the
 3721 transverse momentum distribution of heavy quarks. Similar problems are encountered in hadron collisions
 3722 when studying heavy quark and Higgs production. The natural framework using unintegrated PDFs gives a
 3723 much more reliable description. Furthermore, lowest-order calculations in the framework with unintegrated
 3724 PDFs provide a much more realistic description of cross sections concerning kinematics. This may well lead
 3725 to NLO and higher corrections being much smaller numerically than they typically are at present in standard
 3726 collinear factorization, since the LO description is better.

3727 This approach, however, calls for precise measurements of a variety of relatively exclusive processes in
 3728 a wide kinematic range. As discussed below, measurements of dijets, forward jets and particles, as well as
 3729 transverse energy flow, are required to constrain the unintegrated PDFs and will give valuable information
 3730 about parton dynamics at small x . While we will discuss the case of DIS on a proton, all conclusions can be
 3731 paralleled for DIS on nuclei.

3732 Unintegrated PDFs

3733 The standard integrated parton densities are functions of the longitudinal momentum fraction of a parton
 3734 relative to its parent hadron, with an integral over the parton transverse momentum. In contrast, uninte-
 3735 grated, or transverse-momentum-dependent (TMD), parton densities depend on both parton longitudinal
 3736 momentum fraction and parton transverse momentum. Processes for which unintegrated densities are natural
 3737 include the Drell-Yan process (and its generalization to Higgs production), and semi-inclusive DIS (SIDIS).
 3738 In SIDIS, we need TMD fragmentation functions as well as TMD parton densities.

3739 In the literature there are several apparently different approaches to TMD parton densities, with varying
 3740 degrees of explicitness in the definitions and derivations.

- 3741 • The CSS approach [450–453] and some further developments [454].
- 3742 • The CCFM approach [455–458] for small x .




Figure 5.48: (a) Parton model factorisation for a SIDIS cross section. (b) Factorization for high-energy $q\bar{q}$ photoproduction.

- Related BFKL associated works [231, 459].

Central to this subject is the concrete definition of TMD densities, and complications arise because QCD is a gauge theory. A natural initial definition uses light-front quantization: the unintegrated density of parton j in hadron h would be

$$f_{j/h}(x, \mathbf{k}_\perp) \stackrel{?}{=} \frac{1}{2x(2\pi)^3} \sum_\lambda \frac{\langle P, h | b_{k, \lambda, j}^\dagger b_{k, \lambda, j} | P, h \rangle_c}{\langle P, h | P, h \rangle}, \quad (5.26)$$

where $b_{k, \lambda, j}$ and $b_{k, \lambda, j}^\dagger$ are light-front annihilation and creation operators, j and λ label parton flavor and helicity, while $k = (k^+, \mathbf{k}_\perp)$ is its momentum, and only connected graphs ‘c’ are considered. The ‘?’ over the equality sign warns that the formula does not apply literally in QCD. Expressing $b_{k, \lambda, j}$ and $b_{k, \lambda, j}^\dagger$ in terms of fields gives the TMD density as the Fourier transform of a light-front parton correlator. For example, for a quark

$$f_j(x, \mathbf{k}_\perp) \stackrel{?}{=} \int \frac{dw^- d^2\mathbf{w}_\perp}{(2\pi)^3} e^{-ixP^+w^- + i\mathbf{k}_\perp \cdot \mathbf{w}_\perp} \langle P | \bar{\psi}_j(0, w^-, \mathbf{w}_\perp) \frac{\gamma^+}{2} \psi_j(0) | P \rangle_c. \quad (5.27)$$

One can similarly define a TMD fragmentation function [451] $d_{h/j}(z, \mathbf{p}_\perp)$, for the probability density of final-state hadron h in an outgoing parton j .

The corresponding factorization formula for SIDIS $e + A(P_A) \rightarrow e + B(p_B) + X$ is [454]

$$\frac{d\sigma}{dx dQ^2 dz d^2\mathbf{P}_{B\perp}} = \sum_j \int d^2\mathbf{k}_\perp H_j f_{j/A}(x, \mathbf{k}_\perp) d_{B/j}(z, \mathbf{p}_{B\perp} + z\mathbf{k}_\perp), \quad (5.28)$$

where z and $\mathbf{P}_{B\perp}$ are the fractional longitudinal momentum and the transverse momentum of the detected hadron relative to the simplest parton-model calculation of the outgoing jet, while H_j is the hard-scattering factor for electron-quark elastic scattering; see Fig. 5.48(a). In the fragmentation function $d_{B/j}$ in Eq. (5.28), the use of $z\mathbf{k}_\perp$ with its factor of z is because the transverse-momentum argument of the fragmentation function is a transverse momentum of the outgoing hadron relative to the parton initiating the jet, whereas \mathbf{k}_\perp is the transverse momentum of a parton relative to a hadron.

The most obvious way of applying (5.27) in QCD is to define the operators in light-cone gauge $A^+ = 0$, or, equivalently, to attach Wilson lines to the quark fields with a light-like direction for the Wilson lines. One minor problem in QCD is that, because the wave function is infinite (see below), the exact probability interpretation of parton densities cannot be maintained.

A much harder problem occurs because QCD is a gauge theory. Evaluating TMD densities defined by (5.27) in light-cone gauge gives divergences where internal gluons have infinite negative rapidity [450]. These

cancel only in the integrated density. The physical problem is that any coloured parton entering (or leaving) the hard scattering is accompanied by a cloud of soft gluons, and the soft gluons of a given transverse momentum are distributed uniformly in rapidity. A parton density defined in light-cone gauge corresponds to the asymptotic situation of infinite available rapidity.

A quark in a realisable hard scattering can be considered as having a transverse recoil against the soft gluons, but with a physically restricted range of rapidity. So a proper definition of a TMD density must implement a rapidity cut-off in the gluon momenta. Evolution equations must take into account the rapidity cut-off. The CSS formalism [450] has an explicit form of the rapidity cut-off and an equation for the dependence of TMD functions on the cut-off. But in any alternative formalism the need in the definitions for a cut-off to avoid rapidity divergences is non-negotiable.

Parton densities and fragmentation functions are only useful because they appear in factorisation theorems, so a useful definition must allow useful factorisation theorems to be formulated and derived. An improved definition involving Wilson line operators has recently been given in [460]; see also [461].

A second train of argument leads to a related kind of factorisation (the so-called k_{\perp} -factorisation) for processes at small x [125]. A classic process is photo- or electro-production of charm pairs $\gamma(p_1) + h(p_2) \rightarrow Q(p_3) + \bar{Q}(p_4) + X$, for which k_{\perp} -factorisation has the form

$$4M^2\sigma_{\gamma g}(\rho, M^2/Q_0^2) = \int d^2\mathbf{k}_{\perp} \int_0^1 \frac{dz}{z} \hat{\sigma}(\rho/z, \mathbf{k}_{\perp}^2/M^2) f_{g/h}(x, \mathbf{k}_{\perp}), \quad (5.29)$$

see Fig. 5.48(b). Here $\rho = M^2/(p_1 + p_2)^2 \ll 1$, and M is the mass of the heavy quark. The corresponding definition of the TMD gluon density [455] is said to use light-cone gauge, but there is in fact a hidden rapidity cut-off resulting from the use of the BFKL formalism.

Although both (5.28) and (5.29) use k_{\perp} -dependent parton densities, there are important differences. In (5.29), the hard scattering cross section $\hat{\sigma}$ has the incoming gluon *off*-shell, whereas in (5.28), the hard scattering H_j uses on-shell partons. This is associated with a substantial difference in the kinematics. In (5.28) for SIDIS, the transverse momenta of the partons relative to their hadrons are less than Q , which allows the neglect of parton virtuality in the hard scattering. This approximation fails at large partonic transverse momentum, $\mathbf{k}_{\perp} \sim Q$, but ordinary collinear factorisation is valid in that region. So the factorisation formula is readily corrected, by adding a suitable matching term [450].

In contrast, in the small- x formula (5.29), the gluon transverse momentum is comparable with the hard scale M . So it is not appropriate to neglect \mathbf{k}_{\perp} with respect to M , and the hard scattering is computed with an off-shell gluon. Factorisation is actually obtained from BFKL physics, where the gluons in Fig. 5.48(b) couple the charm quark subgraph to a subgraph where the lines have much larger rapidity.

The evolution equation of the CS-style TMD functions used in (5.28) gives the dependence of the TMD functions on the rapidity difference between the hadron and the virtual photon momenta. The results for TMD functions and for the cross sections can finally be obtained [454] in terms of (a) ordinary integrated parton densities and fragmentation functions, (b) perturbatively calculable quantities, and (c) a restricted set of non-perturbative quantities. The most important of these non-perturbative quantities is the distribution in recoil transverse momentum per unit rapidity against the emission of the soft interacting gluons, which is exponentiated after evolution. Importantly, it is independent of x and z , and it is universal between processes [462], and different only between gluons (color octet) and quarks (color triplet). There is also what can be characterised as a non-perturbative intrinsic transverse momentum distribution in both parton densities and fragmentation functions. In the quark sector, all but the fragmentation function are well measured in Drell-Yan processes [463].

On the other hand, evolution for the small- x formalism in (5.29) is given by the BFKL method.

The avenues for further improvement on this subject are both theoretical and experimental. On the theory side, these concern the relation between different formalisms for evolution [231, 450, 454, 459, 464], the extension of factorisation theorems to a larger number of particles in the final state, and the matching to Monte Carlo generators. On the experimental side, the sensitivity to TMD functions is linked to a sensitivity to parton transverse momentum. This is the case of SIDIS at low transverse momentum. Another interesting process which would enable the TMD gluon functions to be probed is $ep \rightarrow e\pi\pi X$, with the pions being in

3815 different directions (different jets), but such that they are close to back-to-back in the (q, p_i) (the so-called
 3816 brick wall) frame.

3817 Finally, measuring SIDIS and dijet production off protons or nuclei at the LHeC will allow detailed
 3818 investigations of non-linear parton evolution in QCD. In this respect, the SIDIS cross section [465] and
 3819 dihadron production [466] have been studied in the CGC framework. It turns out that, for small x , one is
 3820 sensitive to the saturation regime of the target (proton or nucleus) wave function if the transverse momentum
 3821 of the produced hadron is of the order of the saturation momentum.

3822 Dijet production and angular decorrelation

3823 Dijet production in high energy deep inelastic electron-proton scattering is a very valuable process for the
 3824 study of the small- x behavior in QCD. The dominant process is illustrated in Fig. 5.49, which is that of the
 3825 $\gamma^* g \rightarrow q\bar{q} \rightarrow$ dijet production. The incoming gluon can have sizeable transverse momentum accumulated
 3826 from diffusion in k_T along the gluon chain. As Bjorken- x becomes smaller, and therefore the longitudinal
 3827 momentum of the gluon also decreases, larger values of the transverse momentum k_T can be sampled. This
 3828 will lead to an azimuthal decorrelation between the jets which increases with decreasing x . The definition of
 3829 $\Delta\phi$ is indicated in Fig. 5.49. That is, the jets are no longer back-to-back since they must balance the sizable
 3830 transverse momentum k_T of the incoming virtual gluon.




Figure 5.49: Schematic representation of the production of a system of two jets in the process of virtual photon-gluon fusion. The incoming gluon has non-vanishing transverse momentum $k_T \neq 0$ which leads to the decorrelation of the jets. $\Delta\phi$ is the angle between two jets.

3831 This picture of dijet production is to be contrasted with the conventional picture which uses integrated
 3832 parton distributions, and typically leads to a narrow distribution about the back-to-back jet configuration.
 3833 Higher orders usually broaden the distribution. However, as shown by direct measurements of DIS dijet
 3834 data [467], NLO DGLAP calculations are not able to accommodate the pronounced effect of the decorrelation.

3835 Explicit calculations for HERA kinematics show that the models which include the resummation of
 3836 powers of $\log 1/x$ compare favourably with the experimental data [468–472]. The proposal and calculations
 3837 to extend such studies to diffractive DIS also exist [473, 474].

3838 In Fig. 5.50 we show the differential cross section as a function of $\Delta\phi$ for jets in the region $-1 < \eta_{jet} <$
 3839 2.5 with $E_{T,jet1} > 7$ GeV and $E_{T,jet2} > 5$ GeV found with the k_t jet algorithm in the kinematic range
 3840 $Q^2 > 5$ GeV, $0.1 < y < 0.6$ for different regions in x . The ‘MEPS’ prediction comes from a Monte Carlo
 3841 generator [132] using $\mathcal{O}(\alpha_s)$ matrix elements with a DGLAP-type parton shower. The ‘CDM’ prediction
 3842 uses the same generator [132], but with higher order parton radiation simulated with the Colour Dipole

3843 Model [475], thus effectively including some k_t diffusion. Finally, the CASCADE Monte Carlo prediction
 3844 [476], uses off-shell matrix elements convoluted with an unintegrated gluon distribution (CCFM set A), with
 3845 subsequent parton showering according to the CCFM evolution equation.

3846 At large x all predictions agree reasonably well, in both shape and normalisation. At smaller x the
 3847 $\Delta\phi$ -distribution becomes flatter for CDM and CASCADE, indicating higher order effects leading to a larger
 3848 decorrelation of the produced jets. Whereas a decorrelation is observed, its size depends on the details of the
 3849 parton evolution and thus a measurement of the $\Delta\phi$ cross section provides a direct measurement of higher
 order effects which need to be taken into account at small x .




Figure 5.50: Differential cross section for dijet production as a function of the azimuthal separation $\Delta\phi$ for dijets with $E_{T,\text{jet}1} > 7$ GeV and $E_{T,\text{jet}2} > 5$ GeV.

3850

3851 Thus, in principle, a measurement of the azimuthal dijet distribution offers a direct determination of
 3852 the k_T -dependence of the unintegrated gluon distribution. When additionally supplemented by inclusive
 3853 measurements, it can serve as an important constraint for the precise determination of the fully unintegrated
 3854 parton distribution, with the transverse momentum dynamics in the proton completely unfolded.

3855 Dihadron correlations

3856 Another interesting observable which is directly sensitive to the transverse momentum dependence of the
 3857 parton distribution in the proton or nucleus is the process of two hadron production¹². Instead of two jets,
 3858 one observes semi-inclusively two hadrons with certain transverse momentum. One can define the function
 3859 which describes the angular correlation of the two produced hadrons in the following way:

$$C(\phi_{12}) = \frac{1}{\frac{d\sigma(\gamma^*N \rightarrow h_1 X)}{dz_{h_1}}} \frac{d\sigma^{\gamma^*N \rightarrow h_1 h_2 + X}}{dz_{h_1} dz_{h_2} d\phi_{12}}. \quad (5.30)$$

3860 In the above formula z_{h_1}, z_{h_2} are the longitudinal momentum fractions of the two produced hadrons w.r.t.
 3861 the photon momentum and ϕ_{12} is the azimuthal angle between them. The quantity $\frac{d\sigma(\gamma^*N \rightarrow h_1 X)}{dz_{h_1}}$ is the single
 3862 inclusive cross section. In Fig. 5.51 we show the results of the calculation using the formalism presented
 3863 in [465]. The gluon density was evaluated using the GBW model [241] for the proton and a modified version
 3864 of the same model for the nucleus. The electron energy is assumed to be $E_e = 50$ GeV, the proton energy is
 3865 7 TeV and the nucleus energy is 2.75 TeV. Also for the direct comparison with the nuclear case the curve
 3866 with proton energy of 2.75 TeV is shown. The transverse momenta of the produced pions are integrated
 3867 over, it is assumed that the leading particle has a minimum transverse momentum of $p_T = 3$ GeV and the
 3868 associated particle $p_T = 2$ GeV. The photon virtuality is $Q^2 = 4$ GeV², $y = 0.7$ and the fractions of the
 3869 longitudinal momenta of the produced pions are fixed to be equal to $z_{1h} = z_{2h} = 0.3$. One clearly sees that
 3870 the correlation function is wider for a larger target (nucleus) than for the proton. This suppression of the
 3871 peak in the correlation function can be interpreted in this model as the effect of the stronger saturation in
 3872 the gluon density for the nucleus than for the proton. We also see that the correlation function varies mildly
 3873 with the available energy for the same target (i.e. proton). One observes stronger de-correlation of the
 3874 produced hadrons with a higher energy or at smaller values of x which is indicative of the importance of the
 3875 $\ln 1/x$ effects for this observable. Therefore the measurement of the dihadron correlation provides another
 3876 way of constraining the unintegrated gluon distribution. In particular, measuring the dihadron correlations
 3877 in DIS provides with a unique opportunity [466, 477] to directly study the so-called Weizsäcker-Williams
 3878 unintegrated gluon distribution.

3879 Forward observables

3880 It was proposed some time ago [478, 479] that a process which would be very sensitive to the parton dynamics
 3881 and the transverse momentum distribution was the production of forward jets in DIS. According to [478, 479],
 3882 DIS events containing identified forward jets provide a particularly clean window on small- x dynamics. The
 3883 schematic view of the process is illustrated in Fig. 5.52. The forward jet transverse momentum provides
 3884 the second hard scale p_T . Hence one has a process with two hard scales: the photon virtuality Q and
 3885 the transverse momentum of the forward jet p_T . As a result the collinear (DGLAP) configurations (with
 3886 no diffusion and strongly ordered transverse momenta) can be eliminated by choosing the scales to be
 3887 of comparable size, $Q^2 \simeq p_T^2$. Additionally, the jet is required to be produced in the forward direction by
 3888 demanding that x_J , the longitudinal momentum fraction of the produced jet, is as large as possible, and x/x_J
 3889 is as small as possible. This requirement selects events with a large sub-energy between the jet and the virtual
 3890 photon, such that the BFKL framework should be applicable. There have been dedicated measurements of
 3891 forward jets at HERA [480–485], which demonstrated that DGLAP dynamics at NLO are indeed incompatible
 3892 with the experimental measurements. On the other hand, calculations based on resummations of powers of
 3893 $\log 1/x$ (BFKL and others) [486–492] are consistent with the data. The azimuthal dependence of forward
 3894 jet production has also been studied [493, 494] as a sensitive probe of the small- x dynamics.

3895 Another observable that provides a valuable insight into the features of small- x physics is the transverse
 3896 energy (E_T -flow) accompanying DIS events at small x . The diffusion of the transverse momenta in this

¹²This observable is currently discussed in the forward (proton) rapidity region in dAu collisions at RHIC and it shows features suggestive of physics beyond standard collinear factorization, although no consensus has been reached so far, see [296–300] and references therein.




Figure 5.51: Di-hadron correlation function for the case of the scattering off the proton (red-dashed and black-solid lines) compared to the eA case (blue-dotted line). The energy of the electron is assumed to be equal $E_e = 50$ GeV. The observed hadrons are pions.




Figure 5.52: Schematic representation of the production of a high transverse momentum forward jet in DIS.

3897 region leads to a strongly enhanced distribution of E_T at small x . As shown in [495, 496], small- x evolution
 3898 results in a broad Gaussian E_T -distribution as a function of rapidity. This should be contrasted with the
 3899 much smaller E_T -flow obtained assuming strong k_T -ordering as in DGLAP-based approaches, which give an
 3900 E_T -distribution that narrows with decreasing x , for fixed Q^2 .

3901 The first experimental measurements of the E_T -flow in small- x DIS events indicate that there is signifi-
 3902 cantly more E_T than is given by conventional QCD cascade models based on DGLAP evolution. Instead we
 3903 find that they are in much better agreement with estimates which incorporate dynamics beyond fixed-order
 3904 DGLAP [475, 491, 497] such as BFKL evolution. The latter dynamics are characterized by an increase of the
 3905 E_T -flow in the central region with decreasing x .

3906 However, the experimental data from HERA do not enable a detailed analysis due to their constrained
 3907 kinematics. At the LHeC one could perform measurements with large separations in rapidity and for different
 3908 selections of the scales (Q, p_T) . In particular, there is a possibility of varying scales to test systematically
 3909 the parton dynamics from the collinear (strongly ordered) regime $Q^2 \gg p_T^2$ to the BFKL (equal scale, Regge
 3910 kinematics) regime $Q^2 \simeq p_T^2$. Measurements of the energy flow in different x -intervals, in the small- x regime,
 3911 should therefore allow a definitive check of the applicability of BFKL dynamics and of the eventual presence
 3912 of more involved, non-linear effects.

3913 A simulation of forward jet production at the LHeC is shown in Figs. 5.53 and 5.54. The jets are required
 3914 to have $E_T > 10$ GeV with a polar angle $\Theta_{jet} > 1^\circ$ or 3° in the laboratory frame. Jets are found with the
 3915 SIScone jet-algorithm [498]. The DIS phase space is defined by $Q^2 > 5$ GeV, $0.05 < y < 0.85$.




Figure 5.53: Cross section for forward jets with $\Theta_{jet} > 3^\circ$ (left) and $\Theta_{jet} > 1^\circ$ (right). Predictions from MEPS, CDM and CASCADE are shown. Jets are found with the SIScone algorithm using $R = 0.5$.

3916 In Fig. 5.53 the differential cross section is shown as a function of Bjorken x for an electron energy of
 3917 $E_e = 50$ GeV. The calculations are obtained from the MEPS [132], CDM [475] and CASCADE [491] Monte
 3918 Carlo models, as described in the previous section. Predictions for $\Theta_{jet} > 3^\circ$ and $\Theta_{jet} > 1^\circ$ are shown. One
 3919 can clearly see that the small- x range is explored in detail with the small angle scenario. In Fig. 5.54 the
 3920 forward jet cross section is shown when using $R = 1$ instead of $R = 0.5$ (Fig. 5.53). It is important to note
 3921 that good forward acceptance of the detector is crucial for the measurement of forward jets. The dependence
 3922 of the cross section on the acceptance angle is very strong as is evident from comparisons between the cross
 3923 sections for different Θ_{jet} cuts in Figs. 5.53 and 5.54.




Figure 5.54: Cross section for forward jets with $\Theta_{jet} > 3^\circ$ (left) and $\Theta_{jet} > 1^\circ$ (right). Predictions from MEPS, CDM and CASCADE are shown. Jets are found with the SIScone algorithm using $R = 1.0$.

3924 A complementary reaction to that of forward jets is the production of forward π^0 mesons in DIS. Despite
 3925 having a lower rate, this process offers some advantages over forward jet production. By looking onto
 3926 single particle production the dependencies on the jet finding algorithms can be eliminated. Also, the
 3927 non-perturbative hadronisation effects can be effectively encompassed into fragmentation functions [487].

3928 **Perturbative and non-perturbative aspects of final state radiation and hadronization**

3929 The mechanism through which a highly virtual parton produced in a hard scattering gets rid of its virtuality
 3930 and colour and finally projects onto an observable final state hadron, is unknown to a great extent (see [323]
 3931 and references therein). The different postulated stages of the process are illustrated in Fig. 5.55. The
 3932 coloured parton undergoes QCD radiation before forming first a coloured excited bound state (pre-hadron),
 3933 then a colourless pre-hadron and ultimately a final state hadron. These sub-processes are characterised by
 3934 different time scales. While the first stage can be described in perturbative QCD [499], subsequent ones
 3935 require models (e.g. the QCD dipole model for the pre-hadron stages) and non-perturbative information.

3936 The LHeC offers great opportunities to study these aspects and improve our understanding of all of
 3937 them. The energy of the parton which is struck by the virtual photon implies a Lorentz dilation of the
 3938 time scales for each stage of the radiation and hadronisation processes. All of them are influenced by the
 3939 fact that they do not take place in the vacuum, but within the QCD field created by the other components
 3940 of the hadron or nucleus. While at fixed target SIDIS or DY experiments, the lever arm in energy is
 3941 relatively small (energy transfer to the struck parton in its rest frame $\nu < 100$ GeV), at the LHeC this lever
 3942 arm will be huge ($\nu < 10^5$ GeV; see also in Subsec. 4.7.2 the abundant yield of expected high transverse
 3943 momentum jets in photoproduction), implying that the different stages can be considered to happen in or
 3944 out of the hadron field depending on the parton energy. Furthermore, the fact that we can introduce a piece
 3945 of coloured matter of known length and density - a nucleus - by doing ePb collisions at different centralities,
 3946 allows a controllable variation of the contribution of the different processes. The induced differences in
 3947 the final distributions of hadrons, both in terms of their momenta and of their relative abundance, will
 3948 provide important information about the time scales and the detailed physical mechanisms at work in each
 3949 stage. Dramatic effects are predicted in some models [159], with a significant suppression of the forward




Figure 5.55: Sketch of the different postulated stages in the hadronisation of a highly virtual parton. From left to right: radiating parton; radiating coloured pre-hadron, colourless pre-hadron and final state hadron.

3950 hadron spectra due to the existence of a dense partonic system. Note that SIDIS experiments already
 3951 provide information for the determination of standard fragmentation functions (see [500, 501] for a recent
 3952 analysis). The other pieces of information, coming mainly from e^+e^- experiments, will not be improved
 3953 until next-generation linear colliders become available.

3954 Furthermore, these studies will shed light on two aspects already discussed in Subsec. 5.1.4, related
 3955 to the study of ultrarelativistic heavy-ion collisions: the characterization of the medium created in such
 3956 collisions through hard probes, and the details of particle production in a dense situation which will define
 3957 the initial conditions for the collective behavior of this medium. Concerning the latter, our theoretical tools
 3958 for computing particle production in eA collisions are more advanced e.g. within the CGC framework, and
 3959 on a safer ground than in nucleus-nucleus collisions (see Subsec. 5.1.1 and e.g. [322] and refs. therein). The
 3960 possibility of disentangling the different mechanisms through which the factorisation that is used in dilute
 3961 systems - collinear factorisation [194] - becomes broken by density effects (e.g. initial and final state energy
 3962 loss or final state absorption) will be possible at the LHeC and will complement existing studies done at
 3963 much smaller energies in fixed target SIDIS and DY experiments [323].

3964 In order to quantify the possibilities for SIDIS studies, we first show the expected cross sections for π^0
 3965 production in ep and ePb collisions at the LHeC for $E_e = 60$ GeV, see Fig. 5.56. There the calculations are
 3966 done at NLO [502], using as nucleon PDFs those from [267] and, in order to illustrate their effect, different
 3967 nuclear PDFs [152, 312] and both ordinary [500, 501] and modified [503]¹³ fragmentation functions. Cuts
 3968 have been applied as in the H1 study [504]¹⁴ whose data are well reproduced by the NLO calculation: angle
 3969 of the π^0 from the proton in the laboratory $\theta_\pi \in [5^\circ, 25^\circ]$, pion energy fraction $x_\pi = E_\pi/E_p > 0.01$ and pion
 3970 transverse momentum $2.5 < p_T < 15$ GeV/c. All scales in the calculation have been fixed to $(Q^2 + p_T^2)/2$
 3971 (K -factors and the scale dependence of the results are discussed in [502]). From the plots in the figure, it
 3972 becomes clear that even for these very restrictive cuts and for a modest integrated luminosity of 1 fb^{-1} , a
 3973 large number of pions will be produced with relatively large transverse momentum. The nuclear effects on
 3974 PDFs and on fragmentation require measurements with good statistic and systematic precision in order to
 3975 be disentangled.

3976 The results with looser cuts: $\theta_\pi \in [1^\circ, 25^\circ]$, $x_\pi = E_\pi/E_p > 0.005$ that could be achieved at the LHeC,
 3977 have also been studied. Their effect is an increase of the cross section by a factor ~ 3 with respect to the
 3978 results with the more restrictive H1 cuts.

3979 SIDIS also offers the possibility to measure the nuclear effects on fragmentation functions through the
 3980 double ratio for nucleus A and particle k :

$$R_A^k(\nu, z, Q^2) = \frac{1}{N_A^e} \frac{dN_A^k}{d\nu dz} \bigg/ \frac{1}{N_p^e} \frac{dN_p^k}{d\nu dz}, \quad (5.31)$$

3981 with N^e the number of scattered electrons at a given ν and Q^2 i.e. the DIS cross section. At LO and for a
 3982 single quark flavour, this double ratio becomes the ratio of fragmentation functions in eA over ep , see [323].

¹³In this reference, fragmentation functions in nuclear matter are extracted in a DGLAP analysis at LO and NLO.

¹⁴Studies with looser cuts - a more realistic situation at the LHeC, and of the achievable resolution in x and p_T , are left for the future.




Figure 5.56: Cross section for inclusive π^0 production versus Bjorken x_{Bj} for $p_T > 3.5$ GeV/c (left) and versus p_T (right), computed in NLO QCD [502]. Dashed-dotted black lines refer to ep collisions. All other line types refer to ePb collisions: dashed black ones to standard nucleon PDFs [267] and fragmentation functions [500,501], solid red (green) ones to nuclear PDFs [312] ([152]) and nucleon fragmentations functions, and solid blue ones to nuclear PDFs [312] and nuclear fragmentation functions [503]. All cross sections are given per nucleon i.e. divided by 208 for Pb. Cuts: $\theta_\pi \in [5^\circ, 25^\circ]$, $x_\pi = E_\pi/E_p > 0.01$, have been applied. See the text for further explanations.

Usually, the energy of the lepton-hadron/nucleus collisions are the same in numerator and denominator, and the collisions in the denominator are eD in order to suppress isospin effects as much as possible.

In order to estimate the nuclear modifications of fragmentation functions for the case of the LHeC, we compute this double ratio. For the numerator, we consider ePb collisions at 60+2750 GeV while for the denominator we take ep collisions at 60+7000 GeV. We follow the model in [505] which considers the energy loss of the parent parton through radiative processes¹⁵ plus formation time arguments which make the effective length of transversed nuclear matter L smaller at small ν than the geometrical one L_{max} . We use the LO nucleon PDFs in [267] and the nucleon fragmentation functions in [500,501], and also considered the nuclear modification of PDFs in [152]. We employ a value of the transport coefficient characterizing the strength of the interaction of a quark with nuclear matter $\hat{q} = 0.7$ GeV²/fm¹⁶.

The results for π^0 production are shown in Fig. 5.57. Several conclusions can be drawn. First, the effect of the difference in energy between numerator and denominator, and of isospin, are very small. Second, nuclear effects on fragmentation are larger for smaller ν , as expected in a model in which the energy loss becomes energy-independent [505,506]. Third, the nuclear suppression is larger for larger z and it decreases with increasing Q^2 , both effects due to the steepness of the fragmentation function and its evolution with Q^2 . Finally, formation time limitations are only sizable for small ν , as naively expected due to the possibility of hadron formation inside the nucleus in this kinematical region, see [505].

From these results we conclude that the study of SIDIS at the LHeC looks very promising. Still, extensive analyses at detector level are required in order to establish the accesible kinematical regions and to further explore the possibilities for particle identification.

¹⁵For this, we use the quenching weights in [506] instead of the simplified expressions employed in [505].

¹⁶This value is larger than the one used in [505]. We have checked that the model reproduces fixed target data on the ν dependence of the ratio (5.31) for pion production on Kr over D in [507] using this value of \hat{q} without formation time considerations.




Figure 5.57: Ratio $R_{\text{Pb}}^{\pi^0}(\nu, z, Q^2)$, Eq. (5.31), versus ν (lower horizontal axes) or $1/x$ (upper horizontal axes) in ePb over ep at the LHeC, for $z = 0.05, 0.1$ and 0.5 (from left to right) and $Q^2 = 2, 10$ and 100 GeV^2 (from top to bottom). Dashed-dotted black lines show the results without any nuclear effect but isospin, dotted blue ones further include the nuclear modification of PDFs [152], solid red ones the effect of parton energy loss with a geometrical length, and dashed green include formation time considerations. See the text and [505] for details of the calculation.

4003

5.2.6 Implications for ultra-high energy neutrino interactions and detection

The stringent constraints of the parton distributions at very small x from a future LHeC will have important implications for neutrino astronomy. Ultra-high energy neutrinos can provide important information about distant astronomical objects and the origin of the Universe. They have attracted a lot of attention during recent years, see the reviews [508, 509]. Neutrino astronomy has many advantages over conventional photon astronomy. This is due to the fact that neutrinos, unlike photons, interact only weakly, so they can travel long distances being practically undisturbed. The typical interaction lengths for neutrinos and photons at energy $E \sim 1 \text{ TeV}$ are about

$$\mathcal{L}_{int}^{\nu} \sim 250 \times 10^9 \text{ g/cm}^2, \quad \mathcal{L}_{int}^{\gamma} \sim 100 \text{ g/cm}^2.$$




Figure 5.58: Contour plot showing the x, Q^2 domain of the dominant contribution to the differential cross section $d\sigma/d\ln(1/x)d\log Q^2$ for the total ν -nucleon interaction at neutrino laboratory energies of $E_\nu = 10^{11}$ GeV (left plot) and $E_\nu = 10^7$ GeV (right plot). The 20 contours enclose contributions of 5, 10, 15 \dots 100 % of the cross section. The saturation scale according to the model in [241] is shown as a dashed line. See the text for further explanation.

Thus, very energetic photons with energy bigger than ~ 10 TeV cannot reach the Earth from the very distant corners of our Universe without being rescattered. In contrast, neutrinos can travel very long distances without interacting. They are also not deflected by galactic magnetic fields, and therefore at ultra-high energies the angular distortion of the neutrino trajectory is very small. As a result, highly energetic neutrinos reliably point back to their sources. The interest in the neutrinos at these high energies has led to the development of several neutrino observatories, see [509] and references therein.

For reliable observations based on neutrino detection, precise knowledge about their production rates and interactions is essential to estimate the background, the expected fluxes and the detection probabilities. Even though neutrinos interact only weakly with other particles, strong interactions play an essential role in the calculations of their production rates and interaction cross sections. This is due to the fact that neutrinos are produced in the decays of various mesons such as π, K, D and even B , which are produced in high-energy proton-proton (or proton-nucleus or nucleus-nucleus) collisions. These hadronic processes occur mainly in the atmosphere though possibly also in the accretion discs of remote Active Galactic Nuclei. Further, the interactions of highly energetic neutrinos with matter are dominated by the deep inelastic cross section with nucleons or nuclei. Hence, low- x information from high-energy collider experiments such as HERA, Tevatron, LHC and, most importantly, the future LHeC, is invaluable.

One of the main uncertainties (if not the dominant one) in the current limits on high-energy neutrino production is due to the neutrino-nucleon (nucleus) cross section. In fact, event rates are proportional to the neutrino cross section in many experiments. This cross section involves the gluon distribution probed at very small values of Bjorken x , down to even $\sim 10^{-9}$, which corresponds to a very high centre of mass energy.

To visualize the kinematic regime probed in ultra-high energy neutrino-nucleon interactions, contour plots of the differential cross section $\frac{d^2\sigma}{d\ln 1/x d\ln Q^2/\Lambda^2}$ in the (x, Q^2) plane are shown in Fig. 5.58. The contours enclose regions with different contributions to the total cross section $\sigma(E_\nu)$. For very high energy $E_\nu = 10^{11}$ GeV the dominant contribution comes from the domain $Q^2 \simeq M_W^2$ and $x_{\min} \simeq M_W^2/(2M_N E) \sim 10^{-8} - 10^{-7}$ where M_N is the nucleon mass, inaccessible to any current or proposed accelerators. However,

at lower neutrino energy $E_\nu = 10^7$ GeV the relevant domain of (x, Q^2) could be very well covered by the LHeC, thus providing important new constraints on the neutrino-nucleon cross section.

On the other hand, another process that has been proposed for neutrino detection comes from the discovery of neutrino flavor oscillations, which makes it possible that high rates of τ neutrinos reach the Earth despite being heavily suppressed in most postulated production mechanisms. The possibility to search for ν_τ 's by looking for τ leptons that exit the Earth, Earth-skimming neutrinos, has been shown to be particularly advantageous to detect neutrinos of energies in the EeV (10^{18} eV) range [510]. The short lifetime of a τ lepton originating a neutrino charged current interaction allows the τ to decay in flight while still close to the Earth's surface, producing an outgoing air shower, detectable in principle by various techniques. This channel suffers from negligible contamination for other neutrino flavors. The sensitivity to ν_τ 's through the Earth-skimming channel directly depends both on the neutrino charged current cross section and on the τ range (the energy loss) which is determined by the amount of matter with which the neutrino has to interact to produce an emerging τ . It turns out that the τ energy loss is also determined by the behavior of the proton and nucleus structure functions at very small values of x , see e.g. [511]. The average energy loss per unit depth, X , is conveniently represented by:

$$-\left\langle \frac{dE}{dX} \right\rangle = a(E) + b(E)E, \quad b(E) = \frac{N_A}{A} \int dy y \int dQ^2 \frac{d\sigma^{lA}}{dQ^2 dy}, \quad (5.32)$$

where the $a(E)$ term is due to ionization, $b(E)$ is the sum of fractional losses due to e^+e^- pair production, bremsstrahlung and photonuclear interactions, N_A is Avogadro's number and A is the mass number. The parameter $a(E)$ is nearly constant and the term $b(E)E$ dominates the energy loss above a critical energy that for τ leptons is a few TeV, with the photonuclear interaction being dominant for τ energies exceeding $E = 10^7$ GeV (as already assumed in Eq. (5.32)). In Fig. 5.59 the relative contribution to $b(E)$ of different x and Q^2 regions is shown. It can be observed that the energy loss is dominated by very small x and, in contrast to the case of the neutrino cross section, by small and moderate $Q^2 \lesssim m_\tau^2$.




Figure 5.59: The relative contribution of $x < x_{cut}$ (plot on the left) and of $Q^2 < Q_{cut}^2$ (plot on the right) to the photonuclear energy loss rate, $b(E)$, for different neutrino energies $E = 10^6, 10^9$ and 10^{12} GeV, in two different models for the extrapolation of structure functions to very small x . See the text and [511] - from which these plots were taken - for explanations.

As the LHeC will be able to explore a new regime of low x and moderate-to-high Q^2 , and constrain the parton distributions, the measurements performed at this collider will be invaluable for the precise evaluation of the neutrino-nucleon (or nucleus) scattering cross sections and τ energy loss necessary for ultra-high energy neutrino astronomy.

Chapter 6

New Physics at High Energy

Although the LHC is expected to be the discovery machine for physics beyond the Standard Model at the TeV scale, it will not always be possible to measure with precision the parameters of the new physics. In this section, it is shown that in several cases the LHeC can probe in detail deviations from the expected electroweak interactions shared by leptons and quarks, thus adding essential information on the new physics. Previous studies [2, 512–514] of the potential of high-energy $e-p$ colliders for the discovery of exotic phenomena have considered a number of processes, most of which are reviewed here.

In some cases, Standard Model processes can also be better measured at the LHeC. Here, the charged and neutral current processes of SM Higgs production by vector boson fusion are investigated with the goal of measuring the $H-b-b$ coupling.

6.1 New Physics in inclusive DIS at high Q^2

The LHeC collider would enable the study of deep inelastic neutral current scattering at very high squared momentum transfers Q^2 , thus probing the structure of eq interactions at very short distances. At these small scales new phenomena not directly detectable may become observable as deviations from the Standard Model predictions. A convenient tool to assess the experimental sensitivity beyond the maximal available center of mass energy and to parameterise indirect signatures of new physics is the concept of an effective four-fermion contact interaction. If the contact terms originate from a model where fermions have a substructure, a compositeness scale can be related to the size of the composite object. If they are due to the exchange of a new heavy particle, such as a leptoquark, the effective scale is related to the mass and coupling of the exchanged boson. Contact interaction phenomena are best observed as a modification of the expected Q^2 dependence and all information is essentially contained in the differential cross section $d\sigma/dQ^2$. An alternative way to parameterize the effects of fermion substructure makes use of form factors, which would also lead to deviations of $d\sigma/dQ^2$ with respect to the SM prediction. As a last example, low scale quantum gravity effects, which may be mediated via gravitons coupling to SM particles and propagating into large extra spatial dimensions, could also be observed as a modification of $d\sigma/dQ^2$ at highest Q^2 . These possible manifestations of new physics in inclusive DIS are addressed in this section.

6.1.1 Quark substructure

The remarkable similarities in the electromagnetic and weak interactions of leptons and quarks in the Standard Model, and their anomaly cancellations in the family structure, strongly suggest a fundamental connection. It would therefore be natural to conjecture that they could be composed of more fundamental constituents, or that they form a representation of a larger gauge symmetry group than that of the Standard Model, in a Grand Unified Theory.

4089
4090
4091
4092
4093

A possible method to investigate fermion substructures is to assign a finite size of radius R to the electroweak charges of leptons and/or quarks while treating the gauge bosons γ and Z still as pointlike particles [515]. A convenient parametrisation is to introduce ‘classical’ form factors $f(Q^2)$ at the gauge boson–fermion vertices, which are expected to diminish the Standard Model cross section at high momentum transfer:

$$f(Q^2) = 1 - \frac{1}{6} \langle r^2 \rangle Q^2, \tag{6.1}$$

$$\frac{d\sigma}{dQ^2} = \frac{d\sigma^{SM}}{dQ^2} f_e^2(Q^2) f_q^2(Q^2). \tag{6.2}$$

4094
4095
4096
4097
4098
4099
4100

The form factor $f(Q^2)$ is related to the Fourier transform of the electroweak charge distribution within the fermion. The square root of the mean-square radius of this distribution, $R = \sqrt{\langle r^2 \rangle}$, is taken as a measure of the particle size. Since the pointlike nature of the electron/positron is already established down to extremely low distances in $e^+ e^-$ and $(g - 2)_e$ experiments, only the quarks are allowed to be extended objects i.e. the form factor f_e can be set to unity in the above equation.

Figure.6.1 shows the sensitivity that an LHeC collider could reach on the ‘quark radius’ [516]. Two configurations have been studied ($E_e = 70$ GeV and $E_e = 140$ GeV), and two values of the integrated luminosity, per charge, have been assumed in each case. A sensitivity to quark radius below 10^{-19} m could




Figure 6.1: Sensitivity (95% confidence level limits) of an LHeC collider to the effective quark radius. The dashed lines show the sensitivity when systematic uncertainties are neglected, while a systematic uncertainty of 5% is accounted for when calculating the sensitivities shown as the full histograms.

4101
4102
4103
4104
4105
4106
4107

be reached, which is one order of magnitude better than the current constraints.

At the LHC, quark compositeness can be investigated by studying the properties of dijet events, in particular their mass spectrum together with angular distributions. This is usually done in the context of four-quark contact interactions (CI), defined similarly to the $eeqq$ contact interactions that are considered in the next paragraph (see Eq. 6.3 and Eq. 6.4). With the statistics collected in 2011 at $\sqrt{s} = 7$ TeV, the ATLAS experiment rules out four-quark contact interaction scales lower than 7.8 TeV [517]. This is

4108 not directly related to the quark radius considered above, the latter being defined from the distribution of
4109 electroweak charge within the quark. Dijet production at the LHC is largely dominated by strong interactions,
4110 and a deviation from the SM of the electroweak production of dijet would lead to a very small effect in the
4111 total dijet production cross section. From a naive scaling of the CI contribution by $(\alpha_{em}/\alpha_S)^2$, the current
4112 bound would translate into an upper limit of $7 \cdot 10^{-19}$ m on the quark radius. With 300 fb^{-1} of LHC data
4113 at 14 TeV, a factor of about 4 could be gained on this sensitivity.

4114 6.1.2 Contact Interactions

4115 New currents or heavy bosons may produce indirect effects through the exchange of a virtual particle inter-
4116 fering with the γ and Z fields of the Standard Model. For particle masses and scales well above the available
4117 energy, $\Lambda \gg \sqrt{s}$, such indirect signatures may be investigated by searching for a four-fermion pointlike
4118 $(\bar{e}e)(\bar{q}q)$ contact interaction. The most general chiral invariant Lagrangian for neutral current vector-like
4119 contact interactions can be written in the form [518–520]

$$\begin{aligned} \mathcal{L}_V = & \sum_{q=u,d} \{ \eta_{LL}^q (\bar{e}_L \gamma_\mu e_L) (\bar{q}_L \gamma^\mu q_L) + \eta_{LR}^q (\bar{e}_L \gamma_\mu e_L) (\bar{q}_R \gamma^\mu q_R) \\ & + \eta_{RL}^q (\bar{e}_R \gamma_\mu e_R) (\bar{q}_L \gamma^\mu q_L) + \eta_{RR}^q (\bar{e}_R \gamma_\mu e_R) (\bar{q}_R \gamma^\mu q_R) \} , \end{aligned} \quad (6.3)$$

4120 where the indices L and R denote the left-handed and right-handed fermion helicities and the sum extends
4121 over *up-type* and *down-type* quarks and antiquarks q . In deep inelastic scattering at high Q^2 the contributions
4122 from the first generation u and d quarks completely dominate and contact terms arising from sea quarks s ,
4123 c and b are strongly suppressed. Thus, there are eight independent effective coupling coefficients, four for
4124 each quark flavour

$$\eta_{ab}^q \equiv \epsilon \frac{4\pi}{\Lambda_{ab}^q{}^2} , \quad (6.4)$$

4125 where a and b indicate the L , R helicities, Λ_{ab}^q is a scale parameter and ϵ is a prefactor, often set to $\epsilon = \pm 1$,
4126 which determines the interference sign with the Standard Model currents. The ansatz eq. (6.3) can be
4127 easily applied to any new phenomenon, *e.g.* (eq) compositeness, leptoquarks or new gauge bosons, by an
4128 appropriate choice of the coefficients η_{ab} . Scalar and tensor interactions of dimension 6 operators involving
4129 helicity flip couplings are strongly suppressed at HERA [520] and therefore not considered.

4130 Figure 6.2 shows the sensitivity that an LHeC could reach on the scale Λ , for two example cases of contact
4131 interactions [516]. In general, with 10 fb^{-1} of data, LHeC would probe scales between 25 TeV and 45 TeV,
4132 depending on the model. The ultimate sensitivity of LHC to such $eeqq$ interactions, which would affect the
4133 di-electron Drell-Yan (DY) spectrum at high masses, is similar. With $\sim 1 \text{ fb}^{-1}$ of data at $\sqrt{s} = 7 \text{ TeV}$,
4134 the ATLAS and CMS experiments rule out $eeqq$ contact interactions with a scale below $\sim 10 \text{ TeV}$. The
4135 sensitivity will extend to typically 30 TeV with 100 fb^{-1} of data at $\sqrt{s} = 14 \text{ TeV}$.

4136 Figure 6.3 shows how the DY cross-section at LHC would deviate from the SM value, for three examples
4137 of $eeqq$ contact interactions. In the “LL” model considered here, the sum in eq. (6.3) only involves left-
4138 handed fermions and all amplitudes have the same phase ϵ . With only pp data, it will be difficult to
4139 determine simultaneously the size of the contact interaction scale Λ and the sign of the interference of the
4140 new amplitudes with respect to the SM ones: for example, for $\Lambda = 20 \text{ TeV}$ and $\epsilon = -1$, the decrease of the
4141 cross-section with respect to the SM prediction for di-electron masses below $\sim 3 \text{ TeV}$, which is characteristic
4142 of a negative interference, is too small to be firmly established when uncertainties due to parton distribution
4143 functions are taken into account. Angular distributions and forward-backward asymmetries can help in
4144 principle to disentangle between the various possible CI scenarios. However, the statistical uncertainties
4145 expected for dilepton masses above $\sim 2.5 - 3 \text{ TeV}$ limit the power of these variables to scales well below the
4146 sensitivity limit. A similar conclusion was reached in [521] in a study of the indirect effects of a very heavy
4147 Z' boson on dilepton events at the LHC.




Figure 6.2: Sensitivity (95% confidence level limits) on the scale Λ for two example contact interactions. The dashed lines show the sensitivity when systematic uncertainties are neglected, while a systematic uncertainty of 5% is accounted for when calculating the sensitivities shown as the full histograms.




Figure 6.3: Example deviations, from its SM value, of the Drell-Yan cross-section at LHC as a function of the dilepton mass, in the presence of an $eeqq$ contact interaction. The blue band shows the relative uncertainty of the predicted SM cross-sections due to the current uncertainties of the parton distribution functions, as obtained from the CTEQ 6.1 sets. With a luminosity of 300 fb^{-1} , the statistical uncertainty of the measurement would be about 20% (60%) at $M_{ll} = 3 \text{ TeV}$ ($M_{ll} = 4 \text{ TeV}$).




Figure 6.4: (top) Example deviations of the e^-p DIS cross-section at LHeC, in the presence of an $eeqq$ CI, for $E_e = 70$ GeV. The ratio of the “measured” to the SM cross-sections, $r = \sigma/\sigma_{SM}$, is shown. For an integrated luminosity of 10 fb^{-1} , the cross-sections would be measured with a statistical accuracy of a few % (of $\sim 20\%$) at $Q^2 = 2 \cdot 10^5 \text{ GeV}^2$ ($Q^2 = 4 \cdot 10^5 \text{ GeV}^2$). (bottom) Asymmetry $\frac{r(e^+) - r(e^-)}{r(e^+) + r(e^-)}$ between e^+p and e^-p measurements of σ/σ_{SM} .

4148 For the same “LL” model, the sign of this interference can be unambiguously determined at LHeC from
 4149 the asymmetry of σ/σ_{SM} in e^+p and e^-p data, as shown in Fig. 6.4.

4150
 4151 Moreover, with a polarised lepton beam, ep collisions would help determine the chiral structure of the
 4152 new interaction. More generally, it is very likely that both pp and ep data would be necessary to underpin the
 4153 structure of new physics which would manifest itself as an $eeqq$ contact interaction. Such a complementarity
 4154 of pp , ep (and also ee) data was studied in [522] in the context of the Tevatron, HERA and LEP colliders.

4155 6.1.3 Kaluza-Klein gravitons in extra-dimensions

4156 In some models with n large extra dimensions, the SM particles reside on a four-dimensional “brane”, while
 4157 the spin 2 graviton propagates into the extra spatial dimensions and appears in the four-dimensional world
 4158 as a tower of massive Kaluza-Klein (KK) states. The summation over the enormous number of Kaluza-Klein
 4159 states up to the ultraviolet cut-off scale, taken as the Planck scale M_S in the $4 + n$ space, leads to effective
 4160 contact-type interactions $ff'f'$ between two fermion lines, with a coupling $\eta = O(1)/M_S^4$. In ep scattering,
 4161 the exchange of such a tower of Kaluza-Klein gravitons would affect the Q^2 dependence of the DIS cross-
 4162 section $d\sigma/dQ^2$. At LHeC, such effects could be observed as long as the scale M_S is below 4 – 5 TeV. While
 4163 at the LHC, virtual graviton exchange may be observed for scales up to ~ 10 TeV, and the direct production
 4164 of KK gravitons, for scales up to 5 – 7 TeV depending on n , would allow this phenomenon to be studied
 4165 further, LHeC data may determine that the new interaction is universal by establishing that the effect in
 4166 the $eq \rightarrow eq$ cross-section is independent of the lepton charge and polarization, and, to some extent, of the
 4167 quark flavor.

4168 6.2 Leptoquarks and leptogluons

4169 The high energy of the LHeC extends the kinematic range of DIS physics to much higher values of electron-
 4170 quark mass $M = \sqrt{sx}$, beyond those of HERA. By providing both baryonic and leptonic quantum numbers
 4171 in the initial state, it is ideally suited to a study of the properties of new bosons possessing couplings to an
 4172 electron-quark pair in this new mass range. Such particles can be squarks in supersymmetric models with R -
 4173 parity violation (\tilde{R}_p), or first-generation leptoquark (LQ) bosons which appear naturally in various unifying
 4174 theories beyond the Standard Model (SM) such as: E_6 [44], where new fields can mediate interactions
 4175 between leptons and quarks; extended technicolor [47, 523], where leptoquarks result from bound states of
 4176 technifermions; the Pati-Salam model [45], where the leptonic quantum number is a fourth color of the
 4177 quarks or in lepton-quark compositeness models. They are produced as single s -channel resonances via the
 4178 fusion of incoming electrons with quarks in the proton. They are generically referred to as “leptoquarks” in
 4179 what follows. The case of “leptogluons”, which could be produced in ep collisions as a fusion between the
 4180 electron and a gluon, is also addressed at the end of this section.

4181 6.2.1 Phenomenology of leptoquarks in ep collisions

4182 In ep collisions, LQs may be produced resonantly up to the kinematic limit of $\sqrt{s_{ep}}$ via the fusion of
 4183 the incident lepton with a quark or antiquark coming from the proton, or exchanged in the u -channel, as
 4184 illustrated in Fig. 6.5. The coupling λ at the $LQ - e - q$ vertex is an unknown parameter of the model.

4185 In the narrow-width approximation, the resonant production cross-section is proportional to $\lambda^2 q(x)$ where
 4186 $q(x)$ is the density of the struck parton in the incoming proton.

4187 The resonant production or u -channel exchange of a leptoquark gives $e + q$ or $\nu + q'$ final states leading to
 4188 individual events indistinguishable from SM NC and CC DIS respectively. For the process $eq \rightarrow LQ \rightarrow eq$,
 4189 the distribution of the transverse energy $E_{T,e}$ of the final state lepton shows a Jacobian peak at $M_{LQ}/2$,
 4190 M_{LQ} being the LQ mass. Hence the strategy to search for a LQ signal in ep collisions is to look, among
 4191 high Q^2 (i.e. high $E_{T,e}$) DIS event candidates, for a peak in the invariant mass M of the final $e - q$ pair.




Figure 6.5: Example diagrams for resonant production in the s -channel (a) and exchange in the u -channel (b) of a LQ with fermion number $F = 0$. The corresponding diagrams for $|F| = 2$ LQs are obtained from those depicted by exchanging the quark and antiquark.

4192 Moreover, the significance of the LQ signal over the SM DIS background can be enhanced by exploiting the
 4193 specific angular distribution of the LQ decay products (see spin determination, below).

4194 6.2.2 The Buchmüller-Rückl-Wyler Model

4195 A reasonable phenomenological framework to study first generation LQs is provided by the BRW model [524].
 4196 This model is based on the most general Lagrangian that is invariant under $SU(3) \times SU(2) \times U(1)$, respects
 4197 lepton and baryon number conservation, and incorporates dimensionless family diagonal couplings of LQs
 4198 to left- and/or right-handed fermions. Under these assumptions LQs can be classified according to their
 4199 quantum numbers into 10 different LQ isospin multiplets (5 scalar and 5 vector), half of which carry a
 4200 vanishing fermion number $F = 3B + L$ (B and L denoting the baryon and lepton number respectively) and
 couple to $e^+ + q$ while the other half carry $|F| = 2$ and couple to $e^+ + \bar{q}$. These are listed in Table 6.1.

$F = -2$	Prod./Decay	β_e	$F = 0$	Prod./Decay	β_e
Scalar Leptoquarks					
$^{1/3}S_0$	$e_R^+ \bar{u}_R \rightarrow e^+ \bar{u}$	1/2	$^{5/3}S_{1/2}$	$e_R^+ u_R \rightarrow e^+ u$	1
	$e_L^+ \bar{u}_L \rightarrow e^+ \bar{u}$	1		$e_L^+ u_L \rightarrow e^+ u$	1
$^{4/3}\tilde{S}_0$	$e_L^+ \bar{d}_L \rightarrow e^+ \bar{d}$	1	$^{2/3}S_{1/2}$	$e_L^+ d_L \rightarrow e^+ d$	1
$^{4/3}S_1$	$e_R^+ \bar{d}_R \rightarrow e^+ \bar{d}$	1	$^{2/3}\tilde{S}_{1/2}$	$e_R^+ d_R \rightarrow e^+ d$	1
$^{1/3}S_1$	$e_R^+ \bar{u}_R \rightarrow e^+ \bar{u}$	1/2			
Vector Leptoquarks					
$^{4/3}V_{1/2}$	$e_L^+ \bar{d}_R \rightarrow e^+ \bar{d}$	1	$^{2/3}V_0$	$e_L^+ d_R \rightarrow e^+ d$	1
	$e_R^+ \bar{d}_L \rightarrow e^+ \bar{d}$	1		$e_R^+ d_L \rightarrow e^+ d$	1/2
$^{1/3}V_{1/2}$	$e_L^+ \bar{u}_R \rightarrow e^+ \bar{u}$	1	$^{5/3}\tilde{V}_0$	$e_L^+ u_R \rightarrow e^+ u$	1
$^{1/3}\tilde{V}_{1/2}$	$e_R^+ \bar{u}_L \rightarrow e^+ \bar{u}$	1	$^{5/3}V_1$	$e_R^+ u_L \rightarrow e^+ u$	1
			$^{2/3}V_1$	$e_R^+ d_L \rightarrow e^+ d$	1/2

Table 6.1: Leptoquark isospin families in the Buchmüller-Rückl-Wyler model. For each leptoquark, the superscript corresponds to its electric charge, while the subscript denotes its weak isospin. β_e denotes the branching ratio of the LQ into $e + q$.

4201 We use the nomenclature of [525] to label the different LQ states. In addition to the underlying hypotheses
 4202 of BRW, we restrict LQs couplings to only one chirality state of the lepton, given that deviations from lepton
 4203

4204 universality in helicity suppressed pseudoscalar meson decays have not been observed [526, 527].

4205 In the BRW model, LQs decay exclusively into eq and/or νq and the branching ratio $\beta_e = BR(LQ \rightarrow eq)$
 4206 is fixed by gauge invariance to 0.5 or 1 depending on the LQ type.

4207 6.2.3 Phenomenology of leptoquarks in pp collisions

4208 **Pair production** In pp collisions leptoquarks would be mainly pair-produced via gg or qq interactions.
 4209 As long as the coupling λ is not too strong (e.g. $\lambda \sim 0.3$ or below, corresponding to a strength similar
 4210 to or lower than that of the electromagnetic coupling, $\sqrt{4\pi\alpha_{em}}$), the production cross-section is essentially
 4211 independent of λ . At the LHC, LQ masses up to about 1.2 (scalar LQs) and 1.5 TeV (vector LQs) will be
 4212 probed [528], independently of the coupling λ . However, the determination of the quantum numbers of a
 4213 first generation LQ in the pair-production mode is not possible (e.g. for the fermion number) or ambiguous
 4214 and model-dependent (e.g. for the spin). Single LQ production is much better suited for such studies.




Figure 6.6: Diagrams for single LQ production in pp collisions, shown for the example case of the $\tilde{S}_{1/2}^L$ scalar leptoquark. The production may occur via qq interactions (a and b), or via $q\gamma$ interactions (c, d and e). In the latter case, the photon can be emitted by the proton (elastic regime) or by a quark coming from the proton (inelastic regime).

4215 **Single production** Single LQ production at the LHC is also possible. So far, only the production mode
 4216 $gq \rightarrow e + LQ$ (see example diagrams in Fig. 6.6a and b) has been considered in the literature (see e.g. [528]).
 4217 In the context of this study, the additional production mode $\gamma q \rightarrow e + LQ$ has been considered as well (see
 4218 example diagrams in Fig. 6.6c, d and e). This cross-section has been calculated by taking into account:

- 4219 • the inelastic regime, where the photon virtuality q^2 is large enough and the proton breaks up in a
 4220 hadronic system with a mass well above the proton mass. In that case, the photon is emitted by a
 4221 parton in the proton, and the process $qq' \rightarrow q + e + LQ$ is calculated.
- 4222 • the elastic regime, in which the proton emitting the photon remains intact. This calculation involves
 4223 the elastic form factors of the proton.

4224 As the resonant LQ production in ep collisions, the cross-section of single LQ production in pp collisions
 4225 approximately scales with the square of the coupling, $\sigma \propto \lambda^2$. Figure 6.7 (left) shows the cross-section for

4226 single LQ production at the LHC as a function of the LQ mass, assuming a coupling $\lambda = 0.1$. While the
 4227 inelastic part of the γq cross-section can be neglected, the elastic production (which often yields an associated
 4228 electron in the forward direction) plays an important role at high masses; its cross-section is larger than that
 4229 of LQ production via gq interactions for masses above ~ 1 TeV. However, the cross-section for single LQ
 4230 production at LHC is much lower than that at LHeC, in e^+p or e^-p collisions, as shown in Fig.6.7 (right).




Figure 6.7: left: Single LQ production cross-section at the LHC. right: comparison of the cross-section for single LQ production, at LHC and at LHeC.

4231 **LQ exchange in the t-channel** In pp collisions, the t -channel exchange of first generation LQs would
 4232 lead to di-electron events, $q\bar{q} \rightarrow e^+e^-$. The squared amplitude of that process is proportional to λ^4 and its
 4233 interference with the standard Drell-Yan production scales as λ^2 . Hence, its effect is sizable only for large
 4234 values of the coupling λ . It can be used to explore part of the very high mass domain, beyond the discovery
 4235 reach offered by pair-production.

4236 6.2.4 The Contact Term Approach

4237 For LQ masses far above the kinematic limit, the contraction of the propagator in the $eq \rightarrow eq$ and $qq \rightarrow ee$
 4238 amplitudes leads to a four-fermion interaction. Such interactions are studied in the context of general contact
 4239 terms, which can be used to parameterize any new physics process with a characteristic energy scale far above
 4240 the kinematic limit.

4241 In ep collisions, Contact Interactions would interfere with NC DIS processes and lead to a distortion of
 4242 the Q^2 spectrum of NC DIS candidate events. The results presented in section 6.1 can be re-interpreted into
 4243 expected sensitivities on high mass leptoquarks.

4244 6.2.5 Current status of leptoquark searches

4245 The H1 and ZEUS experiments at the HERA ep collider have constrained the coupling λ to be smaller than
 4246 the electromagnetic coupling ($\lambda < \sqrt{4\pi\alpha_{em}} \sim 0.3$) for first generation LQs lighter than 300 GeV. The D0 and
 4247 CDF experiments at the Tevatron pp collider set constraints on first-generation LQs that are independent of




Figure 6.8: Constraints on first generation scalar leptoquarks obtained by the ATLAS experiment with 1 fb^{-1} of data taken at $\sqrt{s} = 7 \text{ TeV}$. From [529].

4248 the coupling λ , by looking for pair-produced LQs that decay into eq (νq) with a branching ratio β ($1 - \beta$).
 4249 For a branching fraction $\beta = 1$, masses below 299 GeV are excluded by the D0 experiment [530]. The CMS
 4250 and ATLAS experiments have recently set tighter constraints [529, 531]. The most recent published result is
 4251 illustrated in Fig. 6.8. With $\sim 1 \text{ fb}^{-1}$ of data taken in 2011 at $\sqrt{s} = 7 \text{ TeV}$, the ATLAS experiment rules
 4252 out scalar LQ masses below 660 GeV (607 GeV) for $\beta = 1$ ($\beta = 0.5$).

4253 6.2.6 Sensitivity on leptoquarks at LHC and at LHeC

4254 Leptoquark searches at the LHC will greatly benefit from the increased center of mass energy, which was
 4255 already raised to 8 TeV for the 2012 data taking. Assuming that $2 \times 25 \text{ fb}^{-1}$ of data can be collected by
 4256 the end of 2012, combining the results from ATLAS and CMS should allow scalar LQ masses up to nearly
 4257 900 GeV to be probed. A similar sensitivity would be obtained, per experiment, with 10 fb^{-1} of data
 4258 at 14 TeV. With 100 fb^{-1} the mass domain below 1 TeV should be fully covered, and with 300 fb^{-1} the
 4259 sensitivity could reach about 1.1 to 1.2 TeV.

4260 Figure 6.9 shows the expected sensitivity [516] of the LHC and LHeC colliders for scalar leptoquark
 4261 production. For a coupling λ of $\mathcal{O}(0.1)$, LQ masses up to about 1 TeV could be probed at the LHeC with
 4262 $E_e = 70 \text{ GeV}$. In pp interactions at the LHC, such leptoquarks would be mainly pair-produced. Beyond the
 4263 mass domain that can be probed via pair-production, independently of the coupling λ , the LHC curve in
 4264 Fig. 6.9 shows the sensitivity expected from t -channel exchange.

4265 6.2.7 Determination of LQ properties

4266 In ep collisions LQ production can be probed in detail, taking advantage of the formation and decay of
 4267 systems which can be observed directly as a combination of jet and lepton invariant mass in the final state.
 4268 It will thereby be possible at the LHeC to probe directly and with high precision the perhaps complex
 4269 structures which will result in the lepton-jet system and to determine the quantum numbers of new states.
 4270 Examples of the sensitivity of high energy ep collisions to the properties of LQ production follow. In partic-
 4271 ular, a quantitative comparison of the potential of LHC and LHeC to measure the fermion number of a LQ,
 4272 and the flavour of the quark it couples to, is given.




Figure 6.9: Mass-dependent upper bounds on the LQ coupling λ as expected at LHeC for a luminosity of 10 fb^{-1} per lepton charge (full red curve) and at the LHC for 100 fb^{-1} (full blue curve). These are shown for an example scalar LQ coupling to e^-u . The LHC curve shows the sensitivity expected from LQ pair-production, that is insensitive to the value of the coupling λ ; beyond that limit, the curve shows the sensitivity expected from t -channel exchange.

4273

Fermion number (F) Since the parton densities for u and d at high x are much larger than those for \bar{u} and \bar{d} , the production cross section at LHeC of an $F = 0$ ($F = 2$) LQ is much larger in e^+p (e^-p) than in e^-p (e^+p) collisions. A measurement of the asymmetry between the e^+p and e^-p LQ cross sections,

$$\mathcal{A}_{ep} = \frac{\sigma_{prod}(e^+p) - \sigma_{prod}(e^-p)}{\sigma_{prod}(e^+p) + \sigma_{prod}(e^-p)}$$

thus determines, via its sign, the fermion number of the produced leptoquark. Pair production of first generation LQs at the LHC will not allow this determination. Single LQ production at the LHC, followed by the LQ decay into e^\pm and q or \bar{q} , could determine F by comparing the signal cross sections with an e^+ and an e^- coming from the resonant state. Indeed, for a $F = 0$ leptoquark, the signal observed when the resonance is made by a positron and a jet corresponds to diagrams involving a *quark* in the initial state (see Fig.6.10a). Hence the corresponding cross-section, $\sigma(e_{out}^+j)$ is larger than that of the signal observed when the resonance is made by an electron and a jet, $\sigma(e_{out}^-j)$, since a high x *antiquark* is involved in that latter case (see Fig.6.10b). In contrast, for a $F = 2$ LQ, $\sigma(e_{out}^+j)$ is smaller than $\sigma(e_{out}^-j)$. The measurement of (the sign of) the asymmetry

$$\mathcal{A}_{pp} = \frac{\sigma(e_{out}^+j) - \sigma(e_{out}^-j)}{\sigma(e_{out}^+j) + \sigma(e_{out}^-j)}$$

4274 should thus provide a determination of the LQ fermion number. However, the single LQ production cross
4275 section at the LHC is two orders of magnitude lower than at the LHeC (Fig. 6.7), so that the asymmetry \mathcal{A}_{pp}
4276 measured at the LHC will suffer from statistics in a large part of the parameter space. For a LQ coupling
4277 to ed and $\lambda = 0.1$, no information on F can be extracted from 300 fb^{-1} of LHC data for a LQ mass above
4278 $\sim 1 \text{ TeV}$, while the LHeC can determine F for LQ masses up to 1.5 TeV (Fig. 6.11 and Fig. 6.12). Details
4279 of the determination of \mathcal{A}_{pp} at the LHC are given in the next paragraph.

4280
4281 An estimate of the precision with which the asymmetry \mathcal{A}_{pp} can be measured at the LHC was obtained
4282 from a Monte Carlo simulation. First, using the model [532] implemented in CalcHep [533], samples were
4283 generated for the processes $g u \rightarrow e^+ e^- u$ and $g \bar{u} \rightarrow e^+ e^- \bar{u}$, keeping only diagrams involving the exchange
4284 of a scalar LQ of charge $1/3$, isospin 0 and fermion number 2. This leptoquark ($^{1/3}S_0$ in the notation of
4285 Table 6.1) couples to $e_R^- u_R$. Assuming that it is chiral, only right-handed coupling was allowed. The $^{1/3}S_0$
4286 leptoquark was also assumed to couple only to the first generation. Masses of 500 GeV, 750 GeV and 1
4287 TeV were considered. The renormalisation and factorisation scales were set at $Q^2 = m_{LQ}^2$ and the coupling
4288 parameter $\lambda = 0.1$. A center of mass energy of 14 TeV was assumed at the LHC.




Figure 6.10: *Single production of a $F = 0$ leptoquark decaying (a) into a positron and a jet and (b) into an electron and a jet. In (a) (resp. (b)), the jet comes from a quark (an antiquark); conservation of the baryon number implies that the parton involved in the initial state is a quark (an antiquark).*

4289 High statistics background samples, corresponding to 150 fb^{-1} were also produced by generating the
4290 same processes $pp \rightarrow e^+ e^- + \text{jet}$, including all diagrams except those involving the exchange of leptoquarks.
4291 Kinematic preconditions were applied at the generation level to both signals and background: (i) $p_T(\text{jet}) >$
4292 50 GeV , (ii) $p_T(e^\pm) > 20 \text{ GeV}$, (iii) invariant mass of jet- $e^+ - e^-$ system $> 200 \text{ GeV}$. The cross sections for
4293 the signals and backgrounds under these conditions are: 19.7 fb , 3.4 fb and 0.87 fb for LQ's of mass 500 GeV,
4294 750 GeV and 1 TeV respectively, and 1780 fb for the background. These events were subsequently passed to
4295 Pythia [130] to perform parton showering and hadronization, then processed through Delphes [534] for a fast
4296 simulation of the ATLAS detector. Finally, considering events with two reconstructed electrons of opposite
4297 sign and, assuming that the leptoquark has already been discovered (at the LHC), the combination of the
4298 highest p_T jet with the reconstructed e^- or e^+ with a mass closest to the known leptoquark mass is chosen
4299 as the LQ candidate. The following cuts for $m_{LQ} = 500, 750$ and 1000 GeV , respectively, are applied:

- 4300 • dilepton invariant mass $m_{ll} > 150, 200, 250 \text{ GeV}$. This cut rejects very efficiently the $Z + \text{jets}$ back-
4301 ground.
- 4302 • $p_T(e_1) > 150, 200, 250 \text{ GeV}$ and $p_T(e_2) > 75, 100, 100 \text{ GeV}$, where e_1 is the reconstructed e^\pm with
4303 higher p_T and e_2 the lower p_T electron.
- 4304 • $p_T(j_1) > 100, 250, 400 \text{ GeV}$, where j_1 is the reconstructed jet with highest p_T , used for the reconstruction
4305 of the LQ.

4306 Table 6.2 summarizes the results of the simulation for an integrated luminosity of 300 fb^{-1} . The expected
4307 number of signal events shown in the table is then simply the number of events due to the leptoquark




Figure 6.11: Asymmetries which would determine the fermion number F of a LQ and the flavour of the quark the LQ couples to. The sign of the asymmetry is the relevant quantity to determine F . The dashed curve shows the asymmetry that could be measured at the LHC; the yellow band shows the statistical uncertainty of this quantity, assuming an integrated luminosity of 300 fb^{-1} . The red and blue symbols, together with their error bars, show the asymmetry that would be measured at LHeC, assuming $E_e = 70 \text{ GeV}$ (left) or $E_e = 140 \text{ GeV}$ (right). Two values of the integrated luminosity have been assumed. These determinations correspond to the $\hat{S}_{1/2}^L$ (scalar LQ coupling to $e^+ + d$), with a coupling of $\lambda = 0.1$.

4308 production and decay, falling in the resonance peak within a mass window of width (60, 100, 160 GeV) for
 4309 the three cases studied, respectively. Although this simple analysis can be improved by considering other
 4310 less dominant backgrounds and by using optimised selection criteria, it should give a good estimate of the
 4311 precision with which the asymmetry can be measured. This precision falls rapidly with increasing mass and,
 4312 above $\sim 1 \text{ TeV}$, it becomes impossible to observe simultaneously single production of both $^{1/3}S_0$ and $^{1/3}\bar{S}_0$.
 4313 It must be noted that the asymmetry at the LHC will be further diluted by the abundant leptoquark pair
 4314 production, not taken into account here.

LQ mass (GeV)	$^{1/3}S_0 \rightarrow e^+ \bar{u}$		$^{1/3}\bar{S}_0 \rightarrow e^- u$		Charge Asymmetry
	Signal	Background	Signal	Background	
500	121	431	771	478	0.73 ± 0.05
750	18.3	137	132	102	$0.76_{-0.14}^{+0.16}$
1000	4.9	57	44	42	$0.77_{0.24}^{+0.23}$

Table 6.2: Estimated number of events of signal and background, and the charge asymmetry measurement with 300 fb^{-1} at the LHC, for $\lambda = 0.1$.

4315 **Flavour structure of the LQ coupling** More generally, the same charge asymmetry observables are
 4316 sensitive to the flavour of the quark the LQ couples to, through the dependence on the parton distribution
 4317 functions of the interacting quark in the proton. For example, Fig. 6.13 shows the calculated asymmetry \mathcal{A}_{ep}




Figure 6.12: Significance of the determination of the fermion number of a LQ, at the LHC (black curve) and at the LHeC (blue and red curves). This corresponds to a $\tilde{S}_{1/2}^L$ leptoquark, assuming a coupling of $\lambda = 0.1$.

4318 that could be measured at LHeC, for scalar LQs. Provided that the coupling λ is not too small, the accuracy
4319 of the measurement of \mathcal{A}_{ep} at LHeC (see Fig. 6.11) would allow the various LQ types to be disentangled, as
4320 different LQs lead to values of \mathcal{A}_{ep} that differ by typically 20 – 30%. A similar measurement at the LHC
4321 would be possible only in a very limited part of the phase space (low masses and large couplings), where the
4322 statistics would be large enough to yield an accuracy of less than $\sim 10\%$ on the measured asymmetry \mathcal{A}_{pp} .
4323 This is illustrated in Fig. 6.14 which shows, as a function of the integrated luminosity, the mass range where
4324 the LHC experiments could discover a leptoquark, determine its fermion number, and determine the flavor
4325 of the quark it couples to. This is shown for an example LQ type, the scalar $\tilde{S}_{1/2}^L$, and an example value of
4326 the coupling, $\lambda = 0.1$. The mass range where the LHeC could make the same measurements is also depicted,
4327 for four LHeC configurations. The LHeC would be able to determine these properties over the full mass
4328 range where the LHC could discover a leptoquark, even in a configuration where $E_e \sim 70$ GeV provided that
4329 the integrated luminosity is large enough. On the other hand, the LHC will not deliver any information on
4330 the flavour structure of a leptoquark, unless it is discovered with a mass very close to the current limit and
4331 the experiments collect a very large amount of luminosity.

4332 **Spin** At the LHeC, the angular distribution of the LQ decay products is unambiguously related to its spin.
4333 Indeed, scalar LQs produced in the s -channel decay isotropically in their rest frame leading to a flat $d\sigma/dy$
4334 spectrum where $y = \frac{1}{2}(1 + \cos\theta^*)$ is the Bjorken scattering variable in DIS and θ^* is the decay polar angle
4335 of the lepton relative to the incident proton in the LQ centre of mass frame. In contrast, events resulting
4336 from the production and decay of vector LQs would be distributed according to $d\sigma/dy \propto (1 - y)^2$. These
4337 y spectra from scalar or vector LQ production are markedly different from the $d\sigma/dy \propto y^{-2}$ distribution
4338 expected at fixed M for the dominant t -channel photon exchange in neutral current DIS events¹. Hence, a
4339 LQ signal in the NC-like channel will be statistically most prominent at high y .

4340 The spin determination will be much more complicated, even possibly ambiguous, if only the LHC

¹At high momentum transfer, Z^0 exchange is no longer negligible and contributes to less pronounced differences in the y spectra between LQ signal and DIS background.




Figure 6.13: Charge asymmetry \mathcal{A}_{ep} for different types of scalar LQs as a function of the LQ mass.

4341 leptoquark pair production data are available. Angular distributions for vector LQs depend strongly on the
 4342 structure of the $g LQ \bar{L} \bar{Q}$ coupling, i.e. on possible anomalous couplings. For a structure similar to that of
 4343 the γWW vertex, vector LQs produced via $q\bar{q}$ fusion are unpolarised and, because both LQs are produced
 4344 with the same helicity, the distribution of the LQ production angle will be similar to that of a scalar LQ.
 4345 The study of LQ spin via single LQ production at the LHC will suffer from the relatively low rates and more
 4346 complicated backgrounds.

4347 **Neutrino decay modes** At the LHeC, there is similar sensitivity for LQ decay into both eq and νq . At
 4348 the LHC, in pp collisions, LQ decay into neutrino-quark final states is plagued by huge QCD background.
 4349 At the LHeC, production through eq fusion with subsequent νq decay is thus very important if the complete
 4350 pattern of LQ decay couplings is to be determined.

4351 **Coupling λ** The intrinsic width of a leptoquark, which depends on the coupling λ and on the LQ mass, is
 4352 expected to be small. For example, for a scalar LQ of 1 TeV and $\lambda = 0.1$, the width is below 0.2 GeV, smaller
 4353 than the experimental mass resolution. Hence, the coupling λ cannot be extracted from a measurement of
 4354 the intrinsic width of the leptoquark.

However, the production cross-section of a LQ in ep collisions can be written, in the narrow-width approximation, as :

$$\sigma_{prod} = \frac{\lambda^2}{16\pi} q(x = M^2/s_{ep}) \quad (J = 0) \quad \text{or} \quad \sigma_{prod} = \frac{\lambda^2}{8\pi} q(x = M^2/s_{ep}) \quad (J = 1)$$

4355 depending on its spin J . Hence, at LHeC, the determination of:

- 4356 • the LQ spin, via the analysis of the angular distribution of its decay products;
- 4357 • the flavor of the quark q involved in the $e - q - LQ$ vertex, via the charge asymmetry described above;
- 4358 • the production cross-section, via the cross-sections measured in the eq and νq decay modes

4359 allows the value of the coupling λ to be determined, from the above formula.




Figure 6.14: The mass domain over which the LHC could discover a leptoquark (upper black curve), determine its fermion number (middle red curve), and determine the flavour of the quark it couples to (lower blue curve), as a function of the integrated luminosity. The mass ranges where the LHeC could determine the LQ fermion number (the quark flavour it couples to) are shown in the top part of the figure, as the horizontal upper red (lower blue) lines, for two values of the lepton beam energy and two values of the integrated luminosity. The hatched area corresponds to the mass domain that is already ruled out by the LHC experiments.

4360 **Chiral structure of the LQ coupling** Chirality is central to the SM Lagrangian. Polarised electron and
 4361 positron beams² at the LHeC will shed light on the chiral structure of the LQ-e-q couplings. Measurements
 4362 of a similar nature at LHC are impossible.

4363

4364 In summary, would a first generation leptoquark exist in the TeV mass range with a coupling λ of $\mathcal{O}(0.1)$,
 4365 the LHeC would allow a rich program of “spectroscopy” to be carried out, resulting in the determination of
 4366 most of the LQ properties.

4367 6.2.8 Leptoquarks as R-parity violating squarks

4368 As already mentioned, squarks in R-parity violating supersymmetric models³ could be an example of “lepto-
 4369 quark” scalar bosons. While the LHC experiments already constrain the squark masses to be above ~ 1 TeV
 4370 in the case of five or four degenerate squarks, the limits are much weaker on a stop or a sbottom that
 4371 would be much lighter than the other squarks, this possibility being well motivated theoretically. Would the
 4372 light stop or sbottom possess sizable R-parity violating couplings to first generation leptons, the constraints
 4373 shown in Fig. 6.8 would apply, as well as the general discussion presented above. In addition, the *R*-parity
 4374 conserving decay modes of this squark, if not negligible, could be studied as well at LHeC. The relatively
 4375 clean environment may allow, for example, mass measurements to be performed with an interesting precision.
 4376 This possibility has not been investigated yet.

4377 6.2.9 Leptogluons

4378 While leptoquarks and excited fermions are widely discussed in the literature, leptogluons have not received
 4379 the same attention. However, they are predicted in all models with colored preons [535–540]. For example,
 4380 in the framework of fermion-scalar models, leptons would be bound states of a fermionic preon and a scalar
 4381 anti-preon $l = (F\bar{S}) = 1 \oplus 8$ (both F and S are color triplets), and each SM lepton would have its own colour
 4382 octet partner [540].

4383 A study of leptogluons production at LHeC is presented in [541]. It is based on the following Lagrangian:

$$L = \frac{1}{2\Lambda} \sum_l \{ \bar{l}_8^\alpha g_s G_{\mu\nu}^\alpha \sigma^{\mu\nu} (\eta_L l_L + \eta_R l_R) + h.c. \} \quad (6.5)$$

4384 where $G_{\mu\nu}^\alpha$ is the field strength tensor for gluon, index $\alpha = 1, 2, \dots, 8$ denotes the color, g_s is gauge coupling,
 4385 η_L and η_R are the chirality factors, l_L and l_R denote left and right spinor components of lepton, $\sigma^{\mu\nu}$ is the
 4386 anti-symmetric tensor and Λ is the compositeness scale. The leptonic chiral invariance implies $\eta_L \eta_R = 0$.

4387 The phenomenology of leptogluons at LHC and LHeC is very similar to that of leptoquarks, despite
 4388 their different spin (leptogluons are fermions while leptoquarks are bosons) and their different interactions.
 4389 Figure 6.15 shows typical cross-sections for single leptogluon production at the LHeC, assuming Λ is equal
 4390 to the leptogluon mass. It is estimated that, for example, a sensitivity of to a compositeness scale of 200
 4391 TeV, at 3σ level can be achieved with LHeC having $E_e = 70$ GeV and with 1 fb^{-1} . The mass reach for M_{e8}
 4392 is 1.1 TeV for $\Lambda = 10$ TeV.

4393 As for leptoquarks, would leptogluons be discovered at the LHC, LHeC data would be of highest value
 4394 for the determination of the properties of this new particle.

4395 6.3 Excited leptons and other new heavy leptons

4396 The three-family structure and mass hierarchy of the known fermions is one of the most puzzling charac-
 4397 teristics of the Standard Model (SM) of particle physics. Attractive explanations are provided by models

²Whether it is possible to achieve longitudinal polarisation in a 70 GeV e^\pm beam in the LHC tunnel remains to be clarified.

³The potential of LHeC to observe supersymmetric particles in models where the *R*-parity is conserved has been studied as well. However, the leading process of squark-selectron pair production would have a sizable cross-section only when the sum of the masses of the produced sparticles is below ~ 1 TeV. The constraints on squarks already set by the LHC experiments using the data taken in 2011 largely rule out this possibility.




Figure 6.15: Resonant e_8 production at the LHeC, for two values of the center-of-mass energy.

4398 assuming composite quarks and leptons [542]. The existence of excited states of fermions (F^*) is a natural
 4399 consequence of compositeness models. More generally, various models predict the existence of fundamental
 4400 new heavy leptons, which can have similar experimental characteristics as excited leptons. They could, for
 4401 example, be part of a fourth Standard model family. They arise also in Grand Unified Theories, and appear
 4402 as colorless fermions in technicolor models.

4403 New heavy leptons could be pair-produced at the LHC for masses up to $\mathcal{O}(300)$ GeV. As for the case
 4404 of leptoquarks, pp data from pair-production of new leptons may not allow for a detailed study of their
 4405 properties and couplings. Single production of new leptons is also possible at the LHC, but is expected to
 4406 have a larger cross-section at LHeC, via $e\gamma$ or eW interactions. The case of excited electrons is considered
 4407 in the following, with more details being given in [543] together with a similar study of the production of
 4408 excited neutrinos. The production of new leptons from a fourth generation (l_4, ν_4) via magnetic interactions
 4409 mixing the first and fourth generation is very similar and was studied in [544].

4410 Single production of excited leptons at the LHC (\sqrt{s} up to 14 TeV) may happen via the reactions
 4411 $pp \rightarrow e^\pm e^* \rightarrow e^+ e^- V$ and $pp \rightarrow \nu e^* + \nu^* e^\pm \rightarrow e^\pm \nu V$. The LHC should be able to tighten considerably the current
 4412 constraints on these possible new states [545].

4413 Recent results of searches for excited leptons [546–548] at HERA using all data collected by the H1
 4414 detector have demonstrated that ep colliders are very competitive to pp or e^+e^- colliders. Indeed limits
 4415 set by HERA extend at high mass beyond the kinematic reach of LEP searches [549, 550] and to higher
 4416 compositeness scales than those obtained at the Tevatron [551] using 1 fb^{-1} of data. Therefore a future
 4417 LHeC machine, with a centre of mass energy of 1 – 2 TeV, much higher than at the HERA ep collider,
 4418 should provide a good environment to search for and study excited leptons.

4419 6.3.1 Excited Fermion Models

4420 Compositeness models attempt to explain the hierarchy of masses in the SM by the existence of a substructure
 4421 within the fermions. Several of these models [552–554] predict excited states of the known fermions, in which
 4422 excited fermions are assumed to have spin 1/2 and isospin 1/2 in order to limit the number of parameters
 4423 of the phenomenological study. They are expected to be grouped into both left- and right-handed weak
 4424 isodoublets with vector couplings. The existence of the right-handed doublets is required to protect the
 4425 ordinary light fermions from radiatively acquiring a large anomalous magnetic moment via F^*FV interaction
 4426 (where V is a γ, Z or W).

4427 Interactions between excited and ordinary fermions may be mediated by gauge bosons, as described by

4428 the effective Lagrangian:

$$\mathcal{L}_{GM} = \frac{1}{2\Lambda} \bar{F}_R^* \sigma^{\mu\nu} \left[g f \frac{\vec{\tau}}{2} W_{\mu\nu} + g' f' \frac{Y}{2} B_{\mu\nu} + g_s f_s \frac{\vec{\lambda}}{2} G_{\mu\nu} \right] F_L + h.c., \quad (6.6)$$

4429 where Y is the weak hypercharge, g_s , $g = \frac{e}{\sin\theta_W}$ and $g' = \frac{e}{\cos\theta_W}$ are the strong and electroweak gauge
 4430 couplings, where e is the electric charge and θ_W is the weak mixing angle; $\vec{\lambda}$ and $\vec{\tau}$ are the Gell-Mann
 4431 matrices and the Pauli matrices, respectively. $G_{\mu\nu}$, $W_{\mu\nu}$ and $B_{\mu\nu}$ are the field strength tensors describing
 4432 the gluon, the $SU(2)$, and the $U(1)$ gauge fields; f_s , f and f' are factors multiplying the coupling constants
 4433 associated to each gauge field. They depend on the composite dynamics. The parameter Λ has units of
 4434 energy and can be regarded as the compositeness scale which reflects the range of the new confinement force.

4435 In addition to gauge mediated (GM) interactions, a new interaction could take place at the scale of the
 4436 binding energy of the constituents of quarks and leptons. It would result in new interaction terms between
 4437 excited fermions and ordinary fermions, that can be described by an effective four-fermion Lagrangian [554]:

$$\mathcal{L}_{CI} = \frac{g_*^2}{2\Lambda^2} j^\mu j_\mu, \quad (6.7)$$

4438 where g_* denotes the strength of the new interaction and j_μ is the fermion current

$$j_\mu = \eta_L \bar{F}_L \gamma_\mu F_L + \eta'_L \bar{F}_L^* \gamma_\mu F_L^* + \eta''_L \bar{F}_L^* \gamma_\mu F_L + h.c. + (L \rightarrow R). \quad (6.8)$$

4439 In the following, we set $g_* = 0$ and only consider the “gauge” terms of Eq.6.6. Thus, the results presented
 4440 below are independent of the strength of the new interaction, and can be generically applied to the production
 4441 of any new lepton coupling to an electron-photon pair via the standard electromagnetic interaction.

4442 6.3.2 Simulation and Results

4443 In the following study, excited electron (e^*) production and decays via GM interactions are considered. The
 4444 e^* production cross section under the assumption $f = -f'$ becomes much smaller than for $f = +f'$ and
 4445 therefore only the case $f = +f'$ is studied.

4446 Excited electrons could be produced in ep collisions at the LHeC via a t -channel γ or Z bosons exchange.
 4447 The Monte Carlo (MC) event generator COMPOS [555] is used for the calculation of the e^* production cross
 4448 section and the simulation of signal events. The resulting cross sections for several LHeC configurations,
 4449 assuming $f = +f' = 1$ and $M_{e^*} = \Lambda$, are shown in Fig. 6.16, together with the corresponding production
 4450 cross section at HERA and at the LHC [545]. In the mass range accessible by the LHeC, the e^* production
 4451 cross section via GM interactions is clearly much higher than at the LHC.

4452 In order to estimate the sensitivity of excited electron searches at the LHeC, the e^* production followed
 4453 by its decay in the channel $e^* \rightarrow e\gamma$ is considered. This is the key channel for excited electron searches in ep
 4454 collisions as it provides a very clear signature and has a large branching ratio. Only the main sources of
 4455 backgrounds from SM processes are considered here, namely neutral currents (NC DIS) and QED-Compton
 4456 ($e\gamma$) events. Other possible SM backgrounds are negligible. The MC event generator WABGEN [556] is used
 4457 to generate these background events. Figure 6.17 compares the e^* production cross section to the total cross
 4458 section of SM backgrounds. Background events dominate in the low e^* mass region. Hence to enhance the
 4459 signal, candidate events are selected with two isolated electromagnetic clusters with a polar angle between
 4460 5° and 145° and transverse energies greater than 15 GeV and 10 GeV, respectively.

4461 To translate the results into exclusion limits, expected upper limits on the coupling f/Λ are derived at
 4462 95% Confidence Level (CL) as a function of excited electron masses.

4463 The attainable limits at the LHeC on the ratio f/Λ are shown in figure 6.18 for excited electrons, for the
 4464 hypothesis $f = +f'$ and different integrated luminosities $L = 10 \text{ fb}^{-1}$ for \sqrt{s} up to 1.4 TeV and $L = 1 \text{ fb}^{-1}$
 4465 for \sqrt{s} up to 2 TeV. They are compared to the upper limits obtained at LEP [549, 550], HERA [546] and also
 4466 to the expected sensitivity of the LHC [545]. Considering the assumption $f/\Lambda = 1/M_{e^*}$ and $f = +f'$, excited
 4467 electrons with masses up to 1.2(1.5) TeV, corresponding to centre of mass energies of $\sqrt{s} = 1.4(1.9)$ TeV of




Figure 6.16: The e^* production cross section via gauge mediated interactions, for different design scenarios of the LHeC electron-proton collider, compared to the cross sections at HERA and at the LHC. The cross sections shown correspond to the choice $f = f' = 1$.




Figure 6.17: Electromagnetic production cross section for e^* ($e^* \rightarrow e\gamma$) for different values of Λ , together with the cross section from background processes.

4468 the LHeC, are excluded. Under the same assumptions, LHC ($\sqrt{s} = 14$ TeV) could exclude e^* masses up to
 4469 1.2 TeV for an integrated luminosity of 100 fb^{-1} . In the accessible mass range of LHeC, the LHeC would be
 4470 able to probe smaller values of the coupling f/Λ than the LHC. Similarly to leptoquarks (see section 6.2),
 4471 if an excited electron is observed at the LHC with a mass of $\mathcal{O}(1 \text{ TeV})$, the LHeC would be better suited to
 4472 study the properties of this particle, thanks to the larger single production cross-section (see Fig. 6.16).




Figure 6.18: Sensitivity to excited electron searches for different design scenarios of the LHeC electron-proton collider, compared to the expected sensitivity of the LHC ($\sqrt{s} = 14$ TeV, $L = 100 \text{ fb}^{-1}$). Different integrated luminosities at the LHeC ($L = 10 \text{ fb}^{-1}$ for \sqrt{s} up to 1.4 TeV and $L = 1 \text{ fb}^{-1}$ for \sqrt{s} up to 2 TeV) are assumed. The curves present the expected exclusion limits on the coupling f/Λ at 95% CL as a function of the mass of the excited electron with the assumption $f = +f'$. Areas above the curves are excluded. Present experimental limits obtained at LEP and HERA are also represented.

4473 The ATLAS and CMS experiments have carried out a search for excited leptons using data taken in 2011
 4474 at $\sqrt{s} = 7$ TeV [557, 558]. These analyses assume that the production of excited electrons via $qqee^*$ contact
 4475 interactions is dominant, by setting $g_*^2 = 4\pi$ in Eq. 6.7. This is markedly different from the conservative
 4476 hypothesis made here, $g_* = 0$, where the production of excited electrons is dominated by gauge interactions
 4477 such that the results are independent of the strength of the new interaction g_* . Under the assumption that
 4478 $g_*^2 = 4\pi$, the ATLAS experiment rules out e^* masses below 1.87 TeV for $f = f' = 1$ and $\Lambda = M_{e^*}$. This
 4479 rules out, in this specific model and for the couplings assumed, the observability of an excited electron at
 4480 the LHeC. Lighter e^* with lower couplings, for which the LHC has no sensitivity yet, may be observed and
 4481 studied at the LHeC.

4482 6.4 New physics in boson-quark interactions

4483 Several extensions of the Standard Model predict new phenomena that would be directly observable in boson-
 4484 quark interactions. For example, the top quark may have anomalous couplings to gauge bosons, leading to
 4485 Flavour Changing Neutral Current (FCNC) vertices $tq\gamma$, where q is a light quark. Similarly, excited quarks
 4486 (q^*) or quarks from a fourth generation (Q) could be produced via $\gamma q \rightarrow q^*$ or $\gamma q \rightarrow Q$. The transitions
 4487 $\gamma q \rightarrow t, q^*, Q$ can be studied in ep collisions at the LHeC, but a much larger cross-section would be achieved

4488 at a γp collider, due to the much larger γp centre-of-mass energy. The single production of q^* , Q or of a top
4489 quark via anomalous couplings is also possible at the LHC, but it involves an anomalous coupling together
4490 with an electroweak coupling and the main background processes involve the strong interaction. The signal
4491 to background ratio will thus be much more challenging at the LHC, and any constraints on anomalous
4492 couplings would therefore be obtained from the decay channels of these quarks. The example of anomalous
4493 single top production is detailed in the following.

4494 6.4.1 An LHeC-based γp collider

4495 The possibility to operate the LHeC as a γp collider is described in 8.1.6. If the electron beam is accelerated
4496 by a linac, it can be converted into a beam of high energy real photons, by backscattering off a laser pulse.
4497 The energy of these photons would be about 80% of the energy of the initial electrons.

4498 6.4.2 Anomalous Single Top Production at the LHeC Based γp Collider

4499 The top quark is expected to be most sensitive to physics beyond the Standard Model (BSM) because
4500 it is the heaviest available particle of the Standard Model (SM). A precise measurement of the couplings
4501 between SM bosons and fermions provides a powerful tool for the search of BSM physics allowing a possible
4502 detection of deviations from SM predictions [559]. Anomalous tqV ($V = g, \gamma, Z$ and $q = u, c$) couplings can
4503 be generated through dynamical mass generation [73], sensitive to the mechanism of dynamical symmetry
4504 breaking. They have a similar chiral structure as the mass terms, and the presence of these couplings would
4505 be interpreted as signals of new interactions. This motivates the study of top quark flavour changing neutral
4506 current (FCNC) couplings at present and future colliders.

4507 Current experimental constraints at 95% C.L. on the anomalous top quark couplings are [64]: $BR(t \rightarrow$
4508 $\gamma u) < 0.0132$ and $BR(t \rightarrow \gamma u) < 0.0059$ from HERA; $BR(t \rightarrow \gamma q) < 0.041$ from LEP and $BR(t \rightarrow$
4509 $\gamma q) < 0.032$ from CDF. The HERA experiments have a much higher sensitivity to $u\gamma t$ than $c\gamma t$ due to more
4510 favorable parton density, and provide the best constraint to date on $BR(t \rightarrow \gamma u)$. The ZEUS experiment also
4511 considered an anomalous (vector) coupling tuZ , but the cross section is much suppressed due to the Z boson
4512 mass in the t -channel exchange, and the resulting constraints were not competitive with those obtained at
4513 LEP or at the Tevatron. In this section, the possibility to study anomalous couplings $tu\gamma$ at the LHeC is
4514 addressed.

4515 The top quarks will be copiously produced at the LHC, allowing for detailed studies of their properties.
4516 For a luminosity of 1 fb^{-1} (100 fb^{-1}) the expected ATLAS sensitivity to the top quark FCNC decay is
4517 $BR(t \rightarrow q\gamma) \sim 10^{-3}$ (10^{-4}) [560,561]. The production of top quarks by FCNC interactions at hadron colliders
4518 has been studied in [562–574], e^+e^- colliders in [73,575–578] and lepton-hadron collider in [73,579–581]. LHC
4519 will give an opportunity to probe $BR(t \rightarrow ug)$ down to 5×10^{-3} [582]; ILC/CLIC has the potential to probe
4520 $BR(t \rightarrow q\gamma)$ down to 10^{-5} [583].

4521 The potential of the LHeC to search for anomalous top quark interactions in ep collisions was studied
4522 in [584] and the sensitivity on a coupling $tu\gamma$ was shown to be lower than what could be probed at the
4523 LHC. In contrast, operating the LHeC as a γp collider offers interesting possibilities to study anomalous top
4524 quark interactions. These have been investigated in [585] and are summarised here. The effective Lagrangian
4525 involving anomalous $t\gamma q$ ($q = u, c$) interactions is given by:

$$L = -g_e \sum_{q=u,c} Q_q \frac{\kappa_q}{\Lambda} \bar{t} \sigma^{\mu\nu} (f_q + h_q \gamma_5) q A_{\mu\nu} + h.c. \quad (6.9)$$

4526 where $A_{\mu\nu}$ is the usual photon field tensor, $\sigma_{\mu\nu} = \frac{i}{2}(\gamma_\mu \gamma_\nu - \gamma_\nu \gamma_\mu)$, Q_q is the quark charge, in general f_q and
4527 h_q are complex numbers, g_e is the electromagnetic coupling constant, κ_q is a real and positive anomalous
4528 FCNC coupling constant and Λ is the new physics scale. The neutral current magnitudes in the Lagrangian
4529 satisfy $|(f_q)^2 + (h_q)^2| = 1$ for each term. The anomalous decay width can be calculated as

$$\Gamma(t \rightarrow q\gamma) = \left(\frac{\kappa_q}{\Lambda}\right)^2 \frac{2}{9} \alpha_{em} m_t^3 \quad (6.10)$$

4530 Taking $m_t = 173$ GeV and $\alpha_{em} = 0.0079$, the anomalous decay width ≈ 9 MeV for $\kappa_q/\Lambda = 1$ TeV $^{-1}$
 4531 while the SM decay width is about 1.5 GeV.

4532 For numerical calculations anomalous interaction vertices are implemented into the CalcHEP pack-
 4533 age [533] using the CTEQ6M [131] parton distribution functions. The Feynman diagrams for the subprocess
 4534 $\gamma q \rightarrow W^+ b$, where $q = u, c$ are shown in Fig. 6.19. The first three diagrams correspond to irreducible back-
 4535 grounds and the last one to the signal. The main background comes from associated production of W boson
 4536 and the light jets.




Figure 6.19: Feynman diagrams for $\gamma q \rightarrow W^+ b$, where $q = u, c$.

4537 The differential cross sections for the final state jets are given in Fig. 6.20 ($\kappa/\Lambda = 0.04$ TeV $^{-1}$) for
 4538 $E_e = 70$ GeV and $E_p = 7000$ GeV assuming $\kappa_u = \kappa_c = \kappa$. It is seen that the transverse momentum
 4539 distribution of the signal has a peak around 70 GeV.




Figure 6.20: The transverse momentum distribution of the final state jet for the signal and background processes. The differential cross section includes the b -tagging efficiency and the rejection factors for the light jets. The center of mass energy $\sqrt{s_{ep}} = 1.4$ TeV and $\kappa/\Lambda = 0.04$ TeV $^{-1}$.

4540 Here, b-tagging efficiency is assumed to be 60% and the mistagging factors for light (u, d, s) and c quarks
 4541 are taken as 0.01 and 0.1, respectively. A p_T cut reduces the signal (by $\sim 30\%$ for $p_T > 50$ GeV), whereas
 4542 the background is essentially suppressed (by a factor 4-6) . In order to improve the signal to background
 4543 ratio further, one can apply a cut on the invariant mass of $W + jet$ around top mass. In Table 6.3, the cross
 4544 sections for signal and background processes are given after having applied both a p_T and an invariant mass
 4545 cuts ($M_{Wb} = 150 - 200$ GeV).

$\kappa/\Lambda = 0.01 \text{ TeV}^{-1}$	$p_T > 20 \text{ GeV}$	$p_T > 40 \text{ GeV}$	$p_T > 50 \text{ GeV}$
Signal	8.86×10^{-3}	7.54×10^{-3}	6.39×10^{-3}
Background: W^+b	1.73×10^{-3}	1.12×10^{-3}	7.69×10^{-4}
Background: W^+c	3.48×10^{-1}	2.30×10^{-1}	1.63×10^{-1}
Background: W^+jet	1.39×10^{-1}	9.11×10^{-2}	6.38×10^{-2}

Table 6.3: The cross sections (in pb) according to the p_T cut and invariant mass interval ($M_{Wb} = 150 - 200$ GeV) for the signal and background at γp collider based on the LHeC with $E_e = 70$ GeV and $E_p = 7000$ GeV.

4546 In order to calculate the statistical significance (SS) we use following formula [586] :

$$SS = \sqrt{2 \left[(S + B) \ln\left(1 + \frac{S}{B}\right) - S \right]} \quad (6.11)$$

4547 where S and B are the numbers of signal and background events, respectively. Results are presented in Table
 4548 6.4 for different κ/Λ and luminosity values. It is seen that even with 2 fb^{-1} the LHeC based γp collider will
 4549 provide 5σ discovery for $\kappa/\Lambda = 0.02 \text{ TeV}^{-1}$.

SS	$L = 2 \text{ fb}^{-1}$	$L = 10 \text{ fb}^{-1}$
$\kappa/\Lambda = 0.01 \text{ TeV}^{-1}$	2.58 (2.88)	5.79 (6.47)
$\kappa/\Lambda = 0.02 \text{ TeV}^{-1}$	5.26 (5.92)	11.78 (13.25)

Table 6.4: The signal significance (SS) for different values of κ/Λ and integral luminosity for $E_e = 70$ GeV and $E_p = 7000$ GeV (the numbers in parenthesis correspond to $E_e = 140$ GeV).

4550 Up to now, we have assumed $\kappa_u = \kappa_c = \kappa$. However, it would be interesting to analyze the case
 4551 $\kappa_u \neq \kappa_c$. Indeed, at HERA, valence u -quarks dominate whereas at LHeC energies the c -quark and u -quark
 4552 contributions become comparable. Therefore, the sensitivity to κ_c will be enhanced at LHeC comparing to
 4553 HERA. In Fig. 6.21 contour plots for anomalous couplings in $\kappa_u - \kappa_c$ plane are presented. For this purpose,
 4554 a χ^2 analysis was performed with

$$\chi^2 = \sum_{i=1}^N \left(\frac{\sigma_{S+B}^i - \sigma_B^i}{\Delta\sigma_B^i} \right)^2 \quad (6.12)$$

4555 where σ_B^i is the cross-section for the SM background in the i^{th} bin, including both b -jet and light-jet
 4556 contributions with their corresponding efficiency factors. In the σ_{S+B} calculations, we take into account
 4557 the different values for κ_u and κ_c as well as the signal-background interference. Fig. 6.21 shows that the
 4558 sensitivity is enhanced by a factor of 1.5 when the luminosity changes from 2 fb^{-1} to 10 fb^{-1} . Concerning the
 4559 energy upgrade, increasing electron energy from 70 GeV to 140 GeV results in 20% improvement for κ_c [585].
 4560 Increasing the electron energy further (energy frontier ep collider) does not give an essential improvement in
 4561 the sensitivity to anomalous couplings [587].




Figure 6.21: Contour plot for the anomalous couplings reachable at the LHeC based γp collider with the center of mass energy $\sqrt{s_{ep}} = 1.4$ TeV and integrated luminosity of $L_{int} = 2 \text{ fb}^{-1}$ (left) or $L_{int} = 10 \text{ fb}^{-1}$ (right)

4562 Table 6.4 shows that a sensitivity to anomalous coupling κ/Λ down to 0.01 TeV^{-1} could be reached.
 4563 Noting that the value of $\kappa/\Lambda = 0.01 \text{ TeV}^{-1}$ corresponds to $BR(t \rightarrow \gamma u) \approx 2 \times 10^{-6}$ which is two orders
 4564 smaller than the LHC reach with 100 fb^{-1} , it is obvious that even an upgraded LHC will not be competitive
 4565 with LHeC based γp collider in the search for anomalous $t\gamma q$ interactions. Different extensions of the SM
 4566 (SUSY, technicolor, little Higgs, extra dimensions etc.) predict branching ratio $BR(t \rightarrow \gamma q) = O(10^{-5})$, hence
 4567 the LHeC will provide an opportunity to probe these models.

4568 6.4.3 Excited quarks in γp collisions at LHeC

4569 Excited quarks will have vertices with SM quark and gauge bosons (photon, gluon, Z or W bosons). They
 4570 can be produced at ep and γp colliders via quark photon fusion. Interactions involving excited quark are
 4571 described by the Lagrangian of eq. 6.6 (where F is now a quark q)

4572 A sizeable f_s coupling would allow for resonant q^* production at the LHC via quark-gluon fusion. In that
 4573 case, the LHC would offer a large discovery potential for excited quarks and would be well suited to study
 4574 the properties and couplings of these new quarks. However, if the coupling of excited quarks to gq happens
 4575 to be suppressed, the LHC would mainly produce q^* via pair-production and would have little sensitivity to
 4576 couplings f/Λ or f'/Λ . Such couplings would be better studied, or probed down to much lower values, via
 4577 single-production of q^* at the LHeC. A study of the LHeC potential for excited quarks is presented in [588].
 4578 An example of the 3σ discovery reach, assuming $f = f' = f_s$ and setting Λ to be equal to the q^* mass, is
 4579 given in Fig. 6.22. Both decays $q^* \rightarrow q\gamma$ and $q^* \rightarrow qg$ have been considered here.

4580 6.4.4 Quarks from a fourth generation at LHeC

4581 The case of fourth generation quarks with magnetic FCNC interactions to gauge bosons and standard quarks,

$$\mathcal{L} = \left(\frac{\kappa_\gamma^{q_A q_i}}{\Lambda} \right) e_q g_e \bar{q}_4 \sigma_{\mu\nu} q_i F^{\mu\nu} + \left(\frac{\kappa_Z^{q_A q_i}}{2\Lambda} \right) g_Z \bar{q}_4 \sigma_{\mu\nu} q_i Z^{\mu\nu} + \left(\frac{\kappa_g^{q_A q_i}}{\Lambda} \right) g_s \bar{q}_4 \sigma_{\mu\nu} T^a q_i G_a^{\mu\nu} + h.c. \quad (6.13)$$




Figure 6.22: Observation reach at 3σ for coupling and excited quark mass at a γp collider with $\sqrt{s} = 1.27$ TeV from an analysis of (left) the jj channel and (right) the γj channel.

4582 is very similar to that of excited quarks. A γp collider based on LHeC would have a better sensitivity than
 4583 LHC to anomalous couplings κ_γ and κ_Z . A detailed study is presented in [544] and example results are
 4584 shown in Fig. 6.23. These figures also show the clear advantage of a γp collider compared to an ep collider,
 4585 for the study of new physics in γq interactions.

4586 6.4.5 Diquarks at LHeC

4587 The case of diquark production at LHeC has been studied in [589]. The production cross-section can be
 4588 sizeable at a high energy ep machine, especially when operated as a γp collider. The measurement of the
 4589 $\gamma p \rightarrow DQ + X$ cross-section, for a diquark DQ of known mass and known coupling to the diquark pair⁴
 4590 would provide a measurement of the electric charge of the diquark. It would thus be complementary to
 4591 the pp data, which offer no simple way to access the DQ electric charge. However, the diquark masses and
 4592 couplings that could be accessible at LHeC appear to be already excluded by the recent search for dijet
 4593 resonances at the LHC [590].

4594 6.4.6 Quarks from a fourth generation in Wq interactions

4595 In case fourth generation quarks do not have anomalous interactions as in Eq. 6.13, they (or vector-like quarks
 4596 coupling to light generations [591, 592]) could be produced in ep collisions by Wq interactions provided that
 4597 the V_{Qq} elements of the extended CKM matrix are not too small, via the usual vector WqQ interactions. An
 4598 example of the sensitivity that could be reached at LHeC is presented in [593], assuming some values for the
 4599 V_{Qq} parameters. Measurements of single Q production at LHeC would provide complementary information
 4600 to the LHC data, that could help in determining the extended CKM matrix.

4601 6.5 Sensitivity to a Higgs boson

4602 Understanding the mechanism of electroweak symmetry breaking is a key goal of the LHC physics programme.
 4603 In the SM, the symmetry breaking is realized via a scalar field (the Higgs field) which, at the minimum of the

⁴The LHC would observe diquark as di-jet resonances, and could easily determine its mass, width and coupling to the quark pair.

4604 potential, develops a non-zero vacuum expectation value. The breaking of the $SU(2)_L \times U(1)_Y$ symmetry
 4605 gives mass to the electroweak gauge bosons via the Higgs mechanism while the fermions obtain their mass
 4606 via Yukawa couplings with the Higgs field. The LHC experiments should be able to discover a Higgs boson
 4607 within the full allowable mass range, with an integrated luminosity of less than 10 fb^{-1} . Following its
 4608 discovery, it will be crucial to measure the couplings of this Higgs boson to the SM particles, in particular
 4609 to the fermions, in order to:

- 4610 • establish that the Higgs field is indeed accounting for the fermion masses, via Yukawa couplings $y_f H \bar{f} f$;
- 4611 • disentangle between the SM and (some of) its extensions. For example, despite the richer content of
 4612 the Higgs sector in the Minimal Supersymmetric Standard Model, only the light SUSY Higgs boson h
 4613 would be observable at the LHC in certain regions of parameter space. Its properties are very similar
 4614 to those of the SM Higgs H , and precise measurements of ratios $BR(\Phi \rightarrow VV)/BR(\Phi \rightarrow f\bar{f})$ will be
 4615 essential in determining whether or not the observed boson, Φ , is the SM Higgs scalar.

4616 The LEP experiments have ruled out a SM boson lighter than 114.5 GeV, and electroweak precision mea-
 4617 surements strongly suggest that the SM Higgs boson should be light. This is confirmed by the latest results
 4618 from Higgs searches at the LHC. With $\sim 5 \text{ fb}^{-1}$ of data collected at $\sqrt{s} = 7 \text{ TeV}$, the ATLAS and CMS
 4619 experiments constrain the SM Higgs mass to lie within 117.5 – 127.5 GeV [594, 595]. In this mass range,
 4620 the Higgs would decay into a $b\bar{b}$ pair with a branching ratio of $\sim 52 - 67\%$, but a measurement of the
 4621 $Hb\bar{b}$ coupling will be very challenging at the LHC [560, 586, 596]. Indeed, the observation of $H \rightarrow b\bar{b}$ in the
 4622 inclusive production mode is made very difficult by the huge QCD background, although a possible search
 4623 channel would be associated WH and ZH production, with highly boosted Higgs, leading to a high mass jet
 4624 with substructure [597]. The observability of the signal in the $t\bar{t}H$ production mode also suffers from a large
 4625 background, including background of combinatorics origin, and from experimental systematic uncertainties.

4626 The signal $H \rightarrow b\bar{b}$ may be observed in the exclusive production mode, thanks to the much cleaner
 4627 environment in a diffractive process. However, the production cross-section in this mode suffers from large
 4628 theoretical uncertainties, such that this measurement, if feasible at all, would not translate into a precise
 4629 measurement of the $Hb\bar{b}$ coupling.

4630 At the LHeC, a light Higgs boson could be produced via weak boson fusion (WBF) with a sizeable cross-
 4631 section. This section focusses on the observability of the signal $ep \rightarrow H + X \rightarrow b\bar{b} + X$ at LHeC, which may
 4632 be the first observation of the $H \rightarrow b\bar{b}$ decay. A recent similar study can be found in [598].

4633 6.5.1 Higgs production at LHeC

4634 In ep collisions, the Higgs boson could be produced in neutral current (NC) interactions via the ZZH
 4635 coupling, and in charged current (CC) interactions via the WWH coupling. The corresponding diagrams
 4636 are shown in Fig. 6.24, and the production cross-sections, as a function of the Higgs mass, is displayed
 4637 in Fig. 6.25. The WWH production largely dominates the total cross-section. As is the case for the
 4638 inclusive CC DIS interactions, the cross-section is much larger in e^-p collisions than in e^+p collisions, due
 4639 to the more favorable density of the valence quark that is involved (u in e^-p , d in e^+p), and to the more
 4640 favorable helicity factors. Table 6.5 shows the Higgs production cross-section (at leading order) via CC
 4641 interactions in e^-p collisions, for various values of the Higgs mass and three example values of the electron
 4642 beam energy. The scale dependency of these leading order estimate is of $\mathcal{O}(10\%)$. Next-to-leading order
 4643 corrections were calculated in [599, 600]. They are small, but can affect within $\mathcal{O}(20\%)$ the shape of some
 4644 kinematic distributions.

4645 6.5.2 Observability of the signal

4646 The dominating source of background at large missing transverse energy is coming from multi-jet production
 4647 in CC DIS interactions. In particular, a good rejection of the background coming from single top production
 4648 ($e^-b \rightarrow \nu t$), where the top decays hadronically, puts severe constraints on the acceptance and the resolution

M_H in GeV :	100	120	160	200	240	280
$E_e = 50$ GeV	102	81	50	32	20	12
$E_e = 100$ GeV	201	165	113	79	55	39
$E_e = 150$ GeV	286	239	170	123	90	67

Table 6.5: Production cross-section in fb of a SM Higgs boson via charged current interactions in e^-p collisions, for three example values of the electron beam energy.

4649 of the detector, as will be seen below. The background due to multijet production in NC interactions is also
4650 considered.

4651 MadGraph [601] has been used to generate SM Higgs production, CC and NC DIS background events.
4652 Calculations of cross-sections and generation of final states of outgoing particles are performed by MadGraph,
4653 given the beam parameters, considering all possible tree-level Feynman diagrams in the SM. In the case of
4654 NC, since the cross section is very high, diverging at low scattering angle, only processes producing two or
4655 more b quarks were generated in order to have sufficient MC statistics. By artificially increasing the mistag
4656 probability, it was possible to verify that, after the selection, essentially all the remaining NC background is
4657 indeed due to events with two truly b-quark jets in the final state. Fragmentation and hadronization processes
4658 were simulated by PYTHIA [130] with custom modifications to apply for ep collisions. Finally, particles were
4659 passed through a generic detector using the PGS [602] fast detector simulation tool. We assumed tracking
4660 coverage of $|\eta| < 3$ and calorimeter coverage of $|\eta| < 5$ with electromagnetic calorimeter resolution of
4661 $5\%/\sqrt{E(\text{GeV})}$ (plus 1% of constant term) and hadronic calorimeter resolution of $60\%/\sqrt{E(\text{GeV})}$. Jets
4662 were reconstructed by a cone algorithm with a cone size of $\Delta R = 0.7$. The efficiency of b-flavor tagging was
4663 assumed to be 60% and flat within the calorimeter coverage, whereas mistagging probabilities of 10% and
4664 1% for charm-quark jets and for light-quark jets, respectively, were taken into account.

4665 We set 150 GeV of electron beam energy with 7 TeV of proton beam energy as the reference beam
4666 configuration and assumed 120 GeV of SM Higgs boson mass in the MC simulation study. The results were
4667 compared with those with a different beam energy and Higgs mass.

4668 The following selection criteria were applied, based on observable variables generated by the PGS detector
4669 simulation, to distinguish $H \rightarrow b\bar{b}$ from the CC and NC DIS backgrounds.

4670 • **cut (1): Primary cuts**

- 4671 – Exclude electron-tagged events
- 4672 – $E_{T,miss} > 20$ GeV
- 4673 – $N_{jet}(P_{T,jet} > 20 \text{ GeV}) \geq 3$
- 4674 – $E_{T,total} > 100$ GeV
- 4675 – $y_{JB} < 0.9$, where $y_{JB} = \Sigma(E - p_z)/2E_e$
- 4676 – $Q_{JB}^2 > 400$ GeV, where $Q_{JB}^2 = E_{T,miss}^2/(1 - y_{JB})$

4677 • **cut (2): b-tag requirement**

- 4678 – $N_{b-jet}(P_{T,jet} > 20 \text{ GeV}) \geq 2$, where b-jet means a b-tagged jet

4679 • **cut (3): Higgs invariant mass cut**

- 4680 – $90 < M_H < 120$ GeV; due to the energy carried by the neutrino from b decays, the mass peaks
4681 are slightly lower than the true Higgs mass

4682 Fig. 6.26 shows the missing E_T and number of b-tagged jets for $H \rightarrow b\bar{b}$ events together with the CC and
4683 NC DIS background. The NC background is strongly suppressed by the missing E_T cut and electron-tag

4684 requirement. We required at least two b-tagged jets, and reconstructed the Higgs invariant mass using the
 4685 two b-tagged jets with lowest and second lowest η . After cuts (1) + (2) + (3) were applied, 44.4% of the
 4686 remaining CC background was due to single top production. The following cuts were further applied.

4687 • **cut (4): rejection of single top production** Single top events result in a final state with two b-jets
 4688 and a W decaying into two light-quark jets. The following cuts were found to be efficient in suppressing
 4689 this background.

4690 – $M_{jjj,top} > 250$ GeV, where the three-jet invariant mass ($M_{jjj,top}$) was reconstructed from two
 4691 b-jets with the lowest η and any third jet with the lowest η regardless of b-tag

4692 – $M_{jj,W} > 130$ GeV, where di-jet invariant mass ($M_{jj,W}$) was reconstructed from one b-jet with the
 4693 lowest η and any second jet with the lowest η regardless of b-tag but excluding the second lowest
 4694 η b-jet

4695 • **cut (5): forward jet tagging**

4696 – $\eta_{jet} > 2$ for the lowest- η jet excluding the two b -jets

4697 Fig. 6.27 shows the reconstructed three-jet ($M_{jjj,top}$) and di-jet ($M_{jj,W}$) invariant masses after cuts (1) and
 4698 (2) are applied. It is seen that, for CC background, the former peaks at the top mass and the latter peaks
 4699 at the W mass. The last cut is motivated by the fact that the jet from light quark participating in the CC
 4700 reaction for the signal is kinematically boosted to forward rapidity (in the proton beam direction), as shown
 4701 in Fig. 6.28.

4702 Fig. 6.29 shows the reconstructed Higgs mass distribution for an integrated luminosity of 10 fb^{-1} , after all
 4703 selection criteria except for the Higgs mass cut have been applied. The results are summarized in Table 6.6.
 4704 After the selection, 85 $H \rightarrow b\bar{b}$ events are expected for 10 fb^{-1} luminosity with a 150 GeV electron beam.
 4705 The signal to background ratio is 1.79 and the significance of the signal $S/\sqrt{N} = 12.3$. For a higher Higgs
 4706 mass, $m_H=150$ GeV, the production cross section decreases and the $b\bar{b}$ branching ratio also decreases. The
 4707 expected number of signal events becomes 25 and S/N and S/\sqrt{N} are 0.52 and 3.60, respectively. On
 4708 the other hand, with 60 GeV electron beam and five times larger luminosity (50 fb^{-1}), for 120 GeV Higgs,
 4709 124 $H \rightarrow b\bar{b}$ events are expected after the same cuts have been applied. Considering the CC and NC DIS
 background, S/N and S/\sqrt{N} are 1.05 and 11.4, respectively.

	Higgs production	CC DIS	NC $b\bar{b}j$	S/N	S/\sqrt{N}
cut (1)	816	123000	4630	6.38×10^{-3}	2.28
cut (1) + (2) + (3)	178	1620	179	9.92×10^{-2}	4.21
All cuts	84.6	29.1	18.3	1.79	12.3

Table 6.6: Expected $H \rightarrow b\bar{b}$ signal and background events with 150 GeV electron beam for an integrated luminosity of 10 fb^{-1} . Contents of the cuts are listed in text.

4710 The results shown here are subject to large uncertainties. First, as mentioned above, the very large NC
 4711 background cross section at forward scattering angles makes it impossible to simulate a sufficient number
 4712 of events to limit the Monte Carlo statistical uncertainty. It is estimated that the background evaluation,
 4713 with the above method where only events with at least two b quarks were simulated, has an uncertainty of
 4714 about a factor 3. With a full simulation, it can be expected to be negligible when the true measurement
 4715 is realized. Neglecting, therefore, this source of uncertainty, the systematic errors which will dominate are
 4716 expected to be the theoretical estimates of signals and backgrounds and instrumental effects: efficiency and
 4717 acceptance of lepton and jet reconstruction, b-tagging and mistagging probabilities. They are difficult to
 4718 estimate without real data and a real detector. The statistical uncertainty on the cross section can, however,
 4719 be estimated: 15% for the reference case of 150 GeV \times 7 TeV beams and a Higgs of mass 120 GeV. This
 4720

4721 represents a direct measure of the statistical uncertainty on $g_{Hbb}^2 \cdot g_{HWW}^2 / \Gamma_H$ where g_{Hbb} and g_{HWW} denote
 4722 the Hbb and HWW couplings and Γ_H is the total width of the Higgs.

4723 In addition to providing a constraint on the Hbb coupling, this measurement, combined with the mea-
 4724 surements of (products of) couplings expected from the LHC, would also provide an interesting consistency
 4725 check of the HWW coupling. The LHC is expected to measure the HWW coupling within about 15%
 4726 with a luminosity of 300 fb^{-1} from a fit to the various experimental observables [603]. However, this ex-
 4727 traction requires a few assumptions to be made, in particular relating the HZZ and HWW couplings. The
 4728 LHeC provides the unique opportunity to select experimentally the HWW coupling in Higgs production via
 4729 weak boson fusion, in contrast to WBF production at the LHC where the contributions from the HZZ and
 4730 HWW couplings can not be disentangled. Hence the LHeC could probe the HWW coupling without any
 4731 assumption on the HZZ coupling. This is of particular interest since these couplings could receive sizable
 4732 anomalous contributions from physics beyond the Standard Model. This possibility is further exploited in
 4733 the next paragraph.

4734 6.5.3 Probing Anomalous HWW Couplings at the LHeC

4735 The HWW vertex is an excellent handle on the quartic self-coupling of the scalar doublet. Its measurement
 4736 provides a direct insight into the nature of electroweak symmetry-breaking. Parametrising the $H(k) -$
 4737 $W_\nu^+(p) - W_\nu^-(q)$ vertex in the form $i\Gamma^{\mu\nu}(p, q) \epsilon_\mu(p) \epsilon_\nu^*(q)$, any deviations from the simple SM formula
 4738 $\Gamma_{(\text{SM})}^{\mu\nu}(p, q) = gM_W g^{\mu\nu}$ at a level incompatible with SM loop corrections would immediately indicate the
 4739 presence of new physics. Following Ref. [604], we can parametrize these deviations using two dimension-5
 4740 operators

$$\Gamma_{\mu\nu}^{(\text{BSM})}(p, q) = \frac{-g}{M_W} [\lambda (p \cdot q g_{\mu\nu} - p_\nu q_\mu) + i \lambda' \epsilon_{\mu\nu\rho\sigma} p^\rho q^\sigma] \quad (6.14)$$

4741 where λ and λ' are, respectively, effective coupling strengths for the CP -conserving and the CP -violating
 4742 parts.

4743 An ep collider has a unique advantage in the fact that the HWW vertex gives rise to the process
 4744 $e + p \rightarrow \nu_e + X + H(b\bar{b})$ through the single Feynman diagram shown in Figure 6.24(left), with no "pollution"
 4745 from the HZZ coupling. The final state has missing transverse energy (MET) and three jets J_1 , J_2 and
 4746 J_3 , of which two (say J_2 and J_3) are tagged as b -jets. It can be shown [604] that in the limit when there
 4747 is practically no energy transfer to the W bosons and the final states are very forward, the CP -conserving
 4748 (CP -violating) coupling λ (λ') contributes to the matrix element for this process a term of the form which
 4749 goes through zero when the missing transverse momentum is perpendicular to the p_T of the jet:

$$\mathcal{M} \sim +\lambda \vec{p}_T \cdot \vec{p}_T^{J_1} \quad \widetilde{\mathcal{M}} \sim -\lambda' \vec{p}_T \cdot \vec{p}_T^{J_1} . \quad (6.15)$$

4750 This explains the general trend illustrated in Figure 6.30, for an exact calculation of the $2 \rightarrow 3$ process
 4751 $eq \rightarrow \nu_e q' H$ at the parton level, with parton density functions from the CTEQ-6L1 set [131]. In the case
 4752 considered, 140 GeV electrons collide with 7 TeV protons and the Higgs boson mass is set to 120 GeV.

4753 A detailed simulation of the charged current process was discussed above in Sect. 6.5.2. Here, the analysis
 4754 is based on the kinematic cuts and efficiencies adopted in Ref. [598]. The azimuthal distribution has been
 4755 simulated in 10 bins, each of width $\pi/5$, and the signal and SM backgrounds have been calculated in each
 4756 bin using the same formulae used to create Figure 6.30, followed by a detailed simulation of fragmentation,
 4757 jet identification and detector effects. Assuming statistical errors dependent on the integrated luminosity
 4758 L , we then determine the sensitivity, for a given L , of the experiment to λ, λ' by making a log-likelihood
 4759 analysis. Our results are exhibited in Figure 6.31, where we present 95% exclusion plots for the λ and λ'
 4760 couplings as a function of L . It is clear from this figure that by the time the LHeC has collected 10 fb^{-1}
 4761 of data, we will be able to exclude the anomalous couplings to the level of 0.3 or lower. The experimental
 4762 set-up is somewhat more sensitive to the CP -even coupling, as evidenced by the narrower inaccessible region
 4763 indicated on the left panel. This study is further detailed in [605].




Figure 6.23: The achievable values of the anomalous coupling strength at ep and γp colliders for a) $q_4 \rightarrow \gamma q$ anomalous process and (b) $q_4 \rightarrow Zq$ anomalous process as a function of the q_4 mass; (c) the reachable values of anomalous photon and Z couplings with $L_{int} = 4.1 \text{ fb}^{-1}$.




Figure 6.24: Feynman diagrams for CC(left) and NC(right) Higgs production at the LHeC.




Figure 6.25: Production cross-section of a SM Higgs boson in ep collision with $E_e=150$ GeV and $E_p=7$ TeV, as a function of the Higgs mass.




Figure 6.26: Missing E_T (left) and number of b-tagged jets (right). Solid (black), dashed (red) and dotted (blue) histograms show $H \rightarrow b\bar{b}$, CC and NC DIS background, respectively. The right plot is for events passing cut (1) in the text.




Figure 6.27: Three-jet (left) and di-jet (right) invariant masses. Solid (black), dashed (red) and dotted (blue) histograms show $H \rightarrow b\bar{b}$, CC and NC DIS background, respectively.




Figure 6.28: η_{jet} distribution for the lowest- η jet excluding the two b -tagged jets. Solid (black), dashed (red) and dotted (blue) histograms show $H \rightarrow b\bar{b}$, CC and NC DIS background, respectively.




Figure 6.29: Reconstructed invariant Higgs mass after all selection criteria, except for the Higgs mass cut, have been applied. Points with error bars (black) show the $H \rightarrow b\bar{b}$ signal added to the CC (red histogram) and NC (hatched blue histogram) DIS background for an integrated luminosity of 10 fb^{-1} .




Figure 6.30: Illustrating the SM distribution in azimuthal angle and deviations therefrom which are due to anomalous HWW couplings.




Figure 6.31: Exclusion plots obtainable by a study of the azimuthal angle distributions at the LHeC for the CP -even coupling λ and the CP -odd coupling λ' . Note that this study is for $M_H = 120$ GeV.

Part III

Accelerator

4764

4765

Chapter 7

Ring-Ring Collider

7.1 Baseline Parameters and Configuration

Intense electron-proton beam interactions in the LHC tunnel can be realised with an electron storage ring and the LHC, as has been discussed already at the Lausanne workshop back in 1984. This solution was revived [17] when it had been seen that a hundred fold higher luminosity can be achieved than with HERA, owing to the intense proton beams available with the LHC. With an electron beam energy set between about 50 and 100 GeV and the 7 TeV proton beam energy one can realise a new ep collider of cms energy, $\sqrt{s} = 2\sqrt{E_e E_p}$ beyond 1 TeV. The advantages of a ring-ring (RR) configuration are that one uses known technology, with much experience from HERA and LEP, and that intense beams of both lepton charges are readily available.

For the present design study the electron beam energy has been set to 60 GeV as is discussed above, Sect. 2.3. With extra efforts and higher investments one may double that energy, as had been achieved for LEP [606], should there be strong physics requirements. One yet has to see that power losses vary $\propto E_e^{-4}$ and much higher synchrotron radiation occurs, which causes the operation and technical conditions to be increasingly demanding as E_e increases. A 60 GeV e^\pm beam may be polarised while, following the calculations presented below, that becomes questionable when E_e increases.

Due to the smallness of the ep tuneshift, synchronous pp and ep interactions can be realised with the LHC and the LHeC. This requires to bypass the active pp experiments with separate tunnels which, in adjacent caverns, can house the RF. Excavation of such tunnels may proceed in parallel to LHC operation, like the CMS cavern was excavated while LEP ran. Due to machine hardware or unfortunate geological conditions, none of the 4 machine points (3,4 and 6,7) could house the LHeC interaction region. For the present study IP2 was chosen as the ep IR, currently housing ALICE, and bypasses were considered for ATLAS and CMS.

Maximum luminosity can be achieved with focussing magnets placed close to the interaction point. This limits, however, the polar angle acceptance. Two principal interaction optics solutions have been developed, the high luminosity optics, with acceptance down to about 8° , and the large acceptance optics, covering polar angles down to 1° . As is shown below, there is only a factor of 4 difference in the product of the β functions. It then is likely that one further develops the large acceptance solution only, but both are fully described here.

A complete lattice has been designed for the new ring. This takes into account some peculiarities due to the LHC. In particular, an asymmetric FODO cell, of half the LHC FODO cell length, had to be designed to account for LHC service modules and the DFBS. Similarly, a non-standard solution for the dispersion matching had to be developed, using 8 individually powered quadrupoles instead of regulating the position of dipoles which is too constrained by the LHC.

A further baseline parameter is the injection energy. The LHeC electron storage ring differs from LEP in its bunch structure. The LHeC has a maximum of about $2 \cdot 10^{10}$ electrons per bunch in a much higher repetition rate than LEP, which had a bunch intensity of $4 \cdot 10^{11}$. The smaller intensity allows to inject at

4803 lower energy than LEP. For the current design a new injector is considered, using linac technology with high
4804 frequency cavities, of energy of 10 GeV. This poses constraints on the quality of the main dipole magnets,
4805 which have to ensure a magnetic field reproducibility of about 10^{-4} . C - (and H) shape prototype magnets
4806 have been developed, built and successfully tested at BINP Novosibirsk. Alternative magnets have been built
4807 and are being tested also at CERN. Besides the magnetic field properties, attention was given to small outer
4808 dimensions (of about 35 cm^2 compared to 50 cm^2 at LEP) and to a reduction of the weight (from 800 kg/m
4809 at LEP to 250 kg/m for the LHeC) in order to facilitate the installation. The total number of magnets is
4810 less than 4000. Such an amount is large, but it may be obtained within a few years production, following
4811 1 : 1 prototyping within the technical design phase.

4812 The key question for the storage ring is its possible installation in the LHC tunnel without posing too
4813 harsh constraints on the LHC operation schedule. A first inspection has been made of the various elements
4814 of concern, as described below, with the conclusion that installation of the LHeC was possible but very
4815 demanding. For a TDR of the ring-ring solution, a detailed 3D CAD integration study of both accelerators
4816 is mandatory.

4817 The subsequent chapter describes the studies dedicated to characterize the RR option. It is followed by a
4818 similar chapter on the LR option. Much of the system hardware is common or similar and thus it is contained
4819 in a following chapter. From today's perspective both options may be realised within the coming ten years,
4820 albeit the differences which distinguish them. It is part of the referee process to understand the relative
4821 merits in terms of physics, technics, operation, infrastructure and future developments, which is expected
4822 to lead to a sufficiently deep consideration and comparison of the storage ring versus the linac options, such
4823 that the TDR can be developed for just one of them. Since, however, the cavities, for the ring injector and
4824 for the linac, the dipole magnets, for the ring and for the linac return arcs, and the 3 beam superconducting
4825 triplet of magnets near the interaction point, all have very similar constraints, a next phase of prototyping
4826 and design has been possible to already prepare.

4827 **7.2 Baseline Parameters and Configuration**

4828 **7.3 Geometry**

4829 All lattice descriptions in this chapter are based on LHeC lattice Version 1.1.

4830 **7.3.1 General Layout**

4831 The general layout of the LHeC consists of eight arcs, six straight sections and two bypasses around the
4832 experiments in Point 1 and Point 5. The e-p collision experiment is assumed to be located in Point 2, the
4833 only interaction point of the beams. All straight sections except those in the bypasses have the same length
4834 as the LHC straight sections: 538.8 m at even points and 537.8 m at odd points.

4835 The insertions shared with the LHC are already used for the experiments or for LHC equipment. Therefore
4836 the RF for the electron ring is installed in the straight sections of the bypasses (see section 9.3). For the same
4837 reason the beam is injected in the bypass around Point 1. Point 1 is preferred over Point 5 for geological
4838 and infrastructural reasons. The overall layout of the LHeC is shown in Fig. 7.1.

4839 **7.3.2 Electron Ring Circumference and e-p Synchronization**

4840 The LHeC electron beam collides only in one point (Point 2) with the protons of the LHC. This leaves the
4841 options to either exactly match the circumferences of the proton and electron rings or to allow a difference of
4842 a multiple of the LHC bunch spacing. In the case of different circumferences the proton beam could become
4843 unstable due to beam-beam interactions with the electrons [607], [608]. To avoid this possible effect in the
4844 LHeC, the electron ring circumference is matched exactly to the proton ring circumference.

4845 The circumference can be adjusted in two ways:

1. Different bypass designs, e.g. inner and outer bypass, which compensate each other in length.
2. Radial displacement of the electron ring to the inside or outside of the LHC in the places where the two rings share the same tunnel to compensate for the path length difference caused by the bypasses.

The various design possibilities for the bypasses are discussed in Sec. 7.3.4. Considering their characteristics, the best choice seems to be outer bypasses around both experiments.

In general asynchronization between the e- and p-beam could arise from small differences in the circumferences of the central orbits. Both beams could be synchronized by adjusting the RF frequency of the electron or proton beam accordingly [609]. The feasibility of this method was demonstrated with proton lead in the LHC [610] and also for electrons and protons in Hera [611].

7.3.3 Idealized Ring

In the following the average between LHC beam 1 and beam 2 is taken as reference geometry for the LHC.

General Layout

To compensate the path length differences from the bypasses, the electron ring is placed on average 61 cm to the inside of the LHC in the sections where both rings share the tunnel. For this a complete ring with an ideally constant radial offset of 61 cm to the LHC was designed. In the following we refer to this ring as the *Idealised Ring*.

In addition to the horizontal displacement, the electron ring is set 1 m above the LHC in order to minimize the interference with the LHC elements. The main remaining conflict in the arc are then the service modules as shown in Fig. 7.54 and the DFBs in the insertions (see section 7.16.1). A representative cross section of the LHC tunnel is shown in Fig. 7.2.

In the main arcs the service modules have a length of 6.62 m and are installed at the beginning of each LHC arc cell. The insertions host a different number of DFBs with a varying placement and length. The idealised ring lattice is designed to avoid overlaps of magnet elements with all service modules in the main arcs. In order to show that it is possible to design an optics with no e-ring elements at any DFB positions in the insertions, the dispersion suppressors of the even and odd insertions were adapted to the DFB positions and lengths in IR2 and IR3 respectively. For simplicity all straight sections are filled with a regular FODO cell structure.

Geometry

To adjust the beam optics to the regular reappearance of the service modules at the beginning of each LHC arc cell it was suggested to use a multiple n or submultiple $1/n$ ($n \in \mathbb{N}$) of the LHC arc cell length as LHeC FODO cell length. Beside the integration constraints, the cell has to provide the right emittance. Taking half the LHC arc cell length as LHeC FODO cell length already fulfils this second criterion (Sec. 7.4.1).

As the LHC arc cell is symmetric, the best geometrical alignment with the LHC main arc would be achieved, if the LHeC cell also had a symmetrical layout. Because of the service modules, no elements can be placed in the first 6.9 m of two consecutive cells. If all cells had the same layout, another 6.9 m would be lost in the second FODO cell. This would result in additional unwanted synchrotron radiation losses as the energy loss in a dipole magnet is proportional to the inverse length of the dipole

$$U_{\text{dipole}} = \frac{C_\gamma}{2\pi} E_0^4 \frac{\theta^2}{l}, \quad C_\gamma = \frac{4\pi}{3} \frac{r_e}{(m_e c^2)^3} \quad (7.1)$$

where θ is the bending angle, l the length of the dipole and E_0 the beam energy. In order to avoid this, the LHeC arc cell is a double FODO cell, symmetric in the positioning of the quadrupoles but asymmetric in the placement of the dipoles (Fig. 7.3).

The bending angle in the arc cells and also in the DS is determined by the LHC geometry. In the following we refer to the LHC DS as the section from the end of the arc to the beginning of the LSS. With

4888 this definition the LHC DS consists of two cells. Keeping the same conversion rule as in the arc (one LHC
 4889 FODO cell corresponds to two LHeC FODO cells), the LHeC DS would then ideally consist of 4 equal cells.
 4890 For consistency the ratio between the LHeC DS and arc cell lengths is the same as between the LHC DS
 4891 and arc cell. For the LHC this ratio is 2/3. This leaves the following choices for the number of dipoles in
 4892 the arc and DS cell:

$$N_{\text{Dipole, arc cell}} = \frac{3}{2} N_{\text{Dipole, DS cell}} = 3, 6, 9, 12, 15 \dots \quad (7.2)$$

4893 A good compromise between a reasonable dipole length and optimal use of the available space for the bending
 4894 is 15 dipoles per arc cell. The dipoles are then split up in packages of 3 + 4 + 4 + 4 in one arc cell and 2 + 3
 4895 in one DS cell.

4896 Beside the bending angle, the module length of the electron ring has to be matched to the LHC geometry.
 4897 As the electron ring is radially displaced to the inside of the proton ring, all e-ring modules are slightly shorter
 4898 than their proton ring equivalents (Table 7.1).

	Proton Ring	Electron Ring
Arc Cell Length	106.9 m	106.881 m
DSL Length (even points)	172.80 m	172.78 m
DSR Length (even points)	161.60 m	161.57 m
DSL Length (odd points)	173.74 m	173.72 m
DSR Length (odd points)	162.54 m	162.51 m

Table 7.1: Proton and Electron-Ring Module Lengths. DSL=Dispersion Suppressor Left side, DSR=Dispersion Suppressor Right side

4899 The above considerations already fix the bending angle of the dipoles, which leaves only position and
 4900 length as free parameters. Ideally the dipole length would be chosen as long as possible, but because of the
 4901 asymmetry of the arc cell, the dipoles have to be shortened and moved to the right in order to fit the LHC
 4902 geometry.

4903 The LHeC DS layout would ideally be similar to the LHC DS layout (Fig. 7.4), but has to be modified in
 4904 order to leave space for the DFBS in the DS region. In the final design the dipoles are placed as symmetrically
 4905 as possible between the regular arrangement of the quadrupoles (Fig. 7.5, 7.6). The difference between the
 4906 LHC proton ring and the idealised LHeC electron ring is shown in Fig. 7.7 and 7.8.

4907 7.3.4 Bypass Options

4908 In the design of the e-ring geometry, it is foreseen to bypass the LHC experiments at Point 1 and Point
 4909 5. The main requirements for both bypasses are that all integration constraints are respected, synchrotron
 4910 radiation losses are not significantly increased and that the change in circumference can be compensated by
 4911 increasing or decreasing the radius of the ring.

4912 Three different options are considered as basic bypass designs:

4913 **Vertical Bypass:** A vertical bypass would have to be a vertically upward bypass as downward would
 4914 imply crossing the LHC magnets and other elements. For this a separation of about 20 to 25 m is
 4915 required [612]. This can only be achieved by strong additional vertical bending. In general a vertical
 4916 bypass would therefore be rather long, increase the synchrotron radiation due to the additional vertical
 4917 bends and decrease the polarization compared to a horizontal bypass. A vertical bypasses is therefore
 4918 only considered as an option if horizontal bypasses are not possible.

4919 **Horizontal Inner Bypass:** A horizontal inner bypass can be constructed by simply decreasing the bending
 4920 radius of the main bends. Consequently the synchrotron radiation losses for an inner bypass are larger
 4921 than for a comparable outer bypass. The advantage of an inner bypass is, if used in combination with

4922
4923

an outer one, that it reduces the circumference and the two bypasses could compensate each other's path length differences.

4924
4925
4926

Horizontal Outer Bypass: A horizontal outer bypass uses the existing curvature of the ring instead of additional or stronger dipoles and consequently does not increase the synchrotron radiation losses. In general this is the preferred option.

4927

7.3.5 Bypass Point 1

4928
4929
4930
4931
4932

The cavern in Point 1 reaches far to the outside of the LHC, so that a separation of about 100 m would be necessary in order to fully bypass the experimental hall. For a bypass on the inside, a smaller separation of about 39 m would be required. For an inner bypass with minimal separation, the bending strength in three normal arc cells would have to be doubled resulting in a bypass of more than 2 km length. A sketch of such an inner bypass is shown in Fig. 7.9.

4933
4934
4935
4936

Instead of a long inner bypass, an outer bypasses using the existing survey gallery is chosen as final design. With this design the separation is brought down to 16.25 m. The RF is installed in the straight section next to the straight section of the proton ring. The electron beam is injected into the arc on the right side of the bypass. The design is shown in Fig. 7.10.

4937

7.3.6 Bypasses Point 5

4938
4939
4940
4941
4942

Due to the compact design of the cavern in Point 5 a separation of only about 20 m is needed to completely bypass the experiment on the outside (Fig. 7.11). The separation in the case of an inner horizontal bypass or a vertical bypass would be the same or larger and therefore, as in the case of Point 1, the horizontal outer bypass is preferred over an inner or vertical one. The RF is installed in the centre straight section parallel to the proton ring.

4943

7.3.7 Matching Proton and Electron Ring Circumference

4944
4945
4946
4947

Both bypasses in Point 1 and Point 5 require approximately the same separation and a similar design was chosen for both. To obtain the necessary separation Δ_{BP} a straight section of length s_{BP} is inserted into the lattice of the idealised ring (Sec. 7.3.3) in front of the last two arc cells. The separation Δ_{BP} , the remaining angle θ_{BP} and the inserted straight section s_{BP} are related by (Fig. 7.12):

$$\Delta_{BP} = s_{BP} \sin \theta_{BP} \quad (7.3)$$

4948
4949
4950
4951
4952

As indicated in Fig. 7.12 the separation could be increased by inserting a S-shaped chicane including negative bends. The advantage of additional bends would be the faster separation of the electron and proton ring. On the other hand the additional bends would need to be placed in the LHC tunnel, the straight sections of the bypass would be reduced and the synchrotron radiation losses increased. Hence this is not the preferred solution.

4953
4954
4955

In the following, estimates for the current bypass design, which does not include any extra bends, are presented. Given the separation, angle and length of the inserted straight section, the induced change in circumference is then:

$$\Delta s_{BP} = s_{BP} - x_{BP} = 2\Delta_{BP} \tan\left(\frac{\theta_{BP}}{2}\right) \quad (7.4)$$

4956

This change can be compensated by a change in radius of the idealised ring by:

$$\Delta s_{BP} = 2\pi\Delta R \quad (7.5)$$

4957
4958

Taking the change in radius into account, the separation Δ_{BP} has to be substituted by $\Delta_{BP,tot} := \Delta_{BP} + \Delta R$. The radius change and the total separation are then related by:

$$\Delta R = \frac{\Delta_{BP}}{\pi \cot\left(\frac{\theta_{BP}}{2}\right) - 2}, \quad \text{with } \Delta_{BP} = \Delta_{BP1} + \Delta_{BP5} \quad (7.6)$$

As the bypass in Point 1 passes through the existing survey gallery, the geometry and with it the separation in Point 1, cannot be changed. The bypass in Point 5, on the other hand, is fully decoupled from the existing LHC cavern and tunnel and is therefore used for the fine adjustment of the circumference. The design values of both bypasses are summarized in Table 7.2.

	Point 1	Point 5
Total bypass length	1303.3 m	1303.7 m
Separation	16.25 m	20.56 m
Dispersion free straight section	172 m	297 m
Ideal radius change of the idealised ring	61 cm	

Table 7.2: Lengths characterising the bypasses.

4962

4963 7.4 Layout and Optics

Throughout the whole electron ring lattice, the choice of the optics is strongly influenced by the geometrical constraints and shortage of space in the LHC tunnel. The main interference with the LHC beside Point 1 and Point 5, which have to be bypassed, are the service modules and DFBs in the tunnel, where no electron ring elements can be placed.

4968 7.4.1 Arc Cell Layout and Optics

The LHC service modules are placed at the beginning of each LHC main arc cell. In order to obtain a periodic solution of the lattice, the electron ring arc cell length can only be a multiple or $1/n$ th, $n \in \mathbb{N}$, of the LHC FODO cell length. Given the same phase advance and bending radius, the emittance increases with increasing cell length L of a FODO cell. In the case of the LHeC electron ring a FODO cell length corresponding to half the LHC FODO cell length delivers an emittance close to the design value of $\epsilon_{\text{rms},x/y} = 5.0/2.5$ nm. The emittance of a cell with the full LHC FODO cell length is about a factor of 4 too large.

Choosing half the LHC FODO cell length divides the arc into 23 equal double FODO cells with a symmetric configuration of the quadrupoles and an asymmetric distribution of the dipoles, precisely 8 dipoles in the first FODO cell and 7 in the second. The dipole configuration is asymmetric in order to use all available space for the bending of the e-beam and consequently minimize the synchrotron radiation losses. With a phase advance of 180° horizontally and 120° vertically over the complete double FODO cell, which corresponds to a phase advance of $90^\circ/60^\circ$ per FODO cell, the horizontal emittance lies with 3.96 nm well below the design value of 5 nm. The optics of one arc cell is shown in Fig. 7.3 and the parameters are listed in Table 7.3.

4983 7.4.2 Insertion Layout and Optics

For simplicity all even and all odd insertions of the electron ring have the same layout as described in Sec. 7.3.1. Each insertion is divided in three parts: the dispersion suppressor on the left side (DSL), the straight section and the dispersion suppressor on the right side (DSR).

4987 Dispersion Suppressor

Various well known standard DS designs like the missing bend or half bend scheme exist, but they are all based on specific placement of the dipoles. In the case of the LHeC the position of the dipoles is strongly determined by the LHC geometry and does not match any of the standard schemes. Therefore the dispersion matching is achieved by 8 individually powered quadrupoles and not with the positioning of the dipoles. The DS on the left side is split into two DS sections, reaching from the first DFB to the second and from the

Beam Energy	60 GeV
Phase Advance per Cell	180°/120°
Cell length	106.881 m
Dipole Fill factor	0.75
Damping Partition $J_x/J_y/J_e$	1.5/1/1.5
Coupling constant κ	0.5
Horizontal Emittance (no coupling)	3.96 nm
Horizontal Emittance ($\kappa = 0.5$)	2.97 nm
Vertical Emittance ($\kappa = 0.5$)	1.49 nm

Table 7.3: Optics Parameters of one LHeC arc cell with a phase advance of 90°/60° per half cell.

second to the beginning of the straight section. In the DSL the quadrupoles are distributed equally in each section. In the DSR they are placed with equal distances from each other throughout the complete DS. This layout turned out to be better for the right side due to the different arrangement of the DFBS. The DSs of the even and odd points differ slightly in their length but have the same general layout. The lengths of the DSs are listed in Table 7.1. The DS optics are shown in Fig. 7.5 and 7.6.

4998 Straight Section

4999 For simplicity the straight sections consist of a regular FODO lattice with a phase advance of 90°/60° except
5000 the straight section at Point 3 and Point 7 where the phase advance of the FODO cells is used for the
5001 adjustment of the working point. In a later stage the lattice and optics of the straight sections will have to
5002 be adjusted to the various insertions.

5003 7.4.3 Bypass Layout and Optics

5004 The general layout and nomenclature of the bypasses is illustrated in Fig. 7.13. The straight sections LSSL,
5005 LSSR and IR are dispersion free sections reserved for the installation of RF, wiggler(s), injection etc. Two
5006 normal arc cells (4 FODO cells) with 8 individual quadrupoles are used as dispersion suppressor before the
5007 first straight section LSSL and after the last straight section LSSR. In the sections TLIR and TRIR the
5008 same configuration of dipoles is kept as in the idealised lattice for geometric reasons. Among this fixed
5009 arrangement of dipoles 14 matching quadrupoles per side are placed as equally as possible.

5010 The straight sections consist of a regular FODO lattice with a phase advance of 90°/60°.

5011 The complete bypass optics in Point 1 and Point 5 are shown in Fig. 7.14 and 7.15.

5012 7.4.4 Chromaticity Correction

5013 The phase advance of one LHeC FODO cell of 90°/60° suggests a chromaticity correction with in total 5
5014 interleaved sextupole families, 2 horizontal and 3 vertical. In order to reduce the chromatic stopband and the
5015 off momentum beta beating each arc contains an equal number of sextupoles per family, so $n \cdot 2$ horizontal
5016 and $m \cdot 3$ in the vertical. Further to reduce the sextupole strength and therefore the excitation of resonances,
5017 the families are completed by placing sextupoles also in the dispersion suppressors. This yields a sextupole
5018 scheme as illustrated in Fig. 7.16. A large part of the total natural chromaticity usually comes from the
5019 experiments due to their large β -functions and magnet strength in the final focus quadrupoles. This is only
5020 true for the vertical plane of the 1 Degree optics. In the case of the 10 Degree option and the horizontal
5021 plane of the 1 Degree optics, all insertions including the experimental insertion in Point 2 contribute more
5022 or less equally to the chromaticity. This suggests a global correction of the chromaticity with 2 sextupoles
5023 for the horizontal and 3 for the vertical plane for the 10 Degree option. For the 1 Degree option a local

5024 correction of the off-momentum beta-beating with the two arcs adjacent to IP2 could be considered instead
 5025 of a simple global correction [613]. The contribution of the different insertions to the total chromaticity is
 5026 listed in Table 7.4 and Table 7.5.

	$-dQ_{x/y}$	$-(dQ_{x/y}/dQ_{x/y,tot}) \cdot 100$
full sequence	142.1/115.6	100/100
IR 1	9.6/8.2	6.8/7.1
IR 2	4.6/3.8	3.2/3.3
IR 3/7	4.5/3.6	3.2/3.1
IR 4/6/8	4.6/3.8	3.2/3.3
IR 5	10.0/7.8	7.0/6.7

Table 7.4: Contribution of the insertions to the natural chromaticity for the 10 Degree Option

	$-dQ_{x/y}$	$-(dQ_{x/y}/dQ_{x/y,tot}) \cdot 100$
full sequence	144.1/136.2	100/100
IR 1	9.9/7.5	6.7/5.5
IR 2	7.5/25.0	5.2/18.3
IR 3/7	4.7/3.7	3.2/2.7
IR 4/6/8	4.6/3.7	3.2/2.7
IR 5	10.2/7.8	7.0/5.7

Table 7.5: Contribution of the insertions to the natural chromaticity for the 1 Degree Option

5027 In general the chromaticity correction is expected to be rather unchallenging.

5028 7.4.5 Working Point

5029 Because of the bypasses and the single interaction region, the LHeC lattice has no reflection or rotation
 5030 symmetry. As 50% emittance ratio is required, betatron coupling resonances may be excited and must be
 5031 taken into account for the choice of the working point. In addition the beam will suffer a maximum beam-
 5032 beam tune shift of 0.087 in both planes in the case of the 1 Degree option and 0.085 in the horizontal and
 5033 0.090 in the vertical plane in the case of the 10 Degree option. Besides the systematic resonances also the
 5034 first synchrotron sidebands of at least the integer resonances have to be avoided. Taking the beam-beam
 5035 tune shift and the detuning with amplitude from head-on interactions into account a possible working point
 5036 could be $Q_x = 123.155/Q_y = 83.123$ for the 1 Degree as well as for the 10 Degree option. The working point
 5037 diagrams for both cases are shown in Figs. 7.17 and 7.18.

5038 7.4.6 Aperture

5039 The current LHeC e-ring magnet apertures (see section ??) are based on the experience from LEP [614] ap-
 5040 plied on the LHeC arc cells. They correspond to minimum 36.2σ hor./ 39.9σ ver. in the arc dipoles,
 5041 32.9σ hor./ 59σ ver. in the arc quadrupoles, 14.7σ hor./ 35.9σ ver. in the insertion dipoles and
 5042 14.6σ hor./ 51.6σ ver. in the insertion quadrupoles. In the estimate all insertions were included whereas for
 5043 the IP (Point 2) the values were only calculated for the 1 Degree option. All values are summarized in Table
 5044 7.6, 7.7, 7.8, 7.9. The hor. aperture in the insertion dipoles and quadrupoles is slightly too tight, but as
 5045 the gradients are small, it can be easily increased by around 5 to 7 mm without changing considerably the

5046 magnet design. In all calculations a gaussian profile in all three dimensions was assumed and the maximum
 5047 beam size is consequently given by:

$$\sigma_{x,y} = \sqrt{\beta_{x,y}\epsilon_{x,y} + D_{x,y}^2\sigma_E^2} \quad (7.7)$$

5048 where $\epsilon_{x,y}$ are the design emittances of 5 and 2.5 nm respectively.

Hor. Half Apert. Dip.	30 mm
Ver. Half Apert. Dip.	20 mm
Max. Hor. Beam Size	0.82 mm
Max. Ver. Beam Size	0.50 mm
Hor. Apert./Max. Beam Size	36.2
Ver. Apert./Max. Beam Size	39.9

Table 7.6: Aperture and beam sizes for the arc dipoles

Hor. Half Aperture Dipole	30 mm
Ver. Half Aperture Dipole	20 mm
Max. Hor. Beam Size	2.04 mm
Max. Ver. Beam Size	0.56 mm
Hor. Aperture/Max. Beam Size	14.7
Ver. Aperture/Max. Beam Size	35.9

Table 7.7: Aperture and beam sizes for the insertion dipoles including Point 2 (1 Degree Option)

Apert. Radius Arc Quad.	30 mm
Max. Hor. Beam Size	0.91 mm
Max. Ver. Beam Size	0.51 mm
Hor. Apert./Max. Beam Size	32.9
Ver. Apert./Max. Beam Size	59.0

Table 7.8: Aperture and beam sizes for the arc quadrupoles

Apert. Radius Quad.	30 mm
Max. Hor. Beam Size	2.06 mm
Max. Ver. Beam Size	0.58 mm
Hor. Apert./Max. Beam Size	14.6
Ver. Apert./Max. Beam Size	51.6

Table 7.9: Aperture and beam sizes for the insertion quadrupoles including Point 2 (1 Degree Option)




Figure 7.1: Schematic Layout of the LHeC: In grey the LEP tunnel now used for the LHC, in red the LHC extensions. The two LHeC bypasses are shown in blue. The RF is installed in the central straight section of the two bypasses. The bypass around Point 1 hosts in addition the injection.




Figure 7.2: Representative cross section of the LHC tunnel. The location of the electron ring is indicated in red.




Figure 7.3: Electron ring arc cell optics. One arc cell consists of two FODO cells symmetric in the placement of the quadrupoles and asymmetric for the dipoles.




Figure 7.4: LHC DS on the left side of IP2.




Figure 7.5: LHeC IR for even IRs, based on the DFB configuration in Point 2.




Figure 7.6: LHeC IR for odd IRs, based on the DFB configuration in Point 3.




Figure 7.7: Radial distance between the idealised electron ring and the proton ring




Figure 7.8: LHC and LHeC. The distance between the two rings is exaggerated by a factor 2000.




Figure 7.9: Example of an inner Bypass around Point 1. The Bypass is shown in blue, The LHC proton ring in black.




Figure 7.10: Final bypass design using the survey gallery in Point 1. The LHC proton ring is shown in black, the electron ring in red and the tunnel walls in blue. Dispersion free sections reserved for the installation of RF, wiggler(s), injection and other equipment are marked in light blue. The injection is marked in green and is located in the right arc of the bypass. Beginning and end of the bypass are marked with S.BP1 and E.BP1




Figure 7.11: Horizontal outer bypass in Point 5. The LHC proton ring is shown in black, the electron ring in red and the tunnel walls in blue. Dispersion free sections reserved for the installation of RF, wiggler(s), injection and other equipment are marked in light blue. Beginning and end of the bypass are marked with S.BP5 and E.BP5




Figure 7.12: Outer bypass: a straight section is inserted to obtain the required separation. A larger separation could be achieved by inserting inverted bends.




Figure 7.13: Bypass layout and nomenclature.




Figure 7.14: Bypass optics Point 1.




Figure 7.15: Bypass Optics Point 5.




Figure 7.16: LHeC Sextupole Scheme for a phase advance of $90^\circ/60^\circ$ with sextupoles also placed in the dispersion suppressor.




Figure 7.17: Working Point for the 1 Degree optics. The dashed lines are the coupling resonances up to 4th order, the solid lines the constructive resonances up to 4th order. The black line indicates the working point without beam-beam tune shift, while the blue lines indicate the working point with beam-beam tune shift.




Figure 7.18: Working Point for the 10 Degree optics. The dashed lines are the coupling resonances up to 4th order, the solid lines the constructive resonances up to 4th order. The black line indicates the working point without beam-beam tune shift, while the blue lines indicate the working point with beam-beam tune shift.

7.5 Layout

The design of the Interaction Region (IR) of the LHeC is particularly challenging as it has to consider boundary conditions from

- The lattice design and beam optics of the electron and proton beam
- The geometry of the LHC experimental cavern and the tunnel
- The beam separation scheme which is determined by the bunch pattern of the LHC standard proton operation and related to this the optimisation of the synchrotron light emission and collimation
- The technical feasibility of the hardware.

Therefore the IR has to be optimised with respect to a well matched beam optics that adapts the optical parameters from the new electron-proton interaction point to the standard LHC proton beam optics in the arc and to the newly established beam optics of the electron ring. At the same time the two colliding beams as well as the non-colliding proton beam of LHC have to be separated efficiently and guided into their corresponding magnet lattices. As a general rule that has been established in the context of this study any modification in the standard LHC lattice and any impact on the LHC proton beam parameters had to be chosen moderately to avoid detrimental effects on the performance of the LHC proton-proton operation.

The layout and parameters of the new e/p interaction point are defined by the particle physics requirements. At present the physics programme that has been proposed for the LHeC [615] follows two themes - a high luminosity, high Q^2 programme requiring a forward and backward detector acceptance of around 10° and a low x, low Q^2 programme, which requires an increased detector acceptance in forward and backward direction of at least 1° and could proceed with reduced luminosity. Accordingly two machine scenarios have been studied for the interaction region design. Firstly, a design that has been optimised for high luminosity with an acceptance of 10° and secondly, a high acceptance design that allows for a smaller opening angle of the detector. In both cases the goal for the machine luminosity is in the range of $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$ but the layouts differs in the magnet lattice, the achievable absolute luminosity and mainly the synchrotron radiation that is emitted during the beam separation process. Both options will be presented here in detail and the corresponding design luminosity, the technical requirements and the synchrotron radiation load will be compared. In both cases however, a well matched spot size of the electron and proton beam had to be established at the collision point: Experience in SPS and HERA [616], [617] showed that matched beam cross sections have to be established between the two colliding beams to guarantee stable beam conditions. Considering the different nature of the beams, namely the emittances of the electron beam in the two transverse planes, the interaction region design has to consider this boundary condition and the beam optics has to be established to achieve equal beam sizes $\sigma_x(p) = \sigma_x(e)$, $\sigma_y(p) = \sigma_y(e)$ at the IP.

The basic beam parameters however like energy, particle intensity and beam emittances are identical for both designs, determined by the electron and proton ring lattices and the pre-accelerators. They are summarised in Table 7.10.

Colliding two beams of different characteristics, the luminosity obtained is given by the equation

$$L = \sum_{i=1}^{n_b} (I_e I_p) \frac{1}{e^2 f_0 2\pi \sqrt{\sigma_{xp}^2 + \sigma_{xe}^2} \sqrt{\sigma_{yp}^2 + \sigma_{ye}^2}}, \quad (7.8)$$

where $\sigma_{x,y}$ denotes the beam size of the electron and proton beam in the horizontal and vertical plane and I_e, I_p the electron and proton single bunch currents. In all IR layouts the electron beam size at the IP is matched to the proton beam size in order to optimise the delivered luminosity and minimise detrimental beam beam effects.

The main difference of the IR design for the electron proton collisions with respect to the existing LHC interaction regions is the fact that the two beams of LHeC cannot be focussed and / or guided at the same time: The different nature of the two beams, the fact that the electrons emit synchrotron radiation

Table 7.10: Main parameters for e/p collisions.

Quantity	unit	e	p
Beam energy	GeV	60	7000
Total beam current	mA	100	860
Number of bunches		2808	2808
Particles/bunch N_b	10^{10}	2.0	17
Horiz. emittance	nm	5.0	0.5
Vert. emittance	nm	2.5	0.5
Bunch distance	ns	25	




Figure 7.19: Schematic layout of the LHeC 10 degree interaction region

5092 and mainly the large difference in the particle momentum make a simultaneous focusing of the two beams
 5093 impossible. The strong gradients of the proton quadrupoles in the LHC triplet structure cannot be tolerated
 5094 nor compensated for the electron lattice and a stable optical solution for the electrons is not achievable under
 5095 the influence of the proton magnet fields. The electron beam therefore has to be separated from the proton
 5096 beam after the collision point before any strong “7 TeV like” magnet field is applied.

5097 In order to obtain still a compact design and to optimize the achievable luminosity of the new e/p interaction
 5098 region, the beam separation scheme has to be combined with the electron mini-beta focusing structure.

5099 Figure 7.19 shows a schematic layout of the interaction region. It refers to the 10 degree option and
 5100 shows a compact triplet structure that is used for early focusing of the electron beam. The electron mini
 5101 beta quadrupoles are embedded into the detector opening angle and in order to obtain the required separation
 5102 effect they are shifted in the horizontal plane and act effectively as combined function magnets: Thus focusing
 5103 and separation of the electron beam are combined in a very compact lattice structure, which is the prerequisite
 5104 to achieve luminosity values in the range of $10^{33} \text{ cm}^{-2} \text{ s}^{-1}$.

5105 7.5.1 Beam Separation Scheme

5106 The separation scheme of the two beams has to be optimised with respect to an efficient (i.e. fast) beam
 5107 separation and a synchrotron radiation power and critical energy of the emitted photons that can be tolerated
 5108 by the absorber design. Two main issues have to be accomplished: a sufficient horizontal distance between
 5109 the beams has to be generated at the position of the first proton (half) quadrupole, located at a distance of s
 5110 $= 23\text{m}$ from the interaction point (the nominal value of the LHC proton lattice). In addition to that, harmful
 5111 beam beam effects have to be avoided at the first parasitic bunch encounters which will take place at $s =$
 5112 3.75m , as the nominal bunch distance in LHC corresponds to $\Delta t = 25\text{ns}$. These so-called parasitic bunch
 5113 crossings have to be avoided as they would lead to intolerable beam-beam effects in the colliding beams. As

Ring-ring option half-quadrupole, 4900 A, Gradient 137 T/m,
+ 2.5 T dipole field from feeddown




Figure 7.20: Super conducting half quadrupole in the proton lattice: The electron beam will pass on the right hand side of the mirror plate in a quasi field free region (see section 9.1).

5114 a consequence the separation scheme has to deliver a sufficiently large horizontal distance between the two
5115 counter rotating bunches at these locations.

5116 To achieve the first requirement a separation effect is created inside the mini beta quadrupoles of the
5117 electron beam: The large momentum difference of the two colliding beams provides a very elegant way to
5118 separate the lepton and the hadron beams: Shifting the mini-beta quadrupoles of the electron beam and
5119 installing a 15.8m long, but weak separator dipole magnet close to the IP provides the gentle separation that
5120 is needed to keep the synchrotron radiation level in the IR within reasonable limits.

5121 The nearest proton quadrupole to the IP is designed as a half-quadrupole to ease the extraction of the
5122 outgoing electron beam. At this location (at $s=23$ m) a minimum separation of $\Delta x = 55\text{mm}$ is needed to
5123 guide the electron beam along the mirror plate of a sc. proton half quadrupole (see section 9.1). A first
5124 layout of this magnet is sketched in figure 7.20

5125 The horizontal offsets of the mini beta lenses are chosen individually in such a way that the resulting
5126 bending strength in the complete separation scheme (quadrupole triplet / doublet and separator dipole) is
5127 constant. In this way a moderate separation strength is created with a constant bending radius of $\rho = 6757m$
5128 for the 10 degree option. In the case of the 1 degree option the quadrupole lenses of the electron lattice
5129 cannot be included inside the detector design as the opening angle of the detector does not provide enough
5130 space for the hardware of the electron ring lattice. Therefore a much larger distance between the IP and the
5131 location of the first electron lens had to be chosen ($\Delta s = 6.2\text{m}$ instead of $\Delta s = 1.2\text{m}$). As a consequence
5132 - in order to achieve the same overall beam separation - stronger magnetic separation fields have to be
5133 applied resulting in a bending radius of $\rho = 4057m$ in this case. In both cases the position of the electron
5134 quadrupoles is following the design orbit of the electron beam to avoid local strong bending fields and keep
5135 the synchrotron radiation power to a minimum. This technique has already been succesfully applied at the
5136 layout of the HERA electron-proton collider [618].

5137
5138 Still the separation at the location of the first proton magnet is small and a half quadrupole design for
5139 this super conducting magnet has been chosen at this point. The resulting beam parameters - including the
5140 expected luminosity for this ring ring option - are summarised in Table 2.

5141 It has to be pointed out in this context that the arrangement of the off centre quadrupoles as well as
5142 the strength of the separator dipole depend on the beam optics of the electron beam. The beam size at the

Detector Option Quantity	unit	1°		10°	
		electrons	protons	electrons	protons
Number of bunches		2808			
Particles/bunch N_b	10^{10}	1.96	17	1.96	17
Horiz. beta-function	m	0.4	4.0	0.18	1.8
Vert. beta-function	m	0.2	1.0	0.1	0.5
Horiz. emittance	nm	5.0	0.5	5.0	0.5
Vert. emittance	nm	2.5	0.5	2.5	0.5
Distance to IP	m	6.2	22	1.2	22
Crossing angle	mrad	1.0		1.0	
Synch. Rad. in IR	kW	51		33	
absolute Luminosity	$m^{-2} s^{-1}$	$8.54 * 10^{32}$		$1.8 * 10^{33}$	
Loss-Factor S		0.86		0.75	
effective Luminosity	$m^{-2} s^{-1}$	$7.33 * 10^{32}$		$1.34 * 10^{33}$	

Table 7.11: Parameters of the mini beta optics for the 1° and 10° options of the LHeC Interaction Region.

5143 parasitic crossings and at the proton quadrupole will determine the required horizontal distance between the
5144 electron and proton bunches. The strength and position of these magnets however will determine the optical
5145 parameters, including the dispersion function that is created during the separation process itself. Therefore
5146 a self-consistent layout concerning optics, beam separation and geometry of the synchrotron light absorbers
5147 has to be found.

5148 It is obvious that these boundary conditions have to be fulfilled not only during luminosity operation of
5149 the e/p rings. During injection and the complete acceleration procedure of the electron ring the influence
5150 of the electron quadrupoles on the proton beam has to be compensated with respect to the proton beam
5151 orbit (as a result of the separation fields) as well as to the proton beam optics: The changing deflecting
5152 fields and gradients of the electron magnets will require correction procedures in the proton lattice that will
5153 compensate this influence at any moment.

5154 7.5.2 Crossing Angle

5155 A central aspect of the LHeC IR design is the beam-beam interaction of the colliding electron and proton
5156 bunches. The bunch structure of the electron beam will match the pattern of the LHC proton filling scheme
5157 for maximal luminosity, giving equal bunch spacings of 25 ns to both beams. The IR design therefore
5158 is required to separate the bunches as quickly as possible to avoid additional bunch interactions at these
5159 positions and limit the beam-beam effect to the desired interactions at the IP. The design bunch distance
5160 in the LHC proton bunch chain corresponds to $\Delta t = 25$ ns or $\Delta s = 7.5$ m. The counter rotating bunches
5161 therefore meet after the crossing at the interaction point at additional, parasitic collision points in a distance
5162 $s = 3.75$ m from the IP. To avoid detrimental effects from these parasitic crossings the above mentioned
5163 separation scheme has to be supported by a crossing angle that will deliver a sufficiently large horizontal
5164 distance between the bunches at the first parasitic bunch crossings. This technique is used in all LHC
5165 interaction points. In the case of the LHeC however, the crossing angle is determined by the emittance of
5166 the electron beam and the resulting beam size which is considerably larger than the usual proton beam size
5167 in the storage ring. In the case of the LHeC IR a crossing angle of $\theta = 1$ mrad is considered as sufficient
5168 in the 1° as well as in the 10° option to avoid beam-beam effects from this parasitic crossings. Figure 7.21
5169 shows the position of the first possible parasitic encounters and the effect of the crossing angle to deliver a
5170 sufficient separation at these places.




Figure 7.21: LHeC interaction region including the location of the first parasitic bunch encounters where a sufficient beam separation is achieved by a crossing angle of 1 mrad. The location of the parasitic encounters is indicated by green ovals.

5171 The detailed impact of one beam on another is evaluated by a dedicated beam-beam interaction study
 5172 which is included in this report, based on a minimum separation of $5\sigma_e + 5\sigma_p$ at every parasitic crossing node.
 5173 Due to the larger electron emittance the separation is mainly dominated by the electron beam parameters,
 5174 and as a general rule it can be stated that the rapid growth of the β -function in the drift around the IP,

$$\beta(s) = \beta^* + \frac{s^2}{\beta^*}, \quad (7.9)$$

5175 makes it harder to separate the beams if small β^* and a large drift space s is required in the optical design.

5176 In any design for the LHeC study, a crossing angle is used to establish an early beam separation, reduce
 5177 the required strength in the separation magnets and minimise the synchrotron radiation power that is created
 5178 inside the interaction region.

5179 As a draw back however the luminosity is reduced due to the fact that the bunches will not collide
 5180 anymore head on. This reduction is expressed in a geometric luminosity reduction factor “S”, that depends
 5181 on the crossing angle θ , the length of the electron and proton bunches σ_{ze} and σ_{zp} and the transverse beam
 5182 size in the plane of the bunch crossing σ_x^* :

$$S(\theta) = \left[1 + \left(\frac{\sigma_{sp}^2 + \sigma_{se}^2}{2\sigma_x^{*2}} \right) \tan^2 \frac{\theta}{2} \right]^{-\frac{1}{2}}. \quad (7.10)$$

5183

5184

5185

Accordingly, the effective luminosity that can be expected for a given IR layout is obtained by

$$L = S(\theta) * L_0 \quad (7.11)$$

5186

5187

5188

5189

For the two beam optics that have been chosen for this design study (the 1° and the 10° option) and a crossing angle of $\theta = 1\text{mrad}$ the loss factor amounts to $S = 86\%$ and $S = 75\%$ respectively.




Figure 7.22: Proton optics for the LHeC interaction region. The gradients of the antisymmetric triplet lattice in the standard LHC have been modified to adopt for the requirements of the LHeC flat beam parameters.

7.5.3 Beam Optics and Luminosity

A special boundary condition had to be observed in the design of the proton beam optics of the LHeC: For the layout of the four present proton-proton interaction regions in the LHC machine an anti-symmetric option had been chosen: A solution that is appropriate for a round beam optics ($\sigma_x^* = \sigma_y^*$). An optimised design for collisions with the flat e^\pm beams however requires unequal β -functions for the hadron beam at the IP and the existing LHC optics can no longer be maintained. Therefore the optical layout of the existing triplet structure in the LHC had to be modified to match the required beta functions ($\beta_x = 1.8\text{m}$, $\beta_y = 0.5\text{m}$) at the IP to the regular optics of the FODO structure in the arc (Figure 7.22).

In the case of the electron beam optics, two different layouts of the interaction region are considered: One optical concept for highest achievable luminosity and a solution for maximum detector acceptance. In the first case an opening angle of 10° is available inside the detector geometry and allows to install an embedded magnet structure where the first electron quadrupole lenses can be placed as close as $s = 1.2\text{m}$ from the IP. This early focusing scheme leads to moderate values of the β function inside the mini beta quadrupoles and therefore allows for a smaller spot size at the IP and larger luminosity values can be achieved. Still however the quadrupoles require a compact design: While the gradients required by the optical solution are small (for a super conducting magnet design) the outer radius of the first electron quadrupole has been limited to $r_{max} = 210\text{mm}$.

In the case of the 1° option the detector design is optimised for largest detector acceptance. Accordingly the opening angle of the detector hardware is too small to deliver space for accelerator magnets. The mini beta quadrupoles therefore have to be located outside the detector, and a distance $s = 6.2\text{m}$ from the IP had to be chosen in this case. Even if the magnet dimensions are not limited by the detector design in this case, the achievable luminosity is about a factor of two smaller than in the 10° case.

The two beam optics that are based on these considerations are discussed in detail in the next chapter of this report. In the case of the 10° option a triplet structure has been chosen to allow for moderate values of the beta functions inside the mini beta quadrupoles. As a special feature of the optics that is shown in Figure 7.23 the focusing effect of the first quadrupole magnet is moderate: Its gradient has been limited as it has to deliver mainly the first beam separation. Table 7.11 includes as well the overall synchrotron radiation power that is produced inside the IR. Due to the larger bending radius (i.e. smaller bending forces) in the case of the 10° option the produced synchrotron radiation power is limited to about 30 kW, while the




Figure 7.23: Electron optics for the LHeC interaction region. The plot corresponds to the 1 degree option where a doublet structure combined with a separation dipole has been chosen to separate the two beams.

5219 alternative - high acceptance - option has to handle 50kW of synchrotron light.
 5220 The details of the synchrotron light characteristics are covered in the next chapters of this report for both
 5221 cases, including the critical energies and the design of the required absorbers.
 5222 For the 1° option the mini beta focusing is based on a quadrupole doublet as the space limitations in
 5223 the transverse plane are much more relaxed compared to the alternative option and the main issue here
 5224 was to find a compact design in the longitudinal coordinate: Due to the larger distance of the focusing
 5225 and separating magnets from the IP the magnet structure has to be more compact and the separating
 5226 field stronger to obtain the required horizontal beam distance at the location $s=23\text{m}$ of the first proton
 5227 quadrupole. The corresponding beam optics for both options are explained in full detail below.

5228 7.6 Design Requirements

5229 7.6.1 Detector Coverage and Acceptance

5230 Acceptance describes the amount of angular obstruction of the detector due to the presence of machine
 5231 elements, as shown in figure 7.24. For example, an acceptance of 10° implies a protrusion of machine ele-
 5232 ments into the detector such that a cone of 10° half-angle along the beam axis is blocked. The detector is
 5233 thus unable to see particles emitted at less than this angle, and event data is lost at high pseudo-rapidities.
 5234 Accordingly larger detector opening angles denote lower acceptance but allows to position machine elements
 5235 at a smaller distance to the IP

5236
 5237 Since β grows quadratically with distance, a smaller l^* generally allows stronger focusing of a beam and
 5238 thus higher luminosity. While there is no direct relationship between l^* and luminosity, a balance must be
 5239 found to optimise both luminosity and acceptance. Two IR designs are proposed as solutions to the balance
 5240 between luminosity and acceptance. Both designs aim to achieve a luminosity in the range of $\sim 10^{33} \text{ cm}^{-2}\text{s}^{-1}$.

5241 1. High Luminosity Layout (HL)

- 5242 • 10° acceptance




Figure 7.24: Graphical representation of acceptance. θ_1 shows a lower acceptance cone, while θ_2 shows a higher acceptance cone. For machine elements of constant diameter, higher acceptance increases l^* .

- 5243 • Higher luminosity

5244 2. High Acceptance Layout (HA)

- 5245 • 1° acceptance
- 5246 • Lower luminosity

5247 In concert with these designs, two plans are proposed for running LHeC. One option is to run with the HL
 5248 layout, then switch to the HA layout during a shutdown. The second option is to optimise the HA layout
 5249 for sufficient luminosity to replace the HL layout entirely.

5250 7.6.2 Lattice Matching and IR Geometry

5251 The principle layout and requirements of the beam separation scheme have been described above. A
 5252 minimum separation of $5\sigma_e + 5\sigma_p$ is specified at each parasitic node. In addition an overall distance between
 5253 the proton and electron beam of 55 mm at the location of the first proton magnet, $s = 23$ m, has been
 5254 chosen as an attainable target from optical, radiation (see section 7.12) and magnet design (see section 9.1)
 5255 standpoints.

5256 Once the beams are separated into independent beam pipes, the electron beam must be transported into
 5257 the ring lattice. Quadrupoles are used in the long straight section (LSS) of the electron machine to transport
 5258 the beam from the IP to the dispersion suppressor and match the twiss parameters at either end. Space
 5259 must be available to insert dipoles and further quadrupoles to allow the orbit of the beam to be designed
 5260 with regard to the physical layout of the ring and the IR.

5261

5262 The IR and LSS geometries must be designed around a number of further constraints. In addition to
5263 the beam separation required to avoid parasitic bunch encounters, the electron beam must be steered from
5264 the electron ring into the IR and back out again. The colliding proton beam must be largely undisturbed
5265 by the electron beam. The non-colliding proton beam must be guided through the IR without interacting
5266 with either of the other beams.

5267 7.7 High Luminosity IR Layout

5268 7.7.1 Parameters

5269 Table 7.12 details the interaction point parameters and other parameters for this design. To optimise for
5270 luminosity, a small l^* is desired. An acceptance angle of 10° is therefore chosen, which gives an l^* of 1.2m
5271 for final focusing quadrupoles of reasonable size.

$L(0)$	1.8×10^{33}
θ	1×10^{-3}
$S(\theta)$	0.746
$L(\theta)$	1.34×10^{33}
β_{x^*}	0.18 m
β_{y^*}	0.1 m
σ_{x^*}	3.00×10^{-5} m
σ_{y^*}	1.58×10^{-5} m
SR Power	33 kW
E_c	126 keV

Table 7.12: Parameters for the HL IR. Note that the geometric luminosity reduction factor, S, is calculated using the LHC ultimate bunch length of 7.5×10^{-2} .

5272 SR calculations are detailed in section (see section 7.12). The total power emitted in the IR is similar to
5273 that in the HERA-2 IR [619] and as such appears to be reasonable, given enough space for absorbers.

5274 7.7.2 Layout of the Electron Lattice

5275 A symmetric final quadrupole triplet layout followed by a long weak dipole magnet has been chosen for this
5276 design, due to the relatively round beam spot aspect ratio of 1.8:1. Figure 7.25 and table 7.13 detail the
5277 layout.
5278




Figure 7.25: Layout of machine elements in the HL IR. Note that the left side of the IR is symmetric.

Element	S_{entry} [m]	L [m]	Gradient [T/m]	Dipole Field [T]	Offset [m]
BS.L	-21.5	15.8	-	-0.0296	-
Q3E.L	-5.4	1.0	89.09229	-0.0296	-3.32240×10^{-4}
Q2E.L	-4	1.5	-102.2013	-0.0296	2.89624×10^{-4}
Q1E.L	-2.2	1.0	54.34071	-0.0296	-5.44711×10^{-4}
IP	0.0	-	-	-	-
Q1E.R	1.2	1.0	54.34071	0.0296	5.44711×10^{-4}
Q2E.R	2.5	1.5	-102.2013	0.0296	-2.89624×10^{-4}
Q3E.R	4.4	1.0	89.09229	0.0296	3.32240×10^{-4}
BS.R	5.7	15.8	-	-0.0296	-

Table 7.13: Machine elements for the HL IR. S_{entry} gives the leftmost point of the idealised magnetic field of an element. Note that S is relative to the IP.

5279 The distance of the first electron magnet from the IP, l^* of 1.2 m, allows both strong focusing of the beam,
5280 and constant bending of the beam from $s = 1.2$ m to 21.5 m. This is achieved with offset quadrupoles and
5281 a separation dipole.

5282

5283 Figure 7.26 shows the β functions of the beam in both planes from the IP to the face of the final pro-
5284 ton quadrupole at $s = 23$ m.

5285 7.7.3 Separation Scheme

5286 The electron triplet is powered in FDF mode generating a large peak in β_x , but is designed such that the
5287 peak is between parasitic crossings. The first F quadrupole reduces β_x at $s = 3.75$ m compared to an initial
5288 D quadrupole. The third F quadrupole then reduces β_x sufficiently to avoid large beam-beam interactions
5289 at the second parasitic crossing, $s = 7.5$ m.

5290

5291 This is aided by the bending provided by the offset quadrupoles, and also the IP crossing angle of 1 mrad.
5292 These elements ensure that the separation between the beams, normalised to the beam size, increases at each
5293 parasitic crossing. Note that 1 mrad is not a minimum crossing angle required by beam-beam interaction
5294 separation criteria but is a chosen balance between luminosity loss and minimising bend strength. In theory,
5295 this layout could support an IP with no crossing angle; however the bend strength required to achieve this
5296 would generate an undesirable level of SR power.

5297 7.8 High Acceptance IR Layout

5298 7.8.1 Parameters

5299 Table 7.14 details the main parameters for this design. The chosen acceptance for this layout is 1° . For final
5300 electron focusing magnets of reasonable strength this places all elements outside the limits of the detector,
5301 at $s = \pm 6.2m$. Due to the small crossing angle the first electron magnets have to be placed beyond this
5302 distance. As such, the actual acceptance of the layout is limited by the beam pipe diameter rather than the
5303 size of machine elements. This also gives further flexibility in the strengths and designs of the final focusing
5304 quadrupoles.

5305

5306 SR calculations are detailed in section 7.12. Again, the total power emitted in the IR is similar to that in
5307 the HERA-2 IR [619] and as such appears to be reasonable, given enough space for absorbers. However it is
5308 significantly higher than that in the HL layout. As discussed in section 7.12, an option exists to reduce the




Figure 7.26: β functions in both planes for the HL IR layout, from the IP to the face of the final proton quadrupole at $s = 23$ m. Note that s is relative to the ring, which begins at the left side of the left dispersion suppressor of IP2.

$L(0)$	8.54×10^{32}
θ	1×10^{-3}
$S(\theta)$	0.858
$L(\theta)$	7.33×10^{32}
β_x^*	0.4 m
β_y^*	0.2 m
σ_x^*	4.47×10^{-5} m
σ_y^*	2.24×10^{-5} m
SR Power	51 kW
E_c	163 keV

Table 7.14: Parameters for the HA IR. Note that the geometric luminosity reduction factor, S , is calculated using the LHC ultimate bunch length of 7.5×10^{-2} .

5309 total SR power by including a dipole field in the detector, thus mitigating the limitation imposed on dipole
 5310 length by the larger l^* .

5311 7.8.2 Layout

5312 A symmetric final quadrupole doublet layout has been chosen for the electron lattice in this design. The
 5313 beam spot aspect ratio of 2:1 is marginally flatter than the HL layout, and as such a triplet is less suitable.
 5314 Figure 7.27 and table 7.15 summarise the details of the layout.
 5315




Figure 7.27: Layout of machine elements in the HA IR. Note that the left side of the IR is symmetric.

Element	S_{entry} [m]	L [m]	Gradient [T/m]	Dipole Field [T]	Offset [m]
BS.L	-21.5	12.7	-	-0.0493	-
Q2E.L	-8.5	1.0	-77.30906	-0.0493	6.37700×10^{-4}
Q1E.L	-7.2	1.0	90.38473	-0.0493	-5.45446×10^{-4}
IP	0.0	-	-	-	-
Q1E.R	6.2	1.0	90.38473	0.0493	5.45446×10^{-4}
Q2E.R	7.5	1.0	-77.30906	0.0493	-6.37700×10^{-4}
BS.R	8.8	12.7	-	0.0493	-

Table 7.15: Machine elements for the HA IR. S_{entry} gives the leftmost point of the idealised magnetic field of an element. Note that S is relative to the IP.

5316 The l^* of 6.2m imposes limitations on focusing and bending in this case. Focusing is limited by quadratic β
 5317 growth through a drift space, which is increased for smaller β^* . As such, the achievable luminosity is smaller
 5318 than in the HL design lattice.

5319
 5320 Again offset quadrupoles are used to separate the beams. However this layout has less total dipole length
 5321 available. Additionally, the first parasitic crossing occurs before the location of the first electron quadrupole.
 5322 This further limits final focusing as the beam cannot be permitted to grow too large by this time. Due to
 5323 the reduced effective length for focusing and beam separation, stronger bending must be applied to obtain
 5324 the overall separation of 55 mm at the place of the first proton quadrupole. Accordingly higher synchrotron
 5325 radiation power is generated in this design.

5326
 5327 Figure 7.28 shows the β functions of the beam in both planes from the IP to the face of the final proton
 5328 quadrupole at $s = 23$ m.




Figure 7.28: β functions in both planes for the HA IR layout, from the IP to the face of the final proton quadrupole at $s = 23$ m. Note that s is relative to the ring, which begins at the left side of the left dispersion suppressor of IP2.

7.8.3 Separation Scheme

The final electron doublet is optimised to limit the peak in β_x on the cost of higher β_y . Unlike the HL layout, the first parasitic crossing is reached before focusing begins. As such a minimum crossing angle of roughly 0.7 mrad is required, which is dependent solely upon β growth in the drift space. As a balance between luminosity loss and SR power generation, and aiding comparison with the HL layout, a crossing angle of 1 mrad has been chosen.

7.9 Comparison of the two Layouts

Table 7.16 shows a direct comparison of various parameters of the two layouts.

The difference in luminosity after considering losses due to the crossing angle is a factor of 1.8. However it should be noted that this design strives for technical feasibility and both layouts could potentially be squeezed further to decrease β^* in both planes. The HL layout could likely be squeezed further than the HA layout due to the large difference in l^* , as shown in figure 7.29 which compares the two IR layouts. At

Parameter	HL	HA
$L(0)$	1.8×10^{33}	8.54×10^{32}
θ	1×10^{-3}	1×10^{-3}
$S(\theta)$	0.746	0.858
$L(\theta)$	1.34×10^{33}	7.33×10^{32}
β_x^*	0.18 m	0.4 m
β_y^*	0.1 m	0.2 m
σ_x^*	3.00×10^{-5} m	4.47×10^{-5} m
σ_y^*	1.58×10^{-5} m	2.24×10^{-5} m
SR Power	33 kW	51 kW
E_c	126 keV	163 keV

Table 7.16: Parameter comparison for the HL and HA layouts.

5342 this stage both designs deliver their required IP parameters of luminosity and acceptance and appear feasible.
5343
5344 The HA design on the other side generates more SR power. This appears to be within reasonable lim-
5345 its and is discussed in section 7.12. Furthermore, an option is discussed to install a dipole magnet in the IR,
5346 detector. This early separation would reduce the required strength of the dipole fields in the IR, significantly
5347 reducing total SR power.




Figure 7.29: Scale comparison of the layouts for the HL and HA designs. Note the large difference in l^* .

5348 7.9.1 Crab Cavities

5349 Both IR designs incorporate a crossing angle of 1mrad to facilitate fast beam separation. As discussed this
5350 introduces a luminosity loss factor S . The crossing angle is optimised to balance separation, SR power and
5351 luminosity. The loss factor is greater for the HL layout (0.746) than the HA (0.858) due to the smaller beam
5352 spot. However both are moderate, and as such a need for crab cavities is not foreseen.

5353

5354 Crab cavities rotate the bunch locally to the IP to counteract the effect of the crossing angle. They present
5355 a significant technical challenge, although feasibility has been demonstrated at KEKB [620]. It is preferred
5356 to avoid their necessity. However, their use remains a possibility if needs arise. For example, if designs for
5357 the proton half-quadrupoles prove to require larger beam separation than expected, increasing the crossing
5358 angle is likely the best option, as increased bending would quickly generate unfeasible levels of SR power.
5359 In this case, crab cavities would need to be considered to recover luminosity.

5360 **7.10 Long Straight Section**

5361 The Long Straight Section (LSS) geometrically and optically matches the IR to the rest of the LHeC ring
5362 lattice. For the purposes of this report, the LSS is defined from the start of the left dispersion suppressor
5363 (DS) to the end of the right DS. This is due to the need to alter the DS's optically and geometrically from
5364 the nominal design to obtain a valuable solution.

5365

5366 The LSS geometry for the electron ring uses a complex bending scheme in the horizontal and vertical
5367 planes to satisfy the various constraints. These include the 0.6 m radial offset of the LHeC ring as mentioned
5368 in section 7.3, the 1 m vertical offset, and the IR separation geometry. The resulting small path length
5369 difference must be compensated elsewhere in the ring, nominally in the bypasses.

5370

5371 It has to be noted that in the current LSS design there are some conflicts between placements of the mag-
5372 nets for the LSS layout of the LHeC and standard LHC rings. The aim has been to design a self-consistent
5373 LHeC solution, and then iterate upon this to eliminate these conflicts. Future plans are discussed later in
5374 this section. It should also be noted that the solution presented is only matched for the HA IR layout.
5375 However generating a similar solution for the HL layout presents no additional challenges.

5376 **7.10.1 Dispersion**

5377 A key constraint coupled to optics and geometry is dispersion. Since dispersion is an optical quantity
5378 generated by the deflecting fields, this becomes a challenge for the complex LSS bending scheme. The LHeC
5379 DSs are designed to match horizontal dispersion from the LSS to the arc. There is no equivalent scheme to
5380 deal with large vertical dispersion. Therefore an achromatic vertical separation scheme is proposed. Two
5381 vertical double bend achromat (DBA) sections on either side of the IR form doglegs while generating no
5382 vertical dispersion outside this region. Figures 7.30 and 7.31 detail the geometry and optics of the DBA
5383 sections used in the LSS.

5384 **7.10.2 Geometry**

5385 Figure 7.32 shows the geometry of the LSS solution on a larger scale. Note that the vertical doglegs are
5386 placed between the two horizontal dipole sets. To maximise use of space, schemes were explored with inter-
5387 leaved horizontal and vertical bends, as shown in figure 7.33. This allows increased bend length and distance
5388 between the bending magnets to reduce the SR power. However this coupled bending generates rotation of
5389 the beam around the s axis, effectively causing all subsequent quadrupoles to have a skew component.

5390

5391 Note that the left DS has nominal bend strength, while the right DS dipoles are weakened to accommodate the
5392 1.2 m horizontal separation. Note also that future iterations of the LSS will include changes to accommodate
5393 the solution for the non-colliding proton beam detailed in section 7.11. In practise this simply manifests as
5394 a rotation of the IR section, and no complex changes are required.




Figure 7.30: Geometry plot for a DBA dogleg pair in the HA LSS design.

5395 7.10.3 Electron Optics in the LSS

5396 Placement of quadrupole elements is constrained by LSS geometry requirements, and by the LHC lattice,
 5397 although this constraint is ignored for this iteration. While the LSS horizontal dipoles alone do not signif-
 5398 icantly constrain space, the combination of these and the vertical DBA scheme takes up large amounts of
 5399 space.

5400

5401 To gain sufficient matching flexibility, quadrupole triplets are used in the centre of the DBAs. The triplet
 5402 DBA generates a characteristic beta function shape, resulting in peaks and waists which make matching
 5403 more challenging but feasible. Figure 7.34 shows the beta and dispersion functions of the LSS optics.

5404 7.10.4 Synchrotron Radiation

5405 While detailed simulations have not yet been run, a simple analytical calculation of SR generated by the
 5406 dipoles in the LSS has been performed, giving an initial estimate of ~ 1.4 MW. Note that this includes the
 5407 left and right DS sections. This is manageable considering the ~ 50 MW estimate for the rest of the ring.




Figure 7.31: Optics plot for a single DBA module in the HA LSS design. Note waists and peaks in β_y .

5408 7.10.5 LHC Integration

5409 Currently, the DBA modules and quadrupoles near the IP conflict with the LHC proton triplet. After suffi-
 5410 cient horizontal and/or vertical separation electron elements may be placed arbitrarily. Work is in progress
 5411 on an updated design which moves vertical separation outward from the IP, after horizontal separation. In
 5412 this case, no quadrupoles are required until ~ 75 m from the IP, leaving space for the proton triplet. This
 5413 geometry also successfully incorporates the solution for the non-colliding proton beam. However at the time
 5414 of writing, optical matching is not yet finalised.

5415

5416 This "late vertical separation" scheme changes optical constraints. In the current "early" vertical sepa-
 5417 ration scheme, limited space between the IR and the DBA decreases matching flexibility. In the "late"
 5418 design, flexibility between the IR and DBA increases, but decreases correspondingly between the DBA and
 5419 the DS.

5420

5421 Note that it is to some degree possible to reduce a bending scheme's space requirements arbitrarily, at
 5422 the cost of more SR power.




Figure 7.32: Geometry of the LSS design. Due to small angles involved, the s axis approximates the z axis well, and is used to allow MADX to display lattice elements.

7.11 The Non-Colliding Proton Beam

In both IRs, a solution must be found for dealing with the second proton beam. The second beam must not collide with either of the other two beams, or generate significant beam-beam effects. Also, detector designs strongly prefer for the second beam to occupy the same central beam pipe as the other two beams, rather than allowing space through the detector for a second pipe.

7.11.1 Design Elements

To avoid collisions and beam-beam effects, the bunches of the non-colliding (NC) beam will be shifted in time by half a bunch distance. This prevents proton-proton collisions at the IP, and allows the NC beam to overlap with the co-rotating electron beam.

Proton-proton interactions at the parasitic encounters however and accordingly beam-beam effects can still occur. To minimise these, the NC beam is left unsqueezed, and a proton-proton crossing angle is implemented which generates sufficient separation at these locations. For the unsqueezed optics, the so-called LHC alignment optics [621] is modified for use on the NC beam only. The same scenario is proposed in the




Figure 7.33: Example of geometry of a design with coupled horizontal and vertical bends. Interleaving bends in this way generates roll around s axis. The IP is at zero in both axes.

5437 linac-ring design in section 8.2.

5438

5439 The required crossing angle for the second proton beam is generated by changing the LHC separator dipoles
 5440 D1 and D2. Figure 7.35 shows the trajectories of the three beams for the HA design. The proton final triplet
 5441 is rotated in the horizontal plane and moved to match the new trajectory of the colliding beam while its
 5442 position in s stays constant.

5443

5444 Note that the electron trajectory is rotated as well to match the colliding proton beam, such that the
 5445 electron-proton crossing angle of 1 mrad is kept constant. This requires a change to the LSS geometry and
 5446 optics solution which has not yet been implemented. This will be included in the next iteration of the LSS
 5447 design. No new issues are likely to be introduced. Note also that the electron IR itself is unchanged in both
 5448 the HL and HA designs, so SR calculations and detector designs do not require updates.

5449 7.11.2 Solution

5450 For the unsqueezed optics of the second proton beam, zero triplet strength is required. The triplet quadrupoles
 5451 each have a single proton aperture and as such the proton beams cannot be focused differently if both pass




Figure 7.34: Optics plot for the HA LSS design.

5452 through the main aperture. Therefore the NC beam is guided through the same aperture as the electron
 5453 beam, and experiences effectively no focusing. The proton LSS matching quadrupoles, which are separately
 5454 powered for each beam, are then used to implement the NC beam optics.

5455

5456 As shown in section 9.1, Q1 will be a half-quadrupole. A large field-free aperture accomodates the elec-
 5457 tron beam and the NC proton beam. Q2 and Q3 have standard designs which incorporate low-field pockets
 5458 which will be used for the shared electron and NC proton apertures.

5459

5460 Aperture calculations are based on 15σ proton envelopes and 20σ electron envelopes. In both cases, the
 5461 aperture need is driven by horizontal requirements, since the horizontal envelopes and horizontal separation
 5462 dominate over the vertical electron envelope. Note that the Q2 and Q3 apertures are circular; aperture
 5463 radius is thus determined by the larger dimension.

5464 High Luminosity

5465 The proton-proton crossing angle is optimised to 3 mrad to minimise aperture requirements, by making
 5466 the NC beam follow the electron beam closely. The electron trajectory is determined by the IR separation
 5467 scheme.




Figure 7.35: Trajectories of the three beams in the HA interaction region design. Note that in this plot the beams are reversed compared to the LSS plots.

Element	Ap Radius	Ap Centre
Q1	0.0311	-0.0666
Q2A	0.0274	-0.1001
Q2B	0.0259	-0.1251
Q3	0.0257	-0.1592

Table 7.17: Proton triplet aperture requirements of the non-colliding proton beam for the HL layout.

5468 High Acceptance

5469 In this case the proton-proton crossing angle is optimised to 3.4 mrad to minimise aperture requirements.
 5470 Again the NC proton beam will follow closely the electron beam trajectory, which is determined by the
 5471 IR separation scheme. The electron beam, having larger emittance, dominates aperture requirements. The
 5472 separation between the electron beam and the NC proton beam is larger in the HA layout than in the HL
 5473 layout, due to the later bending in the HA separation scheme. Table 7.18 and figure 7.37 show the required
 5474 apertures.

5475 7.11.3 Summary

5476 Aperture requirements for the HL layout are somewhat less demanding than for the HA layout, but both
 5477 sets of requirements are feasible and do not present difficulties in magnet design using existing technology.
 5478 The existing Q1 design is easily sufficient. Q2A and Q2B would ideally be two copies of the same yoke,
 5479 requiring a larger hole in each. Q3 requires a larger yoke than the existing 200 mm radius design, but the
 5480 tooling limit of 270 mm should be sufficient.




Figure 7.36: Proton triplet aperture requirements with trajectories and envelopes of the electron beam and NC proton beam for the HL layout. Note that in this plot the beams are reversed compared to the LSS plots.

Element	Aperture Radius	Aperture Centre
Q1	0.0296	-0.0752
Q2A	0.0227	-0.1100
Q2B	0.0233	-0.1402
Q3	0.0264	-0.1811

Table 7.18: Proton triplet aperture requirements of the non-colliding proton beam for the HA layout.

5481

5482 In both designs, the crossing angle may be increased if desired for beam-beam reasons. The existing Q1
 5483 design supports a crossing angle up to 4 mrad, but this would require significantly larger apertures in the
 5484 other magnets.

5485 7.12 Synchrotron radiation and absorbers

5486 7.12.1 Introduction

5487 The synchrotron radiation (SR) in the interaction region has been analyzed in three ways. The SR was
 5488 simulated in depth using a program made with the Geant4 (G4) toolkit. In addition a cross check of the
 5489 total power and average critical energy was done in IRSYN, a Monte Carlo simulation package written by




Figure 7.37: Proton triplet aperture requirements with trajectories and envelopes of the electron beam and NC proton beam for the HA layout. Note that in this plot the beams are reversed compared to the LSS plots.

5490 R. Appleby [622]. A final cross check has been made for the radiated power per element using an analytic
 5491 method. These other methods confirmed the results seen using G4. The G4 program uses Monte Carlo
 5492 methods to create gaussian spatial and angular distributions for the electron beam. The electron beam is
 5493 then guided through vacuum volumes that contain the magnetic fields for the separator dipoles and electron
 5494 final focusing quadrupoles.

5495 The SR is generated in these volumes using the appropriate G4 process classes. The G4 SR class was
 5496 written for a uniform magnetic field, and therefore the quadrupole volumes were divided such that the
 5497 field remained approximately constant in each volume. This created agreement between upstream and
 5498 downstream quadrupoles since for a downstream quadrupole the beta function at the entrance and exit are
 5499 reversed from its upstream counterpart. This agreement confirms that the field was approximately constant
 5500 in each volume.

5501 The position, direction, and energy of each photon created is written as ntuples at user defined Z values.
 5502 These ntuples are then used to analyze the SR fan as it evolves in Z. The analysis was done primarily
 5503 through the use of MATLAB scripts. It was necessary to make two versions of this program. One for the
 5504 high luminosity design and one for the high detector acceptance design.

5505 Before going further, some conventions used for this section will be explained. The electron beam is
 5506 referred to as *the beam* and the proton beams will be referred to as either the interacting or non interacting
 5507 proton beams. The beam propagates in the -Z direction and the interacting proton beam propagates in the
 5508 +Z direction. A right handed coordinate system is used where the X axis is horizontal and the Y axis is
 5509 vertical. The beam centroid always remains in the $Y = 0$ plane. The *angle of the beam* will be used to refer
 5510 to the angle between the beam centroid's velocity vector and the Z axis, in the $Y = 0$ plane. This angle is

5511 set such that the beam propagates in the -X direction as it traverses Z.

5512 The SR fans extension in the horizontal direction is driven by the angle of the beam at the entrance
 5513 of the upstream separator dipole. Because the direction of emitted photons is parallel to the direction of
 5514 the electron that emitted it, the angle of the beam and the distance to the absorber are both greatest at
 5515 the entrance of the upstream separator dipole and therefore this defines one of the edges of the synchrotron
 5516 fan on the absorber. The other edge is defined by the crossing angle and the distance from the IP to the
 5517 absorber. The S shaped trajectory of the beam means that the smallest angle of the beam will be reached
 5518 at the IP. Therefore the photons emitted at this point will have the lowest angle and for this given angle the
 5519 smallest distance to the absorber. This defines the other edge of the fan in the horizontal direction.

5520 The SR fans extension in the vertical direction is driven by the beta function and angular spread of the
 5521 beam. The beta function along with the emittance defines the r.m.s. spot size of the beam. The vertical
 5522 spot size defines the Y position at which photons are emitted. On top of this the vertical angular spread
 5523 defines the angle between the velocity vector of these photons and the Z axis. Both of these values produce
 5524 complicated effects as they are functions of Z. These effects also affect the horizontal extension of the fan
 5525 however are of second order when compared to the angle of the beam. Since the beam moves in the Y = 0
 5526 plane these effects dominate the vertical extension of the beam.

5527 The number density distribution of the fan is a complicated issue. The number density at the absorber
 5528 is highest between the interacting beams. The reason for this is that although the separator dipoles create
 5529 significantly more photons the number of photons generated per unit length in Z is much lower for the dipoles
 5530 as opposed to the quadrupoles due to the high fields experienced in the quadrupoles. The position of the
 5531 quadrupole magnets then causes the light radiated from them to hit the absorber in the area between the
 5532 two interacting beams.

5533 7.12.2 High Luminosity

5534 Parameters

5535 The parameters for the high luminosity option are listed in Table 7.19. The separation refers to the dis-
 5536 placement between the two interacting beams at the face of the proton triplet.

Characteristic	Value
Electron Energy [GeV]	60
Electron Current [mA]	100
Crossing Angle [mrad]	1
Absorber Position [m]	-21.5
Dipole Field [T]	0.0296
Separation [mm]	55
γ/s	5.39×10^{18}

Table 7.19: High Luminosity: Parameters

5537 The energy, current, and crossing angle (θ_c) are common values used in all RR calculations. The dipole
 5538 field value refers to the constant dipole field created throughout all dipole elements in the IR. The direction
 5539 of this field is opposite on either side of the IP. The quadrupole elements have an effective dipole field created
 5540 by placing the quadrupole off axis, which is the same as this constant dipole field. The field is chosen such
 5541 that 55 mm of separation is reached by the face of the proton triplet. This separation was chosen based on
 5542 S. Russenschuck's SC quadrupole design for the proton final focusing triplet [623]. The separation between
 5543 the interacting beams can be increased by raising the constant dipole field. However, for a dipole magnet
 5544 $P_{SR} \propto |B^2|$ [624], therefore an optimization of the design will need to be discussed. The chosen parameters
 5545 give a flux of 5.39×10^{18} photons per second at Z = -21.5 m.

5546 **Power and Critical Energy**

5547 Table 7.20 shows the power of the SR produced by each element along with the average critical energy
 5548 produced per element. This is followed by the total power produced in the IR and the average critical
 5549 energy. Since the G4 simulations utilize Monte Carlo, multiple runs should be made with various seeds to
 5550 get an estimate for the standard error.

Element	Power [kW]	Critical Energy [keV]
DL	6.4	71
QL3	5.3	308
QL2	4.3	218
QL1	0.6	95
QR1	0.6	95
QR2	4.4	220
QR3	5.2	310
DR	6.4	71
Total/Avg	33.2	126

Table 7.20: High Luminosity: Power and Critical Energies as calculated with Geant4.

5551 The power from the dipoles is greater than any one quadrupole however the critical energies of the
 5552 quadrupoles are significantly higher than in the dipoles. It is expected that the dipole and quadrupole
 5553 elements can create power on the same order however have very different critical energies. This is because
 5554 the dipole is an order of magnitude longer than the quadrupole elements. Since the SR power created for
 5555 both the quadrupole and dipoles are linearly dependent on length [624] one needs to have a much higher
 5556 average critical energy to create comparable amounts of power.

5557 **Comparison**

5558 The IRSYN cross check of the power and critical energies is shown in Table 7.21. This comparison was done
 5559 for the total power and the average critical energy.

	Power [kW]		Critical Energy [keV]	
	Geant4	IRSYN	Geant4	IRSYN
Total/Avg	33.2	33.7	126	126

Table 7.21: High Luminosity: Geant4 and IRSYN comparison

5560 A third cross check to the G4 simulations was made for the power as shown in Table 7.22. This was done
 5561 using an analytic method for calculating power in dipole and quadrupole magnets [624]. This was done for
 5562 every element which provides confidence in the distribution of this power throughout the IR.

5563 **Number Density and Envelopes**

5564 The number density of photons as a function of Z is shown in Figure 7.38. Each graph displays the density
 5565 of photons in the $Z = Z_o$ plane for various values of Z_o . The first three figures give the growth of the SR
 5566 fan inside the detector area. This is crucial for determining the dimensions of the beam pipe. Since the
 5567 fan grows asymmetrically in the $-Z$ direction an asymmetric elliptical cone geometry will minimize these
 5568 dimensions, allowing the tracking to be placed as close to the beam as possible. The horizontal extension of
 5569 the fan in the high luminosity case is the minimum for the two Ring Ring options as well as the Linac Ring

Element	Power [kW]	
	Geant4	Analytic
DL	6.4	6.3
QL3	5.3	5.4
QL2	4.3	4.6
QL1	0.6	0.6
QR1	0.6	0.6
QR2	4.4	4.6
QR3	5.2	5.4
DR	6.4	6.3
Total/Avg	33.2	33.8

Table 7.22: High Luminosity: Geant4 and Analytic method comparison




Figure 7.38: High Luminosity: Number Density Growth in Z

option, which is most important inside the detector region. This is due to the lower value of l^* . Because the quadrupoles are closer to the IP and contain effective dipole fields the angle of the beam at the entrance of the upstream dipole can be lower as the angle of the beam doesn't need to equal the crossing angle until $Z = l^*$. The number density of this fan appears as expected. There exists the highest density between the two beams at the absorber.




Figure 7.39: High Luminosity: Beam Envelopes in Z

In Figure 7.38 the distribution was given at various Z values however a continuous envelope distribution is also important to see everything at once. This can be seen in Figure 7.39, where the beam and fan envelopes are shown in the $Y = 0$ plane. This makes it clear that the fan is antisymmetric which comes from the S shape of the electron beam as previously mentioned.

Critical Energy Distribution

The Critical Energy is dependent upon the element in which the SR is generated, and for the quadrupole magnets it is also dependent upon Z. This is a result of the fact that the critical energy is proportional to the magnetic field component that is perpendicular to the particle direction. i.e. $E_c \propto B_{\perp}$ [625]. Since the magnitude of the magnetic field is dependent upon x and y, then for a gaussian beam in position particles will experience different magnetic fields and therefore have a spectrum of critical energies. In a dipole the field is constant and therefore regardless of the position of the particles as long as they are in the uniform field area of the magnet they have a constant critical energy. Since the magnetic field is dependent upon x and y it is clear that as the r.m.s. spot size of the beam decreases there will be a decrease in critical energies. The opposite will occur for an increasing spot size. This is evident from Figure 7.40.

Absorber

The Photon distribution on the absorber surface is crucial. The distribution decides how the absorber must be shaped. The shape of the absorber in addition to the distribution on the surface then decides how much SR is backscattered into the detector region. In HERA backscattered SR was a significant source of background that required careful attention [626]. Looking at Figure 7.41 it is shown that for the high luminosity option




Figure 7.40: High Luminosity: Critical Energy Distribution in Z




Figure 7.41: High Luminosity: Photon distribution on Absorber Surface

5594 19.2 kW of power from the SR light will fall on the face of the absorber which is 58% of the total power.
5595 This gives a general idea of the amount of power that will be absorbed. However, backscattering and IR
5596 photons will lower the percent that is actually absorbed.

5597 **Proton Triplet**

5598 The super conducting final focusing triplet for the protons needs to be protected from radiation by the
5599 absorber. Some of the radiation produced upstream of the absorber however will either pass through the
5600 absorber or pass through the apertures for the two interacting beams. This is most concerning for the
5601 interacting proton beam aperture which will have the superconducting coils. A rough upper bound for
5602 the amount of power the coils can absorb before quenching is 100W [627]. There is approximately 217 W
5603 entering into the interacting proton beam aperture as is shown in Figure 7.41. This doesn't mean that all
5604 this power will hit the coils but simulations need to be made to determine how much of this will hit the
5605 coils. The amount of power that will pass through the absorber can be disregarded as it is not enough to
5606 cause any effects. The main source of power moving downstream of the absorber will be the photons passing
5607 through the beams aperture. This was approximately 13.7 kW as can be seen from Figure 7.41. Most of
5608 this radiation can be absorbed in a secondary absorber placed after the first downstream proton quadrupole.
5609 Overall protecting the proton triplet is important and although the absorber will minimize the radiation
5610 continuing downstream this needs to be studied in depth.

5611 **Backscattering**

5612 Another Geant4 program was written to simulate the backscattering of photons into the detector region.
5613 The ntuple with the photon information written at the absorber surface is used as the input for this program.
5614 An absorber geometry made of copper is described, and general physics processes are set up. A detector
5615 volume is then described and set to record the information of all the photons which enter in an ntuple. The
5616 first step in minimizing the backscattering was to optimize the absorber shape. Although the simulation
5617 didn't include a beam pipe the backscattering for different absorber geometries was compared against one
5618 another to find a minimum. The most basic shape was a block of copper that had cylinders removed for the
5619 interacting beams. This was used as a benchmark to see the maximum possible backscattering. In HERA a
5620 wedge shape was used for heat dissipation and minimizing backscattering [626]. The profile of two possible
5621 wedge shapes in the YZ plane is shown in Figure 7.42. It was found that this is the optimum shape for
5622 the absorber. The reason for this is that a backscattered electron would have to have its velocity vector be
5623 almost parallel to the wedge surface to escape from the wedge and therefore it works as a trap. As can be
5624 seen from Table 7.23 utilizing the wedge shaped absorber did not reduce the power by much. This appears
5625 to be a statistical limitation and needs to be redone with higher statistics to get a better estimate of the
5626 difference between the two geometries.

5627 After the absorber was optimized it was possible to set up a beam pipe geometry. An asymmetric
5628 elliptical cone beam pipe geometry made of beryllium was used since it would minimize the necessary size
5629 of the beam pipe as previously mentioned. The next step was to place the lead shield and masks inside this
5630 beam pipe. To determine placement a simulation was run with just the beam pipe. Then it was recorded
5631 where each backscattered photon would hit the beam pipe in Z. A histogram of this data was made. This
5632 determined that the shield should be placed in the Z region ranging from -20 m until the absorber (-21.5
5633 m). The shields were then placed at -21.2 m and -20.5 m. This decreased the backscattered power to zero as
5634 can be seen from Table 7.23. Although this is promising this number should be checked again with higher
5635 statistics to judge its accuracy. Overall there is still more optimization that can occur with this placement.

5636 Cross sections of the beam pipe in the $Y = 0$ and $X = 0$ planes with the shields and masks included can
5637 be seen in Figure 7.43.




Figure 7.42: High Luminosity: Absorber Dimensions

Absorber Type	Power [W]
Flat	22
Wedge	18.5
Wedge & Mask/Shield	0

Table 7.23: High Luminosity: Backscattering/Mask

7.12.3 High Detector Acceptance

Parameters

For the Ring Ring high acceptance option the basic parameters are listed in Table 7.24. The separation refers to the displacement between the two interacting beams at the face of the proton triplet.

Characteristic	Value
Electron Energy [GeV]	60
Electron Current [mA]	100
Crossing Angle [mrad]	1
Absorber Position [m]	-21.5
Dipole Field [T]	0.0493
Separation [mm]	55.16
γ/s	6.41×10^{18}

Table 7.24: High Acceptance: Parameters

The energy, current, and crossing angle (θ_c) are common values used in all RR calculations. The dipole




Figure 7.43: High Luminosity: Beampipe Cross Sections

5643 field value refers to the constant dipole field created throughout all dipole elements in the IR. The separation
 5644 is the same as in the high luminosity case and can be altered for the same reasons with the same ramifica-
 5645 tions. The chosen parameters give a flux of 6.41×10^{18} photons per second at $Z = -21.5$ m, which is slightly
 5646 higher than in the high luminosity case. This is expected as the fields experienced in the high acceptance
 5647 case are higher.

5648 Power and Critical Energy

5649 Table 7.25 shows the power of the SR produced by each element along with the average critical energy
 5650 produced per element. This is followed by the total power produced in the IR and the average critical
 5651 energy. Since the G4 simulations utilize Monte Carlo, multiple runs should be made with various seeds to
 5652 get an estimate for the standard error.

Element	Power [kW]	Critical Energy [keV]
DL	13.9	118
QL2	6.2	318
QL1	5.4	294
QR1	5.4	293
QR2	6.3	318
DR	13.9	118
Total/Avg	51.1	163

Table 7.25: High Acceptance: Power and Critical Energies [Geant4]

5653 The distribution of power and critical energy over the IR elements is similar to that of the high acceptance
 5654 option with the exception of the upstream and downstream separator dipole magnets. The power and

critical energies are significantly higher than before. This is due to the higher dipole field and the quadratic dependence of power on magnetic field and linear dependence of critical energy on magnetic field [625].

5657 **Comparison**

5658 The IRSYN cross check of the power and critical energies is shown in Table 7.26. This comparison was done
5659 for the total power and the critical energy.

	Power [kW]		Critical Energy [keV]	
	Geant4	IRSYN	Geant4	IRSYN
Total/Avg	51.1	51.3	163	162

Table 7.26: High Acceptance: Geant4 and IRSYN comparison

5660 A third cross check to the G4 simulations was also made for the power as shown in Table 7.27. This
5661 was done using an analytic method for calculating power in dipole and quadrupole magnets [624]. This
5662 comparison provides confidence in the distribution of the power throughout the IR.

Element	Power [kW]	
	Geant4	Analytic
DL	13.9	14
QL2	6.2	6.2
QL1	5.4	5.3
QR1	5.4	5.3
QR2	6.3	6.2
DR	13.9	14
Total	51.1	51

Table 7.27: High Acceptance: Geant4 and Analytic method comparison

5663 **Number Density and Envelopes**

5664 The number density of photons as a function of Z is shown in Figure 7.44. The horizontal extension of the
5665 fan in the high acceptance case is larger than in the high luminosity case however still lower than in the LR
5666 option. Since the beam stays at a constant angle for the first 6.2 m after the IP it requires larger fields to
5667 bend in order to reach the desired separation. This means that an overall larger angle is reached near the
5668 absorber, and since the S shaped trajectory is symmetric in Z the angle of the beam at the entrance of the
5669 upstream quadrupoles is also larger and therefore the fan extends further in X.

5670 The envelope of the SR fan can be seen in Figure 7.45, where the XZ plane is shown at the value $Y = 0$.
5671 Once again the fan is antisymmetric due to the S shape of the electron beam.

5672 **Critical Energy Distribution**

5673 The critical energy distribution in Z is similar to that of the high luminosity case. This is due to the focusing
5674 of the beam in the IR. This is evident from Figure 7.46.

5675 **Absorber**

5676 Looking at Figure 7.47 it is shown that for the high acceptance option 38.5 kW of power from the SR light
5677 will fall on the face of the absorber which is 75% of the total power. This gives a general idea of the amount of




Figure 7.44: High Acceptance: Number Density Growth in Z




Figure 7.45: High Acceptance: Beam Envelopes in Z




Figure 7.46: High Acceptance: Critical Energy Distribution in Z




Figure 7.47: High Acceptance: Photon distribution on Absorber Surface

5678 power that will be absorbed. However, backscattering and IR photons will lower the percent that is actually
5679 absorbed.

5680 Proton Triplet

5681 The super conducting final focusing triplet for the protons needs to be protected from radiation by the
5682 absorber. Some of the radiation produced upstream of the absorber however will either pass through the
5683 absorber or pass through the apertures for the two interacting beams. This is most concerning for the
5684 interacting proton beam aperture which will have the superconducting coils. A rough upper bound for
5685 the amount of power the coils can absorb before quenching is 100 W [627]. In the high acceptance option
5686 there is approximately 0.4 W entering into the interacting proton beam aperture as is shown in Figure 7.47.
5687 Therefore for the high acceptance option this is not an issue. The amount of power that will pass through
5688 the absorber can be disregarded as it is not enough to cause any significant effects. The main source of
5689 power moving downstream of the absorber will be the photons passing through the beams aperture. This
5690 was approximately 12.7 kW as can be seen from Figure 7.47. Most of this radiation can be absorbed in
5691 a secondary absorber placed after the first downstream proton quadrupole. Overall protecting the proton
5692 triplet is important and although the absorber will minimize the radiation continuing downstream this needs
5693 to be studied in depth.

5694 Backscattering

5695 Another Geant4 program was written to simulate the backscattering of photons into the detector region.
5696 The ntuple with the photon information written at the absorber surface is used as the input for this program.
5697 An absorber geometry made of copper is described, and general physics processes are set up. A detector
5698 volume is then described and set to record the information of all the photons which enter in an ntuple. The
5699 first step in minimizing the backscattering was to optimize the absorber shape. Although the simulation
5700 didn't include a beam pipe the backscattering for different absorber geometries was compared against one
5701 another to find a minimum. The most basic shape was a block of copper that had cylinders removed for the
5702 interacting beams. This was used as a benchmark to see the maximum possible backscattering. In HERA a
5703 wedge shape was used for heat dissipation and minimizing backscattering [626]. The profile of two possible
5704 wedge shapes in the YZ plane is shown in Figure 7.48. It was found that this is the optimum shape for
5705 the absorber. The reason for this is that a backscattered electron would have to have its velocity vector be
5706 almost parallel to the wedge surface to escape from the wedge and therefore it works as a trap. As can be
5707 seen from Table 7.28 utilizing the wedge shaped absorber decreased the backscattered power by a factor of
5708 9.

5709 After the absorber was optimized it was possible to set up a beam pipe geometry. An asymmetric
5710 elliptical cone beam pipe geometry made of beryllium was used since it would minimize the necessary size
5711 of the beam pipe as previously mentioned. The next step was to place the lead shield and masks inside this
5712 beam pipe. To determine placement a simulation was run with just the beam pipe. Then it was recorded
5713 where each backscattered photon would hit the beam pipe in Z. This determined that the shield should be
5714 placed in the Z region ranging from -20 m until the absorber (-21.5 m). The shields were then placed at -21.2
5715 m and -20.6 m. This decreased the backscattered power to zero as can be seen from Table 7.28. Although
5716 this is promising this number should be checked again with higher statistics to judge its accuracy. Overall
5717 there is still more optimization that can occur with this placement.

Absorber Type	Power [W]
Flat	91.1
Wedge	10
Wedge & Mask/Shield	0

Table 7.28: High Acceptance: Backscattering/Mask




Figure 7.48: High Acceptance: Absorber Dimensions

5718 Cross sections of the beam pipe in the $Y = 0$ and $X = 0$ planes with the shields and masks included can
 5719 be seen in Figure 7.49.




Figure 7.49: High Acceptance: Beampipe Cross Sections

7.13 Beam-beam effects in the LHeC

In the framework of the Large Hadron electron Collider a ring-ring option is considered where protons of one beam collide with the protons of the second proton beam as well as with leptons from a separate ring. To deduce possible limitations the present knowledge of the LHC beam-beam effects from proton-proton collisions are fundamental to define parameters of an interaction point with electron-proton collisions. From past experience it is known that the maximum achievable luminosity in a collider is limited by beam-beam effects. These are often quantified by the maximum beam-beam tune shifts in each of the two beams. An important aspect in electron-proton collisions is that the proton beam, more sensitive to transverse noise, could be perturbed by a higher level of noise in the electron beam. In this section we will assess some limits to the possible tune shift achievable in collision based on experience from past colliders as CESR [628] and LEP [629] and more recent ones like the LHC [630].

7.13.1 Head-on beam-beam effects

A first important performance issue in beam-beam interaction comes from the restricted choice of the β -function at the interaction point to keep the transverse beam sizes equal for the two beams since proton and electron emittances are different. The choice of beta functions at the interaction point has to be different for the two beams in order to keep $\sigma_x^e = \sigma_x^p$ and $\sigma_y^e = \sigma_y^p$ for the reasons explained in detail in [631]. In a mismatched collision the larger bunch may suffer more because a large part of the particle distribution will experience the non-linear beam-beam force of the other bunch. With this in mind it is preferable to keep the electron beam slightly larger than the proton beam since the electron beam may be less sensitive due to strong radiation damping. This matching implies that the electron emittances must be controlled during operation and kept as constant as possible (i.e. H/V coupling). For the proton beam the beam-beam effects from the electron beam will be different for the two planes. Optical matching of the beam sizes at the IP is the first constraint for any interaction region layout proposed.

Another important issue is the achievable tune shift and how this relates to the linear beam-beam parameter which is normally the parameter used to evaluate the strength of the beam-beam interaction.

The linear beam-beam parameter is defined as ξ_{bb} and is expressed for the case of round beams like in proton-proton collision at the LHC as:

$$\xi_{bb} = \frac{Nr_p\beta^*}{4\pi\gamma\sigma^2} \quad (7.12)$$

where r_p is the classical proton radius, β^* is the optical amplitude function (β -function) at the interaction point, $\sigma = \sigma_{x,y}$ is the transverse beam size in meters at the interaction point, N_p is the bunch intensity and γ is the relativistic factor. For proton-proton collisions where ξ_{bb} does not reach too large values and the operational tune is far enough away from linear resonances, this parameter is about equal to the linear tune shift ΔQ expected from the head-on beam-beam interaction. This is the case for the LHC proton-proton collisions at IP1 and IP5 where the linear tune shift per IP is of the order of 0.0034/0.0037 for nominal beam parameters as summarized in Table 7.29 and corresponds to the linear beam-beam parameter ξ_{bb} . This is in general not true for lepton colliders where the operational scenario differs from hadron colliders and other effects become dominant and have to be taken into account.

In the case of electron beams the transverse shape of the beams is normally elliptical with $\sigma_x > \sigma_y$. In this configuration one can generalize the linear beam-beam parameter calculation with the following formula [632]:

$$\xi_{x,y} = \frac{Nr_e\beta_{x,y}^*}{2\pi\gamma\sigma_{x,y}(\sigma_x + \sigma_y)} \quad (7.13)$$

with r_e is the electron classical radius.

In the case of electron-proton collisions one has to also take into account the different species during collision and the beam-beam parameters become:

Parameter	LEP	LHC (nominal)
Beam sizes	180 μ m \cdot 7 μ m	16.6 μ m \cdot 16.6 μ m
Intensity N	4.0 \cdot 10 ¹¹ /bunch	1.15 \cdot 10 ¹¹ /bunch
Energy	100 GeV	7000 GeV
$\beta_x^* \cdot \beta_y^*$	1.25 m \cdot 0.05 m	0.55 m \cdot 0.55 m
Crossing angle	0.0	0/285 μ rad
Beam-beam tune shift(ΔQ)	0.0400	0.0037/0.0034

Table 7.29: Comparison of parameters for the LEP collider and the LHC.

$$\xi_{(x,y),b_1} = \frac{N_{b_2} r_{b_1} \beta_{(x,y),b_1}^*}{2\pi \gamma_{b_1} \sigma_{(x,y),b_2} (\sigma_{x,b_2} + \sigma_{y,b_2})} \quad (7.14)$$

5763 Here b_1 and b_2 refer to Beam1 and Beam2 respectively. The linear beam-beam parameter ξ is often used
5764 to quantify the strength of the beam-beam interaction, however it does not reflect the non-linear nature of
5765 the electromagnetic interaction. Nevertheless, it can be used for comparison and as a scaling parameter.
5766 Since a general beam-beam limit cannot be found and will be different from one collider to the next, the
5767 interpretation should be conservative.

5768 In Table 7.29 we compare LEP and LHC beam parameters and achieved linear beam-beam parameters.
5769 Some of the differences are striking: while the beams in the LHC are round at the interaction point, they are
5770 very flat in LEP. This is due to the excitation of the beam in the horizontal plane by the strong synchrotron
5771 radiation and damping in the vertical plane. Another observation is the much larger beam-beam parameter
5772 in LEP.

5773 One reason for the larger achievable beam-beam parameter in lepton colliders is due to a significant
5774 dynamic beta effect when operating at a working point close to integer tune. This is considered more
5775 difficult with proton beams. In Equation 7.15 the perturbed β^* is expressed as a function of the beam-beam
5776 parameter ξ and the phase advance between two interaction points $2\pi Q^i$. The tune shift ΔQ becomes a
5777 function of the tune which can be chosen to keep the actual shift small.

$$\beta^*(Q, \xi) = \frac{\beta}{\sqrt{1 + 4\pi\xi(\cot(2\pi Q^i)) - 4\pi^2\xi^2}} \quad (7.15)$$

5778 From experience it is known that electrons have a bigger range for the linear head-on beam-beam param-
5779 eter: LEP II has proved an unperturbed beam-beam parameter of 0.07 per interaction point corresponding
5780 to a measured ΔQ of 0.03 - 0.04 as also confirmed in other lepton colliders. The large difference between the
5781 beam-beam parameter and the achieved tune shift was due to the strong dynamic β effect in LEP. CESR
5782 demonstrated the possibility to achieve tune shifts of the order of 0.09. A second and most important reason
5783 for a higher acceptable tune shift in lepton colliders is the synchrotron radiation damping. Furthermore,
5784 while for lepton colliders a clear indication for a "beam-beam limit" exists, not such criteria can be easily de-
5785 fined for hadron machines [630]. From these considerations we have to assume that the choice of beam-beam
5786 parameters ξ_{bb} of the proton beam is restricted.

5787 The LHC as a proton-proton collider has confirmed previous experience from $Spp\bar{p}S$ and Tevatron that
5788 a total linear tune shift of 0.018 (0.006 per IP) is tolerable with neither important losses nor reduction of
5789 beam lifetime during normal operation. It is generally admitted that ξ_{bb} could reach a value of 0.01 per
5790 interaction point. Recent experiments at the LHC with very high intensity beams beyond ultimate and
5791 reduced transverse beam sizes demonstrated the possibility to reach head-on tune shifts well beyond the
5792 nominal values [630]. At the LHC tune shifts per IP close to 0.02 have been achieved. Total tune shifts
5793 exceeding 0.034 have also been achieved with stable beams for two symmetric crossings at IP1 and IP5. These
5794 latest experiments demonstrate the possibility to operate with larger than nominal beam-beam parameters.

IR Option	1 degree		10 degree	
	Electrons	Protons	Electrons	Protons
Beams	Electrons	Protons	Electrons	Protons
Energy	60 GeV	7 TeV	60 GeV	7 TeV
Intensity	$2 \cdot 10^{10}$	$1.7 \cdot 10^{11}$	$2 \cdot 10^{10}$	$1.7 \cdot 10^{11}$
β_x^*	0.4 m	4.05 m	0.18 m	1.8 m
β_y^*	0.2 m	0.97 m	0.1 m	0.5 m
ϵ_x	5 nm	0.5 nm	5 nm	0.5 nm
ϵ_y	2.5 nm	0.5 nm	2.5 nm	0.5 nm
σ_x	45 μm		30 μm	
σ_y	22 μm		15.8 μm	
Crossing angle	1 mrad		1 mrad	
$\xi_{bb,x}$	0.086	0.0008	0.085	0.0008
$\xi_{bb,y}$	0.088	0.0004	0.090	0.0004
Luminosity	$7.33 \cdot 10^{32} \text{ cm}^{-2}\text{s}^{-1}$		$1.34 \cdot 10^{33} \text{ cm}^{-2}\text{s}^{-1}$	

Table 7.30: Beam parameters for the interaction region options and the linear beam-beam parameters ξ .

	Nominal		Upgrade	
	Electrons	Protons	Electrons	Protons
$\xi_{bb,x}$	0.016	0.0013	0.027	0.0017
$\xi_{bb,y}$	0.018	0.0012	0.041	0.0005

Table 7.31: Linear beam-beam parameters for HERA, nominal machine and upgrade parameters.

5795 The calculated beam-beam parameters for the electron and proton beams due to an electron-proton
5796 collision in the LHeC are summarized in Table 7.30 for the two interaction region options (1 Degree Option
5797 and 10 Degree Option).

5798 The two proposed interaction region options will give for the proton beam a maximum beam-beam
5799 parameter in the horizontal plane of about $8 \cdot 10^{-4}$. This effect is in the shadow of the proton-proton
5800 collision at IP1 and IP5 which will give a beam-beam parameter of $5.5 \cdot 10^{-3}$ per IP for nominal beam
5801 emittances and assuming intensities of $1.7 \cdot 10^{11}$ protons/bunch, which was already exceeded during 2010
5802 operation at the LHC with reduced emittances and nominal beam intensities. One should not expect
5803 detrimental effects of the head-on interactions with the electron beam apart from a potential coupling of
5804 noise from the electron into the proton beam.

5805 For the electron beam, on the contrary, the beam-beam parameter of $8.6 \cdot 10^{-2}$ is large and represents a
5806 value at the limit of what has been achieved so far in other lepton machines (LEP at 90 GeV energy achieved
5807 an unperturbed beam-beam parameter of 0.07, (with a maximum tune shift of 0.04) while KEK and HERA
5808 achieved a maximum $\xi_{bb} = 0.04$ during operation, CESR achieved a beam-beam parameter of 0.09 for single
5809 IP but with lower luminosity). The beam-beam tune shifts achieved at HERA for the nominal and upgrade
5810 version are summarized in Table 7.31 for comparison. The foreseen beam-beam parameter of $8.6 \cdot 10^{-2}$ is
5811 optimistic and a significant reduction due to dynamic beta and the small number of interaction points could
5812 make it feasible.

IR Option	1 degree		10 degree	
Beams	Electrons	Protons	Electrons	Protons
β_x^*	0.4 m	4.05 m	0.18 m	1.8 m
β_y^*	0.2 m	0.97 m	0.1 m	0.5 m
ϵ_x	5 nm	0.5 nm	5 nm	0.5 nm
ϵ_y	2.5 nm	0.5 nm	2.5 nm	0.5 nm
Crossing angle	1 mrad		1 mrad	
d_x	$90 \sigma_p$	$8.94 \sigma_e$	$60 \sigma_p$	$6.0 \sigma_e$

Table 7.32: Normalized beam separation d_x at beam-beam long range encounters for the two interaction region options.

7.13.2 Long range beam-beam effects

So far we have discussed head-on beam-beam interactions but an important issue are the long range interactions which will occur at the electron-proton collision and their interplay with the proton-proton crossings at IP1 and IP5. The two interaction points IP1 and IP5 will give up to 60 proton-proton long-range interactions which should be added to the two interaction region options which will give two additional parasitic encounters. The beam separation at this encounters should be as large as possible to reduce any non-linear perturbation. The parasitic encounters occur every 3.75 m from the interaction point for a bunch spacing of 25 ns. The proposed optics will then lead to parasitic beam-beam interactions which will occur at a transverse separation d as:

$$d(s)_{x,y} = \alpha \frac{s}{\sqrt{\epsilon_{x,y} \beta(s)_{x,y}}} \quad (7.16)$$

with $\epsilon_{x,y}$ are the beam emittance in the separation plane and $\beta(s)$ is the betatron function at a distance s from the interaction point.

In Table 7.32 the distances of the parasitic encounters in units of the transverse beam sizes are shown for both interaction region layouts.

The 1 degree option gives long range interactions at larger separation with respect to the 10 degree option which results in small separations of $\approx 6 \sigma$ for the proton beam. Particles in the tail of the proton beam particles will experience the non linearity of the electron beam electromagnetic force. The presence of two long range at 6σ separation may be acceptable since it is shown experimentally that few encounters also at smaller separation do not affect the beams dramatically [633]. However, the interplay of these two encounters with the long-range interactions from IP1 and IP5 should be studied in detail with numerical simulation to highlight possible limitations. In this framework future experiments at the LHC will help defining a possible beam parameters space for the control of the long-range effects from proton-proton collisions. If encounters at 6σ present a limitation to the collider performance then a possible cure to increase the long-range separation could be a further increase of the crossing angle and using crab cavities can recover the increased geometric luminosity reduction factor. In this case a study of the crab cavities effects on the proton beam would be essential to define the effects of transverse noise on colliding beams.

For any reliable study of the LHeC project one has to address other possible beam-beam issues with extensive numerical simulations of the operational scenario of the LHeC. This is fundamental since there is no other possible simplification which can be adopted in evaluating the non-linear parts of the beam-beam forces. For this reason a detailed and full interaction layout with crossing schemes matched in thin lens version is needed. With the complete optic layout beam-beam effects which still need further studies by means of numerical simulation campaign are the following:

- Long-range tune shifts and orbit effects.
- Self-consistent study of the proton-proton and electron-proton beam dynamics interplay.

- 5846 • Dynamic aperture tracking studies.
- 5847 • Multi-bunch effects.
- 5848 • Noise coupling from the electron to the proton beam.

5849 The evaluation of the non-linear effects of the beam-beam interactions with self-consistent calculations will
 5850 define a set of parameters for operation [634].

5851 7.14 Performance as an electron-ion collider

5852 7.14.1 Heavy nuclei, e-Pb collisions

5853 With the first collisions of lead nuclei ($^{208}\text{Pb}^{82+}$) in 2010 [288, 635], the LHC has already demonstrated
 5854 its capability as a heavy-ion collider and this naturally opens up the possibility of electron-nucleus (e-A)
 5855 collisions in the LHeC.

5856 In order to avoid interference with the high luminosity proton-proton operation, this mode of operation
 5857 would naturally be included in the annually-scheduled ion operation period of the LHC. In principle, the
 5858 CERN complex could provide A-A (or even p-A) collisions to the LHC experiments while the LHeC operates
 5859 with e-A collisions. The lifetime of the nuclear beam would depend mainly on whether it was exposed to
 5860 the losses from A-A luminosity in the LHC (in this case it would be at least a few hours).

5861 In the first decade or so of LHC operation, the ion injector chain is expected to provide mainly $^{208}\text{Pb}^{82+}$,
 5862 but also other species such as $^{40}\text{Ar}^{18+}$ or $^{129}\text{Xe}^{54+}$, either to the LHC or from the SPS to fixed target
 5863 experiments in the North Area. These beams could also be collided with electrons in the LHeC but solid
 5864 intensity estimates are not yet available for the lighter ions. For simplicity, we shall estimate LHeC perfor-
 5865 mance in e-Pb collisions with the design performance values of the ion injector chain as described in [636]
 5866 and the assumption of a single nuclear beam in one ring of the LHC with parameters as recalled from [637]
 5867 in Table 7.33. It is assumed that present uncertainties about the Pb intensity limits at full energy in the
 5868 LHC will have been resolved, if necessary, by installation of new collimators in the dispersion suppressors of
 5869 the collimation insertions in the LHC. This simplifies the discussion because the design emittances of Pb and
 5870 proton beams in the LHC are such that both species have the same geometric beam sizes and considerations
 5871 of optics and aperture can be taken over directly. The “Ultimate Pb” value of the Pb single bunch intensity
 5872 was already attained in 2010 [635] using a simplified injection scheme but not yet with the nominal filling
 5873 scheme for 592 bunches; it can be considered an optimistic goal. At present, there are no prospects for
 5874 increasing the number of bunches significantly. Lower Pb emittances may be possible but would not increase
 5875 e-Pb luminosity unless matched with smaller optical functions or emittances for the electron beam.

		Design Pb	Ultimate Pb
Energy	E_{Pb}	574. TeV	
Energy per nucleon	E_N	2.76 TeV	
No. of bunches	n_b	592	
Ions per bunch	N_{Pb}	$7. \times 10^7$	1.2×10^8
Normalised emittance	ε_n	$1.5 \mu\text{m}$	

Table 7.33: Parameters for the $^{208}\text{Pb}^{82+}$ beam according to Chapter 21 of [637].

5876 Assume that the injection system can create an electron bunch train matching the 592-bunch train of Pb
 5877 nuclei in the LHC so that every Pb bunch finds a collision partner in the electron beam. Assuming further
 5878 that the hadron optics can be adjusted to match the sizes of the electron and Pb beams, the luminosity
 5879 can be expressed in terms of the interaction point optical functions and emittances of the electron beam.

5880 Since the e-A physics is focused on low- x these are taken from Table 7.14 describing the Ring-Ring High
 5881 Acceptance optics, which reduces the luminosity by a factor 2 as compared with the High-Luminosity optics.

5882 In e-p mode, the intensity of the 2808 electron bunches, N_e is limited for the Ring-Ring version of the
 5883 LHeC by the total RF power available to compensate the synchrotron radiation loss. For the same power
 5884 (some 44 MW for $N_e = 2 \times 10^{10}$ of Table 7.11), the intensity of the $n_b = 592$ bunches required to collide
 5885 with the Pb nuclei can be increased by a factor 2808/592 to $N_e = 9.5 \times 10^{10}$. Electron beam parameters
 5886 for the LHeC Ring-Ring option other than the single bunch intensity can be taken from Table 7.11. Present
 5887 experience with beam-beam effects in the LHC suggests that the additional electron intensity would not
 5888 present any problem for the proton beam. The single-bunch intensity is still well below that achieved in
 5889 LEP although the feasibility of these values should be confirmed by further analysis of the ring impedance
 5890 and collective effects.

5891 Neglecting the geometric reduction factor due to the crossing angle and the hourglass effect, the *electron-*
 5892 *nucleon* luminosity, $L_{eN} = AL_{eA}$, is then given by

$$L_{eN} = \frac{n_b f_0 N_e (AN_{\text{Pb}})}{4\pi \sqrt{\beta_{xe}^*} \varepsilon_x \sqrt{\beta_{ye}^*} \varepsilon_y} = \begin{cases} 2.6 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1} & \text{(Nominal Pb)} \\ 4.5 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1} & \text{(Ultimate Pb)} \end{cases} \quad (7.17)$$

5893 This gives an indication of the range of peak luminosities that can be expected. A factor of 2 could be gained
 5894 by switching to the high-luminosity interaction region optics.

5895 By the time the LHeC comes into operation, it is not unreasonable to hope that ways to increase the
 5896 number of Pb bunches and perhaps to reduce their emittance (by cooling) may be implemented. Therefore,
 5897 on an optimistic view, the luminosity could be even higher than the value quoted here.

5898 Finally, we note that the dependence of luminosity on electron beam energy ($\propto E_e^{-6}$) is very strong at
 5899 the power limit so that a trade-off between energy and luminosity may be of interest.

5900 7.14.2 Electron-deuteron collisions

5901 As discussed in [283], deuteron beams are not presently available in the CERN complex. Meanwhile it has
 5902 been clearly demonstrated [638] that it would not be feasible to set up a D^- source and accelerate them
 5903 via Linac4. The present proton Linac2 is due to be shut down so the only way to accelerate them would
 5904 be via the heavy ion Linac3. However this would require a new source, RFQ and switch-yard at the input
 5905 to Linac3. The study of practical feasibility, space limitations, design and potential performance of these
 5906 modifications to the injector complex started in late 2011 with a view to supplying light ions to fixed target
 5907 experiments and the LHC in several years' time.

5908 Assuming that a practical design can be implemented, the intensity of bunches in the LHC ring can be
 5909 estimated as follows.

5910 The present GTS-LHC source delivers $^{208}\text{Pb}^{29+}$ ions with a charge-to-mass ratio $Q/A = 1/7.2$. A
 5911 safe estimate of the space-charge limit at the entrance of Linac3 is $200 \mu\text{A}$. To accelerate deuterons with
 5912 $Q/A = 1/2$, all magnetic and electric fields would have to be reduced by a factor 3.6, leading to a space-charge
 5913 limited current of $55 \mu\text{A}$.

5914 However there is then a very comfortable margin in the electric and magnetic fields and deuterons are
 5915 not subject to the loss factors associated with the subsequent stripping stages for Pb. If enough deuteron
 5916 current is available from the source (say 5 mA), and one accepts losses in the linac and a somewhat degraded
 5917 beam quality at the end, then a current in the range of 200-500 μA would probably be available at the end
 5918 of the linac.

5919 As a caveat, early measurements of poor transmission of helium ions in Linac3 [639] should be mentioned.
 5920 However the explanation is unclear due to the lack of appropriate diagnostics.

5921 The bunch number and filling pattern in the LHC would be similar to that of the Pb beam. A naive
 5922 transposition of the scaling of the ratios of Linac3 output current ($50 \mu\text{A}$) to LHC bunch intensity (7×10^7)
 5923 from Pb to deuterons would suggest that the deuteron single-bunch intensity in the LHC could be $N_D \approx$
 5924 1.5×10^{10} .

5925 However this does not consider the differences in performance of the remainder of the injector chain (the
5926 LEIR cooling ring, PS and SPS synchrotrons). A proper evaluation of these requires a more detailed study.
5927 To be safe, we can apply a factor 5 reduction to this value.

5928 Then, assuming that we collide such a beam with the electron beam described in the preceding sub-
5929 section, we see that *electron-nucleon* luminosities of order $L_{eN} \gtrsim 10^{31} \text{ cm}^{-2}\text{s}^{-1}$ could be accessible in e-D
5930 collisions at the LHeC.

5931 7.15 Spin polarisation – an overview

5932 Before describing concepts for attaining electron and positron spin polarisation for the ring-ring option of
5933 the LHeC we present a brief overview of the theory and phenomenology. We can then draw on this later as
5934 required. This overview is necessarily brief but more details can be found in [640,641].

5935 7.15.1 Self polarisation

5936 The spin polarisation of an ensemble of spin-1/2 fermions with the same energies travelling in the same
5937 direction is defined as

$$\vec{P} = \left\langle \frac{2}{\hbar} \vec{\sigma} \right\rangle \quad (7.18)$$

5938 where $\vec{\sigma}$ is the spin operator in the rest frame and $\langle \rangle$ denotes the expectation value for the mixed spin
5939 state. We denote the single-particle rest-frame expectation value of $\frac{2}{\hbar} \vec{\sigma}$ by \vec{S} and we call this the “spin”.
5940 The polarisation is then the average of \vec{S} over an ensemble of particles such as that of a bunch of particles.

5941 Electrons and positrons circulating in the (vertical) guide field of a storage ring emit synchrotron radiation
5942 and a tiny fraction of the photons can cause spin flip from up to down and vice versa. However, the up-
5943 to-down and down-to-up rates differ, with the result that in ideal circumstances the electron (positron)
5944 beam can become spin polarised anti-parallel (parallel) to the field, reaching a maximum polarisation, P_{st} ,
5945 of $\frac{8}{5\sqrt{3}} = 92.4\%$. This, the Sokolov-Ternov (S-T) polarising process, is very slow on the time scale of other
5946 dynamical phenomena occurring in storage rings, and the inverse time constant for the exponential build up
5947 is [642]:

$$\tau_{\text{st}}^{-1} = \frac{5\sqrt{3}}{8} \frac{r_e \gamma^5 \hbar}{m_e |\rho|^3} \quad (7.19)$$

5948 where r_e is the classical electron radius, γ is the Lorentz factor, ρ is the radius of curvature in the magnets
5949 and the other symbols have their usual meanings. The time constant is usually in the range of a few minutes
5950 to a few hours.

5951 However, even without radiative spin flip, the spins are not stationary but precess in the external fields.
5952 In particular, the motion of \vec{S} for a charged particle travelling in electric and magnetic fields is governed by
5953 the Thomas-BMT equation $d\vec{S}/ds = \vec{\Omega} \times \vec{S}$ where s is the distance around the ring [641,643]. The vector $\vec{\Omega}$
5954 depends on the electric (\vec{E}) and magnetic (\vec{B}) fields, the energy and the velocity (\vec{v}) which evolves according
5955 to the Lorentz equation:

$$\vec{\Omega} = \frac{e}{m_e c} \left[- \left(\frac{1}{\gamma} + a \right) \vec{B} + \frac{a\gamma}{1+\gamma} \frac{1}{c^2} (\vec{v} \cdot \vec{B}) \vec{v} + \frac{1}{c^2} \left(a + \frac{1}{1+\gamma} \right) (\vec{v} \times \vec{E}) \right] \quad (7.20)$$

$$= \frac{e}{m_e c} \left[- \left(\frac{1}{\gamma} + a \right) \vec{B}_{\perp} - \frac{g}{2\gamma} \vec{B}_{\parallel} + \frac{1}{c^2} \left(a + \frac{1}{1+\gamma} \right) (\vec{v} \times \vec{E}) \right]. \quad (7.21)$$

5956 Thus $\vec{\Omega}$ depends on s and on the position of the particle $u \equiv (x, p_x, y, p_y, l, \delta)$ in the 6-D phase space of
5957 the motion. The coordinate δ is the fractional deviation of the energy from the energy of a synchronous
5958 particle (“the beam energy”) and l is the distance from the centre of the bunch. The coordinates x and y are

5959 the horizontal and vertical positions of the particle relative to the reference trajectory and $p_x = x', p_y = y'$
 5960 (except in solenoids) are their conjugate momenta. The quantity g is the appropriate gyromagnetic factor
 5961 and $a = (g - 2)/2$ is the gyromagnetic anomaly. For e^\pm , $a \approx 0.0011596$. \vec{B}_\parallel and \vec{B}_\perp are the magnetic fields
 5962 parallel and perpendicular to the velocity.

5963 In a simplified picture, the majority of the photons in the synchrotron radiation do not cause spin flip but
 5964 tend instead to randomise the e^\pm orbital motion in the (inhomogeneous) magnetic fields. Then, if the ring is
 5965 insufficiently-well geometrically aligned and/or if it contains special magnet systems like the “spin rotators”
 5966 needed to produce longitudinal polarisation at a detector (see below), the spin-orbit coupling embodied in
 5967 the Thomas-BMT equation can cause spin diffusion, i.e. depolarisation. Compared to the S-T polarising
 5968 effect the depolarisation tends to rise very strongly with beam energy. The equilibrium polarisation is then
 5969 less than 92.4% and will depend on the relative strengths of the polarisation and depolarisation processes. As
 5970 we shall see later, even without depolarisation certain dipole layouts can reduce the equilibrium polarisation
 5971 to below 92.4%.

5972 Analytical estimates of the attainable equilibrium polarisation are best based on the Derbenev-Kondratenko
 5973 (D-K) formalism [644, 645]. This implicitly asserts that the value of the equilibrium polarisation in an e^\pm
 5974 storage ring is the same at all points in phase space and is given by

$$P_{\text{dk}} = \mp \frac{8}{5\sqrt{3}} \frac{\oint ds \left\langle \frac{1}{|\rho(s)|^3} \hat{b} \cdot (\hat{n} - \frac{\partial \hat{n}}{\partial \delta}) \right\rangle_s}{\oint ds \left\langle \frac{1}{|\rho(s)|^3} \left(1 - \frac{2}{9} (\hat{n} \cdot \hat{s})^2 + \frac{11}{18} \left| \frac{\partial \hat{n}}{\partial \delta} \right|^2 \right) \right\rangle_s} \quad (7.22)$$

5975 where $\langle \rangle_s$ denotes an average over phase space at azimuth s , \hat{s} is the direction of motion and $\hat{b} = (\hat{s} \times \dot{\hat{s}})/|\dot{\hat{s}}|$.
 5976 \hat{b} is the magnetic field direction if the electric field vanishes and the motion is perpendicular to the magnetic
 5977 field. $\hat{n}(u; s)$ is a unit 3-vector field over the phase space satisfying the Thomas-BMT equation along particle
 5978 trajectories $u(s)$ (which are assumed to be integrable), and it is 1-turn periodic: $\hat{n}(u; s + C) = \hat{n}(u; s)$ where
 5979 C is the circumference of the ring.

5980 The field $\hat{n}(u; s)$ is a key object for systematising spin dynamics in storage rings. It provides a reference
 5981 direction for spin at each point in phase space and it is now called the “invariant spin field” [641, 646, 647].
 5982 At zero orbital amplitude, i.e. on the periodic (“closed”) orbit, the $\hat{n}(0; s)$ is written as $\hat{n}_0(s)$. For e^\pm rings
 5983 and away from spin-orbit resonances (see below), \hat{n} is normally at most a few milliradians away from \hat{n}_0 .

5984 A central ingredient of the D-K formalism is the implicit assumption that the e^\pm polarisation at each
 5985 point in phase space is parallel to \hat{n} at that point. In the approximation that the particles have the same
 5986 energies and are travelling in the same direction, the polarisation of a bunch measured in a polarimeter at
 5987 s is then the ensemble average

$$\vec{P}_{\text{ens,dk}}(s) = P_{\text{dk}} \langle \hat{n} \rangle_s. \quad (7.23)$$

5988 In conventional situations in e^\pm rings, $\langle \hat{n} \rangle_s$ is very nearly aligned along $\hat{n}_0(s)$. The *value* of the ensemble
 5989 average, $P_{\text{ens,dk}}(s)$, is essentially independent of s .

5990 Equation 7.22 can be viewed as having three components. The piece

$$P_{\text{bk}} = \mp \frac{8}{5\sqrt{3}} \frac{\oint ds \left\langle \frac{1}{|\rho(s)|^3} \hat{b} \cdot \hat{n} \right\rangle_s}{\oint ds \left\langle \frac{1}{|\rho(s)|^3} \left(1 - \frac{2}{9} (\hat{n} \cdot \hat{s})^2 \right) \right\rangle_s} \approx \mp \frac{8}{5\sqrt{3}} \frac{\oint ds \frac{1}{|\rho(s)|^3} \hat{b} \cdot \hat{n}_0}{\oint ds \frac{1}{|\rho(s)|^3} \left(1 - \frac{2}{9} n_{0s}^2 \right)}. \quad (7.24)$$

5991 gives the equilibrium polarisation due to radiative spin flip. The quantity n_{0s} is the component of \hat{n}_0 along the
 5992 closed orbit. The subscript “bk” is used here instead of “st” to reflect the fact that this is the generalisation
 5993 by Baier and Katkov [648, 649] of the original S-T expression to cover the case of piecewise homogeneous
 5994 fields. Depolarisation is then accounted for by including the term with $\frac{11}{18} \left| \frac{\partial \hat{n}}{\partial \delta} \right|^2$ in the denominator. Finally,
 5995 the term with $\frac{\partial \hat{n}}{\partial \delta}$ in the numerator is the so-called kinetic polarisation term. This results from the dependence
 5996 of the radiation power on the initial spin direction and is not associated with spin flip. It can normally be
 5997 neglected but is still of interest in rings with special layouts.

5998

In the presence of radiative depolarisation the rate in Eq. 7.19 must be replaced by

$$\tau_{\text{dk}}^{-1} = \frac{5\sqrt{3} r_e \gamma^5 \hbar}{8} \frac{1}{m_e} \frac{1}{C} \oint ds \left\langle \frac{1 - \frac{2}{9} (\hat{n} \cdot \hat{s})^2 + \frac{11}{18} \left| \frac{\partial \hat{n}}{\partial \delta} \right|^2}{|\rho(s)|^3} \right\rangle_s. \quad (7.25)$$

5999

This can be written in terms of the spin-flip polarisation rate, τ_{bk}^{-1} , and the depolarisation rate, τ_{dep}^{-1} , as:

$$\frac{1}{\tau_{\text{dk}}} = \frac{1}{\tau_{\text{bk}}} + \frac{1}{\tau_{\text{dep}}}, \quad (7.26)$$

6000 where

$$\tau_{\text{dep}}^{-1} = \frac{5\sqrt{3} r_e \gamma^5 \hbar}{8} \frac{1}{m_e} \frac{1}{C} \oint ds \left\langle \frac{\frac{11}{18} \left| \frac{\partial \hat{n}}{\partial \delta} \right|^2}{|\rho(s)|^3} \right\rangle_s \quad (7.27)$$

6001 and

$$\tau_{\text{bk}}^{-1} = \frac{5\sqrt{3} r_e \gamma^5 \hbar}{8} \frac{1}{m_e} \frac{1}{C} \oint ds \left\langle \frac{1 - \frac{2}{9} (\hat{n} \cdot \hat{s})^2}{|\rho(s)|^3} \right\rangle_s. \quad (7.28)$$

6002

The time dependence for build-up from an initial polarisation P_0 to equilibrium is

$$P(t) = P_{\text{ens,dk}} \left[1 - e^{-t/\tau_{\text{dk}}} \right] + P_0 e^{-t/\tau_{\text{dk}}}. \quad (7.29)$$

6003

In perfectly aligned e^\pm storage rings containing just horizontal bends, quadrupoles and accelerating cavities, there is no vertical betatron motion and $\hat{n}_0(s)$ is vertical. Since the spins do not “see” radial quadrupole fields and since the electric fields in the cavities are essentially parallel to the particle motion, \hat{n} is vertical, parallel to the guide fields and to $\hat{n}_0(s)$ at all u and s . Then the derivative $\frac{\partial \hat{n}}{\partial \delta}$ vanishes and there is no depolarisation. However, real rings have misalignments. Then there is vertical betatron motion so that the spins also see radial fields which tilt them from the vertical. Moreover, $\hat{n}_0(s)$ is also tilted and the spins can couple to vertical quadrupole fields too. As a result \hat{n} becomes dependent on u and “fans out” away from $\hat{n}_0(s)$ by an amount which usually increases with the orbit amplitudes. Then in general $\frac{\partial \hat{n}}{\partial \delta}$ no longer vanishes in the dipoles (where $1/|\rho(s)|^3$ is large) and depolarisation occurs. In the presence of skew quadrupoles and solenoids and, in particular, in the presence of spin rotators, $\frac{\partial \hat{n}}{\partial \delta}$ can be non-zero in dipoles even with perfect alignment. The deviation of \hat{n} from $\hat{n}_0(s)$, and the depolarisation, tend to be particularly large near to the spin-orbit resonance condition

$$\nu_0 = k_0 + k_I Q_I + k_{II} Q_{II} + k_{III} Q_{III}. \quad (7.30)$$

6015

Here $k_0, k_I, k_{II}, k_{III}$ are integers, Q_I, Q_{II}, Q_{III} are the three tunes of the synchrotron motion and ν_0 is the spin tune on the closed orbit, i.e. the number of precessions around $\hat{n}_0(s)$ per turn, made by a spin on the closed orbit¹. In the special case, or in the approximation, of no synchrotron coupling one can make the associations: $I \rightarrow x$, $II \rightarrow y$ and $III \rightarrow s$, where, here, the subscript s labels the synchrotron mode. In a simple flat ring with no closed-orbit distortion, $\nu_0 = a\gamma$ where γ is the Lorentz factor for the nominal beam energy. For e^\pm , $a\gamma$ increments by 1 for every 441 MeV increase in beam energy. In the presence of misalignments and special elements like rotators, ν_0 is usually still approximately proportional to the beam energy. Thus an energy scan will show peaks in τ_{dep}^{-1} and dips in $P_{\text{ens,dk}}(s)$, namely at around the resonances. Examples can be seen in figures 7.50 and 7.51 below. The resonance condition expresses the fact that the disturbance to spins is greatest when the $|\tilde{\Omega}(u; s) - \tilde{\Omega}(0; s)|$ along a trajectory is coherent (“in step”) with the natural spin precession. The quantity $(|k_I| + |k_{II}| + |k_{III}|)$ is called the order of the resonance. Usually, the strongest resonances are those for which $|k_I| + |k_{II}| + |k_{III}| = 1$, i.e., the first-order resonances. The next

6025

6026

¹In fact the resonance condition should be more precisely expressed in terms of the so-called amplitude dependent spin tune [641, 646, 647]. But for typical e^\pm rings, the amplitude dependent spin tune differs only insignificantly from ν_0 .

6027 strongest are usually the so-called “*synchrotron sideband resonances*” of parent first-order resonances, i.e.
 6028 resonances for which $\nu_0 = k_0 \pm Q_{I,II,III} + \tilde{k}_{III} Q_{III}$ where \tilde{k}_{III} is an integer and mode *III* is associated with
 6029 synchrotron motion. All resonances are due to the non-commutation of successive spin rotations in 3-D and
 6030 they therefore occur even with purely linear orbital motion.

6031 We now list some keys points.

- 6032 • The approximation on the r.h.s. of Eq. 7.24 makes it clear that if there are dipole magnets with fields
 6033 not parallel to \hat{n}_0 , as is the case, for example, when spin rotators are used, then P_{bk} can be lower than
 6034 the 92.4% attainable in the case of a simple ring with no solenoids and where all dipole fields and $\hat{n}_0(s)$
 6035 are vertical.
- 6036 • If, as is usual, the kinetic polarisation term makes just a small contribution, the above formulae can
 6037 be combined to give

$$P_{\text{ens,dk}} \approx P_{\text{bk}} \frac{\tau_{\text{dk}}}{\tau_{\text{bk}}} . \quad (7.31)$$

6038 From Eq. 7.26 it is clear that $\tau_{\text{dk}} \leq \tau_{\text{bk}}$.

- 6039 • The underlying rate of polarisation due to the S-T effect, τ_{bk}^{-1} , increases with the fifth power of the
 6040 energy and decreases with the third power of the bending radii.
- 6041 • It can be shown that as a general rule the “normalised” strength of the depolarisation, $\tau_{\text{dep}}^{-1}/\tau_{\text{bk}}^{-1}$,
 6042 increases with beam energy according to a tune-dependent polynomial in even powers of the beam
 6043 energy. So we expect that the attainable equilibrium polarisation decreases as the energy increases.
 6044 This was confirmed LEP, where with the tools available, little polarisation could be obtained at 60
 6045 GeV [650].

6046 7.15.2 Suppression of depolarisation – spin matching

6047 Although the S-T effect offers a convenient way to obtain stored high energy e^\pm beams, it is only useful in
 6048 practice if there is not too much depolarisation. Depolarisation can be significant if the ring is misaligned,
 6049 if it contains spin rotators or if it contains uncompensated solenoids or skew quadrupoles. Then if $P_{\text{ens,dk}}$
 6050 and/or τ_{dk} are too small, the layout and the optic must be adjusted so that $(|\frac{\partial \hat{n}}{\partial \delta}|)^2$ is small where $1/|\rho(s)|^3$
 6051 is large. So far it is only possible to do this within the linear approximation for spin motion. This technique
 6052 is called “*linear spin matching*” and when successful, as for example at HERA [651], it immediately reduces
 6053 the strengths of the first-order spin-orbit resonances. Spin matching requires two steps: “*strong synchrobeta*
 6054 *spin matching*” is applied to the optics and layout of the perfectly aligned ring and then “*harmonic closed-*
 6055 *orbit spin matching*” is applied to soften the effects of misalignments. This latter technique aims to adjust
 6056 the closed orbit so as to reduce the tilt of \hat{n}_0 from the vertical in the arcs. Since the misalignments can
 6057 vary in time and are usually not sufficiently well known, the adjustments are applied empirically while the
 6058 polarisation is being measured.

6059 Spin matching must be approached on a case-by-case basis. An overview can be found in [640].

6060 7.15.3 Higher order resonances

6061 Even if the beam energy is chosen so that first-order resonances are avoided and in linear approximation
 6062 $P_{\text{ens,dk}}$ and/or τ_{dk} are expected to be large, it can happen that that beam energy corresponds to a higher
 6063 order resonance. As mentioned above, in practice the most intrusive higher order resonances are those for
 6064 which $\nu_0 = k_0 \pm Q_k + \tilde{k}_s Q_s$ ($k \equiv I, II$ or *III*). These synchrotron sideband resonances of the first-order
 6065 parent resonances are due to modulation by energy oscillations of the instantaneous rate of spin precession
 6066 around \hat{n}_0 . The depolarisation rates associated with sidebands of isolated parent resonances ($\nu_0 = k_0 \pm Q_k$)

6067 are related to the depolarisation rates for the parent resonances. For example, if the beam energy is such
 6068 that the system is near to a dominant Q_y resonance we can approximate τ_{dep}^{-1} in the form

$$\tau_{\text{dep}}^{-1} \propto \frac{A_y}{(\nu_0 - k_0 \pm Q_y)^2}. \quad (7.32)$$

6069 This becomes

$$\tau_{\text{dep}}^{-1} \propto \sum_{\tilde{k}_s=-\infty}^{\infty} \frac{A_y B_y(\zeta; \tilde{k}_s)}{(\nu_0 - k_0 \pm Q_y \pm \tilde{k}_s Q_s)^2}$$

6070 if the synchrotron sidebands are included. The quantity A_y depends on the beam energy and the optics and
 6071 is reduced by spin matching. The proportionality constants $B_y(\zeta; \tilde{k}_s)$ are called *enhancement factors*, and
 6072 they contain modified Bessel functions $I_{|\tilde{k}_s|}(\zeta)$ and $I_{|\tilde{k}_s|+1}(\zeta)$ which depend on Q_s and the energy spread σ_δ
 6073 through the *modulation index* $\zeta = (a\gamma \sigma_\delta / Q_s)^2$. More formulae can be found in [652, 653].

6074 Thus the effects of synchrotron sideband resonances can be reduced by doing the spin matches described
 6075 above. Note that these formulae are just meant as a guide since they are approximate and explicitly neglect
 6076 interference between the first-order parent resonances. To get a complete impression, the Monte-Carlo
 6077 simulation mentioned later must be used. The sideband strengths generally increase with the energy spread
 6078 and the beam energy and the sidebands are a major contributor to the increase of $\tau_{\text{dep}}^{-1} / \tau_{\text{bk}}^{-1}$ with energy.

6079 7.15.4 Calculations of the e^\pm polarisation in the LHeC

6080 As a first step towards assessing the attainable polarisation we have considered an early version of the LHeC
 6081 lattice: a flat ring with no rotators, no interaction point and no bypasses. The tunes are $Q_x = 123.83$
 6082 and $Q_y = 85.62$. The horizontal emittance is 8 nm. The ring is therefore typical of the designs under
 6083 consideration. With perfect alignment, \hat{n}_0 is vertical everywhere and there is no vertical dispersion. The
 6084 polarisation will then reach 92.4%. At ≈ 60 GeV, $\tau_{\text{bk}} \approx 60$ minutes.

6085 For the simple flat ring these values can be obtained by hand from Eq. 7.24 and Eq. 7.28. However, in
 6086 general, e.g., in the presence of misalignments or rotators, the calculation of polarisation requires special
 6087 software and for this study, the thick-lens code SLICKTRACK was used [654]. This essentially consists of
 6088 four sections which carry out the following tasks:

- 6089 (1) Simulation of misalignments followed by orbit correction with correction coils.
- 6090 (2) Calculation of the optical properties of the beam and the beam sizes.
- 6091 (3) Calculation of $\partial \hat{n} / \partial \delta$ for linearised spin motion with the thick-lens version (SLICK [655]) of the SLIM
 6092 algorithm [640].

6093 The equilibrium polarisation is then obtained from Eq. 7.22. This provides a first impression and only
 6094 exhibits the first order resonances.

- 6095 (4) Calculation of the rate of depolarisation beyond the linear approximation of item 3.

6096 In general, the numerical calculation of the integrand in Eq. 7.27 beyond first order represents a difficult
 6097 computational problem. Therefore a pragmatic approach is adopted, whereby the rate of depolarisation
 6098 is obtained with a Monte-Carlo spin-orbit tracking algorithm which includes radiation emission. The
 6099 algorithm employs full 3-D spin motion in order to see the effect of the higher order resonances. The
 6100 Monte-Carlo algorithm can also handle the effect on the particles and on the spins of the non-linear
 6101 beam-beam forces. An estimate of the equilibrium polarisation is then obtained from Eq. 7.31.

6102 Some basic features of the polarisation for the misaligned flat ring are shown in figures 7.50 and 7.51
 6103 where polarisations are plotted against $a\gamma$ around 60 GeV. In both cases the r.m.s. vertical closed-orbit
 6104 deviation is about $75\mu\text{m}$. This is obtained after giving the quadrupoles r.m.s. vertical misalignments of




Figure 7.50: Estimated polarisation for the LHeC without spin rotators, $Q_s = 0.06$.

6105 $150\mu\text{m}$ and assigning a correction coil to every quadrupole. The vector \hat{n}_0 has an r.m.s. tilt of about 4
 6106 milliradians from the vertical near $a\gamma = 136.5$. For figure 7.50 the synchrotron tune, Q_s , is 0.06 so that
 6107 $\xi \approx 5$. For figure 7.51, $Q_s = 0.1$ so that $\xi \approx 1.9$.

6108 The red curves depict the polarisation due to the Sokolov-Ternov effect alone. The dip to below 92.4%
 6109 at $a\gamma = 136$ is due to the characteristic very large tilt of \hat{n}_0 from the vertical at an integer value of $a\gamma$.
 6110 See [640].

6111 The green curves depict the equilibrium polarisation after taking into account the depolarisation associ-
 6112 ated with the misalignments and the consequent tilt of \hat{n}_0 . The polarisation is calculated with the linearised
 6113 spin motion as in item 3 above. In these examples the polarisation reaches about 68 %. The strong fall off
 6114 on each side of the peak is mainly due to first-order ‘‘synchrotron’’ resonances $\nu_0 = k_0 \pm Q_s$. Since Q_s is
 6115 small these curves are similar for the two values of Q_s .

6116 The blue curves show the polarisation obtained as in item 4 above. Now, by going beyond the linearisa-
 6117 tion of the spin motion, the peak polarisation is about 27 %. The fall from 68 % is mainly due to synchrotron
 6118 sideband resonances. With $Q_s = 0.06$ (Fig. 7.50) the resonances are overlapping. With $Q_s = 0.1$, (Fig. 7.51)
 6119 the sidebands begin to separate. In any case these curves demonstrate the extreme sensitivity of the attain-
 6120 able polarisation to small tilts of \hat{n}_0 at high energy. Simulations for $Q_s = 0.1$ with a series of differently
 6121 misaligned rings, all with r.m.s. vertical closed-orbit distortions of about $75\mu\text{m}$, exhibit peak equilibrium
 6122 polarisations ranging from about about 10 % to about 40 %. Experience at HERA suggests that harmonic
 6123 closed-orbit spin matching can eliminate the cases of very low polarisation.

6124 Figure 7.52 shows a typical energy dependence of the peak equilibrium polarisation for a fixed RF voltage
 6125 and for one of the misaligned rings. The synchrotron tune varies from $Q_s = 0.093$ at 40 GeV to $Q_s = 0.053$
 6126 at 65 GeV due to the change in energy loss per turn. As expected the attainable polarisation falls steeply
 6127 as the energy increases. However, although with this good alignment, a high polarisation is predicted at 45
 6128 GeV, τ_{bk} would be about 5 hours as at LEP. A small τ_{bk} is not only essential for a programme of particle
 6129 physics, but essential for the application of empirical harmonic closed-orbit spin matching.

6130 As mentioned above, it was difficult to get polarisation at 60 GeV at LEP. However, these calculations
 6131 suggest that by adopting the levels of alignment that are now standard for synchrotron-radiation sources
 6132 and by applying harmonic closed-orbit spin matching, there is reason to hope that high polarisation in a flat
 6133 ring can still be obtained.




Figure 7.51: Estimated polarisation for the LHeC without spin rotators, $Q_s = 0.1$.

7.15.5 Spin rotator concepts for the LHeC

The LHeC, like all analogous projects involving spin, needs longitudinal polarisation at the interaction point. However, if the S-T effect is to be the means of producing and maintaining the polarisation, then as is clear from Eq. 7.24, \hat{n}_0 must be close to vertical in most of the dipoles. We have seen at Eq. 7.23 that the polarisation is essentially parallel to \hat{n}_0 . So to get longitudinal polarisation at a detector, it must be arranged that \hat{n}_0 is longitudinal at the detector but vertical in the rest of the ring. This can be achieved with magnet systems called spin rotators which rotate \hat{n}_0 from vertical to longitudinal on one side of the detector and back to vertical again on the other side.

Spin rotators use sequences of magnets which generate large spin rotations around different axes and exploit the non-commutation of successive large rotations around different axes. According to the T-BMT equation, the rate of spin precession in longitudinal fields is inversely proportional to the energy. However, for motion perpendicular to a magnetic field spins precess at a rate essentially proportional to the energy: $\delta\theta_{\text{spin}} = (a\gamma + 1)\delta\theta_{\text{orb}}$ in obvious notation. Thus for the high-energy ring considered here, spin rotators should be based on dipoles as in HERA [651]. In that case the rotators consisted of interleaved horizontal and vertical bending magnets set up so as to generate interleaved, closed, horizontal and vertical bumps in the design orbit. The individual orbit deflections were small but the spin rotations were of the order of a radian. The success in obtaining high longitudinal polarisation at HERA attests to the efficacy of such rotators.

Eq. 7.24 shows that P_{bk} essentially scales with the cosine of the angle of tilt of \hat{n}_0 from the vertical in the arc dipoles. Thus a rotation error resulting in a tilt of \hat{n}_0 of even a few degrees would not reduce P_{bk} by too much. However, as was mentioned above, a tilt of \hat{n}_0 in the arcs can lead to depolarisation. In fact the calculations below show that at 60 GeV, tilts of more than a few milliradians cause significant depolarisation. Thus well-tuned rotators are essential for maintaining polarisation.

Dipole rotators require a significant amount of space in the ring. To minimise the power density as well as to preserve the polarisation, the amount of synchrotron radiation from the rotators needs to be kept to a minimum, in direct conflict with the desire to keep the dipole magnets as short as possible. In addition, longer dipole magnets lead to larger orbit excursions. A numerical example for HERA-type spin rotators in the LHeC with a bending radius of each dipole equal to that of the arc dipoles yields a length of each spin rotator of about 150 m. The net space appears to be available; the challenge being the integration of the string of dipoles and the vertical magnet movers in an already crowded area of the LHC tunnel. Note that




Figure 7.52: Equilibrium polarisation *vs* ring energy, full 3-D spin tracking results

6164 the rotator incorporates a certain amount of bending angle. The excursion away from the nominal orbit is
 6165 about 0.3 m.

6166 A scheme using two Siberian Snakes has been considered by Derbenev and Grote [656] (see below) that
 6167 would integrate the IR rotators with the vertical dogleg required to bring the beams into collision. For this
 6168 the horizontal bends are all of the same polarity and contribute to the overall 360° bend so that the added
 6169 dipole strength in the IR is minimised.

6170 Table 7.34 gives an indication of possible parameters for LHeC spin rotators. These are subject to change
 6171 as the specific geometry in the IR is being further refined. Note that the effect of these rotators on the degree
 6172 of polarisation remains to be evaluated (but see below for further comments on the Derbenev-Grote scheme).

Table 7.34: Possible Parameters for LHeC Spin Rotators

Parameter	Unit	HERA-type	Derbenev-Grote (IP only)
No. of vertical dipole magnets		12	10
No. of horizontal dipole magnets		12	10
Bending angle/magnet	°	0.110	0.132
Length of magnet	m	5.45	5.45
Total length of rotator	m	170	80
Net bending angle	°	0.66	1.32
Vertical offset	m	0	1.25

6173 7.15.6 Further work

6174 We now list the next steps towards obtaining longitudinal polarisation at the interaction point.

- 6175 (1) A harmonic closed-orbit spin matching algorithm must be implemented for the LHeC to try to correct
 6176 the remaining tilt of \hat{n}_0 and thereby increase the equilibrium polarisation.

6177 (2) Practical spin rotators must be designed and appropriate strong synchro-beta spin matching must be
6178 implemented. The design of the rotators and spin matching are closely linked. Some preliminary
6179 numerical investigations (below) show, as expected, that without this spin matching, little polarisation
6180 will be obtained.

6181 (3) If synchrotron sideband resonances are still overwhelming after items 1 and 2 are implemented, a
6182 scheme involving Siberian Snakes could be tried. Siberian Snakes are arrangements of magnets which
6183 manipulate spin on the design orbit so that the closed-orbit spin tune is independent of beam energy.
6184 Normally the spin tune is then $1/2$ and heuristic arguments suggest that the sidebands should be
6185 suppressed. However, the two standard schemes [657] either cause \hat{n}_0 to lie in the machine plane (just
6186 one snake) or ensure that it is vertically up in one half of the ring and vertically down in the other
6187 half (two snakes). In both cases Eq. 7.24 shows that P_{bk} vanishes. In principle, this problem can be
6188 overcome for two snakes by again appealing to Eq. 7.24 and having short strong dipoles in the half of
6189 the ring where \hat{n}_0 points vertically up and long weaker dipoles in the half of the ring where \hat{n}_0 points
6190 vertically down (or vice versa). Of course, the dipoles must be chosen so that the total bend angle is
6191 π in each half of the ring. Moreover, Eq. 7.24 shows that the pure Sokolov-Ternov polarisation would
6192 be much less than 92.4%. One version of this concept [656] uses a pair of rotators which together form
6193 a snake while a complementary snake is inserted diametrically opposite to the interaction point. Each
6194 rotator comprises interleaved strings of vertical and horizontal bends which not only rotate the spins
6195 from vertical to horizontal, but also bring the e^\pm beams down to the level of the proton beam and then
6196 up again. However, the use of short dipoles in the arcs increases the radiation losses.

6197 Note that because of the energy dependence of spin rotations in the dipoles, \hat{n}_0 is vertical in the
6198 arcs at just one energy. This concept has been tested with SLICKTRACK but in the absence of a
6199 strong synchro-beta spin match, the equilibrium polarisation is very small as expected. Nevertheless
6200 the effects of misalignments and of the tilt of \hat{n}_0 away from design energy, have been isolated by
6201 imposing an artificial spin match using standard facilities in SLICKTRACK. The snake in the arc has
6202 been represented as a thin element that has no influence on the orbital motion. Then it looks as if
6203 the synchrotron sidebands are indeed suppressed in the depolarisation associated with tilts of \hat{n}_0 . In
6204 contrast to the rotators in HERA, this kind of rotator allows only one helicity for electrons and one
6205 for positrons.

6206 (4) If a scheme can be found which delivers sufficient longitudinal polarisation, the effect of non-linear
6207 orbital motion, the effect of beam-beam forces and the effect of the magnetic fields of the detector
6208 must then be studied.

6209 7.15.7 Summary

6210 We have investigated the possibility of polarisation in the LHeC electron ring. At this stage of the work it
6211 appears that a polarisation of between 25 and 40% at 60 GeV can be reasonably aimed for, assuming the
6212 efficacy of harmonic closed-orbit spin matching. Attaining this degree of polarisation will require precision
6213 alignment of the magnets to better than $150\mu\text{m}$ rms, a challenging but achievable goal. The spin rotators
6214 necessary at the IP need to be properly spin matched to avoid additional depolarisation and this work is
6215 in progress. An interesting alternative involving the use of Siberian Snakes to try to avoid the depolarising
6216 synchrotron sideband resonances is being investigated. At present, this appears to potentially yield a similar
6217 degree of polarisation, at the expense of increased energy dissipation in the arcs arising from the required
6218 differences of the bending radii in the two halves of the machine.

7.16 Integration and machine protection issues

7.16.1 Space requirements

The integration of an additional electron accelerator into the LHC is a difficult task. Firstly, the LEP tunnel was designed for LEP and not for the LHC, which is now using up almost all space in the tunnel. It is not evident, how to place another accelerator into the limited space. Secondly, the LHC will run for several years, before the installation of a second machine can start. Meanwhile the tunnel will be irradiated and all installation work must proceed as fast as possible to limit the collective and individual doses. The activation after the planned high-luminosity-run of the LHC and after one month of cool-down is expected to be around $0.5...1\mu Sv/h$ [658] on the proton magnets and many times more at exposed positions. Moreover the time windows for installation will be short and other work for the LHC will be going on, maybe with higher priority. Nevertheless, with careful preparation and advanced installation schemes an electron accelerator can be fitted in.

For the installation of the LHC machine proper, all heavy equipment had to pass the UJ2, while entering the tunnel. There the equipment had to be moved from TI2, which comes in from the outside, to the transport zone of LHC, which is on the inner side of the ring. Clearly, applying this procedure to the installation of the LHeC everything above the cold dipoles has to be removed. The new access shafts and the smaller size of the equipment for the electron ring may render this operation unnecessary.

General The new electron accelerator will be partially in the existing tunnel and partially in specially excavated tunnel sections and behind the experiments in existing underground areas. The excavation work will need special access shafts in the neighborhood of the experiments from where the stub-tunnels can be driven. The connection to the existing LEP tunnels will be very difficult. The new tunnel enters with a very small grazing angle, which means over a considerable length. Very likely the proton installation will have to be removed while the last meters of the new tunnel is bored.

Figure 7.53 shows a typical cross section of the LHC tunnel, where the two machines are together. The LHC dipole dominates the picture. The transport zone is indicated at the right (inside of the ring). The cryogenic installations (QRL) and various pipes and cable trays are on the left. The dipole cross section shows two concentric circles. The larger circle corresponds to the largest extension at the re-enforcement rings and marks a very localized space restriction on a very long object. The inner circle is relevant for items shorter than about 10 m longitudinally. A hatched square above the dipole labeled 30 indicates the area, which was kept free in the beginning for an electron machine. Unfortunately, the center of this space is right above the proton beam. Any additional machine will, however, have to avoid the interaction points 1 and 5. In doing so additional length will be necessary, which can only be compensated for by shifting the electron machine in the arc about 60 cm to the inside (right), as indicated by the red square in Figure 7.53. The limited space for compensation puts a constraint on the extra length created by the bypasses. The transport zone will, however, be affected. This requires an unconventional way to mount the electron machine. Nevertheless, there is clearly space to place an electron ring into the LHC, for most of the arc. Figure 7.54 gives the impression that the tunnel for most of its length is not too occupied.

In the arc In Fig. 7.54 one sees the chain of superconducting magnets and in the far distances the *QRL Service Module* with its jumper, the cryogenic connection between the superconducting machine and the cryogenic distribution line. The service modules come always at the position of every second quadrupole and have a substantial length. The optics of the LHeC foresees no e-ring magnet at these positions. A photo of service modules in the workshop is shown in figure 7.55 (courtesy CERN) illustrating that the QRL extends substantially in the vertical direction above the LHC arc cryostat and cryo line. The picture 7.54, taken in sector 3, shows also the critical tunnel condition in this part of the machine. Clearly, heavy loads cannot be suspended from the tunnel ceiling. The limit is set to 100 kg per meter along the tunnel. The e-ring components have to rest on stands from the floor wherever possible. Normally there is enough space between the LHC dipoles and the QRL to place a vertical 10 cm quadratic or rectangular support. Alternatively a




Figure 7.53: Cross-section of the LHC tunnel with the original space holder for the electron beam installation directly above the LHC cryostat and the shifted new required space due to the additional bypass in IR1 and IR5 and the need to keep the overall circumference of the electron ring identical to that of the proton beams.

6266 steel arch bolted to the tunnel walls and resting on the floor can support the components from above. This
 6267 construction is required wherever the space for a stand is not available.

6268 The electron machine, though partially in the transport zone, will be high up in the tunnel. The transport
 6269 of cryogenic equipment may need the full height. Transports of that kind will only happen, when part of the
 6270 LHC are warmed up. This gives enough time to shift the electron ring to the outside by 30 cm, if the stands
 6271 are prepared for this operation. The outside movement causes also a small elongation of the inter-magnet
 6272 connections. This effect is locally so small that the expansion joints, required anyway, can accommodate it.
 6273 One could even think of moving large sections of the e-machine outwards in a semi-automatic way. Thus the
 6274 time to clear the transport path can be kept in the shadow of the warm-up and cool-down times.

6275 **Dump area** The most important space constraints for the electron machine are in the proton dump area,
 6276 the proton RF cavities, point 3, and in particular the collimator sections.

6277 Figure 7.56 [659] shows the situation at the dump kicker. The same area is also shown in a photo in Figure
 6278 7.57, while Figure 7.58 shows one of the outgoing dump-lines. The installation of the e-machine requires
 6279 the proper rerouting of cables (which might be damaged by radiation and in need of exchange anyhow),
 6280 eventually turning of pumps by 90 degrees or straight sections in the electron optics to bridge particularly
 6281 difficult stretches with a beam pipe only.

6282 **Point 4, proton RF** The Figures 7.59 [660] and 7.60 illustrate the situation at the point 4, where the
 6283 LHC RF is installed. Fortunately, the area is not very long. A short straight section could be created for
 6284 the electron ring. This would allow to pass the area with just a shielded beam pipe.



Figure 7.54: View of sector 4 showing the chain of superconducting magnets in the arc.



Figure 7.55: Sideview of a QRL service module with the jumper that extends vertically above the LHC cryostat and the cryogenic distribution line.




Figure 7.56: Dump kicker [659]




Figure 7.57: Dump kicker installation in IR6 for one of the two LHC proton rings.





Figure 7.58: Dump line of one of the LHC proton rings.



h

Figure 7.59: Schematic tunnel cross section with the LHC Proton Proton RF in point 4 [660].




Figure 7.60: Tight space restriction in Point 4 due to the LHC proton RF installation.

6285 **Cryolink in point 3** The geography around point 3 did not permit to place there a cryoplant. The
 6286 cryogenic cooling for the feedboxes is provided by a cryolink, as is shown in the figures 7.61 and 7.62. In
 6287 particular above the Q6 proton quadrupole changes have to be made. There are other interferences with the
 6288 cryogenics, as for example at the DFBA's (main feedboxes). An example is shown in figure 7.63. Eventually
 6289 the electron optics has to be adapted to allow the beampipe to pass the cables, which may have to be moved
 6290 a bit.

6291 **Long straight section 7** An extra air duct is mounted in the long straight section 7 (LSS7) as is indicated
 6292 in Fig. 7.64 (labelled Plenum de ventilation) avoiding the air pollution of the area above point 7. The duct
 6293 occupies the space planned for the electron machine. The air duct has to be replaced by a slightly different
 6294 construction mounted further outside (to the right in the figure). There are also air ducts at points 1 and 5,
 6295 but they are not an issue. The electron ring is passing behind the experiments in these points

6296 **Proton collimation** The areas around Point 3 (-62...+177m) and Point 7 (-149...+205m) [661] are heavily
 6297 used for the collimation of the proton beam. The high dose rate in the neighborhood of a collimator
 6298 makes special precautions for the installation of new components or the exchange of a collimator necessary.
 6299 Moreover, the collimator installation needs the full height of the tunnel. Hence, the electron ring installation
 6300 has to be suspended from the re-enforced tunnel roof. The electron machine components must be removable
 6301 and installable, easy and fast. The re-alignment must be well prepared and fast, possibly in a remote fashion.
 6302 It is uncommon to identify fast mounting and demounting as a major issue. However, with sufficient emphasis
 6303 during the R&D phase of the project, this problem can be solved.




Figure 7.61: The cryogenic connection in point 3

7.16.2 Impact of the synchrotron radiation on tunnel electronics

It is assumed that the main power converters of the LHC will have been moved out of the RRs because of the single event upsets, caused by proton losses.

The synchrotron radiation has to be intercepted at the source, as in all other electron accelerators. A few millimeter of lead are sufficient for the relatively low (critical) energies around 100 to 200 keV. The K-edge of lead is at 88 keV, the absorption coefficient is above 80/cm at this energy [662]. One centimeter of lead is sufficient to suppress 300 keV photons by a factor of 100. Detailed calculations of the optics will determine the amount of lead needed in the various places. The primary shielding needs an effective water cooling to avoid partial melting of the lead.

The electronics is placed below the proton magnets. Only backscattered photons with correspondingly lower energy will reach the electronics. If necessary, a few millimeter of extra shielding could be added here.

The risk for additional single event upsets due to synchrotron radiation is negligible.

7.16.3 Compatibility with the proton beam loss system

The proton beam loss monitoring system works very satisfactory. It has been designed to detect proton losses by observing secondaries at the outside of the LHC magnets. The sensors are ionization chambers. Excessive synchrotron radiation (SR) background will presumably trigger the system and dump the proton beam. The SR background at the monitors has to be reduced by careful shielding of either the monitors or the electron ring. Alternatively, the impact of the photon background can be reduced by using a new loss monitoring system which is based on coincidences (as was done elsewhere [663]).




Figure 7.62: The cryogenic connection in point 3 (grey tube passing above the two LHC proton beam vacuum tubes [yellow]).

6323 7.16.4 Space requirements for the electron dump

6324 The electron beam of the LHeC installation requires a dedicated dump section. Potential interference of
 6325 the losses during or after an electron beam dump with equipment of the LHC proton rings still needs to be
 6326 studied and a suitable space still needs to be found in the LHC tunnel.

6327 7.16.5 Protection of the p-machine against heavy electron losses

6328 The existing proton loss detectors are placed, as mentioned above, at the LHC magnets. The trigger threshold
 6329 requires certain number of detectors to be hit by a certain number of particles. The assumption is that the
 6330 particles come from the inside of the magnets and the particle density there is much higher. Electron losses,
 6331 creating a similar pattern in the proton loss detectors will result in a much lower particle density in the
 6332 superconducting coils. Hence, still tolerable electron losses will unnecessarily trigger the proton loss system
 6333 and dump the proton beam. The proton losses are kept at a low level by installing an advanced system
 6334 of collimators and masks. Fast changes of magnet currents, which will result in a beam loss, are detected.
 6335 A similar system is required for the electrons. An electron loss detection system, like the one mentioned
 6336 in Ref. [663], combined with the proton loss system can be used to identify the source of the observed loss
 6337 pattern and to minimize the electron losses by improved operation. It seems very optimistic to think of a
 6338 hardware discrimination system, which determines very fast the source of the loss and acts correspondingly.
 6339 Such a system could be envisaged only after several years of running.




Figure 7.63: A typical big current feed-box (DFBA) on top of (green) and next to (grey shafts with black power lines) the two proton beam pipes.

6340 7.16.6 How to combine the Machine Protection of both rings?

6341 The existing machine-protection system combines many different subsystems. The proton loss system, the
 6342 quench detection system, cryogenics, vacuum, access, and many other subsystems may signal a dangerous
 6343 situation. This requirement lead to a very modular architecture, which could be expanded to include the
 6344 electron accelerator.

6345 7.17 LHeC Injector for the Ring-Ring option

6346 7.17.1 Injector

6347 The LEP pre-injectors have been dismantled and the infrastructure re-used for the CLIC test facility CTF3.
 6348 The RF cavities that accelerated leptons in the SPS have been removed to reduce its impedance. Re-
 6349 installation of an injector chain similar to LEP's through the PS and SPS would be costly and potentially
 6350 limit the proton performance.

6351 The LHeC e-ring therefore requires new lepton injectors.

6352 In the 30 years from the design of the LEP injectors, there has been substantial progress in accelerator
 6353 technology. This is particularly true in the field of superconducting radio frequency technology which was
 6354 very successfully used for LEP2 on a large scale and which has been further developed for TESLA and the
 6355 ILC. It makes it feasible to design a very compact and efficient 10 GeV injector based on the principle of a
 6356 recirculating LINAC and to take advantage of the studies for ELFE at CERN [664].




Figure 7.64: Air-duct in LSS7 indicated by the box labelled 'Plenum de ventilation' [660].

7.17.2 Required performance

The main requirements for the LHeC ring-ring electron and positron injectors are summarized in Table 7.35.

Table 7.35: Main parameters for the LHeC RR injector

particle types	e^+, e^-
polarized	no
injection energy	$E_b = 10 \text{ GeV}$
bunch intensity	$2 \times 10^{10} e = 3.2 \text{ nC}$
pulse frequency	$\geq 5 / \text{s}$

Polarization is not required from the ring injectors. It would be very difficult to maintain the polarization during the acceleration in the main ring. Instead, polarization can be built up at top energy from synchrotron radiation.

The electron bunch intensity for nominal LHeC performance is 1.4×10^{10} . The target intensity for the injector is taken as 2×10^{10} which includes a safety factor and allows for losses at injection and during the ramp. Higher single-bunch intensities may be useful, with a smaller number of bunches, for the e-A mode of operation. LEP was operated with much higher bunch intensities up to 4×10^{11} limited by the transverse mode coupling instability (TMCI). The TMCI threshold current can be estimated from [665]

$$I_{th} = \frac{\omega_s E}{e \sum \beta k_{\perp}(\sigma_s)} \quad (7.33)$$




Figure 7.65: Layout of the LPI in 2000.

6367 where $\omega_s = 2\pi Q_s f_{\text{rev}}$ is the synchrotron frequency, e the elementary charge, E is the beam energy, β the
 6368 beta function value at the location of the impedance and k_{\perp} the loss factor which accounts for the transverse
 6369 impedance of the machine. LEP had a design injection energy of 20 GeV. It was raised to 22 GeV to increase
 6370 the TMCI threshold.

6371 The relatively low bunch intensity required for the LHeC allows for direct injection without accumulation
 6372 and for a lower injection energy compared to LEP. The LHeC transverse impedance will be similar to LEP,
 6373 with a smaller contribution from the reduced number of cavities and an increased impedance contribution
 6374 from the more compact beam-pipe cross-section. Lowering the beam energy results in weak bending fields
 6375 and loss of synchrotron radiation damping. A beam energy of a few GeV may still be tolerable for transverse
 6376 mode coupling but would not be practical for magnet stability and require strong wigglers to get a significant
 6377 radiation damping (otherwise this requires a minimum beam energy of the order of 10 GeV).

6378 A pulse frequency of on average 5 Hz is required, to fill the LHeC electron ring with 2808 bunches in
 6379 10 minutes.

6380 The injector requirements summarized in Table 7.35 are within the reach of proven technology and con-
 6381 cepts. An example is the FACET facility at SLAC which provides 2×10^{10} electrons of 23 GeV energy at
 6382 30 Hz repetition frequency [666].

6383 The intensities and repetition frequency required here match well with the performance of the LIL, the
 6384 first part of the LEP pre-injectors, which we reconsider here for the source, positron accumulation and pre-
 6385 acceleration to 0.6 GeV. For the acceleration to 10 GeV we propose a new, superconducting recirculating
 6386 LINAC.

6387 7.17.3 Source, accumulator and acceleration to 0.6 GeV

6388 Figure 7.65 shows the layout of the LPI (LEP Pre-Injector) as it was working in 2000. The LPI was composed
 6389 of the LIL (LEP Injector Linac) and the EPA (Electron Positron Accumulator).

6390 Table 7.36 gives the beam characteristics at the end of LIL.

Beam energy	200 to 700 MeV
Charge	5×10^8 to $2 \times 10^{10} e^-$ / pulse
Pulse length	10 to 40 ns (FWHM)
Repetition frequency	1 to 100 Hz
Beam sizes (rms)	3 mm

Table 7.36: LIL beam parameters.

6391

Table 7.37 gives the electron and positron beam parameters at the exit of EPA.

Energy	200 to 600 MeV
Charge	up to $4.5 \times 10^{11} e^\pm$
Intensity	up to 0.172 A
Number of bunches	1 to 8
Emittance	0.1 mm.mrad
Tune	$Q_x = 4.537, Q_y = 4.298$

Table 7.37: The electron and positron beam parameters at the exit of EPA.

6392

6393

6394

6395

6396

With 8 bunches in the EPA for a 1.14s cycle, the 2808 electron bunches required for the LHeC could be filled in 6.7min which is perfectly adequate. According to the original LEP injector design report [614, 667, 668] Vol.I, the cycle length for positrons is 11.22s which would allow the 2808 bunches to be filled in 66 minutes. We conclude that the LIL+EPA performance is fully adequate for the LHeC. A reduction of the cycle length for positrons would be useful to reduce the filling time.




Figure 7.66: LIL and EPA

6397

Timing considerations

6398

6399

6400

6401

6402

6403

6404

6405

EPA was planned for 1 to 8 bunches compatible with the LEP RF-frequency. The EPA circumference of 125.665 m corresponds to $t_{\text{rev}} = 419.173$ ns, which is 16.75×25 ns and would in theory allow for 16 bunches spaced by 25 ns as relevant for the LHeC. Injection in batches of 72 bunches as possible for protons into the LHC would require a five times larger damping ring which would be rather expensive.

EPA had an RF-frequency $f_{\text{RF}} = 19.0852$ MHz. It will be increased to 40 MHz to allow for a bunch spacing of 25 ns. For the injection into the LHC we propose a fast kicker system with a kicker rise-time below 25 ns. This conserves the dimensions of EPA and gives full flexibility to place the bunches into the LHeC electron ring as required to collide with the proton or ion bunches [636, 637].

6406

7.17.4 10 GeV injector

6407

6408

For the acceleration to 10 GeV we propose a re-circulating LINAC, designed as a downscaled, low energy version of the 25 GeV ELFE at CERN design [664] using modern ILC-type RF-technology.



Figure 7.67: Recirculator using 4 ILC modules.

6409

6410

A sketch of the proposed machine is shown in Fig. 7.67. The acceleration is provided by 4 RF-units of the ILC type, providing together 3.13 GV acceleration.

6411 The acceleration from 0.6 GeV to 10 GeV is achieved in three passages through the LINAC. This requires
 6412 only two re-circulation arcs which can be constructed in the horizontal plane. The maximum energy in the
 6413 last re-circulation arc is $10 - 3.13 = 6.87$ GeV.

6414 For a beam energy E and bending radius ρ , the energy loss U_0 by synchrotron radiation in the single
 6415 passage through a re-circulation arc is

$$U_0 = C_\gamma \frac{E^4}{\rho} \quad (7.34)$$

6416 where

$$C_\gamma = \frac{e^2}{3\epsilon_0} \frac{1}{(mc^2)^4} = 8.846 \times 10^{-5} \text{ m GeV}^{-3} .$$

6417 where e is the elementary charge and m the electron mass. The relative energy spread is increased by the
 6418 synchrotron radiation in a single passage by

$$\sigma_e = r_e c_f \frac{\gamma^{5/2}}{\rho} \quad (7.35)$$

6419 where r_e is the classical electron radius and

$$c_f = \frac{3}{2} \sqrt{\frac{55\pi}{27\sqrt{3}\alpha}} = 33.75 . \quad (7.36)$$

6420 A bending radius of $\rho = 2$ m at $E = 6.87$ GeV would result in an energy loss by recirculation of $U_0 = 98$ MeV
 6421 and an energy spread of 10^{-3} . This would both be tolerable, but require very strong superconducting 11 tesla
 6422 magnets for the 6.87 GeV recirculation.

6423 At this stage, we propose the use of warm 2 tesla magnets, resulting in a bending radius of $\rho = 11.5$ m
 6424 for the 6.87 GeV recirculation and $\rho = 6.2$ m for the 3.73 GeV recirculation. The values for the energy loss
 6425 and spread are listed in Table 7.38.

Table 7.38: Energy, bending field and radius, energy loss and energy spread in the recirculator magnets.

E GeV	B tesla	ρ m	U_0 MeV	σ_e
6.87	2	11.45	17.1	1.7×10^{-4}
3.73	2	6.23	2.8	7×10^{-5}

6426 To save space and allow for a single LINAC tunnel, we propose a dogbone-like shape for the recirculators
 6427 as shown in Fig. 7.67.

Chapter 8

Linac-Ring Collider

8.1 Basic Parameters and Configurations

8.1.1 General Considerations

A high-energy electron-proton collider can be realized by accelerating electrons (or positrons) in a linear accelerator (linac) to 60–140 GeV and colliding them with the 7-TeV protons circulating in the LHC. Except for the collision point and the surrounding interaction region, the tunnel and the infrastructure for such a linac are separate and fully decoupled from the LHC operation, from the LHC maintenance work, and from other LHC upgrades (e.g., HL-LHC and HE-LHC).

The technical developments required for this type of collider can both benefit from and be used for many future projects. In particular, to deliver a long or continuous beam pulse, as required for high luminosity, the linac must be based on superconducting (SC) radio frequency (RF) technology. The development and industrial production of its components can exploit synergies with numerous other advancing SC-RF projects around the world, such as the European XFEL at DESY, eRHIC, ESS, ILC, CEBAF upgrade, CESR-ERL, JLAMP, and the CERN HP-SPL.

For high luminosity operation at a beam energy of 50–70 GeV the linac should be operated in continuous wave (CW) mode, which restricts the maximum RF gradient through the associated cryogenics power, to a value of about 20 MV/m or less. In order to limit the active length of such a linac and to keep its construction and operating costs low, the linac should, and can, be recirculating. For the sake of energy efficiency and to limit the overall site power, while boosting the luminosity, the SC recirculating CW linac can be operated in energy-recovery (ER) mode.

Electron-beam energies higher than 70 GeV, e.g. 140 GeV, can be achieved by a pulsed SC linac, similar to the XFEL, ILC or SPL. In this case the accelerating gradient can be larger than for CW operation, i.e. above 30 MV/m, which minimizes the total length, but recirculation is no longer possible at this beam energy due to prohibitively high synchrotron-radiation energy losses in any return arc of reasonable dimension. As a consequence the standard energy recovery scheme using recirculation cannot be implemented and the luminosity of such a higher-energy lepton-hadron collider would be more than an order of magnitude lower than the one of the lower-energy CW ERL machine, at the same wall-plug power.

For a linac it is straightforward to deliver a 80–90% polarized electron beam.

The production of a sufficient number of positrons to deliver positron-proton collisions at a similar luminosity as for electron-proton collisions is challenging for a linac-ring collider¹ A conceivable path towards decent proton-positron luminosities would include a recycling of the spent positrons, together with the recovery of their energy.

The development of a CW SC recirculating energy-recovery linac (ERL) for LHeC would prepare the ground, the technology and the infrastructure for many possible future projects, e.g., for an International

¹A review of linac-ring type collider proposals can be found in Ref. [669].

6463 Linear Collider, for a Muon Collider², for a neutrino factory, or for a proton-driven plasma wake field
 6464 accelerator. A ring-linac LHeC would, therefore, promote any conceivable future high-energy physics project,
 6465 while pursuing an attractive forefront high-energy physics programme in its own right.

6466 8.1.2 ERL Performance and Layout

6467 Particle physics imposes the following performance requirements. The lepton beam energy should be 60
 6468 GeV or higher and the electron-proton luminosity of order $10^{33} \text{ cm}^{-2}\text{s}^{-1}$. Positron-proton collisions are
 6469 also required, with at least a few percent of the electron-proton luminosity. Since the LHeC should operate
 6470 simultaneously with LHC pp physics, it should not degrade the pp luminosity. Both electron and positron
 6471 beams should be polarized. Lastly, the detector acceptance should extend down to 1° or less. In addition,
 6472 the total electrical power for the lepton branch of the LHeC collider should stay below 100 MW.

6473 For round-beam collisions, the luminosity of the linac-ring collider [13] is written as

$$L = \frac{1}{4\pi e} \frac{N_{b,p}}{\epsilon_p} \frac{1}{\beta_p^*} I_e H_{hg} H_D, \quad (8.1)$$

6474 where e denotes the electron charge, $N_{b,p}$ the proton bunch population, β_p^* the proton IP beta function, I_e the
 6475 average electron beam current, H_{hg} the geometric loss factor arising from crossing angle and hourglass effect,
 6476 and H_D the disruption enhancement factor due to the electron pinch in collision, or luminosity reduction
 6477 factor from the anti-pinch in the case of positrons. In the above formula, it is assumed that the electron
 6478 bunch spacing is a multiple of the proton beam bunch spacing. The latter could be equal to 25, 50 or 75 ns,
 6479 without changing the luminosity value.

6480 The ratio $N_{b,p}/\epsilon_p$ is also called the proton beam brightness. Among other constraints, the LHC beam
 6481 brightness is limited by the proton-proton beam-beam limit. For the LHeC design we assume the brightness
 6482 value obtained for the ultimate bunch intensity, $N_{p,p} = 1.7 \times 10^{11}$, and the nominal proton beam emittance,
 6483 $\epsilon_p = 0.5 \text{ nm}$ ($\gamma\epsilon_p = 3.75 \mu\text{m}$). This corresponds to a total pp beam-beam tune shift of 0.01. More than two
 6484 times higher values have already been demonstrated, with good pp luminosity lifetime, during initial LHC
 6485 beam commissioning, indicating a potential for higher ep luminosity.

6486 To maximize the luminosity the proton IP beta function is chosen as 0.1 m. This is considerably smaller
 6487 than the 0.55 m for the pp collisions of the nominal LHC. The reduced beta function can be achieved by
 6488 reducing the free length between the IP and the first proton quadrupole (10 m instead of 23 m), and by
 6489 squeezing only one of the two proton beams, namely the one colliding with the leptons, which increases the
 6490 aperture available for this beam in the last quadrupoles. In addition, we assume that the final quadrupoles
 6491 could be based on Nb₃Sn superconductor technology instead of Nb-Ti. The critical field for Nb₃Sn is almost
 6492 two times higher than for Nb-Ti, at the same temperature and current density, allowing for correspondingly
 6493 larger aperture and higher quadrupole gradient. Nb₃Sn quadrupoles are presently under development for
 6494 the High-Luminosity LHC upgrade (HL-LHC).

6495 The geometric loss factor H_{hg} needs to be optimized as well. For round beams with $\sigma_{z,p} \gg \sigma_{z,e}$ (well
 6496 fulfilled for $\sigma_{z,p} \approx 7.55 \text{ cm}$, $\sigma_{z,e} \approx 300 \mu\text{m}$) and $\theta_c \ll 1$, it can be expressed as³

$$H_{hg} = \frac{\sqrt{\pi} z e^{z^2} \text{erfc}(z)}{S}, \quad (8.2)$$

6497 where

$$z \equiv 2 \frac{(\beta_e^*/\sigma_{z,p})(\epsilon_e/\epsilon_p)}{\sqrt{1 + (\epsilon_e/\epsilon_p)^2}} S$$

²The proposed Muon Collider heavily relies on SC recirculating linacs for muon acceleration as well as on a SC-linac proton driver.

³The derivation of this formula is similar to the one for the LHC in Ref. [670], with the difference that here the two beams have different emittances and IP beta functions, and the electron bunch length is neglected. Curves obtained with formula (8.2) were first reported in [671].




Figure 8.1: Geometric luminosity loss factor H_{hg} , (8.2), as a function of the total crossing angle

6498 and

$$S \equiv \sqrt{1 + \frac{\sigma_{x,p}^2 \theta_c^2}{8\sigma_p^{*2}}}.$$

6499 Luminosity loss from a crossing angle is avoided by head-on collisions. The luminosity loss from the hourglass
 6500 effect, due to the long proton bunches and potentially small electron beta functions, is kept small, thanks
 6501 to a “small” linac electron beam emittance of 0.43 nm ($\gamma\epsilon_e = 50 \mu\text{m}$). We note that the assumed electron-
 6502 beam emittance, though small when compared with a storage ring of comparable energy, is still very large
 6503 by linear-collider standards.

6504 The disruption enhancement factor for electron-proton collisions is about $H_D \approx 1.35$, according to
 6505 Guinea-Pig simulations [672] and a simple estimate based on the fact that the average rms size of the
 6506 electron beam during the collision approaches a value equal to $1/\sqrt{2}$ of the proton beam size. This additional
 6507 luminosity increase from disruption is not taken into account in the numbers given below. On the other
 6508 hand, for positron-proton collisions the disruption of the positrons leads to a significant luminosity reduction,
 6509 by roughly a factor $H_D \approx 0.3$, similar to the case of electron-electron collisions [673].

6510 The final parameter determining the luminosity is the average electron (or positron) beam current I_e . It
 6511 is closely tied to the total electrical power available (taken to be 100 MW).

6512 Crossing Angle and IR Layout

6513 The colliding electron and proton beams need to be separated by 7 cm at a distance of 10 m from the
 6514 IP in order to enter through separate holes in the first proton quadrupole magnet. This separation could
 6515 be achieved with a crossing angle of 7 mrad and crab cavities. The required crab voltage would, however,
 6516 need to be of order 200 MV, which is 20–30 times the voltage needed for pp crab crossing at the HL-LHC.
 6517 Therefore, crab crossing is not considered an option for the L-R LHeC. Without crab cavities, any crossing
 6518 angle should be smaller than 0.3 mrad, as is illustrated in Fig. 8.1. Such small a crossing angle is not useful,
 6519 compared with the 7 mrad angle required for the separation. The R-L interaction region (IR), therefore, uses
 6520 detector-integrated dipole fields around the collision point, to provide head-on ep collisions ($\theta_c = 0$ mrad)
 6521 and to separate the beams by the required amount. A dipole field of about 0.3 T over a length of ± 9 m
 6522 accomplishes these goals.

6523 The IR layout with separation dipoles and crossing angle is sketched in Fig. 8.2. Significant synchrotron
 6524 radiation, with 48 kW average power, and a critical photon energy of 0.7 MeV, is emitted in the dipole




Figure 8.2: Linac-ring interaction-region layout. Shown are the beam envelopes of 10σ (electrons) [solid blue] or 11σ (protons) [solid green], the same envelopes with an additional constant margin of 10 mm [dashed], the synchrotron-radiation fan [orange], the approximate location of the magnet coil between incoming protons and outgoing electron beam [black], and a “1 degree” line.

6525 fields. A large portion of this radiation is extracted through the electron and proton beam pipes. The SC
 6526 proton magnets can be protected against the radiation heat load by an absorber placed in front of the first
 6527 quadrupole and by a liner inside the beam pipe. Backscattering of synchrotron radiation into the detector
 6528 is minimized by shaping the surface of absorbers and by additional masking.

6529 The separation dipole fields modify, and enhance, the geometric acceptance of the detector. Figure 8.3
 6530 illustrates that scattered electrons with energies of 10–50 GeV might be detected at scattering angles down
 6531 to zero degrees.

6532 Electron Beam and the Case for Energy Recovery

6533 The electron-beam emittance and the electron IP beta function are not critical, since the proton beam size is
 6534 large by electron-beam standards (namely about $7\ \mu\text{m}$ rms compared with nm beam-sizes for linear colliders).
 6535 The most important parameter for high luminosity is the average beam current, I_e , which linearly enters
 6536 into the luminosity formula (8.1). In addition to the electron beam current, also the bunch spacing (which
 6537 should be a multiple of the LHC 25-ns proton spacing) and polarization (80–90% for the electrons) need
 6538 to be considered. Having pushed all other parameters in (8.1), Fig. 8.4 illustrates that an average electron
 6539 current of about 6.4 mA is required to reach the target luminosity of $10^{33}\ \text{cm}^{-2}\text{s}^{-1}$.

6540 For comparison, the CLIC main beam has a design average current of 0.01 mA [674], so that it falls
 6541 short by a factor 600 from the LHeC requirement. For other applications it has been proposed to raise the
 6542 CLIC beam power by lowering the accelerating gradient, raising the bunch charge by a factor of two, and
 6543 increasing the repetition rate up to three times, which raises the average beam current by a factor 6 to about
 6544 0.06 mA (this type of CLIC upgrade is described in [675]). This ultimate CLIC main beam current is still
 6545 a factor 100 below the LHeC target. On the other hand, the CLIC drive beam would have a sufficiently
 6546 high current, namely 30 mA, but at the low energy 2.37 GeV, which would not be useful for high-energy ep
 6547 physics. Due to this low energy, also the drive beam power is still a factor of 5 smaller than the one required
 6548 by LHeC. Finally, the ILC design current is about 0.04 mA [676], which also falls more than a factor 100
 6549 short of the goal.

6550 Fortunately, SC linacs can provide higher average current, e.g. by increasing the linac duty factor 10–100
 6551 times, or even running in continuous wave (CW) mode, at lower accelerating gradient. Example average




Figure 8.3: Example trajectories in the detector dipole fields for electrons of different energies and scattering angles, demonstrating an enhancement of the detector acceptance by the dipoles.




Figure 8.4: Linac-ring luminosity versus average electron beam current, according to (8.1).

currents for a few proposed designs illustrate this point: The CERN High-Power Superconducting Proton Linac aims at about 1.5 mA average current (with 50 Hz pulse rate) [677], the Cornell ERL design at 100 mA (cw) [678], and the eRHIC ERL at about 50 mA average current at 20 GeV beam energy (cw) [679]. All these designs are close to, or exceed, the LHeC requirements for average beam current and average beam power (6.4 mA at 60 GeV). It is worth noting that the JLAB UV/IR 4th Generation Light Source FEL is routinely operating with 10 mA average current (135 pC pulses at 75 MHz) [680]. The 10-mA current limit in the JLAB FEL arises from well understood beam break up [?] and significantly larger currents would be possible with suitably designed cavities. It is, therefore, believed that more than 6.4 mA for the LHeC ERL would be feasible.

The target LHeC IP electron-beam power is 384 MW. With a standard wall-plug-power to RF conversion efficiency around 50%, this would imply about 800 MW electrical power, far more than available. This highlights the need for energy recovery where the energy of the spent beam, after collision, is recuperated by returning the beam 180° out of phase through the same RF structure that had earlier been used for its acceleration, again with several recirculations. An energy recovery efficiency η_{ER} reduces the electrical power required for RF power generation at a given beam current by a factor $(1 - \eta_{ER})$. We need an efficiency η_{ER} above 90% or higher to reach the beam-current goal of 6.4 mA with less than 100 MW total electrical power.

The above arguments have given birth to the LHeC Energy Recovery Linac high-luminosity baseline design, which is being presented in this chapter.

Choice of RF Frequency

Two candidate RF frequencies exist for the SC linac. One possibility is operating at the ILC and XFEL RF frequency around 1.3 GHz, the other choosing a frequency of about 720 MHz, close to the RF frequencies of the CERN High-Power SPL, eRHIC, and the European Spallation Source (ESS).

The ILC frequency would have the advantage of synergy with the XFEL infrastructure, of profiting from the high gradients reached with ILC accelerating cavities, and of smaller structure size, which could reduce the amount of high-purity niobium needed by a factor 2 to 4.

Despite these advantages, the present LHeC baseline frequency is 720 MHz, or, more precisely, 721 MHz to be compatible with the LHC bunch spacing. The arguments in favor of this lower frequency are the following:

- A frequency of 721 MHz requires less cryo-power (about two times less than at 1.3 GHz according to BCS theory; the exact difference will depend on the residual resistance [681]).
- The lower frequency will facilitate the design and operation of high-power couplers [682], though the couplers might not be critical [683].
- The smaller number of cells per module (of similar length) at lower RF frequency is preferred with regard to trapped modes [684].
- The lower-frequency structures reduce beam-loading effects and transverse wake fields.
- The project can benefit from synergy with SPL, eRHIC and ESS.
- Other projects, e.g. low-emittance ERL light sources, can reduce the bunch charge by choosing a higher RF frequency. This is not the case for the LHeC, where the bunch distance is not determined by the RF frequency, but by the distance between proton bunches.

In case the cavity material costs at 721 MHz would turn out to be a major concern, they could be reduced by applying niobium as a thin film on a copper substrate, rather than using bulk niobium. Establishing the necessary cavity performance with thin-film coating will require further R&D. It is expected that the thin-film technology may also enhance the intrinsic cavity properties, e.g. increase the Q_0 value.

Linac RF parameters for both 720 MHz and 1.3 GHz in CW mode as well as for a pulsed 1.3-GHz option are compared in Table 8.1. The 721 MHz parameters are derived from eRHIC [685]. Pulsed-linac applications for LHeC are discussed in subsections 8.1.4 and 8.1.6.

	ERL 721 MHz	ERL 1.3 GHz	Pulsed
RF duty factor	CW	CW	0.05
RF frequency [GHz]	0.72	1.3	1.3
cavity length [m]	1	~1	~1
energy gain / cavity [MeV]	18	18	31.5
R/Q [1Ω in Linac def.]	450	1200	1200
Q_0 [10^{10}]	4.0	1	1
power loss stat. [W/cav.]	5	< 0.5	< 0.5
power loss RF [W/cav.]	18	27	< 10
“W per W” (1.8 K to RT)	700	700	700
power loss / GeV at RT [MW]	0.51–1.44	0.6–1.1	0.24
length / GeV [m] (filling=0.57)	97	97	56

Table 8.1: Linac RF parameters for two different RF frequencies and two modes of operation. The row “W to W” refers to the power needed at room temperature (RT) to cool a heat unit at 1.8 K. The numbers quoted for 721 MHz reflect the (measured) parameters of eRHIC prototype cavity BNL-I and an extrapolation to the improved cavity BNL-III [686]. The heat-load values at 18 MV/m indicated for 1.3 GHz have been extrapolated from [676]. The additional static heat loss depends on the cryomodule design and can be made small compared with the dynamic loss.

6598 ERL Electrical Site Power

6599 The cryopower for two 10-GeV accelerating SC linacs is 28.9 MW, assuming 23 W/m heat load at 1.8 K and
6600 18 MV/m cavity gradient and 700 “W per W” cryo efficiency as for the ILC. The RF power needed to control
6601 microphonics for the accelerating RF is estimated at 22.2 MW, considering that 10 kW/m RF power may
6602 be required, as for eRHIC, with 50% RF generation efficiency. The electrical power for the additional RF
6603 compensating the synchrotron-radiation energy loss is 24.1 MW, with an RF generation efficiency of 50%.
6604 The cryo power for the compensating RF is 2.1 MW, provided in additional 1.44 GeV linac sections, and
6605 the microphonics control for the compensating RF requires another 1.6 MW. In addition, with an injection
6606 energy of 50 MeV, 6.4 mA beam current, and as usual 50% efficiency, the electron injector consumes about
6607 6.4 MW. A further 3 MW is budgeted for the recirculation-arc magnets [687]. Together this gives a grand
6608 total of 88.3 MW electrical power, some 25% below the 100 MW limit. The LHeC ERL power budget is
6609 summarized in Table 8.2.

Item	Electrical Power [MW]
Main linac cryopower	18.0
Microphonics control	22.2
Extra RF to compensate SR losses	24.1 MW
Extra-RF cryopower	1.6
Electron injector	6.4
Arc magnets	3.0
Total	75.3

Table 8.2: ERL power budget.




Figure 8.5: LHeC ERL layout including dimensions.

ERL Configuration

The ERL configuration is depicted in Fig. 8.5. The shape, arc radius and number of passes have been optimized with respect to construction cost and with respect to synchrotron-radiation effects [688].

The ERL is of racetrack shape. A 500-MeV electron bunch coming from the injector is accelerated in each of the two 10-GeV SC linacs during three revolutions, after which it has obtained an energy of 60 GeV. The 60-GeV beam is focused and collided with the proton beam. It is then bent by 180° in the highest-energy arc beam line before it is sent back through the first linac, at a decelerating RF phase. After three revolutions with deceleration, re-converting the energy stored in the beam to RF energy, the beam energy is back at its original value of 500 MeV, and the beam is now disposed in a low-power 3.2-MW beam dump. A second, smaller (tune-up) dump could be installed behind the first linac.

Strictly speaking, with an injection energy into the first linac of 0.5 GeV, the energy gain in the two accelerating linacs need not be 10 GeV each, but about 9.92 GeV, in order to reach 60 GeV after three passages through each linac. Considering a rough value of 10 GeV means that we overestimate the electrical power required by about 1%.

Each arc contains three separate beam lines at energies of 10, 30 and 50 GeV on one side, and 20, 40 and 60 GeV on the other. Except for the highest energy level of 60 GeV, at which there is only one beam, in each of the other arc beam lines there always co-exist a decelerating and an accelerating beam. The effective arc radius of curvature is 1 km, with a dipole bending radius of 764 m [689].

The two straight sections accommodate the 1-km long SC accelerating linacs. In addition to the 1km linac section, there is an additional space of 290 m in each straight section of the racetrack. In one straight of the racetrack 260 m of this additional length is allocated for the electron final focus (plus matching and splitting), the residual 30 m on the other side of the same straight allows for combining the beam and matching the optics into the arc. In the second straight section of the racetrack the additional length of the straight sections houses the additional linacs for compensating the 1.88 GeV energy loss in the return arcs [690]. For the highest energy, 60 GeV, there is a single beam and the compensating RF (750 MV) can have the same frequency, 721 MHz, as in the main linac [690]. For the other energies, a higher harmonic RF

6636 system, e.g. at 1.442 GHz, can compensate the energy loss for both decelerating and accelerating beams,
 6637 which are 180° out of phase at 721 MHz. On one side of the second straight one must compensate a total
 6638 energy loss of about 907 MeV per particle (=750+148+9 MeV, corresponding to the energy loss at 60, 40
 6639 and 20 GeV, respectively), which should easily fit within a length of 170 m. On the other side one has to
 6640 compensate 409 MeV (=362+47 MeV), corresponding to SR energy losses at 50 and 30 GeV), for which a
 6641 length of 120 m is available.

6642 The total circumference of the ERL racetrack is chosen as 8.9 km, equal to one third of the LHC
 6643 circumference. This choice has the advantage that one could introduce ion-clearing gaps in the electron
 6644 beam which would match each other on successive revolutions (e.g. for efficient ion clearing in the linacs
 6645 that are shared by six different parts of the beam) and which would also always coincide with the same proton
 6646 bunch locations in the LHC, so that in the latter a given proton beam would either always collide or never
 6647 collide with the electrons [691]. Ion clearing may be necessary to suppress ion-driven beam instabilities. The
 6648 proposed implementation scheme would remove ions while minimizing the proton emittance growth which
 6649 could otherwise arise when encountering collisions only on some of the turns. In addition, this arrangement
 6650 can be useful for comparing the emittance growth of proton bunches which are colliding with the electrons
 6651 and those which are not.

6652 The length of individual components is as follows. The exact length of the 10-GeV linac is 1008 m. The
 6653 individual cavity length is taken to be 1 m. The optics consists of 56-m long FODO cells with 32 cavities.
 6654 The number of cavities per linac is 576. The linac cavity filling factor is 57.1%. The effective arc bending
 6655 radius is set to be 1000 m. The bending radius of the dipole magnets is 764 m, corresponding to a dipole
 6656 filling factor of 76.4% in the arcs. The longest SR compensation linac has a length of 84 m (replacing the
 6657 energy lost by SR at 60 GeV). Combiners and splitters between straights and arcs require about 20–30 m
 6658 space each. The electron final focus may have a length of 200–230 m.

6659 IP Parameters and Beam-Beam Effects

6660 Table 8.3 presents interaction-point (IP) parameters for the electron and proton beams.

	protons	electrons
beam energy [GeV]	7000	60
Lorentz factor γ	7460	117400
normalized emittance $\gamma\epsilon_{x,y}$ [μm]	3.75	50
geometric emittance $\epsilon_{x,y}$ [nm]	0.40	0.43
a IP beta function $\beta_{x,y}^*$ [m]	0.10	0.12
rms IP beam size $\sigma_{x,y}^*$ [μm]	7	7
initial rms IP beam divergence $\sigma_{x',y'}^*$ [μrad]	70	58
beam current [mA]	≥ 430	6.4
bunch spacing [ns]	25 or 50	(25 or) 50
bunch population [ns]	1.7×10^{11}	(1 or) 2×10^9

Table 8.3: IP beam parameters

6661 Due to the low charge of the electron bunch, the proton head-on beam-beam tune shift is tiny, namely
 6662 $\Delta Q_p = +0.0001$, which amounts to only about 1% of the LHC pp design tune shift (and is of opposite
 6663 sign). Therefore, the proton-beam tune spread induced by the ep collisions is negligible. In fact, the electron
 6664 beam acts like an electron lens and could conceivably increase the pp tune shift and luminosity, but only
 6665 by about 1%. Long-range beam-beam effects are equally insignificant for both electrons and protons, since
 6666 the detector-integrated dipoles separate the electron and proton bunches by about $36\sigma_p$ at the first parasitic
 6667 encounter, 3.75 m away from the IP.

6668 One further item to be looked at is the proton beam emittance growth. Past attempts at directly
6669 simulating the emittance growth from ep collisions were dominated by numerical noise from the finite number
6670 of macroparticles and could only set an upper bound [692], nevertheless indicating that the proton emittance
6671 growth due to the pinching electron beam might be acceptable for centered collisions. Proton emittance
6672 growth due to electron-beam position jitter and simultaneous pp collisions is another potential concern. For
6673 a 1σ offset between the electron and proton orbit at the IP, the proton bunch receives a deflection of about
6674 10 nrad (approximately $10^{-4}\sigma_{x',y'}^*$). Beam-beam simulations for LHC pp collisions have determined the
6675 acceptable level for random white-noise dipole excitation as $\Delta x/\sigma_x \leq 0.1\%$ [693]. This translates into a very
6676 relaxed electron-beam random orbit jitter tolerance of more than 1σ . The tolerance on the orbit jitter will
6677 then not be set by beam-beam effects, but by the luminosity loss resulting from off-center collisions, which,
6678 without disruption, scales as $\exp(-(\Delta x)^2/(4\sigma_{x,y}^*)^2)$. The random orbit jitter observed at the SLAC SLC had
6679 been of order $0.3\text{--}0.5\sigma$ [694, 695]. A 0.1σ offset at LHeC would reduce the luminosity by at most 0.3% , a
6680 0.3σ offset by 2.2% . Disruption further relaxes the tolerance.

6681 The strongest beam-beam effect is encountered by the electron beam, which is heavily disrupted. The
6682 electron disruption parameter is $D_{x,y} \equiv N_{b,p}r_e\sigma_{z,p}/(\gamma_e\sigma^{*2}) \approx 6$, and the “nominal disruption angle” $\theta_0 \equiv$
6683 $D\sigma^*/\sigma_{z,p} = N_{b,p}r_e/(\gamma_e\sigma^*)$ [696] is about $600 \mu\text{rad}$ (roughly $10\sigma_{x',y'}^*$), which is huge. Simulations show that
6684 the actual maximum angle of the disrupted electrons is less than half θ_0 .

6685 Figure 8.6 illustrates the emittance growth and optics-parameter change for the electron beam due to
6686 head-on collision with a “strong” proton bunch. The intrinsic emittance grows by only 15% , but there is a
6687 180% growth in the mismatch parameter “ B_{mag} ” (defined as $B_{\text{mag}} = (\beta\gamma_0 - 2\alpha\alpha_0 + \beta_0\gamma)/2$, where quantities
6688 with and without subindex “0” refer to the optics without and with collision, respectively. Without adjusting
6689 the extraction line optics to the parameters of the mismatched beam the emittance growth will be about
6690 200% . This would be acceptable since the arc and linac physical apertures have been determined assuming
6691 up to 300% emittance growth for the decelerating beam [689]. However, if the optics of the extraction line
6692 is rematched for the colliding electron beam (corresponding to an effective β^* of about 3 cm rather than the
6693 nominal 12 cm ; see Fig.8.6 bottom left), the net emittance growth can be much reduced, to only about 20% .
6694 The various optics parameters shown in Fig. 8.6 vary by no more than $10\text{--}20\%$ for beam-beam orbit offsets
6695 up to 1σ .

6696 Figure 8.7 presents the average electron deflection angle as a function of the beam-beam offset. The
6697 extraction channel for the electron beam must have sufficient aperture to accommodate both the larger
6698 emittance due to disruption and the average trajectory change due to off-center collisions.

6699 8.1.3 Polarization

6700 The electron beam can be produced from a polarized DC gun with about 90% polarization, and with,
6701 conservatively, $10\text{--}50 \mu\text{m}$ normalized emittance [697]. Spin-manipulation tools and measures for preserving
6702 polarization, like Wien filter and/or spin rotators, and polarimeters should be included in the optics design
6703 of the injector, the final focus, and the extraction line.

6704 As for the positrons, up to about 60% polarization can be achieved either with an undulator [698] or
6705 with a Compton-based e^+ source [699, 700]⁴.

6706 8.1.4 Pulsed Linacs

6707 For beam energies above about 140 GeV , due to the growing impact of synchrotron radiation, the construction
6708 of a single straight linac is cheaper than that of a recirculating linac [688]. Figure 8.8 shows the schematic of
6709 an LHeC collider based on a pulsed straight 140-GeV linac, including injector, final focus, and beam dump.
6710 The linac could be either of ILC type (1.3 GHz RF frequency) or operate at 721 MHz as the preferred ERL
6711 version. In both cases, ILC values are assumed for the cavity gradient (31.5 MV/m) and for the cavity
6712 unloaded Q value ($Q_0 = 10^{10}$). This type of linac would be extendable to ever higher beam energies and
6713 could conceivably later become part of a linear collider. In its basic, simplest and conventional version no

⁴The primary challenge for positrons is to produce them in sufficient number and with a small enough emittance.




Figure 8.6: Simulated evolution of the electron beam emittance (top left), mismatch factor B_{mag} (top right) beta function (bottom left) and alpha function (bottom right) during the collision with a proton bunch, as a function of distance from the IP.




Figure 8.7: Simulated electron horizontal center-of-mass deflection angle as a function of the horizontal beam-beam offset.




Figure 8.8: Pulsed single straight 140-GeV linac for higher-energy ep collisions.




Figure 8.9: Highest-energy high-luminosity ERL option based on two straight linacs and multiple 10-GeV energy-transfer beams [701].

6714 energy recovery is possible for this configuration, since it is impossible to bend the 140-GeV beam around.
 6715 The lack of energy recovery leads to significantly lower luminosity. For example, with 10 Hz repetition rate,
 6716 5 ms pulse length (longer than ILC), a geometric reduction factor $H_g = 0.94$ and $N_{b,e} = 1.5 \times 10^9$ per bunch,
 6717 the average electron current would be 0.27 mA and the luminosity $4 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1}$.

6718 The construction of the 140-GeV pulsed straight linac could be staged, e.g. so as to first feature a pulsed
 6719 linac at 60 GeV, which could also be used for γ - p/A collisions (see subsection 8.1.6). The linac length
 6720 decreases directly in proportion to the beam energy. For example, at 140-GeV the pulsed linac measures 7.9
 6721 km, while at 60 GeV its length would be 3.4 km. For a given constant wall-plug power, of 100 MW, both
 6722 the average electron current and the luminosity scale roughly inversely with the beam energy. At 60 GeV
 6723 the average electron current becomes 0.63 mA and the pulsed-linac luminosity, without any energy recovery,
 6724 would be more than $9 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1}$.

6725 8.1.5 Higher-Energy LHeC ERL Option

6726 The simple straight linac layout of Fig. 8.8 can be expanded as shown in Fig. 8.9 [701]. The main electron
 6727 beam propagates from the left to the right. In the first linac it gains about 150 GeV, then collides with
 6728 the hadron beam, and is then decelerated in the second linac. By transferring the RF energy back to the
 6729 first accelerating linac, with the help of multiple, e.g. 15, 10-GeV “energy-transfer beams,” a novel type
 6730 of energy recovery is realized without bending the spent beam. With two straight linacs facing each other
 6731 this configuration could easily be converted into a linear collider, or vice versa, pending on geometrical and
 6732 geographical constraints of the LHC site. As there are negligible synchrotron-radiation losses the energy
 6733 recovery could be more efficient than in the case of the 60-GeV recirculating linac. Such novel form of ERL
 6734 could push the LHeC luminosity to the $10^{35} \text{ cm}^{-2}\text{s}^{-1}$ level. In addition, it offers ample synergy with the
 6735 CLIC two-beam technology.

6736 8.1.6 γ - p/A Option

6737 In case of a (pulsed) linac without energy recovery the electron beam can be converted into a high-energy
 6738 photon beam, by backscattering off a laser pulse, as is illustrated in Fig. 8.10. The rms laser spot size at the
 6739 conversion point should be similar to the size of the electron beam at this location, that is $\sigma_\gamma \approx 10 \mu\text{m}$.




Figure 8.10: Schematic of γ - p/A collision; prior to the photon-hadron interaction point (IP), the electron beam is scattered off a several-J laser pulse at the conversion point (CP).

6740 With a laser wavelength around $\lambda_\gamma \approx 250$ nm ($E_{\gamma,0} \approx 5$ eV), obtained e.g. from a Nd:YAG laser with
 6741 frequency quadrupling, the Compton-scattering parameter x [702, 703],

$$x \approx 15.3 \left[\frac{E_{e,0}}{\text{TeV}} \right] \left[\frac{E_{\gamma,0}}{\text{eV}} \right], \quad (8.3)$$

6742 is close to the optimum value 4.8 for an electron energy of 60 GeV (for $x > 4.8$ high-energy photons get
 6743 lost due to the creation of e^+e^- pairs). The maximum energy of the Compton scattered photons is given by
 6744 $E_{\gamma,\text{max}} = x/(x+1)E_0$, which is larger than 80% of the initial electron-beam energy $E_{e,0}$, for our parameters.
 6745 The cross section and photon spectra depend on the longitudinal electron polarization λ_e and on the circular
 6746 laser polarization P_c . With proper orientation ($2\lambda_e P_c = -1$) the photon spectrum is concentrated near the
 6747 highest energy $E_{\gamma,\text{max}}$.

6748 The probability of scattering per individual electron is [704]

$$n_\gamma = 1 - \exp(-q) \quad (8.4)$$

6749 with

$$q = \frac{\sigma_c A}{E_{\gamma,0} 2\pi\sigma_\gamma^2}, \quad (8.5)$$

6750 where σ_c denotes the (polarized) Compton cross section and A the laser pulse energy. Using the formulae
 6751 in [705], the Compton cross section for $x = 4.8$ and $2\lambda_e P_c = -1$ is computed to be $\sigma_c = 3.28 \times 10^{-25}$ cm². The
 6752 pulse energy corresponding to $q = 1$, i.e. to a conversion efficiency of 65%, is estimated as $A \approx E_{\gamma,0} 2\pi\sigma_\gamma^2 / \sigma_c \approx$
 6753 16 J. To set this into perspective, for a $\gamma\gamma$ collider at the ILC, Ref. [706] considered a pulse energy of 9 J at
 6754 a four times longer wavelength of $\lambda \approx 1$ μ m.

6755 The energies of the leftover electrons after conversion extend from about 10 to 60 GeV. This spent
 6756 electron beam, with its enormous energy spread, must be safely extracted from the interaction region. The
 6757 detector-integrated dipole magnets will assist in this process. They will also move the scattered electrons
 6758 away from the interaction point. A beam dump for the high-energy photons should also be installed, behind
 6759 the downstream quadrupole channel.

6760 Figure 8.11 presents the photon energy spectrum after the conversion and the luminosity spectrum [707],
 6761 obtained from a simulation with the Monte-Carlo code CAIN [708].

6762 The much larger interaction-point spot size and the lower electron beam energy at the LHeC compared
 6763 with $\gamma\gamma$ collisions at a linear collider allow placing the conversion point at a much greater distance $\Delta s \approx$
 6764 $\beta^* \sim 0.1$ m from the interaction point, which could simplify the integration in the detector, and is also




Figure 8.11: Simulated example photon spectrum after the conversion point (left) and γ - p luminosity spectrum [707].

6765 necessary as otherwise, with e.g. a mm-distance between CP and IP, the conversion would take place inside
 6766 the proton bunch.

6767 To achieve the required laser pulse energy, external pulses can be stacked in a recirculating optical cavity.
 6768 For an electron bunch spacing of e.g. 200 ns, the path length of the recirculation could be 60m. A schematic
 6769 of a possible mirror system is sketched in Fig. 8.12 (adapted from [706]).

6770 8.1.7 Summary of Basic Parameters and Configurations

6771 The baseline 60-GeV ERL option presented here can provide a ep luminosity of $10^{33} \text{ cm}^{-2}\text{s}^{-1}$, at less than
 6772 100 MW total electrical power for the electron branch of the collider, and with less than 9 km circumference.
 6773 The 21 GV of SC-RF installation represents its main hardware component.

6774 A pulsed 140-GeV linac, without energy recovery, could achieve a luminosity of $1.4 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1}$, at
 6775 higher c.m. energy, again with less than 100 MW electrical power, and shorter than 9 km in length. The
 6776 pulsed linac can accommodate a γ - p/A option. An advanced, novel type of energy recovery, proposed for
 6777 the single straight high-energy linac case, includes a second decelerating linac, and multiple 10-GeV “energy-
 6778 transfer beams”. This type of collider could potentially reach luminosities of $10^{35} \text{ cm}^{-2}\text{s}^{-1}$.

6779 High polarization is possible for all linac-ring options. Beam-beam effects are benign, especially for the
 6780 proton beam, which should not be affected by the presence of the electron beam.

6781 Producing the required number of positrons needed for high-luminosity proton-positron collisions is the
 6782 main open challenge for a linac-ring LHeC. Recovery of the positrons together with their energy, as well as
 6783 fast transverse cooling schemes, are likely to be essential ingredients for any linac-based high-luminosity ep
 6784 collider involving positrons.

6785 8.2 Interaction region

6786 This section presents a first conceptual design of the LHeC linac-ring Interaction Region (IR). The merits of
 6787 the IR are a very low β^* of 0.1m with proton triplets as close as possible to the IP to minimize chromaticity.
 6788 Head-on proton-electron collisions are achieved by means of dipoles around the Interaction Point (IP). The
 6789 Nb₃Sn superconductor has been chosen for the proton triplets since it provides the largest gradient. If this
 6790 technology proves not feasible in the timescale of the LHeC a new design of the IR can be pursued using
 6791 standard technology.

6792 The main goal of this first design is to evaluate potential obstacles, decide on the needs of special
 6793 approaches for chromaticity correction and evaluate the impact of the IR synchrotron radiation.




Figure 8.12: Recirculating mirror arrangement providing a laser-pulse path length of 60 m for pulse stacking synchronously with the arriving electron bunches (adapted from [706]).

8.2.1 Layout

A crossing angle of 6.8 mrad between the non-colliding proton beams allows enough separation to place the proton triplets. Only the proton beam colliding with the electrons is focused. A possible configuration in IR2 could be to inject the electrons parallel to the LHC Beam 1 and collide them head-on with Beam 2, see Fig. 8.13. The signs of the separation and recombination dipoles (D1 and D2) have to be changed to allow for the large crossing angle at the IP. The new D1 has one aperture per beam and is 4.5 times stronger than the LHC design D1. The new D2 is 1.5 times stronger than the LHC design D2. Both dipoles feature about a 6 T field. The lengths of the nominal LHC D1 and D2 dipoles have been left unchanged, 23 m and 9 m, respectively. However the final IR design will need to incorporate a escape line for the neutral particles coming from the IP, probably requiring to split D1 into two parts separated by tens of meters.

Bending dipoles around the IP are used to make the electrons collide head-on with Beam2 and to safely extract the disrupted electron beam. The required field of these dipoles is determined by the L^* and the minimum separation of the electron and the focused beam at the first quadrupole (Q1). A 0.3 T field extending over 9 m allows for a beams separation of 0.07 m at the entry of Q1. This separation distance is compatible with mirror quadrupole designs using Nb₃Sn technology; see Section 9.1. The electron beam radiates 48 kW in the IR dipoles. A sketch of the 3 beams, the synchrotron radiation fan and the proton triplets is shown in Fig. 8.14.

8.2.2 Optics

Colliding proton optics

The colliding beam triplet starts at $L^*=10$ m from the IP. It consists of 3 quadrupoles with main parameters given in Table 8.4. The quadrupole aperture is computed as $11\max(\sigma_x, \sigma_y)+5$ mm. The 5 mm split into 1.5 mm for the beam pipe, 1.5 mm for mechanical tolerances and 2 mm for the closed orbit. The magnet parameters for the first two quadrupoles correspond to Nb₃Sn design described in Section 9.1. The total chromaticity from the two IP sides amounts to 960 units. The optics functions for the colliding beam are shown in Fig. 8.15

It was initially hoped that a compact Nb₃Sn triplet with $L^*=10$ m would allow for a normal chromaticity correction using the arc sextupoles. However after matching this triplet to the LHC and correcting linear




Figure 8.13: LHeC interaction region displaying the two proton beams and the electron beam trajectories with 5σ and 10σ envelopes.




Figure 8.14: LHeC interaction region with a schematic view of synchrotron radiation. Beam trajectories with 5σ and 10σ envelopes are shown. The parameters of the Q1 and Q2 quadrupole segments correspond to the Nb₃Sn half-aperture and single-aperture (with holes) quadrupole of Fig. 9.5.

Name	Gradient [T/m]	Length [m]	Radius [mm]	p1-p2 Sep. [mm]	“Radius” of Field-Free Hole [mm]
Q1	187	9	22	63	40
Q2	308	9	30	87	26
Q3	185	9	32	–	–

Table 8.4: Parameters of the proton triplet quadrupoles. The radius is computed as $11\max(\sigma_x, \sigma_y) + 5$ mm. For Q2 the hole “radius” describes the distance from the closest aperture. “p1-p2 Sep.” refers to the distance between the two proton beams at the entrance of the quadrupole.




Figure 8.15: Optics functions for main proton beam.




Figure 8.16: Chromatic beta-beating at $dp/p=0.001$.

6821 chromaticity the chromatic β -beating at $dp/p=0.001$ is about 100% (see Fig. 8.16). This is intolerable
 6822 regarding collimation and machine protection issues. Therefore a dedicated chromaticity correction scheme
 6823 has to be adopted. A large collection of studies exist showing the feasibility of correcting even larger
 6824 chromaticities in the LHC [709–711]. Other local chromatic correction approaches as [712, 713], where
 6825 quadrupole doublets are used to provide the strong focusing, could also be considered for the LHeC.

6826 Since LHeC anyhow requires a new dedicated chromaticity correction scheme, current NbTi technology
 6827 could be pursued instead of Nb₃Sn and the L^* could also be slightly increased. The same conceptual three-
 6828 beam crossing scheme as in Fig. 8.13 could be kept.

6829 To achieve L^* below 23 m requires a cantilever supported on a large mass as proposed for the CLIC
 6830 QD0 [714] to provide sub-nanometer stability at the IP. The LHeC vibration tolerances are much more
 6831 relaxed, being on the sub-micrometer level.

6832 Non-colliding proton optics

6833 The non-colliding beam has no triplet quadrupoles since it does not need to be focused. The LHC “alignment
 6834 optics” [621] was used as a starting point. Figure 8.17 shows the optics functions around the IP. The LHeC
 6835 IP longitudinal location can be chosen so as to completely avoid unwanted proton-proton collisions.

6836 The non-colliding proton beam travels through dedicated holes in the proton triplet quadrupoles, in Q1
 6837 together with the electron beam. The Q1 hole dimensions are determined by the electron beam, see below.
 6838 By contrast, the non-colliding proton beam travels alone through the first module of the Q2, requiring about
 6839 30 mm full aperture. No fields are assumed in these apertures but the possible residual fields could easily
 6840 be taken into account for the proton optics.

6841 Electron optics

6842 About 200 m are available between the exit of the linac and the IP, of which at least 40 m should be allocated
 6843 for matching, collimation and beam diagnostics. On the IP side, a free length L^* of 30 m is chosen to allow
 6844 for enough separation between the proton and the electron final focusing quadrupoles. Respecting these




Figure 8.17: Optics functions for the non-colliding proton beam without triplets.

length constraints three alternative final-focus optics for the electron beam have been developed. They are illustrated in Fig. 8.18.

The first optics is a round-beam electron optics with $\beta_{e;x,y}^* = 0.1$ m realized by a plain triplet without any sextupoles (Fig. 8.18 top picture). Upstream bending magnets complement the separation dipole so as to match the dispersion at the IP. The total length is 90 m. The SR power is small, about 25 kW on the incoming side of the IP, coming almost entirely from the separation dipole before the collision point. Without any chromatic correction the IP beam size increase for an rms relative momentum spread of 3×10^{-4} is about 10% horizontally and 21% vertically.

The second optics [715] employs a final quadrupole doublet with local chromatic correction using 4 sextupoles arranged according to the “compact final-focus” scheme proposed for future linear colliders [712] (Fig. 8.18 centre picture). It is optimized for unequal IP beta functions $\beta_{e;x}^* = 0.2$ m and $\beta_{e;y}^* = 0.05$, which are more suitable for a final doublet. In order to correct the chromaticity without generating unacceptable residual geometric aberrations a sufficiently large dispersion is needed across the final quadrupoles. Achieving this without introducing too much synchrotron radiation requires a longer system. The actual doublet optics has a length of 150 m. The SR power is 84 kW for the entire final focus on the incoming side of the IP, of which only about one third, 24 kW, is due to last separation dipole, with (at least) the same 24 kW again on the outgoing side. With this optics the IP beam size increase for an rms relative momentum spread of 3×10^{-4} is about 0.2% horizontally and 1.3% vertically, only due optical aberrations. However, synchrotron radiation increases the horizontal beam size by 138%. A future optimization of the location and strength of the bending magnets may improve this figure. The linear momentum bandwidths for the triplet and the doublet-local optics are compared in Fig. 8.19. The bandwidth was computed by MAD-X for a mono-chromatic beam with zero energy spread and varying offset from the design beam energy. These plots reveal the benefit of a chromatic correction.

The third optics [716] employs a final quadrupole doublet with a traditional modular scheme for the chromaticity correction (Fig. 8.18 bottom picture). This implies having dedicated sections for the correction of the horizontal and vertical chromaticities, thus requiring an even longer system. The β -functions at the




Figure 8.18: Electron final focus optics for the three different options: triplet (top), doublet with local chromatic correction (middle) and doublet with traditional chromatic correction (bottom).

Name	triplet			doublet - local			doublet - traditional		
	Gradient [T/m]	Length [m]	Radius [mm]	Gradient [T/m]	Length [m]	Radius [mm]	Gradient [T/m]	Length [m]	Radius [mm]
Q1	19.7	1.34	20	-19.1	1.1	36	-20.54	2.5	36
Q2	-38.8	1.18	32	17.7	1.1	37	20.31	2.5	35
Q3	-3.46	1.18	20	-14.7	1.1	41	-6.59	0.3	17
Q4	22.3	1.34	22	11.8	1.1	41	2.85	0.3	13

Table 8.5: Final electron quadrupole parameters for the triplet and the 2 doublet optics. The radius is computed as $11 \max(\sigma_x, \sigma_y) + 5$ mm. In the doublet solution the third and fourth quadrupole, Q3 and Q4, are located further upstream.

IP are $\beta_x^* = 0.2$ m and $\beta_y^* = 0.05$ m and the total length of the system is $L_{\text{FFS}} = 267.1$ m. The linear spot size is $\sigma_x^* = 9.23 \mu\text{m}$ and $\sigma_y^* = 4.61 \mu\text{m}$ and including nonlinear effects and after correction the beam sizes are $\sigma_x^* = 10.48 \mu\text{m}$ and $\sigma_y^* = 5.66 \mu\text{m}$. In other words, the beam size increases by a 10% in the horizontal plane and 25% in the vertical plane due to the nonlinearities. The compensation of the nonlinear effects is not optimum, because the strength of the dipoles was lowered in order to reduce the synchrotron-radiation effects, and the system was optimized by finding the minimum beam size while varying the dispersion in the sextupoles. The final radiated power due to synchrotron radiation is 49 kW. The radiation increases the horizontal spot size to $\sigma_x^* = 12.8 \mu\text{m}$.

The optics of the three systems are shown in Fig. 8.18, already matched to the exit of the linac. The electron focusing quadrupoles feature moderately low gradients as shown in Table 8.5.

The higher-order aberrations for the three optics were analyzed and minimized by applying a combination of the codes MAD-X/PTC and MAPCLASS [717] with and without the effect of synchrotron radiation. Table 8.2.2 summarizes the relative beam-size increase for the three optics together with an estimate of the luminosity loss based on the geometric overlap of unequal beams.

	triplet	doublet - local	doublet - traditional
$\Delta\sigma_x/\sigma_{x,0}$, no SR	9%	1.5%	5.75%
$\Delta\sigma_y/\sigma_{y,0}$, no SR	21%	1.7%	14.1%
$\Delta\sigma_x/\sigma_{x,0}$, with SR	10%	141%	39.3%
$\Delta\sigma_y/\sigma_{y,0}$, with SR	21%	1.9%	14.3%
$\Delta L/L_0$, with SR	-14%	-46%	-23%

Table 8.6: Relative IP electron beam-size increase with respect to the linear spot size $\sigma_{0,x(y)} = \sqrt{\epsilon_{x(y)}\beta_{x(y)}^*}$ considering a Gaussian momentum distribution of $\delta_{\text{rms}} = 3 \times 10^{-4}$. An indication of the luminosity loss due to the geometric overalpping of unequal proton and electron beams is also given.

The electrons share a hole with the non-colliding proton beam in the first half-quadrupole, Q1, and then travel through a dedicated hole in the cryostat of Q2. The common hole in the proton Q1 must have about 160 mm full horizontal aperture to allow for the varying separation between the electron and non-colliding proton orbit (120 mm) with the usual electron-beam aperture assumptions (± 20 mm). First design of mirror magnets for Q1 feature a field of 0.5 T in the electron beam pipe. This value is considered too large when compared to the IR dipole of 0.3 T, but new designs with active isolation or dedicated coils could considerably reduce this field. Migrating to NbTi technology would reduce this field too.




Figure 8.19: Relative increase in the linear beam size ($\sqrt{\beta}$) as a function of beam energy error for the triplet and doublet-local options, as computed by MAD-X.

6892 Spent electron beam

6893 The electromagnetic field of the proton beam during the collision provides extra focusing for the electron
 6894 beam. This increases the divergence of the spent electrons. Figure 8.20 shows the horizontal distribution
 6895 of the electrons at 10 m from the IP (entry of Q1) as computed by GuineaPig [718]. The contribution of
 6896 dispersion and energy spread to the transverse size of the exiting collided beam can be neglected. Therefore,
 6897 it is possible to linearly scale the sigmas at 10 m to estimate both the horizontal and vertical sigmas at any
 6898 other longitudinal location. The simulation used 10^5 particles. No particles are observed beyond 4.5 mm
 6899 from the beam centroid at 10 m from the IP and beyond 9 mm at 20 m. A radial aperture of 10 mm has
 6900 been reserved for the beam size at the incoming electron Q1 hole. The same value of 10 mm seem to be
 6901 enough to also host the spent electron beams, although it might be worth to allocate more aperture margin
 6902 in the last block of Q1.

6903 8.2.3 Modifications for γp or γ -A

6904 The electron beam can be converted into photons by Compton scattering off a high-power laser pulse, as
 6905 discussed Section 8.1.6. For this option a laser path and high-finesse optical cavities must be integrated into
 6906 the interaction region. A multiple mirror arrangement has been sketched in Fig. 8.12. The 0.3-T dipole field
 6907 after the (now) γ -p interaction point will help to separate the Compton-scattered spent electron beam from
 6908 the high-energy photons. The high-energy photons propagate straight into the direction of the incoming
 6909 proton beam through the main openings of Q1 and Q2, while the spent electrons will be extracted through
 6910 the low-field exit holes shared with the non-colliding proton beam, as for electron-proton collisions.

6911 8.2.4 Synchrotron radiation and absorbers

6912 Introduction

6913 The synchrotron radiation (SR) in the linac-ring interaction region has been analyzed by three different
 6914 approaches. The SR was simulated using a program made with the Geant4 (G4) toolkit. In addition, a cross
 6915 check of the total power and average critical energy was done in IRSYN, a Monte Carlo simulation package
 6916 written by R. Appleby [622]. A final cross check of the radiated power has been performed using an analytic
 6917 method. The latter two checks confirmed the results obtained from G4. The G4 program uses Monte Carlo
 6918 methods to create the desired Gaussian spatial and angular distributions of an electron beam. This electron
 6919 beam distribution is then transported through a “vacuum system,” including the magnetic fields for the
 6920 separator dipoles. In a non-zero magnetic field SR is generated using the appropriate G4 process classes.




Figure 8.20: Distribution of the spent electron beam at 10 m from the IP. The Gaussian and rms sigmas are shown on the plot.

6921 The position, direction, and energy of each photon emitted is written as ntuples at user defined longitudinal
 6922 positions (Z values). These ntuples are then used to analyze the SR fan as it evolves in Z . The latter
 6923 analysis was done primarily through MATLAB scripts.

6924 This section uses the following conventions. The electron beam is being referred to as *the beam* and the
 6925 proton beams will be called either the interacting or non interacting proton beams. The (electron) beam
 6926 propagates in the $-Z$ direction and the interacting proton beam propagates in the $+Z$ direction. At the
 6927 collision point both beams propagate up the straight Z (or $-Z$) direction. A right-handed coordinate system
 6928 is used where the X axis is horizontal and the Y axis vertical. The beam centroid always remains in the
 6929 $Y = 0$ plane. The *angle of the beam* will be used to refer to the angle between the beam centroid's direction
 6930 and the Z axis, in the $Y = 0$ plane. This angle is defined such that the beam propagates in the $-X$ direction
 6931 when it passes through the dipole field as it moves along Z .

6932 The SR fan's extension in the horizontal direction is determined by the angle of the beam at the entrance
 6933 of the upstream separator dipole. Because the direction of the photons is parallel to the direction of the
 6934 electron from which it is emitted, the angle of the beam and the X -distance to the interacting proton beam
 6935 at the Z location of the last proton quadrupole are both greatest for photons generated at the entrance of
 6936 the upstream separator dipole and, therefore, this angle defines one of the edges of the synchrotron fan on
 6937 the absorber in front of the proton quadrupole. The other edge is defined by the crossing angle, which is
 6938 zero for the linac-ring option. The S shaped trajectory of the beam means that the smallest angle of the
 6939 beam will be reached at the IP. Therefore, the photons emitted at this point will move exactly along the Z
 6940 axis. This defines the other edge of the fan in the horizontal direction.

6941 The SR fan's extent in the vertical direction is determined by the beta function and angular spread of
 6942 the beam. The beta function along with the emittance defines the local rms beam size. The vertical rms
 6943 beam size characterizes the range of Y positions at which photons are emitted. Possibly more importantly,
 6944 the vertical angular spread defines the angle between the velocity vector of these photons and the Z axis.
 6945 Both of these dependencies are functions of Z . Similar effects also affect the horizontal extension of the SR

6946 fan, however, in the horizontal plane they are of second order when compared to the horizontal deflection
 6947 angle in the strong dipole field.

6948 The number density distribution of the SR fan is inferred from the simulations. The number density at
 6949 the location of the absorber is highest in the region between the two interacting beams. This is due to the
 6950 S shaped trajectory of the beam.

6951 Parameters

6952 The parameters for the Linac Ring option are listed in Table 8.7. The separation refers to the displacement
 6953 between the two interacting beams at the face of the proton triplet.

Characteristic	Value
Electron Energy [GeV]	60
Electron Current [mA]	6.6
Crossing Angle [mrad]	0
Absorber Position [m]	-9
Dipole Field [T]	0.3
Separation [mm]	75
γ/s	1.37×10^{18}

Table 8.7: LR: Parameters

6954 The energy, current, and crossing angle (θ_c) are the common values used in all LR calculations. The B
 6955 value refers to the constant dipole field created throughout the two dipole magnets in the IR. The direction
 6956 of this field is opposite on either side of the IP. The field is chosen such that 75 mm of separation is reached
 6957 by the face of the proton triplet. This separation was chosen based on S. Russenschuck's SC quadrupole
 6958 design [623]. The separation between the interacting beams can be increased by raising the constant dipole
 6959 field however for a dipole magnet $P_{SR} \propto |B^2|$ [624], therefore an optimization of the design would need to
 6960 be discussed. The chosen parameters give a flux of 1.37×10^{18} photons per second at $Z = -9$ m.

6961 Power and Critical Energy

6962 Table 8.8 shows the power of the SR produced in the IR along with the critical energy. This is followed by
 6963 the total power produced in the IR and the critical energy. Since the G4 simulations utilize Monte Carlo,
 6964 multiple runs were used to provide a standard error. This only caused fluctuations in the power since the
 6965 critical energy is static for a constant field and constant energy.

Element	Power [kW]	Critical Energy [keV]
DL	24.4 +/- 0.1	718
DR	24.4 +/- 0.1	718
Total	48.8 +/- 0.1	718

Table 8.8: LR: Power and Critical Energies as calculated with Geant4.

6966 These magnets have strong fields and therefore produce high critical energies and a substantial amount
 6967 of power. Although the power is similar to that of the RR design the critical energy is much larger. This
 6968 comes from the linear dependence of critical energy on magnetic field (*i.e.* $E_c \propto B$) [625]. With the dipole
 6969 field in the LR case being an order of magnitude larger than the dipole fields in the RR case the critical
 6970 energies from the dipole magnets are also an order of magnitude larger in the LR case.

6971 **Comparison**

6972 The IRSYN cross check of the power and critical energies is shown in Table 8.9. This comparison was done
 6973 for the total power and the critical energy.

	Power [kW]		Critical Energy [keV]	
	Geant4	IRSYN	Geant4	IRSYN
Total	48.8 +/- 0.1	48.8	718	718

Table 8.9: LR: Geant4 and IRSYN comparison.

6974 A third cross check to the Geant4 simulations was made for the power as shown in Table 8.10. This was
 6975 done using an analytic method for calculating power in dipole magnets [624].

	Power [kW]	
Element	Geant4	Analytic
DL	24.4 +/- 0.1	24.4
DR	24.4 +/- 0.1	24.4
Total/Avg	48.8 +/- 0.1	48.8

Table 8.10: LR: Geant4 and Analytic method comparison.

6976 **Number Density and Envelopes**




Figure 8.21: LR: Number Density of photons Growth in Z direction.

6977 The number density of photons at different Z values is shown in Figure 8.21. Each graph displays the
 6978 density of photons in the $Z = Z_o$ plane for various values of Z_o . The first three graphs give the growth

6979 of the SR fan inside the detector area. This is crucial for determining the dimensions of the beam pipe
 6980 inside the detector area. Since the fan grows asymmetrically in the $-Z$ direction an asymmetric elliptical
 6981 cone shaped beam pipe will minimize these dimensions, allowing the tracking to be placed as close to the
 6982 beam as possible. The horizontal extension of the fan in the LR option is larger than in the RR case. This
 6983 is due to the large angle of the beam at the entrance of the upstream separator dipole. As mentioned in
 6984 the introduction this angle defines the fans extension, and in the LR case this angle is the largest, hence the
 6985 largest fan. The number density of this fan appears as expected, with the highest density between the two
 6986 beams at the absorber.




Figure 8.22: LR: Beam Envelopes in Z direction.

6987 In Figure 8.21 the distribution was given at various Z values however a continuous envelope distribution is
 6988 also important to see everything at once. This can be seen in Figure 8.22, where the beam and fan envelopes
 6989 are shown in the $Y = 0$ plane. This makes it clear that the fan is antisymmetric which comes from the S
 6990 shape of the electron beam as previously mentioned.

6991 Absorber

6992 The photon distribution on the absorber surface is crucial. The distribution decides how the absorber must
 6993 be shaped. The shape of the absorber in addition to the distribution on the surface then decides how
 6994 much SR is backscattered into the detector region. In HERA backscattered SR was a significant source of
 6995 background that required careful attention [626]. Looking at Figure 8.23 it is shown that for the LR option
 6996 35.15 kW of power from the SR light will fall on the face of the absorber which is 73% of the total power.
 6997 This gives a general idea of the amount of power that will be absorbed. However, backscattering and IR
 6998 photons will lower the percent that is actually absorbed.

6999 **Proton Triplet:** The super conducting final focusing triplet for the protons needs to be protected from
 7000 radiation by the absorber. Some of the radiation produced upstream of the absorber however will either pass
 7001 through the absorber or pass through the apertures for the two interacting beams. This is most concerning
 7002 for the interacting proton beam aperture which will have the superconducting coils. A rough upper bound




Figure 8.23: LR: Photon distribution on the Absorber Surface.

7003 for the amount of power the coils can absorb before quenching is 100 W [627]. There is approximately 2 kW
 7004 entering into the interacting proton beam aperture as is shown in Figure 8.23. This doesn't mean that all
 7005 this power will hit the coils but simulations need to be made to determine how much of this will hit the coils.
 7006 The amount of power that will pass through the absorber (0.25 W) can be disregarded as it is not enough
 7007 to cause any significant effects. The main source of power moving downstream of the absorber will be the
 7008 photons passing through the beams aperture. This was approximately 11 kW as can be seen from Figure
 7009 8.23. Most of this radiation can be absorbed in a secondary absorber placed after the first downstream proton
 7010 quadrupole. Overall protecting the proton triplet is important and although the absorber will minimize the
 7011 radiation continuing downstream this needs to be studied in depth.

7012 **Beamstrahlung** The beamstrahlung photons travel parallel to the proton beam until the entrance of D1
 7013 without impacting the triplets. Figure 8.24 shows the transverse and energy distributions of the beamstrahlung
 7014 photons at the entry of D1 as computed with Guineapig [718]. The maximum photon energy is about 20 MeV
 7015 the average photon energy is 0.4 MeV. The beamstrahlung power is 980 W. D1 has to be designed to properly
 7016 dispose the neutral debris from the IP. Splitting D1 into two parts could allow an escape line for the neutral
 7017 particles.

7018 **Backscattering** Another G4 program was written to simulate the backscattering of photons into the
 7019 detector region. The ntuple with the photon information written at the absorber surface is used as the
 7020 input for this program. An absorber geometry made of copper is described, and general physics processes
 7021 are set up. A detector volume is then described and set to record the information of all the photons which
 7022 enter in an ntuple. The first step in minimizing the backscattering was to optimize the absorber shape.
 7023 Although the simulation didn't include a beam pipe the backscattering for different absorber geometries was
 7024 compared against one another to find a minimum. The most basic shape was a block of copper that had
 7025 cylinders removed for the interacting beams. This was used as a benchmark to see the maximum possible
 7026 backscattering. In HERA a wedge shape was used for heat dissipation and minimizing backscattering [626].
 7027 The profile of this geometry in the YZ plane is shown in Figure 8.25. It was found that this is the optimum




Figure 8.24: Beamstrahlung photons at the entrance of D1.

7028 shape for the absorber. The reason for this is that a backscattered electron would have to have its
 7029 velocity vector be almost parallel to the wedge surface to escape from the wedge and therefore it works as
 7030 a trap. One can be seen from Table 8.11 utilizing the wedge shaped absorber decreased the backscattered
 7031 power by a factor of 4. The energy distribution for the backscattered photons can be seen in Figure 8.26.




Figure 8.25: LR: Absorber Dimensions.




Figure 8.26: LR: Backscattered Energy Distribution.

7032 After the absorber was optimized it was possible to set up a beam pipe geometry. An asymmetric elliptical
 7033 cone beam pipe geometry made of beryllium was used since it would minimize the necessary size of the beam
 7034 pipe as previously mentioned. The next step was to place the lead shield and masks inside this beam pipe.
 7035 To determine placement a simulation was run with just the beam pipe. Then it was recorded where each
 7036 backscattered photon would hit the beam pipe in Z. A histogram of this data was made as shown in Figure
 7037 8.27. This determined that the shield should be placed in the Z region ranging from -8 m until the absorber
 7038 (-9 m). The masks were then placed at -8.9 m and -8.3 m. This decreased the backscattered power by a
 7039 factor of 40 as can be seen from Table 8.11. Overall there is still more optimization that can occur with this
 7040 placement.

Absorber Type	Power [W]
Flat	645.9
Wedge	159.1
Wedge & Mask/Shield	4.3

Table 8.11: LR: Power deposition due to Backscattered photons.

7041 Cross sections of the beam pipe in the $Y = 0$ and $X = 0$ planes with the shields and masks included can
 7042 be seen in Figure 8.28.

7043 8.3 Linac Lattice and Impedance

7044 8.3.1 Overall Layout

7045 The proposed layout of the recirculating linear accelerator complex (RLA) is illustrated schematically in
 7046 Fig. 8.29. It consists of the following components:




Figure 8.27: LR: Backscattered Photons Exiting the Beam Pipe.




Figure 8.28: LR: Beampipe Cross Sections.

7047

- A 0.5 GeV injector with an injection chicane.

7048

- A pair of 721.44MHz SCRF linacs. Each linac is one kilometer long with an energy gain 10GeV per pass.

7049




Figure 8.29: The schematic layout of the recirculating linear accelerator complex.

7050

- Six 180° arcs. Each arc has a radius of one kilometer.

7051

- For each arc one re-accelerating station that compensates the synchrotron radiation emitted in this arc.

7052

7053

- A switching station at the beginning and end of each linac to combine the beams from different arcs and to distribute them over different arcs.

7054

7055

- An extraction dump at 0.5 GeV.

7056

After injection, the beam makes three passes through the linacs before it collides with the LHC beam.

7057

The beam will then perform three additional turns in which the beam energy is almost completely extracted.

7058

The size of the complex is chosen such that each turn has the same length and that three turns correspond

7059

to the LHC circumference. This choice is motivated by the following considerations:

7060

- To avoid the build-up of a significant ion density in the accelerator complex, clearing gaps may be required in the beam.

7061

7062

- The longitudinal position of these gaps must coincide for each of the six turns that a beam performs. This requires that the turns have the same length.

7063

7064

- Due to the gaps some LHC bunches will collide with an electron bunch but some will not. It is advantageous to have each LHC bunch either always collide with an electron bunch or to never collide. The choice of length for one turn in the RLA allows to achieve this.

7065

7066

7067

Some key beam parameters are given in table 8.12.

7068

8.3.2 Linac Layout and Lattice

7069

The key element of the transverse beam dynamics in a multi-pass recirculating linac is an appropriate choice

7070

of multi-pass linac optics. The focusing strength of the quadrupoles along the linac needs to be set such

Parameter	Symbol	Value
Particles per bunch	N	$2 \cdot 10^9$
Initial normalised transverse emittance	ϵ_x, ϵ_y	$30\mu\text{m}$
Normalised transverse emittance at IP	ϵ_x, ϵ_y	$50\mu\text{m}$
Bunch length	σ_z	$600\mu\text{m}$

Table 8.12: Key beam parameters. It should be noted that normalised emittances are used throughout.

7071 that one can transport the beam at each pass. Obviously, one would like to optimize the focusing profile to
7072 accommodate a large number of passes through the RLA. In addition, the requirement of energy recovery
7073 puts a constraint on the exit/entrance Twiss functions for the two linacs. As a baseline we have chosen a
7074 FODO lattice with a phase advance of 130° for the beam that passes with the lowest energy and a quadrupole
7075 spacing of 28m [719]. Alternative choices are possible. An example is an optics that avoids any quadrupole
7076 in the linacs [720].

7077 Linac Module Layout

7078 The linac consists of a series of units, each consisting of two cryomodules and one quadrupole pack. We
7079 consider one possible configuration for the 10-GeV linac, containing 36×2 cryomodules with an RF gradient
7080 of 18 MV/m. This design is slightly different from the one described in the RF section later, which uses fewer
7081 cavities per linac at a higher gradient; in this case also the modules are longer. However, the conclusions on
7082 the beam stability do not change with these small differences. In the simulations, each cryomodule is 12.8 m
7083 and contains eight 1m-long accelerating cavities, which allows 1.6 m per cavity unit, which leaves little extra
7084 space for interconnects between cavities, with implications on the cavity design. The interconnect between
7085 two adjacent cryomodules is 0.8 m long. The quadrupole pack is 1.6m long, including the interconnects to
7086 the adjacent cryomodules. The whole unit is 28m long.

7087 Each quadrupole pack contains a quadrupole, a beam position monitor and a vertical and horizontal
7088 dipole corrector, see section 2.9.

7089 Linac Optics

7090 The linac consists of 36 units with a total length of 1008 m. In the first linac, the strength of the quadrupoles
7091 has been chosen to provide a phase advance per cell of 130° for the beam in its first turn. In the second
7092 linac, the strength has been set to provide a phase advance of 130° for the last turn of the beam. The initial
7093 Twiss parameters of the beam and the return arcs are optimised to minimise the beta-functions of the beams
7094 in the following passages. The criterion used has been to minimise the integral

$$\int_0^L \frac{\beta}{E} ds \quad (8.6)$$

7095 Single bunch transverse wakefield effects and multi-bunch effects between bunches that have been injected
7096 shortly after each other are proportional to this integral [721]. The final solution is shown in Fig. 8.30. A
7097 significant beta-beating can be observed due to the weak focusing for the higher energy beams.

7098 Return Arc Optics

7099 At the ends of each linac the beams need to be directed into the appropriate energy-dependent arcs for
7100 recirculation. Each bunch will pass each arc twice, once when it is accelerated before the collision and once
7101 when it is decelerated after the collision. The only exception is the arc at highest energy that is passed
7102 only once. For practical reasons, horizontal rather than vertical beam separation was chosen. Rather than
7103 suppressing the horizontal dispersion created by the spreader, the horizontal dispersion can be smoothly
7104 matched to that of the arc, which results in a very compact, single dipole, spreader/recombiner system.




Figure 8.30: Beta-functions in the first linac. On the top, the beta-functions of the six different beam passages in the first linac are shown. On the bottom, the beta-function as seen by the beam during its stay in the linacs are shown.

turn no	E [GeV]	ΔE [MeV]	σ_E/E [%]
1	10.4	0.7	0.00036
2	20.3	9.9	0.0019
3	30.3	48.5	0.0053
4	40.2	151	0.011
5	50.1	365	0.020
6	60.5	751	0.033
7	50.1	365	0.044
8	40.2	151	0.056
9	30.3	48.5	0.074
10	20.3	9.9	0.11
11	10.4	0.7	0.216
dump	0.5	0.0	4.53

Table 8.13: Energy loss due to synchrotron radiation in the arcs as a function of the arc number. The integrated energy spread induced by synchrotron radiation is also shown.

7105 The initial choice of large arc radius (1 km) was dictated by limiting energy loss due to synchrotron
7106 radiation at top energy (60.5 GeV) to less than 1%. However other adverse effects of synchrotron
7107 on beam phase-space such as cumulative emittance and momentum growth due to quantum excitations
7108 are of paramount importance for a high luminosity collider that requires normalized emittance of 50 mm
7109 mrad. Energy losses from resistive wall and cfrom oherent synchrotron radiation have both been shown to
7110 be negligible compared with the energy loss due to incoherent synchrotron radiation [720].

7111 Three different arc designs have been developed [719]. In the design for the lowest energy turns, the beta-
7112 functions are kept small in order to limit the required vacuum chamber size and consequently the magnet
7113 aperture. At the highest energy, the lattice is optimised to keep the emittance growth limited, while the
7114 beta-functions are allowed to be larger. A cell of the lowest and one of the highest energy arc is shown in
7115 Fig. 8.31 All turns have a bending radius of 764m. The beam pipe diameter is 25mm, which corresponds to
7116 more than 12σ aperture.

7117 An interesting alternative optics, which pushes towards a smaller beam pipe, has also been devel-
7118 oped [720].

7119 Synchrotron Radiation in Return Arcs

7120 Synchrotron radiation in the arcs leads to a significant beam energy loss. This loss is compensated by the
7121 small linacs that are incorporated before or after each arc when the beams are already or still separated
7122 according to their energy, see Fig. 8.29. The energy loss at the 60GeV turn-round can be compensated by
7123 a linac with an RF frequency of 721.44MHz. The compensation at the other arcs is performed with an RF
7124 frequency of 1442.88MHz. In this way the bunches that are on their way to the collision point and the ones
7125 that already collided can both be accelerated. This ensures that the energy of these bunches are the same
7126 on the way to and from the interaction point, which simplifies the optics design. If the energy loss were not
7127 compensated the beams would have a different energy at each turn, so that the number of return arcs would
7128 need to be doubled.

7129 The synchrotron radiation is also generating an energy spread of the beam. In Tab. 8.13 the relative
7130 energy spread is shown as a function of the arc number that the beam has seen. At the interaction point,
7131 the synchrotron radiation induced RMS energy spread is only 2×10^{-4} , which adds to the energy spread of
7132 the wakefields. At the final arc the energy spread reaches about 0.22%, while at the beam dump it grows to
7133 a full 4.5%.




Figure 8.31: The optics of the lowest (top) and the highest (bottom) energy return arcs.

turn no	E [GeV]	$\Delta\epsilon_{arc}$ [μm]	$\Delta\epsilon_t$ [μm]
1	10.4	0.0025	0.0025
2	20.3	0.140	0.143
3	30.3	0.380	0.522
4	40.2	2.082	2.604
5	50.1	4.268	6.872
6	60	12.618	19.490
5	50.1	4.268	23.758
4	40.2	2.082	25.840
3	30.3	0.380	26.220
2	20.3	0.140	26.360
1	10.4	0.0025	26.362

Table 8.14: The emittance growth due to synchrotron radiation in the arcs. $\Delta\epsilon_{arc}$ is the growth in each individual arc, $\Delta\epsilon_t$ is the integrated growth including all previous arcs. The collision with the proton beam will take place at the beginning of the arc 6, so one finds $\Delta\epsilon_t \approx 4.3 \mu\text{m}$.

7134 The growth of the normalised emittance is given by

$$\Delta\epsilon = \frac{55}{48\sqrt{3}} \frac{\hbar c}{mc^2} r_e \gamma^6 I_5 \quad (8.7)$$

7135 Here, r_e is the classical electron radius, and I_5 is given by

$$I_5 = \int_0^L \frac{H}{|\rho|^3} ds = \frac{\langle H \rangle \theta}{\rho^2} \quad H = \gamma D^2 + 2\alpha DD' + \beta D'^2 \quad (8.8)$$

7136 For a return arc with a total bend angle $\theta = 180^\circ$ one finds

$$\Delta\epsilon = \frac{55}{48\sqrt{3}} \frac{\hbar c}{mc^2} r_e \gamma^6 \pi \frac{\langle H \rangle \theta}{\rho^2} \quad (8.9)$$

7137 The synchrotron radiation induced emittance growth is shown in table 8.14. Before the interaction point
7138 a total growth of about $7\mu\text{m}$ is accumulated. The final value is $26\mu\text{m}$. While this growth is significant
7139 compared to the target emittance of $50\mu\text{m}$ at the collision point, it seems acceptable.

7140 Switchyard, Matching Sections and Arc Lattices

7141 We have completed a design for the “switchyard” and linac-to-arc matching sections for one side of the
7142 ERL (Arcs 1, 3 and 5). The other side will follow a similar pattern of symmetric vertical spread-recombiner
7143 architecture and it is rather straightforward. We still need to include sections that compensate the energy
7144 loss in the arcs; they have not been designed yet. But this again should be quite straightforward.

7145 **Switchyard** At the ends of each linac the beams need to be directed into the appropriate energy-dependent
7146 arcs for recirculation. For practical reasons vertical rather than horizontal beam separation was chosen.
7147 Similar to CEBAF, two-step-achromat spreaders and mirror symmetric recombiners have been implemented.
7148 The switchyard that separates all three arcs (Arcs 1, 3 and 5) into 1 meter high vertical stack is illustrated
7149 in Figure 8.32.

7150 For Arcs 1 and 3 the vertical dispersion generated by a pair of vertical steps is suppressed by three
7151 quadrupoles placed between the steps, as illustrated in Figure 8.33 a) and b). The highest energy arc, Arc




Figure 8.32: Vertical spreader architecture based on one common “splitter” magnet.

7152 3, is not elevated and remains at the “linac level”. Here, the vertical dispersion is naturally suppressed by
 7153 the appropriate dipole spacing (no quads in between needed), as shown in Figure 8.33 c). In addition, a
 7154 pair of horizontal “doglegs”, used for path-length adjustment, is placed downstream of each spreader. The
 7155 “dogleg” archromats are naturally “meshed into” the beta-matching section, as illustrated in Figure 8.33.

7156 **Complete Arc Lattices with matched Optics** Finally, one can “attach” the above spreaders and
 7157 mirror symmetric recombiners at each end of a given 1800 “arc proper” composed of periodic FMC cells
 7158 introduced previously. As the arc energy goes up, more and more aggressive “emittance preserving” flavors
 7159 of FMC cells are used to configure the arc proper. Complete arc optics for Arc 1, 3 and 5 matched to the
 7160 corresponding linacs are illustrated in Figure 8.34.

7161 8.3.3 Beam Break-Up

7162 Single-Bunch Wakefield Effect

7163 In order to evaluate the single bunch wakefield effects we used PLACET [722]. The full linac lattice has
 7164 been implemented for all turns but the arcs have each been replaced by a simple transfer matrix, since the
 7165 matching sections have not been available.

7166 Single bunch wakefields were not available for the SPL cavities. We therefore used the wakefields in the
 7167 ILC/TESLA cavities [723]. In order to adjust the wakefields to the lower frequency and larger iris radius
 7168 (70mm vs. 39mm for the central irises) we used the following scaling

$$W_{\perp}(s) \approx \frac{1}{(70/39)^3} W_{\perp,ILC}(s/(70/39)) \quad W_L(s) \approx \frac{1}{(70/39)^2} W_{L,ILC}(s/(70/39)) \quad (8.10)$$

7169 First, the RMS energy spread along the linacs is determined. An initial uncorrelated RMS energy spread
 7170 of 0.1% is assumed. Three different bunch lengths were studied, i.e. 300 μ m, 600 μ m and 900 μ m. This longest
 7171 value yields the smallest final energy spread. The energy spread along during the beam life-time can be seen
 7172 in Fig. 8.35. The wakefield induced energy spread is between 1×10^{-4} and 2×10^{-4} at the interaction point,
 7173 $1-2 \times 10^{-3}$ at the final arc and 3.5–4.5% at the beam dump.

7174 Second, the single bunch beam-break-up is studied by tracking a bunch with an initial offset of $\Delta x = \sigma_x$.
 7175 The resulting emittance growth of the bunch is very small, see Fig. 8.36.




Figure 8.33: Vertical spreader architecture based on one common spreader magnet and local dispersion suppression.

f [GHz]	k [V/pCm ²]	f [GHz]	k [V/pCm ²]
0.9151	9.323	1.675	4.160
0.9398	19.095	2.101	1.447
0.9664	8.201	2.220	1.427
1.003	5.799	2.267	1.377
1.014	13.426	2.331	2.212
1.020	4.659	2.338	11.918
1.378	1.111	2.345	5.621
1.393	20.346	2.526	1.886
1.408	1.477	2.592	1.045
1.409	23.274	2.592	1.069
1.607	8.186	2.693	1.256
1.666	1.393	2.696	1.347
1.670	1.261	2.838	4.350

Table 8.15: The considered dipole modes of the SPL cavity design.




Figure 8.34: Complete Arc 1, 3 and 5 lattices including: spreaders, recombiners and path-length correcting “doglegs” matched to the corresponding linacs.




Figure 8.35: The RMS energy spread due to single bunch wakefields along the linacs. The bunch has been cut longitudinally at $\pm 3\sigma_z$ and at $\pm 3\sigma_E$ in the initial uncorrelated energy spread.




Figure 8.36: The single-bunch emittance growth along the LHeC linacs for a bunch with an initial offset of $\Delta x = \sigma_x$. The arcs have been represented by a simple transfer matrix.

7176 **Multi-Bunch Transverse Wakefield Effects**

7177 For a single pass through a linac the multi-bunch effects can easily be estimated analytically [721]. Another
 7178 approach exists in case of two passes through one cavity [724]. It is less straightforward to find an analytic
 7179 solution for multiple turns in linacs with wakefields that vary from one cavity to the next. In this case the
 7180 also phase advance from one passage through a cavity to the next passage depends on the position of the
 7181 cavity within the linac. We therefore addressed the issue by simulation.

7182 Two multi-bunch beam break-up studies have been performed independently. The first study is based
 7183 on a new code that we developed to simulate the multi-bunch effect in the case of recirculation and energy
 7184 recovery [725]. It assumes point-like bunches and takes a number of dipole wake field modes into account.
 7185 A cavity-to-cavity frequency spread of the wakefield modes can also be modeled. The arcs are replaced with
 7186 simple transfer matrices. In the simulation, we offset a single bunch of a long train by one unit and determine
 7187 the final position in phase space of all other bunches.

7188 We evaluated the beam stability using the wakefield modes that have been calculated for the SPL cavity
 7189 design [726]. The level of the Q -values of the transverse modes is not yet known. We assume $Q = 10^5$ for all
 7190 modes, which is comparable to the larger of the Q -values found in the TESLA cavities. A random variation
 7191 of the transverse mode frequencies of 0.1% has been assumed, which corresponds to the target for ILC [723].
 7192 The results in Fig. 8.37 indicate that the beam remains stable in our baseline design. Even in the alternative
 7193 lattice with no focusing in the linacs, the beam would remain stable but with significantly less margin. An
 7194 independent beam-breakup analysis for linacs without focusing, based on measurements and simulations for
 7195 the BNL 5-cell cavity, demonstrated as well that for all practical scenarios with a HOM frequency spread
 7196 above 0.2% the instability threshold current is well above the design beam current [720].

7197 We also performed simulations, assuming that either only damping or detuning were present, see Fig. 8.38.
 7198 The beam is unstable in both cases. Similarly, increasing the Q value to 10^6 will make the beam unstable
 7199 Based on our results we conclude

- 7200 • One has to ensure that transverse higher order cavity modes are detuned from one cavity to the next.
 7201 While this detuning can naturally occur due to production tolerances, one has to find a method to
 7202 ensure its presence. This problem exists similarly for the ILC.
- 7203 • Damping of the transverse modes is required with a Q value below 10^5 .

7204 If these requirements are met, the beam will remain stable in the cavities at 720 MHz. Further studies can
 7205 give more precise limits on the maximum required Q and minimum mode detuning.

7206 A further study used the code TDBBU [?]. The optics model of the machine is the same as for the first
 7207 study. The wakefield model has been based on the BNL3 5-cell cavities, even if their fundamental mode
 7208 frequency is 703.79 MHz. The summary of measured HOMs is illustrated in Figure 8.39.

7209 One can notice that all the Q values are less than $1 \cdot 10^6$ and most of them are smaller than $1 \cdot 10^4$. For
 7210 our BBU simulation, we consider the worst case of $Q_l = 1 \cdot 10^6$. Out of all HOMs collected in Figure 8.39, we
 7211 selected three most offending HOMs with relatively high R/Q values. They are summarized in table 8.16.

Frequency[MHz]	Q_l	R/Q[Ohm]
1003	$1 \cdot 10^6$	32
1337	$1 \cdot 10^6$	32
1820	$1 \cdot 10^6$	32

Table 8.16: The most offending HOMs selected into BBU simulation.

7212 In the simulation, for each cavity along the linac, the three offending HOM frequencies are randomly
 7213 distributed with the full width of 2 MHz. In practice, the HOM frequencies are generated using random
 7214 numbers in that range and these are distributed at each cavity. Twenty samples for different HOM frequency
 7215 distributions are generated. The plots below show the beam behavior near the threshold. The horizontal
 7216 axis corresponds to a bunch number and can be considered as an axis of time (if the bunch numbers are




Figure 8.37: Multi-bunch beam break-up assuming the SPL cavity wakefields. One bunch has been offset at the beginning of the machine and the normalised amplitudes of the bunch oscillations are shown along the train at the end of the last turn. The upper plot shows a small number of bunches before and after the one that has been offset (i.e. bunch 3000). The lower plot shows the amplitudes along the full simulated train for the baseline lattice and the alternative design with no quadrupole focusing. One can see the fast decay of the amplitudes.




Figure 8.38: Multi-bunch beam break-up for the SPL cavities. In one case only damping, in the other case only cavity-to-cavity mode detuning is present.




Figure 8.39: Quality factor of BNL3 cavity per “High Current SRF Cavity Design for SPL and eRHIC”, S. Belomestnykh et al., Proceedings of 2011 Particle Accelerator Conference, New York, NY, USA.




Figure 8.40: Large scale TDBBU simulation results for various beam currents: 4 (top left), 5 (top right) and 6 mA.

7217 divided by frequencies). The vertical axis represents the transverse beam position at the end of the second
 7218 linac. We plot the transverse positions of every 1117th particles. The number 1117 is somehow arbitrary;
 7219 however it is a large prime number chosen to avoid an unexpected sub-harmonic redundancy in the data
 7220 sampling. The simulation results for various beam currents: 4, 5 and 6 mA are illustrated in Figure 8.40.

7221 As illustrated in Figure 8.40, the beam is stable at 4 mA. At 5 mA the transverse position is increasing,
 7222 which indicate onset of the instability. Finally, at 6 mA one explicitly observes an exponential increase
 7223 in transverse beam position - a vivid case of beam instability. Therefore, we could infer that the BBU
 7224 threshold current is somewhere around 5 mA. One needs to keep in mind, our study assumed the worst case
 7225 interpretation of HOM's measurement for a cavity with limited HOM suppression, only one pair of HOM
 7226 dampers per cavity, positioned at 120 degrees to each other. This suggests more extended HOM damping
 7227 will bring the stability threshold above 6.5 mA.

7228 Alternatively, one may consider a more realistic HOM selection extracted from the measurements sum-
 7229 marized in Figure 8.39. Such alternative choice of HOMs, with $Q_l = 1 \cdot 10^5$, is listed in the in table 8.17.

Frequency[MHz]	Q_l	R/Q[Ohm]
1003	$1 \cdot 10^5$	32
1337	$1 \cdot 10^5$	32
1820	$1 \cdot 10^5$	32

Table 8.17: An alternative selection of offending HOMs selected for the BBU simulation.

7230 Most recent BBU study with the above selection of offending HOMs, 8.17, yields the beam stability
 7231 threshold of 22 mA, which is more than sufficient. From this study we conclude that the Q values of the
 7232 transverse modes have to remain somewhere around 10^5 .




Figure 8.41: The oscillation frequency f_c of ions of different mass number A in the linacs using the average focusing strength of the bunches at different energy. The frequency is normalised to the limit frequency f_{limit} above which the ions would not be trapped any more.

7233 Fast Beam-Ion Instability

7234 Collision of beam particles with the residual gas in the beam pipe will lead to the production of positive
 7235 ions. These ions can be trapped in the beam. Their presence modifies the betatron function of the beam
 7236 since the ions focus the beam. They can also lead to beam break-up, since bunches with an offset will induce
 7237 a coherent motion in the ions. This can in turn lead to a kick of the ions on following bunches.

7238 **Trapping Condition in the beam pulse** In order to estimate whether ions are trapped or not, one can
 7239 replace each beam with a thin focusing lens, with the strength determined by the charge and transverse
 7240 dimension of the beam. In this case the force is assumed to be linear with the ion offset, which is a good
 7241 approximation for small offsets.

7242 The coherent frequency f_i of the ions in the field of a beam of with bunches of similar size is given
 7243 by [727]:

$$f_i = \frac{c}{\pi} \sqrt{\frac{Q_i N r_e \frac{m_e}{A m_p}}{3 \sigma_y (\sigma_x + \sigma_y) \Delta L}} \quad (8.11)$$

7244 Here, N is the number of electrons per bunch, ΔL the bunch spacing, r_e the classical electron radius, m_e
 7245 the electron mass, Q_i the charge of the ions in units of e and A is their mass number and m_p the proton
 7246 mass. The beam transverse beam size is given by σ_x and σ_y . The ions will be trapped in the beam if

$$f_i \leq f_{limit} = \frac{c}{4 \Delta L} \quad (8.12)$$

7247 In the following we will use $\Delta L \approx 2.5\text{m}$, i.e. assume that the bunches from the different turns are almost
 7248 evenly spaced longitudinally.

7249 In the linacs, the transverse size of the beam changes from one passage to the next while in each of
 7250 the return arcs the beams have (approximately) the same size at both passages. But the variation from

one turn to the next is not huge, so we use the average focusing strength of the six turns. The calculation shows that ions will be trapped for a continuous beam in the linacs. Since we are far from the limit of the trapping condition, the simplification in our model should not matter. As can be seen in Fig. 8.41 CO_2^+ ions are trapped all along the linacs. Even hydrogen ions H_2^+ would be trapped everywhere. If one places the bunches from the six turns very close to each other longitudinally, the limit frequency f_{limit} is reduced. However, the ratio f_c/f_{limit} is not increased by more than a factor 6, which is not fully sufficient to remove the H_2^+ .

Impact and Mitigation of Ion Effects Without any methods to remove ions, a continuous beam would collect ions until they neutralise the beam current. This will render the beam unstable. Hence one needs to find methods to remove the ions. We will first quickly describe the mitigation techniques and then give a rough estimate of the expected ion effect.

A number of techniques can be used to reduce the fast beam-ion instability:

- An excellent vacuum quality will slow down the build-up of a significant ion density.
- Clearing gaps can be incorporated in the electron beam. During these gaps the ions can drift away from the beam orbit.
- Clearing electrodes can be used to extract the ions. They would apply a bias voltage that lets the ions slowly drift out of the beam.

Clearing Gaps In order to provide the gap for ion cleaning, the beam has to consist at injection of short trains of bunches with duration τ_{beam} separated by gaps τ_{gap} . If each turn of the beam in the machine takes τ_{cycle} , the beam parameters have to be adjusted such that $n(\tau_{beam} + \tau_{gap}) = \tau_{cycle}$. In this case the gaps of the different turns fall into the same location of the machine. This scheme will avoid beam loading during the gap and ensure that the gaps are fully empty. By choosing the time for one round trip in the electron machine to be an integer fraction of the LHC roundtrip time $\tau_{LHC} = m\tau_{cycle}$, one ensures that each bunch in the LHC will either always collide with an electron bunch or never. We chose to use $\tau_{cycle} = 1/3\tau_{LHC}$ and to use a single gap with $\tau_{gap} = 1/3\tau_{cycle} \approx 10 \mu\text{s}$.

In order to evaluate the impact of a clearing gap in the beam, we model the beam as a thick focusing lens and the gap as a drift. The treatment follows [728], except that we use a thick lens approach and correct a factor two in the force. The focusing strength of the lens can be calculated as

$$k = \frac{2Nr_em_e}{A_{ion}m_p\sigma_y(\sigma_x + \sigma_y)\Delta L} \quad (8.13)$$

The ions will not be collected if the following equation is fulfilled

$$\left| 2 \cos(\sqrt{k}(L_{erl} - L_g)) - \sqrt{k}L_g \sin(\sqrt{k}(L_{erl} - L_g)) \right| \geq 2 \quad (8.14)$$

Since the beam size will vary as a function of the number of turns that the beam has performed, we replace the above defined k with the average value over the six turns using the average bunch spacing ΔL ,

$$k = \frac{1}{n} \sum_{i=1}^n \frac{2Nr_em_e}{A_{ion}m_p\sigma_{y,i}(\sigma_{x,i} + \sigma_{y,i})\Delta L}. \quad (8.15)$$

The results of the calculation can be found in Fig. 8.42. As can be seen, in most locations the ions are not trapped. But small regions exist where ions will accumulate. More study is needed to understand which ion density is reached in these areas. Longitudinal motion of the ions will slowly move them into other regions where they are no longer trapped.




Figure 8.42: The trace of the transfer matrix for H_2^+ , CH_4^+ and CO_2^+ ions in presence of a clearing gap. Values above 2 or below -2 indicate that the ions will not be trapped.

7286 **Ion Instability** While the gap ensures that ions will be lost in the long run, they will still be trapped
 7287 at least during the full train length of $20\mu\text{s}$. We therefore evaluate the impact of ions on the beam during
 7288 this time. This optimistically ignores that ions will not be completely removed from one turn to the next.
 7289 However, the stability criteria we employ will be pessimistic. Clearly detailed simulations will be needed in
 7290 the future to improve the predictive power of the estimates.

7291 Different theoretical models exist for the rise time of a beam instability in the presence of ions. A
 7292 pessimistic estimate is used in the following. The typical rise time of the beam-ion instability for the n th
 7293 bunch can be estimated to be [727]

$$\tau_c = \frac{\sqrt{27}}{4} \left(\frac{\sigma_y(\sigma_x + \sigma_y)}{Nr_e} \right)^{\frac{3}{2}} \sqrt{\frac{A_{ion} m_p}{m} \frac{kT}{p\sigma_{ion}} \frac{\gamma}{\beta_y c n^2 \sqrt{L_{sep}}}} \quad (8.16)$$

7294 This estimate does not take into account that the ion frequency varies with transverse position within the
 7295 bunch and along the beam line.

7296 We calculate the local instability rise length $c\tau_c$ for a pressure of $p = 10^{-11}\text{hPa}$ at the position of the
 7297 beam. As can be seen in Fig. 8.43 this instability rise length ranges from a few kilometers to several hundred.
 7298 One can estimate the overall rise time of the ion instability by averaging over the local ion instability rates:

$$\left\langle \frac{1}{\tau_c} \right\rangle = \frac{\int \frac{1}{\tau_c(s)} ds}{\int ds} \quad (8.17)$$

7299 For the worst case in the figure, i.e. CH_4^+ , one finds $c\tau_c \approx 14\text{ km}$ and for H_2^+ $c\tau_c \approx 25\text{ km}$. The beam
 7300 will travel a total of 12 km during the six passes through each of the two linacs. So the typical time scale
 7301 of the rise of the instability is longer than the life time of the beam and we expect no issue. This estimate
 7302 is conservative since it does not take into account that ion frequency varies within the beam and along the
 7303 machine. Both effects will stabilise the beam. Hence we conclude that a partial pressure below 10^{-11} hPa is
 7304 required for the LHeC linacs.

7305 In the cold part of LEP a vacuum level of $0.5 \times 10^{-9}\text{hPa}$ has been measured at room temperature, which
 7306 corresponds to $0.6 \times 10^{-10}\text{hPa}$ in the cold [729]. This is higher than required but this value “represents
 7307 more the outgassing of warm adjacent parts of the vacuum system” [729] and can be considered a pessimistic
 7308 upper limit. Measurements in the cold at HERA showed vacuum levels of 10^{-11}hPa [730], which would be
 7309 sufficient but potentially marginal. Recent measurements at LHC show a hydrogen pressure of $5 \times 10^{-12}\text{hPa}$
 7310 measured at room temperature, which corresponds to about $5 \times 10^{-13}\text{hPa}$ in the cold [731]. For all other
 7311 gasses a pressure of less than 10^{-13}hPa is expected measured in the warm [731], corresponding to 10^{-14}hPa
 7312 in the cold. These levels are significantly better than the requirements. The shortest instability rise length
 7313 would be due to hydrogen. With a length of $c\tau_c \approx 500\text{ km}$ which is longer than 40 turns. Hence we do not
 7314 expect a problem with the fast beam-ion instability in the linacs provided the vacuum system is designed
 7315 accordingly.

7316 The effect of the fast beam-ion instability in the arcs has been calculated in a similar way, taking into
 7317 account the reduced beam current and the baseline lattice for each arc. Even H_2^+ will be trapped in the
 7318 arcs. We calculate the instability rise length $c\tau_c$ for a partial pressure of 10^{-9} hPa for each ion mass and find
 7319 $c\tau_c \approx 70\text{ km}$ for H_2^+ , $c\tau_c \approx 50\text{ km}$ for N_2^+ and CO^+ and $c\tau_c \approx 60\text{ km}$ for CO_2^+ . The total distance the beam
 7320 travels in the arcs is 15 km . Hence we conclude that a partial pressure below 10^{-9} hPa should be sufficient
 7321 for the arcs. More detailed work will be needed in the future to fully assess the ion effects in LHeC but we
 7322 remain confident that they can be handled.

Ion Induced Phase Advance Error The relative phase advance error along a beam line can be calculated
 using [728] for a round beam:

$$\frac{\Delta\phi}{\phi} = \frac{1}{2} \frac{Nr_e}{\Delta L \epsilon_y} \frac{\theta}{\langle \beta_y^{-1} \rangle}$$

7323 Here θ is the neutralisation of the beam by the ions. We use the maximum beta-function in the linac to
 7324 make a conservative approximation $\langle \beta^{-1} \rangle = 1/700\text{ m}$. At the end of the train we find $\rho \approx 3.3 \times 10^{-5}$ for




Figure 8.43: The instability length of the beam-ion instability assuming a very conservative partial pressure of 10^{-11} hPa for each gas.

7325 $p = 10^{-11}$ hPa in the cold and $p = 10^{-9}$ hPa in the warm parts of the machine. This yields $\Delta\Phi/\Phi \approx 7 \times 10^{-4}$.
 7326 Hence the phase advance error can be neglected.

7327 **Impact of the Gap on Beam Loading** It should be noted that the gaps may create some beam-loading
 7328 variation in the injector complex. We can estimate the associated gradient variation assuming that the same
 7329 cavities and gradients are used in the injector as in the linacs. We use

$$\frac{\Delta G}{G} \approx \frac{1}{2} \frac{R}{Q} \omega \frac{\tau_{gap} \tau_{beam} I}{\tau_{gap} + \tau_{beam}} \frac{1}{G} \quad (8.18)$$

7330 In this case the 10 μ s gaps in the bunch train correspond to a gradient variation of about 0.6%. This seems
 7331 very acceptable.

7332 8.3.4 Imperfections

7333 Static imperfections can lead to emittance growth in the LHeC linacs and arcs. However, one can afford an
 7334 emittance budget that is significantly larger than the one for the ILC, i.e. 10 μ m vs. 20nm. If the LHeC
 7335 components are aligned with the accuracy of the ILC components, one would not expect emittance growth
 7336 to be a serious issue. In particular in the linacs dispersion free steering can be used and should be very
 7337 effective, since the energies of the different probe beams are much larger than they would be in ILC.

7338 Gradient Jitter and Cavity Tilt

Since the cavities have tilts with respect to the beam line axis, dynamic variations of the gradient will lead to transverse beam deflections. This effect can be easily calculated using the following expression:

$$\frac{\langle y^2 \rangle}{\sigma_y^2} = \frac{\langle (y')^2 \rangle}{\sigma_{y'}^2} = \frac{1}{2} \frac{1}{\epsilon} \int \frac{\beta}{E} ds \frac{L_{cav} \langle \Delta G^2 \rangle \langle (y'_{cav})^2 \rangle}{mc^2}$$

For an RMS cavity tilt of $300\mu\text{radian}$, an RMS gradient jitter of 1% and an emittance of $50\mu\text{m}$ we find

$$\frac{\langle y^2 \rangle}{\sigma_y^2} = \frac{\langle (y')^2 \rangle}{\sigma_{y'}^2} \approx 0.0125$$

7339 i.e. an RMS beam jitter of $\approx 0.07\sigma_y$. At the interaction point the beam jitter would be $\approx 0.05\sigma_{y'}$.

7340 8.3.5 Touschek Scattering

7341 In recirculating energy recovery linacs, intrabeam scattering and Touschek scattering give rise to beam
7342 halo and to some unavoidable amount of beam losses, in particular, for high brightness beams and after
7343 deceleration [732]. In the LHeC ERL a few dedicated collimators should be foreseen to localize and control
7344 these losses [732]. For round beams the Touschek loss rate can be approximated as [733] (corrected by a
7345 factor of two [734])

$$\frac{\Delta N_b}{\Delta s} = -\frac{N_b^2 r_e^2}{8\sqrt{\pi}\gamma^2 \sigma_z \epsilon_x \epsilon_y} \frac{1}{\eta(s)} D \left(\frac{\delta q(s)}{\eta(s)} \right), \quad (8.19)$$

7346 where $\delta q(s) = \gamma\sigma_x(s)/\beta_x(s)$,

$$D(\epsilon) = \sqrt{\epsilon} \int_{\epsilon}^{\infty} \frac{e^{-u}}{u^{3/2}} \left(\frac{1}{\epsilon} - 1 - \frac{1}{2} \ln \frac{u}{\epsilon} \right) du, \quad (8.20)$$

7347 and η_{acc} denotes the relative momentum acceptance, which varies along the beamline and is a function of the
7348 downstream beam energy, RF voltage, optics and aperture. Equation (8.19) describes the number of bunch
7349 particles which are Touschek scattered per unit length at location s and lost at a later location. No detailed
7350 analysis of Touschek scattering has yet been performed for the LHeC, but with normalized emittances $\epsilon_{x(y)}$
7351 much larger than envisioned for other projects, e.g. CESR-ERL, with less beam current, and higher beam
7352 energy, the effect is expected to be comparatively benign.

7353 8.4 Performance as a Linac-Ring electron-ion collider

7354 The performance as an e-A collider can be evaluated on a basis similar to the Ring-Ring version of the LHeC
7355 discussed in Section 7.14. Again, this relies on the fact that the nominal emittances for Pb beams in the
7356 LHC imply equal geometric beam sizes, at the IP in particular.

7357 8.4.1 Heavy nuclei, e-Pb collisions

7358 The Pb beam is specified in Table 7.33. Assuming that the 60 GeV electron beam specified in Table 8.7 can
7359 be adapted to the irregular 100 ns spacing of the Pb beam, the luminosity follows from Eq. 8.1 (including
7360 the additional factor of $A = 208$ to obtain the electron-nucleon luminosity):

$$L_{eN} = \begin{cases} 9 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1} & \text{(Nominal Pb)} \\ 1.6 \times 10^{32} \text{ cm}^{-2}\text{s}^{-1} & \text{(Ultimate Pb)} \end{cases} \quad (8.21)$$

7361 where we assume $H_{hg} = H_D = 1$ for the additional factors in Eq. 8.1.

7362 8.4.2 Electron-deuteron collisions

7363 An estimate of the parameters for deuteron beams in the LHC is also given in Section 7.14. Proceeding
7364 in the same manner as above, we find that *electron-nucleon* luminosities of order $L_{eN} \gtrsim 3 \times 10^{31} \text{ cm}^{-2}\text{s}^{-1}$
7365 could be accessible in e-D collisions in a Linac-Ring LHeC.




Figure 8.44: Beam pattern at IP

8.5 Polarized-Electron Injector for the Linac-Ring LHeC

We present the injector for the polarized electron beam. The issue of producing a sufficient number of polarized or unpolarized positrons is discussed in section 8.7.

The Linac-Ring option is based on an ERL machine where the beam pattern, at IP, is shown in Figure 8.44.

With this bunch spacing, one needs 20×10^9 bunches/second and with the requested bunch charge, the average beam current is 20×10^9 b/s \times 0.33 nC/b = 6.6 mA.

Figure 8.45 shows a possible layout for the injector complex, as source of polarized electron beam.

The injector is composed of a DC gun where a photocathode is illuminated by a laser beam. Then a linac accelerates electron beam up to the requested energy before injection into the ERL. Downstream a bunch compressor system allows to compress the beam to 1 ps and finally a spin rotator, brings the spin in the vertical plane.

Assuming 90% of transport efficiency between the source and the IP, the bunch charge at the photocathode should 2.2×10^9 e-/b. According to the laser and photocathode performance, the laser pulse width, corresponding to the electron bunch length, will be between 10 and 100 ps.

Table 8.18 summarises the electron beam parameters at the exit of the DC gun.

The challenges to produce the 7 mA beam current are the following:

- a very good vacuum ($< 10^{-12}$ mbar) is required in order to get a good lifetime.
- the issues related to the space charge limit and the surface charge limit should be considered. A peak current of 10 A with 4 ns pulse length has been demonstrated. Assuming a similar value for the DC gun, a laser pulse length of 35 ps would be sufficient to produce the requested LHeC charge.
- the high voltage (100 kV to 500 kV) of the DC gun could induce important field emissions.
- the design of the cathode/anode geometry is crucial for a beam transport close to 100%.
- the quantum efficiency should be as high as possible for the photocathode ($\sim 1\%$ or more).




Figure 8.45: Layout of the injector (not to scale).

Parameters	60 GeV ERL
Electrons /bunch	2.2×10^9
Charge /bunch	0.35 nC
Number bunches / s	20×10^9
Bunch length	10 – 100 ps
Bunch spacing	50 ns
Pulse repetition rate	CW
Average current	7 mA
Peak current of the bunch	3.5 – 350 A
Current density (1 cm)	1.1 – 110 A/cm ²
Polarization	> 90%

Table 8.18: Beam parameters at the source.

- 7390
- the laser parameters (300 nJ/pulse on the photocathode, 20 MHz repetition rate) will need some R&D
- 7391 according to what is existing today on the market.
- 7392
- the space charge could increase the transverse beam emittances.

7393 In conclusion, a tradeoff between the photocathode, the gun and the laser seems reachable to get accept-

7394 able parameters at the gun exit. A classical Pre-Injector Linac accelerates electron beam to the requested

7395 ERL energy. Different stages of bunch compressor are used to compensate the initial laser pulse and the

7396 space charge effects inducing bunch lengthening. A classical spin rotator system rotates the spin before

7397 injection into the ERL.

8.6 Spin Rotator

8.6.1 Introduction

The potential of studying new physics in high precision QCD, substructure etc. at LHeC requires polarized electrons with spin aligned longitudinally at the collision point. For the linac-ring version of the LHeC the electron beam can be generated with 80-90% polarization using a photocathode source. To avoid the polarization loss of the high energy electron beam, the spin vector needs to be aligned vertically during the acceleration in a re-circulating linac and then brought into the longitudinal direction for collision. This section reports possible design choices for the LHeC spin rotator.

The motion of the spin vector \vec{S} in an accelerator is governed by the Thomas-BMT equation [735]

$$\frac{d\vec{S}}{dt} = \frac{e}{m\gamma} \vec{S} \times [(1 + G\gamma)\vec{B}_\perp + (1 + G)\vec{B}_\parallel] \quad (8.22)$$

where e , m and γ are the electric charge, mass and Lorentz factor of the particle. G is the anomalous g-factor (for protons $G = 1.7928474$, and for electrons $G = 0.00115$). \vec{B}_\perp and \vec{B}_\parallel are the magnetic field perpendicular and parallel to the particle velocity direction, respectively. In (8.22) the magnetic field is given in the laboratory frame while the spin vector \vec{S} is in the particle rest frame. Eq. (8.22) implies that, in a perfect circular accelerator with $\vec{B}_\parallel = 0$, a spin vector precesses $G\gamma$ times the particle orbital rotation in the moving frame. For the electron accelerator of LHeC, which consists of two 10 GeV superconducting linear accelerators linked by six 180° arc paths, the depolarization due to the arcs is negligible if the spin is aligned vertically in the arcs.

Eq. (8.22) also shows that both dipole field and solenoid field can be used to manipulate the spin motion. However, the effect of a solenoid field on the spin motion decreases linearly with beam energy, while the effect of a dipole field is almost independent of beam energy.

8.6.2 LHeC Spin Flipper Options

To produce longitudinally oriented polarization at the final collision point for a 60-GeV electron beam, two options have been explored:

- A low energy spin rotator at the LHeC injector to place the spin vector in a direction that after the spin precessions incurred in all the arcs becomes the longitudinal direction at the IP.
- A dedicated high energy spin rotator close to the IP which brings the vertically aligned spin vector into longitudinal direction. For this option, a low energy spin rotator at the injector is also required in order to produce a vertically polarized electron beam for acceleration.

Details of these two options are discussed in the following.

Low energy spin rotator

For the LHeC physics program, the polarization of 60 GeV electron beam needs to be aligned longitudinally at the collision point which is localized after the last arc and after the final linac acceleration. The most economical way to control the spin direction at the collision point is to control the spin direction of the low energy electron beam at the early stage of injector using a Wien Filter, i.e. a traditional low energy spin rotator. Since the spin vector rotates $G\gamma\pi$ each time it passes through a 180° arc, the goal of the Wien Filter is to put the spin vector in the horizontal plane with an angle to the direction of the particle velocity chosen so as to compensate the net effect of all the spin rotations occurring before collision.

For the layout of LHeC, i.e. two linear accelerators linked by two arcs, the spin vector rotates by an amount

$$\phi_{arc} = G\pi[\gamma_i(2n - 1) + \Delta\gamma n(2n - 1)] \quad (8.23)$$

7437 during its n th path. Here, γ_i is the initial Lorentz factor of the beam and $\Delta\gamma$ is the energy gain of each
 7438 linear accelerator. In addition, LHeC also employs a horizontal dipole on either side of the IP to separate
 7439 the electrons from the protons. These dipoles have a field of 0.3 T and span a distance of 9 m from the
 7440 collision point. For the 60 GeV electron beam, such bending magnet rotates the spin vector by $\phi_{IP} = 104.4^\circ$.
 7441 Considering an initial energy of 10 GeV (after the first path through the linac) and for each linear accelerator
 7442 an energy gain of 10 GeV, Table 8.19 lists the amount of spin rotation through the arcs and the amount
 7443 of spin rotation through the final bending dipole at the collision point for a 20, 40 and 60-GeV beam,
 respectively. Here, the amount of spin rotation at the IP refers to the net spin rotation modulo 2π .

Table 8.19: total spin rotation from arcs and final bending dipole at collision point

beam energy GeV	# of path n	ϕ_{arc} [degree]	ϕ_{IP} [degree]
20	1	8101.8	34.8
40	2	36457.9	69.6
60	3	81017.6	104.4

7444 Since the spin rotation is proportional to the beam energy, for a beam of particles with non-zero
 7445 momentum spread, different amounts of spin rotation generate a spread of spin vector directions. This results
 7446 in an effective polarization loss due to the associated spread of the spin vector. Figure 8.46 shows the angle
 7447 spread of the spin vector for an off-momentum particle at 20, 40 and 60 GeV, respectively. It indicates that,
 7448 for a 60-GeV electron beam, a momentum spread of 3×10^{-4} can cause about $(1 - \cos(25^\circ)) \approx 10\%$ effective
 7449 polarization loss due to the spread of the spin vectors. This level of polarization loss is undesirable and
 7450 would compromise the physics reach of the LHeC.




Figure 8.46: Calculated spin vector spread as function of momentum spread. The effective polarization loss is the cosine of the spin vector spread angle, e.g. for an angle of 30 degrees, the effective polarization is $\sim 86\%$ of the initial beam polarization.

7451

7452 High energy spin rotator

7453 In order to provide the desirable polarization direction without sacrificing polarization, one can adopt the
 7454 traditional approach of high-energy polarized beams at HERA and RHIC, i.e. rotate the spin vector into the
 7455 vertical direction before the beam gets accelerated to high energy. Since the spin vector is then aligned with
 7456 the main bending magnetic field direction, this prevents the spread of the spin vector due to the momentum

7457 spread. For the current compact LHeC final-focusing system (FFS), we propose to use a RHIC type spin
 7458 rotator [736, 737]. Besides saving space by being short, this approach also has the additional advantage
 7459 of offering an independent full control over the final spin vector orientation, as well as providing a nearly
 7460 energy-independent spin rotation. The four helical dipoles are arranged in a fashion similar to the RHIC
 7461 spin rotator, i.e. with alternating helicity. Figure 8.47 shows the schematic layout. In the preliminary design,
 7462 each helical dipole is 3.3 m long and the helicity alternates between right hand and left hand from one helical
 7463 dipole to the next. The two inner helical dipoles have the same magnetic field but opposite helicity. The
 same applies for the two outer helical dipoles.




Figure 8.47: Schematic layout of the LHeC spin rotator, consisting of a total of four helical dipoles with alternating helicity marked as + and -. The polarity of the two outer helical dipole fields is opposite, and so is the polarity of the two inner helical dipoles.

7464 For each helical dipole, the magnetic field is given by
 7465

$$B_x = B \cos kz , \tag{8.24}$$

$$B_y = B \sin kz , \tag{8.25}$$

$$B_z = 0 , \tag{8.26}$$

7466 where $B_{x,y,z}$ denotes the horizontal, vertical and longitudinal component of the magnetic field, respectively,
 7467 and z the longitudinal distance along the helical dipole axis, while $|k| = 2\pi/\lambda$ and λ are the wave number
 7468 and the wave length of the helical field, respectively.

7469 For the spin rotator, all helical dipoles are chosen to be one period long, i.e. $\lambda = L$, where L is the
 7470 length of each helical dipole, and, depending on the direction of the helicity, $k/|k| = \pm 1$. Fig. 8.48 shows
 7471 the correlation of the magnetic field for the inner and outer helical magnets of a spin rotator which brings
 7472 the spin vector from the vertical direction into the horizontal plane. Figure 8.49 presents the calculated
 7473 angle of the spin vector for each outer helical magnet field. Both plots show that this design allows for a
 7474 flexible adjustment for the direction of spin vector by varying the outer and inner helical magnetic fields,
 7475 respectively.

7476 This rotator will be placed in the straight section between the end of the second linac and the FFS,
 7477 upstream of the final bending dipole at the collision point as well as of three bends right upstream of the
 7478 final triplet. As mentioned, the 0.3-T final bending dipole next to the IP rotates the spin vector by 104.4
 7479 degrees for a 60-GeV electron beam, while the other, weaker three other bends rotate the spin vector by
 7480 only -1.8 degrees. To align the spin vector of the polarized electrons in the longitudinal direction at the IP
 7481 the spin rotator must bring the spin vector from the vertical direction onto the horizontal plane at an angle
 7482 of 102.6 degrees from the longitudinal direction. This requirement then determines the magnetic field of
 7483 the inner and outer pairs to be 1.92 T and 0.93 T, respectively. The maximum horizontal orbital excursion
 7484 is 17 mm in the 1.92-T dipole and 8.5 mm in the 0.93-T dipole. The fine tuning of the direction of the
 7485 spin vector can be achieved by empirically adjusting the helical dipole magnetic field strengths based on the
 7486 measurements of polarimeters installed before and after the collision point.

7487 About 0.88 MW synchrotron radiation power is emitted by the 60-GeV electron beam passing through
 7488 the spin rotator. This radiation power could be reduced by lengthening the system, while lowering the
 7489 magnetic field of the helical dipoles. Figure 8.50 illustrates the correlation of the magnetic field for the inner
 7490 and outer helical magnets for a ~ 5 times longer longer spin rotator, where each helical dipole now has a




Figure 8.48: Correlation of the outer and inner helical dipole magnetic field strength for a spin rotator which is designed to bring a vertically aligned spin vector to the horizontal plane. The length of the helical dipoles is taken to be 3.3 m each.

7491 length of 15 m. Figure 8.51 presents the calculated angle of the spin vector as a function of the outer helical
 7492 magnet field strength. For a 60 GeV electron beam, the magnetic fields of the inner and outer pairs now
 7493 need to be -0.419 T and -0.2016 T, respectively. These fields will rotate the spin vector into the horizontal
 7494 plane after the exit of the spin rotator. For this longer system, the synchrotron radiation power is reduced
 7495 to 190 kW, whereas the maximum horizontal orbital excursion increases to 75 mm for the -0.419 -T magnet
 7496 and 36 mm for the 0.2016 -T magnet.

7497 8.6.3 Polarimetry

7498 To measure the polarization of the high-energy electron beam a Compton polarimeter is foreseen. Such
 7499 polarimeter detects the electrons and photons produced in Compton scattering of the electron beam off an
 7500 intense circularly polarized laser beam [738]. A Compton polarimeter requires space to accommodate the
 7501 laser as well as the detectors. High-precision measurements require an efficient separation of the Compton-
 7502 scattered electrons from the main electron beam.

7503 The polarimeter could be placed either upstream or downstream of the IP. We tentatively consider two
 7504 polarimeters, one on either side of the IP, which would allow excluding or quantifying any depolarizing effects
 7505 in the final focus or due to the collision process. In order to place these polarimeters at locations where the
 7506 spin direction is longitudinal, we propose installing (or using) additional bending magnets so that the deflec-
 7507 tion angle by the IP dipoles is exactly compensated and the net spin precession angle between polarimeter
 7508 and IP equal to zero, also taking into account the small energy change due to synchrotron radiation emitted
 7509 in these magnets. In this way maximizing the longitudinal polarization at either polarimeter by scanning
 7510 the field strengths of the two pairs of helical magnets in the upstream spin rotator automatically maximizes
 7511 the longitudinal polarization at the collision point. The polarization levels measured at the two polarimeters
 7512 allow deducing the polarization loss in the collision as well as the effective polarization, which is important
 7513 for particle physics. Figure 8.52 sketches the overall spin-related layout of the LHeC interaction region (IR).




Figure 8.49: Spin vector direction in the horizontal plane as a function of the outer helical magnet field strength. The length of the helical dipoles is taken to be 3.3 m each.

8.6.4 Conclusions and Outlook for the Spin Control

This section has presented a flexible spin flipper for the L-R LHeC high-energy electron beam. The proposed design based on a group of helical dipoles next to the final collision point, similar to the spin flipper at RHIC, satisfies the requirement of delivering a high-energy electron beam with high longitudinal polarization. It also has the additional merits of being compact and flexible. For this approach, a low energy spin flipper like a Wien Filter as part of the injector is also required to rotate the spin vector into the vertical direction prior to acceleration.

Synchrotron radiation close to the MW level emitted from the proposed high-energy spin rotator is a concern, which can be addressed by optimizing the field strength and length of the helical dipoles. A reduced synchrotron radiation power implies larger orbit excursions inside the rotator dipoles.

Detailed calculations including helical dipole design, orbital and spin tracking of spin rotator are work in progress.

8.7 Positron Options for the Linac-Ring LHeC

8.7.1 Motivation

It is known that the generation of an intense positron beam with a linac configuration is a particular challenge. This raises the question as to how crucial the availability of positron-proton scattering to the LHeC is. Reasons for the importance of e^+p scattering are given in the physics chapters and have been summarized in an introduction to a topical meeting [739] in May 2011 at CERN, the technical results of which are summarized below. For the physics program, the following topics may serve as important example processes which require very high statistics positron (and electron) data:

- If there exist so far unknown resonant states of leptons and partons, quarks or/and gluons, the asymmetry between the e^+p and e^-p cross sections determines the fermion number of the produced leptoquark to be $F = 2$, as for an $e_L u$ state of charge $-1/3$, or $F = 0$ for an $e_L \bar{u}$ state of charge $-5/3$.




Figure 8.50: Correlation of the outer and inner helical dipole magnetic field strength for a longer spin rotator designed to bring a vertically aligned spin vector to the horizontal plane, for a longer design with reduced synchrotron radiation, where each helical dipole has a length of 15 m.

- 7537 • If there appears a new contact interaction, its nature may be disentangled by considering its charge
7538 dependence. If there was an excited electron observed, one surely would like to check whether the
7539 positron has the same structure.
- 7540 • It has been a long standing question whether the strange quark and anti-quark distributions are
7541 different, for which neutrino-nucleon data provide certain hints. With electron and positron charged
7542 current data, this can be resolved and both s and \bar{s} can be measured. Similarly one will be able to
7543 measure single top and single anti-top quark distributions for the first time.
- 7544 • Access to valence quarks at low x is possible with the precision measurement of the $x F_3^{\gamma Z}$ structure
7545 function, which can be accessed only with high statistics NC cross section asymmetry data.
- 7546 • High statistics beam charge asymmetry data are essential to access generalized parton distributions at
7547 low Q^2

7548 An example for the importance of e^+p scattering with high but perhaps not maximum luminosity is the
7549 precision measurement of the longitudinal structure function F_L , in which the charge symmetric background
7550 at low scattered electron energies has to be experimentally determined and subtracted in order to safely
7551 reach the region of highest sensitivity to F_L . One would finally like to note that if the positron-proton
7552 luminosity was significantly lower than the electron-proton luminosity, there would always be a tendency
7553 to preferentially run with electrons in order to collect a maximum integrated luminosity for those processes
7554 and topics which are less or not dependent on the availability of both beam charge configurations. Examples
7555 here are the precision measurement in polarized e^-p scattering of the weak mixing angle, the physics at low
7556 x or the precision measurement of α_s . It is the physics beyond the standard model, and the searches for
7557 it, which has the highest demands on the e^+p luminosity. One concludes that the physics demands for the
7558 availability of intense e^+p scattering are very strong. A further aspect regards the importance of positron
7559 beam polarization which may deserve further consideration.




Figure 8.51: Spin vector direction in the horizontal plane as a function of the outer helical magnet field strength for a longer design with reduced synchrotron radiation, where each helical dipole has a length of 15 m.




Figure 8.52: Schematic of spin-related IR layout with spin rotator, two polarimeters, and compensating bends.

8.7.2 LHeC Linac-Ring e^+ Requirements

Table 8.20 compares the e^+ beam flux foreseen for LHeC with those obtained at the SLC, and targeted for CLIC and the ILC.

The SLC (Stanford Linear Collider) was the only linear-collider type machine which has produced e^+ for a high-energy particle physics experiment. The flux for the CLIC project (a factor 20 compared to SLC) is already considered challenging [740] and possible options with hybrid targets are under investigation on paper. Even more positrons would be required for the ILC. The requested LHeC flux for pulsed operation at 140 GeV (a factor 300 compared to SLC) could be obtained, in a first approximation, with 10 e^+ target stations working in parallel. Several more advanced solutions are being considered to meet the requested LHeC flux for the CW option (a factor 7300 compared to SLC).

8.7.3 Mitigation Schemes

Two main approaches can lessen the demands on the rate of positrons to be produced at the source, namely

- **Recycling the positrons after the collision**, with considerations on e^+ emittance after collision, emittance growth in the 60-GeV return arc due to synchrotron radiation, and possible cooling schemes,

	SLC	CLIC (3 TeV)	ILC (500 GeV)	LHeC (p= 140)	LHeC (ERL)
Energy (GeV)	1.19	2.86	4	140	60
e^+ /bunch at IP ($\times 10^9$)	40	3.72	20	1.6	2
Norm. emittance (mm.mrad)	30 (H)	0.66 (H)	10 (H)	100	50
	2 (V)	0.02 (V)	0.04 (V)		
Longit. rms emittance (eV-m)	7000	5000	60000	10000	5000
e^+ /bunch after capture ($\times 10^9$)	50	7.6	30	1.8	2.2
Bunches / macropulse	1	312	2625	10^5	NA
Macropulse repetition rate	120	50	5	10	CW
Bunches / second	120	15600	13125	10^6	20×10^6
e^+ / second ($\times 10^{14}$)	0.06	1.1	3.9	18	440

Table 8.20: Comparison of the e^+ flux.

7574 e.g. introducing a tri-ring system with fast laser cooling in the central ring (see below), or using a large
7575 damping ring. If 90% of the positrons are recycled the requirement for the source drops by an order
7576 of magnitude.

- 7577 • **Repeated collisions on multiple turns**, e.g. using a (pulsed) phase-shift chicane in order to recover
7578 60 GeV when reaching the collision point again on the following turn.

7579 8.7.4 Cooling of Positrons

7580 One of the most challenging problems associated with the continuous production of positrons is cooling
7581 (damping) of the positron beam emerging from a source or being recycled after the collision. Possible
7582 cooling scenarios include pushing the performance of a large conventional damping ring with the size of the
7583 SPS, and a novel compact tri-ring scheme.

7584 Damping Ring

7585 The 6.9-km SPS tunnel can accommodate a train of 9221 bunches with 2.5 ns bunch spacing. Considering a
7586 maximum bending field of 1.8 T and a wiggler field of 1.9 T, there is a parametric interdependence between
7587 beam energy, the total wiggler length and the damping time. Figure 8.53 shows the dependence of the
7588 damping ring energy on the total wiggler length for a damping time of 2 ms (red curve). Without wigglers,
7589 the ring has to run at 22 GeV, whereas for around 10 GeV, wigglers with a total length of 800 m are needed.
7590 The blue curve represents the same dependence when a 10 times lower repetition rate is considered, which
7591 increases the required damping time by an order of magnitude. In that case, the ring energy without any
7592 wigglers can be reduced to 7 GeV and it can be dropped to less than 4 GeV for a total wiggler length of 200
7593 m.

7594 A tentative parameter list for low (10 Hz) and high repetition rate (100 Hz) is shown in Table 8.21,
7595 considering 234 bending magnets of 0.5-m long dipoles with 1.8-T bending field. The wiggler field for the
7596 high-repetition option of 1.9 T along with a wiggler period of 5 cm is within the reach of modern hybrid
7597 wiggler technology. A big challenge is the high energy loss per turn for this case, which requires around 300
7598 MV of total RF voltage and implies an average synchrotron-radiation (SR) power of 25 MW. In the low
7599 repetition case, the RF voltage and SR power are an order of magnitude more relaxed.




Figure 8.53: Dependence of the damping ring energy on the total wiggler length for a transverse damping time of 2 ms (red curve) and 20 ms (blue curve).

7600 Tri-Ring Scheme

7601 Another possible solution to cool down a continuous positron beam, both the recycled beam and/or a new
 7602 beam from a source, is the tri-ring scheme illustrated in Fig. 8.54.

Parameter [unit]	High Rep-rate	Low Rep-rate
Energy [GeV]	10	7
Bunch population [10^9]	1.6	1.6
Bunch spacing [ns]	2.5	2.5
Number of bunches/train	9221	9221
Repetition rate [Hz]	100	10
Damping times trans./long. [ms]	2/1	20/10
Energy loss/turn [MeV]	230	16
Horizontal norm. emittance [μm]	20	100
Optics detuning factor	80	80
Dipole field [T]	1.8	1.8
Dipole length [m]	0.5	0.5
Wiggler field [T]	1.9	-
Wiggler period [cm]	5	-
Total wiggler length [m]	800	-
Dipole length [m]	0.5	0.5
Longitudinal norm. emittances [keV.m]	10	10
Momentum compaction factor	10^{-6}	10^{-6}
RF voltage [MV]	300	35
rms energy spread [%]	0.20	0.17
rms bunch length [mm]	5.2	8.8
average power [MW]	23.6	3.6

Table 8.21: Tentative parameter list for a damping ring in the SPS tunnel considering high and low repetition-rate options.




Figure 8.54: Tri-ring scheme converting a continuous beam into a pulsed beam, for cooling, and back.

7603 In this scheme, the basic cycle lasts N turns, during which the following processes happen simultaneously:
 7604 N -turn injection from the ERL into the accumulating ring (bottom); N -turn cooling in the cooling ring
 7605 (middle) possibly with fast laser cooling [741]; and N -turn slow extraction from the extracting ring (top)
 7606 back into the ERL. At the start of the cycle there is a one-turn transfer from the cooling ring into the
 7607 extracting ring, and a one-turn transfer from the accumulating ring into the cooling ring. The average
 7608 current in the cooling ring is N times the average ERL current.

7609 8.7.5 Production Schemes

7610 Positrons can be produced by pair creation when high-energy electrons or photons hit a target. Conventional
 7611 sources, as used at the SLC, send a high-energy electron beam on a conversion target. Alternatively, a high-
 7612 energy electron beam can be used with a hybrid-target configuration where the first thin target is used to
 7613 create high-energy photons, through a channeling process, which are then sent onto a thick target. The
 7614 prior conversion into photons reduces the heat load of the target for a given output intensity and it may
 7615 also improve the emittance of the generated positrons. There exist a number of other schemes that can
 7616 accomplish the conversion of electrons into photons. Several of them employ Compton scattering off a high-
 7617 power laser pulse stacked in an optical cavity. According to the electron-beam accelerator employed, one
 7618 distinguishes Compton rings, Compton linacs, and Compton ERLs [742–744]. An alternative scheme uses
 7619 the photons emitted by an electron beam of very high energy (of order 100 GeV) when passing through a
 7620 short-period undulator [?, 745, 746]. Finally, there even exists a simpler scheme where a high-power laser
 7621 pulse itself serves as the target for (coherent) pair creation.




Figure 8.55: Possible layout with unpolarised e^+ for the LHeC injector (p-140 GeV).

7622 Targets

7623 For the positron flux considered for the LHeC the heating and possible destruction of the target are important
 7624 concerns. Different target schemes and types can address these challenges: (1) multiple, e.g. 10, target
 7625 stations operating in parallel; (2) He-cooled granular W-sphere targets; (3) rotating-wheel targets; (4) sliced-
 7626 rod W tungsten conversion targets; (5) liquid mercury targets; and (6) running tape with annealing process.

7627 The LHeC ERL option requires a positron current of 6 mA or $4 \times 10^{16} e^+/s$, with normalized emittance
 7628 of $\leq 50 \mu\text{m}$ and longitudinal emittance $\leq 5 \text{ MeV}\cdot\text{mm}$. For a conventional conversion target with optimized
 7629 length the power of the primary beam is converted as follows $P_{\text{primary}}(100\%) = P_{\text{thermal}}(30\%) + P_{\gamma}(50\%) +$
 7630 $P_{e^-}(12\%) + P_{e^+}(8\%)$. The average kinetic energy of the newly generated positrons is $\langle T_{e^+} \rangle \approx 5 \text{ MeV}$,
 7631 which allows estimating the total power incident on the target as $P_{\text{target}} = 5 \text{ MV} \times 6 \text{ mA} / 0.08 = 375 \text{ kW}$.
 7632 Assuming an electron linac efficiency of $\eta_{\text{acc}} \approx 20\%$ we find $P_{\text{wall}} = P_{\text{target}}/0.2 = 1.9 \text{ MW}$. This wall-plug
 7633 power level looks feasible and affordable. However, also considering a capture efficiency (for the ‘useful’ e^+)
 7634 of about 5%, P_{wall} becomes 38 MW.

7635 Figure 8.55 illustrates a possible option, which alone would already meet the requirements for the 140-
 7636 GeV single-linac case, where the repetition rate is 10 Hz. The idea is to use 10 e^+ target stations in
 7637 parallel. This implies installing 2 RF deflectors upstream and the same downstream. Experience exists for
 7638 RF deflectors at 3 GHz and with operating 2 lines in parallel. Assuming that this configuration is acceptable
 7639 from the beam-optics point-of-view, it would be necessary to implement a fast damping scheme because the
 7640 bare emittances from the target will be too high for the injection into the ERL.

7641 Table 8.22 shows the beam characteristics at the end of the 10 GeV primary beam Linac for electrons,
 7642 before splitting the beam.

Primary beam energy (e^-)	10 GeV
Number e^- / bunch	1.2×10^9
Number of bunches / pulse	100000
Number e^- / pulse	1.2×10^{14}
Pulse length	5 ms
Beam power	1900 kW
Bunch length	1 ps

Table 8.22: Electron beam parameters before splitting.

7643 Table 8.23 shows the beam parameters at each e^+ target. A power of 5.6 kW is deposited in each target
 7644 and the Peak Energy Deposition Density (PEDD) is around 30 J/g [747]. This value has been chosen, in
 7645 order to stay below the breakdown limit for a tungsten (W) target. It is based on recent simulations [748]
 7646 with conventional W targets. A new study [749] assumes a target made out of an assembly of densely packed
 7647 W spheres (density about 75% of solid tungsten) with diameters of 1–2 mm, cooled by blowing He-gas
 7648 through the voids between the spheres. Such He-cooled granular targets have been considered for neutrino
 7649 factories and recently for the European Spallation Source ESSS.

Yield (e^+/e^-)	1.5
Beam power (for e^-)	190 kW
Deposited power / target	5.6 kW
PEDD	30 J/g
Number e^+ / bunch	1.8×10^9
Number bunches / pulse	10,000
Number e^+ / pulse	1.8×10^{13}

Table 8.23: Beam parameters at each e^+ target.

7650 To achieve the required cooling and the corresponding mass flow of the cooling fluid, we consider pres-
 7651 surized He at 10 bar entering the target volume at a velocity of 10 m/s, i.e. a mass flow 1.8 g/s is required
 7652 for each target. From this a convection coefficient of about $\alpha = 1 \text{ W/cm}^2/\text{K}$ can be expected and a cooling
 7653 time constant τ (exponential decay time after an adiabatic temperature rise of a sphere) of 185 ms will
 7654 result. Clearly, not much cooling during a pulse of 5 ms duration will occur, but cooling will set in during
 7655 the off-beam time of 95 ms between the pulses. The peak temperature after each pulse will stabilize at about
 7656 500 K above that of the cooling fluid. An average exit temperature of the He-gas of about 600 °C will have
 7657 still to be added, which drives the maximum temperature of the spheres up to about 1100 °C. Although
 7658 compatible with W in an inert atmosphere, it should be attempted to reach lower temperatures. This could
 7659 be achieved by increasing the He-pressure to 20 bar and the velocity of He to 20 m/s which might reduce
 7660 the maximum temperature in a sphere to 500 °C. Thus, a He-cooled granular 10-W-target system could be
 7661 a viable solution.

7662 Another approach has been considered. To achieve, as in the previous case, a reduction of the energy
 7663 deposition density by a factor of 10, a fast rotating wheel could be designed. The beam pulse of 5 ms duration
 7664 is spread over the rim of the rotating wheel and a linear velocity of the rotating rim of 20 m/s would be
 7665 required. This would lead to a repetition rate of about 1000 rpm, assuming a wheel diameter of 0.4 m. Such
 7666 a solution is actually under investigation for the ILC with a rotation speed of 1800 rpm.

7667 Here tungsten spheres, again, are contained in a structure, similar to a car tyre, as is illustrated in
 7668 Fig. 8.56. The container is possibly made of light Ti-alloy where the sides, facing the beam entrance and
 7669 exit should be made of Beryllium, compatible with the beam heating. The helium for the cooling is injected
 7670 from the rotating axle through spokes into the actual target ring and is recuperated in the same way.

7671 If the beam pulse duration is extended by a factor 10, i.e. to 50 ms duration, maintaining of course the
 7672 same average power, then the rotation time could be reduced. The velocity of the wheel is such that over
 7673 the duration of 5 ms the rim is displaced by one beam width, i.e. 1 cm. This leads to much reduced rotation
 7674 speeds of 2 m/s, which can readily be achieved in a wheel with a diameter of 16 cm, rotating at 240 rpm.

7675 By choosing appropriately the rotation velocity, the average time between two hits of the same spot on
 7676 the rim of the wheel, is about 0.5 s. With the aforementioned cooling time constant for the He-circuit of 185
 7677 ms, the adiabatic temperature rise during one hit over 5 ms of 211 K will have dropped to nearly zero before
 7678 the next hit. For simultaneously cooling the whole rim of the wheel a He-flow of 90 g/s must be provided.
 7679 Taking into account the temperature increase in the cooling fluid, a maximum tungsten temperature in the
 7680 W-spheres of about 350°C can be expected, which is rather comfortable.

7681 Using a continuous D.C.-beam with no gaps will further alleviate the structure and performance of the




Figure 8.56: Sketch of rotating wheel containing W spheres with He cooling.

7682 target wheel.

7683 The interference of the rotating wheel with the downstream flux concentrator will have to be assessed. One
 7684 may, however, expect considerably less forces than presently considered for the ILC, due to the much lower
 7685 velocity of the wheel. Moreover, proper choice of materials with high electrical resistivity and laminating
 7686 the structure may be considered.

7687 Clearly, the W-granules must be contained inside the beam vacuum within a structure which is He-leak
 7688 tight at the selected He-pressure. As material for the upstream and downstream beam windows, Beryllium
 7689 must be considered which, due to its large radiation length (34 cm as compared to W with 0.34 cm), should
 7690 resist to the thermal loads. This, however, has to be verified.

7691 Also, radiation damage and life time issues will still have to be assessed.

7692 It is believed that rotating “Air to Vacuum” seals at 240 rpm are commercially available or can be
 7693 adapted to the radiation environment. Rotating “High Pressure He to Air” seals may have to be developed,
 7694 where small He-leaks can be tolerated.

7695 Presently with conventional targets, the transverse normalized rms beam emittances, in both planes, are
 7696 in the range of 6000 to 10 000 μm . With the new types of target, we do not know yet by how much the
 7697 transverse emittances will be changed. In any case, a strong reduction of emittances is mandatory for the
 7698 requested LHeC performance. Assuming that large or small emittances could be recombined, Table 8.24
 7699 shows a possible e^+ flux after recombination. If a solution is found for the emittances, it will be necessary
 7700 to design and implement a linac accelerating the positron beam up to 500 MeV, the energy for the ERL
 7701 injection.

7702 For Compton sources (discussed below) the conversion of gammas to positrons is a bottleneck, which
 7703 requires a study and optimization of effective converter targets such as the sliced-rod converter. A typical
 7704 tungsten converter optimized for Compton gammas with a maximal energy of 20 MeV can deliver 0.02
 7705 positrons per incident scattered gamma. A sliced-rod converter target may produce 0.07/0.13 positrons per

Secondary beam energy (e^+)	200 MeV
Number e^+ bunch	1.8×10^9
Number of bunches / pulse	100000
Number of e^+ / pulse	1.8×10^{14}
Bunch spacing	50 ns
Repetition rate	10 Hz

Table 8.24: Positron beam parameters after recombination.

Table 8.25: IP e^+ current and the implied minimum e^- beam current in a Compton Ring. Electron-beam currents below 5 A are considered achievable.

	LHeC pulsed	LHeC ERL
I_{e^+} at IP [μ A]	290	7050
typical I_{e^-} [A]	4.3	105.7
I_{e^-} with 5 J [A]	0.46	11.2
I_{e^-} with 5 J+1 m rod [A]	0.065	1.6

7706 gamma for a 1 m or 3 m long rod, respectively [750].

7707 Compton Sources

7708 In Compton sources (polarized) positrons are generated by scattering of an electron beam off a higher-power
7709 laser pulse, and by converting the resulting gammas in a target.

7710 • **Compton Ring:** Table 8.25 illustrates that a Compton-ring source equipped with an array of optical
7711 resonators yielding a total (single-IP ‘equivalent’) laser-pulse energy of 5 Joule, together with a sliced-
7712 rod conversion target, may produce the desired flux of polarized positrons even for the LHeC ERL
7713 option. The emission of 30-MeV gammas at the required rate can induce significant beam energy
7714 spread in the Compton ring, which requires further studies and optimization.

7715 • **Compton Linac:**An optimistic power analysis for a single-pass Compton linac using a CO₂ laser
7716 shows that the wall plug power for generating the Compton-linac electron beam alone exceeds the
7717 limit of 100 MW set for the entire LHeC project.

7718 • **Compton ERL:** A high current ERL appears to perhaps be a possible approach, e.g. a 3-GeV 1.3-A
7719 ERL with 2-micron wavelength optical enhancement cavities would provide the desired e^+ rate, with
7720 “only” 50 MW of wall plug power, and with upper-bound estimates on the transverse and longitudinal
7721 emittances for the captured positron beam of $\gamma\epsilon_{\perp} \leq 1.5$ m, and $\epsilon_{\parallel,N} \approx 450 \mu\text{m}$.

7722 The desired emittances are not reached from any Compton scheme source, even if the target is immersed in
7723 a strong magnetic field. Therefore, cooling or scraping would be required.

7724 Undulator Source

7725 An undulator process for e^+ production could be based on the main high-energy e^- (or e^+) beam. The
7726 LHeC undulator scheme can benefit from the pertinent development work done for the ILC. The beam
7727 energy at LHeC would be lower, e.g. 60 GeV, which might possibly be compensated by more ambitious
7728 undulator magnets, e.g. ones made from Nb₃Sn or HTS. However, the requested photon flux calls for a
7729 careful investigation. The undulator scheme could most easily be applied for the 140-GeV pulsed LHeC.

7730 Coherent Pair Creation

7731 The normalized transverse emittance of all positrons from a target is of order $\epsilon_N \approx 1 - 10$ mm, to be
7732 compared with a requested emittance of $\epsilon_N = 0.05$ mm. Therefore, a factor 100 emittance reduction is
7733 required. Possible solutions are cutting the phase space or damping. A third solution would be to produce
7734 positrons in a smaller phase space volume. Indeed the inherent transverse emittance from pair production
7735 is small. The large phase space volume only comes from multiple scattering in the production target.

7736 Pair production from relativistic electrons in a strong laser field would not need any solid target, since
7737 the laser itself serves as the target, and it would not suffer from multiple scattering. This process has been
7738 studied in the 1960's and 1990's [751–753]. It should be reconsidered with state-of-the-art TiSa lasers and
7739 X-ray FELs, and could offer an interesting prospect for the LHeC.

7740 8.7.6 Conclusions on Positron Options for the Linac-Ring LHeC

7741 The challenging requirements for the LHeC Linac-Ring positron source may be relaxed, to a certain extent,
7742 by e^+ recycling, e^+ re-colliding, and e^+ cooling. The compact tri-ring scheme is an attractive proposal for
7743 recooling the spent and recycled positrons, with a pushed conventional damping ring in the SPS tunnel as
7744 an alternative solution.

7745 Assuming some of the aforementioned measures are taken to lessen the required positron intensity to be
7746 produced at the source, by at least an order of magnitude, and also assuming that an advanced target is
7747 available, several of the proposed concepts could provide the intensity and the beam quality required by the
7748 LHeC ERL.

7749 For example, the Compton ring and the Compton ERL are viable candidates for the Linac-Ring LHeC
7750 positron source. Coherent pair production and an advanced undulator represent other possible schemes, still
7751 to be explored for LHeC in greater detail. The coherent pair production would have the appealing feature
7752 of generating positrons with an inherently small emittance.

7753 In conclusion, it may be possible to meet the very demanding requirements for the LHeC positron source.
7754 A serious and concerted R&D effort will be required to develop and evaluate a baseline design for the linac-
7755 ring positron configuration. Among the priorities are a detailed optics & beam-dynamics study of multiple
7756 collisions and of the tri-ring scheme, a theoretical exploration of coherent pair production, and participation
7757 in experiments on Compton sources, e.g. at the KEK ATF.

Chapter 9

System Design

9.1 Magnets for the Interaction Region

9.1.1 Introduction

The technical requirements for the ring-ring options are easily achieved with superconducting magnets of proven technology. It is possible to make use of the wire and cable development for the LHC inner triplet magnets. We have studied all-together seven variants of which two are selected for this CDR. Although these magnets will require engineering design efforts, there are no challenges because the mechanical design will be very similar to the MQXA [754] magnet built for the LHC [637].

The requirements in terms of aperture and field gradient are much more difficult to obtain for the linac-ring option. We reverse the arguments and present the limitations for the field gradient and septum size, that is, the minimum distance between the proton and electron beams, for both Nb-Ti and Nb₃Sn superconducting technology. Here we limit ourselves to the two most promising conceptual designs.

9.1.2 Magnets for the ring-ring option

The interaction region requires a number of focussing magnets with apertures for the two proton beams and field-free regions to pass the electron beam after the collision point. The lattice design was presented in Sections 7.3 and 8.47; the schematic layout is shown in Fig. 7.19.

The field requirements for the ring-ring option (gradient of 127 T/m, beam stay clear of 13 mm (12 σ), aperture radius of 21 mm for the proton beam, 30 mm for the electron beam) allow a number of different magnet designs using the well proven Nb-Ti superconductor technology and making use of the cable development for the LHC. In the simulations presented here, we have used the parameters (geometrical, critical surface, superconductor magnetization) of the cables used in the insertion quadrupole MQY of the LHC.

Fig. 9.1 shows a superferric magnet as built for the KEKb facility [755]. This design comes to its limits due to the saturation of the iron poles. Indeed, the fringe field in the aperture of the electron beam exceeds the limit tolerable for the electron beam optics, and the field quality required for proton beam stability, on the order of one unit in 10^{-4} at a reference radius of 2/3 the aperture, is difficult to achieve.

The magnetic flux density in the low-field region of the design shown in Fig. 9.1 (right) is about 0.3 T. We therefore disregard this design as well. Moreover, the engineering design work required for the mechanical structure of this magnet would be higher than for the proven designs shown in Fig. 9.2.

Fig. 9.2 shows the three alternatives based on LHC magnet technology. In the case of the double aperture version the aperture for the proton beams is 21 mm in radius, in the single aperture version the beam pipe radius is 26 mm. In all cases the 127 T/m field gradient can be achieved with a comfortable safety margin to quench (exceeding 30%) and using the cable(s) of the MQY magnet of the LHC. The operation temperature is supposed to be 1.8 K, employing superfluid helium technology. The cable characteristic data are given in




Figure 9.1: Cross-sections of insertion quadrupole magnets with iso-surfaces of the magnetic vector potential (field-lines). Left: Super-ferric, similar to the design presented in [755]. Right: Superconducting block-coil magnet as proposed in [756] for a coil-test facility.

7793 Table 9.1. The outer radii of the magnet coldmasses do not exceed the size of the triplet magnets installed
 7794 in the LHC (diameter of 495 mm). The fringe field in the aperture of the electron beam is in all cases below
 7795 0.05 T.

7796 Fig. 9.3 shows half-aperture quadrupoles (single and double-aperture versions for the proton beams) in a
 7797 similar design as proposed in [17]. The reduced aperture requirement in the double-aperture version makes
 7798 it possible to use a single layer coil and thus to reduce the beam-separation distance between the proton and
 7799 the electron beams. The field-free regions is large enough to also accommodate the counter rotating proton
 7800 beam. The version shown in Fig. 9.3 (left) employs a double-layer coil. In all cases the outer diameter of
 7801 the coldmasses do not exceed the size of the triplet magnets currently installed in the LHC tunnel.

7802 For this CDR we retain only the single aperture version for the Q2 (shown in Fig. 9.2, left) and the
 7803 half-aperture quadrupole for the Q1 (shown in Fig. 9.3, top left). The separation distance between the
 7804 electron and proton beams in Q1 requires the half-aperture quadrupole design to limit the overall synchrotron
 7805 radiation power emitted by bending of the 60 GeV electron beam. The single aperture version for Q2 is
 7806 retained in the present layout, because the counter rotating proton beam can be guided outside the Q2
 7807 triplet magnet. The design of Q3 follows closely that of Q2, except for the size of the septum between the
 7808 proton and the electron beams.

7809 The coils in all three triplet magnets are made from two layers, using both Nb-Ti composite cables as
 7810 specified in Table 9.1. The layers are individually optimized for field quality. This reduces the sensitivity
 7811 to manufacturing tolerances and the effect of superconductor magnetization [757]. The mechanical design
 7812 will be similar to the MQXA magnet where two kinds of interleaved yoke laminations are assembled under
 7813 a hydraulic press and locked with keys in order to obtain the required pre-stress of the coil/collar structure.
 7814 The main parameters of the magnets are given in Table 9.2.

7815 9.1.3 Magnets for the linac-ring option

7816 The requirements in terms of aperture and field gradient are more difficult to obtain for the linac-ring option.
 7817 Consequently we present the limitations for the field gradient and septum size achievable with both Nb-Ti
 7818 and Nb₃Sn superconducting technologies. We limit ourselves to the two conceptual designs already chosen
 7819 for the ring-ring option. For the half quadrupole, shown in Fig. 9.5 (right), the working points on the
 7820 load-line are given for both superconducting technologies in Fig. 9.4.

7821 However, the conductor size must be increased and in case of the half quadrupole, a four layer coil must

Table 9.1: Characteristic data for the superconducting cables and strands. OL = outer layer, IL = inner layer

Magnet	MQY (OL)	MQY (IL)
Diameter of strands (mm)	0.48	0.735
Copper to SC area ratio	1.75	1.25
Filament diameter (μ m)	6	6
B_{ref} (T) @ T_{ref} (K)	8 @ 1.9	5 @ 4.5
$J_c(B_{\text{ref}}, T_{\text{ref}})$ (A mm^{-2})	2872	2810
$-dJ_c/dB$ ($\text{A mm}^{-2} \text{T}$)	600	606
$\rho(293 \text{ K})/\rho(4.2 \text{ K})$ of Cu	80	80
Cable width (mm)	8.3	8.3
Cable thickness, thin edge (mm)	0.78	1.15
Cable thickness, thick edge (mm)	0.91	1.40
Keystone angle (degree)	0.89	1.72
Insulation thicken. narrow side (mm)	0.08	0.08
Insulation thicken. broad side (mm)	0.08	0.08
Cable transposition pitch length (mm)	66	66
Number of strands	34	22
Cross section of Cu (mm^2)	3.9	5.2
Cross section of SC (mm^2)	2.2	4.1

7822 be used; see Fig. 9.5. The thickness of the coil is limited by the flexural rigidity of the cable, which will
7823 make the coil-end design difficult. Moreover, a thicker coil will also increase the beam separation between
7824 the proton and the electron beams. The results of the field computation are given in Table 9.2, column 3
7825 and 4. Because of the higher iron saturation, the fringe fields in the electron beam channel are considerably
7826 higher than in the magnets for the ring-ring option.

7827 For the Nb_3Sn option we assume composite wire produced with the internal Sn process (Nb rod extru-
7828 sions), [758]. The non-Cu critical current density is 2900 A/mm^2 at 12 T and 4.2 K. The filament size of 46
7829 μm in Nb_3Sn strands give rise to higher persistent current effects in the magnet. The choice of Nb_3Sn would
7830 impose a considerable R&D and engineering design effort, which is however, not more challenging than other
7831 accelerator magnet projects employing this technology [759].

7832 Fig. 9.6 shows the conceptual design of the mechanical structure of these magnets. The necessary
7833 prestress in the coil-collar structure, which must be high enough to avoid unloading at full excitation, cannot
7834 be exerted with the stainless-steel collars alone. For the single aperture magnet as shown in Fig. 9.6 left,
7835 two interleaved sets of yoke laminations (a large one comprising the area of the yoke keys and a smaller,
7836 floating lamination with no structural function) provide the necessary mechanical stability of the magnet
7837 during cooldown and excitation. Preassembled yoke packs are mounted around the collars and put under
7838 a hydraulic press, so that the keys can be inserted. The sizing of these keys and the amount of prestress
7839 before the cooldown will have to be calculated using mechanical FEM programs. This also depends on the
7840 elastic modulus of the coil, which has to be measured with a short-model equipped with pressure gauges.
7841 Special care must be taken to avoid nonallowed multipole harmonics because the four-fold symmetry of the
7842 quadrupole will not entirely be maintained.

7843 The mechanical structure of the half-quadrupole magnet is somewhat similar, however, because of the
7844 left/right asymmetry four different yoke laminations must be produced. The minimum thickness of the
7845 septum will also have to be calculated with structural FEM programs.




Figure 9.2: Cross-sections with field-lines of insertion quadrupole magnets. Classical designs similar to the LHC magnet technology. Top left: Single aperture with a double layer coil employing both cables listed in Table 9.1. Design chosen for Q2. Top right: Double aperture vertical. Bottom: Double aperture horizontal. The double-aperture magnets can be built with a single layer coil using only the MQY inner layer cable; see the right column of Table 9.1.




Figure 9.3: Cross-sections of insertion quadrupole magnets with field-lines. Left: Single half-aperture quadrupole with field-free domain [17]; design selected for Q1. Right: Double-aperture magnet composed of a quadrupole and half quadrupole.




Figure 9.4: Working points on the load-line for both Nb-Ti and Nb₃Sn variants of the half quadrupole for Q1.




Figure 9.5: Cross-sections of the insertion quadrupole magnets for the linac-ring option. Left: Single aperture quadrupole. Right: Half quadrupole with field-free region.

Table 9.2: SC = type of superconductor, g = field gradient, R = radius of the aperture (without coldbore and beam-screen), LL = operation percentage on the load line of the superconductor material, I_{nom} = operational current, B_0 = main dipole field, S_{beam} = beam separation distance, B_{fringe} = fringe field in the aperture for the electron beam, g_{fringe} = gradient field in the aperture for the electron beam.

Type		Ring-ring single aperture	Ring-ring half-quad	Linac-ring single aperture	Linac-ring half-quad
Function		Q2	Q1	Q2	Q1
SC		Nb-Ti at 1.8 K			
R	mm	36	35	23	46
I_{nom}	A	4600	4900	6700	4500
g	T/m	137	137	248	145
B_0	T	-	2.5	-	3.6
LL	%	73	77	88	87
S_{beam}	mm	107	65	87	63
B_{fringe}	T	0.016	0.03	0.03	0.37
g_{fringe}	T/m	0.5	0.8	3.5	18
SC		Nb ₃ Sn at 4.2 K			
I_{nom}	A			6700	4500
g	T/m			311	175
B_0	T			-	4.7
LL	%			83	82
B_{fringe}	T			0.09	0.5
g_{fringe}	T/m			9	25




Figure 9.6: Sketch of the mechanical structure. Left: Single aperture magnet. Right: Half quadrupole with field-free region.

9.2 Accelerator Magnets

In this section the main magnets needed for the accelerator are considered. The analysis focuses separately on the ring-ring (RR) and linac-ring (LR) layouts. The requirements are listed and an initial design is proposed. The RR dipoles prompted an experimental activity, involving the manufacturing and magnetic characterization of short models, whose results are briefly reported here.

We gratefully acknowledge the fruitful discussion with Neil Marks about the design of these electromagnets. We thank Miriam Fitterer and Alex Bogacz for help in checking the requirements of the magnets according to the lattice, for the RR and LR option, respectively.

9.2.1 RR option, dipole magnets

A total of 3080 bending magnets, 5.35 m long, are needed in the LHC tunnel for the RR layout, of which 3040 form the arcs and the remaining 40 are for the insertion and by-pass regions. The nominal strength is 0.0127 T at 10 GeV and 0.0763 T at 60 GeV. As a comparison, the LEP collider contained 3280 main dipole magnets, with a nominal flux density at injection (20 GeV) of 0.0215 T, and at collision energy (100 GeV) of 0.1100 T [760].

The main points to consider in the design of these magnets are:

- the low working flux density, in particular at injection, that constitutes a challenge for cycle-to-cycle reproducibility and for good field quality throughout the ramp;
- the need for compactness, to fit in the present tunnel with the installed LHC systems;
- the required compatibility with the emitted synchrotron radiation power.

Different designs have been proposed at BINP and CERN to respond to these demands. In particular, the first point (low injection field) has prompted an experimental activity, with several short models manufactured and measured. This experience is briefly summarized next.

BINP model

Two different types of models have been manufactured at BINP, see Fig. 9.7. The aim was to demonstrate that a cycle-to-cycle reproducibility at injection better than $0.1 \cdot 10^{-4}$ T can be achieved. Both models have shown a field reproducibility at injection current within $\pm 0.075 \cdot 10^{-4}$ T, when cycled between injection and maximum field. To achieve such results the iron laminations were made of 3408 type grain oriented silicon steel 0.35 mm thick. Their coercive force in the direction of the grain orientation is $H_{c\parallel} \approx 6$ A/m, while in the direction perpendicular to the grain orientation it remains relatively low, $H_{c\perp} \approx 22$ A/m. The C-type model has been assembled in two variants, with the central iron part with the grains oriented vertically and horizontally (both blocks are as shown in the picture). The magnetic measurements did not show relevant differences between the two versions.

CERN model

As a complementary study to the one made by BINP, the CERN model has explored the manufacture of lighter magnets, with the yoke consisting of interleaved steel and plastic laminations. A thickness ratio between plastic and steel of 2:1 has been chosen. As the flux produced in the magnet aperture is concentrated in the high permeability regions only, the magnetic field in the iron pole is about 3 times that in the gap. In addition to a lighter assembly, this solution has the advantage of increasing the magnetic working point of the iron at injection field. This makes the design less sensitive to the characteristics of the iron and in particular to the coercive force. A similar strategy had been adopted for the LEP dipoles, where 1.5 mm thick low-carbon steel laminations were spaced by 4 mm and embedded in a cement mortar.

The proposed design is a compact C type dipole, see Fig. 9.8. The aperture is on the external side of the ring, so that the magnet does not intercept the emitted synchrotron radiation, and possibly room is left




Figure 9.7: H and C type model magnets made by BINP at Novosibirsk.

7889 for a vacuum pre-chamber. The geometry involves a rather unusual shape for the poles. The objective was
 7890 to design a cross-section able to minimize the difference of flux lines length over the horizontal aperture.
 7891 This makes the field quality (in particular, the quadrupole component) less dependent on variations of iron
 7892 characteristics, both at injection and collision energies.

7893 For the coils, a 1-turn solution (per pole) has been adopted, with solid copper bars which after insulation
 7894 are individually slid inside the magnet.

7895 To explore the potential of the proposed design, in particular in terms of magnetic field reproducibility
 7896 at injection energy, three models have been built using three different materials:

- 7897 • model 1: a rather noble Supra 36 NiFe steel, 1.0 mm thick laminations, with a measured coercive field
 7898 (after heat treatment for 4 hours at 1050 °C under hydrogen), equal to $H_c \approx 6$ A/m;
- 7899 • model 2: a conventional low carbon steel with low silicon content, 1.0 mm thick laminations, 0.5% Si,
 7900 $H_c \approx 70$ A/m;
- 7901 • model 3: a 35M6 grain oriented steel, 0.35 mm thick laminations, 3.1% silicon, with $H_{c\parallel} \approx 7$ A/m and
 7902 $H_{c\perp} \approx 25$ A/m.

7903 In all cases 2 mm thick phenolic sheets have been used as spacers, stacked and glued with an epoxy
 7904 resin together with the steel sheets. For the last model, to compensate for the thinner laminations, three of
 7905 them were stacked together, in order to keep a similar magnetic field distribution as in the stacks with the
 7906 isotropic steels.

7907 Magnetic measurements have been performed to assess the field reproducibility at injection. A cycle from
 7908 10 GeV to 60 GeV, requiring a dipole field of 0.0127 T to 0.0763 T, corresponds to currents from 210 A to



Figure 9.8: One of the 400 mm long model magnets made at CERN with interleaved laminations.

7909 1340 A. Unfortunately the available power converter could provide a sufficiently good stability only over a
 7910 smaller range, namely between 260 A and 1300 A, with measured stabilities of $4 \cdot 10^{-5}$ at 260 A and $2 \cdot 10^{-5}$
 7911 at 1300 A. Each of the models was submitted to 5 conditioning cycles and thereafter to 8 cycles between
 7912 these currents at a ramp rate of 400 A/s. The reproducibility of the magnetic field in the gap was measured
 7913 with an integral coil coupled with a digital integrator, providing the results summarized in Tables 9.3 and
 7914 9.4.

7915 The performance is in all cases very satisfactory. There might be an indication that models 1 and 3,
 7916 as expected, perform better than model 2; however, the values are close to the measurement errors. In
 7917 practice these results show that within this range of field levels the value of the coercive field does not seem
 7918 to play a major role in the reproducibility of the magnetic field from cycle to cycle. More details about the
 7919 manufacturing of these models and the magnetic measurements can be found in [761].

Model	Low field	High field
Model 1 (NiFe steel)	$5 \cdot 10^{-5}$	$4 \cdot 10^{-5}$
Model 2 (Low carbon steel)	$6 \cdot 10^{-5}$	$6 \cdot 10^{-5}$
Model 3 (Grain oriented 3.5% Si steel)	$4 \cdot 10^{-5}$	$6 \cdot 10^{-5}$

Table 9.3: Reproducibility of magnetic field over 8 cycles, maximum deviation from average.

Model	Low field	High field
Model 1 (NiFe steel)	$3 \cdot 10^{-5}$	$3 \cdot 10^{-5}$
Model 2 (Low carbon steel)	$4 \cdot 10^{-5}$	$5 \cdot 10^{-5}$
Model 3 (Grain oriented 3.5% Si steel)	$2 \cdot 10^{-5}$	$4 \cdot 10^{-5}$

Table 9.4: Reproducibility of magnetic field over 8 cycles, standard deviation from average.

7920 The conclusion of this analysis is that all three models meet the LHeC specifications. However, the

7921 similarity that can be achieved in a series production of 3080 units has to be further investigated. The low
7922 value of injection field amplifies the problem, as in that region the variation in magnetic parameters is larger.
7923 This problem is already partially taken care of in the design of the cross-section, that is meant to be less
7924 sensitive to the iron characteristics, and in the low stacking factor. Furthermore, the usual procedure of
7925 “shuffling” (or “sorting”) the laminations during the production has to be envisaged, with results that might
7926 depend on the statistical distribution of coercive forces and permeabilities (at low field) in the steel, as well
7927 as on the shuffling technique.

7928 **Proposal for dipole magnets, RR option**

7929 The proposed cross-section for the dipoles of the ring-ring option is shown in Fig. 9.9. The main parameters
7930 are summarized in Table 9.5.

7931 The idea of assembling the yoke with steel laminations interleaved by plastic spacers is retained, as in
7932 the CERN models. This has the mechanical advantage of a lower weight of the assembly, and the magnetic
7933 advantage of magnifying the field in the steel by a factor of about 3. This is of particular interest at injection
7934 energy.

7935 The conductor can be in aluminium (like in LEP) or in copper depending on economical reasons coming
7936 from a correct balance between investment and operation costs. The present design is based on an aluminium
7937 conductor. With respect to copper, this has the advantage of making the magnet lighter (about 200 kg of
7938 coil instead of about 625 kg). Using copper, however, would imply a power consumption, per magnet, at
7939 60 GeV around 190 W instead of around 300 W. Notwithstanding the material, the choice of having 1-turn
7940 coils, i.e., solid straight bars, has several technical and economical consequences:

- 7941 • the coil manufacturing is simpler and hence cheaper;
- 7942 • the high current (1300 A) involves large terminals and connections between the magnets;
- 7943 • the power supply is rated at high current, but with rather low voltage and impedance;
- 7944 • the resistive losses in the interconnections, terminals and in the power cables are significantly higher
7945 than those for a multi-turn magnet working at lower current;
- 7946 • it is possible to envisage to use the conductor as bus-bar to connect the string of magnets in series,
7947 thus reducing the number of interconnections.

7948 The solution proposed here for the conductor is similar to the one that had been adopted for LEP. However,
7949 these aspects need to be further investigated in the TDR on a wider perspective.

7950 The conductor size is sufficiently large so that the current density is around 0.4 A/mm². The dissipated
7951 resistive power (of the order of 50 W per meter of length of the magnet, considering aluminium as conductor)
7952 is reduced to levels which can be possibly dealt with by the ventilation in the LHC tunnel: this is a
7953 considerable advantage in terms of simplicity of magnet manufacture, connections, reliability and of course
7954 it avoids the installation of a water cooling circuit dedicated to the dipoles in the arcs.

7955 **9.2.2 RR option, quadrupole magnets**

7956 The quadrupole magnets needed for the ring-ring option can be considered undemanding and well within
7957 the compass of standard design.

7958 **Quadrupoles in the arcs**

7959 In the arcs, 336 focusing quadrupoles (QF) providing 10.28 T integrated strength, and 336 defocusing
7960 quadrupoles (QD) each providing 8.40 T integrated strength are needed. These are to be installed in the
7961 LHC tunnel.

7962 Considering that the integrated strengths of the QD and QF are not much different, it is proposed here to
7963 have the same type of magnets. The relevant parameters are summarized in Table 9.6 and the cross-section
7964 is illustrated in Fig. 9.10.

7965 **Quadrupoles in the insertion and by-pass**

7966 In total 148 QF and 148 QD magnets are needed in the insertion and by-pass regions. The required integrated
7967 strength is 18 T for the QF and 13 T for the QD. In this case, it is proposed to keep the same magnet cross-
7968 section but to have two different lengths for the quadrupoles, namely, 1.0 m for the QF and 0.7 m for the
7969 QD. The relevant parameters are summarized in Table 9.7 and the cross-section is illustrated in Fig. 9.11.
7970 A value of 19 T/m is taken as design gradient.




Figure 9.9: Bending magnets for the RR option (scale 1:5).

Beam energy	10 to 60	GeV
Magnetic field	0.0127 to 0.0763	T
Magnetic length	5.35	m
Vertical aperture	40	mm
Pole width	150	mm
Mass	1400	kg
Number of magnets	3080	
Current @ 0.0763 T	1300	A
Number of turns per pole	1	
Current density @ 0.0763 T	0.4	A/mm ²
Conductor material	aluminium	
Magnet inductance	0.13	mH
Magnet resistance	0.18	mΩ
Power @ 60 GeV	300	W
Total power consumption @ 60 GeV	0.92	MW
Cooling	air	

Table 9.5: Main parameters of bending magnets for the RR option.




Figure 9.10: Arc quadrupoles for the RR option (scale 1:5).

Beam energy	10 to 60	GeV
Field gradient @ 60 GeV (QF/QD)	10.28 / -8.40	T/m
Magnetic length	1.0	m
Aperture radius	30	mm
Mass	400	kg
Number of magnets (QF/QD)	336 / 336	
Current @ 60 GeV (QF/QD)	380 / 310	A
Number of turns per pole	10	
Current density @ 60 GeV (QF/QD)	4.0 / 3.3	A/mm ²
Conductor material	copper	
Magnet inductance	4	mH
Magnet resistance	16	mΩ
Power @ 60 GeV (QF/QD)	2.3 / 1.5	kW
Total power consumption @ 60 GeV (QF/QD)	0.77 / 0.52	MW
Cooling	water	

Table 9.6: Main parameters of arc quadrupoles for the RR option.




Figure 9.11: Insertion and by-pass quadrupole magnets for the RR Option (scale 1:5).

Beam energy	10 to 60	GeV
Field gradient @ 60 GeV	19	T/m
Magnetic length (QD/QF)	1.0 / 0.7	m
Aperture radius	30	mm
Mass (QD/QF)	560 / 390	kg
Number of magnets (QD/QF)	148 / 148	
Current @ 19 T/m	420	A
Number of turns per pole	17	
Current density @ 19 T/m	4.6	A/mm ²
Conductor material	copper	
Magnet inductance (QD/QF)	15 / 10	mH
Magnet resistance (QD/QF)	30 / 23	mΩ
Power @ 60 GeV (QD/QF)	5.3 / 3.9	kW
Total power consumption @ 60 GeV (QD/QF)	0.78 / 0.58	MW
Cooling	water	

Table 9.7: Main parameters of insertion and by-pass quadrupoles for the RR option.

9.2.3 LR option, dipole magnets

The bending magnets for the LR option are used in the arcs of the recirculator. Each of the six arcs needs $58 \times 10 = 580$ dipoles for the standard arc cells, plus $2 \times 2 = 4$ for the dispersion suppression regions at the two ends. This results in a total of 584 units. These magnets are 4 m long and they provide a magnetic field ranging from 0.046 T to 0.264 T depending on the arc energy, from 10.5 GeV to 60.5 GeV. Additionally, a few bending magnets (4 at each end of an arc) are needed for the switch-yards regions. These magnets – providing vertical bends – are in a separate category and are not considered at the moment.

Considering the relatively low field strength required even for the highest energy arc, and the small required physical aperture of 25 mm only, it is proposed here to adopt the same cross-section for all the magnets, possibly using smaller conductors for the ones at the lowest energies. This allows the design of very compact and relatively cheap magnets, running at low current densities to minimize the power consumption.

The choice of having 1-turn coils prompts the same comments as for the dipoles of the RR option. In this case, though, the maximum current is considerably higher (2700 A vs. 1300 A), although the overall dissipated power is lower.

Table 9.8 summarizes the main parameters of the proposed magnet design, which is illustrated in Fig. 9.12.

The proposed design is based on classical resistive electromagnets. The use of units embedding permanent magnets could be envisaged, given the (almost stationary) requirements on the field. The capital cost would be significantly higher, but savings would occur on the side of power supplies and interconnections, besides clearly on the electric bill.

9.2.4 LR option, quadrupole magnets

Quadrupoles for the recirculator arcs

In each of the six recirculator arcs, four different types of quadrupoles are needed, each type in 60 units, adding up to 240 quadrupoles per arc. The Q0, Q1 and Q3 magnets provide each about 35 T integrated strength, whereas the Q2 ones provide each about 50 T integrated strength. The required integrated gradients can be met with one type of quadrupole manufactured in two different length, 900 mm (for Q0, Q1 and Q3) and 1200 mm (for Q2). A few additional quadrupoles (of the order of 14 per arc) are needed for the switch-yard regions; these units are not included in the total count here.

As for the dipoles, also the quadrupoles in the different arcs may or may not have the same conductor, that is, it is possible to use a smaller conductor (or less turns) in the low energy arcs, or to use the same conductor everywhere and simply operating the first ones at a lower power. The relevant parameters are summarized in Table 9.9 and the cross-section is illustrated in Figure 9.13.

Also for the quadrupoles, it could be envisaged to use a hybrid configuration, with most of the excitation given by permanent magnets. The gradient strength could be varied by trim coils and/or by mechanical methods (see, for example, [762]).

Quadrupoles for the two 10 GeV linacs

In the two 10 GeV linacs, $37 + 37$ quadrupoles each providing 2.5 T integrated strength are required. The present design solution considers 70 mm aperture radius magnets to be compatible with any possible aperture requirement. The relevant parameters are summarized in Table 9.10 and the cross-section is illustrated in Figure 9.14.

The magnet could be more compact, but a bit longer to compensate for the lower gradient. Alternatively, one could consider superconducting magnets that could be hosted in the linac cryostats.

It could also be convenient to have in the two linacs, or at different positions along the acceleration, several families of quadrupoles with different apertures. Here a cross-section for the more demanding ones is reported.




Figure 9.12: Bending magnets for the LR recirculator (scale 1:5).

Beam energy	10.5 to 60.5	GeV
Magnetic field	0.046 to 0.264	T
Magnetic length	4.0	m
Vertical aperture	25	mm
Pole width	80	mm
Mass	2000	kg
Number of magnets	$6 \times 584 = 3504$	
Current @ 60.5 GeV	2700	A
Number of turns per pole	1	
Current density @ 0.264 T	0.7	A/mm ²
Conductor material	copper	
Magnet inductance	0.08	mH
Magnet resistance	0.08	m Ω
Power @ 10.5 GeV	20	W
Power @ 20.5 GeV	65	W
Power @ 30.5 GeV	150	W
Power @ 40.5 GeV	260	W
Power @ 50.5 GeV	405	W
Power @ 60.5 GeV	585	W
Total power consumption six arcs	0.87	MW
Cooling	air	

Table 9.8: Main parameters of bending magnets for the LR recirculator. Resistance and powers refer to the same conductor size across the six arcs.




Figure 9.13: Quadrupoles for the recirculators of the LR option (scale 1:5).

Beam energy	10.5 to 60.5	GeV
Field gradient	41	T/m
Magnetic length (short/long)	0.9 / 1.2	m
Aperture radius	20	mm
Mass (short/long)	750 / 980	kg
Number of magnets (Q0+Q1+Q2+Q3)	$6 \times 240 = 1440$	
Current @ 41 T/m	400	A
Number of turns per pole	17	
Current density @ 41 T/m	4.8	A/mm ²
Conductor material	copper	
Magnet inductance (short/long)	17 / 22	mH
Magnet resistance (short/long)	30 / 40	mΩ
Power @ 10.5 GeV (short/long)	0.15 / 0.20	kW
Power @ 20.5 GeV (short/long)	0.55 / 0.74	kW
Power @ 30.5 GeV (short/long)	1.22 / 1.63	kW
Power @ 40.5 GeV (short/long)	2.15 / 2.87	kW
Power @ 50.5 GeV (short/long)	3.35 / 4.46	kW
Power @ 60.5 GeV (short/long)	4.80 / 6.40	kW
Total power consumption six arcs	3.17	MW
Cooling	water	

Table 9.9: Main parameters of quadrupoles for the recirculators of the LR option. Resistance and powers refer to the same conductor size across the six arcs.




Figure 9.14: Quadrupoles for the 10 GeV linacs of the LR option (scale 1:5).

Field gradient	10	T/m
Magnetic length	0.250	m
Aperture radius	70	mm
Mass (QD/QF)	440	kg
Number of magnets	37 + 37	
Current @ 10 T/m	460	A
Number of turns per pole	44	
Current density @ 10 T/m	5.0	A/mm ²
Conductor material	copper	
Magnet inductance	24	mH
Magnet resistance	25	mΩ
Power @ 10 T/m	5.3	kW
Cooling	water	

Table 9.10: Main parameters of quadrupoles for the 10 GeV linacs of the LR option.

8015 **9.2.5 LR option, corrector magnets for the two 10 GeV linacs**

8016 In the two 10 GeV linacs, 37 + 37 dipole (vertical / horizontal) correctors are needed. These combined
 8017 function correctors shall provide an integrated field of 10 mTm in an aperture of 140 mm. The relevant
 8018 parameters are summarized in Table 9.11 and the cross-section is illustrated in Figure 9.15.




Figure 9.15: Combined function corrector magnets for the LR option.

Magnetic field	25	mT
Magnetic length	0.400	m
Yoke length	0.250	m
Total length	0.350	m
Free aperture	140 × 140	mm × mm
Mass	100	kg
Number of magnets (QD+QF)	37 + 37	
Current	40	A
Number of turns per circuit	2 × 100	
Current density	1.5	A/mm ²
Conductor material	copper	
Magnet inductance per circuit	10	mH
Magnet resistance per circuit	0.1	Ω
Power per circuit	160	W
Cooling	air	

Table 9.11: Main parameters of combined function corrector magnets for the LR option.

9.3 Ring-Ring RF Design

9.3.1 Design Parameters

The RF system parameters for the e-ring are listed in Table 9.12. For a beam energy of 60 GeV the synchrotron losses are 437 MeV/turn. With a nominal beam current of 100 mA the rather significant amount of power of 47.3 MW is lost due to synchrotron radiation. For the voltages needed superconducting RF is the only choice.

9.3.2 Cavities and klystrons

Cavity design

The most important issue determining the RF design is not so much in achieving high accelerating gradient but rather the need to handle large powers through the power coupler. The choice of RF frequency is based on relatively compact cavities which are able to handle the relatively high beam intensities and allowing fitting of power couplers of sufficient dimensions to handle the RF power. A frequency in the range 600 to 800 MHz is the most appropriate. Cavities of frequency of 704 MHz are currently being developed at CERN in the context of the study of a Superconducting Proton Linac (SPL) [763] [764] [765]. The same frequency is also used at BNL for ERL cavities for the RHIC upgrade project [766]. Both cavities are 5-cell and can achieve gradients greater than 20 MV/m. For the present study we take an RF frequency of 721.42 MHz, which is compatible with the minimum 25 ns bunch spacing in the LHC. An RF voltage of 500 MV gives a quantum lifetime of 50 hours; this is taken as the minimum operating voltage. An RF voltage of 560 MV gives infinite quantum lifetime and a margin of 60 MV which permits feedback system voltage excursions and provides tolerance to temporary failure of part of the RF system without beam loss.

5-cell cavities would require too much RF power transferred through the power coupler, therefore we use 2-cell cavities here in keeping the cell shape. Then with a total of 112 cavities, the power per cavity supplied to the beam to compensate the synchrotron radiation losses is 390 kW. This level of power handling is only just reached for the power couplers of the larger 400 MHz cavities of the LHC. It is therefore proposed to use two power couplers per cavity and split the power. In terms of voltage, only 5 MV per cavity is required to make 560 MV, hence it is sufficient to use cavities with two cells instead of five. The resulting cavity active length is 0.42 m and the gradient is 11.9 MV/m. Under these conditions the matched loaded Q is $2.8 \cdot 10^5$. Over-coupling by 50 % to $1.9 \cdot 10^5$ provides a stability margin and incurs relatively small power overhead. Under this condition the average forward power through the coupler is just under 200 kW. This nevertheless remains challenging for the design of power coupler.

Cryomodule layout

With 8 cavities per cryomodule there are a total of 14 cryomodules. The estimated cryomodule length, scaled from the 8 5-cell cavity of SPL to two cells per cavity is 10 m. There are 8 double cell cavities in 14 10m cryomodules, the total RF cryomodule length is therefore 140 m, but space must be allowed for quadrupoles, vacuum equipment and beam instrumentation. A total of 208 m is available in the by-passes: 124 m at CMS and 2 x 42m at ATLAS. Eight cryomodules can therefore be installed in the CMS bypass and six, three on each side, in the ATLAS by-passes. The distance between the modules can be taken as 3 m to allow space for the other equipment. The positioning of the RF tunnels in the CMS and ATLAS bypasses is shown in Figure 9.16.

RF Power System

The configuration for powering the eight cavities within one cryomodule is shown in figure 9.17. Each klystron feeds two cavities with power being split near the cavity to its two couplers. Taking two cavities per klystron with an estimated 7 % losses in the waveguide system gives a mean required klystron output power of 870 kW. A 15 % margin for the feedbacks gives a klystron rated power of 1 MW. The total number

Energy	GeV	60
Beam current	mA	100
Synchrotron losses	MeV/turn	437
Power loss to synchrotron radiation	MW	43.70
Bunch frequency (25 ns spacing)	MHz	40.08
Multiplying factor		18
RF frequency	MHz	721.42
Harmonic number		64152
RF Voltage for 50 hour quantum lifetime	MV	500.00
Nominal RF voltage (MV)	MV	560.00
Synchronous phase angle	degrees	129
Quantum lifetime at nominal RF voltage	hrs	infinite
Number of cavities		112
Number of 8-cavity cryomodules		14
Power couplers per cavity		2
Average RF power to beam per power coupler	kW	195
Voltage per cavity at nominal voltage	MV	5.00
Cells per cavity		2
Cavity active length	m	0.42
Cavity R/Q	linac Ω	114
Cavity Gradient	MV/m	11.90
Cavity loaded Q (Matched)		$2.8 \cdot 10^5$
Cavity forward power (nom. current, nom. voltage) for matched condition	kW	390
Nominal cavity loaded Q (matched for 50 % more beam)		$1.9 \cdot 10^5$
Cavity forward power (nominal current, voltage & loaded Q)	kW	406
Forward power per coupler	kW	203
Number of cavities per klystron		2
Waveguide losses	%	7
Klystron output power	kW	870
Feedbacks & detuning power margins	%	15
Klystron rated power	kW	1000
Total number of klystrons		56
Total average operating klystron RF power	MW	49
DC power to klystrons assuming 65% klystron efficiency	%	75
Grid power for RF, assuming 95% efficiency of power converters	MW	79

Table 9.12: RF system parameters for the electron ring.




Figure 9.16: RF tunnel Layouts at CMS and ATLAS bypasses. Note only the right hand side at ATLAS shown.

8063 of klystrons is 56, delivering an average total RF power of 49 MW. Taking 65 % klystron efficiency and 95 %
 8064 efficiency in the power converters gives roughly 79 MW grid power needed for the RF power system.

8065 **RF Power System Layout**

8066 The klystrons are installed in the additional tunnels parallel to the by-passes. An estimated surface area of
 8067 100 m^2 is needed for the two klystrons, circulators, HV equipment and Low Level RF and controls racks for
 8068 each 8 cavity module in adjacent RF gallery. This defines the tunnel width over the 13 m module interval
 8069 (length + spacing) to be 8 m. Waveguide ducts are needed between the by-passes and the RF tunnels. With
 8070 one waveguide per klystron into the tunnel, and two waveguides per duct, there are 16 ducts in the CMS
 8071 tunnels, spaced roughly 6.5 m apart. At ATLAS there would be six ducts on either side with the same
 8072 spacing. The required diameter of the duct tunnel is 90cm.




Figure 9.17: Layouts of RF power equipment in bypass and in RF gallery for one cryomodule.

8073 **Surface Installations**

8074 One HV Power Converter rated at 6 MVA is needed per 4 klystrons. These are housed in surface buildings:
 8075 eight converters at CMS, and six at ATLAS.

8076 **Conclusions**

8077 721.4 MHz RF systems can be just fitted in the two bypasses nearest ATLAS and CMS. Detailed studies need
 8078 to be done on the optimization of the cavity geometry for the high beam current and ensuring acceptable
 8079 transverse impedance. The RF power system is large. Further work is needed on integration to exactly
 8080 define tunnel and cavity cavern layouts and quantify the space requirements. Phased installation with
 8081 gradual energy build-up, as was done for LEP, is an interesting possibility. The power needed for RF is
 8082 79 MW. To this must be added power for RF controls, cryogenics and all other machine equipment.

8083 **9.4 Linac-Ring RF Design**

8084 **9.4.1 Design Parameters**

8085 The ERL design [767] [768] [769] is based on two 10 GeV linacs, with a 0.3 GeV injection energy and 6 linac
 8086 passes to reach 60 GeV. This is shown in Figure 8.5.

Arc	Arc energy [GeV]	Energy loss per arc passage [MeV]	Number of passages	Beam current in arc [mA]	Total energy loss per arc [MeV]
6	60	751.3	1	6.6	751.3
5	50	362.3	2	13.2	724.6
4	40	148.4	2	13.2	296.8
3	30	47.0	2	13.2	94.0
2	20	9.3	2	13.2	18.6
1	10	0.6	2	13.2	1.2
		1319.9			1886.5

Table 9.13: Energy losses in the arcs on a half circle of 764 m radius

8087 The overall parameters are given in Table 8.1. With a beam current of 6.6 mA produced, there are
8088 currents of nearly 20 mA in both directions in the linacs. Significant power, greater than the injection
8089 energy, is lost in the passages though the arcs due to synchrotron radiation as shown in Table 9.13.

8090 The energy loss in the arcs can be compensated by independent RF systems operating at twice the normal
8091 RF frequency. As proposed by [720,770] it could be envisaged to let the main linacs replace the energy lost
8092 to synchrotron radiation, i.e. the linacs had to supply about 0.75 GeV and 0.36 GeV, respectively, more
8093 voltage (maximum energy loss per turn for arc 6 and 5, table 9.13). However, this scheme significantly
8094 restricts operational freedom and is not tested yet. Therefore we keep it only as one possible option. For
8095 the present report only the case for additional RF systems in the arcs compensating synchrotron radiation
8096 losses is shown.

8097 Linac design

8098 High accelerating gradient is needed. First tests on cavities at similar frequency at BNL have already reached
8099 20 MV at Q_0 of $2.5 \cdot 10^{10}$. Improved cavity design and careful cavity processing should allow meeting the
8100 specifications. The optimum number of cavities and the gradient is an overall compromise taking into account
8101 cost, cryogenics consumption and operational reliability. The RF power system needs to compensate energy
8102 loss and non-ideal energy recovery due to beam losses, phasing errors, transients, ponderomotive effects and
8103 noise. It also needs to allow testing and processing of the cavities at full gradient without circulating beam.
8104 The main RF parameters are given in Table 9.14, for the two cases described above.

8105 The linac RF design is based on 5-cell cavities operating at 721.42 MHz, this frequency being compatible
8106 with 25 ns bunch spacing in LHC, as for the electron ring option. A gradient of 20 MV/m can be taken.
8107 This is a conservative estimate based on SPL type cavities presently being developed, with a design aim of
8108 25 MV/m. The unloaded Q (Q_0) is taken as $2.5 \cdot 10^{10}$. This is presently a challenging figure, but recent
8109 tests on cavities at this frequency for e-RHIC have been very encouraging. With an active cavity length of
8110 1.04 m the voltage is 20.8 MV per cavity. This requires 960 cavities in total, or 480 cavities per linac. The
8111 cavity external Q (Q_{ext}) is derived from optimum coupling to the required beam power to compensate the 4
8112 energy losses. It should be noted that the 300 MeV injection linac, with nearly 2 MW beam power will also
8113 take grid power of between 3 and 4 MW.

8114 9.4.2 Layout and RF powering

8115 Cryomodule and RF power system layout

8116 With eight cavities in a cryomodule, there are 60. cryomodules per linac with a total linac length of 990 m.
8117 This is summarized in table 9.15.

Parameter	Unit	Main RF system
Beam energy	GeV	60.0
Injection energy	GeV	0.3
Average beam current out	mA	6.6
Av. accelerated beam current in linacs	mA	19.8
Required total voltage in both linacs	GV	20.0
Energy recovery efficiency	%	96
Total power needed to compensate recovery losses	MW	15.8
RF frequency	MHz	721.42
Gradient	MV/m	20
Cells per cavity		5
Active cavity length	m	1.04
Cavity voltage	MV	20.8
Number of cavities		960
Energy gain per cycle	GeV	20
Power to compensate recovery losses per cavity	kW	16.5
Cavity R/Q	circuit Ω	285
Cavity unloaded Q [Q_o]	10^{10}	2.5
Loaded Q [Q_{ext}]	10^6	46
Cavity forward power	kW	16.5
Cavity forward power - no beam	kW	4.1
Number of cavities per solid state amp.		1
Transmission losses	%	7
Amplifier output power per cavity	kW	17.6
Feedbacks power margin	%	15
Amplifier rated power	kW	21
Total number of amplifiers		960
Total average amplifier output power	MW	16.9
Assumed overall conversion efficiency grid to amplifier RF output	%	70
Grid power for linacs RF (without cryogenics power)	MW	24

Table 9.14: Linac RF parameters.

Parameter	Unit	Value
Number of cryomodules		60
Cavities per cryomodule		8
Number of cavities		480
Module length incl. bellows, vac. pumps, cold-warm transitions, BPM, $\frac{1}{2}$ quad	m	15.5
Linac length	m	990

Table 9.15: ERL cryomodule numbers and length.

8118 RF power system

8119 Assuming optimum coupling the forward power per cavity is approximately 16.5 kW. The available power
8120 per cavity must be somewhat higher to allow margin for operation of RF the feedback systems; i.e. 21 kW.
8121 These levels can certainly be achieved with solid state amplifiers, avoiding the need for high voltage power
8122 supplies and associated protection equipment. The grid to RF conversion efficiency is also somewhat higher;
8123 70 % can be taken. The total supplied average RF power is 17 MW and the grid power required for powering
8124 of the linacs is 24 MW.

8125 RF Power system layout

8126 The RF amplifiers and RF feedback and controls racks are housed in a separate parallel powering gallery.
8127 There is one RF amplifier per cavity, the power being fed by WR1150 standard waveguides, each 11.5 inches
8128 by 5.75 inches (30 cm by 15 cm). The number of holes between the powering and linac tunnels can be limited
8129 to one per four cavities, i.e. two per cryomodule, spaced 8 m apart giving 118 holes per linac. The diameter
8130 is 90cm. The diameters could be reduced if half height waveguides or coax lines are used.

8131 9.4.3 Arc RF systems

8132 Table 9.13 shows the synchrotron radiation losses in the arcs; they are negligible in the 10 GeV arc. In the
8133 20, 30, 40 and 50 GeV arc both the accelerated and decelerated beams pass the same arc RF system with
8134 180° phase shift at the basic frequency of 721.42 MHz; hence to accelerate both beams, the arc RF system
8135 is operated at twice the frequency, i.e. at 1442.82 MHz. The 60 GeV arc carries only the decelerated beam
8136 and there one can use the linac RF cavities at 721.42 MHz. However, since here the required power per
8137 cavity is much larger the solid state amplifiers of the main linac cannot be used but a klystron or IOT must
8138 be applied. Overall parameters for these RF systems are given in Table 9.16.

8139 The arc systems provide very different voltages. Parameters for the individual systems are given in
8140 table 9.17. Use of cavities and cryostats scaled to those in the linacs is assumed; however short cryostats
8141 containing four cavities could be used in the 20 and 40 GeV arc systems. Powering would be by klystrons,
8142 at 1442 MHz a total of 31 rated at a maximum of 360 kW with one klystron supplying two cavities and at
8143 721 MHz 10 klystrons of 680 kW with one klystron supplying four cavities.

8144 9.5 Crab crossing for the LHeC

8145 Due to the very high electron beam energies in the LHeC and the associated interaction region design, the
8146 emitted synchrotron radiation and the required RF power are challenging. The IR layout for the RR option
8147 consists of a crossing angle to mitigate parasitic interactions and allows for a simple scheme to accommodate
8148 the synchrotron radiation fan. A crab crossing scheme for the proton beam is highly desirable to recover the
8149 geometric luminosity loss due to this crossing angle. Some issues associated with the complexity of the IR

Parameter	Unit	Value
Total energy loss in 20-60GeV arcs	MeV	1885.3
Power loss in 20-60GeV arcs	MW	12.4
Arc RF frequency	MHz	1442/721
Number of cavities	-	58/38
Number of klystrons	-	31/10
Total average supplied klystron RF power	MW	10.5
Assumed overall conversion efficiency - grid to klystrons RF out	%	60
Grid power for arc RF systems	MW	23

Table 9.16: Arc RF systems overall parameters.

Parameter	Unit	Arc 2	Arc 3	Arc 4	Arc 5	Arc 6	Totals
Arc energy	GeV	20	30	40	50	60	
Energy lost per arc passage	MeV	9.3	47.0	148.4	362.3	751.3	
Number of passes		2	2	2	2	1	
Total beam current in arc	mA	13.2	13.2	13.2	13.2	6.6	
Power loss in arc	MW	0.1	0.6	2.0	4.8	5.0	12.4
RF frequency 1442 MHz	MHz	x	x	x	x		
RF frequency 721 MHz	MHz					x	
Max. acc. gradient	MV/m	20.0	20.0	20.0	20.0	20.0	
Max. acc. voltage	MV	10.4	10.4	10.4	10.4	20.8	
Cavities at 1442 MHz		1	5	156	37		38
Cavities at 721 MHz						40	41
Required voltage/cavity	MV	9.6	8.1	9.6	9.6	19.0	
RF Power/cavity	kW	123	124	131	129	130	
Nominal RF power/cavity	kW	128	129	136	135	136	
Klystron output power per cavity	kW	137	138	146	144	145	
Kl. rated power/cavity	kW	160	160	170	170	170	
Cavities/klystron		2	2	2	2	4	
Klystron rated power	kW	320	320	340	340	780	
Klystrons at 1442 MHz		1	3	8	19	-	31
Klystrons at 721 MHz	-	-	-	-	-	10	10
Total average supplied klystron RF power	MW	0.1	0.5	1.7	4.0	4.2	10.5
Assumed overall conversion efficiency grid to klystrons total RF power	%	60	60	60	60	60	
Grid power arc RF systems	MW	0.2	1.2	3.6	8.9	9.2	23

Table 9.17: Parameters of the individual arc RF systems.

8150 design and the associated synchrotron radiation can be relaxed with the implementation of crab crossing near
8151 the IR. A crab crossing scheme would also provide a natural knob for regulating the beam-beam parameter
8152 if required. Although the linac-ring option plans to employ separation dipoles and mirrors for synchrotron
8153 radiation, crab crossing can prove to be a simpler option if the technology is viable.

8154 9.5.1 Luminosity Reduction

8155 In the nominal LHC with proton-proton collision, the two beams share a common vacuum chamber for
8156 approximately a 100m from the IP. Therefore, a crossing angle is required in the IRs to avoid parasitic inter-
8157 actions. Consequently, the luminosity is reduced by a geometrical reduction factor which can be expressed
8158 as

$$R = \frac{1}{\sqrt{1 - \Phi^2}} \quad (9.1)$$

8159 where $\Phi = \sqrt{\theta\sigma_z/2\sigma_x}$ is the Piwinski parameter, which is proportional to ratio of the longitudinal and
8160 transverse beam sizes in the plane of the crossing.

8161 Reducing β^* at a constant beam-to-beam separation in the IRs ($\sim 10\sigma$), the luminosity reduction factor
8162 can become quite significant. To compensate for this reduction from the crossing angle, a crab crossing
8163 scheme is proposed and R&D is moving rapidly to realize the technology [771, 772].

8164 For the electron-proton collisions, the Piwinski parameter can be redefined as

$$\Phi_p = \frac{\theta_c}{2\sqrt{2}\sigma_x^*} \sqrt{\sigma_{z,p}^2 + \sigma_{z,e}^2} \quad (9.2)$$

8165 where $\sigma_{z,p}$ and $\sigma_{z,e}$ are the proton and electron bunch lengths. Table 9.18 lists the relevant parameters of
the crossing schemes in the LHeC as compared to some other machines.

	KEK-B	LHC		LHeC		eRHIC
		Nominal	Upgrade	RR	LR	
θ_c [mrad]	22.0	0.285	0.4-0.6	1.0	0.0 (4.0)	0.0 (5.0)
σ_z [cm]	0.7	7.55		7.55 (0.7 [†])		20/1.2 [†]
σ_x^* [μm]	103	16.6	11.2	30 (15.8 [*])	-	32
Φ	0.75	0.64	1-1.4	0.9 (1.6 [*])	0.0	0.0 (11.0)

Table 9.18: Relevant parameters of the crossing schemes in the LHeC compared to LHC, KEK-B and eRHIC. Note [†] corresponds to electrons and ^{*} corresponds vertical plane.

8166

8167 9.5.2 Crossing Schemes

8168 Since the bunch length of the electrons are significantly smaller (at least factor 10) than that of the protons,
8169 the geometrical overlap due to crossing angle is mainly dominated by the angle of the proton bunches. Four
8170 different cases (see Fig. 9.18) were simulated to determine the luminosity gain in the different cases with
8171 crab cavities and comparing it to the nominal case (see Table 9.19).

8172 The luminosity gains strongly depend on the choice of RF frequency as the reduction factor due to the
8173 RF curvature at frequencies of interest (0.4-0.8 GHz) is non-negligible.

8174 9.5.3 RF Technology

8175 The required cavity voltage can be calculated using

$$V_{crab} = \frac{2cE_0 \tan(\theta_c/2) \sin(\mu_x/2)}{\omega_{RF} \sqrt{\beta_{crab} \beta^*} \cos(\psi_{cc \rightarrow ip}^x - \mu_x/2)} \quad (9.3)$$




Figure 9.18: Schematic of different crossing schemes using crab cavities on either proton or electron beams as compared to the head-on collision. Top: Crabbing of both beams; Second from top: crabbing of the proton beam only; Third from top: crabbing of electron beam only; Bottom: no crabbing at all.

Scenario	L/L ₀	
	400 MHz	800 MHz
X-Angle (1 mrad)	1.0	
Uncross both e^- and p^+	1.88%	1.48
Uncross only e^-	1.007	
Uncross only p^+	1.88	1.48

Table 9.19: Luminosity gains computed for different crossing schemes with crab cavities and a crossing angle of 1 mrad.

8176 where E_0 is the beam energy, ω_{RF} is the RF frequency of the cavity, β_{crab} and β^* are the beta-functions
8177 at the cavity and the IP respectively, $\psi_{cc \rightarrow ip}^x$ is the phase advance from the cavity to the IP and μ_x is the
8178 betatron tune. The nominal scenarios for both proton-proton and electron-proton IRs are anticipated to
8179 have local crab crossing with two cavities per beam to create a local crab-bump within the IR. Since the
8180 β -functions are typically large in the location of the crab cavities, a voltage of approximately 20 MV should
8181 suffice for crossing angles of approximately 1-2 mrad. The exact voltage will depend on the final interaction
8182 region optics of both the proton and the electron beams.

8183 To accommodate the crab cavities within the IR region, deflecting structures with a compact footprint are
8184 required. Conventional pill-box type elliptical cavities at frequencies of 400 MHz are too large to fit within
8185 the LHC interaction region constraints. The effort to compress the cavity footprint recently resulted in
8186 several TEM type deflecting mode geometries [772]. Apart from being significantly smaller than its elliptical
8187 counterpart, the deflecting mode is the primary mode of the TEM type cavity, paving the way to a new class
8188 of cavities at lower frequencies (400 MHz) which is preferred from the RF curvature point of view.

8189 Demonstration of a robust operation of such novel RF concepts with high deflecting gradients within the
8190 LHC constraints is the prerequisite for exploiting the crab crossing concept for the LHeC IR design. R&D
8191 on these novel concepts is already underway for the LHC upgrade. The issues of impedance, collimation and
8192 machine protection are similar to that of the implementation of the proton-proton IRs.

9.6 Ring Ring option power converters

9.6.1 Overview

The LHeC Ring-Ring Collider option at 60 GeV with normal conducting magnets could be compared to LEP phase 1 (60 GeV) in particular for the main magnet (MB and MQs) circuits. The emergence of IGBT (new power semiconductors) in the 1990s has permitted the development of new power converter topologies and today the SCR power converters are replaced by switch mode power converters. Here, the possible topologies of power converters and the powering strategies for the main magnet circuits (MB and MQ) are presented. The last paragraph concerns infrastructure needs for LHeC Ring-Ring Collider power converters.

9.6.2 Powering considerations

The characteristics of power converters depend mainly on the electrical parameters of magnet circuits (e.g. R, L or current) and on operating mode of the accelerator (eg Einj/Ecoll or time need to reach collision energy): The LHeC Ring-Ring Collider option could be compared to LEP Phase 1 and the main parameters to define the power converters are similar:

1. Time constants of the magnet circuits are low (< 1 s).
2. Time to reach collision energy is relatively long (> 1 min) with the consequence that the inductive voltages of the circuits ($L \cdot di/dt$) are low ($< 10\%$ resistive voltage).
3. Currents in the circuits are below 1 kA and the voltages below 500 V, except for main magnet (MB and MQ) circuits.

9.6.3 Power converter topologies

Based on the assumptions mentioned in the preceding paragraph, the needs for the LHeC could be covered by three power converter families.

1. 1 quadrant ($I > 0$ and $V > 0$) high power (> 0.5 MW) switch mode power converters for the main magnet circuits. Voltages and currents needed are achieved by putting sub-converters with maximum ratings of 800 A and 600 V in parallel and/or in series (see figure 9.19).




Figure 9.19: Possible topology for main magnet power converters To reduce harmonic currents sent to the CERN electrical network, the input diode rectifier could be replaced by active front-end rectifier.

2. 4 quadrant (I and V bidirectional) medium power (< 0.5 MW) switch mode power converters for corrector circuits and insertion quadrupole circuits (see figure 9.20).
3. 4 quadrant low power (< 2 kW) switch mode power converters for COD (see figure 9.21).

The advantages of switch mode power converters are mainly the following:

1. Better robustness against network disturbances.
2. No reactive power sent to the network.




Figure 9.20: Possible topology for corrector power converters.




Figure 9.21: Possible topology for COD power converters.

8223 3. Small power converters.

8224 But the disadvantages are:

- 8225 1. EMI (Electro-Magnetic Interference) constraints are more significant, but experience with LHC power
8226 converters has shown that solutions exist and can be easily implemented (shielding, earth connexions,
8227 etc...).
- 8228 2. Lower MTBF (Mean Time Between Failures), but the loss of MTBF could be compensated by redun-
8229 dancy strategies using additional sub-converters.

8230 9.6.4 Main power converters

8231 Main dipole power converters

8232 The Ring-Ring Collider option needs 3080 MB magnets and the characteristics of the circuit are given in
8233 table 9.20.

Current [A]	1300
Number of magnets	3080
Total magnet inductance [H]	0.462
Total magnet resistance [Ω]	0.493
Total magnet voltage [V]	640
Total magnet consumption [MW]	0.832
Total magnet length [m]	16478
Total circuit length [m]	54000

Table 9.20: Electrical characteristics of MB circuit.

8234 If the coils of the MB magnets could be used to interconnect the magnet (see figure 9.22), 30 km of
8235 DC cable can be saved and the output power of the MB converter can be reduced. For example, 54 km of
8236 1500mm² DC cable (reasonable cable size for 1300 A) is about 0.6 Ω and would need the same power and
8237 voltage as the magnets.

8238 Different strategies are possible to power the MB magnets: 1 or several independent circuits, as illustrated
8239 in figure 9.23.




Figure 9.22: Different possibilities to connect the MB magnets.




Figure 9.23: Different possibilities to power the MB magnets.

8240 In the case of a single main dipole circuit, to avoid a dipole moment, it is not possible to close the circuit
 8241 directly by doing a single loop. The circuit must be closed by return path close to the magnets path. 4
 8242 independent circuits solution seems to be the optimal solution:

- 8243 1. The total power is the same as that for the 1 circuit solution
- 8244 2. The voltage constraints for magnets are lower
- 8245 3. This solution allows different currents between sectors to compensate the SR energy losses.
- 8246 4. The LHC has shown that the current tracking between the different MB circuits is not an issue.

8247 To allow e^- and e^+ physics, mechanical or semiconductor polarity switches will be needed at the output
 8248 of the main dipole power converters (also for the MQ power converters).

8249 Main quadrupole power converters

8250 The Ring-Ring Collider option needs 2×368 magnets for the MQD et MQF circuits and the characteristics
 8251 of these circuits are given in table 9.21.

Current [A]	390
Number of magnets	2×368
Total magnet inductance [H]	2×1.104
Total magnet resistance [Ω]	2×5.888
Total magnet voltage [V]	2×2300
Total magnet consumption [MW]	2×0.900
Total magnet length [m]	2×441.6
Total circuit length [m]	2×27000

Table 9.21: Electrical characteristics of MQ circuits.

8252 The length of the MQ circuits is mainly dominated by the DC cable length and in this case it is important
 8253 to optimise the MQ circuits to reduce power and voltage requested to supply the two MQ circuits (magnets
 8254 and DC cables). The actual MQ magnet design optimises the DC cable part of the circuits with low current,
 8255 but not the magnet part with high resistance magnets. High current in the MQ circuits is disadvantageous
 8256 for the magnet part but not for the DC cable part of the circuits. An optimum must be sought with a current
 8257 between 0.5 kA and 1.5 kA to reduce power and voltage needed to supply the circuits and also to reduce
 8258 the global cost, material and electricity. Two options are possible for supplying the MQ magnets, shown in
 8259 figure 9.24. Two independent circuits or several circuits with trim power converters. The advantages and
 8260 disadvantages of each option must be studied in detail before taking a final decision, but in both cases the
 8261 total power and cost of the powering system will be similar.




Figure 9.24: Different possibilities to power the MQ magnets.

8262 9.6.5 Insertion and by-pass quadrupole power converters

8263 The Ring-Ring option requires 97 QF magnets and 97 QD magnets in insertion and bypass regions. To
 8264 obtain flexibility for the beam setting, these magnets could be powered individually. In this case the main
 8265 characteristics of these circuits are given in table 9.22.

Current [A]	385
Number of magnets per circuit	1
Number of circuits	97 + 97
Magnet inductance (QD/QF) [H]	0.012/0.009
Magnet resistance (QD/QF) [Ω]	0.04/0.03
Magnet voltage [V]	15.4/11.55
PC output voltage [V]	30
PC power [kW]	15

Table 9.22: Electrical characteristics of IPQ circuits.

8266 To allow e^- and e^+ physics, the insertion and bypass quadrupole power converters must be 4 quadrants
 8267 (second family of converter) to reverse the magnet currents when the physic type is changed. The use of
 8268 polarity switches to reverse the magnet currents would be too complex and too expensive for the 194 IPQ
 8269 (Individually Powered Quadrupole) circuits.

8270 **9.6.6 Power converter infrastructure**

8271 The magnets being resistive, there are no real advantages to install the power converters in the underground
8272 facilities. In this case, it is better to install them at the surface. This solution simplifies power converter
8273 operation and avoids possible issues with radiation. LEP infrastructure (buildings, shafts and AC network,
8274 etc...) can be reused for LHeC. However, this solution must be confirmed by a detailed integration study. If
8275 new infrastructure is needed for the power converters, it should be installed on the current CERN sites.

8276 **9.7 Linac-Ring option power converters**

8277 **9.7.1 Overview**

8278 The second option for the LHeC is a Linac-Ring accelerator with two 10 GeV Linacs and six recirculation
8279 arcs allowing several passes of the beam in the two linacs to reach the final beam energy of 60 GeV. As for
8280 the Ring-ring option, the needs for the Linac-Ring option could be covered by three IGBT power converter
8281 families: 1 quadrant high power converters, 4 quadrant medium power converters and 4 quadrants low
8282 power converters. Here, the different power converters of the linacs and recirculation arc main magnets are
8283 described. The last paragraph concerns infrastructure needs for Linac-Ring LHeC power converters.

8284 **9.7.2 Powering considerations**

8285 The power converter study for the Linac-Ring option is based on the assumption that the power converters
8286 are operated in DC. In this case the inductive voltage needed to ramp the current in the circuit can be
8287 ignored to define the characteristics of power converters. As for the Ring-Ring option, the power converters
8288 for the Linac-Ring option will be based on three IGBT power converter families:

- 8289 1. Family 1: 1 quadrant high power switch mode power converters for the main dipole and quadrupole
8290 magnets of recirculation arcs. To reverse the current in the circuit for e^- or e^+ physics, mechanical or
8291 semiconductor polarity switches will be installed at the output of the power converters.
- 8292 2. Family 2: 4 quadrant medium power switch mode power converters for corrector circuits and individ-
8293 ually powered dipole (IPD) and quadrupole (IPQ) circuits.
- 8294 3. Family 3: 4 quadrant low power switch mode power converters mainly for orbit corrector circuits.

8295 **9.7.3 Linac quadrupole and corrector power converters**

8296 Each linac is about 1.3 km long and contains 37 quadrupoles and 37 associated correctors.

8297 **Linac quadrupole power converters**

8298 For the design of linac main quadrupole power converters (Family 2), the assumption is that the magnet
8299 currents are similar (less than 10% of difference). In this case, two solutions are possible to power the
8300 magnets:

- 8301 1. Power each quadrupole magnet independently.
- 8302 2. Power the quadrupole magnets in clusters of 4 magnets with TRIM power converters to allow different
8303 currents in the magnets.

8304 The two powering options are shown in figure 9.25.

8305 Tables 9.23 and 9.24 give the main characteristics of the linac quadrupole circuits and power converters
8306 for the both solutions.

8307 The second solution, with clusters of four magnets, saves a factor of two in the cost of power converters and
8308 DC cables without a significant increase of the circuit complexity. In addition, the TRIM power converters
8309 can be similar to those used for linac orbit corrector circuits.




Figure 9.25: Different possibilities to power the linac quadrupoles magnets.

Circuit current [A]	500
Number of magnets per circuit	1
Number of circuits	37 + 37
Magnet inductance [H]	0.012
Magnet resistance [Ω]	0.024
DC cable section [mm ²]	500
Max. DC cable length [m]	1200
Max. DC cable resistance [Ω]	0.045
PC output voltage [V]	35
PC power [kW]	18

Table 9.23: Electrical characteristics of circuits for IPQ option.

Circuit Current [A]	500
Max. Nb. of magnets per circuit	4
Number of circuits	10 + 10
Magnet inductance [H]	0.012
Magnet resistance [Ω]	0.024
Main DC cable section [mm ²]	500
Trim DC cables section [mm ²]	50
Max. DC cable length [m]	1200
Max. main DC cable resistance [Ω]	0.045
Max. TRIM DC cable resistance [Ω]	0.45
Main PC output voltage [V]	75
Main PC output current [A]	500
Main PC output power [kW]	38
Trim PC output voltage [V]	40
Trim PC output current [A]	50
Trim PC output power [kW]	2

Table 9.24: Electrical characteristics of circuit for cluster option.

8310 Linac corrector power converters

8311 Each orbit corrector magnet of the linacs will be powered individually. The characteristics of the circuits
 8312 and power converters (family 3) are given in table 9.25.

Current [A]	40
Number of magnets per circuit	1
Number of circuits	37 + 37
Magnet inductance [H]	0.010
Magnet resistance [Ω]	0.1
DC cable section [mm ²]	50
Max. DC cable length [m]	1200
Max. DC cable resistance [Ω]	0.45
PC output voltage [V]	40
PC output current	50
PC power [kW]	2

Table 9.25: Electrical characteristics of linac COD.

8313 9.7.4 Recirculation main power converters

8314 6 recirculation arcs connect the two linacs together and allow several passes of the beam in the linacs to
8315 reach the final energy of 60 GeV. Each recirculation arc has one main dipole circuit (MB) and four main
8316 quadrupole circuits (MQ0, MQ1, MQ2 and MQ3).

8317 Main dipole power converters

8318 All the main dipole magnets of the same recirculation arc are powered in series. The main characteristics of
8319 the 6 main dipole power converters are described in table 9.26.

8320 To reduce the number of different types of power converter and simplify the LHeC operation, a modular
8321 approach will be chosen with two types of sub converters: [400 A/100 V] for the first three power converters
8322 and [750 A/200 V] for the last three converters. Desired PC output current is achieved by putting sub
8323 converters in parallel.

8324 Main quadrupole power converters

8325 Each recirculation arc has four MQ circuits with 60 magnets connected in series for each circuit, as shown
8326 in table 9.27.

8327 As for the MB circuits, the MQ power converters will be composed of sub converters connected in series
8328 to achieve the desired output voltage. For the first three recirculation arcs (10.5, 20.5 and 30.5 GeV), the
8329 MQ power converters will be composed of [210 A/170 V] sub converters. For the other three recirculation
8330 arcs, the sub converter ratings will be [420 A/680 V].

8331 9.7.5 Power converter infrastructure

8332 4 shafts are planned in the LHeC Linac-Ring option (see figure 9.26): Two at each end of the “TI2” linac
8333 (points 3 and 4) and two at each third of ”outside” linac (point 1 and 2).

8334 For the power converter installation, a solution with 4 surface buildings is proposed:

- 8335 • Two small buildings in points 1 and 2 for the “outside” linac power converters.
- 8336 • Two large buildings in points 3 and 4 for the “TI2” linac power converters and the recirculation arcs.

8337 Concerning the two small buildings, the area required for the power converter installation is estimated
8338 at 400 m² per building. The global AC consumption of the power converters is estimated at 0.5 MVA per
8339 building. Each building must be equipped with a 100 kW air-conditioning system to extract the power

Number of MB circuits	6
Number of magnets per MB circuit	600
Total magnet inductance per MB circuit [H]	0.060
Total magnet resistance per MB circuit [Ω]	0.060
DC cable section [mm ²]	1000
DC cable length [m]	1600
DC cable resistance [Ω]	0.030
PC output current @10.5 GeV [A]	367
PC output voltage @10.5 GeV [V]	33
PC output current @20.5 GeV [A]	734
PC output voltage @20.5 GeV [V]	66
PC output current @30.5 GeV [A]	1100
PC output voltage @30.5 GeV [V]	99
PC output current @40.5 GeV [A]	1467
PC output voltage @40.5 GeV [V]	132
PC output current @50.5 GeV [A]	1834
PC output voltage @50.5 GeV [V]	165
PC output current @60.5 GeV [A]	2200
PC output voltage @60.5 GeV [V]	198

Table 9.26: Electrical characteristics of recirculation arc MB circuits.

8340 converter losses. Concerning the two large buildings, the area required for power converter installation is
8341 estimated at 800 m² per building. In point 4 of LHeC (point 2 of LHC), a large part of SR2 is available for
8342 LHeC power converters. Per building, the electric power requirements are estimated at 1 MVA and cooling
8343 requirements at 200 kW.

8344 9.7.6 Conclusions on power converters

8345 From the power converter point of view, the two options of LHeC are similar. The power converter topologies
8346 will be based on diode input rectifiers with IGBT legs. The converters can be classified into three main
8347 families:

- 8348 • Family 1: 1 quadrant ($I > 0$ and $V > 0$) high power switch mode power converters for the main dipole
8349 and quadrupole circuits.
- 8350 • Family 2: 4 quadrant (I and $V > 0$ and < 0) medium power switch mode power converters for the
8351 correctors circuits and individual power dipole and quadrupole magnets.
- 8352 • Family 3: 4 quadrant and low power switch mode power converters mainly for the orbit corrector
8353 magnets.

8354 When the option has been chosen for the LHeC (Ring-Ring or Linac-Ring) the next studies should focus
8355 on the circuit definition and optimisation.

Number of MQ circuits	6×4
Number of magnets per MQ circuit	60
Total magnet inductance per MQ circuit [H]	0.9/1.2
Total magnet resistance per MQ circuit [Ω]	1.8/2.4
DC cable section [mm ²]	500
DC cable length [m]	6000
DC cable resistance [Ω]	0.2
PC output current @10.5 GeV [A]	69
PC output voltage @10.5 GeV [V]	140/170
PC output current @20.5 GeV [A]	138
PC output voltage @20.5 GeV [V]	280/340
PC output current @30.5 GeV [A]	207
PC output voltage @30.5 GeV [V]	420/510
PC output current @40.5 GeV [A]	276
PC output voltage @40.5 GeV [V]	560/680
PC output current @50.5 GeV [A]	345
PC output voltage @50.5 GeV [V]	700/850
PC output current @60.5 GeV [A]	414
PC output voltage @60.5 GeV [V]	840/1020

Table 9.27: Electrical characteristics of recirculation arc MQ circuits.

9.8 Vacuum

9.8.1 Vacuum requirements

In particle accelerators, beams are traveling under vacuum to reduce beam-gas interactions i.e. the scattering of beam particles on the molecules of the residual gas. The beam-gas interaction is dominated by the bremsstrahlung on the nuclei of gas molecules and therefore depends on the partial pressure, the weight and the radiation length [g/cm²] of the gas species. In presence of a photon-stimulated desorption, the residual gas is dominated by hydrogen (75%) followed by CO/CO₂ (24%) and 1% CH₄. Argon normally represents less than 1% of the residual gas if welding best practice for UHV applications is applied. It is to be noted that Argon is 67 times more harmful than hydrogen (H₂); CO₂, CO and N₂ are about 30 times worse than hydrogen and Methane is 10 times worse than hydrogen.

The beam-gas interactions are responsible for machine performance limitations such as reduction of beam lifetime (nuclear scattering), machine luminosity (multiple coulomb scattering), intensity limitation by pressure instabilities (ionization) and for positive beams only, electron (ionization) induced instabilities (beam blow up). The heat load induced by scattered protons and ions can also be an issue for the cryomagnets since local heat loads can lead to a magnet quench i.e. a transition from the superconducting to the normal state. The heavy gases are the most dangerous because of their higher ionization cross-sections. In the case of the LHeC, this limitation exists only in the experimental areas where the two beams travel in the same beam pipe. The beam-gas interactions can also increase the background to the detectors in the experimental areas (non-captured particles or nuclear cascade generated by the lost particles upstream the detectors) and the radiation dose rates in the accelerator tunnels. Thus, leading to material activation, dose rates to intervention crews, premature degradation of tunnel infrastructures like cables and electronics and finally higher probability of electronic single events induced by neutrons which can destroy the electronics in the tunnel but also in the service galleries.




Figure 9.26: LHeC Linac Ring civil engineering.

8379 The design of the vacuum system is also driven by severe additional constraints which have to be consid-
 8380 ered at the design stage since retrofitting mitigation solutions is often impossible or very expensive. Among
 8381 them, the vacuum system has to be designed to minimise beam impedance and higher order modes (HOM)
 8382 generation while optimising beam aperture in particular in the magnets. It has to provide also enough ports
 8383 for the pumps and vacuum diagnostics. For accelerators with cryogenic magnets, the beampipe has to be
 8384 designed to intercept heat loads induced by synchrotron radiation, energy loss by nuclear scattering, image
 8385 currents, energy dissipated during the development of electron clouds, the later building up only in presence
 8386 of positively charged beams.

8387 The integration of all these constraints often lead to a compromise in performances and in the case of
 8388 the LHeC, the compromise will differ between the Linac-Ring and the Ring-Ring options.

8389 9.8.2 Synchrotron radiation

8390 The presence of a strong synchrotron radiation has two major implications for the vacuum system: it has
 8391 to be designed to operate under the strong photon-induced stimulated desorption while being compatible
 8392 with the significant heat loads onto the beampipes. In the common beampipe, the photo-electrons generated
 8393 by the synchrotron radiation will dramatically enhance the electron cloud build-up and mitigation solutions
 8394 shall be included at the design stage. Furthermore, experience with LEP has shown that the Compton
 8395 scattering of the beam on photons coming from Blackbody radiation can have a significant effect on the
 8396 beam lifetime [773] [774]. In the following analysis, we have neglected this effect, assuming that a technical
 8397 solution can be found for keeping the beam vacuum chamber at sufficiently low temperatures. While this
 8398 does not impose a principle problem to the vacuum system design, it still requires a detailed technical study
 8399 for identifying a suitable solution for cooling the vacuum system in the presence of ca. 3 kW/m synchrotron

8400 radiation power.

8401 Synchrotron radiation power

8402 The synchrotron radiation power is an issue for the heat load deposited on the beam pipes and for its
8403 evacuation and will be the driving factor for the mechanical engineering of the beam pipes. Indeed, the
8404 heated surfaces will have a higher outgassing rates, the increase being exponentially dependent with the
8405 surface temperature (factor 10 for a $\Delta T = 50^\circ\text{C}$ increase). The synchrotron radiation power can be calculated
8406 with equation 9.4. Since scaling linearly with the beam intensity, I , with the power of 4 for energy, E , and
8407 inversely to power of 2 of the bending radius, the synchrotron radiation power in the Ring-Ring option is
8408 expected to be 45 times higher than LEP and locally at the by-passes, the power can be about 180 times
8409 higher. To be compared with the factor 10 expected in the bending and injection sections of the Linac-Ring
8410 option.

$$P[\text{W}/\text{m}] = 1.24 \times 10^3 \frac{E^4 I}{\rho^2} \quad (9.4)$$

8411 Photon-induced desorption

8412 The desorption rate depends on critical energy of the synchrotron light, ϵ_c , the energy which divides in two
8413 the emitted power. For most materials, the desorption rates vary quasi linearly with the critical energy
8414 (equation 9.5).

$$\epsilon_c(\text{eV}) = \frac{3 \cdot 10^{-7}}{R} \left(\frac{E_B}{E_0} \right)^3 \quad (9.5)$$

8415 $E_0 = 5.10^{-4}$ GeV for electrons, E_B is the energy of the beam and R the bending radius.

8416 For the LHeC, the beam energies will be equivalent to the LEP at start. Then, a similar value of the
8417 critical energy can be assumed allowing the comparison with LEP pressure observations. Figure 9.27 shows
8418 typical photo-desorption yields measured on copper and stainless steel samples. But the beam intensities
8419 being by far larger, the linear photon flux which scales linearly (equation 3) with energy and intensity and
8420 inversely with bending radius will increase significantly.

$$\Gamma[\text{photons}/\text{s}/\text{m}] = 7 \times 10^{19} \frac{EI}{\rho} \quad (9.6)$$

8421 For the Ring-Ring option (bending sections and by-passes), the linear photon flux is expected to be 45
8422 times larger than in LEP, to be compared to the factor 5 expected for the Linac-Ring option.

8423 The photon stimulated pressure rise, ΔP , depends linearly on the critical energy, on the beam energy and
8424 beam intensity as shown by equation 9.7. The temperature affecting the dependence of the desorption yield
8425 (equation 9.8 and 9.9), η , to the critical energy, ϵ_c the pressure rises will differ between surfaces at ambient
8426 temperature (equation 9.8) and at cryogenic temperature (equation 9.9).

$$\Delta P \propto \eta(\epsilon_c) EI \quad (9.7)$$

$$\text{at room temperature : } \eta \propto \epsilon_c \text{ and } \epsilon_c \propto E^3 \text{ such that } \Delta P \propto E^4 I \quad (9.8)$$

$$\text{at cryogenic temperature : } \eta \propto \epsilon_c^{2/3} \text{ and } \epsilon_c \propto E^3 \text{ such that } \Delta P \propto E^3 I \quad (9.9)$$

8427 Therefore, the photon stimulated pressure rise is expected to be 45 times higher than LEP for the Ring-
8428 Ring option, to be compared with the factor 30 for the Linac-Ring option.




Figure 9.27: Photodesorption yields measured on copper and stainless steel surfaces. To be noted that the desorption yields of methane, η_{CH_4} , is 50 times lower than η_{H_2} .

8429 Vacuum cleaning and beam scrubbing

8430 The dynamic pressure i.e. the pressure while operating the accelerator with beams will be dominated by the
 8431 beam-induced dynamic effects like stimulated desorption due to beam losses or synchrotron radiations or by
 8432 electron stimulated desorption in case an electron cloud is building-up.

8433 In presence of synchrotron radiation, the vacuum cleaning process which characterises the reduction of
 8434 the desorption yields (η) of a surface resulting from the bombardment of the surface by electrons, photons
 8435 or ions, significantly decreases the induced gas loads (3 – 4 orders of magnitude observed in LEP) improving
 8436 the dynamic pressure at constant pumping speed. This results in a progressive increase of the beam lifetime.

8437 In presence of an electron cloud, the beam scrubbing which characterises the reduction of the secondary
 8438 electron yield (SEY, δ) of a surface resulting from the bombardment of the surface by electrons, photons or
 8439 ions, significantly decreases the induced gas loads (2 – 3 orders of magnitude observed in SPS) improving
 8440 the dynamic pressure at constant pumping speed. Similarly to what happens with the vacuum cleaning, this
 8441 results also in a progressive increase of the beam lifetime.

8442 By default and mainly driven by costs and integration issues, the vacuum system of an accelerator
 8443 dominated by beam-induced dynamic effects is never designed to provide the nominal performances as from
 8444 “day 1”. Indeed, vacuum cleaning and beam scrubbing are assumed to improve the beampipe surface
 8445 characteristics while the beam intensity and beam energy are progressively increased during the first years
 8446 of operation.

8447 This implies accepting a shorter beam lifetime or reduced beam current during the initial phase; about
 8448 500 h of operation with beams were required for LEP to achieve the nominal performances. New technical
 8449 developments such as Non-Evaporable Coatings (NEG) shall be considered since significantly decreasing the
 8450 time required to achieve the nominal performances (Figures 9.28 and 9.29).

8451 9.8.3 Vacuum engineering issues

8452 The engineering of the vacuum system has to be integrated right from the beginning of the project. This
 8453 becomes imperative for the Ring-Ring option since it has to take into account the constraints of the LHC and
 8454 allow for future consolidations and upgrades. For the Linac-Ring option, the tangential injection and dump
 8455 lines will be in common with the LHC beam vacuum over long distances. The experience has shown that
 8456 the vacuum engineering shall proceed in parallel on the following topics: expertise provided to beam-related
 8457 components (magnets, beam instrumentation, radio-frequency systems, etc.), engineering of vacuum related






Figure 2: Pressure rise measured in the centre of the TiZrV coated test chamber before activation ($<1 \cdot 10^{20}$ photons/m) and after activation ($>1 \cdot 10^{20}$ photons/m).

Figure 9.28: NEG pumping speed for different gas species and pressure rises measured in presence of a photon flux before and after NEG activation.

Table 2: Summary of results from the activated test chamber

Gas	Sticking probability	Photodesorption yield (molecules/photon)
H ₂	~0.007	~1.5·10 ⁻⁵
CH ₄	0	2·10 ⁻⁷
CO (28)	0.5	<1·10 ⁻⁵
C _x H _y (28)	0	<3·10 ⁻⁸
CO ₂	0.5	<2·10 ⁻⁶



•C. Benvenuti et al. J.Vac Sci Technol A 16(1) 1998

Figure 9.29: Photon (left) and Electron (right) desorption yields.




Figure 9.30: Reduction of the secondary electron yield (SEY, δ) by Photons a) and Electron b) desorption yields.

8458 components (beampipes, bellows, pumping ports, etc.) and machine integration including the cabling and
 8459 the integration of the services.

8460 Basically, the vacuum system is designed to interconnect the beam related equipments installed on the
 8461 beam line (magnets, kickers, RF cavities, beam absorbers, beam instrumentation, etc.) and to provide
 8462 the adequate pumping speed and vacuum instrumentation. The vacuum components are often composed
 8463 by vacuum pipes, interconnection bellows, diagnostics, pumping ports and sector valves. The number of
 8464 pumps, vacuum diagnostics, bellows and ports will differ significantly between the two options discussed in
 8465 this CDR and also between vacuum sectors of the same accelerator.

8466 Vacuum pumping

8467 The vacuum system of the LHeC will be mainly operated at ambient temperature. These systems rely more
 8468 and more on NEG coatings since they provide a distributed pumping and huge pumping speed (Fig.2) and
 8469 capacity and reduce the outgassing and desorption yields (Fig.3-4). These coatings are compatible with
 8470 copper, aluminium and stainless steel beampipes. An alternative could be to use the LEP configuration
 8471 with NEG strips. This alternative solution has only the advantage of avoiding the bake out constraints for
 8472 the activation of the NEG coatings. A configuration of a distributed ion pumps is not considered since less
 8473 performing and only applicable in dipole magnets i.e. bending sections. In any case, ion pumps are required
 8474 as a complement of the NEG coatings to pump the noble gasses and methane to avoid the ion beam-induced
 8475 instability. Sublimation pumps are not excluded in case of local huge outgassing rates, NEG cartridges being
 8476 an interesting alternative since recent developments made by manufacturers include an ion pump and a NEG
 8477 cartridge in the same body.

8478 The roughing from atmosphere down to the UHV range will be obtained using mobile turbo-molecular
 8479 pumping stations. These pumps are dismantled prior to beam circulations.

8480 The part of the vacuum system operated at cryogenic temperature, if any, could rely on gas condensation if
 8481 the operating temperatures are below 2 K. Additional cryosorbing material could be required if an important
 8482 hydrogen gas load is expected. This issue still needs to be addressed. As made for the LHC, the parts at
 8483 cryogenic temperature must be isolated from the NEG coated part by sector valves when not at their
 8484 operating temperature to avoid the premature saturation of the NEG coatings.

8485 The pumping layout will be simpler for the Ring-Ring option since more space is available around the
 8486 beam pipes. The tighter tolerances for the Linac-Ring option make the integration and pumping layout
 8487 more delicate. However, the vacuum stability will be easier to ensure in the Linac-Ring option since only
 8488 the bending sections are exposed to the synchrotron radiation.

8489 Vacuum Diagnostics

8490 For both options, the radiation level expected will be too high to use pressure sensors with onboard electron-
8491 ics. Therefore, passive gauges shall be used, inducing additional cabling costs and need for gauge controllers.

8492 Vacuum Sectorisation

8493 The sectorisation of the beam vacuum system results from the integration of various constraints, the major
8494 being: venting and bake-out requirements, conditioning requirements (RF and HV devices), protection
8495 of fragile and complex systems (experimental areas and ceramic chambers), decoupling of vacuum parts at
8496 room temperature from upstream and downstream parts at cryogenic temperature thus non-baked, radiation
8497 issues, etc.

8498 For UHV beam vacuum systems, all-metal gate valves shall be preferred in order to allow for bake-out at
8499 temperature above 250°C. VITON-sealed valves even though the VITON has been submitted to a special
8500 treatment are not recommended nearby NEG coatings or NEG pumps since minor outgassing of Fluor will
8501 degrade the pump characteristics.

8502 In the injection and extraction regions, the installation of the sector valves will lead to integration issues
8503 since the space left between the beampipes with a tangential injection/extraction and the circulating beams
8504 is often limited. This could result in a long common beam vacuum which implies that the LHC beam vacuum
8505 requirements will apply to the LHeC part shared with LHC.

8506 Vacuum protection

8507 The distribution of the vacuum sector valves will be made in order to provide the maximum protection to
8508 the beam vacuum in case of failure (leak provoked or not). Interlocking the sector valves is not an obvious
8509 task. Indeed, increasing the number of sensors will provide more pressure indications but often results in
8510 a degradation of the overall reliability. The protection at closure (pressure rise, leaks) is treated differently
8511 from the protection while recovering from a technical stop with parts of the accelerator beampipe vented or
8512 being pumped down.

8513 The vacuum protections of the common beampipes between LHeC and LHC shall fulfill the strong LHC
8514 requirements. Indeed, any failure in the LHeC propagating to the LHC could lead to long machine downtime
8515 (several months) in case of an accidental venting of an LHC beam vacuum sector.

8516 HOM and Impedance implications

8517 The generation and trapping of higher order mode (HOM) resulting from the changes in beampipe cross-
8518 sections are severe issues for high intensity electron machines. Thus, the engineering design of LHeC must
8519 be inspired on new generation of synchrotron radiation light sources instead of the simple LEP design. All
8520 bellows and gaps shall be equipped with optimised RF fingers, designed to avoid sparking resulting from bad
8521 electrical continuity. Indeed, these effects could induce pressure rises and machine performance limitations.

8522 Bake-out of vacuum system

8523 An operating pressure in the UHV range (10^{-10} Pa) will be required for both options. This implies the use
8524 of a fully baked-out beam vacuum system. Two options are possible: permanent and dismountable bake out.
8525 The permanent solution could be an option for the Linac-Ring but has to be excluded for the Ring-Ring
8526 option for cost reasons. As done for the dipole chambers (bending sections) of LEP, hot pressurised water can
8527 be used but the limit at 150°C is a constraint for the activation of NEG coatings. Developments are being
8528 carried on at CERN to lower the activation temperature from 180°C down to 150°C but this technology is
8529 not yet available.

8530 Shielding issues

8531 The synchrotron radiation power is an engineering challenge for the beam pipes. Indeed, 50% of the radiation
8532 power hitting the vacuum chamber is absorbed in the beam pipe chamber (case of LEP aluminum chamber).
8533 The remainder 50%, mainly the high-energy part of the spectrum, escapes into the tunnel and creates severe
8534 problems like degradation of organic material and electronics due to high dose rates and formation of ozone
8535 and nitric acid could lead to severe corrosion problems in particular with aluminum and copper materials.

8536 In this respect, the Ring-Ring option is less favorable since the synchrotron radiation will be localized at
8537 the plane of the existing LHC cable trays and electrical distribution boxes in the tunnel. Similar constraints
8538 exist also for the Linac-Ring option but these zones are localized at the bending sections of the LHeC.

8539 Detailed calculations are still to be carried on but based on LEP design, a lead shielding of 3 to 8 mm
8540 soldered directly on the vacuum chamber would be required for 70 GeV beams. Higher energies could require
8541 more thickness. The evacuation of the synchrotron radiation induced heat load on the beam pipe wall and
8542 on lead shielding is a critical issue which needs to be studied. In case of insufficient heat propagation and
8543 cooling, the lead will get melted as observed in LEP in the injection areas. The material fatigue shall also
8544 be investigated since running at much higher beam current as compared to LEP, will increase the induced
8545 stress to the material and welds of the beampipes.

8546 As made in LEP, the best compromise to fulfill the above mentioned constraints is the use of aluminum
8547 beam pipes, covered by a lead shielding layer. The complex beam pipe cross-section required to optimize
8548 the water cooling of the beam pipe and shielding is feasible by extrusion of aluminum billets and the costs
8549 are acceptable for large productions. The large heat conductivity helps also the heat exchange. However,
8550 extruded aluminum beam pipes induce limitations for the maximum bake out temperature and therefore
8551 for the NEG coatings activation. Special grades of aluminum shall be used. The reliability of vacuum
8552 interconnections based on aluminum flanges is a concern at high temperature ($>150^{\circ}\text{C}$) and corrosion issues
8553 shall be addressed. The stainless steel beam pipes do not have these limitations but they have poorer heat
8554 conductivity and they are more difficult and costly to machine and shape.

8555 The LEP 110 GeV operation has shown the criticality of unexpected synchrotron radiations heating
8556 vacuum components and in particular the vacuum connections between pipes or equipments. Indeed, the
8557 flanges, by “offering” a thick path, are behaving as photon absorbers and heat up very quickly. Hence, at
8558 cool down and due to the differential dilatation, leaks are opening. In LEP, these unexpected SR induced
8559 heat loads resulted from orbit displacement in quadrupoles during the ramp in energy and of the use of the
8560 wigglers also during the ramp. In LHeC, resulting from the much higher beam current, these issues shall be
8561 carefully studied.

8562 Corrosion issues

8563 In vacuum systems, feedthroughs and bellows are particularly exposed to corrosion. The feedthroughs,
8564 particularly those of the ion pumps where high voltage is permanently present, are critical parts. A demon-
8565 strated and cheap solution to prevent the risk of corrosion consists in heating directly the protective cover
8566 to reduce the relative humidity around the feedthrough.

8567 The bellows are critical due to their thickness, often between 0.1 – 0.15 mm. PVC material must be
8568 prohibited in the tunnel. Indeed, in presence of radiations, it can generate hydrochloric acid (HCl) which
8569 corrodes stainless steel materials. This corrosion has the particularity to be strongly penetrating, once seen
8570 at the surface, it is often too late to mitigate the effects. Aluminum bellows are exposed to corrosion by
8571 nitric acid (HNO_3) which is generated by the combination of O_3 and NO .

8572 Humidity is the driving factor and shall be kept 50%. However, in the long term, accidental spillage can
8573 compromise locally the conditions and therefore, corrosion-resistant design are strongly recommended.

9.9 Beam Pipe Design

9.9.1 Requirements

The vacuum system inside the experimental sector has a number of different and sometimes conflicting requirements. Firstly, it must allow normal operation of the LHC with two circulating beams in the chamber. This implies conformity with aperture, impedance, RF, machine protection as well as dynamic vacuum requirements. The addition of the incoming electron beam adds constraints in terms of geometry for the associated synchrotron radiation (SR) fan and the addition of SR masks in the vacuum. Finally, optimization of the surrounding detector for high acceptance running means that all materials for chambers, instrumentation and supports must be optimized for transparency to particles and the central chamber must be as small and well aligned as possible to allow detectors to approach the beam aperture limit at the interaction point.

9.9.2 Choice of Materials for beampipes

LHC machine requirements imply an inner beam pipe wall that has low impedance (good electrical conductivity) along with low desorption yields for beam stimulated emissions and resistance to radiation damage.

Ideal materials for transparency to particles have low radiation length (Z) and hence low atomic mass. These materials either have poor (i.e. high) desorption yields (eg. aluminum, beryllium) or are not vacuum and impedance compatible (eg. carbon). Solutions to this problem typically include thin film coatings to improve desorption yields and composite structures to combine good mechanical properties with vacuum and electrical properties.

The LHC experimental vacuum systems, along with most other colliders currently use metallic beryllium vacuum chambers around the interaction points due to a very favourable combination of Z , electrical conductivity, vacuum tightness, radiation resistance, plus mechanical stiffness and strength. High desorption yields are suppressed by a thin film TiNiV non-evaporable getter (NEG) coating. This coating also gives a high distributed vacuum pumping speed, allowing long, small aperture vacuum chambers to be used that would otherwise be conductance-limited. Activation of this coating requires periodic heating of the chamber to $180-220^{\circ}\text{C}$ under vacuum for a few hours. This means that the chamber and environment must be designed for these temperatures. This activation is scheduled in annual LHC shutdowns. Long-term development is in progress for low desorption yield coatings that do not require high temperature activation [775]. These may have applications for LHeC.

Production technology developed for the LHC uses beryllium sections machined from hot-pressed blocks and electron beam welded to produce chambers. This has the advantage that a wide range of vacuum chamber forms can be manufactured. Cylindrical and conical chamber sections are installed in the LHC experiments.

Disadvantages of beryllium include high cost, fragility and toxicity in the powder form, as well as limited availability. For this reason, long-term development of other technologies for experimental beam pipes is under way at CERN which may yield applications for LHeC.

Composite beam pipe structures made from carbon and other low- Z materials have been developed for colliders. These typically use a thin inner membrane to comply with vacuum and impedance requirements. Composite structure pipes were eventually rejected for LHC application for reasons of temperature and radiation resistance and the risk of de-lamination due to mismatch of thermal expansion coefficients. Lower luminosity in LHeC experiments combined with new low temperature coatings may allow these materials to be re-evaluated.

9.9.3 Beampipe Geometries

The proposed geometry has a cross section composed of a half-circle intersecting with a half-ellipse. Cylindrical cross-sections under external pressure fail by elastic instability (buckling) whereas elliptical sections can (depending on the geometry) fail by plastic collapse (yielding).




Figure 9.31: Section through the LR geometry showing contours of Von Mises equivalent stress (Pa).




Figure 9.32: Section through the RR geometry showing contours of Von Mises equivalent stress (Pa).




Figure 9.33: 3-D view of the LR geometry showing contours of bending displacement [m].

8620 Figure 9.31 and 9.32 show optimizations of the proposed geometries for the LINAC-Ring (LR) and Ring-
 8621 Ring (RR) beam pipes assuming a long chamber of constant cross section made from beryllium metal.
 8622 Preliminary analyses have been performed using the ANSYS finite element code. The wall thickness was
 8623 minimized for the criteria of yield strength and buckling load multiplier. The LR geometry considered has
 8624 a circular section radius of 22 mm and elliptical major radius of 100 mm. The RR geometry has a circular
 8625 section radius of 22 mm and elliptical major radius of 55 mm. This preliminary analysis suggests that a
 8626 constant wall thickness of 2.5 – 3 mm for the LR and 1.3 to 1.5 mm for the RR would be sufficient to resist
 8627 the external pressure. Failure for both of these sections would be expected to occur by plastic collapse.

8628 At this stage of the project, these geometries represent the most optimized forms that fulfill the LHC
 8629 machine requirements. However, for 1 degree tracks this corresponds to $X/X_0 \approx 21\text{-}25\%$ for the LR and
 8630 $\approx 41\text{-}49\%$ for the RR designs. This suggests that additional effort must be put into beam pipe geometries
 8631 optimized for low angles. Composite beam pipe concepts suggested for machines such as the LEP [776]
 8632 should be re-considered in the light of advances in lightweight materials and production techniques.

8633 The optimized section of the experimental chamber is 6.1 m in length. This length will require a number of
 8634 optimized supports. These supports function to reduce bending deflection and stresses to within acceptable
 8635 limits and to control the natural frequency of chamber vibration. The non-symmetric geometry will lead to
 8636 a torsional stress component between supports which must be considered in their design. Figure 9.33 shows
 8637 a preliminary analysis of bending displacement for the LR chamber geometry. With 2 intermediate supports
 8638 the maximum calculated displacement (without bakeout equipment) is 0.21 mm.

8639 9.9.4 Vacuum Instrumentation

8640 If, as assumed, this chamber is coated with a NEG film on the inner surfaces, then a high pumping speed of
 8641 chemically active gasses will be available. Additional lumped pumps will be required for non-gettered gasses
 8642 such as CH_4 and noble gasses; however, outgassing rates for these gasses are typically very low.

8643 The vacuum sector containing the experiment will be delimited from the adjacent machine by sector
8644 valves. These will be used to allow independent commissioning of machine and experiment vacuum. The
8645 experimental vacuum sector will require pressure gauges covering the whole range from atmospheric to UHV,
8646 these are used both for monitoring the pressure in the experimental chamber and as interlocks for the machine
8647 control system.

8648 **9.9.5 Synchrotron Radiation Masks**

8649 LHeC experimental sector will require a moveable SR mask upstream of the interaction. From the vacuum
8650 perspective, this implies a system for motion separated from atmosphere by UHV bellows. The SR flux on
8651 the mask will generate a gas load that should be removed by a local pumping system dedicated to the mask.
8652 As the load due to thermally stimulated desorption increases exponentially with the temperature, cooling
8653 may be required. However, cooling the mask would significantly complicate the vacuum system design. The
8654 generation of photo-electrons must also be avoided since these photo-electrons can interact with the proton
8655 beam and lead to an electron cloud build-up.

8656 **9.9.6 Installation and Integration**

8657 The installation of the vacuum system is closely linked to the detector closure sequence. Therefore, the
8658 design has to be validated in advance to prevent integration issues which would lead to significant delay
8659 and increase of costs. Temporary supports and protections are required at each stage of the installation.
8660 Indeed, as compared to the size of the detectors, the beam pipe are small, fragile and need to be permanently
8661 supported and protected while moving the detector components. Leak tightness and bake-out testing are
8662 compulsory at each step of the installation since all vacuum systems are subsequently enclosed in the detector,
8663 preventing any access or repair. Their reliability is therefore critical. Precise survey procedures must also
8664 be developed and incorporated in the beam pipe design to minimize the mechanical component of the beam
8665 aperture requirement. Engineering solutions for bake out also has to be studied in details since the equipment
8666 (heaters, probes and cables) must fit within the limited space available between beam pipes and the detector
8667 components.

9.10 Cryogenics

9.10.1 Ring-Ring Cryogenics Design

Introduction

The Ring-Ring version foresees the 60 GeV accelerator to be installed in the existing LHC tunnel. Acceleration of the particles is done with 0.42 m long 5 MV superconducting (SC) cavities housed in fourteen 10 m long cryomodules. They will be placed at two opposite locations in by-passes of point 1 (ATLAS) and, point 5 (CMS). While at CMS a continuous straight by-pass can be built, at ATLAS two straight sections are conceived on each side of the detector cavern (“left” and “right”) with a connecting beam pipe crossing the detector hall. Lay-outs and detailed RF description see Chapter 9.3. The three separate cryomodules locations require three dedicated 2 K cryo-systems. Injection to the Ring at 10 GeV is done with a 1.3 GHz pulsed three-pass re-circulating high field injector. A dedicated cryoplant provides 2 K cooling of its SC cavities. In total four independent cryoplants with their respective distribution systems are needed for the Ring-Ring version. For the LHeC detector the high gradient focusing insertion magnets will be SC and housed in LHC dipole type cryostats. The cooling principle is the same as for LHC dipoles and, the existing cryogenic infrastructure can be used with comparatively small adaptations of the feed boxes. More detailed engineering studies are beyond the scope of this report. This chapter describes the cryosystems of the e-Ring accelerator and the related injector.

Ring-Ring cryogenics

The cavities operate at 2 K superfluid helium temperatures and dissipate an estimated 4 W per cavity at 5 MV. The 8-cavity cryomodule has three temperature levels; a 2 K saturated bath containing the cavities, a 5 – 8 K combined thermal shield and heat intercept for couplers and other equipment and, a 40 – 80 K thermal shield. The thermal loss estimates are listed in Table 9.28 . With efficiencies of modern state of the art cryoplants reaching 1/COP values of 1000 W/W at 2 K, 250 W/W at 5 K and 20 W/W at 40 – 80 K the minimum plant powers are calculated. To the equivalent cooling power at 4.5 K we add a 50% contingency for the distribution system with transfer lines running parallel to the cryomodules. In Table 9.29 the equivalent cooling powers of the three cryoplants are given.

Temperature (K)	2	5 – 8	40 – 80
One cryomodule			
Static loss (W)	5	15	100
Dynamic loss (W)	32	15	80
Sum (W)	37	30	180
8 modules (CMS site) (W)	296	240	1440(2160)
3 modules (ATLAS left) (W)	111	90	720(1080)
3 modules (ATLAS right) (W)	111	90	720(1080)

Table 9.28: Thermal loss estimate of cryomodules. In brackets the values with ultimate thermal losses (50% contingency) which are taken into account for the cryoplant sizing.

At CMS site a dedicated 3 kW @ 4.2 K cryoplant is needed. Except for some general infrastructure equipment like e.g. gas tanks it will be separated from the existing CMS cryoplant used to cool the solenoid magnet. Comparatively modest cooling powers suggest the use of a single compact refrigerator cold box, in contrast to split versions as proposed in this CDR for the Linac-Ring version described below. (The split version is based on LHC technology with a combined surface and underground cold box.) The cold box will be installed directly in the underground cavern at proximity to the cryomodule string. Ambient temperature high and low pressure lines make the link to the compressor stations on surface. For the 2 K

Site	Plant power @ 4.2 K (kW)
CMS site	3.0
ATLAS left	1.2
ATLAS right	1.2

Table 9.29: Cryoplant equivalent cooling powers.




Figure 9.34: Lay-out of the CMS by-pass with location of the cryomodules and the 3 kW @ 4.5 K cryoplant.

8701 temperature level two cold compressors with a total compression ratio of 10 are proposed followed by warm
8702 compressors to compress the gas to ambient pressure. Figure 9.34 shows the lay-out of the CMS by-pass
8703 region. At the two ATLAS sites (left, right) with three cryomodules each, two options are conceivable. The
8704 first consists of connecting to the LHC QRL transfer lines and their terminal feedboxes at vicinity for a
8705 “parasitic” use of excessive cooling power of the LHC cryoplants. For this two additional 10 – 15 m long
8706 perpendicular tunnels to connect the LHC tunnel with the LHeC by-pass would have to be constructed. The
8707 feasibility of this option and potential (negative) impacts have to be studied in more detail in a subsequent
8708 report. The second option is to use two dedicated cryoplants as proposed for the CMS site, however, with
8709 reduced capacity. Also in this case the cold box will be installed at proximity to the cryomodule strings in
8710 the cryo-hall. The two refrigerators are of the same design principle as for CMS, except for their size and
8711 capacity which is smaller. Their location will be on ATLAS terrain which allows to potentially use already
8712 existing cryogenic infrastructure of the large cryo-system for the cooling of the ATLAS toroidal and solenoid
8713 magnets. Among these are the gas storage tanks, the compressor hall and control rooms. Figure 9.35 shows
8714 the lay-out of the ATLAS by-pass region.




Figure 9.35: Lay-out of the ATLAS by-pass with locations of the cryomodules and the two 1.2 kW @ 4.5 K cryoplants.




Figure 9.36: Principle of the 10 GeV re-circulating Injector with high gradient pulsed SC cavities (23 MV/m) and 12 cryomodules of the ILC/XFEL type operating at 2 K.

8715 Cryogenics for the 10 GeV Injector

8716 The injector is a three-pass recirculating pulsed 10 Hz machine providing leptons at injection energies of 10
 8717 GeV to the LHeC Ring machine. Figure 9.36 shows its basic principle. Cryomodules of the XFEL (ILC)
 8718 type with 1.3 GHz superconducting cavities are proposed which allow the application of already existing
 8719 technology requiring little adaptation effort for LHeC. A 146 m long string will be composed of in total
 8720 12 cryomodules each 12.2 m long. Cryogen distribution is done within the volume of the cryostats. Bath
 8721 cooling is at 2 K saturated superfluid helium. Adopted from XFEL the common pump line of 300 mm
 8722 runs within the cryomodules envelope to collect vapor of all individual cavity baths. Therefore no external
 8723 transfer line is required which simplifies the overall design. The suction pressure of 30 mbar is provided by
 8724 cold compressors in the cold box and subsequent ambient temperature compressors. Two more temperature
 8725 levels of 5–8 K and 40–80 K are used for intercepts and thermal shielding. The operation of the injector at
 8726 LHeC is in part comparable to XFEL, this during the injection and loading phase of leptons into the LHeC
 8727 ring. During all other operation phases of a complete LHeC cycle (ramping to final particle energies in the
 8728 LHC/LHeC tunnel and subsequent physics runs) the injector machine is “idle”. Only static heat losses of
 8729 the cryomodules and the cryogenic infrastructure have to be intercepted during this time period. Principly a
 8730 reduced power cryogenic system operating with an “economizer” could be conceived, i.e. a large liquid helium
 8731 storage is filled during low demands which in turn boosts the cryomodules during the injection phases. A
 8732 simpler approach, however, is the design for constant (maximum) cooling power when active and, during idle
 8733 periods, internal electric heaters in the 2 K bath are switched on to keep the load constant. This principle
 8734 is adopted for these initial studies. A compact single refrigerator cold box providing temperatures from 300
 8735 K to 2 K will be installed in a protected area at vicinity to the extraction region of the cryomodule string
 8736 while the compressor set is at surface. For the estimation of power consumption and cooling performances
 8737 we shall use the experience gained at DESY during testing of XFEL cryomodules. With a final energy of
 8738 10 GeV and three pass operation the acceleration field required is 23 MV/m. At DESY power consumption
 8739 measurements have been made with cryomodules for a similar acceleration field of 23.8 MV/m and 10 Hz
 8740 operation. Our estimates as shown in the Table 9.30 are based on these recent data. With 1/COP values
 8741 as used in above chapter and a 50% margin for additional thermal losses we estimate the required cooling
 8742 power of the plant to 2 kW @ 4.5 K.

Temperature (K)	2	5 – 8	40 – 80
Static loss (W)	5	15	100
Dynamic loss (W)	8	3	40
Sum (W)	11	18	140
Sum 12 modules (W)	132(198)	216(324)	1680(2520)

Table 9.30: Thermal loss estimate of the 146 m long string built of 12 XFEL type cryo-modules. In brackets values with 50% contingency. Cryoplant equivalent cooling power; 2 kW @ 4.5 K.




Figure 9.37: Schematic proposal of the 14 m long cryomodules with eight 5-cell 721 MHz cavities operating at 2 K. Supply pipes and the 30 mbar pump line are within cryostat envelope. For the case with inclination right part is lower (only 2 K circuits are shown).

9.10.2 Linac-Ring Cryogenics Design

Location and basic lay-out

The ERL (Energy Recovery Linac) is of racetrack shape with two 1 km long straight SC acceleration sections and, two arcs of 1 km radius with normal conducting magnets. Location and lay-out studies made are described in chapter 10. The currently favored position is within the LHC perimeter (see Figure 10.9) versus the external version being largely under St. Genis community. For the “inside” version more of the newly required surface areas could be located on existing CERN grounds comprising SM18, North Area and, Point 2. Next steps following this CDR will require more detailed combined studies of civil engineering, RF, cryogenics and other services to try optimize the lay-out also, and in particular, for the cryogenic equipment having impact on its own complexity and costs. As base in this study we propose a symmetric lay-out with a sub-division of the respective 1 km long straight sections in four equally spaced sections each housing four 250 m long cryomodule strings. As indicated in chapter 10, the ERL will be inclined towards the Lake of Geneva by 1.4%, however, due to its orientation the tilt in longitudinal direction relevant to the cryogenics is smaller.

Cryomodules

Eight 721 MHz SC 5-cell cavities of length 1.04 m long will be housed in 14 m long cryomodules. Bath cooling of the cavities is done with slightly subcooled saturated superfluid helium at 2 K. Each cryostat is equipped with a J.T. valve located upstream to expand the 2 K supply helium to the 30 mbar bath pressure and the liquid is brought gravity assist to the downstream individual 8 cavity bath volumes via an interconnecting header pipe. This principle is similar to the SPL preliminary design which has to cope with a tilt of 1.7% [777]. Heat intercept and thermal shielding is at 5-8 K and 40-80 K. The final LHeC L-R cryomodule design can be based on extensive previous work and studies of both existing SC linear accelerators and, such being under construction or planned ones. Among these are CEBAF, ILC, XFEL, SPL, e-RHIC. For this study adapted TESLA/XFEL type cryomodules are proposed. Figure 9.37 shows a design proposal of a module with the eight cavities and the cold correction magnets in their individual bath. All cryogen distribution is done within the cryostat module which interconnects to the adjacent ones with the pipe runs throughout a 250 m long cryomodule string. Also the pump line is proposed to be within the cryostat envelope. The expected mass flow rate of 180 g/s at 2 K of a 250 m long section with 15 cryomodules (see calculations next chapter) is approximately comparable to XFEL for its entire machine for which the corresponding pump line diameter has been designed and tested [778]. The parameters of the LHeC SC cavities and cooling requirements are listed in Table 9.31.

Parameter	Value
Two linacs	length 1 km
5-cell cavities	length 1.04 m
Number	944
Cavities/ cryomodule	8
Number cryomodules	118
Length cryomodule	14 m
Voltage per cavity	21.2 MV
R/Q	285 Ω
Cavity Q_0	$2.5 \cdot 10^{10}$
Operation	CW
Bath cooling	2 K
Cooling power/cav.	32 W @ 2 K
Total cooling power (2 linacs)	30 kW @ 2 K

Table 9.31: Parameters and cooling requirements of the ERL (Linac-Ring version).

8774 Cryogenic System

8775 The estimated thermal loads per cavity are based on a voltage of 21.2 MV, an R/Q of 285 Ω and a Q_0
8776 of $2.5 \cdot 10^{10}$. With CW operation the dissipated heat per cavity will be 32 W, respectively 256 W per
8777 cryomodule. This consists of a very high load. The 1 km long straight sections are sub-divided in four 250 m
8778 long sub-sections each with 15 interconnecting cryomodules forming a string which are individually supplied
8779 by a respective refrigerator through local distribution boxes. Eight dedicated refrigerators supply the eight
8780 strings. Figure 9.38 gives a basic lay-out of the cryo-system with its sectorisation. The refrigerator cold boxes
8781 will be of the so-called “split” type with a surface cold box and a connecting underground cold box as explored
8782 and implemented first for LEP2 and later at a larger scale for LHC. The surface cold box will be installed
8783 close to the compressor set and produce temperature levels between 300 K and 4.5 K. The underground
8784 cold box will be installed at proximity to the respective cryomodule string in a protected area and produce
8785 the 2 K with cold compressors. Figure 9.39 gives a principle lay-out of the refrigerator configuration. The
8786 final location of the ERL will dictate civil engineering constraints and the “ideal” symmetric configuration
8787 of placement of the refrigerators as done here will have to be reviewed accordingly and, hence, partially
8788 deviate from this proposal. Also in case only one access shaft per linac can be conceived the four surface
8789 cold boxes may be installed in form of clusters around the pit while the four related 2 K underground cold
8790 boxes will be installed remotely close to the respective cryomodule string to be supplied as described above
8791 and shown in Figure 9.38. The total dynamic cooling power of the ERL with 944 cavities amounts to 30 kW
8792 @ 2 K. For the calculation of the cooling performances of the refrigerators in this document only the largely
8793 dominating dynamic thermal loads of the cavities are taken into account dwarfing all other thermal losses
8794 of the cryomodules which become negligible in a first order approach. Recent developments and industrial
8795 design of large scale refrigerator systems as for LHC [779] indicate the feasibility of a 1/COP of 700 W/W
8796 for 2 K large scale cryoplants. Hence, with this figure the total electric grid power amounts to 21 MW. The
8797 total equivalent refrigerator power at 4.5 K is estimated to 80 kW. This corresponds to about half of the
8798 installed cooling power at LHC. In case contingencies are taken into account in the engineering design the
8799 cooling capacity could approach LHC. For this preliminary study contingencies are omitted, this also in view
8800 of expected future improved cavity performances. Eight cryoplants with 10 kW @ 4.5 K each are proposed
8801 for the ERL. The technology to design and construct such units as well as the overall systems engineering is
8802 largely available today and can be based on experience from LHC, CEBAF, XFEL. Nevertheless it consists
8803 of an engineering challenge due to its sheer size and the large performance capacities required. Development
8804 work will have to be done for the cold compressors units together with detailed combined CERN/industrial




Figure 9.38: Basic lay-out of the 6 pass ERL. Two 1 km long SC acceleration sections with a 10 GeV linac each. Eight 10 kW @ 2 K cryoplants. Configuration such that each plant supplies a cryomodule string of 250 m length (figure not to scale).

8805 engineering design of the refrigerator cold boxes. Implementation and operation of such large systems will
 8806 consist of a complex task. Further cavities and cryomodules will require a limited R&D program. From this
 8807 we expect improved quality factors with respect to today's state of the art. The cryogenics of the L-R version
 8808 consists of a formidable engineering challenge, however, it is feasible and, CERN disposes of the respective
 8809 know-how.

Parameter	Value
Number of Refrigerators	8
1/COP @ 2 K	700
Minimum cooling capacity/refrigerator	10 kW @ 4.5 K
Contingency	none
Minimum total cooling power	80 kW @ 4.5 K
Grid power consumption	21 MW

Table 9.32: Refrigerator cooling capacity and power consumption (minimum cooling power).

8810 9.10.3 General Conclusions Cryogenics for LHeC

8811 These conclusions reference to the complete cryogenic contributions, i.e. for the detector cryogenics, the R-R
 8812 and the L-R version;

8813 The striking advantage of an extension from LHC to a LHeC lies, apart from the new physics, in the
 8814 comparatively small investment cost, the possibility of quasi undisturbed continuation of LHC hadron physics
 8815 and the fact that the technologies are largely already at hand today. This applies also to the cryogenic part.
 8816 No so-called "show-stoppers" could be detected during these studies. For the detector SC magnet and




Figure 9.39: Basic principle of a Split Cold Box lay-out (comparable to LHC accelerator cryogenics).

8817 LArgon cryogenics technologies developed and implemented at the ATLAS experiment can be used in a
 8818 “down-scaled” way. For the accelerator cryogenics the two options Ring-Ring and Linac-Ring differ strongly
 8819 in principle and investment. While for the R-R only four small to medium sized 2 K refrigerators are
 8820 required, for the cryomodules of the injector and the three LHC tunnel bypasses, the L-R option with two
 8821 1 km long CW operated 2 K SC cavities is extremely demanding. The total installed cryogenic power will
 8822 likely exceed 100 kW @ 4.5 K equivalent, approaching values of the LHC. However, these estimates are only
 8823 based on currently proved data of the cavity Q_0 . The development of high Q SC cavities is being pursued
 8824 in several laboratories and new encouraging results are on the horizon indicating improvement of quality
 8825 having positive and direct impact for cryogenic requirements and respective plant sizes.

9.11 Beam Dumps and Injection Regions

9.11.1 Injection Region Design for Ring-Ring Option

A 10 GeV recirculating Linac will be used to inject the electrons in the LHeC. This will be built on the surface or underground and a transfer line will connect the linac to the LHeC injection region. At this stage a purely horizontal injection is considered, since this will be easier to integrate into the accelerator. The electron beam will be injected in the bypass around ATLAS, with the baseline being injection into a dispersion free region (at the right side of ATLAS). Bunch-to-bucket injection is planned, as the individual bunch intensities are easily reachable in the injector and accumulation is not foreseen. Two options are considered: a simple septum plus kicker system where single bunches or short trains are injected directly onto the closed orbit; and a mismatched injection, where the bunches are injected with either a betatron or dispersion offset.

Injection onto the closed orbit

The baseline option is injection onto the orbit, where a kicker and a septum would be installed in the dispersion free region at the right side of ATLAS bypass (see Fig. 9.40). Injecting the beam onto the closed orbit has the advantage that the extra aperture requirements around the rest of the machine from injection oscillations or mismatch are minimised. The kicker and septum can be installed around a Defocusing




Figure 9.40: Injection optics is shown. The sequence starts ($s=0$) at the beginning of the dispersion suppressor at the left side of IP2 and proceeds clockwise, while the electron beam rotates counterclockwise (from right to left in the figure). The injection kicker and septum are installed in the dispersion free region of the bypass at the right side of ATLAS.

quadrupole to minimise the kicker strength required. The kicker-septum phase advance is 75° .

Some assumptions made to define the required element apertures are made in Table 9.33.

For the septum, an opening between injected and circulating beam of 47 mm is required, taking into account some pessimistic assumptions on orbit, tolerances and with a 4 mm thick septum. This determines

8846 the kicker strength of about 1 mrad.

Orbit variation	± 4 mm
Injection precision	± 3 mm
Mechanical/alignment tolerance	± 1 mm
Horizontal normalised emittance $\varepsilon_{n,x}$	0.58 mm
Vertical normalised emittance $\varepsilon_{n,y}$	0.29 mm
Injection mismatch (on emittance)	100 %
β_x, β_y @ Kicker	61.3 m, 39.7 m
β_x, β_y @ Septum	57.3 m, 42.3 m
σ_x, σ_y @ Kicker and Septum	0.8 mm, 0.4 mm

Table 9.33: Assumptions for beam parameters used to define the septum and kicker apertures

8847 The septum strength should be about 33 mrad to provide enough clearance for the injected beam at the
 8848 upstream lattice quadrupole, the yoke of which is assumed to have a full width of 0.6 m. This requires about
 8849 1.1 T m, and a 3.0 m long magnet at about 0.37 T is reasonable, of single turn coil construction with a
 8850 vertical gap of 40 mm and a current of 12 kA.

8851 The RF frequency of the linac is 1.3 GHz and a bunch spacing of 25 ns is considered, as the LHeC electron
 8852 beam bunch structure is assumed to match with the LHC proton beam structure. Optimally a train of 72
 8853 bunches would be injected, which would require a 1.8 μ s flattop for the kickers and a very relaxed 0.9 μ s
 8854 rise time (as for the LHC injection kickers [780]). However, this train length is too long for the recirculating
 8855 linac to produce, and so the kicker rise time and fall time requirements are therefore assumed to be about
 8856 23 ns, to allow for the bunch length and some jitter.

8857 For a rise time $t_m = 23$ ns, a system impedance Z of 25 Ω is assumed, and a rather conservative system
 8858 voltage U of 60 kV.

8859 Assuming a full vertical opening h of 40 mm, and a full horizontal opening w of 60 mm (which allow ± 6
 8860 σ beam envelopes with pessimistic assumptions on various tolerances and orbit), the magnetic length l_m of
 8861 the individual magnets is:

$$l_m = ht_m Z / \mu_0 w = 0.31 \text{ m}$$

8862 For a terminated system the gap field B is simply:

$$B = \frac{\mu_0 U}{2hZ} = 0.037 \text{ T}$$

8863 As 0.03 Tm are required, the magnetic length should be 0.8 m, which requires 3 magnets. Assuming each
 8864 magnet is 0.5 m long, including flanges and transitions the total installed kicker length is therefore about
 8865 1.5 m.

8866 Mismatched injection

8867 A mismatched injection is also possible, Figure 9.41 with a closed orbit bump used to bring the circulating
 8868 beam orbit close to the septum, and then switched off before the next circulating bunch arrives.

8869 The injected beam then performs damped betatron or synchrotron oscillations, depending on the type of
 8870 mismatch used. In LHeC the damping time is about 3 seconds, so that to achieve the suggested 0.2 s period
 8871 between injections, a damping wiggler would certainly be needed - the design of such a wiggler needs to be
 8872 investigated.

8873 Three kickers (KICKER 1, KICKER 2 and KICKER 3 in Fig. 9.41) are used to generate a closed orbit
 8874 bump of 20 mm at the injection point. The kicker parameters are summarized in table 9.34. In case of




Figure 9.41: layout of mismatched injection system. To minimise kicker strengths the magnets are located near focusing quadrupoles.

Magnet	θ_x [mrad]	B dl [Tm]
KICKER1	1.35	0.04
KICKER2	2.37	0.08
KICKER3	0.55	0.02

Table 9.34: Kickers strength and integrated magnetic field needed to generate an orbit bump of 20 mm at the injection point.

betatron mismatch, the bumpers can be installed in the dispersion free region considered for the injection onto the closed orbit case discussed in the previous section (see Fig. 9.42). The installed magnet lengths of the kickers should be 2 m, 3.5 m and 1 m respectively, for the kickers size, Z and U parameters given above. Overall the kicker system is not very different to the system needed to inject onto the orbit.

To allow for the possibility of synchrotron injection, the injection kicker-septum would need to be located where the horizontal dispersion D_x is large. The beam is then injected with a position offset x and a momentum offset δp , such that:

$$x = D_x \delta p$$

The beam then performs damped synchrotron oscillations around the ring, which can have an advantage in terms of faster damping time and also smaller orbit excursions in the long straight sections, particularly experimental ones, where the dispersion functions are small.

As an alternative to the fast (23 ns rise time) kicker for both types of mismatched injection, the kicker rise- and fall-time could be increased to almost a full turn, so that the bump is off when the mismatched bunch arrives back at the septum. This relaxes considerably the requirements on the injection kicker in terms of fall time. However, this does introduce extra complexity in terms of synchronizing the individual kicker pulse lengths and waveform shapes, since for the faster kicker once the synchronization is reasonably well corrected only the strengths need to be adjusted to close the injection bump for the single bunch.

9.11.2 Injection transfer line for the Ring-Ring Option

The injection transfer line from the 10 GeV injection recirculating linac is expected to be straightforward. A transfer line of about 900 m, constituted by 15 FODO cells, has been considered. The phase advance of




Figure 9.42: A closed orbit bump of 20 mm is generated by three kickers installed in the dispersion free region located at the right side of the bypass around ATLAS (electron beam moves from right to left in the Figure).

8894 each cell corresponds to about 100° .




Figure 9.43: Transfer line optics for the injection onto orbit case (top) and mismatched injection case (bottom).

8895 The last two cells are used for optics matching. In particular, four quadrupoles, 1 m long each, are used
 8896 for β_x and β_y matching, while two rectangular bending magnets, 5 m long each, are used for matching the
 8897 horizontal dispersion D_x to 0 (maximum $D_x = -1.48$ m for the injection onto closed orbit case and maximum
 8898 $D_x = -0.57$ m for the mismatched injection case). The “good field region” for a 6σ beam envelope requires
 8899 a minimum half-aperture, in the matching insertion, of 15 mm and 10 mm for the focusing and defocusing
 8900 quadrupoles respectively, corresponding to a pole tip field of about 0.02 T. The maximum strength of the
 8901 bending magnets, which are used for dispersion matching, corresponds to about 39 mrad. This requires
 8902 1.3 T m and a maximum field of 0.3 T. A single turn coil of 9.5 kA with a vertical gap of 40 mm could be
 8903 used.

8904 9.11.3 60 GeV internal dump for Ring-Ring Option

8905 An internal dump will be needed for electron beam abort. The design for LEP [781] consisted of a boron
 8906 carbide spoiler and an Aluminum alloy (6% copper, low magnesium) absorbing block (0.4 m \times 0.4 m \times 2.1 m
 8907 long). A fast kicker was used to sweep eight bunches, of 8.3×10^{11} electrons at 100 GeV, onto the absorber.
 8908 The first bunch was deflected by 65 mm and the last by 45 mm, inducing a temperature increase ΔT of
 8909 165° .

8910 The bunch intensity for the LHeC is about a factor of 20 lower than for LEP and beam size is double (σ
 8911 $= 0.5$ mm in LEP and $\sigma = 1$ mm in LHeC).

8912 The lower energy (60 GeV) and energy density permit to dump 160 bunches in 20 mm to obtain the
 8913 same ΔT as for LEP. However, in total LHeC will be filled with 2808 bunches, which means that significant
 8914 additional dilution will be required. A combination of a horizontal and a vertical kicker magnet can be
 8915 used, as an active dilution system, to paint the beam on the absorber block and increase the effective sweep
 8916 length. The kickers and the dump can be located in the bypass around CMS, in a dispersion free region (see
 8917 fig. 9.44).




Figure 9.44: The optics in the region of the CMS bypass where the beam dump system could be installed is shown. The system consists of two kickers, one spoiler and a Carbon-composite absorber which are installed in the dispersion free region of the bypass at the right side of CMS (beam proceeds from right to left in the Figure).

8918 It is envisaged to use Carbon-composite for the absorber block, since this has much better thermal and
 8919 mechanical properties than aluminum. The required sweep length is then assumed to be about 100 mm,
 8920 from scaling of the LEP design. The minimum sweep speed in this case is about 0.6 mm per μs , which
 8921 means about 54 bunches per mm. Taking into account the energy and the beam size, this represents less
 8922 than a factor 2 higher energy density on the dump block, compared to the average determined by the simple
 8923 scaling, that should be feasible using carbon. More detailed studies are required to optimise the diluter and
 8924 block designs. Vacuum containment, shielding and a water cooling system has to be incorporated. A beam
 8925 profile monitor can be implemented in front of each absorber to observe the correct functioning of the beam
 8926 dump system.

8927 The vertical kicker would provide a nominal deflection of about 55 mm (see fig.9.45), modulated by
 8928 $\pm 13\%$ for three periods during the 100 μs abort (see fig.9.46), while the horizontal kicker strength would
 8929 increase linearly from zero to give a maximum deflection at the dump of about 55 mm (see Fig.9.45 and
 8930 Fig.9.46). This corresponds to system kicks of 2.7 and 1.6 mrad respectively.

8931 Parameters characterizing the kicker magnets are presented in Table 9.35.




Figure 9.45: A vertical and a horizontal kicker are used to dilute the beam on the dump absorbing block.

8932 In the present lattice the dump is placed ~ 30 m downstream of the kickers, corresponding to a phase
 8933 advance of about 63° in the horizontal plane and 35° in the vertical plane. The minimum horizontal and
 8934 vertical aperture at the dump are 26 mm and 22 mm respectively (at the dump: $\beta_x = 37$ m and $\beta_y = 55$ m,
 8935 using the same beam and machine parameter assumptions, as presented in Table 9.33). The kicker system
 8936 field rise time is assumed to be at most 3 μs (abort gap) and the kicker field flat-top at least 90 μs as for the
 8937 LHC proton beam. Same design as for the LHC dump kicker magnets MKD can be used: a steel yoke with
 8938 a one-turn HV winding. These magnets can provide a magnetic field in the gap of 0.34 T. For a magnetic
 8939 length of 0.31 m ($Z = 25 \Omega$ and $U = 60$ kV), a total installed kicker length of 1.5 m for the horizontal system
 8940 and 2.5 m for the vertical system has to be considered.

8941 A spoiler (one-side single graphite block: 0.3 m \times 0.10 m \times 0.5 m long) can be installed 5 m upstream
 8942 of the dump at the extraction side to provide further dilution.




Figure 9.46: The strength of the vertical kicker oscillates in time by $\pm 13\%$ around its nominal value. The deflection provided by the horizontal kicker increases almost linearly in time.

	MKDV	MKDH
Length [m]	2.5	1.5
Maximum angle [mrad]	2.7	1.6
Maximum field [T]	0.34	0.34
Rise/Fall time [ns]	800	800
Flat top length [μ s]	90	90

Table 9.35: Parameters characterising vertical and horizontal kicker magnets of the extraction system.

9.11.4 Post collision line for 140 GeV Linac-Ring option

The post collision line for the 140 GeV Linac option has to be designed taking care of minimizing beam losses and irradiation. The production of Beamstrahlung photons and e^-e^+ pairs is negligible and the energy spread limited to 2×10^{-4} . A standard optics with FODO cells and a long field-free region allowing the beam to naturally grow before reaching the dump can be foreseen. The aperture of the post collision line is defined by the size of the spent beam and, in particular, by its largest horizontal and vertical angular divergence (to be calculated). A system of collimators could be used to keep losses below an acceptable level. Strong quadrupoles and/or kickers should be installed at the end of the line to dilute the beam in order to reduce the energy deposition at the dump window. Extraction line requirements:

- Acceptable radiation level in the tunnel.
- Reasonably big transverse beam size at the dump window and energy dilution.
- Beam line aperture big enough to host the beam: beta function and energy spread must be taken into account.
- Elements of the beam line must have enough clearance.

9.11.5 Absorber for 140 GeV Linac-Ring option

Nominal operation with the 140 GeV Linac foresees to dump a 50 MW beam. This power corresponds to the average energy consumption of 69000 Europeans. An *Eco Dump* could be used to recover that energy; detailed studies are needed and are not presented here. Another option is to start from the concept of the ILC water dump and scale it linearly to the LHeC requirements. The ILC design is based on a water dump with a vortex-like flow pattern and is rated for 18 MW beam of electrons and positrons [782]. Cold pressurized water (18 m³ at 10 bar) flows transversely with respect to the direction of the beam. The beam always encounters fresh water and dissipates the energy into it. The heat is then transmitted through heat exchangers. Solid material plates (Cu or W) are placed beyond the water vessel to absorb the tail of the beam energy spectrum and reduce the total length of the dump. This layer is followed by a stage of solid material, cooled by air natural convection and thermal radiation to ambient, plus several meters of shielding. The size of the LHeC dump, including the shielding, should be 36 m longitudinally and 21 m transversely and it should contain 36 m³ of water. The water is separated from the vacuum of the extraction line by a thin Titanium Alloy (Ti-6Al-4V) window which has high temperature strength properties, low modulus of elasticity and low coefficient of thermal expansion. The window is primarily cooled by forced convection to water in order to reduce temperature rise and thermal stress during the passage of the beam. The window must be thin enough to minimise the energy absorption and the beam spot size of the undisturbed beam must be sufficiently large to prevent window damage. A combination of active dilution and optical means, like strong quadrupoles or increased length of the transfer line, can be use on this purpose. Further studies and challenges related to the dump design are:

- Pressure wave formation and propagation into the water vessel.
- Remotely operable window exchange.
- Handling of tritium gas and tritiated water.

9.11.6 Energy deposition studies for the Linac-Ring option

Preliminary estimates, of the maximum temperature increase in the water and at the dump window, have been defined according to FLUKA simulation results performed for the ILC dump [783]. A 50 MW steady state power should induce a maximum temperature increase ΔT of 90° corresponding to a peak temperature of 215°. The water in the vessel should be kept at a pressure of about 35 bar in order to insure a 25° margin from the water boiling point.

FLUKA studies have been carried out for a 1 mm thick Ti window with a hemispherical shape. The beam size at the ILC window is $\sigma_x = 2.42$ mm and $\sigma_y = 0.27$ mm; an extraction line with 170 m drift and 6 cm sweep radius for beam dilution have been considered. A beam power of 25 W with a maximum heat source of 21 W/cm³ deposited on the window have been calculated. This corresponds to a maximum temperature of 77° for the minimum ionisation particle ($dE/dx = 2$ MeV \times cm²/g), no shower is produced because the thickness of the window is significantly smaller than the radiation length. A maximum temperature lower than 100° would require a minimum beam size of $\sigma_{x,y} = 1.8$ mm. A minimum β function of 8877 m would be needed being the beam emittance $\varepsilon_{x,y} = 0.37$ nm for the undisturbed beam. The radius of the dump window depends on the size of the disrupted beam. The emittance of the disrupted beam is $\varepsilon_{x,y} = 0.74$ nm corresponding to a beam size $\sigma_{x,y}$ of 2.56 mm (for $\beta = 8877$ m); a radius $R = 5$ cm could then fit a 10σ envelope. The yield strength of the Ti alloy used for the window is $\sigma_{Ti} = 830$ MPa, this, according to the formula:

$$\sigma_{Ti} = 0.49 \times \Delta P \frac{R^2}{d^2} \quad (9.10)$$

where $\Delta P = 3.5$ MPa, imposes that the thickness of the window d is bigger than 2.3 mm.

Length of the transfer line drift space and possible dilution have to be estimated together with possible cooling.

9001 **9.11.7 Beam line dump for ERL Linac-Ring option**

9002 The main dump for the ERL Linac-ring option will be located downstream of the interaction point. Splitting
 9003 magnets and switches have to be installed in the extraction region and the extracted beam has to be tilted
 9004 away from the circulating beam by 0.03 rad to provide enough clearance for the first bending dipole of the
 9005 LHeC arc (see Fig. 9.47). A 90 m transfer line, containing two recombination magnets and dilution kickers,
 is considered to be installed between the LHeC and the LHC arcs(see Fig. 9.48). The beam dump will be




Figure 9.47: Scheme of the transfer line from end of long straight section of the linac and beam dump.

9006 housed in a UD62/UD68 like cavern at the end of the TL and the option of having service caverns for water
 9007 treatment and heat exchange is explored. An additional dump, and its extraction line, could be installed at
 9008 the end of the first linac(see Fig. 9.48) for beam setup purposes at intermediate energy. The same design as
 9009 for the nominal dump and extraction line would be applied.
 9010




Figure 9.48: Two beam dumps are installed 90 m downstream the end of the long straight section of each linac for nominal operation and beam setup. Note that this drawing is only indicative for the beam dump positions: the currently preferred location of the Linac is 'mirrored' such that it is inside the LHC.

9011 **9.11.8 Absorber for ERL Linac-Ring option**

9012 During nominal operation a 0.5 GeV beam has to be dumped with a current of 6.6 mA. The setup beam
9013 will have a maximum current of 0.05 mA and an energy varying from 10 GeV to 60 GeV (10 GeV step size).
9014 Globally, a maximum beam power of 3 MW has to be dumped. The same design as for the 140 GeV option
9015 can be used by scaling linearly. In this case, a 3 m³ water dump (0.5 m diameter and 8 m length) with a
9016 3 m × 3 m × 10 m long shielding has to be implemented. No show stopper has been identified for the 18
9017 MW ILC dump, same considerations are valid in this less critical case.

Chapter 10

Civil Engineering and Services

10.1 Overview

Infrastructure costs for projects such as LHeC, typically represent approximately one third of the overall budget. For this reason, particular emphasis has been placed on Civil Engineering and Services studies, to ensure a cost efficient conceptual design. This chapter provides an overview of the designs adopted for the key infrastructure cost driver, namely, civil engineering. The costs for the other infrastructure items such as cooling & ventilation, electrical supply, transport & installation will be pro-rated for the CDR and studied in further detail during the next phase of the project. For the purposes of this conceptual design report, the Civil Engineering (CE) studies have assumed that the Interaction Region (IR) for LHeC will be at LHC Point 2, which currently houses the ALICE detector. As far as possible, any surface facilities have been situated on existing CERN land. Both the Ring-Ring and Linac-Ring underground works will be discussed in this Chapter. Surface buildings/structures have not been considered for the CDR.

10.2 Location, Geology and Construction Methods

This section describes the general situation and geology that can be expected for both the Ring-Ring and Linac Ring options.

10.2.1 Location

The proposed siting for the LHeC project is in the North-Western part of the Geneva region at the existing CERN laboratory. The proposed Interaction Region is fully located within existing CERN land at LHC Point 2, close to the village of St.Genis, in France. The CERN area is extremely well suited to housing such a large project, with the very stable and well understood ground conditions having several particle accelerators in the region for over 50 years. The civil engineering works for the most recent machine, the LHC were completed in 2005, so excellent geological records exist and have been utilised for this study to minimise the costs and risk to the project. Any new underground structures will be constructed in the stable Molasse rock at a depth of 100-150m in an area with little seismic activity. CERN and the Geneva region have all the necessary infrastructure at their disposal to accommodate such a project. Due to the fact that Geneva is the home of many international organizations excellent transport and communication networks already exist. Geneva Airport is only 5km from the CERN site, with direct links and a newly constructed tramway, shown in Figure 10.1, gives direct access from the Meyrin Site to the city centre.

The governments of France and Switzerland have long standing agreements concerning the support of particle accelerators in the Geneva region, which make it very likely that the land could be made available free of charge, as it was for previous CERN projects.



Figure 10.1: Tram stop outside CERN Meyrin Site.




Figure 10.2: Simplified cross section of the LHC housed mostly in Molasse Rock

10.2.2 Land Features

The proposed location for the accelerator is situated within the Swiss midlands embedded between the high mountain chains of the Alps and the lower mountain chain of the Jura. CERN is situated at the feet of the Jura mountain chain in a plain slightly inclined towards the lake of Geneva. The surface terrain was shaped by the Rhone glacier which once extended from the Alps to the valley of the Rhone. The water of the area flows to the Mediterranean Sea. The absolute altitude of the surface ranges from 430 to 500m with respect to sea level. The physical positioning for the project has been developed based on the assumption that the maximum underground volume possible should be housed within the Molasse Rock and should avoid as much as possible any known geological faults or environmentally sensitive areas. The shafts leading to any on-surface facilities have been positioned in the least populated areas, however, as no real discussions have taken place with the local authorities, the presented layouts can only be regarded as indicative, for costing purposes only.

10.2.3 Geology

The LHeC project is within the Geneva Basin, a sub-basin of the large North Alpine Foreland (or Molasse) Basin. This is a large basin which extends along the entire Alpine Front from South-Eastern France to Bavaria, and is infilled by Molasse deposits of Oligocene and Miocene age. The basin is underlain by crystalline basement rocks and formations of Triassic, Jurassic and Cretaceous age. The Molasse, comprising an alternating sequence of marls and sandstones (and formations of intermediate compositions) is overlain by Quaternary glacial moraines related to the Würmian and Rissian glaciations. Figure 10.2 shows a simplified layout of the LHC.

10.2.4 Site Development

As most of the new works are on a close to existing facilities, it is assumed for the CDR that the existing facilities such as restaurant, main access, road network etc are sufficient and have not been costed. However, for the parts located outside the existing fence line, but within CERN property, the following items will have to be included in the costs:

- Roads and car parks.
- Drainage networks.
- Landscaping and planting.
- Spoil dumps.



Figure 10.3: TBM Gripper type machine used for Neutrino tunnel at CERN (left) and roadheader type machine (right).

9079 All temporary facilities needed for the construction works have also been included in the cost estimate.

9080 10.2.5 Construction Methods

9081 It is envisaged that Tunnel Boring Machines (TBMs) will be utilised for the main tunnel excavation greater
 9082 than approximately 2km in length. In the Molasse rock, a shielded TBM will be utilised, with single pass pre-
 9083 cast segmental lining, followed by injection grouting behind the lining. For planning and costing exercises,
 9084 an average TBM advancement of 25m per day, or 150m per week is predicted.

9085 The second phase excavation will be executed using a roadheader type machine. Both machine types are
 9086 shown in Figure 10.3. Any new shafts that have to pass through substantial layers of water bearing moraines
 9087 (for example at CMS) will have to utilize the ground freezing technique. This involves freezing the ground
 9088 with a primary cooling circuit using ammonia and a secondary circuit using brine at -23C, circulating in
 9089 vertical tubes in pre-drilled holes at 1.5 metre intervals. This frozen wall allows excavation of the shafts in
 9090 dry ground conditions and also acts as a retaining wall. Figure 10.4 shows this method being utilized for
 9091 LHC shaft excavation at CMS.

9092 10.3 Civil Engineering Layouts for Ring-Ring

9093 The Ring-Ring solution will require new bypass tunnels at both Point 5 (currently housing the CMS detector)
 9094 and Point 1 (ATLAS). Both of the bypass tunnels are on the outside of the LHC ring.

9095 The Bypass around CMS Point 5 is 1km long with an internal tunnel diameter of 4.5m. Only one new
 9096 shaft is required for excavation works. A roadheader type machine will be used for excavation, with the new
 9097 tunnel position as close as possible to the LHC tunnel as not to induce movements or create operational
 9098 problems to the existing facilities. Figure 10.5 shows the new bypass tunnel and service cavern required
 9099 around CMS.

9100 Figure 10.6 shows the bypass tunnel in blue needed around Point 1. This tunnel is 730 m long and has
 9101 an internal diameter of 4.5 m. Two new 7 m diameter shafts are required to allow access to construct the
 9102 underground areas with minimum disruption to LHC operations. Underground areas are made available for
 9103 RF/Cryogenic and general services. Two junction caverns will be excavated to create a liaison with the LHC
 9104 tunnel.

9105 Waveguides ducts (0.9 m diameter) will connect the LHeC Bypass tunnel to the RF cavern, as shown in
 9106 Figure 10.7. In order to position the bypass as close as possible to the LHC ring, it has been assumed that




Figure 10.4: LHC Shaft PM54, linking up cylinders of ice to construct a temporary wall.




Figure 10.5: Ring-Ring Bypass around CMS Point 5.




Figure 10.6: Ring-Ring Bypass around ATLAS Point 1.




Figure 10.7: Cryo and RF Cavern (one side only) at Point 1.




Figure 10.8: 3d model of Ring-Ring Bypass around CMS Point 5.

9107 the LHeC beampipe can be accommodated within the existing survey gallery, and pass through the ATLAS
 9108 experimental hall.

9109 Figure 10.8 shows a 3d model of the bypass around the CMS Point 5. The new excavations will have a
 9110 minimum of 7m of Molasse rock separating the new works from existing LHC structures. This is to avoid
 9111 any unwanted deformation or vibration problems on the existing LHC structures.

9112 The civil engineering for the electron beam injection complex for the Ring-Ring option has not been
 9113 studied for the CDR.

9114 10.4 Civil Engineering Layouts for Linac-Ring

9115 For the CDR it has been assumed that the 60 GeV Energy Recovery Linac (ERL) will be located around
 9116 the St.Genis area of France, injecting directly into the LHC ALICE Cavern at Point 2. Approximately
 9117 10 km of new tunnels (5 m and 6 m diameter), 2 shafts and 9 caverns will be required. The majority of civil
 9118 engineering works can be completed while LHC is operational. Figure 10.9 highlights the area on the LHC
 9119 where the new ERL will be situated.

9120 The ERL will be positioned inside the LHC Ring, in order to ensure that new surface facilities are
 9121 located, as much as possible, on existing CERN land. Secondary tunnels running alongside the long straight
 9122 sections will house RF, Cryogenic and Services for the machine. One of the long straight sections is shown
 9123 in Figure 10.10. The entire ERL, illustrated in Figure 10.11, will be tilted in order to follow a suitable layer
 9124 of Molasse rock. On average the ERL will be tilted approximately 1.4%, dipping towards Lake Geneva, as
 9125 per LHC.

9126 10.5 Summary

9127 From a civil engineering point of view, both the Ring-Ring and Linac-Ring options are feasible. The Ring-
 9128 Ring option will provide a cheaper solution, however, with a marginally increased risk to LHC activity, due




Figure 10.9: Schematic model of ERL position injecting into IP2.




Figure 10.10: ERL Injection area into IP2 and RF/Cryo/Services Cavern (yellow & green).




Figure 10.11: View on the ERL placed inside the LHC ring and tangential to IP2. TI2 is the injection line into the LHC. The insert shows the view towards IP2, which currently houses the ALICE experiment, from the direction of the protons colliding with the electron beam incoming from behind.

⁹¹²⁹ to the fact that most of the excavation works being in close proximity to the existing installations. The
⁹¹³⁰ Linac-Ring option is the cleaner solution from a civil engineering point of view, with much less risk to LHC,
⁹¹³¹ but with substantial extra cost and greater time needed for environmental and building permit procedures.

Chapter 11

Project Planning

We base the planning of the LHeC project on the assumption that the LHC machine will reach the end of its lifetime when the High Luminosity LHC project reaches its design goal of $3000fb^{-1}$. Figure 11.1 shows the current status of the CERN planning for the LHC related upgrade projects. The current planning foresees three long shutdowns:

- Long Shutdown 1 (LS1) for repairing the faulty splice connections in the LHC and allowing operations at nominal energy of 7 TeV.
- Long Shutdown 2 (LS2) for consolidating the LHC for operation above nominal beam intensities
- Long Shutdown 3 (LS3) for implementing the HL-LHC upgrade installations.

Figure 11.2 shows the resulting evolution of the integrated luminosity per experiment over time assuming the LHC performance stabilizes at nominal luminosity after LS1. Figure 11.3 shows a similar evolution of the integrated luminosity assuming the LHC performance stabilizes at ultimate luminosity after LS1.

In both scenarios, the LHC reaches a total integrated luminosity of ca. $200fb^{-1}$ before LS3 and the installation of the HL-LHC upgrade. The HL-LHC project aims at a generation of $200fb^{-1}$ to $300fb^{-1}$ per year [785] and one can assume that the HL-LHC design goal can be reached by between 9 and 13 years after the LS3. Assuming a one year long shutdown for LS3, this implies the accumulation of $3000fb^{-1}$ by ca. 2030 to 2035. Aiming for the LHeC at an exploitation time of 10 years the LHeC operation should therefore start together with the HL-LHC operation after the LS3 in 2022.

We base our estimates for the project time line on the experience of other projects, such as (LEP, LHC and LINAC4 at CERN and the European XFEL at DESY and the PSI XFEL). In the following we will analyze separately the required time line for the project construction for the RF system development, the production of the magnet system, the required civil engineering and the installation of the accelerator components in the tunnel.

The superconducting RF development for LEP and LHC both required approximately 2 to 3 years for the cavity prototyping and testing and approximately 5 to 6 years of test stand operation of the superconducting RF cavity modules adding up to a total time of approximately 6 to 8 years from first prototype to final installation. The first LHC cavity prototypes were constructed in 2000 with a final installation of the 4 cryo modules in the LHC tunnel in 2006. The first LEP superconducting RF cavity was tested in LEP in 1991. LEP2 operation started in 1996 but still required 2 years of progressively commissioning all cryo modules in building B180 before their final installation in the LEP tunnel. The last cryo module of the 73 4-cell LEP cryo modules was installed in the LEP tunnel in 1999. Both RF installations featured extensive test stand operations. The LEP RF system had cavity test stands in building SM18 and a separate power test in building B180 which were operated from 1994 until 1999. The LHC RF system had both, the cavity and the power test stands, in SM18. The LHC test stands were operated from 2002 until 2006 (the test stand operation was slowed down at the end due to difficulties with the RF coupler design). In both cases, LEP




Figure 11.1: CERN medium term plan (MTP), draft as of July 2011, from [784].




Figure 11.2: Left: Projected luminosity evolution for the LHC assuming the LHC reaches nominal performance levels after the first long shutdown (LS1) and then remains at nominal performance after 2016. Right: The resulting evolution of the integrated luminosity for the LHC experiments. [785].

9168 and LHC, the RF system installation was therefore accompanied by a 5 to 6 year test stand operation which
 9169 overlapped with the actual installation period in the tunnel [786].

9170 The LHeC linac-ring RF system requires 118 cryomodules of eight 721 MHz 5-cell superconducting RF
 9171 structures, amounting to a total of approximately 950 structures or thirteen times the number of LEP RF
 9172 structures. It seems therefore reasonable to assume for the LHeC linac-ring RF system a total time of
 9173 10 years from first prototype construction to final installation in the tunnel with a dedicated test stand
 9174 operation for approximately 8 years. ¹ The LHeC ring-ring RF system corresponds approximately to the
 9175 LEPII RF system in terms of total power and overall length of the RF installation and it seems reasonable
 9176 to assume for the LHeC ring-ring RF system a slightly shorter time scale. Here we assume the same time
 9177 scale as for LEPII: a total time of 8 years from first prototype construction to final installation in the tunnel
 9178 with a dedicated test stand operation for approximately 6 years.

9179 For the magnet system we base a first order estimate of the required timescale for the magnet production
 9180 and installation on the experience with LHC transfer lines. The LHC transfer lines have a total length of 6 km
 9181 and feature a total of ca. 350 normal conducting magnets. The magnet production extended over 3 years
 9182 with a production rate of ca. 10 magnets per month [788]. It is, however, important to underline that the
 9183 production rate was not limited by production capacity but rather, was following the project requirements
 9184 and the CERN ability for magnet testing after reception at CERN. Both LHeC options feature a relatively
 9185 large number of magnets, approximately 4000 magnets. Compared to the LHC transfer line magnets, these
 9186 magnets are much more compact and one can assume that the magnet production rate can be significantly
 9187 larger than that for the LHC transfer lines. The LHeC magnet production requires therefore industrial
 9188 production rates featuring several contractors and production lines. The price to pay for such an industrial
 9189 production scheme will be the requirement for a pre-series production and a thorough quality assurance

¹Faster production rates could be possible by using several manufacturers in parallel as it is, for example, planned for the ILC. The ILC project requires approximately 15000 cavities and aims at a 10 to 15 times faster production rate as compared to the XFEL cavity production. But such an approach requires long preparation studies for the industrialization (the ILC assumes more than 3 years for such studies [787]), dedicated production test facilities (the ILC has production test facilities at three different laboratories: DESY, KEK and FNAL), an extensive pre-series production and test bench operation for verifying the cavity and cryomodule design before launching the mass production (the ILC project has more than 20 years experience of pre-series production and test bench operation in form of the TTF, FLASH and XFEL installations) and a large production volume so that it is lucrative for several manufacturers to split the overall production while still undertaking significant investments for the production lines. Such an approach may not apply to a 'small' project like the LHeC and may therefore not lead to a much faster production time line.




Figure 11.3: Left: Optimistic projection of the luminosity evolution for the LHC assuming the LHC reaches ultimate performance levels after the first long shutdown (LS2). Right: The resulting evolution of the integrated luminosity for the LHC experiments. [785].

9190 over the whole production process. All LHeC magnets will require furthermore a detailed geometry and
 9191 field quality measurement program after reception at CERN. In the following we assume 1-2 years for the
 9192 pre-series production and first testing followed by potential design modifications and a peak production rate
 9193 of ca. 60 dipoles and 20 quadrupoles per month (ca. ten times the production rate of the LHC transfer
 9194 lines). These assumptions lead to a total construction time of ca. 4 to 6 years and a total of 6 to 8 years
 9195 from magnet design to final installation in the tunnel.

9196 For the civil engineering we base our first order estimate for the time line on the estimates for the CLIC
 9197 500 GeV option which features a total length that is comparable to the 60 GeV linac-ring option. The
 9198 civil engineering work requires for the LHeC linac-ring option the construction of ca. 10 km underground
 9199 installations which is estimated to take approximately 4 years construction time (the required underground
 9200 construction for the ring-ring solution is smaller but will occur in the direct vicinity of the main LHC tunnel).
 9201 The installation of the technical infrastructure (water, electricity etc.) will take approximately 2 years and
 9202 the final installation of the machine elements in the tunnel another 2 years. All three activities can partially
 9203 overlap, leading to an estimate of the total construction time of ca. 6 years [789].

9204 For all other components (cryogenics, injector complex, detector etc.) we assume for the moment that
 9205 their development and installation can be done in the shadow of the three components mentioned above.

9206 In summary, we estimate:

- 9207 • Between 8 and 10 years for the production of the RF system (time from prototype to final installation
 9208 in the tunnel) with dedicated test stand operation over 6 to 8 years.
- 9209 • Between 6 and 8 years for the production of the magnet system (time from prototype to final installation
 9210 in the tunnel) with several production lines and test facilities for the quality assurance during the
 9211 magnet production.
- 9212 • Approximately 6 years for the civil engineering work and actual installation in the tunnel.
- 9213 • All other components such as injector complex, cryogenics installation, detector construction etc, are
 9214 assumed to lie in the shadow of the above components.

9215 The above time estimates appear as reasonable estimates compared to the planning of other projects like
 9216 the European XFEL at DESY, the European Spallation Source (ESS) in Sweden, LINAC4 at CERN and
 9217 the PSI XFEL facilities:

9218
9219
9220
9221
9222
9223
9224

9225
9226

9227
9228
9229
9230
9231
9232
9233

9234
9235
9236
9237

9238
9239
9240
9241
9242
9243
9244
9245
9246
9247
9248
9249
9250
9251
9252
9253
9254
9255
9256
9257
9258
9259
9260

- The European XFEL project features a 3 km long superconducting linear accelerator (comparable in size to the linac section of the LHeC linac-ring option) started the civil engineering in January 2009 and plans for completing the civil engineering work in end 2012 (→ 4 years of bare civil engineering work) [790]. The project had in form of the FLASH (TTF) installation a pre-series production of 150 1.3 GHz 9-cell cavity modules that went from 1993 to 2005 (12 years) and an extended test stand operation. The XFEL project plans for an industrial production of more than 600 1.3 GHz 9-cell cavity module from 2010 until 2014 (4 to 5 year production time) [791].
- The ESS facility features ca. 300 m superconducting RF sections and plans for a construction phase of 9 years (2009 until 2017) with first operation in 2018 and full performance reach in 2025 [792].
- The LINAC4 project is a ca. 200 m long normal conducting linac installation which has a ca. 3 year long civil engineering construction period, followed by one year of infrastructure installation and 1.5 years of waveguide and accelerator component installation, amounting to a total construction period of ca. 5.5 years (start of civil engineering in beginning 2008 and end of the accelerator installation by mid 2013) which seems rather long compared to the civil engineering estimates for the LHeC (installation length of ca. 10 km and ca. 100 m underground; ca. 50 times the LINAC4 installation length which is mainly above surface) [793].
- The PSI XFEL project features an approximately 1 km long normal conducting linac and plans for 2 years for the generation of a TDR, a 5 year test stand operation, a 4 year construction period and an installation period of 3 years leading to a total project time line of 6 years from start of the test facilities to the start of the actual project [794].

Except for the European XFEL project, which has a longer superconducting RF section than both LHeC versions, all of the above reference facilities are smaller in scale than the LHeC project and plan between 6 and 9 years from beginning of construction (civil engineering) until the start of operation. All facilities with superconducting cavities plan for an RF production time of ca. 5 years for their key components and a substantial period of test bench operation and pre-series production for critical elements (5 years or more).

Figure 11.4 summarizes the above considerations in form of a schematic outline of the project planning. The planning in Fig. 11.4 addresses only aspects related to the accelerator complex and does not address additional constraints coming from the detector installation in the cavern. Furthermore, it does not include additional constraints arising from the LHC operation, logistics constraints and resource limitations due to the planning for the long shutdowns of the LHC and does therefore certainly not attempt to be an accurate project projection. Rather than presenting an accurate timeline for the LHeC installation, the presented planning aims at illustrating that a start of the LHeC operation in 2023 requires the start of first prototype development and testing already by 2012. Meeting the milestone of an LHeC operation start in 2023 requires a rather swift project launch starting with the generation of a proper TDR and the launch of first RF R&D activities by 2012. This ambitious goal can only be achieved if the project receives adequate resource allocations in 2012. Potential first activities for the prototype development and testing could focus around the development of superconducting RF cavities, where synergies with ESS and SPL studies exist, with the goal of setting up an ERL test facility. It could also include the development of electron and positron sources where synergies with the CLIC and ILC projects exist. Because of their synergies with the ESS, SPL and the linear collider projects, a start of R&D activities for the LHeC by 2012 appears to be quite timely. In case the Ring-Ring installation turns out to be the better option for the LHeC, a ERL test facility could in the end also serve as an injector complex for the Ring-Ring option of the LHeC. It represents therefore a reasonable investment into the LHeC project independent of a the final implementation choice.




Figure 11.4: Planning considerations for the LHeC, where we assumed a partial overlap of the time lines for the various LHeC project steps (for example a partial overlap of the civil engineering for the tunnel construction and the installation of the technical infrastructure and accelerator components). The overall planning goal of completion by the LS3 seems quite ambitious even with such a partial overlap of individual activities and requires first prototype development as soon as by 2012. The presented planning discusses only aspects related to the accelerator complex and does not address additional constraints coming from the detector installation in the cavern.

Part IV

Detector

9261

9262

Chapter 12

Detector Requirements

In this chapter the core aspects of the main detector design for the LHeC are discussed. The physics requirements are illustrated along with the boundary conditions from the accelerator options and the interaction region design. These considerations converge in chapter 13 where a first picture of the main detector is presented along with a discussion on the choice for the detector elements and the overall detector assembly. Aspects involving the design of the interaction region, the beam pipe, the particle backgrounds, the magnets and the simulation environment are discussed in the later sections. Finally the single detector components are presented starting from the innermost ones, tracking, calorimetry and muon detectors. Detector components not located in the proximity of the interaction region are described in chapter 14.

12.1 Requirements on the LHeC Detector

The new ep/A detector at the LHeC has to basically be a precision instrument of maximum acceptance. The physics program depends on a high level of precision, as for the measurement of α_s , and in the reconstruction of complex final states, like the charged current single top production and decay or the precision measurement of the b -quark density. The acceptance has to extend as close as possible to the beam axis because of the interest in the physics at low and at large Bjorken x . The dimensions of the detector are constrained by the radial extension of the beam pipe in combination with maximum polar angle coverage¹, desirably down to about 1° and 179° for forward going final state particles and backward scattered electrons at low Q^2 , respectively. A further general demand is a high modularity enabling much of the detector construction to be performed above ground for keeping the installation time at a minimum, and to be able to access inner detector parts within reasonable shut down times.

The time schedule of the project demands to have a detector ready within about ten years. This prevents any significant R&D program to be performed. The choice of components fortunately can rely on the vast experience obtained at HERA, the LHC, including its detector upgrades to come, and on ILC detector development studies. The next few sections outline the acceptance and measurement requirements on the detector in detail. Then follow more detailed technical considerations, including alternative solutions, which taken together illustrate the feasibility of experimentation at the LHeC.

12.1.1 Installation and Magnets

The LHeC project represents an upgrade of the LHC. The experiment would be the fifth large experiment, and the detector the third multi-purpose 4π acceptance detector. It requires a cavern, which for the purpose

¹This CDR adopts the HERA convention of the coordinate system, which has been defined with the z axis given by the proton beam direction. This implies that Rutherford "backscattering" of the electron is viewed as scattering into small angles. When the partons are essentially at rest, at very small x , the electrons are scattered "forward" as in fixed target forward spectrometers. The somewhat unfortunate HERA convention calls this backwards. The x and y coordinates are defined such that there is a right handed coordinate system formed with y pointing upwards and x to the center of the proton ring.




Figure 12.1: Cross section of the IP2 cavern with the L3 magnet. Round access shaft of 23m diameter, cavern about 50m along the beam-line.

9293 of the design study has been considered to be the ALICE cavern in IP2, see Fig. 12.1. The installation of the
 9294 detector has to proceed as fast as possible in order not to introduce large extra delays to the LHC program.
 9295 High modularity and pre-assembly above ground are therefore inevitable demands for the design.

9296 The cost has to be limited in order for the project to be fundable in parallel to when the large upgrade
 9297 investments are presumably made for the ATLAS and CMS detectors in the high luminosity phase of the
 9298 LHC. The cost is related to technology choices, the detector granularity and its size. Crucial parameters of
 9299 the detector are the beam pipe dimensions, when combined with the small angle acceptance constraint, see
 9300 below this section, and the parameters of the solenoid. The cost C of a solenoid can be represented as a
 9301 function of the energy density, ρ_E , $C \simeq 0.5(\rho_E/MJ)^{0.66}$ [64], which is determined as

$$\rho_E = \frac{1}{2\mu_0} \cdot \int B^2 dV \simeq \frac{1}{2\mu_0} \cdot \pi r^2 \cdot l \cdot B^2. \quad (12.1)$$

9302 From these relations one derives roughly that the solenoid cost scales linearly with the radius r and field
 9303 strength B and with the length l to the power 0.66. The solenoid radius influences the track length in the
 9304 transverse plane, which determines $\propto r^{-2}$ the transverse momentum resolution whereas field strength enters
 9305 linearly $\propto B^{-1}$.

9306 The Linac-Ring version of the LHeC requires to put an extended dipole field of 0.3T into the detector
 9307 for ensuring head-on ep collisions and for separating the beams.

9308 A balance between a strong magnetic field for optimal tracking resolution and an affordable sized magnet
 9309 has to be found, knowing that the magnets themselves represent one source of inactive material and that
 9310 the energy stored in the magnets and their return flux require an outer shielding proportional to the field
 9311 and to the square of the solenoid radius.

9312 In the current design the solenoid is placed in between the electromagnetic and the hadron calorime-

9313 ter^2 at a radius of about 1 m. The magnetic field is set to 3.5 T in order to compensate the small radial
 9314 extension of the tracker, the focus of which in the LHeC environment is on the forward direction. The cho-
 9315 sen design position with dipoles and solenoid placed outside the electromagnetic calorimeter ensures good
 9316 electromagnetic calorimetry and high dipole field quality near to the beam line. Fig. 12.2 shows such the
 magnet arrangement inside the detector volume schematically. The total material budget of the solenoid




Figure 12.2: Schematic xy and rz views of the magnets and barrel calorimeter arrangement for the baseline layout.

9317 and the dipole, at perpendicular crossing, may be represented by about 16 cm of Aluminum, corresponding
 9318 to about one quarter of an interaction length (λ_I) and about 1 radiation length (X_0). This further supports
 9319 the choice of the magnets located outside of the electromagnetic calorimeter, yet placed before the hadronic
 9320 calorimeter in order to limit the radial dimensions. More details on the design study of the detector magnets
 9321 are addressed in Sect.13.2.

9323 12.1.2 Kinematic reconstruction

9324 The inclusive ep DIS kinematics are defined by the negative four-momentum transfer squared, Q^2 , and
 9325 Bjorken x . Both are related to the cms energy squared s via the inelasticity y through the relation $Q^2 = sxy$,
 9326 which implies $Q^2 \leq s$. The energy squared s is determined by the product of the beam energies, $s = 4E_p E_e$,
 9327 for head-on collisions and large energies compared to the proton mass.

9328 The kinematics are determined from the scattered electron with energy E'_e and polar angle θ_e and from
 9329 the hadronic final state of energy E_h and scattering angle θ_h . The variables Q^2 and y can be calculated from
 9330 the scattered electron kinematics as

$$\begin{aligned} Q_e^2 &= 4E_e E'_e \cos^2\left(\frac{\theta_e}{2}\right) \\ y_e &= 1 - \frac{E'_e}{E_e} \sin^2\left(\frac{\theta_e}{2}\right) \end{aligned} \quad (12.2)$$

9331 and from the hadronic final state kinematics as

$$\begin{aligned} Q_h^2 &= \frac{1}{1 - y_h} \cdot E_h^2 \sin^2(\theta_h) \\ y_h &= \frac{E_h}{E_e} \sin^2\left(\frac{\theta_h}{2}\right) \end{aligned} \quad (12.3)$$

²An option is also considered of placing the solenoid outside the calorimeters, at about 2.5 m radius, combined with a second, bigger solenoid for the flux return, with the muon detector in between. A two-solenoid solution was considered already in the fourth detector concept for the ILD [795].

9332 and x is given as Q^2/sy . The kinematic reconstruction in neutral current scattering therefore is redundant,
 9333 which is one reason why DIS experiments at ep colliders are precise. An important example is the calibration
 9334 of the electromagnetic energy scale from the measurements of the electron and the hadron scattering angles.
 9335 At HERA, this led to energy calibration accuracies for E'_e at the per mil level. In a large part of the phase
 9336 space, around $x = E_e/E_p$, the scattered electron energy is approximately equal to the beam energy, $E'_e \simeq E_e$,
 9337 which causes a large “kinematic peak” in the scattered electron energy distribution. The hadronic energy
 9338 scale can be obtained from the transverse momentum balance in neutral current scattering, $p_t^e \simeq p_t^h$. It is
 9339 determined to about 1% at HERA.

9340 Following Eq.12.3, the kinematics in charged current scattering is reconstructed from the transverse and
 9341 longitudinal momenta and energy of the final state particles according to

$$\begin{aligned} Q_h^2 &= \frac{1}{1-y_h} \sum p_t^2 \\ y_h &= \frac{1}{2E_e} \sum (E - p_z). \end{aligned} \quad (12.4)$$

9342 There have been many refinements used in the reconstruction of the kinematics, as discussed e.g. in [796],
 9343 which for the principle design considerations, however, are of less importance.

9344 12.1.3 Acceptance regions - scattered electron

9345 The positions of isolines of constant energy and angle of the scattered electron in the (Q^2, x) plane are given
 9346 by the relations:

$$\begin{aligned} Q^2(x, E'_e) &= sx \cdot \frac{E_e - E'_e}{E_e - xE_p} \\ Q^2(x, \theta_e) &= sx \cdot \frac{E_e}{E_e + xE_p \tan^2(\theta_e/2)}. \end{aligned} \quad (12.5)$$

9347 Following these relations, an acceptance limitation of the scattered electron angle, as due to the beam pipe
 9348 or focussing magnets, to a maximum value θ_e^{max} defines a constant minimum Q^2 which independently of E_p
 9349 is given as

$$Q_{min}^2(x, \theta_e^{max}) \simeq [2E_e \cot(\theta_e^{max}/2)]^2. \quad (12.6)$$

9350 apart from the smallest x . This is illustrated in Fig.12.3. There follows that a $179^\circ(170^\circ)$ angular cut
 9351 corresponds to a minimum Q^2 of about 1(100) GeV^2 at nominal electron beam energy. One easily recognizes
 9352 in Fig.12.3 that the physics at low x and Q^2 requires to measure electrons scattered backwards from about
 9353 135° up to 179° . Their energy in this θ_e region does not exceed E_e significantly. At lower x to very good
 9354 approximation $y = E'_e/E_e$ (as can be seen from the lines $y = 0.5$ and $E'_e = 30 \text{ GeV}$ in Fig.12.3).

9355 Following Eq.12.6, Q_{min}^2 varies $\propto E_e^2$. It thus is as small as 0.03 GeV^2 for $E_e = 10 \text{ GeV}$, the injection
 9356 energy of the ring accelerator but increases to 6.0 GeV^2 for $E_e = 140 \text{ GeV}$, the maximum electron beam
 9357 energy considered in this design report, apart from smallest x , if $\theta_e^{max} = 179^\circ$. While Q_{min}^2 decreases $\propto E_e^2$,
 9358 the acceptance loss towards small x is only $\propto E_e$. The measurement of the transition region from hadronic
 9359 to partonic behavior, from 0.1 to 10 GeV^2 , therefore requires to take data at lower electron beam energies³.
 9360 These variations are illustrated in Fig.12.4 for an electron beam energy of 10 GeV , the injection energy for
 9361 the ring and a one-pass linac energy, and for the highest E_e of 140 GeV considered in this report.

³The requirement of acceptance up to 179° determines the length of the backward detector. It could be tempting to utilize this E_e dependence in the design: if one limited the backward electron acceptance to for example 178° instead of 179° this would reduce the backward detector extension in $-z$. With data taken at reduced E_e one would come back to lower Q^2 . From Eq.12.6 one derives that $E_e = 30 \text{ GeV}$ and 178° is leading to the same Q_{min}^2 of about 1.1 GeV^2 , at not extremely small x , as is $E_e = 60 \text{ GeV}$ and 179° . However, one would loose in acceptance to the lowest x , linearly with E_e . Moreover, for the present design the (inner) beam pipe radius in vertical direction is 2.2 cm . This results in an extension of about 1.5 m for the first tracker plane to register an electron scattered at 179° . If one adds about 1 m for the tracker length, and 1 m for the backward calorimeter following the tracker, one arrives at about 3.5 m backward detector length. Obviously for 178° one could reduce

LHeC - electron kinematics




Figure 12.3: Kinematics of electron detection at the LHeC. Lines of constant scattering angle θ_e and energy, in GeV, are drawn. The region of low $Q^2 \lesssim 10^2 \text{ GeV}^2$, comprising the lowest x region, requires to measure electrons scattered backwards with energies not exceeding E_e . At small energies, for $y \lesssim 0.5$ a good e/h separation is important to suppress hadronic background, as from photoproduction. The barrel calorimeter part, of about $90 \pm 45^\circ$, measures scattered electrons of energy not exceeding a few hundreds of GeV, while the forward calorimeter has to reconstruct electron energies of a few TeV. Both the barrel and the forward calorimeters measure the high x part, which requires very good scale calibration as the uncertainties diverge $\propto 1/(1-x)$ towards large x .




Figure 12.4: Kinematics at low x and Q^2 of electron and hadronic final state detection at the LHeC with an electron beam energy of 10 GeV (top) as compared to 140 GeV (bottom). At larger x , the iso- θ_e lines are at about constant $Q^2 \propto E_e^2$. At low x , the scattered energies, not drawn here, are approximately at $E'_e \simeq (1 - y) \cdot E_e$, and at lower Q^2 and x one has $E_h \simeq E_e - E'_e \simeq y \cdot E_e$. At very high E_e part of the very low Q^2 region may be accessible with the electron tagged along the e beam direction, outside the central detector, and the kinematics measured with the hadronic final state.

9362 Electrons scattered forward correspond to scattering at large $Q^2 \geq 10^4 \text{ GeV}^2$, as is illustrated in the
 9363 zoomed kinematic region plot Fig. 12.5. The energies in the very forward region, $\theta_e \lesssim 10^\circ$, exceed 1000 GeV.
 9364 For large E_e and x , Eq. 12.5 simplifies to $Q^2 \simeq 4E_e E'_e$, i.e. a linear relation of Q^2 and E'_e which is independent
 of x and of E_p , apart from the fact that $Q_{max}^2 = s$.




Figure 12.5: Kinematics of electron detection in the forward detector region corresponding to large $Q^2 \geq 10^4 \text{ GeV}^2$. The energy values are given in GeV. At very high Q^2 the iso- E'_e lines are rather independent of x , i.e. $Q^2(x, E'_e) \simeq 4E_e E'_e$.

9365

9366 12.1.4 Acceptance regions - hadronic final state

9367 The positions of isolines in the (Q^2, x) plane of constant energy and angle of the hadronic final state,
 9368 approximated here by the current jet or struck quark direction, are given by the relations:

$$\begin{aligned}
 Q^2(x, E_h) &= sx \cdot \frac{x E_p - E_h}{x E_p - E_e} \\
 Q^2(x, \theta_h) &= sx \cdot \frac{x E_p}{x E_p + E_e \cot^2(\theta_h/2)}
 \end{aligned}
 \tag{12.7}$$

9369 and are illustrated in Fig. 12.6. At low $x \lesssim 10^{-4}$, the hadronic final state is emitted backwards, $\theta_h > 135^\circ$,
 9370 with energies of a few GeV to a maximum of E_e . Lines at constant y at low x are approximately at
 9371 $y = 1 - E'_e/E_e$ and $E'_e + E_h = E_e$, i.e. $y = E_h/E_e$. Final state physics at lowest $x \lesssim 3 \cdot 10^{-6}$ requires access
 9372 to the backward region within a few degrees of the beam pipe (Fig. 12.6). This is the high y region in which
 9373 the longitudinal structure function is measured.

the first 1.5 m to say 80 cm but one would still like to have a sizable tracker length for achieving some sagitta to determine the charge of the scattered electron and perhaps arrive at an overall backward detector length of about 2.5 m. While this is an interesting reduction one loses the lowest x corner which opens $\propto E_e$. The access to lowest x in the DIS region is a fundamental part of the LHeC physics program and thus the about 179° design requirement has been kept. There are reasons to take data with reduced E_e as for F_L , thus the LHeC detector will access the region below 1 GeV^2 too.

LHeC - hadronic final state kinematics




Figure 12.6: Kinematics of hadronic final state detection at the LHeC. Lines of constant energy and angle of the hadronic final state are drawn, as represented by simple kinematics of the struck quark. One easily recognizes that the most demanding region is the large x domain, where very high energetic final state particles are scattered close to the (forward) direction of the proton beam. The barrel region, of about $90 \pm 45^\circ$, is rather modest in its requirements. At low x the final state is not very energetic, $E_h + E'_e \simeq E_e$, and scattered into the backward detector region.

9374 The x range accessed with the barrel calorimeter region, of θ_h between 135° and 45° , is typically around
 9375 10^{-4} and smaller than a decade for each Q^2 , as can be seen in Fig. 12.6. The hadronic energies in this
 9376 part do not exceed typically 200 GeV. The detector part which covers this region is quite large but the
 9377 requirements are modest. One might even be tempted to consider a two-arm spectrometer only. However,
 9378 the measurement of missing transverse energy and the importance of using the longitudinal momentum
 9379 conservation for background and radiative correction reductions, with the $E - p_z$ criterion, demand the
 9380 detector to be hermetic and complete.

9381 For the measurement of the hadronic final state the forward detector is most demanding. Due to the
 9382 high luminosity, the large x region will be populated and a unique physics program at large x and high Q^2
 9383 may be pursued. In this region the relative systematic error increases like $1/(1-x)$ towards large x , see
 9384 below this section. At high x and not extreme Q^2 the $Q^2(x, E_h)$ line degenerates to a line $x = E_h/E_p$ as
 9385 can be derived from Eq. 12.7 and be seen in Fig. 12.6. High x coverage thus demands the registration of up
 9386 to a few TeV of energy close to the beam pipe, i.e. a dedicated high resolution calorimeter is mandatory for
 9387 the region below about $5 - 10^\circ$ extending to as small angles as possible. A minimum angle cut $\theta_{h,min}$ in the
 9388 forward region, the direction of the proton beam, would exclude the large x region from the hadronic final
 9389 state acceptance (Fig. 12.6), along a line

$$Q^2(x, \theta_{h,min}) \simeq [2E_p x \tan^2(\theta_{h,min}/2)]^2, \quad (12.8)$$

9390 which is linear in the $\log Q^2, \log x$ plot and depends on E_p only. Thus at $E_p = 7$ TeV the minimum Q^2
 9391 is roughly $(1000[100]x)^2$ at a minimum angle of $10[1]^\circ$. Since the dependence in Eq. 12.8 is quadratic with
 9392 E_p , lowering the proton beam energy is of considerable interest for reaching the highest possible x and
 9393 overlapping with the large x data of previous experiments or searches for specific phenomena as intrinsic
 9394 heavy flavour.

9395 12.1.5 Acceptance at the High Energy LHC

9396 Presently one considers to build a high energy (HE) LHC in the thirties with proton beam energies of
 9397 16 TeV [797]. Such an accelerator would better be combined with an electron beam of energy exceeding the
 9398 60 GeV, considered as default here, in order to profit from the doubled proton beam energy and to limit the
 9399 asymmetry of the two beam energies. Choosing the 140 GeV beam mentioned above in this section as an
 9400 example, Figure 12.7 displays the kinematics and acceptance regions for given scattering angles and energies
 9401 of the electron (dashed green and red) and of the hadronic final state (black, dotted and dashed dotted).
 9402 The cms energy in this case is enhanced by about a factor of five. The maximum Q^2 reaches 10 TeV^2 , which
 9403 is 10^6 times higher than the typical momentum transfer squared covered by the pioneering DIS experiment
 9404 at SLAC. The kinematic constraints in terms of angular acceptance would be similar to the present detector
 9405 design as can be derived from the Q^2, x plot. At very high x (Q^2) the energy E_h (E'_e) to be registered would
 9406 be doubled. With care in the present design, one would probably be able to use the main LHeC detector
 9407 components also in the HE phase of the LHC.

9408 12.1.6 Energy Resolution and Calibration

9409 The LHeC detector is dedicated to most accurate measurements of the strong and electroweak interaction
 9410 and to the investigation of new phenomena. The calorimetry therefore requires:

- 9411 • Optimum scale calibrations, as for the measurement of the strong coupling constant. This is much
 9412 helped by the redundant kinematic reconstruction and kinematic relations, as $E'_e \simeq E_e$ at low Q^2 ,
 9413 $E'_e + E_h \simeq E_e$ at small x , the double angle reconstruction [798] of E'_e and the transverse momentum
 9414 balance of p_T^e and p_T^h . From the experience with H1 and the much increased statistics it is assumed
 9415 that E'_e may be calibrated to $0.1 - 0.5\%$ and E_h to $1 - 2\%$ accuracy. The latter precision will be most
 9416 crucial in the forward, high x part of the calorimeter because the uncertainties diverge $\propto 1/(1-x)$
 9417 towards large x .

Kinematics at HE-LHeC




Figure 12.7: Scattered electron and hadronic final state kinematics for the HE-LHC at $E_p = 16$ TeV coupled with a 140 GeV electron beam. Lines of constant scattering angles and energies are plotted. The line $y = 0.011$ defines the edge of the HERA kinematics and $y = 0.19$ defines the edge of the default machine considered in this report ($E_e = 60$ GeV and $E_p = 7$ TeV).

9418
9419
9420
9421
9422
9423
9424
9425
9426
9427
9428
9429

- High resolution, for the reconstruction of multi-jet final states as from the $H \rightarrow b\bar{b}$ decay. This is a particular challenge for the forward calorimeter. While detailed simulations are still ongoing one may assume that $(10 - 15)/\sqrt{E/GeV}$ % resolutions for E'_e and $(40 - 50)/\sqrt{E/GeV}$ % for E_h are appropriate, with small linear terms. These requirements are very similar to the ATLAS detector which quotes electromagnetic resolutions of $10/\sqrt{E/GeV} \oplus 0.007$ % and hadronic energy resolutions of $50/\sqrt{E/GeV} \oplus 0.03$ %. The basic electromagnetic calorimeter choice for the LHeC can be for Liquid Argon (LAr)⁴. The hadronic calorimeter is outside the magnets and serving also for the magnetic flux return may be built as a tile calorimeter with the additional advantage of supporting the whole detector. The first year of operating the ATLAS combined LAr/TileCal calorimeter has been encouraging. Some special calorimeters are needed in the small angle forward region ($\theta \lesssim 5^\circ$) where the deposited energies are extremely large, and also in the backward region ($\theta \geq 135^\circ$) where the electron detection of modest energy is a special task.

⁴In H1 very good experience has been collected with the longterm stability of the LAr calorimeter. A special demand is the low noise performance because the measurements at small inelasticity y are crucial for reaching large Bjorken x . In this region a small misidentified deposition of energy in the backward part of the detector can spoil the measurement at low $y \lesssim 0.01$, as can be seen from Eq. 12.4.

9430
9431
9432
9433

- Good electron-hadron separation, as for the electron identification at high y and low Q^2 (backwards) or high Q^2 (in the extreme forward direction). This is a requirement on the segmentation of the calorimeters and on building trackers in front also of the forward and backward calorimeters to support the energy measurements and the electron identification in particular.

9434

Obviously the calorimetry needs to be hermetic for the identification of the charged current process and good measurement of $E_{T,miss}$. These considerations are also summarised in Tab.12.1.

region of detector approximate angular range / degrees	backward 179 - 135	barrel 135 -45	forward 45-1
scattered electron energy/GeV	3-100	10-400	50-5000
x_e	$10^{-7} - 1$	$10^{-4} - 1$	$10^{-2} - 1$
elm scale calibration in %	0.1	0.2	0.5
elm energy resolution $\delta E/E$ in % $\cdot \sqrt{E/GeV}$	10	15	15
hadronic final state energy/GeV	3-100	3-200	3-5000
x_h	$10^{-7} - 10^{-3}$	$10^{-5} - 10^{-2}$	$10^{-4} - 1$
hadronic scale calibration in %	2	1	1
hadronic energy resolution in % $\cdot \sqrt{E/GeV}$	60	50	40

Table 12.1: Summary of calorimeter kinematics and requirements for the default design energies of $60 \times 7000 \text{ GeV}^2$, see text. The forward (backward) calorimetry has to extend to 1° (179°).

9435

9436

12.1.7 Tracking Requirements

9437

The tracking detector has to enable

9438
9439
9440
9441
9442
9443

- Accurate measurements of the transverse momenta and polar angles
- Secondary vertexing in a maximum polar angle acceptance range
- Resolution of complex, multiparticle and highly energetic final states in forward direction
- Charge identification of the scattered electron
- Distinction of neutral and charged particle production
- Measurement of vector mesons, as the J/ψ or Υ decay into muon pairs

9444

The transverse momentum resolution in a solenoidal field can be approximated by

$$\frac{\delta p_T}{p_T^2} = \frac{\Delta}{0.3BL^2} \cdot \sqrt{\frac{720}{N+4}} \quad (12.9)$$

9445
9446
9447
9448
9449
9450
9451
9452
9453

where B is the field strength, Δ is the spatial hit resolution and L the track length in the plane transverse to the beam direction, and N being the number of measurements on a track, which enters as prescribed in [799]. As an example, for $B = 3.5 \text{ T}$, $\Delta = 10 \mu\text{m}$, $N = 4 + 5$ and $L = 0.42 \text{ m}$ one obtains a transverse momentum measurement accuracy of about $3 \cdot 10^{-4}$. A simulation, using the LICTOY program [800], of the transverse momentum, transverse impact parameter and polar angle resolutions is shown in Fig. 12.8. One can see that the estimate following Eq. 12.9 is approximately correct for larger momenta where the multiple scattering becomes negligible. This momentum resolution, in terms of $\delta p_T/p_T^2$ is about ten times better than the one achieved with the H1 central drift chamber. It is similar to the ATLAS momentum resolution for central tracks and thus considered to be adequate for the enlarged momenta at LHeC as compared to




Figure 12.8: Transverse momentum (top), impact parameter (middle) and polar angle (bottom) measurement resolutions as function of the polar angle for the default detector design for four values of track transverse momentum.

HERA and the goal of high precision vertex tagging. One finds that the impact parameter resolution, for high momenta, is a factor of eight improved over the H1 or ZEUS result.

In backward direction, a main tracking task is to determine the charge of the scattered electron or positron, which has momenta $E'_e \leq E_e$, down to a few GeV for DIS at high $y \simeq 1 - E'_e/E_e$. With a beam spot as accurate as about $10 \times 30 \mu\text{m}^2$ and the beam pipe radius of a few cm only, the backward Silicon strip tracker will allow a precise E/p determination when combined with the backward calorimeter, even better than has been achieved with the H1 backward silicon detector [68].

In the forward region, $\theta < 5^\circ$, as may be deduced from Figs. 12.5, 12.6, the hadronic final state, for all Q^2 , and the scattered electron, when scattered "back" at high Q^2 , are very energetic. This requires a dedicated calorimeter. Depending on the track path and momentum, the track sagitta becomes very small, for example about $10 \mu\text{m}$ for a 1 TeV track momentum and a 1 m track length. In such extreme cases of high momenta, the functionality of the tracker will be difficult to achieve: the sagitta becoming small means that there will be limits to the transverse momentum measurement while the ability to distinguish photons and electrons will be compromised by the high probability of showering and conversion when the pipe is passed under very small angles. A forward tracker yet is considered to be useful down to small angles for the reconstruction of the event structure, the rejection of beam induced background and the reconstruction of forward going muons. This region requires detailed simulation studies in a next phase of the project.

12.1.8 Particle Identification Requirements

The requirements on the identification of particles focus on the identification of the scattered electron, a reliable missing energy measurement and precision tracking for measuring the decay of charm and beauty particles, the latter rather on a statistical basis than individually. Classic measurements as the identification of the D meson from the $K\pi\pi$ decay with a slow pion or the identification of B production from high p_T leptons require a very precise track detector. The tracker should determine some dE/dX properties but there is no attempt to distinguish strange particles, as kaons from pions, as the measurement of the strange quark distribution is traced back to charm tagging in CC events. The identification of muons, apart from some focus on the forward and backward direction, is similar to that of pp detectors. In addition a number of taggers is foreseen to tag

- electrons scattered near the beam pipe in backward direction to access low Q^2 events and control the photoproduction background;
- photons scattered near the beam pipe in backward direction to measure the luminosity from Bethe Heitler scattering;
- protons scattered in forward direction to measure diffractive DIS in ep scattering and to tag the spectator proton in en scattering in electron-deuteron runs;
- neutrons scattered in forward direction to measure pion exchange in ep scattering and to tag the spectator neutron in ep scattering in electron-deuteron runs;
- deuterons scattered in forward direction in order to discover diffraction in lepton-nucleus scattering.

From the perspective of particle identification therefore no unusual requirements are derived. One needs a state of the art tracker with a very challenging forward part and a tagger system with the deuteron as a new component in forward direction.

12.1.9 Summary of the Requirements on the LHeC Detector

The considerations discussed in this chapter along with the constraints from machine operation and the physics program let to following main items for the detector design.

1. The LHeC experiment has to be operated in parallel to the other LHC experiments and has to be set up in accordance to CERN regulations.

- 9498 2. The detector realization requires a modular design and construction with the assembly process done in
9499 parallel partly at surface level and partly in the experimental area following the LHC machine running
9500 and maintenance periods.
- 9501 3. The beam pipe will host the electron beam along with the two LHC counter rotating proton beams.
9502 The non interacting proton/ion beam has to bypass the IP region guided through the same beam pipe
9503 housing the electron and interacting proton/ion beam.
- 9504 4. The detector should be modular and flexible to accommodate the high acceptance as well as the high
9505 luminosity running foreseen for the two main physics programs. The flexibility should accommodate
9506 reducing/enhancing the energy asymmetry of the beams - section 13.3.
- 9507 5. The detector design can profit from the experience at HERA and the LHC and will be based on the
9508 recent detector developments in order to meet the ambitious physics requirements, summarized in pre-
9509 vious chapter, using settled technology, avoiding extended R&D programs and being of comparatively
9510 reasonable cost.
- 9511 6. Mechanics/services have to be optimized minimizing the amount of material in sensitive regions of the
9512 experimental setup.
- 9513 7. The detector has to be operated in a high luminosity environment L . High \bar{L} is anticipated with small
9514 beam spot sizes ($\sigma_x \approx 30\mu m$, $\sigma_y \approx 16\mu m$), small β^* and relatively large IP angles (see acc. part). On
9515 the other hand β^* has to be chosen to eliminate effects of parasitic bunch crossings. The machine and
9516 detector requirements near the IP is an optimization problem.
- 9517 8. The detector must experience acceptable backgrounds. The design has to be background insensitive as
9518 far as possible and the machine has to incorporate masks, shielding's and an appropriate optics design
9519 that minimizes background sources and a vacuum profile that reduces backgrounds. The detectors
9520 have to be radiation hard.
- 9521 9. It might be necessary to have insertable/removable shielding protecting the detector against injection
9522 and poor machine performance.
- 9523 10. Special Interaction Region (IR) instrumentation for tuning of the machine with respect to background
9524 and luminosity is needed. Radiation detectors e.g. near mask and tight apertures are useful for fast
9525 identification of background sources. Fast bunch related informations are useful for beam optimization
9526 in that context.
- 9527 11. Good vertex resolution for decay particle secondary vertex tagging is required, which implies a small
9528 radius and thin beam pipe optimized in view of synchrotron radiation and background production -
9529 see section 9.9.
- 9530 12. The detector will have one solenoid in its default version building a homogenous field in the tracking
9531 area of 3.5 T extending over $z = +370cm, -200cm$. Solenoid options are described in section 13.2.
- 9532 13. The tracking and calorimetry in the forward and backward directions has to be set up to take into
9533 account the extreme asymmetry of the production kinematics. The layout and choice of technology for
9534 the detector design will be chosen accordingly. The tracker requires to be optimized in view of energy
9535 flow corrections for optimal calorimetry. The highest affordable granularity anticipated for tracking
9536 and calorimeter ensures the best energy/momentum measurements.
- 9537 14. Very forward/backward detectors have to be set up to access the diffractive produced events and
9538 measuring the luminosity with high precision, respectively - chapter 14.

Chapter 13

Central Detector

Following the considerations of the physics requirements and the technical and operational constraints outlined in chapter 12.1, a detector design for high precision and large acceptance Deep Inelastic Scattering is presented. The detectors for the Linac-Ring or the Ring-Ring options are nearly identical: the two notable differences are the dipoles in the Linac-Ring case for separating the e and the p beams and the larger beam pipe due to the wider synchrotron radiation fan. For practical reasons of this report the more complicated Linac-Ring detector has been chosen as the baseline, termed version A. This evidently affects the solenoid-dipole configuration and the inner shape of the tracker but is of no severe concern. For the Ring-Ring case the luminosity may be maximised by inserting focussing quadrupoles near to the IP. This causes the inner detector to be designed modular such that a transition could be made between the two phases, with the quadrupoles to achieve maximum luminosity and without, to ensure maximum polar angle acceptance ¹.

13.1 Basic Detector Description

The LHeC detector is asymmetric in design, reflecting the beam energy asymmetry and reducing cost. It is a general purpose 4π detector, which consists of an inner silicon tracker, with extended forward and backward parts, surrounded by an electromagnetic calorimeter, which is separated from the hadronic calorimeter by a solenoid with 3.5 T field incorporating dipoles, in the Linac-Ring case, Fig. 13.1, or not, in the Ring-Ring case, Fig. 13.2. The hadron calorimeter is enclosed in a muon tracker system, not shown here but discussed in section 13.7. The main detector is complemented by hadron tagging detectors in the forward direction and a polarimeter and luminosity measurement system backwards, as is also presented below. Its longitudinal extension is determined by the need to cover polar angles down to 1° at the given beam pipe dimension. Its radial size is mainly determined by the requirement of full energy containment of hadronic showers in the calorimeter.

The dipoles for the Linac-Ring IR cannot be of a too large radius to act on the beam and be affordable. Their bulk material should also not compromise tracking and electromagnetic energy measurements and thus have to be placed outside the electromagnetic calorimeter, chosen to be Liquid Argon. The solenoid cost scales, as discussed above (see Eq.12.1), approximately with its radius which in absolute allows tens of millions CHF to be economised, with the solenoid placed inside the hadronic calorimeter also considering the cost of the 10 kt of iron needed for shielding. In order to minimize cost and material, it appears appropriate to foresee a single cryostat housing the electromagnetic calorimeter and the solenoid and dipole magnets. This leads also to some modification of the forward and backward calorimeter inserts, which can be seen

¹The very recent optics design results suggest that there is only a factor of two difference between the luminosity achievable with and without the quadrupoles. That is not enough to justify considering two measurement phases, in particular having in mind that such a transition, as happened at HERA, may take much more time than one would estimate beforehand. If the Ring-Ring solution was chosen, therefore, it would most likely only require one unchanged main detector configuration. The baseline considered here would be fully adequate for this case, with less complication of the magnets and a narrower pipe.

9570 comparing the Linac-Ring Fig. 13.1 with the Ring-Ring Fig. 13.2. Since for the physics performance it is
 9571 evidently advantageous to place the solenoid outside the hadronic calorimeter, this option, termed B, has
 9572 also been studied and is discussed in section 13.2. The radius of the large coil would be about 2.5 m which
 9573 still compares well with for example the H1 and the CMS coils but is an option for the Ring-Ring machine
 design only and not the baseline currently.




Figure 13.1: Schematic rz view of the detector design for the Linac-Ring machine option showing the characteristic dipole and solenoid placement between the electromagnetic and the hadronic calorimeters. The proton beam, from the right, collides with the electron beam, from the left, at the IP which is surrounded by a central tracker system complemented by large forward and backward tracker telescopes followed by sets of calorimeters. The detector as sketched here, i.e. without the muon tracking system, has a radius of 2.6 m and extends from about $z = -3.6$ m to $z = +5.9$ m in the direction of the proton beam.

9574 The Ring-Ring configuration possibly requires separate data taking phases with maximum polar angle
 9575 acceptance, for physics at low and high x , and with ultimate luminosity, for electroweak physics and the search
 9576 for rare phenomena. Correspondingly, the LHeC inner detector is designed here with a modular structure as
 9577 is illustrated in Figs. 13.3 and 13.4 which show the detector without and with the low β quadrupoles inserted
 9578 to accommodate for either configuration, respectively. This requires the removal of the forward/backward
 9579 tracking setup (shown in red in Fig. 13.3) and the subsequent reinstallation of the external forward/backward
 9580 electromagnetic and hadronic calorimeter plugins near to the vertex. The high luminosity apparatus would
 9581 have a polar angle acceptance coverage of about 8° - 172° for an estimated gain in luminosity of slightly
 9582 higher than a factor of two with respect to the large acceptance configuration. The Ring-Ring and Linac-
 9583 Ring detectors also differ due to the different optics and the beam pipe geometry.

9584 In the Ring-Ring design the e and p/A beams collide with a small non-zero crossing angle, large enough
 9585 to avoid parasitic crossings, which for a 25 ns bunch crossing occur at ± 3.75 m from the IP. Additional
 9586 masks are used to shield the inner part of the detector from synchrotron radiation generated upstream of
 9587 the detector.
 9588

9589 For the Linac-Ring design, the dipole field in the detector area which allow for head-on collisions and
 9590 provide the required separation, produces additional synchrotron radiation which has to pass through the
 9591 interaction region requiring a larger beam pipe. This difference results in a factor of two wider extension of
 9592 the horizontal beam pipe in the outer region in the Linac-Ring case, which in this regard is the unfavorable




Figure 13.2: Schematic rz view of the detector design for the Ring-Ring machine option. Note that the outer part of the forward and backward calorimeters ends at smaller radii, as compared to the Linac-Ring case, since there are no dipole magnets foreseen.

9593 solution but unavoidable and necessary fully containing the synchrotron radiation fan. The radius of the
 9594 circular part has been chosen according to tentative choices of the LHC upgrade beam pipe dimensions.

9595 According to a first estimate of the synchrotron radiation and an initial placement of masks, shielding
 9596 the Ring-Ring detector from direct and backscattered photons, the beam pipe geometries have been chosen
 9597 as shown in Fig. 13.5 for the Ring-Ring case and in Fig. 13.6 for the Linac-Ring case.

9598 As already mentioned, the necessity to register particle production down to 1 and 179° poses severe
 9599 constraints on the material and the thickness of the pipe. In the design as shown here, a beryllium pipe
 9600 would have 3.0 (1.5) mm thickness in the Linac-Ring (Ring-Ring) case. An extensive R&D program is
 9601 needed aiming for higher stability of the beam pipe at given dimensions and for thinner/lighter beam wall
 9602 construction resulting in higher transparency for all final state particles. This R&D program is necessary
 9603 regardless of which machine option for the LHeC facility is selected. It may also turn out to be advantageous
 9604 to use a trumpet shaped beampipe when this problem gets revisited in a more advanced phase of the LHeC
 9605 design when more detailed simulations will be available and results of pipe material developments become
 9606 known.

9607 In order to ensure optimal polar angle acceptance, the innermost subdetector dimensions have to be
 9608 adapted to the beam pipe shape. Fig. 13.7 illustrates the configuration that a circular silicon tracker would
 9609 imply and the corresponding acceptance losses. These can be reduced as shown in Fig. 13.8 if the detector
 9610 acceptance follows as close as possible the elliptic-circular shape of the pipe. Electrons scattered at high
 9611 polar angle, corresponding to small $Q^2 \sim 1 \text{ GeV}^2$, will only be registered in the inner part of the azimuthal
 9612 angle region for the nominal electron beam energy. As had been shown in chapter 12.1 (Eq. 12.6), the lowering
 9613 of the electron beam energy effectively reduces the strong requirement of measuring up to about 179° , at
 9614 the expense however, of a somewhat reduced acceptance towards lowest Bjorken x .

9615 The optimum configuration of the inner detector will be revisited when the choice between the Linac-Ring
 9616 and the Ring-Ring option is made. It represents in any case one of the most challenging problems to be
 9617 solved for the LHeC.




Figure 13.4: An rz cross section and dimensions of the main detector (muon detector not shown) for the Ring-Ring detector version (no dipoles) in which the luminosity is maximised by replacing the forward and backward tracker telescopes by focusing, low β quadrupole magnets at ± 1.2 m away from the nominal interaction point. The polar angle acceptance is thus reduced to about $8 - 172^\circ$. As compared to the high acceptance detector (Fig. 13.3), the outer forward/backward calorimeter inserts have been moved nearer to the interaction point.

RR - Inner Dimensions
 Circular(x)=2.2cm; Elliptical($-x$)=-5.5, y =2.2cm




Figure 13.5: Perspective drawing of the beam pipe and its dimensions in the ring-ring configuration. The dimensions consider a 1 cm safety margin around the synchrotron radiation envelope with masks (not shown) for primary synchrotron radiation suppression placed at $z = 6, 5, 4$ m.

LR - Inner Dimensions
 Circular(x)=2.2cm; Elliptical(-x)=-10., y=2.2cm




Figure 13.6: Perspective drawing of the beam pipe and its dimensions in the linac-ring configuration. The dimensions consider a 1 cm safety margin around the synchrotron radiation envelope.

13.1.1 Baseline Detector Layout

The baseline configuration (A) of the main detector has the solenoid in between the two calorimeters, combined with a dipole field in the Linac-Ring case. The configuration B makes sense only for the Ring-Ring machine design since an outer dipole would be a bad practice for that functionality and a second cryostat with inner dipole between electromagnetic and hadronic calorimeter is bad practice as well, obviously. The main detector is subdivided into a central barrel and the forward and backward end-cap regions, which differ in their design because the forward region sees the remnant and the highly energetic ($E_h \lesssim E_p$) jet from the struck quark while the backward region sees the scattered electron of energy $E'_e \leq E_e$. The detector configuration is sketched in Fig. 13.9 with component abbreviations and some dimensions given. More detailed dimensions are given in Fig. 13.10.

For the purpose of this design, technologies had to be chosen in line with the detector requirements, see Sect. 12.1, and based on an evaluation of the technologies available or under development for the LHC experiments or foreseen for a linear collider detector. Due to its compactness and proven technological feasibility, the complete inner tracker is considered to be made of silicon. This allows to keep the radius of the magnets small, about 1 m. Based on experience with H1 and ATLAS the EMC is chosen to be a Liquid Argon (LAr) Calorimeter. The superconducting dipoles (light grey in Fig. 13.9) are placed in a common cryostat with the detector solenoid (dark grey) and the LAr EMC (green). The use of common cryostat is optimum for reducing the amount of material present in front of the hadronic barrel calorimeter. The HAC is an iron-scintillator tile calorimeter, which also guides the return flux of the magnetic field, as in ATLAS [801, 802]. In the baseline design (A) the muon detectors are placed outside of the magnetic field with the function of tagging muons, the momentum of which is determined mainly by the inner tracker.

For the Ring-Ring machine, in order to maximize the luminosity, extra focusing magnets must be placed near to the interaction point ². This would mean replacing the FST and the BST tracking detectors by the low- β quadrupoles (see Fig. 13.4), at the expense of loosing about 8° of polar angle acceptance. The modular design of the forward and backward trackers and the corresponding calorimeter modules allow the trackers to be mounted/unmounted and the calorimeter inserts to be moved in and out of position as required. The inner electromagnetic and hadronic endcap inserts, FEC1/BEC1 and FHC1/BHC1, respectively, will be removed allowing the insertion of the low β -magnets and only partially put back in. Particular attention is needed for the mechanical support structures of the quadrupoles. The structure must ensure the stability of reproducible beam steering, while interfering as little as possible with the detector. The presence of strong focussing magnets close to the interaction point was one issue experienced during HERA2 running [803].




Figure 13.7: Linac-Ring beam pipe design and acceptance gaps due to deviations of inner shapes of the forward/backward tracking detectors FST/BST (circular) and the innermost central pixel detector layer (elliptical) from the pipe shape.




Figure 13.8: Beam pipe design for Linac-Ring and optimized circular-elliptical shape following the beam pipe for all adjacent detector parts.




Figure 13.9: An rz cross section of the LHeC detector in its baseline configuration (A). In the central barrel, the following components are considered: a central silicon pixel detector (CPT); silicon tracking detectors (CST,CFT/CBT) of different technology; an electromagnetic calorimeter (EMC) surrounded by the magnets and followed by a hadronic calorimeter (HAC). Not shown is the muon detector. The electron at low Q^2 is scattered into the backward silicon tracker (BST) and its energy measured in the BEC and BHC calorimeters. In the forward region similar components are placed for tracking (FST) and calorimetry (FEC, FHC).

13.1.2 An Alternative Solenoid Placement - Option B

The configuration A is determined by the intention to keep the detector ‘small’: it uses the HAC as flux return for an inside solenoid which, for the Linac-Ring case, is combined with long dipoles. This is not ideal for the hadronic energy measurement. Therefore a second configuration (B) has been considered, to much less detail, in which the solenoid is placed outside the HAC. Option B might be of interest only for the Ring-Ring case as otherwise, the requirement of the bending dipoles to be placed right after the EMC would anyhow compromise the design requiring anyhow similar cryogenics and support structures as in option A.

In considering a solenoid around the HAC one finds, as from the CMS geometry, that the return iron would be massive, of order 10000 tons, and extend by several meters further out in radius, which may pose problems when one has the IP2 cavern in mind. One then is lead to consider using a second solenoid for an active flux return, which gives a good muon momentum reconstruction. A strong magnetic field of 3.5 T covering the barrel calorimeter (HAC) leads to a better separation of charged hadron induced showers in the HAC area compared to the sole fringe field effect in case of the inner solenoid baseline design A. The HAC would have to be designed very carefully as there would be no muon-iron return yoke following for catching shower tails. A warm EMC design with no need for a cryostat would become an option worth considering. Also extending the tracker by an extra more conventional layer of tracking chambers in front of the EMC would be an interesting possibility, with which the amount and radius of the Silicon detector may be somewhat reduced.

An overview of the detector configuration B is given in Fig.13.11. A two solenoid configuration is proposed as an innovative solution with many advantages. A similar design was proposed earlier for the 4th

²See chapter ?? for an evaluation of that possibility.




Figure 13.10: View of the baseline detector configuration (A) with some dimensions for each of the main detector components.




Figure 13.11: An rz cross section of the LHeC detector, option B, in which the solenoid is placed outside the HAC. A compensating larger solenoid is considered, see text. The muon detector is not shown but would be placed inside the second solenoid. The overall dimensions of this detector configuration are about 11 m length and 8 m diameter.

9669 Concept for an ILC Detector [795]. The second outer solenoid keeps the overall dimensions of the detector
9670 limited. A detailed consideration of option B has not been intended at this stage of the project, however,
9671 the statement is made that the option B magnet system is technically feasible and can be chosen if physics
9672 arguments require to do so and the required extra budget is made available.

9673 13.2 Magnet Design

9674 The principle magnet configuration in the Linac-Ring baseline option is introduced and the principle design
9675 of solenoid and dipole magnets as well as their cryogenic services are described. In section 13.2.5, the twin
9676 solenoid system option (detector option B) providing 3.5 T in the entire calorimeter space in combination
9677 with a 1.5 T space for a high precision muon tracking detector is addressed briefly.

9678 13.2.1 Magnets configuration

9679 The LHeC magnet system provides a 3.5 T solenoid with a free bore of 1.8 m and a coil length of 5.7 m
9680 for the bending of the particles produced in the collisions. The bore is dimensioned to provide space for
9681 the Pixel (CPT) and Strip (CST) detectors as well as the electromagnetic Liquid Argon calorimeter (EMC)
9682 immersed in a magnetic field while the hadronic tile calorimeter (HAC) and muon tagging detectors are left
9683 outside. The layout of the magnets in the baseline detector is shown in Figure 13.12. The iron present in
9684 the hadronic calorimeter also provides the return path for the solenoid magnetic field. In the Linac-Ring
9685 option also a set of 18 m long e-beam bending dipoles are required that provide 0.3 T on axis, a plus and
9686 a minus dipole of 9 m length each, respectively. The first dipole is to bring the e-beam into the collision
9687 point and the second to guide the beam away after the collision point. In the Ring-Ring option this set is
9688 obsolete. The Linac-Ring option obviously is more demanding and thus taken as the reference design and
9689 presented here. The introduction of the set of dipoles requires choosing a radial position and radial gap
9690 for these coils. Since cryogenic space is required for the solenoid as well, an elegant solution is to combine
9691 within the detector volume the dipoles and the solenoid in one cryostat, thereby minimizing the total radial
9692 gap as well as maximizing particle transparency. A second combination of cryogenic objects can be made
9693 by also housing the liquid argon electromagnetic calorimeter in the same cryostat which would reduce the
9694 radial built up of material significantly. Since a combination is easier the separate option is more demanding
9695 and therefore engineered and described here. Since the set of dipoles is 18 m long to provide the 2·2.5 Tm
9696 magnetic field integral, and the detector is 10 m long, each of the two dipoles are split in two sections. The
9697 inner superconducting sections sit with the solenoid in the same cryostat and the outer normal conducting
9698 iron based electromagnetic sections with much smaller bore of 0.3 m are positioned on the beam line at
9699 either side of the detectors, see Figure 13.12.

9700 13.2.2 Detector Solenoid

9701 The conceptual design of the solenoid is presented and where necessary some details on the dipoles are
9702 mentioned as well. The position of the solenoid with respect to the other detector components and the
9703 envelopes respected have been shown before in Figure 13.9. The longitudinal section of the LHeC baseline
9704 detector for the default detector configuration and the Linac-Ring option are shown; indicated are the
9705 position of the 3.5 T solenoid and the 0.3 T inner superconducting dipole sections. Solenoid and dipoles are
9706 on a common support cylinder and housed in a single cryostat with a free bore of 1.8 m and extending along
9707 the entire detector with a length of ≈ 10 m.

9708 The design of the solenoid is based on the very successful experience with the many detector magnets built
9709 over the past 30 years, in particular the most recent ATLAS and CMS solenoids [804], [805], [806], [807].
9710 The dimensions of the LHeC solenoid (3.5 T, 5.7 m long and 0.96 m inner radius) are about those of the
9711 ATLAS solenoid (2.0 T, 5.3 m long with 1.25 m radius) while it has to provide the magnetic field of the much
9712 larger CMS solenoid. Since the requested magnetic field is 1.75 times higher than in the ATLAS solenoid a




Figure 13.12: Configuration of the solenoid and electron beam bending dipoles in the baseline Linac-Ring detector. Longitudinal r-z section showing the position to solenoid and the two dipoles, each split in two sections, a superconducting inner section incorporated with the solenoid in one cryostat and a normal conducting iron based outer section magnet with smaller bore.

9713 double layer coil will be needed. Using well established design codes with proven records on earlier detector
 9714 magnets, the main solenoid parameters are determined and are listed in Table 13.1.

9715 The solenoid is wound in two layers internally in an Al5083 alloy support cylinder with 30 mm wall
 9716 thickness and a length of about 6 m. When finished two extensions cylinders are flanged to the central
 9717 solenoid section at either end for supporting the inner superconducting dipole sections, see Figure 13.13. In
 9718 this way the solenoid can be produced as a 6 m long coil unit in a company, transported to the integration
 9719 site where the adjacent sections are coupled and the dipoles sections can be introduced.

9720 The magnetic field generated by the system of solenoid and internal dipoles is shown in Figure 13.13.
 9721 The peaks in magnetic field in the solenoid and dipole windings as results of their combined operation at
 9722 nominal current are 3.9 and 2.6 T respectively. The B_z and B_y components of the magnetic field are shown
 9723 in Figure 13.14.

9724 The superconductor used for the solenoid is an Al stabilized NbTi/Cu Rutherford cable based on state-of-
 9725 the-art NbTi strands featuring 3000 A/mm² critical current density at 5 T and 4.2 K. A 20 strands Rutherford
 9726 cable carries the nominal current of 10 kA which is 30% of its critical current.

9727 The conductor has a comfortable temperature margin of 2.0 K when operating the coil with a forced
 9728 Helium flow enabling 4.6 K in the solenoid windings. The high purity Al used for the co-extrusion of Al
 9729 and cable is mechanically reinforced by micro-alloying with either Ni or Zn, or another qualified material, a
 9730 technology qualified for the ATLAS solenoid. Two conductor units of 5.4 km would be perfect, corresponding
 9731 to the two layers in the coil windings. Eventually internal splices are acceptable and can be made reliably
 9732 by overlapping a full turn and performing welding on the two adjacent thin edges of the conductors.

9733 The conductor insulation is a double layer of 0.3 mm thick polyimide/glass tape (or similar product) featuring
 9734 a high breakdown voltage of more than 2 kV and robustness for coil winding damage in order to limit the
 9735 risk of turn-to-turn shorts. Coil winding can be performed either using the wet winding technique with
 9736 pre-impregnated tape or a vacuum impregnation technique may be applied. Both techniques are appropriate

Property	Parameter	value	unit
Dimensions	Cryostat inner radius	0.900	m
	Length	10.000	m
	Outer radius	1.140	m
	Coil windings inner radius	0.960	m
	Length	5.700	m
	Thickness	60.0	mm
	Support cylinder thickness	0.030	m
	Conductor section, Al-stabilized NbTi/Cu + insulation	30.0×6.8	mm^2
	Length	10.8	km
	Superconducting cable section, 20 strands	12.4×2.4	mm^2
Masses	Superconducting strand diameter Cu/NbTi ratio = 1.25	1.24	mm
	Conductor windings	5.7	t
	Support cylinder, solenoid section + dipole sections	5.6	t
	Total cold mass	12.8	t
	Cryostat including thermal shield	11.2	t
Electro-magnetics	Total mass of cryostat, solenoid and small parts	24	t
	Central magnetic field	3.50	T
	Peak magnetic field in windings (dipoles off)	3.53	T
	Peak magnetic field in solenoid windings (dipoles on)	3.9	T
	Nominal current	10.0	kA
	Number of turns, 2 layers	1683	
	Self-inductance	1.7	H
	Stored energy	82	MJ
	E/m, energy-to-mass ratio of windings	14.2	kJ/kg
	E/m, energy-to-mass ratio of cold mass	9.2	kJ/kg
Margins	Charging time	1.0	hour
	Current rate	2.8	A/s
	Inductive charging voltage	2.3	V
	Coil operating point, nominal / critical current	0.3	
	Temperature margin at 4.6 K operating temperature	2.0	K
Mechanics	Cold mass temperature at quench (no extraction)	~ 80	K
	Mean hoop stress	~ 55	MPa
Cryogenics	Peak stress	~ 85	MPa
	Thermal load at 4.6 K, coil with 50% margin	~ 110	W
	Radiation shield load width 50% margin	~ 650	W
	Cooling down time / quench recovery time	4 and 1	day
	Use of liquid helium	~ 1.5	g/s

Table 13.1: Main parameters of the baseline LHeC Solenoid providing 3.5 T in a free bore of 1.8 m.




Figure 13.13: Magnetic field of the magnet system of solenoid and the two internal superconducting dipoles at nominal currents (effect of iron ignored). The position of the peak magnetic field of 3.9 T is local due to the adjacent current return heads on top of the solenoid where all magnetic fields add up.




Figure 13.14: Magnetic field components B_z (solenoid) and B_y (set of internal dipoles) on the beam axis across 12 m in z . Note, the magnetic field of the external electromagnets are not included here.




Figure 13.15: Cryostat of the magnet system. Left: the integrated cryostat, and right: longitudinal cut through the cryostat comprising a single cold mass of solenoid and internal superconducting dipole sections.

9737 provided fully qualified with the coil winding contractor.

9738 Once the solenoid windings are finished and delivered to the coil integration site, the dipole coil sections
 9739 are inserted in slots milled into the outer surface of the support cylinder, see section 13.2.3. The four dipole
 9740 upper and lower coil sections are separately produced as flat racetrack coils and then bent onto the fully
 9741 assembled support cylinder. Next all interconnections and bus connections to the current leads are laid down
 9742 and the cold mass is inserted in the cryostat.

9743 The cryostat design is shown in Figure 13.15. The cold mass is supported from the cryostat with a system of
 9744 triangle brackets, a proven technique providing a very compact solution [804], [805]. The cryostat is equipped
 9745 with thermal shields and multi-layer super-insulation in the usual way.

9746 The coil windings of both solenoid and dipole sections are cooled by conduction by forced flow liquid helium
 9747 circulating in 14 mm sized cooling tubes that are attached to the outer surface of the integrated support
 9748 cylinder. The two layer winding pack of 60 mm radial built and fully bonded to the support cylinder is
 9749 sufficiently thin to warrant a thermal gradient in the winding pack of less than 0.1 K. The total radial
 9750 material built of essentially Al alloys is about 150 mm featuring an acceptable effective radiation thickness.
 9751 Quench protection of the solenoid with 82 MJ stored energy in a cold mass with 9 kJ/kg can be done
 9752 safely. The stored energy is absorbed by the cold mass enthalpy (no energy extraction) and the cold mass
 9753 temperature will raise to a safe 80 K level. Heat drains are incorporated in the coil windings to accelerate
 9754 quench propagation and in addition an active heater system will implemented for the same purpose.

9755 13.2.3 Detector integrated e-beam bending dipoles

9756 The two e-beam bending dipoles are positioned symmetrically around the beams intersection point. As
 9757 outlined before each 9 m long dipole is split into a superconducting section integrated with the central
 9758 solenoid and a normal conducting iron based electro-magnet positioned around the beam outside the main
 9759 detector envelope. The external dipole magnets are conventional and will not be further detailed here. The
 9760 principle parameters of the superconducting dipole sections are listed in Table 13.2.

9761 13.2.4 Cryogenics for magnets and calorimeter

9762 The cryogenic operating conditions are achieved by circulating forced flow two-phase helium in cooling pipes
 9763 attached to the Al-alloy coil support cylinder. Electric powering of the solenoid and dipole magnets at 10




Figure 13.16: Principle cryogenic flow scheme for the cooling of the superconducting magnets.




Figure 13.17: Principle cryogenic flow scheme for the cooling of the liquid argon calorimeter.

	Plus coil	Minus coil	
Magnetic field on axis	0.3		T
Peak magnetic field in windings (solenoid off)	0.7		T
Peak magnetic field in windings (solenoid on)	2.6		T
Dipole length (including external sections)	9.0		m
Field integral internal section (sc dipole)	1.6	1.0	Tm
Field integral external section (iron magnet)	1.1	1.7	Tm
Operating current	2.0		kA
Stored Energy	1.9	1.2	MJ
Coil inductance	0.50		H
Coil inner / outer radius	1.042/1052		m
Coil length	6.00	3.70	m
NbTi/Cu conductor diameter (12 strands Rutherford cable)	2.0		mm
Conductor length	5.4	3.6	km

Table 13.2: Main design parameters of the set of superconducting electron beam bending dipoles.

9764 and 2 kA, respectively, is through two pairs of low-loss high-temperature superconducting current leads. The
9765 current leads are housed in a separate service cryostat installed at distance in a side cavern, a non-radiation
9766 environment. The service cryostat contains a larger amount of helium sufficient for a safe 1-2 hours ramp
9767 down in the case of refrigerator failure as well as to maintain the magnets at operating temperature for a
9768 few hours. Redundant centrifugal pumps provide for circulation of the slightly sub-cooled liquid helium to
9769 the magnets. The two-phase return flow is brought to a phase separator in the service cryostat. A combined
9770 superconducting link and helium transfer line connects the service cryostat with the current leads and helium
9771 buffer to the magnets. For this circuit static and dynamic losses of the magnets and transfer lines have to be
9772 taken into account, which are about 85 W. With 50% contingency the losses amount to 130 W. For reasons
9773 of flow stability the vapor quality of the return flow shall not exceed 10%.
9774 The mass flow rate of the pump is calculated to 65 g/s maximum. We assume a thermo-hydraulic efficiency of
9775 the pump of 35%, a value based on measurements on already running similar systems. The pump introduces
9776 an additional 40 W to the system.
9777 The refrigerator is at proximity to the cryostat and the compressor set is installed on surface. The expected
9778 modest thermal loss of the magnet system and its proximity cryogenics like service cryostat and transfer lines
9779 amounts to some 200 W@4.5 K. The estimated overall system loss suggest a small sized standard refrigerator
9780 in the class of 300 to 400 W@4.5 K. The thermal load of the system is summarized in Table 13.3. Figure 13.16
9781 shows the simplified flow scheme of the helium cryogenic system.

Component heat load at temperature		4.5 K	20-300 K	40-80 K
Magnets	static	45 W		430 W
	dynamic	30 W		
Transfer line/bus	static	10 W		150 W
Valve box cryostat	static	10 W		150 W
Helium pump	static	40 W		
Current leads	static		1.0 g/s	
Sums with and extra 50% contingency		200 W	1.5 g/s	1100 W

Table 13.3: Thermal load of the cryogenics system including magnets and helium distribution.

9782 A liquid Argon calorimeter is envisaged as part of an EMC. As mentioned before, it can be installed
9783 in a separate cryostat or preferably share the cryostat with the solenoid. In the latter case the systems
9784 compactness is increased and the inner thermal shield can be omitted. The calorimeter will have an overall
9785 18 m^3 volume from which approximately 12 m^3 will be slightly sub-cooled liquid argon. Cooling is with two-
9786 phase liquid nitrogen in longitudinal pipe runs and its circulation is provided by two redundant small sized
9787 liquid nitrogen pumps. The liquid nitrogen is supplied from a standard dewar on surface to an intermediate
9788 cryostat which serves also as the phase separator. For the liquid argon filling, a line connects from the surface
9789 to an intermediate dewar from which it is transferred to the LAr cryostat in the detector. This dewar also
9790 serves as emergency volume in the case of vacuum loss or leak problems to which the liquid argon can be
9791 transferred from the cryostat. Figure 13.17 shows the functional principle of the Argon cooling units.

9792 The cooling principles of both cryogenic systems proposed in this paper are based on previous design and
9793 experience from the much more complex ATLAS detector cryogenics.

9794 13.2.5 Twin Solenoid System

9795 Being written.

9796 13.3 Tracking Detector

9797 The constraints given by the magnet system (dipole/solenoid) force the tracking detectors to be kept as
9798 small as possible in radius.

9799 According to equation 12.9, the momentum resolution is proportional to $1/L^2$ and is therefore limited
9800 by the tracker radius. For a given magnetic field strength, the only other parameters left to improve are
9801 the intrinsic detector resolution, Δ , and the number of points sampled along the track trajectory. The
9802 forward/backward tracking extensions provide additional measurement points in these regions. Hence, a
9803 balance of number of track points (number of sensitive detector layers), material economy and costs must
9804 be found.

9805 The design adopted here is an all-Silicon detector, with very high resolution. The readout scheme must
9806 be such that a signal weighting using analog information is possible without losing the advantages of digital
9807 signal processing and on-chip zero suppression. All of the components need power and cooling, influencing
9808 the material budget of the tracker system which should be kept as low as possible. The technology used
9809 must be advanced at the industrial level, radiation hard and relatively cheap. A good candidate are `n_in_p`
9810 single sided sensors [808].

9811 In the following, the layout of a tracker system for the baseline detector configuration A is defined, along
9812 with the design criteria and possible solutions for a tracker which provides high resolution impact parameter
9813 measurement, momentum determination (as far as possible) and optimal support of the calorimetry.

9814 13.3.1 Tracking Detector - Baseline Layout

9815 The tracking detectors (Fig. 13.22) inside the electromagnetic calorimeter are all-Silicon devices. The tracker
9816 covers the pseudorapidity range $-4.8 < \eta < 5.5$ and is located inside the solenoidal field of 3.5T. Addition-
9817 ally a dipole field of 0.3T, resulting from the steering dipoles required for the Linac-Ring configuration, is
9818 superimposed.

9819 The tracker is subdivided into central (CPT, CST, CFT/CBT) and forward/backward parts (FST, BST).
9820 Fig. 13.18 shows the tracker configuration for LHeC operation at maximal acceptance in the baseline (A)
9821 detector design. More details are summarized in Tab. 13.4³. The shape of the CPT and the inner dimensions
9822 of all near-beam detectors have been chosen to maximise detector acceptance by measuring as close to the

³The item *project area* in table 13.4 describes the area which has to be equipped with appropriate Si-sensors (e.g. single-sided or double-sided sensors). An alternative would be the usage of Si-Gas detectors providing track segment information instead of track points, e.g. in the CST cylinders (Ref. [809], [810], [811])




Figure 13.18: Tracker and barrel Electromagnetic-Calorimeter rz view of the baseline detector (Linac-Ring case).

9823 beam-line as possible (see Fig. 13.19 which shows the xy view of the circular-elliptical CPT and the cylindrical
 9824 CST detectors).

9825 13.3.2 Performance

9826 Some results of preliminary tracker performance simulations using the LicToy-2.0 program [800] for the
 9827 tracker setup (see table 13.4 and Fig. 13.20), and with parameters given in table 13.5 are summarised in
 9828 Fig. 13.21. The detector performance is very good, as expected. For 1° tracks the bending solenoidal field
 9829 component (0.36T) is of the same order as the dipole field and the resulting track sagitta only reaches the
 9830 mm range when particles of momentum < 100 GeV have a track length of 250cm (see Fig. 13.18). The
 9831 tracker described here measures 1° tracks over a distance of ≈ 180 cm, and therefore high momentum tracks
 9832 will have a poor momentum determination. Nevertheless, the position information can be used to match a
 9833 track to a calorimeter deposit with high precision.

9834 The backward measurement is characterised by even shorter track lengths and in this case the analysis
 9835 has to rely on the energy measurement in the calorimeters matched to a well defined track. Thanks to
 9836 the much reduced particle flux in the backward direction due to kinematics, the performance and precision
 9837 achievable is expected to be higher. Very low Q^2 /low x processes will be more easily accessible by reducing the
 9838 electron beam energy, thus measuring at larger angles in the backward direction (see Fig. 12.3 and Fig. 12.4
 9839 and discussion in chapter 12.1).

9840 13.3.3 Tracking detector design criteria and possible solutions

9841 The experience of former attempts for an optimal detector design suggest that some criteria should be
 9842 discussed as early as possible.

9843 The main items to consider [808, 813] are discussed in the following.

Central Barrel	CPT1	CPT2	CPT3	CPT4	CST1	CST2	CST3	CST4	CST5
Min. Radius R [cm]	3.1	5.6	8.1	10.6	21.2	25.6	31.2	36.7	42.7
Min. Polar Angle θ [°]	3.6	6.4	9.2	12.0	20.0	21.8	22.8	22.4	24.4
Max. $ \eta $	3.5	2.9	2.5	2.2	1.6	1.4	1.2	1.0	0.8
ΔR [cm]	2	2	2	2	3.5	3.5	3.5	3.5	3.5
$\pm z$ -length [cm]	50	50	50	50	58	64	74	84	94
Project Area [m ²]	1.4				8.1				
Central Endcaps	CFT4	CFT3	CFT2	CFT1		CBT1	CBT2	CBT3	CBT4
Min. Radius R [cm]	3.1	3.1	3.1	3.1		3.1	3.1	3.1	3.1
Min. Polar Angle θ [°]	1.8	2.0	2.2	2.6		177.4	177.7	178	178.2
at z [cm]	101	90	80	70		-70	-80	-90	-101
Max./Min. η	4.2	4.0	3.9	3.8		-3.8	-3.9	-4.0	-4.2
Δz [cm]	7	7	7	7		7	7	7	7
Project Area [m ²]	1.8					1.8			
Fwd/Bwd Planes	FST5	FST4	FST3	FST2	FST1		BST1	BST2	BST3
Min. Radius R [cm]	3.1	3.1	3.1	3.1	3.1		3.1	3.1	3.1
Min. Polar Angle θ [°]	0.48	0.54	0.68	0.95	1.4		178.6	178.9	179.1
at z [cm]	370	330	265	190	130		-130	-170	-200
Max./Min. η	5.5	5.4	5.2	4.8	4.5		-4.5	-4.7	-4.8
Outer Radius R [cm]	46.2	46.2	46.2	46.2	46.2		46.2	46.2	46.2
Δz [cm]	8	8	8	8	8		8	8	8
Project Area [m ²]	3.3						2.0		

Table 13.4: Summary of tracker dimensions. The 4 Si-Pixel-Layers CPT1-CPT4 (resolution of $\sigma_{\text{pix}} \approx 8\mu\text{m}$) are positioned as close to the beam pipe as possible. Si-stixel (CST1-CST5) (resolution of $\sigma_{\text{stixel}} \approx 12\mu\text{m}$) form the central barrel layers. An alternative is the 2_in_1 single sided Si-strip solution for these barrel cylinders ($\sigma_{\text{strip}} \approx 15\mu\text{m}$) [812]. The endcap Si-Strip detectors CFT/CBT(1-4) complete the central tracker. The tracker inserts, 5 wheels of Si-Strip detectors in forward direction (FST) and 3 wheels in backward direction (BST) have to be designed according to granularity requirements for optimized energy flow correction and jet resolution. It might well be that specifically in forward direction Si-Pixel or Si-Stixel detectors have to be used instead to meet those requirements whereas for the backward BST wheels where the particle density is less demanding Si-Strip detectors might be sufficient. The FST/BST wheels have to be removed in case of high luminosity running for the Ring-Ring option of the accelerator configuration (see Fig. 13.4).

Linear-Ring




Figure 13.19: XY cut away view of the Central Pixel (CPT) and Central Strixel Tracker (CST) (Linac-Ring layout).




Figure 13.20: LicToy2.0 tracker design of the central/forward FST(top) and central/backward direction BST(bottom).




Figure 13.21: Scaled momentum, impact parameter and polar angle resolution as function of polar angle θ resulting from tracker design simulation using LiCToy2 for the FST(left) and BST(right) side. Tracker setup used as shown in Fig. 13.20.

Parameters	
B	3.5T
$X/X_0^{\text{beam pipe}}$	0.002
$X/X_0^{\text{CPT/CFT/CBT/FST/BST-det}}$ <i>per (double) layer</i>	0.025
$X/X_0^{\text{CST-det}}$ <i>per (double) layer</i>	0.02
efficiency	0.99%
Minimal inner radius	3.15cm
σ_{CPT}	8 μm
$\sigma_{\text{CST,CFT,CBT}}$	12 μm
$\sigma_{\text{FST,BST}}$	15 μm

Table 13.5: The main parameters assumed in LicToy2 tracking simulation.




Figure 13.22: Track Sagitta vs. Momentum of 1°-tracks in a superposed dipole (0.3T) and solenoidal field component (0.361T).

9844 **Optimising cost for all components**

9845 The technology developments for HL-LHC/ILC experiments [814–827] should be used as far as possible
9846 while relying on existing technologies because of time constraints. The sensors, integrated electronics, read-
9847 out/trigger circuitry, mechanics, cooling, etc. available today have to be used in order to meet the goal of
9848 installation in the early 2020’s. One should make use of the advanced research in instrumentation, work on
9849 manufacturability and their actual construction. Whenever possible and affordable innovative instruments
9850 and approaches should be re-used.

9851 **Choice of sensor type**

9852 The default tracker design is based on the silicon microstrip detector technology developed for the experiments
9853 at LHC, ILC, TEVATRON, b-factories etc. within the last 20 years. The final decision for sensor types
9854 (pixel, strixel, strip) depend on many factors and will be taken according to their functionality.

9855 **Radiation hardness** The expected radiation load is defined and influenced by the interaction rate (25ns),
9856 luminosity ($\approx 10^{33}cm^{-2}s^{-1}$), particle rate per angle interval, fluence n_{eq} and ionisation dose. Some data
9857 will be better defined after evaluation of more detailed simulations. Specifically the radiation impact on
9858 tracker wheels, calorimeter inserts and the inner tracker-barrel layer has to be studied. The tools for those
9859 simulations are being prepared. First estimates are discussed in section 13.8 in more detail, but there is
9860 as yet no indication for extremely high radiation load into the detectors adjacent to the beam pipe. The
9861 expected levels are far below what the LHC experiments have to withstand.

9862 A side remark is related to the active parts of the forward/backward calorimeter. For safety reasons those
9863 calorimeter inserts should be equipped with radiation hard silicon-based sensors according to LHC/HL-LHC
9864 standards. Relatively small in volume but still large in terms of layer area $\mathcal{O}(m^2)$, the use of Si-strip/Si-pad
9865 based calo-inserts might turn out as a sizeable investment which is anyhow needed in order to guarantee
9866 for a stable performance and a sufficient detector lifetime. A final decision will only be possible after more
9867 detailed **FLUKA** [828, 829] simulations are complete. But since radiation hardness seems to be of lower
9868 priority for the LHeC detector compared to the harsh environment at LHC one could use the ”traditional”
9869 sensor technology (p_in_n) instead of the radiation harder n_in_p or n_in_n sensors, which are being developed
9870 for HL-LHC, but the cost argument will decide finally.

9871 **Trigger** The trigger capabilities of the tracking system is yet to be defined and will have a direct impact
9872 on sensor choice, associated electronics and arrangement. It is possible that very recent developments of
9873 3D integration semiconductor layers interconnected to form monolithic unities of sensor&electronic circuitry
9874 would be available in time for installation in the 2020’s, but conventional wire bonded or bump bonded
9875 solutions may be more cost efficient and rely on components available today. For example, the 2_in_1
9876 strip sensor design p_t -trigger discussed by the CMS upgrade design group [812], shown in Fig. 13.23, would
9877 have a direct impact on a muon-trigger definition. The sensor, hybrid and readout modules are available
9878 and interconnected by wire bonds. The 2_in_1 sensor design is an elegant way of saving resources when
9879 designing a tracker, as shown in Fig. 13.24

9880 **Front-end** Candidates of readout chips attached to the sensors are e.g. the ATLAS FE-I4 ($50\mu m*250\mu m$)
9881 [808] and CMS ROC ($100\mu m*150\mu m$) [814]). The sensor pitch has to be matched and the electronics scheme
9882 defined beforehand.

9883 **Powering and cooling**

9884 The size of the largest stave structure to be installed (half z-length $\approx 94cm$) is smaller than the stave length
9885 used e.g. by ATLAS ($\approx 120cm$). Powering and cooling per stave are therefore less demanding than for the
9886 current LHC installations. Minimisation of cooling directly reduces the material budget; cooling is related
9887 to power consumption issues and it may be a criterion for technology selection. A decision on the powering




Figure 13.23: Layout of the 2_in_1 strip sensor design used as p_t -trigger setup for the CMS experiment.




Figure 13.24: Layout of the 2_in_1 strip sensor design used as tracker module. Double use of e.g. power and cooling for the two strip wafer.

9888 concept is needed (serial, parallel powering). It will depend on the template chosen for readout and services.
 9889 An obvious solution is to re-apply the scheme used by a current LHC experiment in line with the sensor,
 9890 electronics & readout option selected.




Figure 13.25: Proposed mechanics and sensor layout for the ATLAS pixel upgrade.

9891 **Mechanical support**

9892 The mechanical support and cooling elements have to be chosen to minimise the material budget and hence
 9893 minimise the impact of multiple-scattering on track resolution by the tracker material. Rigid but very light
 9894 mechanics in connection with improved sensor arrangement, incorporation of cooling systems and all other
 9895 services into the support structure are the main design criteria for HL-LHC upgrade projects for e.g. ATLAS
 9896 and CMS - this is also the case for LHeC.

9897 In Figs. 13.25, 13.26 and 13.27, possible mechanical solutions for the ATLAS [808, 830] and CMS [812]
 9898 tracker upgrades in the barrel and forward/backward tracker regions are shown. These designs may serve as
 9899 templates for the LHeC detector. As an example, an artist's view in Fig. 13.28 shows an implementation of
 9900 the double-I ATLAS pixel arrangement into a 4 layer pixel structure for the LHeC detector. The goal is the
 9901 design of a tracker which is in the range $\approx 15 - 20\%X_0$ in terms of radiation lengths.

9902 **Readout**

9903 Possible paths for the IN/OUT services of the LHeC tracking detectors are sketched in Fig. 13.29. The cables
 9904 and tubes are integrated into the support structures of the sub-detectors as far as possible. Optimisation of
 9905 detector readout reduces the cost and material impact of cables. An example is discussed in detail for the
 9906 ATLAS/CMS HL-LHC opto-link upgrade in Ref. [831]. The front end electronics buffer depth will depend
 9907 on bunch crossing rate (25ns) and the trigger/readout speed capability.

9908 **Radiation detectors**

9909 Special Interaction Region instrumentation for tuning of the machine in order to minimise background and
 9910 optimise luminosity is needed. Radiation detectors, e.g. near mask and tight apertures, are useful for
 9911 fast identification of background sources. Fast bunch related informations are collected efficiently e.g. by
 9912 dedicated diamond detectors, e.g. for CMS [832–835].




Figure 13.26: Proposed mechanics layout for the CMS inner barrel tracker upgrade.

Inner & outer ring of blades

CO₂ tubes embedded in half disk support:

- support cylinder:
 - Carbon carbon
 - Grooves for cooling tube
 - Stainless steel tube:
 - 1.8mm OD, 100µm wall

Blades:

- all identical
- Rotated by 20° radial
- Tilted by 12° (inner ring)
- 2 modules per blade (φ overlap)
- individually replaceable





Figure 13.27: Proposed mechanics layout for the CMS tracker wheel upgrade.




Figure 13.28: Artist view of the pixel sensor arrangement using the double-I ATLAS layout as template (Fig. 13.25).




Figure 13.29: Path of services for all tracking detectors (shown in orange). The services are integrated into support structures whenever possible

13.4 Calorimetry

The LHeC calorimetry has to fulfill the requirements described in 12.1. The goal is a powerful level 1 trigger and a detector able to resolve shower development in three-dimensional space with no or minimal punch through. High transverse and longitudinal segmentation are necessary along with a good matching to tracking detectors for particle identification and separation of neutral and charged particles. The calorimetry needs to be hermetic in order to provide a good measurement of the total transverse energy in the charged current process. These considerations are summarised in Tab. 12.1.

The baseline design foresees a modular structure of independent electromagnetic (EMC) and hadronic (HAC) calorimeter components. In order to fully contain electromagnetic showers, the EMC must provide $\sim 25 - 30X_0$. The design of the EMC modules will vary when moving from the very forward region, where energies up to $\mathcal{O}(1\text{TeV})$ are expected, to the barrel and the backward region, where an accurate and precise measurement of the scattered electron with energy $\mathcal{O}(60\text{ GeV})$ is paramount.

In the baseline design, the EMC is surrounded by the solenoid coil which provides the magnetic field for momentum measurement in the tracking. The hadronic calorimetry comes next and has sufficient depth in order to precisely measure jets over the full energy range, while providing the granularity in a projective modular design such that it can faithfully separate multiple jet events. The forward part of the HAC will need to provide up to $10\lambda_I$ to guarantee containment of energies up to a few TeV.

In the next sections the baseline design for the EMC and HAC components is presented and discussed along with a comparison of technologies and the experience from other HEP detectors e.g. [836], [837], [838], [839], [840]. A brief summary of ongoing R&D into new technologies which could extend the precision and scope of the detector are briefly addressed.

13.4.1 The Barrel Electromagnetic Calorimeter

In the barrel region ($2.8 < \eta < -2.3$), a Liquid Argon calorimeter (LAr) with *accordion-shaped* electrodes, as is currently in use by ATLAS [841], is proposed as default. The principle of LAr sampling calorimetry is to arrange many layers of passive material, in this case lead ($X_0=0.56\text{ cm}$), alternated with layers of active material, here LAr with $X_0=14.0\text{ cm}$. The choice of Liquid Argon follows from its intrinsic properties of excellent linearity, stability in time and radiation tolerance [842–849]. A LAr calorimeter would provide the required energy resolution, detector granularity and projective design. The detector, with an outer diameter of 88 cm, would share the same cryostat as the main solenoid which in the case of a Linac-Ring design would include the bending dipoles. The performance of the LAr calorimetry system has been extensively addressed [841] and here only specific design issues and detector simulation will be discussed. As an alternative a (warm) rough concept for a lead-scintillator electromagnetic calorimeter has been simulated for comparison 13.5.4.

Fig. 13.30 shows a x - y and r - z view of the LHeC Barrel EM calorimeter. The layout allows the extraction of detector signals without significantly degrading the high-frequency components which are vital for fast shaping. The flexibility in the longitudinal and transverse segmentation, and the possibility of implementing a section with narrow strips to measure the shower shape in its initial development, represent additional advantages. It is worth noting that due to the asymmetric design, the projective structure is not fully symmetric as the calorimeter and the solenoid centre are shifted forward with respect to the interaction point.

Fig. 13.31 shows a detail of the accordion-electrode structure. A basic cell consists of an absorber plate, a liquid argon gap, a readout electrode and a second liquid argon gap. The mean thickness of the liquid argon gap is constant along the whole barrel and along the calorimeter depth. The readout granularity is subdivided into 3 cylindrical sections of increasing size in $\Delta\eta \times \Delta\phi$. As shown in Fig. 13.32, the first sampling section of the EMC would have a very fine granularity ($\Delta\eta \times \Delta\phi = 0.003 \times 0.1$), to optimize the ability to separate photons from π^0 energy deposits. The second sampling section, mainly devoted to energy measurement, would have a granularity of about 0.025×0.025 , and the final sampling section has a slightly coarser granularity of $\Delta\eta \times \Delta\phi = 0.050 \times 0.025$.




Figure 13.30: x - y and r - z view of the LHeC Barrel EM calorimeter (green).




Figure 13.31: Longitudinal view of one cell of the ATLAS LAr Calorimeter, showing the accordion structure.




Figure 13.32: 3D view of the accordion structure of the ATLAS LAr Calorimeter

13.4.2 The Hadronic Barrel Calorimeter

The baseline hadronic calorimeter in the barrel region is a sampling calorimeter using steel and scintillating tiles as absorber and active material, respectively [850]. The *Tile Calorimeter* would provide the required mechanical stability for the inner LAr and Magnet cryostat along with the iron required for the return flux of the solenoidal field, as is also the case in ATLAS [841].

The Tile calorimeter consists of a cylindrical structure with inner and outer radius of 120 and 260 cm respectively (Tab. 13.6). The central HAC barrel part is 580 cm in length along the beam axis. Endcaps extend the calorimetry further in the forward and backward direction in order to guarantee sufficient energy containment. The detector cylinder would be built of several independent wedges along the azimuthal direction while the modularity and segmentation may vary depending on the machine design.

The Tile calorimeter forms the shell of the inner part of the LHeC detector. Once the barrel and the extended barrels are assembled, all of the sub-detectors apart from the muon system will be placed inside of it. The massive iron structure is rigid enough to support their weight, in particular the liquid argon cryostat and the solenoid.

The absorber structure is a laminate of steel plates of various dimensions, connected to a massive structural element referred to as a girder. The highly periodic structure of the system allows the construction of a large detector by assembling smaller sub-modules together. Since the mechanical assembly is completely independent from the optical instrumentation, the design is simple and cost effective. Simplicity has also been the guideline for the light collection scheme: the fibres are coupled radially to the tiles along the external faces of each module. The laminated structure of the absorber allows for channels in which the fibres run. The use of fibres for the readout allows a layered cell read-out to be used, creating a projective geometry for triggering and energy reconstruction. A compact electronics read-out is housed in the girder of each module. Finally, the scintillating tiles are read out in two separate photomultipliers, providing the required redundancy.

The granularity of the Tile Calorimeter is important to finely match the electromagnetic LAr calorimeter

E-Calo Parts	FEC1	FEC2		EMC		BEC2	BEC1
Min. Inner radius R [cm]	3.1	21		48		21	3.1
Min. polar angle θ [°]	0.48	3.2		6.6/168.9		174.2	179.1
Max. pseudorapidity η	5.5	3.6		2.8/-2.3		-3.	-4.8
Outer radius [cm]	20	46		88		46	20
z -length [cm]	40	40		660		40	40
Volume [m ³]	0.3			11.3		0.3	
H-Calo Parts barrel			FHC4	HAC	BHC4		
Inner radius [cm]			120	120	120		
Outer radius [cm]			260	260	260		
z -length [cm]			217	580	157		
Volume [m ³]			121.2				
H-Calo Parts Inserts	FHC1	FHC2	FHC3		BHC3	BHC2	BHC1
Min. inner radius R [cm]	11	21	48		48	21	11
Min. polar angle θ [°]	0.43	2.9	6.6		169.	175.2	179.3
Max/min pseudorapidity η	5.6	3.7	2.9		-2.4	-3.2	-5.
Outer radius [cm]	20	46	88		88	46	20
z -length [cm]	177	177	177		117	117	117
Volume [m ³]	4.2				2.8		

Table 13.6: Summary of calorimeter dimensions.

The electromagnetic barrel calorimeter is currently represented by the barrel part EMC (LAr-Pb module); the setup reaches $X_0 \approx 25$ radiation length) and the movable inserts forward FEC1, FEC2 (Si-W modules ($X_0 \approx 30$) and the backward BEC1, BEC2 (Si-Pb modules; $X_0 \approx 25$).

The hadronic barrel parts are represented by FHC4, HAC, BHC4 (forward, central and backward - Scintillator-Fe Tile modules; $\lambda_I \approx 8$ interaction length) and the movable inserts FHC1, FHC2, FHC3 (Si-W modules; $\lambda_I \approx 10$), BHC1, BHC2, BHC3 (Si-Cu modules, $\lambda_I \approx 8$) see Fig. 13.9.

9986 in front and correct for the dead material of the magnet complex. The proposed hadronic segmentation for
9987 the cells behind the electromagnetic section, will allow an efficient hadron leakage cut, needed for electron
9988 and photon identification. A reasonable longitudinal segmentation, especially around the maximum depth
9989 of the shower, favours an appropriate weighting technique to restore, at the level of 1-2%, the linearity of
9990 the energy response to hadrons, which is intrinsically non-linear because of the non-compensating nature
9991 of the calorimeter. At the highest energies, the resolution of the calorimetry is dominated by the constant
9992 term, for which the largest contribution comes from the detector non-linearity and calibration. An attempt
9993 is made to keep the constant term below the 2% level.

9994 13.4.3 Endcap Calorimeters

9995 Calorimetry in the forward and backward direction at the LHeC is of extreme importance: in the forward
9996 region for the measurement of the hadronic final state, and in the backward region for the measurement
9997 of the low energy scattered electron. Here, a good e/h separation is also important to suppress hadronic
9998 background.

9999 As seen in Fig. 13.60, the very forward and to a lesser extent the backward parts of the calorimeter are
10000 exposed to high levels of particle radiation and must therefore be radiation hard by design. Synchrotron
10001 radiation and any further background radiation must also be tolerated in addition.

10002 Fig. 13.9 shows in detail the endcap calorimeters for the Ring-Ring design. The two-phase experimental
10003 program requires the endcaps to be modular as these components will either be moved along the beam
10004 line or completely removed to allow the placement of the strong focussing magnets for the high luminosity
10005 phase. The relevant dimensions and specifications are summarised in Tab. 13.6. For the Linac-Ring design,
10006 where no additional magnets along the beam line will be required, the subcomponents FHC2/FHC3 and
10007 BHC2/BHC3, can be combined into single modules.

10008 The restrictive geometry of the insert calorimeters requires a non-conventional and challenging design
10009 based on previous developments [851–858]. Tungsten (W) is considered as the absorber material, in particular
10010 for the forward inserts, because of its very short radiation length and large absorption to radiation length
10011 ratio. About 26 cm of tungsten will absorb electromagnetic showers completely and will contain the hadronic
10012 shower to a large extent and over a large range of energy ($\approx 30X_0 \approx 10\lambda_I$). The electromagnetic and
10013 hadronic sections can be combined to minimise boundary effects. An alternative to tungsten for the hadronic
10014 absorber is copper (Cu).

10015 Simulations have been performed to compare the different absorbers. Since the backward inserts have
10016 looser requirements, the material for the absorbers are lead (Pb) for the electromagnetic part and copper
10017 for the hadronic. For the Ring-Ring option, where no dipole field along the beampipe is required, a more
10018 economical choice of steel (Fe) instead of copper can be considered. The active signal sensors for both the
10019 forward and backward calorimeters have been chosen to be silicon-strip (electromagnetic fwd/bwd parts)
10020 and silicon-pad (hadronic fwd/bwd parts).

10021 13.5 Calorimeter Simulation

10022 In this section preliminary results on simulations of the barrel and endcap calorimeters are illustrated using
10023 the simulation frameworks **GEANT4** and **FLUKA**. In general the parameters of the functions have been
10024 fitted to the **GEANT4** data. The **FLUKA** results are shown for comparison, if available yet. The detector
10025 components presented in 13.4.1, 13.4.2, 13.4.3 have been simulated using **GEANT4.9.2** [859] with single and
10026 multiple particle events along with full $e-p$ events from the **QGSP-3.3** [860] physics list and **FLUKA** with
10027 **CALORIMetry** card. The Quark-Gluon String Precompound (**QGSP**) is based on theory-driven models
10028 and uses the quark-gluon-string model for interactions and a pre-equilibrium decay model for fragmentation.
10029

10030 The detector geometry, including the various layers of active, absorbing and support material were coded
10031 and inserted in the simulation. Energy resolutions for electromagnetic and hadronic deposits were studied
10032 along with concepts for optimal trigger and signal reconstruction. Particular attention was put into the key

10033 features and the construction constraints of the detector, namely the beam optics and the magnets (the
 10034 solenoid and the Linac-Ring dipoles). Where a similar design from an existing or developing detector are
 10035 available, the results are presented complemented by referenced studies.

10036

10037 The energy resolution of a calorimeter is parameterized by the following quadratic sum:

$$\frac{\sigma_E}{E} = \frac{a}{\sqrt{E}} \oplus b \quad (13.1)$$

10038 where E is the particle energy in GeV , a is the stochastic term, which is arising from fluctuations in the
 10039 number of signal producing processes, b is the constant term, which describes imperfections in calorimeter
 10040 construction, fluctuations in longitudinal energy containment, non-uniformities in signal collection etc. A
 10041 third term c (left out here) is often also added which would represent the noise in experimental data de-
 10042 scription. The energy deposition of primary and secondary particles in the calorimeter was obtained using
 10043 **GEANT4** and **FLUKA**, and fitted to extract a and b using the data obtained in **GEANT4**. Effects due to
 10044 the readout process were not considered at this stage.




Figure 13.33: Example for a pion energy distribution and the Gaussian fit. The resulting σ and mean values are estimated for pions of an incident angle $\theta = 70^\circ$ and 10 GeV energy into the tile-calorimeter module (**GEANT4**).

10045

10046 Each energy distribution was fitted with a Gaussian, $\pm 2\sigma$ around the mean and the energy depended
 10047 resolution was calculated using those mean values fitted. An example of the energy distribution and Gaussian
 10048 fit applied is shown in Fig. 13.33. The a and b parameters are then calculated from the fit of σ/E (**GEANT4**).

10049

10050 13.5.1 The Barrel LAr Calorimeter Simulation

10051 A simplified layout, adapted from the ATLAS LAr calorimeter [841], has been implemented in a **GEANT4**
 10052 simulation and used to extract the main characteristics of the LHeC barrel electromagnetic calorimeter.

10053 The accordion shaped absorber sheets are 2.2 mm thick lead layers interspersed with 3.8 mm wide gaps
 10054 filled with liquid argon. In the present model the electrodes which in the case for ATLAS are 2×0.275 mm

10055 thick, were not considered. Both absorber and the liquid argon gap have an accordion fold length of 40.1 mm
 10056 and 13 bend angles of 90° . A total of 62 absorber sheets each 250 cm wide in z -direction have been incorpo-
 10057 rated into the simulation (Fig. 13.35-left). A 20 GeV incident single electron showering in the stack is shown
 10058 in Fig. 13.35-right. The energy resolution for electrons was obtained from the ratio of the mean and the
 10059 standard deviation of the electron response, both obtained by fitting a Gaussian to the energy spectrum.
 10060 Figure 13.36 shows the energy resolution for electrons of energy between 10 and 400 GeV at $\theta = 90^\circ$. Here, the
 10061 stochastic term of the energy resolution is found to be 8.47% and the constant term is 0.318% which compare
 10062 well with 9.99% and 0.35%, respectively at about $\theta = 90^\circ$ [861]. In the simulation the energy deposited in
 10063 the active material is normalized to the energy of the incident particle.

10064 13.5.2 The Barrel Tile Calorimeter Simulation

Tile Rows	Height of Tiles in Radial Direction	Scintillator Thickness
1-3	97 mm	3 mm
4-6	127 mm	3 mm
7-11	147 mm	3 mm
x -depth	1407 mm	

Table 13.7: Longitudinal (into x -direction) segmentation of the hadronic tile calorimeter (HAC).




Figure 13.34: Tile Calorimeter energy resolution for electrons at $\theta = 70^\circ$ and 90° (left) and for pions at $\theta = 90^\circ$ (right).

10065 The HAC is a scintillator-steel tile calorimeter: 4 mm thick steel plates are interspaced by 3 mm thick
 10066 scintillator tiles. The tiles are placed in planes perpendicular to the z -direction. The absorber structure
 10067 consist of 262 repeated periods, each of which spans 19 mm in z and consist of 16 mm of steel and 3 mm of
 10068 scintillator tile. 11 transverse rows of tiles are used in a module. The total interaction depth of the HAC
 10069 prototype correspond to $\lambda_I = 7$. The longitudinal segmentation of the HAC module is described in Tab. 13.7.
 10070 In this section the performance of the hadron calorimeter alone has been investigated. In the later sections
 10071 the combined use of EMC and HAC parts has been studied. The energy resolution of the tile calorimeter was
 10072 simulated with electrons and pions within the energy range 3-200 GeV (Fig. 13.34). The stochastic term and
 10073 constant term values obtained for electrons shown on the left side of the figure are consistent with results
 10074 obtained for ATLAS [862]. It is clearly seen that, both stochastic and constant term values decreases with

10075 decreasing angles. The parametrization values for pions on the right side of the figure are in agreement
 10076 with [863](Page 1, Eq. 1) as well. The response to electrons show the general good resolution such that any
 10077 leakage from the electromagnetic calorimetry in front of HAC would be resolved safely.




Figure 13.35: View of the parallel geometry accordion calorimeter (left) and simulation of a single electron shower with initial energy of 20 GeV (right) - LAr calorimeter module.

10078 13.5.3 Combined Liquid Argon and Tile Calorimeter Simulation

10079 The combined system (accordion and tile calorimeter) has been studied. The effect of the dead material due to the magnet and the cryostat between the EMC and HAC has been studied in first approximation. The
 10080 energy resolution of the combined system has been simulated. The effect of the solenoid and the cryostat
 10081 infrastructure has been simulated by adding a thick Aluminum layer (14 cm) in between EMC and HAC.
 10082 The study has been performed with particles in a wide range of energy and for different incident angle in
 10083 order to obtain information about the detector response for particles entering the calorimeters at different z .
 10084 The hadronic shower simulations have been obtained in the energy range 3 GeV-200 GeV. First results of the
 10085 energy resolutions as a function of energy for pions are shown in Fig. 13.37. The stochastic and constant term
 10086 values obtained for the combined system with and without Al block are consistent with results parameterized
 10087 for ATLAS [863](Page 1, Eq. 2).
 10088

10089 13.5.4 Lead-Scintillator Electromagnetic Option

10090 Along with the baseline liquid argon calorimeter, a more conservative option, not requiring a dedicated
 10091 cryogenic system, has been considered for the barrel electromagnetic calorimetry. For this purpose a lead-
 10092 scintillator sampling calorimeter (EMC_{Pb-Sc}), composed of 20×0.85 cm thick Pb layers interspaced by 4 mm
 10093 plastic scintillator plates was setup for simulation. The radiation length of this systems correspond to
 10094 $30X_0$ ($X_0(Pb)=0.56$ cm). All dimensions of the calorimeter systems have been kept according to the default
 10095 solution summarized in Tab. 13.6.

10096 The EMC_{Pb-Sc} stack was placed 30 cm in front of the HAC. Again an aluminum block of 16 cm was
 10097 inserted between EMC and HAC representing the magnet/cryostat system as illustrated in Fig. 13.38. The
 10098 sketched module would be one out of 6 azimuthal segments of the complete barrel EMC and HAC. The energy
 10099 resolution of the electromagnetic lead-scintillator calorimeter as obtained with electrons of 10-400 GeV is
 10100 shown in Fig. 13.39.




Figure 13.36: LAr accordion calorimeter energy resolution for electrons between 10 and 400 GeV (**GEANT4**).




Figure 13.37: Combined LAr Accordion and Tile Calorimeter energy resolution for pions with and without 14 cm Al block (**GEANT4**)




Figure 13.38: Simulation - EMC_{Pb-Sc} stack / solenoid-dipole-system($\propto 16$ cm Al-block equivalent) / HAC.




Figure 13.39: The electromagnetic lead-scintillator calorimeter energy resolution for electrons at $\theta = 90^\circ$.




Figure 13.40: Electron longitudinal shower profile for EMC_{Pb-Sc} at various energies (**GEANT4** (left) and **FLUKA** (right)). Only the statistical uncertainties are shown.

10101 As the energy loss for electrons and pions differs in shape, normalization and depth, it is worth looking
 10102 in more detail into their shower profiles when traversing the calorimeter. At detector level, this information,
 10103 if available, can be used to identify and discriminate particles and improve the energy resolution. High
 10104 granularity, necessary to separate jets and energy deposits coming from different products, along with a
 10105 longitudinal segmentation and software reweighting are essential.

10106 Longitudinal and transverse shower profiles have been studied with electrons and pions of different energies.
 10107 The detector structure set up here for first test only and non projective designed but the comparison of studies
 10108 with electrons and pions sent into the calorimeter system with incident angles between 30° and 90° are of some
 10109 interest for studying shower profile properties. The effective calorimeter depth is larger for particles with
 10110 $\theta \neq 90^\circ$ (37 cm for the EMC_{Pb-Sc} and 140 cm for the barrel HAC in case of perpendicular impact). The
 10111 longitudinal shower profiles for electrons and pions are summarized in Fig. 13.40 and Fig. 13.41. They show
 10112 the mean deposited energy as a function of the calorimeter stack depth. The longitudinal shower profile of
 10113 electrons is shorter than for pions as expected. The energy deposition of the electrons has its maximum in
 10114 the EMC_{Pb-Sc} (Fig. 13.40). The leakage into the hadronic part of the calorimeter system is small and sums
 10115 up to $\mathcal{O}(10)$ MeV. Pions penetrate deeper into the calorimeter and the maximum of energy deposition is
 10116 seen consistently in the HAC region (Fig. 13.41-right). Less energy deposition occurs in the region between
 10117 37 and 67 cm because of the aluminum layer which represents the cryostat-wall, the solenoid and the dipole
 10118 magnet structures. The containment of the hadronic showers is complete.

10119 Transverse profiles are usually expressed as a function of the transverse coordinates and are integrated
 10120 over the longitudinal coordinate. Fig. 13.42 shows the transverse shower profiles for electrons and pions.
 10121 Since the electromagnetic showers are compact, the electromagnetic energy is deposited relatively close to
 10122 the core of the shower. As expected the hadronic profiles show a larger transverse spread.

10123 13.5.5 Forward and Backward Inserts Calorimeter Simulation

10124 The very important forward/backward instrumentation for calorimetric measurement has been chosen such
 10125 that from the point of view of performance and availability of the technology all currently known boundary
 10126 conditions could be met. More detailed studies towards a technical design will clarify open issues. The
 10127 details of the stack constructions are summarized in Table 13.8. The following options have been considered
 10128 for the insert calorimeters:

- 10129 • The forward electromagnetic calorimeter (FEC) inserts (i.e. FEC1 and FEC2) are tungsten-silicon
 10130 sampling calorimeters for compact and radiation hard stack design matching the tracking system
 10131 towards the interaction point with high granularity.




Figure 13.41: Electron (left) and Pion (right) longitudinal shower profile for the EMC_{Pb-Sc}/solenoid-dipole-system (Al-block)/HAC at various energies (GEANT4 (top) and FLUKA (bottom)).




Figure 13.42: Energy deposit and transverse shower profiles for electron (left) and pion (right) - both for the EMC_{Pb-Sc} stack (GEANT4 (top) and FLUKA (bottom)).

Calorimeter Module	Layer	Absorber	Thickness	Instrumented Gap	Total Depth
FEC _(W-Si) 30X ₀	1-25	1.4 mm	16 cm	5 mm	35.5 cm
	26-50	2.8 mm	19.5 cm		
FHC _(W-Si) 10λ _I	1-15	1.2 cm	39 cm	14 mm	165 cm
	16-31	1.6 cm	48 cm		
	32-46	3.8 cm	78 cm		
FHC _(Cu-Si) 10λ _I	1-10	2.5 cm	30 cm	5 mm	165 cm
	11-20	5 cm	55 cm		
	21-30	7.5 cm	80 cm		
BEC _(Pb-Si) 25X ₀	1-25	1.8 mm	17 cm	5 mm	39 cm
	26-50	3.8 mm	22 cm		
BHC _(Cu-Si) 7.9λ _I	1-15	2.0 cm	39.75 cm	6.5 mm	145.35 cm
	16-27	3.5 cm	49.8 cm		
	28-39	4.0 cm	55.8 cm		

Table 13.8: Layer material choice and dimension of electromagnetic and hadronic calorimeter modules simulated. X_0 denotes the radiation length and λ_I the interaction length for the whole stack, respectively. Additional to each absorber layer, layers are placed inside the gap describing the instrumentation (support and readout, respectively): Si-sensors (525 μ m), Si-support structures (FR4; 0.65 mm) and Kapton based circuits (1.15 mm). Constants used: $X_0(W)=0.3504$ cm, $\lambda_I(W)=9.946$ cm, $\lambda_I(Cu)=15.06$ cm and $X_0(Pb) = 0.5612$ cm.

- 10132 • The forward hadronic calorimeter (FHC) inserts (i.e. FHC1, FHC2 and FHC3) have been simulated
10133 using two different absorber materials, Copper (*Cu*) and Tungsten (*W*). Using *W* only would make
10134 the forward insert calorimeters FEC&FHC very homogenous. The electromagnetic and the hadronic
10135 part could be combined in the same compartment. On the other hand using *Cu* is probably more
10136 economical.
- 10137 • The backward electromagnetic calorimeter (BEC) inserts (i.e. BEC1 and BEC2) are lead-silicon sam-
10138 pling calorimeters, with silicon as sensitive media because of the synchrotron radiation risk, specifically
10139 in the backward direction. The energy of particles, predominantly the "kinematical peak electrons"
10140 scattered backward, is expected to be low enough such that a smaller integrated radiation length X_0
10141 installed and the use of *Pb* as absorber material is justified.
- 10142 • The backward hadronic calorimeter (BHC) inserts (i.e. BHC1, BHC2 and BHC3) have been setup as
10143 copper-silicon sampling calorimeters.

10144 The BEC, BHC and BEC&BHC composite calorimeter are generally structured as their forward electromag-
10145 netic and hadronic calorimeter counterparts sketched in Figure 13.43.

10146 The lateral size of a shower is due to the multiple scattering of electrons and positrons and characterized
10147 by the Molière radius (ρ_M) of the setup. The lateral development of the electromagnetic showers initiated by
10148 electrons or photons scales with the Molière radius. The Molière radii of tungsten and lead are $\rho_M=0.9327$ cm
10149 and $\rho_M=1.602$ cm [64], respectively. ⁴ ρ_M has to be low enough to separate showers, thus that argument is
10150 in favour of *W* specifically for the construction of the forward insert calorimeters (Fig. 13.46).

10151 The simulated maximum longitudinal shower profiles for electrons in the FEC and BEC (Fig 13.47) are
10152 in agreement with former results [864]. In average 99.4% and 98.8% of the incident energy for simulated

⁴The Molière radius, ρ_M , is the radius of a cylinder containing on average 90% of the electromagnetic shower's energy deposition.




Figure 13.43: Cross section in rz of FHC+FEC. Color coding: the absorber of the FHC is in blue. The absorber of the FEC is in pink. The silicon detectors, silicon support and kapton circuits of FEC and FHC are in brown, green and gray respectively.




Figure 13.44: Energy resolution spectra for electrons in the energy range 1 GeV-1 TeV in the $FEC_{(W-Si)}$ (left) and for electrons (energy range 3 GeV-100 GeV) in the $BEC_{(Pb-Si)}$ stacks (right).

Calorimeter Module (Composition)	Parameterized Energy Resolution
Electromagnetic Response	
FEC _(W-Si)	$\frac{\sigma_E}{E} = \frac{(14.0 \pm 0.16)\%}{\sqrt{E}} \oplus (5.3 \pm 0.049)\%$
BEC _(Pb-Si)	$\frac{\sigma_E}{E} = \frac{(11.4 \pm 0.5)\%}{\sqrt{E}} \oplus (6.3 \pm 0.1)\%$
Hadronic Response	
FEC _(W-Si) & FHC _(W-Si)	$\frac{\sigma_E}{E} = \frac{(45.4 \pm 1.7)\%}{\sqrt{E}} \oplus (4.8 \pm 0.086)\%$
FEC _(W-Si) & FHC _(Cu-Si)	$\frac{\sigma_E}{E} = \frac{(46.0 \pm 1.7)\%}{\sqrt{E}} \oplus 6.1 \pm 0.073)\%$
BEC _(Pb-Si) & BHC _(Cu-Si)	$\frac{\sigma_E}{E} = \frac{(21.6 \pm 1.9)\%}{\sqrt{E}} \oplus (9.7 \pm 0.4)\%$

Table 13.9: Energy resolution parameterization for electrons in the electromagnetic stacks (FEC/BEC) and for pions in the composite FEC&FHC and BEC&BHC stack structures, respectively. For each stack structure, the energy range used in the fits is:

- FEC_(W-Si): 1 GeV-5 TeV electrons,
- BEC_(Pb-Si): 3 GeV-100 GeV electrons,
- FEC_(W-Si) & FHC_(Cu-Si) and FEC_(W-Si) & FHC_(W-Si): 50 GeV-1 TeV pions,
- BEC_(Pb-Si) & BHC_(Cu-Si): 3 GeV-100 GeV pions.

The energy resolution spectra from the simulation are summarized in Figs. 13.44 and 13.45.




Figure 13.45: Comparison of energy resolution spectra for pions (energy range 50 GeV-1 TeV) in FEC_(W-Si)&FHC_(Cu-Si) and FEC_(W-Si)&FHC_(W-Si) composite system, respectively (left) and energy resolution spectrum for pions (energy range 3 GeV-100 GeV) in the BEC_(Pb-Si)&BHC_(Cu-Si) composite system (right) (**GEANT4**).




Figure 13.46: Comparison of transverse shower profiles for electrons with energies 75 GeV-5 TeV on $FEC_{(W-Si)}$ (left) and 3 GeV-100 GeV on $BEC_{(Pb-Si)}$ (right) (**GEANT4** (top) and **FLUKA** (bottom)).




Figure 13.47: Comparison of average energy deposition as a function of longitudinal shower extension for electrons energies of 50 GeV (left) and 75 GeV (right) in $FEC_{(W-Si)}$ (black) and $BEC_{(Pb-Si)}$ (red) (**GEANT4** (top) and **FLUKA** (bottom)).

10153 electron energies in the range of 1 GeV-1 TeV for $FEC_{(W-Si)}$ and 3 GeV-100 GeV for $BEC_{(Pb-Si)}$, respec-
 10154 tively, are contained in the electromagnetic calorimeters. Thus the high energy electromagnetic showers are
 10155 sufficiently well contained in the $30X_0^{FEC}$ and $25X_0^{BEC}$ stack construction, respectively, taking into account
 10156 the considerably lower energies expected in backward direction.




Figure 13.48: Average energy deposition as a function of depth for pions in the energy range 50 GeV-1 TeV in the $FEC_{(W-Si)}$ & $FHC_{(W-Si)}$ system (left) and in the $FEC_{(W-Si)}$ & $FHC_{(Cu-Si)}$ composite stack system (right) (**GEANT4** (top) and **FLUKA** (bottom)).

10157 The longitudinal distribution of the hadronic calorimeters and shower maxima of the longitudinal distri-
 10158 bution scales with the nuclear interaction length λ_I . For copper λ_I is by $\approx 51\%$ larger than for tungsten.
 10159 Indeed we observed that showers in the $FHC_{(W-Si)}$ stack (Fig. 13.48-left) reaches the energy deposition
 10160 maximum already earlier in the calorimeter, i.e. at smaller depth values. That effect is more pronounced for
 10161 lower energetic pions (Fig. 13.49-left). The thickness of $10\lambda_I$ provides sufficient containment of the hadronic
 10162 cascades for precision measurements both of jet properties and of E_T^{miss} . The overall containment when
 10163 using $FHC_{(W-Si)}$ instead of $FHC_{(Cu-Si)}$ for the configurations described in Tab. 13.9 seems to be better.

10164 Some leakage for the hadronic calorimetry ($BEC_{(Pb-Si)}$ & $BHC_{(Cu-Si)}$) in the backward direction has
 10165 been observed. This is not too worrisome as the main focus in the backward direction is the analysis of
 10166 the electromagnetic component of the $e^\pm p/e^\pm A$ scattering. It should be mentioned that important design
 10167 details which will affect the performance of the real calorimeter are not defined yet. Two of these are the
 10168 granularity definitions which have to be optimized for shower separation, and the impact of the dead regions
 10169 coming from the cabling and the mechanical infrastructure, which is unavoidable and introducing losses in
 10170 terms of energy measurement [865], [866]. A detailed simulation will take that into account.




Figure 13.49: Comparison of $FEC_{(W-Si)} \& FHC_{(Cu-Si)}$ (red) and $FEC_{(W-Si)} \& FHC_{(W-Si)}$ (black) stack systems in terms of average energy depositions as a function of stack depth for pions of energy 50 GeV (left) and the same comparison for pions with energy 1 TeV (right) (**GEANT4** (top) and **FLUKA** (bottom)).




Figure 13.50: Average energy deposition as a function of depth for pions in the energy range 3 GeV-100 GeV incident on the $\text{BEC}_{(Pb-Si)}$ & $\text{BHC}_{(Cu-Si)}$ composite system (**GEANT4** (top) and **FLUKA** (bottom)).

13.6 Calorimeter Summary

At the LHeC different calorimeter approaches are required following the asymmetric interaction region and energy imbalance of the interacting beams.

High energy jets with energy up to few TeV are expected in the forward region requiring radiation hard design, a high granularity and depth of up to $10 \lambda_I$ and in a very compact space. More relaxed are the requirements in the barrel and backward region.

The choice of the sampling calorimetry for all calorimeter parts is motivated by the good experience from past experiments and from the LHC along with considerations on the available technologies, their costs and the detector dimensions.

In the barrel region, the need for a precise match to the tracking system and the ability to separate multijet events pushes toward a solution which allows for a high energy linearity and a high readout granularity as obtainable for liquid argon. The use of a compensating calorimeter, as was for instance the uranium calorimeter of ZEUS, would allow to reduce the e/h energy fluctuations and provide an absolute energy measurement, but only hardly and at high manufacturing expense, provide the required granularity. Moreover software compensation and energy-reweighting for a linear response of the electromagnetic/hadronic calorimeter is nowadays well established (H1/ATLAS).

Particle-Flow Calorimeter [867–869] as presently being designed for the future ILC, have very specific construction requirements making at present their choice also not suitable for the LHeC. Some of these aspects are the powering scheme and the related duty cycle which follows from the large number of channels involved, the required cooling, the large dimensions and costs.

As already mentioned very challenging appears the design in the forward and backward endcaps especially at small angle. In these regions the momentum measured by the tracking system is also less precise due to the almost parallel magnetic field and the higher multiple scattering due to an effective thicker beampipe and infrastructure the particles have to cross. The silicon-absorber based inserts in the forward and backward directions will have to be compact and efficiently matched to the tracking devices in front. In any case the projective design of the calorimeter stack cells has to be ensured making use of signal weighting for good space resolutions (of the order of 1 mm).

An alternative approach would be the implementation of the **Double Readout Calorimeter** concept [870]⁵. The dual readout calorimeters measure each shower twice and in two different ways. The major component, dE/dx contributions of all charged particles (e^\pm, π^\pm, K^\pm , spallation p, recoil p, nuclear fragments, etc.), is measured in scintillating material and the electromagnetic part, predominantly coming from subshowers from $\pi^0 \rightarrow \gamma\gamma$ decays, is measured by the Čerenkov light generated in clear fibres/plates by the relativistic e^\pm passing through [871]. Making use of a obviously constant ratio of $(e/h)_C$ (for Čerenkov light emitting material) and $(e/h)_S$ (for Scintillation light emitting material), respectively, the energy response of the calorimeter to electrons e and to hadrons h at all energies can be controlled by construction with convincing results [872] [871].

The preliminary simulations and the results shown indicate the validity of the proposed design concepts as a baseline solution for the given dimensions of the LHeC detector. The results of **GEANT4** and **FLUKA** simulations are comparable. A more elaborated design will be possible as soon as general decisions on the accelerator concept and therefore magnet design have been taken.

13.7 Muon Detector

Muon detection is an important aspect of the physics program covered by the LHeC. In particular the muon detector can improve the scope and the spectrum of measurements, here only a few are listed:

- Higgs decay, leptoquarks, lepton flavor violation
- PDF fits from semileptonic decay of hadrons and heavy flavors.

⁵using plates/fibres in the double readout calorimeter stack for both signal components which are radiation hard

10217

- Vector meson production

10218

10219

10220

10221

10222

10223

10224

10225

10226

The penetrative power of muons would be exploited by several layers of muon chambers ensuring good tracking resolution and hermetic coverage, in particular towards small angles in the forward and backward regions. These regions, particular challenging for central tracking detector due to the accelerator infrastructure, are more accessible at larger distance from the interaction region as is done for travelling minimum ionizing particles as muons are.

Fig. 13.51 shows the muon polar distributions at the LHeC coming from the decay elastic $ep \rightarrow J/\psi \rightarrow \mu^+ \mu^-$ production. The improvement by enlarging the coverage towards small angles is evident as shown in Fig. 13.52 where the coverage as a function of the γp system center of mass energy W is shown for the cases of 10° and 1° detector acceptance.




Figure 13.51: Distribution for J/ψ with $E_e = 50$ GeV. Polar angle of positive (top) and negative (bottom) muon respectively.

10227

13.7.1 Muon detector design

10228

10229

10230

10231

The LHeC main detector will be surrounded by multiple layers of muon detectors. Fig. 13.53 shows a 3d view of the baseline detector (option A). Three muon double detector layers mechanically attached to an iron structure which could provide either the return flux of residual B field from the inner solenoid or an additional field from warm magnets.

10232

10233

10234

Following the state of the art of present muon detector as implemented in the LHC experiments and in similar high energy physics experiments, several options providing the required tracking resolution, rate sustainability and prompt trigger and readout are available.

10235

10236

10237

10238

10239

The two LHC general purpose detectors, ATLAS and CMS, combine Drift Tubes and Cathode Strip Chambers for precision measurements along with with Resistive Plates Chambers and Thin Gap Chambers for Trigger and second coordinate measurements [873, 874]. A similar approach can be considered for the LHeC muon detector with 2 or 3 superlayers each one composed of a double layer of 2d trigger detector and a precision measurement as shown in Fig.13.54.

10240

10241

Other technologies (as for instance micromegas [875], etc.) along with further developments of the existing ones (thin gap RPC [876], smaller monitored drift tubes [877], thin strip TGC [878, 879]), might also




Figure 13.52: Acceptance for J/ψ with $E_e = 50$ GeV as a function of W , the center of mass energy of the γp system. A detector with larger coverage both in the forward and in the rear region allows for measurements on a much wider W range.




Figure 13.53: A full view of the baseline detector in the r - z plane with all components shown. The detector dimensions are ≈ 14 m in z with a diameter of ≈ 9 m.




Figure 13.54: Artist 3d view of the projective arrangement of the layers barrel muon chambers (left). A schematic view of the cross section of one of the chambers which include a double layer of $\eta\phi$ trigger measurement used also for level one triggering along with the precision measurement obtained by drift tubes

10242 be considered for the LHeC. It is anyhow evident that the requirements from the LHC would also satisfy the
 10243 running at the LHeC where backgrounds and luminosity are expected to be lower.

10244 To provide at this stage a complete design of the muon detector is beyond the scope of this document
 10245 as too many options are available and depend on the choices to be taken in the accelerator and the main
 10246 detector design. Only a few options are discussed below with the aim to demonstrate, for the baseline design,
 10247 the feasibility and scope of a detector using available technologies. More studies and design optimization
 10248 will follow in the next steps.

10249 13.7.2 The LHeC muon detector options

10250 Neglecting for the moment the detector technologies to be used, depending on the experimental weight the
 10251 muon detector will have within the LHeC detector, few different approaches satisfying increasing requirements
 10252 can be considered.

- 10253 1. Muon tagging
- 10254 2. Combined muon momentum measurement
- 10255 3. Standalone momentum measurement

10256 With “muon tagging”(1) we indicate a muon detector built with at least 2 layers of muon chambers that
 10257 provide $\eta\phi$ measurement and a fast coincidence for trigger purposes. No additional magnetic field would be
 10258 set up and the muon detector, using only the return flux of the central solenoid would be able to provide only
 10259 a very rough estimate of the particle momentum. The multiple layers and the fast detector response would
 10260 allow a pointing trigger to reject non prompt particles. Muon Momentum measurements would be done
 10261 using mainly the tracking detector and possibly complemented by the energy deposits in the calorimeter
 10262 (that have to be compatible with those of a minimum ionizing particle) and the muon tag.

10263 The next step (2) would be to enhance the muon momentum measurement by adding an extra magnetic
 10264 field, embedding the muon chambers in an iron yoke. The amount of iron and the size of the yoke can be
 10265 optimized in order maximize the resolution in the energy range required.

10266 Both options (1) and (2) can be considered for the baseline design option A and. It is worth noticing that
 10267 for low energy muons (as expected in the barrel and rear region) an instrumented yoke might not be required
 10268 as the momentum resolution of the tracking system will be far superior. For muon momenta of 20 GeV and

10269 above the presence of an additional magnetic field or an instrumented iron yoke could improve especially in
10270 the forward and backward region, where the momentum resolution is worse due to the solenoidal field being
10271 parallel to the beamline.

10272 Although the presence of an iron mass serves four good purposes, namely:

- 10273 • return the magnetic flux
- 10274 • serve as a hadron (π^\pm, K, p, n) particle filter so that predominantly μ^\pm emerge at a large radius
- 10275 • provide excellent mechanical support for all detector systems, especially the massive calorimeter
- 10276 • serve as a radiation shield for the area and the electronics

10277 as soon as the solenoid field and its size increase, the required shielding also increases proportionally and its
10278 density, weight and costs pose important limitations which might be overcome by the use of a twin solenoid
10279 system as discussed in 13.2.5.

10280 This novel approach which would guarantee a “standalone momentum measurement ” (3). The outer
10281 solenoid allows for a very smooth and constant field in an iron free region. As shown in Fig. 13.55, the muon
10282 detector is immersed in a strong constant field (~ 1.5 T) which would allow precise momentum measurement
10283 of momenta up to 500 GeV with $\delta p/p \ll x$. A strong advantage of an air muon spectrometer is the significant
10284 reduction of the the uncertainty due to multiple Coulomb scattering. Additionally, the use of forward
10285 and backward coils can improve the field quality also in the endcap regions allowing the field to line up
10286 transversely to the beam line, for an improved longitudinal momentum measurement.




Figure 13.55: Magnetic field lines for the dual solenoid and wall of coil [880]. The whole detector is enclosed in a second return solenoid; forward and rear coils which allow for a smooth field at the detector muon encaps

10287 13.7.3 Forward Muon Extensions

10288 Detection of muons in the forward hemisphere is extremely relevant at the LHeC where the kinematics of
10289 important physical phenomena (production of heavy flavours, high x physics, leptoquarks etc.) requires a
10290 coverage down to the smallest possible angle with respect to the beam axis. Since the tracking momentum
10291 resolution deteriorates at small angles an independent measurement in the forward region would provide a
10292 completely independent tool for the measurement of the muon momentum.

10293 Given the high particle, and specifically, muons flux expected in the forward region, the use of a dedicated
10294 forward muon toroid would allow the measurement of muon charge and momentum. In Fig.13.56 a sketch of a
10295 possible design for a “small” forward muon toroid is given. For the baseline detector A, a more conventional,
10296 iron based solution (as in HERA for H1 and ZEUS) could be adopted incorporated or located outside of the
10297 the muon iron-yoke. The option of an air core forward toroid combined, either with the option A detector
10298 inside the iron yoke system or in the larger twin solenoid option B would even more enhance the forward
10299 muon momentum resolution especially for very small angles with respect to the beam line.

10300 The insertion of a forward air core based toroid closer to the central tracking system was also consid-
10301 ered and rejected as the bulk material of the required coils, located between the tracking planes and the
10302 calorimeters would compromise the calorimetry measurements.




Figure 13.56: CAD drawing for a 2T air core toroid with 20 cm bore and a size about 1 m³

10303 13.7.4 Muon Detector Summary

10304 Several options for the LHeC muon detector are available.

10305 These range from a simple muon tagging detector which, combined with the baseline detector A would
10306 already be sufficient for a clean muon trigger, allowing to remove beam gas background and non pointing
10307 tracks. The precision of the momentum resolution would depend mostly on the main detector (tracking and
10308 calorimetry) which anyhow would degrade at small forward and backward angle.

10309 Improvements by means of a iron yoke and conventional forward muon toroids would allow improved
10310 performance especially for higher momenta and for muon spectroscopy in the forward region. The experience
10311 from HERA indicate that a solution lacking of a standalone muon trigger could be acceptable for most of
10312 the physics program.

10313 The ultimate design nevertheless appears to be the the twin solenoid option. This more challenging
10314 design, shown in Fig.13.57 naturally follows the option B of the baseline design: the larger main solenoid is
10315 located outside of the hadronic calorimeter and together with a second active shielding solenoid provides a
10316 wide material free region for precise standalone muon momentum measurement. The higher energies available
10317 in the forward region and the interesting physics channels also push for a leading edge design towards use

10318 of additional forward muon toroid. The detector acceptance for the muon channel physics could be largely
 10319 extended.




Figure 13.57: The option B of the LHeC baseline detector. The larger solenoid surrounds the hadronic calorimetry. The volume outside the solenoid is filled with an approximately uniform magnetic field of 1.5 T and is instrumented with 3 multilayers of muon chambers.

10320 13.8 Event and Detector Simulations

10321 Minimum bias events in the LHeC Detector have been simulated using the **GEANT4** Toolkit [859]. In
 10322 addition **ROOT** [881], **GDML** [882], **AIDA** [883] and **Pythia6** [130] have also been incorporated. A **ROOT**
 10323 macro has been written which gives a general description of the LHeC Detector geometry and materials. This
 10324 description is then transported from **ROOT** to **GEANT4** in XML format via **GDML**. A **Pythia6** program
 10325 has also been used to create minimum bias ep events. **Pythia6** outputs the events in HEPEVT format. This
 10326 is then run through a subroutine to produce a format readable by **GEANT4**. The actual simulations are
 10327 completed natively in **GEANT4** once the geometry, materials and events are loaded. The Analysis is done
 10328 with **ROOT** (and the Java Analysis Studio **JAS** [883]) which is interfaced to **GEANT4** via **AIDA**. The
 10329 flow of these simulations is outlined in Figure 13.58.

10330 13.8.1 Pythia6

10331 The **Pythia6**([130]) event used in the **GEANT4** simulations contains γ^*P interactions convoluted with the
 10332 γ/e^- flux. This setup contains non vanishing cross sections including semihard QCD, elastic scattering,




Figure 13.58: Simulation Framework Flow Chart

10333 single/double diffractive among others (The listed interactions dominate σ_{tot}). In order for the events to be
 10334 minimum bias no restrictions are placed on the W or Q^2 range.

10335 Table 13.10 gives the **Pythia6** parameters used for the minimum bias events. The logarithm of the
 10336 variables W and Q^2 are given. Since these variables obey amplitudes given by $P(x) \propto \frac{1}{x^2}$ then $P(\text{Log}(x)) \propto$
 10337 e^{-x^2} showing that $\text{Log}(x)$ produces mean and rms values following normal statistics.

10338 The tools available for ep event generation are not current. The frontier of high energy physics is focused
 10339 on hadron collisions due to the LHC. The numerous problems present in a new energy scale require developers
 10340 to focus in this area. This results in a lack of development of event generation tools for a new energy scale of
 10341 ep collisions. This is the reason we are using **Pythia6** as opposed to its C++ successor. Although it works
 10342 fine for an approximation it would be advantageous to have development here.

Characteristic	Value
$\text{Log}(W)_{mean}$ [GeV]	2.09
$\text{Log}(W)_{rms}$ [GeV]	0.55
$\text{Log}(Q^2)_{mean}$ [GeV^2]	-4.98
$\text{Log}(Q^2)_{rms}$ [GeV^2]	3.15
Electron Energy [GeV]	60
Proton Energy [GeV]	7000

Table 13.10: Pythia6 Parameters

10343 The parameters used to scale the results of the simulation in order to find annual quantities are given in
 10344 Table 13.11.

Characteristic	Value
Total Cross Section [mb]	0.0686
Luminosity [mb ⁻¹ s ⁻¹]	10 ⁶
$\frac{dN}{dt}$ [int/yr]	2.57×10^{12}

Table 13.11: Scaling Parameters

10345 13.8.2 1 MeV Neutron Equivalent

10346 In order to find the 1 MeV Neutron Equivalent one must find the appropriate displacement damage functions
 10347 [D(E)] for the particles. By scaling the damage functions by the reciprocal of D(n, 1 MeV) one arrives at
 10348 a weight which will turn a fluence of random particles into the 1 MeV Neutron Equivalent fluence. D(E) is
 10349 not only dependent on particle type but also on the material in which the particles are traversing. The D(E)
 10350 functions used in the simulations can be found in Figure 13.59 [884].




Figure 13.59: Displacement Damage for various particles in Silicon

10351 In order to find the 1 MeV Neutron Equivalent fluence through the tracking portion of the detector scoring
 10352 was incorporated into the **GEANT4** simulations. A user defined scorer was used that would calculate the
 10353 number of hits on the surface of a detector component, weight the hits according to the appropriate damage
 10354 functions and finally divide the sum of these weighted hits by the inner surface area of the detector component.
 10355 The flux was then scaled by the number of events per year using the mentioned scaling parameters given in
 10356 Table 13.11. The total 1 MeV Neutron Equivalent fluences are given in Table 13.12.

10357 A different approach was used in order to find the 1 MeV Neutron Equivalent fluence distribution in
 10358 R_{polar} and Z. In order to retain data generated on the event level instead of the run level a set up of
 10359 Sensitive Detectors [SD] must be initialized that will measure user defined quantities for traversing particles.
 10360 The entire tracking region was set as one SD, with each hit containing the position information, and the

Central Barrel			
Region	ΔZ [cm]	R_{min} [cm]	Fluence [$\frac{N}{cm^2 yr}$]
CPT1	100	3.1	1.38×10^{10}
CPT2	100	5.6	9.99×10^9
CPT3	100	8.1	8.26×10^9
CPT4	100	10.6	7.25×10^9
CST1	116	21.2	6×10^9
CST2	128	25.6	5.66×10^9
CST3	148	31.2	5.38×10^9
CST4	168	36.7	5.25×10^9
CST5	188	42.7	5.16×10^9
Central Endcaps			
Region	Z [cm]	ΔR [cm]	Fluence [$\frac{N}{cm^2 yr}$]
CFT1	70	26	8×10^9
CFT2	80	31.6	7.42×10^9
CFT3	90	37.1	7.08×10^9
CFT4	101	43.1	6.93×10^9
CBT1	-70	26	2.77×10^9
CBT2	-80	31.6	2.48×10^9
CBT3	-90	37.1	2.26×10^9
CBT4	-101	43.1	2.09×10^9
Fwd/Bwd Planes			
Region	Z [cm]	ΔR [cm]	Fluence [$\frac{N}{cm^2 yr}$]
FST1	130	43.1	8.2×10^9
FST2	190	43.1	1.14×10^{10}
FST3	265	43.1	1.63×10^{10}
FST4	330	43.1	2.29×10^{10}
FST5	370	43.1	2.75×10^{10}
BST1	-130	43.1	1.96×10^9
BST2	-170	43.1	1.91×10^9
BST3	-200	43.1	1.99×10^9

Table 13.12: 1 MeV Neutron Equivalent Fluence

10361 current $D(E)$ value of the given track. A 2D histogram is generated for the variables R_{polar} and Z. The
10362 intensity (each hit weighted by its $D(E)$ value) is then scaled by the number of events in the run, the number
10363 of events per year, and a fluence weighting function. This function divides the number of entries in each bin
10364 by the average surface area the bin represents (i.e. $2\pi R_{mean}\Delta Z$ where R_{mean} is the mean R value which
10365 the bin spans and ΔZ is the width of the Z bins). By this weighting process the resulting 2D histogram
10366 (Figure 13.60) displays the 1 MeV Neutron Equivalent Fluence in $\frac{cm^{-2}}{year}$.




Figure 13.60: 1 MeV Neutron Equivalent Fluence [$\text{cm}^{-2}/\text{year}^{-1}$].

10367 **13.8.3 Nearest Neighbor**

Tracking Component	Hits under $10 \mu\text{m}$ [%]
CFT1	0.18
CFT4	0.23
FST1	0
FST5	0.1

Table 13.13: Nearest Neighbor under $10 \mu\text{m}$

10368 The **Geant4** simulations were also used to find the resolution required in the forward tracking. Firstly,
 10369 the flux through the surface of CFT1, CFT4, FST1, and FST5 was found. A minimization algorithm is
 10370 then used to find the nearest neighboring hit at the $Z = \text{constant}$ surface for each hit. This distance scale
 10371 is characteristic of the resolution required for the tracking component in question. The nearest neighboring
 10372 hit distribution is calculated on the event level. This implies that only the hits from the same event are
 10373 compared. This will have to be studied further to take pileup into account, however information on the event
 10374 level is a nice approximation. The nearest neighbor distribution for CFT4 is shown in Figure 13.61 and for
 10375 FST5 in Figure 13.62. The x axis contains the value of the nearest neighbor for each hit in terms of μm while
 10376 the y axis contains R in terms of cm. A required resolution of 10 or less μm would require pixel detectors
 10377 instead of strip detectors. The CFT4 and FST5 Figures display a very low hit density in this area. The
 10378 percentage of hits with $D < 10 \mu\text{m}$ for the four tracking components in question are given in Table 13.13.

10379 **13.8.4 Cross Checking**

10380 DAWN was used for visualization of the detector. This was able to produce clear pictures which was one
 10381 way to make sure the translation of geometry from **ROOT** to **GEANT4** went as expected. An event in the
 10382 central tracking region is presented in Figure 13.63.

10383 In addition to the minimum bias events, **Pythia6** was also used to create some Leptoquark events. This
 10384 was one method of checking the **Pythia6** input (i.e. that the events produced describe the given kinematic




Figure 13.61: Nearest Neighbor distribution for CFT4




Figure 13.62: Nearest Neighbor distribution for FST5




Figure 13.63: G4 Event




Figure 13.64: Leptoquark Event XY




Figure 13.65: Leptoquark Event RZ

10385 range and cross sections available). However it was also utilized to determine the detector response at various
 10386 kinematic ranges. Since $\sigma_{EM} \propto \frac{1}{Q^4}$ The minimum bias events have very low Q^2 and therefore very forward
 10387 jets, which leaves almost no activity in the barrel HCAL. By looking at some high Q^2 events it is possible
 10388 to see the response of the hadronic calorimetry in the barrel region, making sure it is showering correctly.
 10389 Some pictures of the Leptoquark events are given in Figure 13.64 and Figure 13.65.

10390 13.8.5 Future Goals

10391 There are many goals still to be accomplished by the LHeC Detector Simulations. The set up needs to be
 10392 modified to include a detailed calorimeter description. Currently e.g. the forward/backward calorimeter
 10393 volumes contain a mixture of FR4, Kapton, Active and Passive material which is weighted according to a
 10394 realistic set up. This design must be replaced with a realistic setup of the calorimeters. This also needs
 10395 to be done for the tracking which is currently composed of single silicon pieces instead of smaller modules.
 10396 The majority of the work in making these changes comes from the required read out geometry and sensitive
 10397 detector set up that would be required for analysis of a complicated geometrical structure. This also might
 10398 require a restructuring of the simulation package. Since the detector description was done first in **ROOT**,
 10399 **GDML** was an option to allow utilizing **GEANT4** without recoding the geometry. However if the geometry
 10400 will significantly change then this might benefit from being done natively in **GEANT4**. Of course the
 10401 Geometry needs to be iterated until it actually describes the exact detector (service pipes, read out, etc...).
 10402 However this will come with the TDR.

10403 Finally the stability of the simulations needs to be assessed. Eventually a complex multifunctional
 10404 detector simulation package needs to be produced. This is best done by wrapping numerous simulation
 10405 toolkits into a single package utilizing **ROOT**, such as **AliROOT** [885], [886], [887] or **ILCROOT** [888].
 10406 The LHeC simulations at some point need to make a shift towards creating a package like this, in order to

10407 promote greater functionality and greater accessibility.

Chapter 14

Forward and Backward Detectors

In this chapter forward and backwards detector are presented. These detector are located from few tens of meters from the interaction point up to several hundreds in order to provide specific information not accessible to the main detector. Main focus are the measurements of

- the instantaneous luminosity (Section 14.1)
- the electron or positron beam polarization (Section 14.2)
- very forward diffractive nucleons (Section ??,14.4)

The placement of dedicated taggers both forward and backwards along the beampipe, as discussed in Section 14.1 will provide also additional means to trigger and select data for specific analyses.

14.1 Luminosity Measurement and Electron Tagging

Luminosity measurement is an important issue for any collider experiment. At the LHeC, where precision measurements constitute a significant part of the physics programme, the design requirement is $\delta\mathcal{L} = 1\%$.

In addition to an accurate determination of integrated luminosity, \mathcal{L} , for the normalisation of physics cross sections, the luminosity system should allow for fast beam monitoring with a typical statistical precision of 1%/sec for tuning and optimisation of ep -collisions and to provide good control of the mid-term variations of instantaneous luminosity, L .

Rich experience gained by H1 [889,890] and ZEUS [891,892] Collaborations at HERA was used in the design studies of the luminosity system for the LHeC. In particular, one important lesson to be learnt from HERA is to prepare several alternative methods for luminosity determination.

For the LHeC we consider both Linac-Ring (LR) and Ring-Ring (RR) options as well as high Q^2 ($10^\circ - 170^\circ$ acceptance) and low Q^2 ($1^\circ - 179^\circ$ acceptance) detector setups. This spans over a wide range of instantaneous luminosity¹ $L = (10^{32} - 2 \cdot 10^{33})\text{cm}^{-2}\text{s}^{-1}$. Hence suitable processes for the three tasks outlined above should have the following minimal visible cross sections²:

- fast monitoring ($\delta\mathcal{L} = 1\%/sec \Rightarrow 10\text{ kHz}$) - $\sigma_{\text{vis}} \gtrsim 100\mu\text{b}$,
- mid-term control ($\delta\mathcal{L} = 0.5\%/hour \Rightarrow 10\text{ Hz}$) - $\sigma_{\text{vis}} \gtrsim 100\text{nb}$,
- physics sample normalisation ($\delta\mathcal{L} = 0.5\%/week \Rightarrow 0.1\text{ Hz}$) - $\sigma_{\text{vis}} \gtrsim 1\text{nb}$.

¹This also takes into account exponential reduction of L during the data taking in every luminosity fill.

²Statistical error has to be small in comparison with total error δL_{tot} in order not to spoil overall accuracy.

10435 The best candidate for luminosity determination is the purely electromagnetic *bremstrahlung reaction* $ep \rightarrow$
 10436 $e\gamma + p$ shown in Figure 14.1a, which has a large and precisely known cross section. Depending on the photon
 10437 emission angle it is called either Bethe-Heitler process (collinear emission) or QED Compton scattering (wide
 10438 angle bremsstrahlung). In addition, Neutral Current DIS events in a well understood (x, Q^2) range can be
 10439 used for the *relative* normalisation and mid-term yield control.

10440 While QED Compton and NC DIS processes can be measured in the main detector dedicated ‘tunnel
 10441 detectors’ are required to register Bethe-Heitler events. For the latter, additional challenges as compared
 10442 to HERA are related to the LHeC specifics: non-zero beam crossing angle in IP for RR option, and severe
 10443 aperture limitation for LR option. Finally, for the high luminosity LHeC running one should not forget
 10444 about significant pileup (L/bunch is $\sim 2 - 3$ times bigger as compared to HERA-II running).

10445 14.1.1 Options

10446 The huge rate of ‘zero angle’ electrons and photons from Bethe-Heitler reaction³ makes a dedicated luminosity
 10447 system in the tunnel ideal for fast monitoring purposes. However, it is usually very sensitive to the details
 10448 of the beam optics at the IP, may suffer from synchrotron radiation (SR) and requires, for accurate absolute
 10449 normalisation, a large and precisely known geometrical acceptance which is often difficult to ensure. On
 10450 the contrary, the main detector has stable and well known acceptance and is safely shielded against SR.
 10451 Therefore, although QED Compton events in the detector acceptance have significantly smaller rates they
 10452 may be better suited for overall global normalisation of the physics samples. Thus the two methods are
 10453 complementary, having very different systematics and providing useful redundancy and cross check for the
 10454 luminosity determination.

10455 To evaluate the main LHeC detector acceptance for NC DIS events and for the elastic QED Compton
 10456 process DJANGO [893] and COMPTON [894] event generators were used respectively. Different options for
 10457 dedicated luminosity detectors in the LHC tunnel have been studied with help of the special H1LUMI program
 10458 package [895], which contains Monte Carlo generation of the ‘collinear’ photons and electrons from various
 10459 processes (Bethe-Heitler reaction, quasi-real photoproduction, e-beam scattering on the rest gas) as well as
 10460 a simple tracking through the beamline.⁴

10461 14.1.2 Use of the Main LHeC Detector

10462 To estimate visible cross sections for NC DIS and elastic QED Compton events a typical HERA analysis
 10463 strategy was used. That is: safe fiducial cuts against energy leakage over the backward calorimeter boundaries
 10464 at small radii, safe (Q^2, y) cuts for NC DIS events to restrict measurement to the phase space where F_2 is
 10465 known to good precision of $1 - 2\%$ and the F_L contribution is negligible, and elasticity cuts for QEDC events
 10466 to reject the less precisely known inelastic contribution. In addition basic cuts against major backgrounds
 10467 were applied (photoproduction in case of NC DIS and DVCS, elastic VM production and low mass diffraction
 10468 in case of QED Compton).

10469 The visible NC DIS cross section, $\sigma_{\text{vis}}^{\text{DIS}}(Q^2 > 10\text{GeV}^2, 0.05 < y < 0.6) \simeq 10$ nb for 10° setup and $\simeq 150$
 10470 nb for 1° setup. This corresponds to a $10 - 15$ Hz rate which is comfortable enough for mid-term yield
 10471 control.

10472 For elastic QED Compton events, the visible cross section, $\sigma_{\text{vis}}^{\text{QEDC}} \simeq 0.03$ nb for 10° setup and $\simeq 3.5$ nb
 10473 for 1° setup. Hence while for the latter sufficiently high rate is possible even for $L = 10^{32}\text{cm}^{-2}\text{s}^{-1}$, in case
 10474 of ‘high Q^2 ’ setup the QEDC event rate is $4 - 5$ times smaller, thus only providing acceptable statistical
 10475 precision for large samples, of the order 0.5% /month.

10476 In order to improve this a special small dedicated calorimeter could eventually be added after the strong
 10477 focusing quadrupole, at $z = -6\text{m}$. Such ‘QEDC tagger’ should consist of two movable stations approaching
 10478 the beam-pipe from the top and the bottom in the vertical direction, as sketched in Figure 14.1b. This way
 10479 detector sections will be safe with respect to SR fan confined in the median plane. The visible elastic QED

³Total cross section, $\sigma_{BH} \simeq 870$ mb for 60×7000 GeV² ep collisions at the LHeC.

⁴The tracking has been performed by interfacing H1LUMI to GEANT3 [896] having LHeC beamline implemented up to $\sim 110\text{m}$ from the IP.

10480 Compton cross section for such a device is 4.3 ± 0.2 nb which significantly improves statistics for the luminosity
 10481 measurement. The angular acceptance of the ‘QEDC tagger’ corresponds to the range $\theta = 0.5^\circ - 1^\circ$ which
 10482 lies outside the tracking acceptance. Therefore calorimeter sections should be supplemented by small silicon
 10483 detectors in order to make it possible to reconstruct the event vertex from the final state containing only
 10484 one electron and one photon. These silicon trackers are also useful for e/γ separation and rejection of the
 10485 potential background. Actual dimensions and parameters of this optional ‘QEDC tagger’ requires extra
 10486 design studies.

10487 14.1.3 Dedicated Luminosity Detectors in the tunnel

10488 In case of the RR-option which implies non-zero crossing angle for early e/p beam separation, the dominant
 10489 part of the Bethe-Heitler photons will end up at $z \simeq -22$ m, between electron and proton beam-pipes (see
 10490 Figure 14.1c). This is the hottest place where also a powerful SR flux must be absorbed. On the first glance
 10491 this makes luminosity monitoring based upon the bremsstrahlung photons impossible.

10492 There is however an interesting possibility. SR absorber needs good cooling system. The most natural
 10493 cooling utilises circulating water. This cooling water can be used at the same time as an active media for
 10494 Čerenkov radiation from electromagnetic showers initiated by the energetic Bethe-Heitler photons. The idea
 10495 is based on two facts:

- 10496 1. The dominant part of the SR spectrum lies below the Čerenkov threshold for water, $E_{\text{thr}} = 260$ keV,
 10497 and hence will not produce light signal. Low intensity tail of the energetic synchrotron photons can be
 10498 further suppressed by few radiation lengths of the absorber material in front of the water volume.
- 10499 2. Water is absolutely radiation resistant media and hence such simple Čerenkov counter can stand any
 10500 dose without performance deterioration.

10501 The Čerenkov light can be collected and read out by two photo-multipliers as sketched on Figure 14.1d.
 10502 The geometric acceptance depends on the details of the e -beam optics. For the actual RR design with the
 10503 crossing angle ~ 1 mrad the acceptance to the Bethe-Heitler photons is up to 90%, thus allowing fast and
 10504 reliable luminosity monitoring with 3 – 5% systematic uncertainty.

10505 Of course, such an active SR absorber is not a calorimeter with good energy resolution, but just a simple
 10506 counter. It is worth noting, that similar water Čerenkov detector has been successfully used in the H1
 10507 Luminosity System during HERA-I operation.

10508 In case of LR-option, electrons collide with protons head-on, with zero crossing angle. This makes
 10509 the situation very similar to HERA, where Bethe-Heitler photons travel along the proton beam direction
 10510 and can be caught at around $z = -120$ m, after the first proton bending dipole. Essential difference is
 10511 that unlike HERA, LHC protons are deflected horizontally at this place rather than vertically. Thus the
 10512 luminosity detector should be placed in the median plane next to the interacting proton beam, p_1 , as shown
 10513 on Figure 14.1e. In this case energy measurement with good resolution is not a problem, so major uncertainty
 10514 will come from the knowledge of the limited geometric acceptance. This limitation is defined by the proton
 10515 beam-line aperture, in particular by the aperture of the quadrupoles Q1-Q3 of the low-beta proton triplet.
 10516 Moreover, it might be necessary to split D1 dipole into two parts in order to provide escape path for the
 10517 photons with sufficient aperture. First estimates show that the geometric acceptance of the Photon Detector
 10518 up to 95% is possible at the nominal beam conditions. HERA experience tells, that the uncertainty can be
 10519 estimated as $\delta A = 0.1 \cdot (1 - A)$ leading to the total luminosity error of $\delta L = 1\%$ in this case.

10520 14.1.4 Small angle Electron Tagger

10521 The Bethe-Heitler reaction can be tagged not only by detecting a final state photon, but also by detecting the
 10522 outgoing electron. Since all other competing processes have much smaller cross sections measuring inclusive
 10523 rate of the scattered electrons under zero angle will provide a clean enough sample for luminosity monitoring.
 10524 The remaining small background (mainly due to off-momentum electrons from e -beam scattering on the rest
 10525 gas) can be precisely controlled and statistically subtracted using non-colliding (*pilot*) electron bunches.




Figure 14.1: Options for the luminosity monitoring at the LHeC. (a) Feynman diagram for QEDC (γ^* pole) or BH (γ^* , e^* poles) processes; (b) QEDC tagger at $z = -6\text{m}$; (c,d) active SR absorber at $z = -22\text{m}$ for RR-option (circles show 1-, 2- and 3- σ contours for BH photons); (e) schematic view for the LR-option with 3- σ fan of BH photons.

10526
10527
10528
10529
10530

In order to determine the best positions for the Electron taggers the LHeC beamline simulation has been performed in the vicinity of the Interaction Region for the RR-option. Several positions for the e -tagger stations were tried:⁵ $z = -14\text{m}$, -22m and -62m . As one can see on the top part of Figure 14.2 all places provide reasonable acceptances, reaching approximately (20 – 25)% at the maximum. However, $z = -14\text{m}$ and $z = -22\text{m}$ most likely will suffer from SR flux, making e -tagger operation problematic at those positions.




Figure 14.2: Top: acceptances of the e -taggers for Bethe-Heitler events at different z -positions from IP (RR-option). Bottom: variations in the acceptance of the e -tagger at $z = -62\text{m}$ as a function of its position with respect to the e -beam axis and on the horizontal offset of the beam orbit at the IP.

10531
10532
10533
10534
10535
10536
10537
10538
10539
10540

The most promising position for the Electron tagger is at $z = -62\text{m}$. The actual acceptance strongly depends both on the distance of the sensitive detector volume from the e -beam axis and on the details of the electron optics at the IP, such as beam tilt or small trajectory offset, as illustrated on the bottom part of Figure 14.2. Therefore a precise independent monitoring of beam optics and accurate position measurement of the e -tagger are required in order to control geometrical acceptance to a sufficient precision. For example, instability in the horizontal trajectory offset at IP, x_{off} , of $\pm 20\mu\text{m}$ leads to the systematic uncertainty of 5% in the visible cross section, $\sigma_{\text{vis}}(ET62)$.

It is fair to note, that the magnetic field of the main LHeC detector was not taken into account in the simulation. The influence of this field is expected to be very small and will not alter basic conclusions of this section. Also, for the LR-option a similar acceptance is expected, although it may differ in shape somewhat.

⁵For the station at $z = -14\text{m}$ the electron dipole magnet should be split into two parts, while the region around $z = -62\text{m}$ has sufficiently comfortable place for the Electron tagger, before the e -beam is bended vertically.

10541
10542
10543
10544
10545
10546

In order to demonstrate that the ideas described in Sec. 14.1.3 and 14.1.4 are realistic a typical example of the online rates variations for the H1 Luminosity System at HERA is shown on Figure 14.3. The system utilised all three types of the detectors discussed above: a total absorption electromagnetic calorimeter for the Bethe-Heitler photons (PD), a water Čerenkov counter (VC) and the Electron tagger (ET6). One can see, that online luminosity estimate by every of those detectors is well within 5% in spite of significant changes in the acceptance due to electron beam tilt jumps and adjustments at the IP.




Figure 14.3: Online H1 Lumi System acceptance and rates variations in a typical HERA luminosity fill.

10547

14.1.5 Summary and Open Questions

10548
10549
10550

Accurate luminosity measurement at the LHeC is highly non-trivial task. As follows from HERA experience unexpected surprises are possible, hence it is important to consider several scenarios from the beginning and to prepare alternative methods for luminosity determination.

10551
10552

Statistical precision and systematic uncertainties for different methods of luminosity measurement are summarised in Table 14.1.

10553
10554
10555
10556
10557

Precise determination of integrated luminosity, \mathcal{L} , is possible with the main detector utilising the QEDC process. $\delta\mathcal{L} = 1.5 - 2\%$ is within reach. Further improvement requires in particular more accurate theoretical calculation of the elastic QED Compton cross section, with $\delta\sigma_{\text{el}}^{\text{QEDC}} \lesssim 0.5\%$. To enhance statistical precision a dedicated QEDC tagger at $z = -6\text{m}$ might be useful. This device could also be used to access very low Q^2 region, interpolating between DIS and photoproduction regimes.

10558
10559

Fast instantaneous luminosity monitoring is challenging, but several options do exist which are based upon detection of the photons and/or electrons from the Bethe-Heitler process.

Method	Stat. error	Syst.error	Systematic error components		Application
BH (γ)	0.05%/sec	1–5%	$\sigma(E \gtrsim 10\text{GeV})$ acceptance, A E -scale, pileup	0.5% 10%(1– A) 0.5 – 4%	Monitoring, tuning, short term variations
BH (e)	0.2%/sec	3–6%	$\sigma(E \gtrsim 10\text{GeV})$ acceptance background E -scale	0.5% 2.5 – 5% 1% 1%	Monitoring, tuning, short term variations
QEDC	0.5%/week	1.5%	σ (el/inel) acceptance vertex eff. E -scale	1% 1% 0.5% 0.3%	Absolute \mathcal{L} , global normalisation
NC DIS	0.5%/h	2.5%	σ ($y < 0.6$) acceptance vertex eff. E -scale	2% 1% 1% 0.3%	Relative \mathcal{L} , mid-term variations

Table 14.1: Dominant systematics for various methods of luminosity measurement.

- 10560 • Photon Detector at $z = 110\text{m}$ for LR option requires properly shaped proton beam-pipe at $z =$
10561 $-68 - 120\text{m}$ from IP2.
 - 10562 • In case of RR option Bethe-Heitler photons can be detected using a water Čerenkov counter integrated
10563 with SR absorber at $z = -22\text{m}$.
 - 10564 • Electron tagger at $z = -62\text{m}$ is very promising for both LR and RR schemes. It can be used not only
10565 for luminosity monitoring, but also to enhance photoproduction physics capabilities and to provide
10566 extra control of the γp background to DIS, by tagging quasi-real photoproduction events.
- 10567 Good monitoring of the e -optics at the IP is required to control acceptances of the tunnel detectors to a
10568 level of 2 – 5%.

10569 14.2 Polarimeter

The most powerful technique to measure the polarisation of the electrons and positrons of LHeC is Compton polarimetry. At high electron beam energies, this technique has been successfully used in the past at SLC [897] and at HERA [898] for example. The experimental setup consists of a laser beam which scatters off the electron/positron beam, and a calorimeter to measure the scattered gamma ray. At SLC, the scattered electron was also measured in a dedicated spectrometer. From the kinematics of Compton scattering one can get the expression for the maximum scattered photon energy:

$$E_{\gamma,max} \approx E_0 \frac{x}{1+x}$$

and the minimum scattered electron energy

$$E_{e,min} \approx E_0 \frac{1}{1+x},$$

10570 where E_0 is the electron/positron beam energy and $x = 4kE_0/m_e^2$ with k being the laser photon beam
10571 energy. At LHeC and for a $\approx 1\mu\text{m}$ laser beam wavelength, one gets $E_{\gamma,max} \approx 29\text{GeV}$ and $E_{e,min} \approx 31\text{GeV}$.

10572 Providing that the laser beam is circularly polarised, the electron/positron beam longitudinal polarisation is
10573 obtained from a fit to the scattered photon and/or to the electron energy spectrum. From an experimental
10574 point of view, both measurements can be complementary since the high energy region of the scattered
10575 photon energy spectrum is sensitive to the electron/positron beam longitudinal polarisation, whereas it is
10576 the opposite for the scattered electron/positron energy spectrum. Indeed, the high measurement precision of
10577 SLC was achieved thanks to the measurement of the scattered electrons. The measurement of both scattered
10578 photon and electron/positron spectra was therefore foreseen for a very high precision polarimetry at future
10579 electron-positron high energy colliders [583, 899].

10580 For LHeC, we may follow the work done for the future linear colliders [899]. In order to reach the per
10581 mille level on the longitudinal polarisation measurement, one may measure both the scattered photon and
10582 electron energy spectra.

10583 14.2.1 Polarisation from the scattered photons

10584 The photons are scattered within a very narrow cone of half aperture $\approx 1/\gamma$. It is therefore impossible
10585 to distinguish the photons reaching the calorimeter. As for the extraction of the longitudinal polarisation
10586 from the scattered photon beam energy, one may then distinguish three dynamical regimes [900]. The
10587 single and few scattered photons regimes, where one can extract the polarisation from a first principle fit
10588 to the scattered photon energy spectrum; the multi-photon regime where the central limit theorem holds
10589 for the energy spectra and where the longitudinal polarisation is extracted from an asymmetry between the
10590 average scattered energies corresponding to a circularly left and right laser beam polarisation [901]. Both
10591 regimes have positive and negative experimental features. In the single and few photon regimes the energy
10592 spectra exhibits kinematical edges which allow an in situ calibration of the detector energy response but
10593 the physical accelerator photon background which is difficult to model precisely, e.g. synchrotron radiation,
10594 limits the final precision on the polarisation measurement [900]. In the multi-photon regime, the background
10595 is negligible since it is located at low energy but one cannot measure the energy calibration of the detector
10596 in situ and one must rely on some high energy extrapolation of calibrations obtained at low energy [901]
10597 (e.g. for 100 scattered photon/bunch the deposited energy in the calorimeter would be more than 1TeV at
10598 LHeC). However, the laser technology has improved in the last ten years and one can consider at present
10599 a very stable pulsed laser beam with adjustable pulse energy allowing to operate in single, few and multi
10600 photon regimes. In this way, one can calibrate the calorimeter in situ and optimise the dynamical regime, a
10601 multi-photon regime as close as possible to the few photon regime, in order to minimise the final uncertainty
10602 on the polarisation measurement.

10603 14.2.2 Polarisation from the scattered electrons

10604 The nice feature of the scattered electron/positron is that one can use a magnetic spectrometer to distinguish
10605 them from each other. Following [899] one may carefully design a Compton interaction region in order to
10606 implement a dedicated electron spectrometer followed by a segmented electron detector in order to measure
10607 the scattered electron angular spectrum, itself related to the electron energy spectrum. A precise particle
10608 tracking is needed but this experimental method also allows a precise control of the systematic uncertainties
10609 [897].

10610 Common to both techniques is the control and measurement of the laser beam polarisation. it was shown
10611 in [902] that a few per mille precision can be achieved in an accelerator environment. Therefore, with a
10612 redundancy in measuring the electron/positron beam longitudinal polarisation from both the electron and
10613 photon scattered energy spectra, a final precision at the per mille level will be reachable at LHeC.

10614 14.3 Zero Degree Calorimeter

10615 The goal of the Zero Degree Calorimeter (ZDC) is to measure the energies and angles of the very forward
10616 particles. At HERA experiments, H1 and ZEUS, the forward neutral particles scattered at polar angles

10617 below 0.75 mrad were measured in the dedicated Forward Neutron Calorimeters (FNC) [437,903]. The LHC
10618 experiments, CMS, ATLAS, ALICE and LHCf, have the ZDC calorimeters for detection of forward neutral
10619 particles [904–908], ALICE has also the ZDC calorimeter for the measurements of spectator protons (for an
10620 illustration, a photo of the neutron calorimeter of ALICE experiment [904,905] is shown in Figure 14.4).

10621 The ZDC calorimeter will be an important addition to the future LHeC experiment as many physics
10622 measurements in ep , ed and eA collisions can be made possible with the installation of the ZDC.




Figure 14.4: Photo of the Zero Degree Neutron Calorimeter of ALICE experiment [904].

10623 14.3.1 ZDC detector design

10624 The position of the Zero Degree Calorimeter in the tunnel and the overall dimensions depend mainly on the
10625 space available for the installation. At the LHC the beams are deflected by two separating dipoles. These
10626 dipoles also deflect the spectator protons, separating them from the neutrons and photons, which scatter at
10627 polar angle $\sim 0^\circ$.

10628 The geometry, technical specifications and proposed design of the ZDC detector are to large extent similar
10629 to the ZDCs of the LHC experiments. There the ZDC calorimeters for detection of neutral particles are
10630 placed at $z = 115 - 140$ m in ~ 90 mm narrow space between two beam pipes. In the case of the LHeC, the
10631 ZDC calorimeter can be placed in the space available at about $90 - 100$ m next to the interacting proton
10632 beam pipe, as indicated in Figure 14.5.

10633 Below the general considerations for the design are presented. In order to finalise the study of the
10634 geometry of detectors, a detailed simulation of the LHeC interaction region and the beamline must be
10635 performed.

10636 14.3.2 Neutron Calorimeter

10637 The design of the ZDC has to satisfy the various technical issues. Detector has to be capable of detecting
10638 neutrons and photons produced with scattering angles up to 0.3 mrad or more and energies between some
10639 hundreds GeV to the proton beam energy (7 TeV) with a reasonable resolution of few percents. It must
10640 be able to distinguish hadronic and electromagnetic showers (i.e. separate neutrons from photons) and




Figure 14.5: Schematic layout of the LHeC interaction region. The possible position of the ZDC is indicated.

10641 to distinguish showers from two or more particles entering the detector (i.e. needs position resolution of
 10642 $\mathcal{O}(1\text{mm})$ or better). The ZDC will be operating in a very hard radiation environment, therefore it has to be
 10643 made of radiation resistant materials.

10644 The neutron ZDC can be built as a longitudinally segmented tungsten-quartz calorimeter. In this design
 10645 the ZDC will contain the electromagnetic and hadronic sections. The electromagnetic section with 1.5-2
 10646 nuclear interaction lengths (λ_I) and fine granularity is needed for precise determination of the position of
 10647 the impact point, discrimination of the electromagnetic and hadronic showers and separation of the showers
 10648 from two or more particles entering the detector. The hadronic section of the ZDC can be built with coarser
 10649 sampling, which will give an increase of average density and, consequently, the increase of effective nuclear
 10650 interaction length. The total depth of the calorimeter will be about 8-9 λ_I , which will allow for more than
 10651 90% containment of hadronic shower of $\mathcal{O}(\text{TeV})$ energies. Since the different parts of calorimeter undergo
 10652 different intensity of radiation (higher for front part), it is advantageous to have longitudinal segmentation
 10653 of 3-4 identical sections, which will provide the control of the change of energy response due to radiation
 10654 damage. Comparison of the energy spectrum from the showers which start in different sections can be used
 10655 for correction of changes in energy response.

10656 One of the possibilities to build a compact calorimeter with good radiation resistance is to use tungsten
 10657 absorbers and quartz fibres, similar to the one operated by CMS Experiment [907] (a schematic view is
 10658 shown in Fig.14.6). The principle of operation is based on the detection of Čerenkov light produced by
 10659 the shower's charged particles in the fibres. Using tungsten as a passive material allows the construction of
 10660 compact devices. (One can also consider option to use THGEM, thick gaseous electron multipliers, as an
 10661 active media [909,910].) These detectors are proven to be fast (\sim few ns) and radiation hard. The tungsten-
 10662 quartz technology is used in ZDC calorimeters implemented by the CMS, ATLAS and ALICE experiments
 10663 [904,906,907]. However, these calorimeters based on the detection of Čerenkov light are sensitive mainly to
 10664 the electromagnetic component of the hadronic shower. Therefore, they are highly non-compensating and
 10665 the energy resolution is not very high, e.g.the hadronic energy resolution for the CMS ZDC is $\sigma(E)/E \approx$
 10666 $176\%/\sqrt{E[\text{GeV}]} \oplus 8\%$ [911].

10667 An interesting new solution for the ZDC calorimeter is offered by the Dual Readout calorimetry technique,
 10668 which is currently being developed within the DREAM/RD52 Project [912]. In this approach the detector
 10669 is equipped with both scintillating and quartz fibers, which are sensitive to the different components of the




Figure 14.6: A side view of the CMS ZDC calorimeter with electromagnetic section in front and hadronic section behind.

10670 hadron shower. Hadron showers developing in this detector generate signals in both types of fibres and
 10671 these signals provide complementary information about these showers. With this experimental method, the
 10672 dominant source of fluctuations contributing to the hadronic energy resolution can be eliminated, since it
 10673 allows for a measurement of the electromagnetic energy fraction event-by-event [913]. The ZDC calorimeter
 10674 for LHeC detector can be built using tungsten absorber and SiPM readout. The readout from the scintillating
 10675 fibres can be made on the both ends of fibres, which will give a handle on the effects of radiation damage.
 10676 The discrimination between neutrons and photons will be possible using the time structure of the signals.
 10677 With the prototype tested by DREAM Collaboration, the depth resolutions of the order of 10 cm has been
 10678 reached, which is sufficient to distinguish between neutrons and photons in such longitudinally unsegmented
 10679 calorimeter [913, 914].

10680 14.3.3 Proton Calorimeter

10681 In addition to the ZDC calorimeter for measurement of neutral particles at 0° , a proton calorimeter positioned
 10682 externally to the outgoing proton beam can be installed for the measurement of spectator protons from eD
 10683 and eA scattering produced at zero degree. In analogy to ALICE experiment [904, 905], this detector can
 10684 be positioned at about a same distance from the interaction point as neutron ZDC. The size of proton
 10685 ZDC has to be small, due to the few cm small size of spectator proton spot, but sufficient to obtain shower
 10686 containment. This calorimeter will be made using the same technique as the neutron ZDC.

14.3.4 Calibration and monitoring

After initial calibration of the ZDCs with test-beams, it is essential to have regular online and offline control of the stability of the response, in particular due to hard radiation and temperature environment. The stability of the gain of the PMTs and the radiation damage in fibres can be monitored using the laser or LED light pulses. The stability of absolute calibration can be monitored using the interactions of the proton beam and residual gas molecules in the beam-pipe and comparison with the results of Monte Carlo simulation based on pion exchange, as used at HERA [437,903]. A useful tool for absolute energy calibration will be the reconstruction of invariant masses, e.g. $\pi^0 \rightarrow 2\gamma$ or $\Lambda, \Delta \rightarrow n\pi^0$, with decay particles produced at very small opening angles and reconstructed in the ZDC. It is therefore essential that in the ZDC several particles within the same event are reconstructed.

14.4 Forward Proton Detection

In diffractive interactions between protons or between an electron and a proton, the proton may survive a hard collision and be scattered at a low angle θ along the beam line while losing a small fraction ξ ($\sim 1\%$) of its energy. The ATLAS and CMS collaborations have investigated the feasibility to install detectors along the LHC beam line to measure the energy and momentum of such diffractively scattered protons [915]. Since the proton beam optics is primarily determined by the shape of the accelerator - which will not change for proton arm of the LHeC - the conclusions reached in this R&D study are still relevant for an LHeC detector.

In such a setup, diffractively scattered protons are separated from the nominal beam when traveling through dipole magnets with a slightly lower momentum. This spectroscopic behavior of the accelerator is described by the energy dispersion function, D_x , which, when multiplied with the actual energy loss, ξ , gives the additional offset of the trajectory followed by the off-momentum proton:

$$x_{\text{offset}} = D_x \times \xi.$$

The acceptance window in ξ is therefore determined by the closest possible approach of the proton detectors to the beam for low ξ and by the distance of the beam pipe walls from the nominal proton trajectory for high ξ . The closest possible approach is often taken to be equal to 12σ with σ equal to the beam width at a specific point. At the point of interest, 420m from the interaction point, the beam width is approximately equal to $250 \mu\text{m}$. On the other hand, the typical LHC beam pipe radius at large distances from the interaction point is approximately 2 cm. Even protons that have lost no energy, will eventually hit the beam pipe wall if they are scattered at large angles. This therefore fixes the maximally allowed fourmomentum-transfer squared t , which is approximately equal to the square of the transverse momentum p_T of the scattered proton at the interaction point.

At 420 m from the interaction point, the dispersion function at the LHC reaches 1.5 m, which results in an optimal acceptance window for diffractively scattered protons (roughly $0.002 < \xi < 0.013$). The acceptance as function of ξ and t is shown in Fig. 14.7, using the LHC proton beam optics [916]. The small corrections to be applied for the LHeC proton beam optics are not considered to be relevant for the description of the acceptance.

When the proton's position and angle w.r.t. the nominal beam can be accurately measured by the detectors, it is in principle possible to reconstruct the initial scattering angles and momentum loss of the proton at the interaction point. Even with an infinitesimally small detector resolution, the intrinsic beam width and divergence will still imply a lower limit on the resolution of the reconstructed kinematics. As the beam is typically maximally focussed at the interaction point in order to obtain a good luminosity, it will be the beam divergence that dominates the resolution on reconstructed variables.

Figure 14.8 shows the relation between position and angle w.r.t. the nominal beam and the proton scattering angle and momentum loss in both the horizontal and vertical plane as obtained from the LHC proton beam optics [916]. Clearly, in order to distinguish angles and momentum losses indicated by the curves in Fig. 14.8, the detector must have a resolution better than the distance between the curves.




Figure 14.7: The acceptance for a proton detector placed at 420m from the interaction point is shown as function of the momentum loss ξ and the fourmomentum-transfer squared t . The color legend runs from 0‰(no acceptance) to 1000‰(full acceptance).




Figure 14.8: Lines of constant ξ and $t \approx (1 - \xi)E_{\text{beam}}\theta^2$ are shown in the plane of proton position and angle w.r.t. the nominal proton beam in the horizontal (left) and vertical (right) plane.

10728
10729
10730
10731
10732

As stated above, protons with the same momentum loss and scattering angles will still end up at different positions and angles due to the intrinsic width and divergence of the beam. Lower limits on the resolution of reconstructed kinematics can therefore be determined. These are typically of the order of 0.5‰ for ξ and 0.2 μrad for the scattering angle θ . Figure 14.9 shows the main dependences of the resolution on ξ , t and the azimuthal scattering angle ϕ .




Figure 14.9: The lower limit due to the intrinsic beam width and divergence on the resolution of kinematic variables is shown for ξ as function ξ (top left), t as function t (top right) and ϕ as function of t (bottom).

10733
10734
10735
10736
10737
10738
10739
10740
10741
10742

A crucial issue in the operation of near-beam detectors is the alignment of the detectors w.r.t. the nominal beam. Typically, such detectors are retracted when beams are injected and moved close to the beam only when the accelerator conditions are declared to be stable. Also the beam itself, may not always be reinjected at the same position. It is therefore important to realign the detectors at for each accelerator run and to monitor any drifts during the run. At HERA, a kinematic peak method was used for alignment: as the reconstructed scattering angles depend on the misalignment, one may extract alignment constants by required that the observed cross section is maximal for forward scattering. In addition, this alignment procedure may be cross-checked by using a physics process with a exclusive system produced in the central detector such that the proton kinematics is fixed by applying energy-momentum conservation to the full set of final state particles. The feasibility of various alignment methods at the LHeC remains to be studied.

10743

Part V

10744

Summary

The summary will be added when the referee process is completed.

10746 Acknowledgement

10747 The authors express their gratitude to the CERN directorate, the CERN SPC, to ECFA, NuPECC, several
10748 members of the Scientific Advisory Committee and their home institutions for their support, interest and
10749 help in this development. We wish to thank many colleagues, engineers, experimentalist and theorists, for
10750 their contributions to the design report and interesting discussions.

Bibliography

- 10752 [1] A. Vera et al., *5D tiny black holes and perturbative saturation*, Talk at the LHeC Workshop at Divonne 08,
10753 <http://cern.ch/lhec>.
- 10754 [2] G. Altarelli, B. Mele, and R. Ruckl, *Physics of ep collisions in the TeV energy range*, . Presented at ECFA-CERN
10755 Workshop on Feasibility of Hadron Colliders in LEP Tunnel, Lausanne and Geneva, Switzerland, 1984.
- 10756 [3] A. Febel, H. Gerke, M. Tigner, H. Wiedemann, and B. Wiik, *The proposed desy proton-electron colliding beam*
10757 *experiment. (talk)*, IEEE Trans.Nucl.Sci. **20** (1973) 782–785.
- 10758 [4] B. Wiik et al., *PROPER - ep with PETRA*, DESY preprint **38** (1977).
- 10759 [5] J. R. Ellis, B. Wiik, and K. Hubner, *CHEEP: AN e-p FACILITY IN THE SPS*, CERN Yellow Report NN (1978).
- 10760 [6] SLAC-LBL Collaboration, M. Allen et al., *Particle Physics with electron-positron-proton beams*, SLAC-146 (1972).
- 10761 [7] J. T. Kamae et al., *Tristan ep Working Group Report*, UTPN-165, University of Tokyo (1980).
- 10762 [8] E. Blackmore et al., *Electron - proton collisions at Fermilab*, Fermilab-Proposal-0703 (1981).
- 10763 [9] A. Verdier, *An e p insertion for LHC and LEP*, Proc. Aachen LHC Workshop, CERN-90-10-B, 820-823 (1990).
- 10764 [10] W. Bartel, *e p experiments in LEP/LHC interaction regions*, Proc. Aachen LHC Workshop, CERN-90-10-B, B 824-832
10765 (1990).
- 10766 [11] R. Ruckl, *e p physics at LEP x LHC*, Proc. Aachen LHC Workshop, CERN-90-10-B, MPI-PAE-PTH-76-90 (1990).
- 10767 [12] E.Keil, *LHC ep Option*, LHC Report 93, CERN (1996).
- 10768 [13] P. Grosse-Wiesmann, *Colliding a Linear Electron Beam with a Storage Ring Beam*, NIM A **274** (1989) 21.
- 10769 [14] M. Tigner, B. Wiik, and F. Willeke, *An Electron - proton collider in the TeV range*, Proc. PAC IEEE, 2910-2912, San
10770 **Francisco** (1991).
- 10771 [15] U. Katz, A. Levy, M. Klein, and S. Schlenstedt, *Physics and experimentation at a linear electron positron collider. Vol.*
10772 *4: The THERA book. Electron proton scattering at $s^{**}(1/2)$ approx. 1-TeV, 445p.*, .
- 10773 [16] D. Schulte and F. Zimmermann, *QCD explorer based on LHC and CLIC-1*, . Prepared for 9th European Particle
10774 Accelerator Conference (EPAC 2004), Lucerne, Switzerland, 5-9 Jul 2004.
- 10775 [17] J. B. Dainton, M. Klein, P. Newman, E. Perez, and F. Willeke, *Deep inelastic electron nucleon scattering at the LHC*,
10776 *JINST 1* (2006) P10001, [arXiv:hep-ex/0603016](http://arxiv.org/abs/hep-ex/0603016).
- 10777 [18] M. Klein, *Physics at HERA and beyond*, AIP Conf.Proc. **792** (2005) 1065–1076.
- 10778 [19] M. Breidenbach, J. I. Friedman, H. W. Kendall, E. D. Bloom, D. Coward, et al., *Observed Behavior of Highly Inelastic*
10779 *electron-Proton Scattering*, Phys.Rev.Lett. **23** (1969) 935–939.
- 10780 [20] E. D. Bloom, D. Coward, H. DeStaabler, J. Drees, G. Miller, et al., *High-Energy Inelastic e p Scattering at 6-Degrees*
10781 *and 10-Degrees*, Phys.Rev.Lett. **23** (1969) 930–934.
- 10782 [21] LHeC Study Group, M. Klein, *Status of the LHeC Design*, Reports to ECFA 2008-2011, ICFA 2008,
10783 <http://cern.ch/lhec>.
- 10784 [22] *NuPECC Long Range Plan 2010*. <http://www.nupecc.org/>.
- 10785 [23] S. Myers, *Invited Talk at ICHEP, Paris*, 2010.
- 10786 [24] F. Wilczek, *Talk at the 50 Years of the PS Nobel Prize Winner Colloquium, CERN*, 2009.
- 10787 [25] H. Geiger and E. Marsden, *On a Diffuse Reflection of the α Particles*, Proc. Royal Society **A82** (1909) 495–500.
- 10788 [26] E. Rutherford, *The scattering of the α and β Particles by Matter and the Structure of the Atom*, Philosophical
10789 Magazine, Series 6 **21** (1911) 669–688.
- 10790 [27] R. Hofstadter and R. McAllister, *ELECTRON SCATTERING FROM THE PROTON*, Phys.Rev. **98** (1955) 217–218.
- 10791 [28] D. J. Gross and F. Wilczek, *Ultraviolet behaviour of non-abelian gauge theories*, Phys. Rev. Lett. **30** (1973) 1343–1346.

- 10792 [29] H. D. Politzer, *Reliable perturbative results for strong interactions?*, Phys. Rev. Lett. **30** (1973) 1346–1349.
- 10793 [30] R. Feynman, *Photon-hadron interactions*, . New York, 1973.
- 10794 [31] H. Fritzsch, M. Gell-Mann, and H. Leutwyler, *Advantages of the Color Octet Gluon Picture*, Phys.Lett. **B47** (1973)
10795 365–368.
- 10796 [32] M. Froissart, *Fundamental Theoretical Questions, Rapporteurs Talk at the Rochester Conference, Berkeley*, 1966.
- 10797 [33] V. N. Gribov and L. N. Lipatov, *Deep inelastic ep scattering in perturbation theory*, Sov. J. Nucl. Phys. **15** (1972)
10798 438–450.
- 10799 [34] Y. L. Dokshitzer, *Calculation of the Structure Functions for Deep Inelastic Scattering and e^+e^- Annihilation by
10800 Perturbation Theory in Quantum Chromodynamics*, Sov. Phys. JETP **46** (1977) 641–653.
- 10801 [35] G. Altarelli and G. Parisi, *Asymptotic Freedom in Parton Language*, Nucl. Phys. **B126** (1977) 298.
- 10802 [36] S. Moch, J. Vermaseren, and A. Vogt, *The Three loop splitting functions in QCD: The Nonsinglet case*, Nucl.Phys.
10803 **B688** (2004) 101–134, [arXiv:hep-ph/0403192](#) [[hep-ph](#)].
- 10804 [37] A. Vogt, S. Moch, and J. Vermaseren, *The Three-loop splitting functions in QCD: The Singlet case*, Nucl.Phys. **B691**
10805 (2004) 129–181, [arXiv:hep-ph/0404111](#) [[hep-ph](#)].
- 10806 [38] H1 and ZEUS Collaborations, F. Aaron et al., *Combined Measurement and QCD Analysis of the Inclusive e^+p
10807 Scattering Cross Sections at HERA*, JHEP **1001** (2010) 109, [arXiv:0911.0884](#) [[hep-ex](#)].
- 10808 [39] F. Schrempp, *Instanton-induced processes: An Overview*, [arXiv:hep-ph/0507160](#) [[hep-ph](#)].
- 10809 [40] L. N. Lipatov, *Effective action for the Regge processes in gravity*, [arXiv:1105.3127](#) [[hep-th](#)]. * Temporary entry *.
- 10810 [41] B. L. Ioffe, V. S. Fadin, and L. N. Lipatov, *Quantum chromodynamics: Perturbative and nonperturbative aspects*, .
10811 Cambridge University Press, 2010.
- 10812 [42] A. De Rujula, *Charm is found*, . Proceedings of XVIII ICHEP Conference, Tbilissi, 1976.
- 10813 [43] A. Salam, *The Unconfined Quarks and Gluons*, . Proceedings of XVIII ICHEP Conference, Tbilissi, 1976.
- 10814 [44] J. L. Hewett and T. G. Rizzo, *Low-Energy Phenomenology of Superstring Inspired $E(6)$ Models*, Phys. Rept. **183**
10815 (1989) 193.
- 10816 [45] J. C. Pati and A. Salam, *Lepton Number as the Fourth Color*, Phys. Rev. **D10** (1974) 275–289.
- 10817 [46] L. Susskind, *Dynamics of Spontaneous Symmetry Breaking in the Weinberg-Salam Theory*, Phys.Rev. **D20** (1979)
10818 2619–2625.
- 10819 [47] E. Farhi and L. Susskind, *Technicolor*, Phys. Rept. **74** (1981) 277.
- 10820 [48] B. Andersson, G. Gustafson, G. Ingelman, and T. Sjostrand, *Parton Fragmentation and String Dynamics*, Phys. Rept.
10821 **97** (1983) 31–145.
- 10822 [49] A. Glazov, S. Moch, and V. Radescu, *Parton Distribution Uncertainties using Smoothness Prior*, Phys.Lett. **B695**
10823 (2011) 238–241, [arXiv:1009.6170](#) [[hep-ph](#)].
- 10824 [50] J. Kuti and V. F. Weisskopf, *Inelastic lepton - nucleon scattering and lepton pair production in the relativistic quark
10825 parton model*, Phys.Rev. **D4** (1971) 3418–3439.
- 10826 [51] S. Brodsky, P. Hoyer, C. Peterson, and N. Sakai, *The Intrinsic Charm of the Proton*, Phys.Lett. **B93** (1980) 451–455.
- 10827 [52] M. Krasny, F. Dydak, F. Fayette, W. Placzek, and A. Siodmok, $\Delta M_W \leq 10 MeV/c^2$ at the LHC: a forlorn hope?,
10828 Eur.Phys.J. **C69** (2010) 379–397, [arXiv:1004.2597](#) [[hep-ex](#)].
- 10829 [53] K. Kovarik, I. Schienbein, F. Olness, J. Yu, C. Keppel, et al., *Nuclear corrections in neutrino-nucleus DIS and their
10830 compatibility with global NPDF analyses*, Phys.Rev.Lett. **106** (2011) 122301, [arXiv:1012.0286](#) [[hep-ph](#)].
- 10831 [54] D. Mueller, D. Robaschik, B. Geyer, F. M. Dittes, and J. Horejsi, *Wave functions, evolution equations and evolution
10832 kernels from light-ray operators of QCD*, Fortschr. Phys. **42** (1994) 101, [arXiv:hep-ph/9812448](#).
- 10833 [55] A. V. Belitsky and A. V. Radyushkin, *Unraveling hadron structure with generalized parton distributions*, Phys. Rept.
10834 **418** (2005) 1–387, [arXiv:hep-ph/0504030](#).
- 10835 [56] V. N. Gribov, *Interaction of gamma quanta and electrons with nuclei at high-energies*, Sov. Phys. JETP **30** (1970)
10836 709–717.
- 10837 [57] M. Tigner, *A possible apparatus for electron clashing-beam experiments*, Nuovo Cim. **37** (1965) 1228–1231.
- 10838 [58] M. Klein and T. Riemann, *Electroweak interactions probing the nucleon structure*, Z.Phys. **C24** (1984) 151.
- 10839 [59] E. Derman, *Tests for a weak neutral current in ln to $l+$ anything at high energy*, Phys.Rev. **D7** (1973) 2755–2775.
- 10840 [60] J. Callan, Curtis G. and D. J. Gross, *High-energy electroproduction and the constitution of the electric current*,
10841 Phys.Rev.Lett. **22** (1969) 156–159.
- 10842 [61] G. Altarelli and G. Martinelli, *Transverse Momentum of Jets in Electroproduction from Quantum Chromodynamics*,
10843 Phys.Lett. **B76** (1978) 89.

- 10844 [62] A. Argento, A. Benvenuti, D. Bollini, G. Bruni, T. Camporesi, et al., *Measurement of the interference structure*
10845 *function $xG(3)(x)$ in muon - nucleon scattering*, Phys.Lett. **B140** (1984) 142.
- 10846 [63] A. Arbuzov, D. Y. Bardin, J. Blumlein, L. Kalinovskaya, and T. Riemann, *Hector 1.00: A Program for the calculation*
10847 *of QED, QCD and electroweak corrections to $e p$ and lepton+- N deep inelastic neutral and charged current scattering*,
10848 Comput.Phys.Commun. **94** (1996) 128–184, arXiv:hep-ph/9511434 [hep-ph].
- 10849 [64] Particle Data Group, K. Nakamura, *Review of particle physics*, J. Phys. **G37** (2010) 075021.
- 10850 [65] J. Blumlein and M. Klein, *On the cross calibration of calorimeters at $e p$ colliders*, Nucl. Instrum. Meth. **A329** (1993)
10851 112–116.
- 10852 [66] M. Klein, *Scenarios and Measurements with the LHeC*, Talk given at the LHeC Meeting at DIS 2009, Madrid, Spain,
10853 April 2009.
- 10854 [67] ZEUS Collaboration, S. Chekanov et al., *Measurement of the Longitudinal Proton Structure Function at HERA*,
10855 Phys.Lett. **B682** (2009) 8–22, arXiv:0904.1092 [hep-ex].
- 10856 [68] F. Aaron, C. Alexa, V. Andreev, S. Backovic, A. Baghdasaryan, et al., *Measurement of the Inclusive $e\pm p$ Scattering*
10857 *Cross Section at High Inelasticity y and of the Structure Function FL* , Eur.Phys.J. **C71** (2011) 1579, arXiv:1012.4355
10858 [hep-ex].
- 10859 [69] M. Botje, *QCDNUM manual*. <http://www.nikhef.nl/~h24/qcdnum/>. <http://www.nikhef.nl/~h24/qcdnum/>.
- 10860 [70] E. Rizvi and T. Sloan, *$x F^{**}(\gamma Z)(3)$ in charged lepton scattering*, Eur.Phys.J.direct **C3** (2001) N2,
10861 arXiv:hep-ex/0101007 [hep-ex].
- 10862 [71] HERMES Collaboration, A. Airapetian et al., *Measurement of Parton Distributions of Strange Quarks in the Nucleon*
10863 *from Charged-Kaon Production in Deep-Inelastic Scattering on the Deuteron*, Phys. Lett. **B666** (2008) 446–450,
10864 arXiv:0803.2993 [hep-ex].
- 10865 [72] U. Baur and J. van der Bij, *Top quark production at HERA*, Nucl.Phys. **B304** (1988) 451.
- 10866 [73] H. Fritzsch and D. Holtmannspotter, *The Production of single t quarks at LEP and HERA*, Phys. Lett. **B457** (1999)
10867 186–192, arXiv:hep-ph/9901411.
- 10868 [74] C. Pascaud, *CFNS*, Talk given at DIS 2011, Newport News, USA, April 2011.
- 10869 [75] G. Brandt, *Single top production of diquarks at LHeC*, Talk given at the 1st CERN-ECFA Workshop on the LHeC,
10870 Divonne-les-Bains, France, 1-3 September 2008.
- 10871 [76] CMS Collaboration, S. Chatrchyan et al., *Measurement of the t -channel single top quark production cross section in pp*
10872 *collisions at $\sqrt{s} = 7$ TeV*, arXiv:1106.3052 [hep-ex]. * Temporary entry *.
- 10873 [77] S. Alekhin, J. Blumlein, P. Jimenez-Delgado, S. Moch, and E. Reya, *NNLO Benchmarks for Gauge and Higgs Boson*
10874 *Production at TeV Hadron Colliders*, Phys. Lett. **B697** (2011) 127–135, arXiv:1011.6259 [hep-ph].
- 10875 [78] J. A. M. Vermaseren, A. Vogt, and S. Moch, *The third-order QCD corrections to deep-inelastic scattering by photon*
10876 *exchange*, Nucl. Phys. **B724** (2005) 3–182, arXiv:hep-ph/0504242.
- 10877 [79] I. Bierenbaum, J. Blumlein, and S. Klein, *Mellin Moments of the $O(\alpha^{**3}(s))$ Heavy Flavor Contributions to*
10878 *unpolarized Deep-Inelastic Scattering at $Q^{**2} \gg m^{**2}$ and Anomalous Dimensions*, Nucl.Phys. **B820** (2009) 417–482,
10879 arXiv:0904.3563 [hep-ph].
- 10880 [80] J. Blumlein, H. Bottcher, and A. Guffanti, *Non-singlet QCD analysis of deep inelastic world data at $O(\alpha(s)^{**3})$* ,
10881 Nucl.Phys. **B774** (2007) 182–207, arXiv:hep-ph/0607200 [hep-ph].
- 10882 [81] M. Gluck, E. Reya, and C. Schuck, *Non-singlet QCD analysis of $F(2)(x, Q^{**2})$ up to NNLO*, Nucl.Phys. **B754** (2006)
10883 178–186, arXiv:hep-ph/0604116 [hep-ph].
- 10884 [82] S. Alekhin, J. Blumlein, S. Klein, and S. Moch, *The 3, 4, and 5-flavor NNLO Parton from Deep-Inelastic-Scattering*
10885 *Data and at Hadron Colliders*, Phys.Rev. **D81** (2010) 014032, arXiv:0908.2766 [hep-ph].
- 10886 [83] P. Jimenez-Delgado and E. Reya, *Dynamical NNLO parton distributions*, Phys. Rev. **D79** (2009) 074023,
10887 arXiv:0810.4274 [hep-ph].
- 10888 [84] A. D. Martin, W. J. Stirling, R. S. Thorne, and G. Watt, *Uncertainties on α_s in global PDF analyses and*
10889 *implications for predicted hadronic cross sections*, Eur. Phys. J. **C64** (2009) 653–680, arXiv:0905.3531 [hep-ph].
- 10890 [85] S. Alekhin, J. Blumlein, and S.-O. Moch, *Update of the NNLO PDFs in the 3-, 4-, and 5-flavour scheme*, PoS
10891 **DIS2010** (2010) 021, arXiv:1007.3657 [hep-ph].
- 10892 [86] S. Bethke, *The 2009 World Average of $\alpha(s)$* , Eur.Phys.J. **C64** (2009) 689–703, arXiv:0908.1135 [hep-ph].
- 10893 [87] J. Blumlein, S. Riemersma, W. van Neerven, and A. Vogt, *Theoretical uncertainties in the QCD evolution of structure*
10894 *functions and their impact on $\alpha-s(M(Z)^{**2})$* , Nucl.Phys.Proc.Suppl. **51C** (1996) 97–105, arXiv:hep-ph/9609217
10895 [hep-ph].
- 10896 [88] S. J. Brodsky, *Novel QCD Phenomenology at the LHeC*, arXiv:1106.5820 [hep-ph]. LHeC-Note-2011-002 PHY and
10897 SLAC-PUB-14487.

- 10898 [89] P. Baikov and K. Chetyrkin, *New four loop results in QCD*, Nucl.Phys.Proc.Suppl. **160** (2006) 76–79.
- 10899 [90] M. Buza, Y. Matiounine, J. Smith, and W. van Neerven, *Charm electroproduction viewed in the variable flavor number*
10900 *scheme versus fixed order perturbation theory*, Eur.Phys.J. **C1** (1998) 301–320, arXiv:hep-ph/9612398 [hep-ph].
- 10901 [91] S. Alekhin and S. Moch, *Heavy-quark deep-inelastic scattering with a running mass*, Phys. Lett. **B699** (2011) 345–353,
10902 arXiv:1011.5790 [hep-ph].
- 10903 [92] T. Gehrmann, M. Jaquier, and G. Luisoni, *Hadronization effects in event shape moments*, Eur.Phys.J. **C67** (2010)
10904 57–72, arXiv:0911.2422 [hep-ph].
- 10905 [93] R. Abbate, M. Fickinger, A. H. Hoang, V. Mateu, and I. W. Stewart, *Thrust at N3LL with Power Corrections and a*
10906 *Precision Global Fit for $\alpha_s(m_Z)$* , Phys.Rev. **D83** (2011) 074021, arXiv:1006.3080 [hep-ph].
- 10907 [94] M. Virchaux and A. Milsztajn, *A Measurement of α_s and higher twists from a QCD analysis of high statistics F-2*
10908 *data on hydrogen and deuterium targets*, Phys.Lett. **B274** (1992) 221–229.
- 10909 [95] H1 Collaboration, C. Adloff et al., *Deep-inelastic inclusive e p scattering at low x and a determination of α_s* , Eur.
10910 Phys. J. **C21** (2001) 33–61, arXiv:hep-ex/0012053.
- 10911 [96] R. Wallny, *A Measurement of the Gluon Distribution in the Proton and of the Strong Coupling Constant α_s from*
10912 *Inclusive Deep-Inelastic Scattering*, H1 PhD Thesis 2001, Zurich, Switzerland, 2001.
- 10913 [97] A. Martin, W. Stirling, R. Thorne, and G. Watt, *α_s in MSTW Analyses*, Talk given in [99], February 2011.
- 10914 [98] S. Lionetti, R. D. Ball, V. Bertone, F. Cerutti, L. Del Debbio, et al., *Precision determination of α_s using an unbiased*
10915 *global NLO parton set*, arXiv:1103.2369 [hep-ph].
- 10916 [99] S. Bethke et al., *Workshop on Precision Measurements on α_s* , MPI Munich, Germany, February, 2011.
- 10917 [100] T. Kluge, *Prospects of α_s Determinations in DIS*, Talks given at the CERN-ECFA-NuPECC Workshops on the
10918 LHeC, Divonne-les-Bains, France, September 2008/09.
- 10919 [101] BCDMS Collaboration, A. Benvenuti et al., *A comparison of the structure functions F2 of the proton and the neutron*
10920 *from Deep Inelastic muon scattering at high Q**2*, Phys.Lett. **B237** (1990) 599.
- 10921 [102] BCDMS Collaboration, A. C. Benvenuti et al., *A High Statistics Measurement of the Deuteron Structure Functions*
10922 *F(2) (x, Q**2) and R from Deep Inelastic Muon Scattering at High Q**2*, Phys. Lett. **B237** (1990) 592.
- 10923 [103] European Muon Collaboration, J. Aubert et al., *Measurements of the nucleon structure functions F2n in deep inelastic*
10924 *muon scattering from deuterium and comparison with those from hydrogen and iron*, Nucl.Phys. **B293** (1987) 740.
- 10925 [104] T. A. et al., *eD Scattering with H1, A Letter of Intent DESY 03-194*, .
- 10926 [105] T. A. et al., *A New experiment For HERA, MPP-2003-62*, .
- 10927 [106] T. Greenshaw and M. Klein, *The Future of lepton nucleon scattering: A Summary of the Durham Workshop, December*
10928 *2001*, J.Phys.G **G28** (2002) 2503–2508, arXiv:hep-ex/0204032 [hep-ex].
- 10929 [107] I. Schienbein, J. Yu, K. Kovarik, C. Keppel, J. Morfin, et al., *PDF Nuclear Corrections for Charged and Neutral*
10930 *Current Processes*, Phys.Rev. **D80** (2009) 094004, arXiv:0907.2357 [hep-ph].
- 10931 [108] L. Frankfurt, V. Guzey, and M. Strikman, *Nuclear shadowing in inclusive and tagged deuteron structure functions and*
10932 *extraction of F(2)**p - F(2)**n at small x from electron-deuteron collider data*, Mod.Phys.Lett. **A21** (2006) 23–40,
10933 arXiv:hep-ph/0601123 [hep-ph].
- 10934 [109] T. Hobbs, J. Londergan, D. Murdock, and A. Thomas, *Testing Partonic Charge Symmetry at a High-Energy Electron*
10935 *Collider*, Phys.Lett. **B698** (2011) 123–127, arXiv:1101.3923 [hep-ph].
- 10936 [110] S. J. Brodsky and B. Chertok, *The Asymptotic Form-Factors of Hadrons and Nuclei and the Continuity of Particle*
10937 *and Nuclear Dynamics*, Phys.Rev. **D14** (1976) 3003–3020.
- 10938 [111] V. A. Matveev and P. Sorba, *Is Deuteron a Six Quark System?*, Lett.Nuovo Cim. **20** (1977) 435.
- 10939 [112] S. J. Brodsky, C.-R. Ji, and G. Lepage, *Quantum Chromodynamic Predictions for the Deuteron Form-Factor*,
10940 Phys.Rev.Lett. **51** (1983) 83.
- 10941 [113] R. Arnold, B. Chertok, E. Dally, A. Grigorian, C. Jordan, et al., *Measurement of the electron-Deuteron Elastic*
10942 *Scattering Cross-Section in the Range 0.8 GeV**2 <math>j q**2 <math>j 6 GeV**2, Phys.Rev.Lett. **35** (1975) 776.*
- 10943 [114] G. R. Farrar, K. Huleihel, and H.-y. Zhang, *Deuteron form-factor*, Phys.Rev.Lett. **74** (1995) 650–653.
- 10944 [115] B. W. Harris and J. Smith, *Charm quark and D*+- cross sections in deeply inelastic scattering at HERA*, Phys. Rev.
10945 **D57** (1998) 2806–2812, arXiv:hep-ph/9706334.
- 10946 [116] S. Frixione, M. L. Mangano, P. Nason, and G. Ridolfi, *Total Cross Sections for Heavy Flavour Production at HERA*,
10947 Phys. Lett. **B348** (1995) 633–645, arXiv:hep-ph/9412348.
- 10948 [117] S. Frixione, P. Nason, and G. Ridolfi, *Differential distributions for heavy flavor production at HERA*, Nucl. Phys. **B454**
10949 (1995) 3–24, arXiv:hep-ph/9506226.
- 10950 [118] J. Binnewies, B. A. Kniehl, and G. Kramer, *Inclusive B meson production in e+ e- and p anti-p collisions*, Phys. Rev.
10951 **D58** (1998) 034016, arXiv:hep-ph/9802231.

- 10952 [119] J. Binnewies, B. A. Kniehl, and G. Kramer, *Coherent description of D^{*+-} production in e^+e^- and low- Q^{*2} $e p$*
10953 *collisions*, Z. Phys. **C76** (1997) 677–688, [arXiv:hep-ph/9702408](#).
- 10954 [120] B. A. Kniehl, G. Kramer, and M. Spira, *Large $p(T)$ photoproduction of D^{*+-} mesons in $e p$ collisions*, Z. Phys. **C76**
10955 (1997) 689–700, [arXiv:hep-ph/9610267](#).
- 10956 [121] M. Cacciari and M. Greco, *Charm Production via Fragmentation*, Z. Phys. **C69** (1996) 459–466, [arXiv:hep-ph/9505419](#).
- 10957 [122] G. Kramer and H. Spiesberger, *Inclusive photoproduction of D^* mesons with massive charm quarks*, Eur. Phys. J. **C38**
10958 (2004) 309–318, [arXiv:hep-ph/0311062](#).
- 10959 [123] B. A. Kniehl, G. Kramer, I. Schienbein, and H. Spiesberger, *Inclusive D^{*+-} production in p anti- p collisions with*
10960 *massive charm quarks*, Phys. Rev. **D71** (2005) 014018, [arXiv:hep-ph/0410289](#).
- 10961 [124] S. Catani, M. Ciafaloni, and F. Hautmann, *Gluon contributions to small x heavy flavor production*, Phys. Lett. **B242**
10962 (1990) 97.
- 10963 [125] S. Catani, M. Ciafaloni, and F. Hautmann, *High-energy factorization and small x heavy flavor production*, Nucl. Phys.
10964 **B366** (1991) 135–188.
- 10965 [126] A. Belyaev, J. Pumplin, W.-K. Tung, and C. P. Yuan, *Uncertainties of the inclusive Higgs production cross section at*
10966 *the Tevatron and the LHC*, JHEP **01** (2006) 069, [arXiv:hep-ph/0508222](#).
- 10967 [127] S. J. Brodsky, J. C. Collins, S. D. Ellis, J. F. Gunion, and A. H. Mueller, *INTRINSIC CHEVROLETS AT THE SSC*, .
- 10968 [128] B. Harris, J. Smith, and R. Vogt, *Reanalysis of the EMC charm production data with extrinsic and intrinsic charm at*
10969 *NLO*, Nucl.Phys. **B461** (1996) 181–196, [arXiv:hep-ph/9508403](#) [[hep-ph](#)].
- 10970 [129] M. Franz, M. V. Polyakov, and K. Goeke, *Heavy quark mass expansion and intrinsic charm in light hadrons*, Phys.Rev.
10971 **D62** (2000) 074024, [arXiv:hep-ph/0002240](#) [[hep-ph](#)].
- 10972 [130] T. Sjostrand, S. Mrenna, and P. Z. Skands, *PYTHIA 6.4 Physics Manual*, JHEP **05** (2006) 026, [arXiv:hep-ph/0603175](#).
- 10973 [131] J. Pumplin et al., *New generation of parton distributions with uncertainties from global QCD analysis*, JHEP **07** (2002)
10974 012, [arXiv:hep-ph/0201195](#).
- 10975 [132] H. Jung, *Hard diffractive scattering in high-energy $e p$ collisions and the Monte Carlo generator RAPGAP*, Comp.
10976 Phys. Commun. **86** (1995) 147–161.
- 10977 [133] CTEQ, H. L. Lai et al., *Global QCD analysis of parton structure of the nucleon: CTEQ5 parton distributions*, Eur.
10978 Phys. J. **C12** (2000) 375–392, [arXiv:hep-ph/9903282](#).
- 10979 [134] G. Ingelman, A. Edin, and J. Rathsman, *LEPTO 6.5 - A Monte Carlo Generator for Deep Inelastic Lepton-Nucleon*
10980 *Scattering*, Comput. Phys. Commun. **101** (1997) 108–134, [arXiv:hep-ph/9605286](#).
- 10981 [135] H1 and ZEUS Collaborations, *Combination of F_2^{cc} from DIS measurements at HERA*, Preliminary measurements
10982 H1prelim-09-171,ZEUS-prel-09-015.
- 10983 [136] H1 Collaboration, F. D. Aaron et al., *Measurement of the Charm and Beauty Structure Functions using the H1 Vertex*
10984 *Detector at HERA*, Eur. Phys. J. **C65** (2010) 89–109, [arXiv:0907.2643](#) [[hep-ex](#)].
- 10985 [137] J. Pumplin, H. L. Lai, and W. K. Tung, *The charm parton content of the nucleon*, Phys. Rev. **D75** (2007) 054029,
10986 [arXiv:hep-ph/0701220](#).
- 10987 [138] S. J. Brodsky, B. Kopeliovich, I. Schmidt, and J. Soffer, *Diffractive Higgs production from intrinsic heavy flavors in the*
10988 *proton*, Phys.Rev. **D73** (2006) 113005, [arXiv:hep-ph/0603238](#) [[hep-ph](#)].
- 10989 [139] P. Aurenche, M. Fontannaz, and J. P. Guillet, *New NLO parametrizations of the parton distributions in real photons*,
10990 Eur. Phys. J. **C44** (2005) 395–409, [arXiv:hep-ph/0503259](#).
- 10991 [140] W. K. Tung et al., *Heavy quark mass effects in deep inelastic scattering and global QCD analysis*, JHEP **02** (2007) 053,
10992 [arXiv:hep-ph/0611254](#).
- 10993 [141] T. Kneesch, B. A. Kniehl, G. Kramer, and I. Schienbein, *Charmed-Meson Fragmentation Functions with Finite-Mass*
10994 *Corrections*, Nucl. Phys. **B799** (2008) 34–59, [arXiv:0712.0481](#) [[hep-ph](#)].
- 10995 [142] M. Gluck, E. Reya, and A. Vogt, *Photonic parton distributions*, Phys. Rev. **D46** (1992) 1973–1979.
- 10996 [143] M. Klasen and G. Kramer, *Inclusive two-jet production at HERA: Direct and resolved cross sections in next-to-leading*
10997 *order QCD*, Z. Phys. **C76** (1997) 67–74, [arXiv:hep-ph/9611450](#).
- 10998 [144] S. Catani and M. H. Seymour, *A general algorithm for calculating jet cross sections in NLO QCD*, Nucl. Phys. **B485**
10999 (1997) 291–419, [arXiv:hep-ph/9605323](#).
- 11000 [145] D. Stump et al., *Inclusive jet production, parton distributions, and the search for new physics*, JHEP **10** (2003) 046,
11001 [arXiv:hep-ph/0303013](#).
- 11002 [146] J. Pumplin, A. Belyaev, J. Huston, D. Stump, and W. K. Tung, *Parton distributions and the strong coupling:*
11003 *CTEQ6AB PDFs*, JHEP **02** (2006) 032, [arXiv:hep-ph/0512167](#).
- 11004 [147] T. Gehrmann and E. W. N. Glover, *Two-Loop QCD Helicity Amplitudes for $(2+1)$ -Jet Production in Deep Inelastic*
11005 *Scattering*, Phys. Lett. **B676** (2009) 146–151, [arXiv:0904.2665](#) [[hep-ph](#)].

- 11006 [148] A. Daleo, A. Gehrmann-De Ridder, T. Gehrmann, and G. Luisoni, *Antenna subtraction at NNLO with hadronic initial*
11007 *states: initial-final configurations*, JHEP **01** (2010) 118, [arXiv:0912.0374 \[hep-ph\]](#).
- 11008 [149] S. Frixione, Z. Kunszt, and A. Signer, *Three jet cross-sections to next-to-leading order*, Nucl. Phys. **B467** (1996)
11009 399–442, [arXiv:hep-ph/9512328](#).
- 11010 [150] S. Frixione, *A General approach to jet cross-sections in QCD*, Nucl. Phys. **B507** (1997) 295–314,
11011 [arXiv:hep-ph/9706545](#).
- 11012 [151] M. Gluck, E. Reya, and A. Vogt, *Parton structure of the photon beyond the leading order*, Phys. Rev. **D45** (1992)
11013 3986–3994.
- 11014 [152] K. J. Eskola, H. Paukkunen, and C. A. Salgado, *EPS09 - a New Generation of NLO and LO Nuclear Parton*
11015 *Distribution Functions*, JHEP **04** (2009) 065, [arXiv:0902.4154 \[hep-ph\]](#).
- 11016 [153] S. D. Ellis and D. E. Soper, *Successive combination jet algorithm for hadron collisions*, Phys. Rev. **D48** (1993)
11017 3160–3166, [arXiv:hep-ph/9305266](#).
- 11018 [154] H1 Collaboration, C. Adloff et al., *Measurement of inclusive jet cross-sections in photoproduction at HERA*, Eur. Phys.
11019 J. **C29** (2003) 497–513, [arXiv:hep-ex/0302034](#).
- 11020 [155] S. Frixione and G. Ridolfi, *Jet photoproduction at HERA*, Nucl. Phys. **B507** (1997) 315–333, [arXiv:hep-ph/9707345](#).
- 11021 [156] V. M. Budnev, I. F. Ginzburg, G. V. Meledin, and V. G. Serbo, *The Two photon particle production mechanism.*
11022 *Physical problems. Applications. Equivalent photon approximation*, Phys. Rept. **15** (1975) 181–281.
- 11023 [157] T. H. Bauer, R. D. Spital, D. R. Yennie, and F. M. Pipkin, *The Hadronic Properties of the Photon in High-Energy*
11024 *Interactions*, Rev. Mod. Phys. **50** (1978) 261.
- 11025 [158] J. M. Butterworth and M. Wing, *High energy photoproduction*, Rept. Prog. Phys. **68** (2005) 2773–2828,
11026 [arXiv:hep-ex/0509018](#).
- 11027 [159] L. Frankfurt, V. Guzey, M. McDermott, and M. Strikman, *Revealing the black body regime of small x DIS through final*
11028 *state signals*, Phys. Rev. Lett. **87** (2001) 192301, [arXiv:hep-ph/0104154](#).
- 11029 [160] T. C. Rogers and M. I. Strikman, *Hadronic interactions of ultra-high energy photons with protons and light nuclei in*
11030 *the dipole picture*, J. Phys. **G32** (2006) 2041–2063, [arXiv:hep-ph/0512311](#).
- 11031 [161] ZEUS Collaboration, S. Chekanov et al., *Measurement of the photon proton total cross section at a center-of-mass*
11032 *energy of 209-GeV at HERA*, Nucl. Phys. **B627** (2002) 3–28, [arXiv:hep-ex/0202034](#).
- 11033 [162] H1 Collaboration, S. Aid et al., *Measurement of the total photon-proton cross-section and its decomposition at 200-GeV*
11034 *center-of-mass energy*, Z. Phys. **C69** (1995) 27–38, [arXiv:hep-ex/9509001](#).
- 11035 [163] G. M. Vereshkov, O. D. Lalakulich, Y. F. Novoseltsev, and R. V. Novoseltseva, *Total cross section for photon nucleon*
11036 *interaction in the energy range $\sqrt{s} = 40\text{-GeV} - 250\text{-GeV}$* , Phys. Atom. Nucl. **66** (2003) 565–574.
- 11037 [164] ZEUS Collaboration, *Measurement of the energy dependence of the total photon-proton cross section at HERA*,
11038 Phys.Lett. **B697** (2011) 184–193, [arXiv:1011.1652 \[hep-ex\]](#). * Temporary entry *.
- 11039 [165] R. M. Godbole, A. Grau, G. Pancheri, and Y. N. Srivastava, *Total photoproduction cross-section at very high energy*,
11040 Eur. Phys. J. **C63** (2009) 69–85, [arXiv:0812.1065 \[hep-ph\]](#).
- 11041 [166] M. M. Block and F. Halzen, *Evidence for the saturation of the Froissart bound*, Phys. Rev. **D70** (2004) 091901,
11042 [arXiv:hep-ph/0405174](#).
- 11043 [167] M. M. Block and F. Halzen, *New evidence for the saturation of the Froissart bound*, Phys. Rev. **D72** (2005) 036006,
11044 [arXiv:hep-ph/0506031](#).
- 11045 [168] M. M. Block, E. M. Gregores, F. Halzen, and G. Pancheri, *Photon - proton and photon-photon scattering from nucleon-*
11046 *nucleon forward amplitudes*, Phys. Rev. **D60** (1999) 054024, [arXiv:hep-ph/9809403](#).
- 11047 [169] H. Flacher, M. Goebel, J. Haller, A. Hocker, K. Monig, et al., *Gfitter - Revisiting the Global Electroweak Fit of the*
11048 *Standard Model and Beyond*, Eur.Phys.J. **C60** (2009, see <http://gfitter.desy.de/>) 543–583, [arXiv:0811.0009](#)
11049 [\[hep-ph\]](#).
- 11050 [170] J. Erler, *The Mass of the Higgs Boson in the Standard Electroweak Model*, Phys.Rev. **D81** (2010) 051301,
11051 [arXiv:1002.1320 \[hep-ph\]](#).
- 11052 [171] P. Gambino, *The top priority: Precision electroweak physics from low to high energy*, Int. J. Mod. Phys. **A19** (2004)
11053 808–820, [arXiv:hep-ph/0311257](#).
- 11054 [172] M. Davier, A. Hoecker, B. Malaescu, and Z. Zhang, *Reevaluation of the Hadronic Contributions to the Muon $g-2$ and to*
11055 *$\alpha(MZ)$* , Eur.Phys.J. **C71** (2011) 1515, [arXiv:1010.4180 \[hep-ph\]](#).
- 11056 [173] S. Haywood, P. Hobson, W. Hollik, Z. Kunszt, G. Azuelos, et al., *Electroweak physics, hep-ph/0003275* ,
11057 [arXiv:hep-ph/0003275 \[hep-ph\]](#).
- 11058 [174] K. Rabbertz, *QCD and Electroweak Physics at LHC*, PoS **RADCOR2009** (2010) 016, [arXiv:1002.3628 \[hep-ph\]](#).
- 11059 [175] S. <http://www.jlab.org/qweak/>, , .

- 11060 [176] S. <http://hallaweb.jlab.org/12GeV/Moller/>, , .
- 11061 [177] R. Cashmore, E. Elsen, B. A. Kniehl, and H. Spiesberger, *Electroweak physics at HERA: Introduction and summary*,
11062 [arXiv:hep-ph/9610251](https://arxiv.org/abs/hep-ph/9610251) [[hep-ph](#)].
- 11063 [178] H1 and ZEUS Collaborations, Z. Zhang, *Electroweak and beyond the Standard Model results from HERA*,
11064 *Nucl.Phys.Proc.Suppl.* **191** (2009) 271–280, [arXiv:0812.4662](https://arxiv.org/abs/0812.4662) [[hep-ex](#)].
- 11065 [179] H1 Collaboration, A. Aktas et al., *A Determination of electroweak parameters at HERA*, *Phys.Lett.* **B632** (2006)
11066 35–42, [arXiv:hep-ex/0507080](https://arxiv.org/abs/hep-ex/0507080) [[hep-ex](#)].
- 11067 [180] H1 Collaboration, Z.-Q. Zhang, *Combined electroweak and QCD fits including NC and CC data with polarised electron
11068 beam at HERA-2*, *PoS DIS2010* (2010) 056.
- 11069 [181] D0 Collaboration, V. Abazov et al., *Measurement of $\sin^2 \theta_{\text{eff}}^{\ell}$ and Z-light quark couplings using the forward-backward
11070 charge asymmetry in $p\bar{p} \rightarrow Z/\gamma^* \rightarrow e^+e^-$ events with $\mathcal{L} = 5.0 \text{ fb}^{-1}$ at $\sqrt{s} = 1.96 \text{ TeV}$* , *Phys.Rev.D* (2011) ,
11071 [arXiv:1104.4590](https://arxiv.org/abs/1104.4590) [[hep-ex](#)]. * Temporary entry *.
- 11072 [182] E. Salvioni, A. Strumia, G. Villadoro, and F. Zwirner, *Non-universal minimal Z' models: present bounds and early
11073 LHC reach*, *JHEP* **1003** (2010) 010, [arXiv:0911.1450](https://arxiv.org/abs/0911.1450) [[hep-ph](#)].
- 11074 [183] J. Erler and P. Langacker, *Indications for an extra neutral gauge boson in electroweak precision data*, *Phys.Rev.Lett.*
11075 **84** (2000) 212–215, [arXiv:hep-ph/9910315](https://arxiv.org/abs/hep-ph/9910315) [[hep-ph](#)].
- 11076 [184] R. Barbier, C. Berat, M. Besancon, M. Chemtob, A. Deandrea, et al., *R-parity violating supersymmetry*, *Phys.Rept.*
11077 **420** (2005) 1–202, [arXiv:hep-ph/0406039](https://arxiv.org/abs/hep-ph/0406039) [[hep-ph](#)].
- 11078 [185] M. Carpentier and S. Davidson, *Constraints on two-lepton, two quark operators*, *Eur.Phys.J.* **C70** (2010), and refs.
11079 therein) 1071–1090, [arXiv:1008.0280](https://arxiv.org/abs/1008.0280) [[hep-ph](#)].
- 11080 [186] J. Erler, A. Kurylov, and M. J. Ramsey-Musolf, *The Weak charge of the proton and new physics*, *Phys.Rev.* **D68**
11081 (2003) 016006, [arXiv:hep-ph/0302149](https://arxiv.org/abs/hep-ph/0302149) [[hep-ph](#)].
- 11082 [187] C. Prescott, W. Atwood, R. Cottrell, H. DeStaebler, E. L. Garwin, et al., *Further Measurements of Parity
11083 Nonconservation in Inelastic electron Scattering*, *Phys.Lett.* **B84** (1979) 524.
- 11084 [188] E. A. Paschos and L. Wolfenstein, *Tests for neutral currents in neutrino reactions*, *Phys. Rev.* **D7** (1973) 91–95.
- 11085 [189] J. Blumlein, M. Klein, and T. Riemann, *Testing the electroweak standard model at HERA*, .
- 11086 [190] A. Czarnecki and W. J. Marciano, *Polarized Moller scattering asymmetries*, *Int.J.Mod.Phys.* **A15** (2000) 2365–2376,
11087 [arXiv:hep-ph/0003049](https://arxiv.org/abs/hep-ph/0003049) [[hep-ph](#)].
- 11088 [191] T. Regge, *Introduction to complex orbital momenta*, *Nuovo Cim.* **14** (1959) 951.
- 11089 [192] V. N. Gribov, *A Reggeon diagram technique*, *Sov. Phys. JETP* **26** (1968) 414–422.
- 11090 [193] H. D. I. Abarbanel, J. B. Bronzan, R. L. Sugar, and A. R. White, *Reggeon Field Theory: Formulation and Use*, *Phys.*
11091 *Rept.* **21** (1975) 119–182.
- 11092 [194] J. C. Collins, D. E. Soper, and G. F. Sterman, *Factorization of Hard Processes in QCD*, *Adv. Ser. Direct. High Energy
11093 Phys.* **5** (1988) 1–91, [arXiv:hep-ph/0409313](https://arxiv.org/abs/hep-ph/0409313).
- 11094 [195] L. V. Gribov, E. M. Levin, and M. G. Ryskin, *Semihard Processes in QCD*, *Phys. Rept.* **100** (1983) 1–150.
- 11095 [196] A. H. Mueller, *Small x Behavior and Parton Saturation: A QCD Model*, *Nucl. Phys.* **B335** (1990) 115.
- 11096 [197] J. Jalilian-Marian, A. Kovner, A. Leonidov, and H. Weigert, *The Wilson renormalization group for low x physics:
11097 Towards the high density regime*, *Phys. Rev.* **D59** (1999) 014014, [arXiv:hep-ph/9706377](https://arxiv.org/abs/hep-ph/9706377).
- 11098 [198] I. Balitsky, *Operator expansion for high-energy scattering*, *Nucl. Phys.* **B463** (1996) 99–160, [arXiv:hep-ph/9509348](https://arxiv.org/abs/hep-ph/9509348).
- 11099 [199] Y. V. Kovchegov, *Small-x F2 structure function of a nucleus including multiple pomeron exchanges*, *Phys. Rev.* **D60**
11100 (1999) 034008, [arXiv:hep-ph/9901281](https://arxiv.org/abs/hep-ph/9901281).
- 11101 [200] M. Froissart, *Asymptotic behavior and subtractions in the Mandelstam representation*, *Phys. Rev.* **123** (1961)
11102 1053–1057.
- 11103 [201] A. Martin, *Unitarity and high-energy behavior of scattering amplitudes*, *Phys. Rev.* **129** (1963) 1432–1436.
- 11104 [202] L. Frankfurt, V. Guzey, M. McDermott, and M. Strikman, *Electron nucleus collisions at THERA*,
11105 [arXiv:hep-ph/0104252](https://arxiv.org/abs/hep-ph/0104252) [[hep-ph](#)].
- 11106 [203] E. A. Kuraev, L. N. Lipatov, and V. S. Fadin, *The Pomernanchuk Singularity in Nonabelian Gauge Theories*, *Sov. Phys.*
11107 *JETP* **45** (1977) 199–204.
- 11108 [204] I. I. Balitsky and L. N. Lipatov, *The Pomernanchuk Singularity in Quantum Chromodynamics*, *Sov. J. Nucl. Phys.* **28**
11109 (1978) 822–829.
- 11110 [205] S. Catani and F. Hautmann, *High-energy factorization and small x deep inelastic scattering beyond leading order*, *Nucl.*
11111 *Phys.* **B427** (1994) 475–524, [arXiv:hep-ph/9405388](https://arxiv.org/abs/hep-ph/9405388).

- 11112 [206] F. Caola, S. Forte, and J. Rojo, *Deviations from NLO QCD evolution in inclusive HERA data*, Phys. Lett. **B686**
11113 (2010) 127–135, [arXiv:0910.3143 \[hep-ph\]](#).
- 11114 [207] V. S. Fadin and L. N. Lipatov, *BFKL pomeron in the next-to-leading approximation*, Phys. Lett. **B429** (1998) 127–134,
11115 [arXiv:hep-ph/9802290](#).
- 11116 [208] M. Ciafaloni and G. Camici, *Energy scale(s) and next-to-leading BFKL equation*, Phys. Lett. **B430** (1998) 349–354,
11117 [arXiv:hep-ph/9803389](#).
- 11118 [209] G. Altarelli, R. D. Ball, and S. Forte, *An anomalous dimension for small x evolution*, Nucl. Phys. **B674** (2003)
11119 459–483, [arXiv:hep-ph/0306156](#).
- 11120 [210] G. Altarelli, R. D. Ball, and S. Forte, *Perturbatively stable resummed small x evolution kernels*, Nucl. Phys. **B742**
11121 (2006) 1–40, [arXiv:hep-ph/0512237](#).
- 11122 [211] G. Altarelli, R. D. Ball, and S. Forte, *Small x Resummation with Quarks: Deep-Inelastic Scattering*, Nucl. Phys. **B799**
11123 (2008) 199–240, [arXiv:0802.0032 \[hep-ph\]](#).
- 11124 [212] M. Ciafaloni, D. Colferai, G. P. Salam, and A. M. Stasto, *Renormalisation group improved small- x Green's function*,
11125 Phys. Rev. **D68** (2003) 114003, [arXiv:hep-ph/0307188](#).
- 11126 [213] M. Ciafaloni, D. Colferai, G. P. Salam, and A. M. Stasto, *The gluon splitting function at moderately small x* , Phys.
11127 Lett. **B587** (2004) 87–94, [arXiv:hep-ph/0311325](#).
- 11128 [214] M. Ciafaloni, D. Colferai, G. P. Salam, and A. M. Stasto, *A matrix formulation for small- x singlet evolution*, JHEP **08**
11129 (2007) 046, [arXiv:0707.1453 \[hep-ph\]](#).
- 11130 [215] V. N. Gribov, *Glauber corrections and the interaction between high- energy hadrons and nuclei*, Sov. Phys. JETP **29**
11131 (1969) 483–487.
- 11132 [216] N. Armesto, A. B. Kaidalov, C. A. Salgado, and K. Tywoniuk, *A unitarized model of inclusive and diffractive DIS with*
11133 *Q^2 -evolution*, Phys. Rev. **D81** (2010) 074002, [arXiv:1001.3021 \[hep-ph\]](#).
- 11134 [217] N. Armesto, A. B. Kaidalov, C. A. Salgado, and K. Tywoniuk, *Nuclear shadowing in Glauber-Gribov theory with Q^2 -*
11135 *evolution*, Eur. Phys. J. **C68** (2010) 447–457, [arXiv:1003.2947 \[hep-ph\]](#).
- 11136 [218] A. H. Mueller and J.-w. Qiu, *Gluon Recombination and Shadowing at Small Values of x* , Nucl. Phys. **B268** (1986) 427.
- 11137 [219] J. Bartels and M. Wusthoff, *The Triple Regge limit of diffractive dissociation in deep inelastic scattering*, Z. Phys. **C66**
11138 (1995) 157–180.
- 11139 [220] L. D. McLerran and R. Venugopalan, *Computing quark and gluon distribution functions for very large nuclei*, Phys.
11140 Rev. **D49** (1994) 2233–2241, [arXiv:hep-ph/9309289](#).
- 11141 [221] L. D. McLerran and R. Venugopalan, *Gluon distribution functions for very large nuclei at small transverse momentum*,
11142 Phys. Rev. **D49** (1994) 3352–3355, [arXiv:hep-ph/9311205](#).
- 11143 [222] L. D. McLerran and R. Venugopalan, *Green's functions in the color field of a large nucleus*, Phys. Rev. **D50** (1994)
11144 2225–2233, [arXiv:hep-ph/9402335](#).
- 11145 [223] J. Jalilian-Marian, A. Kovner, and H. Weigert, *The Wilson renormalization group for low x physics: Gluon evolution at*
11146 *finite parton density*, Phys. Rev. **D59** (1999) 014015, [arXiv:hep-ph/9709432](#).
- 11147 [224] A. Kovner, J. G. Milhano, and H. Weigert, *Relating different approaches to nonlinear QCD evolution at finite gluon*
11148 *density*, Phys. Rev. **D62** (2000) 114005, [arXiv:hep-ph/0004014](#).
- 11149 [225] H. Weigert, *Unitarity at small Bjorken x* , Nucl. Phys. **A703** (2002) 823–860, [arXiv:hep-ph/0004044](#).
- 11150 [226] E. Iancu, A. Leonidov, and L. D. McLerran, *Nonlinear gluon evolution in the color glass condensate. I*, Nucl. Phys.
11151 **A692** (2001) 583–645, [arXiv:hep-ph/0011241](#).
- 11152 [227] E. Ferreiro, E. Iancu, A. Leonidov, and L. McLerran, *Nonlinear gluon evolution in the color glass condensate. II*, Nucl.
11153 Phys. **A703** (2002) 489–538, [arXiv:hep-ph/0109115](#).
- 11154 [228] T. Altinoluk, A. Kovner, M. Lublinsky, and J. Peressutti, *QCD Reggeon Field Theory for every day: Pomeron loops*
11155 *included*, JHEP **03** (2009) 109, [arXiv:0901.2559 \[hep-ph\]](#).
- 11156 [229] F. Gelis, E. Iancu, J. Jalilian-Marian, and R. Venugopalan, *The Color Glass Condensate*, Ann.Rev.Nucl.Part.Sci. **60**
11157 (2010) 463–489, [arXiv:1002.0333 \[hep-ph\]](#).
- 11158 [230] Y. V. Kovchegov and H. Weigert, *Triumvirate of Running Couplings in Small- x Evolution*, Nucl.Phys. **A784** (2007)
11159 188–226, [arXiv:hep-ph/0609090 \[hep-ph\]](#).
- 11160 [231] I. Balitsky and G. A. Chirilli, *Next-to-leading order evolution of color dipoles*, Phys. Rev. **D77** (2008) 014019,
11161 [arXiv:0710.4330 \[hep-ph\]](#).
- 11162 [232] E. Iancu, A. Mueller, and S. Munier, *Universal behavior of QCD amplitudes at high energy from general tools of*
11163 *statistical physics*, Phys.Lett. **B606** (2005) 342–350, [arXiv:hep-ph/0410018 \[hep-ph\]](#).
- 11164 [233] Y. V. Kovchegov, J. Kuokkanen, K. Rummukainen, and H. Weigert, *Subleading- $N(c)$ corrections in non-linear small- x*
11165 *evolution*, Nucl.Phys. **A823** (2009) 47–82, [arXiv:0812.3238 \[hep-ph\]](#).

- 11166 [234] A. Dumitru and J. Jalilian-Marian, *Forward dijets in high-energy collisions: Evolution of QCD n-point functions beyond the dipole approximation*, Phys.Rev. **D82** (2010) 074023, [arXiv:1008.0480](#) [hep-ph].
- 11167
- 11168 [235] C. Marquet and H. Weigert, *New observables to test the Color Glass Condensate beyond the large- N_c limit*, Nucl.Phys. **A843** (2010) 68–97, [arXiv:1003.0813](#) [hep-ph].
- 11169
- 11170 [236] Y. Hatta, E. Iancu, C. Marquet, G. Soyez, and D. Triantafyllopoulos, *Diffusive scaling and the high-energy limit of deep inelastic scattering in QCD at large $N(c)$* , Nucl.Phys. **A773** (2006) 95–155, [arXiv:hep-ph/0601150](#) [hep-ph].
- 11171
- 11172 [237] S. Munier, *Quantum chromodynamics at high energy and statistical physics*, Phys.Rept. **473** (2009) 1–49, [arXiv:0901.2823](#) [hep-ph]. * Temporary entry *.
- 11173
- 11174 [238] J. C. Collins, *Proof of factorization for diffractive hard scattering*, Phys. Rev. **D57** (1998) 3051–3056, [arXiv:hep-ph/9709499](#).
- 11175
- 11176 [239] F. Low, *A Model of the Bare Pomeron*, Phys. Rev. **D12** (1975) 163.
- 11177 [240] S. Nussinov, *Colored Quark Version of Some Hadronic Puzzles*, Phys. Rev. Lett. **34** (1975) 1286.
- 11178 [241] K. J. Golec-Biernat and M. Wusthoff, *Saturation effects in deep inelastic scattering at low Q^{*2} and its implications on diffraction*, Phys. Rev. **D59** (1998) 014017, [arXiv:hep-ph/9807513](#).
- 11179
- 11180 [242] K. J. Golec-Biernat and M. Wusthoff, *Saturation in diffractive deep inelastic scattering*, Phys. Rev. **D60** (1999) 114023, [arXiv:hep-ph/9903358](#).
- 11181
- 11182 [243] N. Armesto, *Nuclear shadowing*, J. Phys. **G32** (2006) R367–R394, [arXiv:hep-ph/0604108](#).
- 11183 [244] L. Frankfurt, M. Strikman, and C. Weiss, *Small- x physics: From HERA to LHC and beyond*, Ann. Rev. Nucl. Part. Sci. **55** (2005) 403–465, [arXiv:hep-ph/0507286](#).
- 11184
- 11185 [245] J. Albacete, J. Milhano, P. Quiroga-Arias, and J. Rojo, *Linear vs non-linear QCD evolution: from HERA data to LHC phenomenology*, [arXiv:1203.1043](#) [hep-ph].
- 11186
- 11187 [246] E. Iancu, K. Itakura, and S. Munier, *Saturation and BFKL dynamics in the HERA data at small x* , Phys. Lett. **B590** (2004) 199–208, [arXiv:hep-ph/0310338](#).
- 11188
- 11189 [247] J. R. Forshaw and G. Shaw, *Gluon saturation in the colour dipole model?*, JHEP **12** (2004) 052, [arXiv:hep-ph/0411337](#).
- 11190 [248] A. M. Stasto, K. J. Golec-Biernat, and J. Kwiecinski, *Geometric scaling for the total $\gamma^* p$ cross-section in the low x region*, Phys. Rev. Lett. **86** (2001) 596–599, [arXiv:hep-ph/0007192](#).
- 11191
- 11192 [249] N. Armesto, C. A. Salgado, and U. A. Wiedemann, *Relating high-energy lepton hadron, proton nucleus and nucleus nucleus collisions through geometric scaling*, Phys. Rev. Lett. **94** (2005) 022002, [arXiv:hep-ph/0407018](#).
- 11193
- 11194 [250] C. Marquet and L. Schoeffel, *Geometric scaling in diffractive deep inelastic scattering*, Phys. Lett. **B639** (2006) 471–477, [arXiv:hep-ph/0606079](#).
- 11195
- 11196 [251] V. Goncalves and M. Machado, *Geometric scaling in inclusive charm production*, Phys.Rev.Lett. **91** (2003) 202002, [arXiv:hep-ph/0307090](#) [hep-ph].
- 11197
- 11198 [252] L. McLerran and M. Praszalowicz, *Saturation and Scaling of Multiplicity, Mean p_T and p_T Distributions from 200 GeV to \sqrt{s} at 7 TeV*, Acta Phys.Polon. **B41** (2010) 1917–1926, [arXiv:1006.4293](#) [hep-ph].
- 11199
- 11200 [253] F. Caola and S. Forte, *Geometric Scaling from GLAP evolution*, Phys. Rev. Lett. **101** (2008) 022001, [arXiv:0802.1878](#) [hep-ph].
- 11201
- 11202 [254] N. N. Nikolaev and B. G. Zakharov, *Colour transparency and scaling properties of nuclear shadowing in deep inelastic scattering*, Z. Phys. **C49** (1991) 607–618.
- 11203
- 11204 [255] N. Nikolaev and B. G. Zakharov, *Pomeron structure function and diffraction dissociation of virtual photons in perturbative QCD*, Z. Phys. **C53** (1992) 331–346.
- 11205
- 11206 [256] A. H. Mueller and B. Patel, *Single and double BFKL pomeron exchange and a dipole picture of high-energy hard processes*, Nucl. Phys. **B425** (1994) 471–488, [arXiv:hep-ph/9403256](#).
- 11207
- 11208 [257] A. H. Mueller, *Unitarity and the BFKL pomeron*, Nucl. Phys. **B437** (1995) 107–126, [arXiv:hep-ph/9408245](#).
- 11209 [258] M. L. Good and W. D. Walker, *Diffraction dissociation of beam particles*, Phys. Rev. **120** (1960) 1857–1860.
- 11210 [259] A. H. Mueller, *Parton saturation: An overview*, [arXiv:hep-ph/0111244](#).
- 11211 [260] J. Bartels, K. J. Golec-Biernat, and H. Kowalski, *A modification of the saturation model: DGLAP evolution*, Phys. Rev. **D66** (2002) 014001, [arXiv:hep-ph/0203258](#).
- 11212
- 11213 [261] H. Kowalski and D. Teaney, *An impact parameter dipole saturation model*, Phys. Rev. **D68** (2003) 114005, [arXiv:hep-ph/0304189](#).
- 11214
- 11215 [262] H. Kowalski, L. Motyka, and G. Watt, *Exclusive diffractive processes at HERA within the dipole picture*, Phys. Rev. **D74** (2006) 074016, [arXiv:hep-ph/0606272](#).
- 11216
- 11217 [263] A. D. Martin, R. G. Roberts, W. J. Stirling, and R. S. Thorne, *Uncertainties of predictions from parton distributions. I: Experimental errors. ((T))*, Eur. Phys. J. **C28** (2003) 455–473, [arXiv:hep-ph/0211080](#).
- 11218

- 11219 [264] A. D. Martin, W. J. Stirling, R. S. Thorne, and G. Watt, *Update of Parton Distributions at NNLO*, Phys. Lett. **B652**
11220 (2007) 292–299, [arXiv:0706.0459 \[hep-ph\]](#).
- 11221 [265] P. M. Nadolsky et al., *Implications of CTEQ global analysis for collider observables*, Phys. Rev. **D78** (2008) 013004,
11222 [arXiv:0802.0007 \[hep-ph\]](#).
- 11223 [266] G. Watt, A. D. Martin, W. J. Stirling, and R. S. Thorne, *Recent Progress in Global PDF Analysis*, [arXiv:0806.4890](#)
11224 [\[hep-ph\]](#).
- 11225 [267] A. Martin, W. Stirling, R. Thorne, and G. Watt, *Parton distributions for the LHC*, Eur.Phys.J. **C63** (2009) 189–285,
11226 [arXiv:0901.0002 \[hep-ph\]](#).
- 11227 [268] H.-L. Lai, J. Huston, Z. Li, P. Nadolsky, J. Pumplin, et al., *Uncertainty induced by QCD coupling in the CTEQ global*
11228 *analysis of parton distributions*, Phys.Rev. **D82** (2010) 054021, [arXiv:1004.4624 \[hep-ph\]](#).
- 11229 [269] R. D. Ball et al., *A first unbiased global NLO determination of parton distributions and their uncertainties*, Nucl. Phys.
11230 **B838** (2010) 136–206, [arXiv:1002.4407 \[hep-ph\]](#).
- 11231 [270] J. R. Forshaw, R. Sandapen, and G. Shaw, *Further success of the colour dipole model*, JHEP **11** (2006) 025,
11232 [arXiv:hep-ph/0608161](#).
- 11233 [271] H.-L. Lai, M. Guzzi, J. Huston, Z. Li, P. M. Nadolsky, et al., *New parton distributions for collider physics*, Phys.Rev.
11234 **D82** (2010) 074024, [arXiv:1007.2241 \[hep-ph\]](#).
- 11235 [272] R. D. Ball and R. K. Ellis, *Heavy quark production at high-energy*, JHEP **05** (2001) 053, [arXiv:hep-ph/0101199](#).
- 11236 [273] S. Marzani, R. D. Ball, V. Del Duca, S. Forte, and A. Vicini, *Higgs production via gluon-gluon fusion with finite top*
11237 *mass beyond next-to-leading order*, Nucl. Phys. **B800** (2008) 127–145, [arXiv:0801.2544 \[hep-ph\]](#).
- 11238 [274] S. Marzani, R. D. Ball, V. Del Duca, S. Forte, and A. Vicini, *Finite-top-mass effects in NNLO Higgs production*, Nucl.
11239 Phys. Proc. Suppl. **186** (2009) 98–101, [arXiv:0809.4934 \[hep-ph\]](#).
- 11240 [275] S. Marzani and R. D. Ball, *High Energy Resummation of Drell-Yan Processes*, Nucl. Phys. **B814** (2009) 246–264,
11241 [arXiv:0812.3602 \[hep-ph\]](#).
- 11242 [276] S. Marzani and R. D. Ball, *Drell-Yan processes in the high-energy limit*, [arXiv:0906.4729 \[hep-ph\]](#).
- 11243 [277] G. Diana, *High-energy resummation in direct photon production*, Nucl. Phys. **B824** (2010) 154–167, [arXiv:0906.4159](#)
11244 [\[hep-ph\]](#).
- 11245 [278] G. Diana, J. Rojo, and R. D. Ball, *High energy resummation of direct photon production at hadronic colliders*,
11246 Phys.Lett. **B693** (2010) 430–437, [arXiv:1006.4250 \[hep-ph\]](#).
- 11247 [279] S. Forte, G. Altarelli, and R. D. Ball, *Can we trust small x resummation?*, Nucl. Phys. Proc. Suppl. **191** (2009) 64–75,
11248 [arXiv:0901.1294 \[hep-ph\]](#).
- 11249 [280] M. Dittmar et al., *Parton Distributions*, [arXiv:0901.2504 \[hep-ph\]](#).
- 11250 [281] J. Rojo, G. Altarelli, R. D. Ball, and S. Forte, *Towards small x resummed DIS phenomenology*, [arXiv:0907.0443](#)
11251 [\[hep-ph\]](#).
- 11252 [282] J. Rojo and F. Caola, *Parton distributions and small- x QCD at the Large Hadron Electron Collider*, [arXiv:0906.2079](#)
11253 [\[hep-ph\]](#).
- 11254 [283] C. Salgado, J. Alvarez-Muniz, F. Arleo, N. Armesto, M. Botje, et al., *Proton-Nucleus Collisions at the LHC: Scientific*
11255 *Opportunities and Requirements*, J.Phys.G **G39** (2012) 015010, [arXiv:1105.3919 \[hep-ph\]](#).
- 11256 [284] D. G. d’Enterria, *Quarkonia photoproduction at nucleus colliders*, Nucl.Phys.Proc.Suppl. **184** (2008) 158–162,
11257 [arXiv:0711.1123 \[nucl-ex\]](#).
- 11258 [285] D. d’Enterria, *Forward jets physics in ATLAS, CMS and LHCb*, [arXiv:0911.1273 \[hep-ex\]](#).
- 11259 [286] R. Ichou and D. d’Enterria, *Sensitivity of isolated photon production at TeV hadron colliders to the gluon distribution*
11260 *in the proton*, Phys.Rev. **D82** (2010) 014015, [arXiv:1005.4529 \[hep-ph\]](#).
- 11261 [287] LHCb Collaboration, F. de Lorenzi et al. Proceedings of DIS2010.
- 11262 [288] J. M. Jowett, *The LHC as a Nucleus-Nucleus Collider*, J.Phys.G **G35** (2008) 104028, [arXiv:0807.1397 \[nucl-ex\]](#). *
11263 Temporary entry *.
- 11264 [289] P. Quiroga-Arias, J. G. Milhano, and U. A. Wiedemann, *Testing nuclear parton distributions with pA collisions at the*
11265 *TeV scale*, Phys.Rev. **C82** (2010) 034903, [arXiv:1002.2537 \[hep-ph\]](#).
- 11266 [290] K. Eskola, V. Kolhinen, and R. Vogt, *Obtaining the nuclear gluon distribution from heavy quark decays to lepton pairs*
11267 *in pA collisions*, Nucl.Phys. **A696** (2001) 729–746, [arXiv:hep-ph/0104124 \[hep-ph\]](#).
- 11268 [291] F. Arleo and T. Gousset, *Measuring gluon shadowing with prompt photons at RHIC and LHC*, Phys.Lett. **B660** (2008)
11269 181–187, [arXiv:0707.2944 \[hep-ph\]](#).
- 11270 [292] H. Paukkunen and C. A. Salgado, *Constraints for the nuclear parton distributions from Z and W production at the*
11271 *LHC*, JHEP **1103** (2011) 071, [arXiv:1010.5392 \[hep-ph\]](#).

- 11272 [293] A. Baltz, G. Baur, D. d’Enterria, L. Frankfurt, F. Gelis, et al., *The Physics of Ultrapерipheral Collisions at the LHC*,
11273 Phys.Rept. **458** (2008) 1–171, arXiv:0706.3356 [nucl-ex].
- 11274 [294] BRAHMS Collaboration, I. Arsene et al., *On the evolution of the nuclear modification factors with rapidity and
11275 centrality in $d + Au$ collisions at $s(NN)^{1/2} = 200\text{-GeV}$* , Phys.Rev.Lett. **93** (2004) 242303, arXiv:nucl-ex/0403005
11276 [nucl-ex].
- 11277 [295] B. Kopeliovich, J. Nemchik, I. Potashnikova, M. Johnson, and I. Schmidt, *Breakdown of QCD factorization at large
11278 Feynman x* , Phys.Rev. **C72** (2005) 054606, arXiv:hep-ph/0501260 [hep-ph].
- 11279 [296] STAR Collaboration, E. Braidot, *Suppression of Forward Pion Correlations in $d+Au$ Interactions at STAR*,
11280 arXiv:1005.2378 [hep-ph].
- 11281 [297] L. Frankfurt and M. Strikman, *Energy losses in the black disc regime and correlation effects in the STAR forward pion
11282 production in $d Au$ collisions*, Phys.Lett. **B645** (2007) 412–421, arXiv:nucl-th/0603049 [nucl-th].
- 11283 [298] J. L. Albacete and C. Marquet, *Azimuthal correlations of forward di-hadrons in $d+Au$ collisions at RHIC in the Color
11284 Glass Condensate*, Phys.Rev.Lett. **105** (2010) 162301, arXiv:1005.4065 [hep-ph].
- 11285 [299] PHENIX Collaboration, A. Adare et al., *Suppression of back-to-back hadron pairs at forward rapidity in $d+Au$
11286 Collisions at $\sqrt{s_{NN}} = 200\text{ GeV}$* , arXiv:1105.5112 [nucl-ex]. * Temporary entry *.
- 11287 [300] A. Stasto, B.-W. Xiao, and F. Yuan, *Back-to-Back Correlations of Di-hadrons in dAu Collisions at RHIC*,
11288 arXiv:1109.1817 [hep-ph].
- 11289 [301] F. Arleo et al., *Photon physics in heavy ion collisions at the LHC*, arXiv:hep-ph/0311131.
- 11290 [302] STAR Collaboration, B. Abelev et al., *Three-particle coincidence of the long range pseudorapidity correlation in high
11291 energy nucleus-nucleus collisions*, Phys.Rev.Lett. **105** (2010) 022301, arXiv:0912.3977 [hep-ex].
- 11292 [303] CMS Collaboration, V. Khachatryan et al., *Observation of Long-Range Near-Side Angular Correlations in
11293 Proton-Proton Collisions at the LHC*, JHEP **1009** (2010) 091, arXiv:1009.4122 [hep-ex].
- 11294 [304] CMS Collaboration, S. Chatrchyan et al., *Long-range and short-range dihadron angular correlations in central PbPb
11295 collisions at a nucleon-nucleon center of mass energy of 2.76 TeV*, JHEP **1107** (2011) 076, arXiv:1105.2438
11296 [nucl-ex].
- 11297 [305] A. Dumitru, K. Dusling, F. Gelis, J. Jalilian-Marian, T. Lappi, et al., *The Ridge in proton-proton collisions at the
11298 LHC*, Phys.Lett. **B697** (2011) 21–25, arXiv:1009.5295 [hep-ph].
- 11299 [306] N. Armesto, *Predictions for the heavy-ion programme at the Large Hadron Collider*, arXiv:0903.1330 [hep-ph].
- 11300 [307] ALICE Collaboration, K. Aamodt et al., *Charged-particle multiplicity density at mid-rapidity in central Pb-Pb collisions
11301 at $\sqrt{s_{NN}} = 2.76\text{ TeV}$* , Phys.Rev.Lett. **105** (2010) 252301, arXiv:1011.3916 [nucl-ex]. * Temporary entry *.
- 11302 [308] ALICE Collaboration, J. Nystrand, *Photon-Induced Physics with Heavy-Ion Beams in ALICE*, Nucl.Phys.Proc.Suppl.
11303 **179-180** (2008) 156–161, arXiv:0807.0366 [nucl-ex].
- 11304 [309] M. Arneodo, *Nuclear effects in structure functions*, Phys. Rept. **240** (1994) 301–393.
- 11305 [310] D. F. Geesaman, K. Saito, and A. W. Thomas, *The nuclear EMC effect*, Ann. Rev. Nucl. Part. Sci. **45** (1995) 337–390.
- 11306 [311] A. Accardi et al., *Hard probes in heavy ion collisions at the lhc: pdfs, shadowing and pa collisions*,
11307 arXiv:hep-ph/0308248.
- 11308 [312] D. de Florian and R. Sassot, *Nuclear parton distributions at next to leading order*, Phys. Rev. **D69** (2004) 074028,
11309 arXiv:hep-ph/0311227.
- 11310 [313] M. Hirai, S. Kumano, and T. H. Nagai, *Determination of nuclear parton distribution functions and their uncertainties
11311 at next-to-leading order*, Phys. Rev. **C76** (2007) 065207, arXiv:0709.3038 [hep-ph].
- 11312 [314] D. de Florian, R. Sassot, M. Stratmann, and P. Zurita, *Global Analysis of Nuclear Parton Distributions*,
11313 arXiv:1112.6324 [hep-ph].
- 11314 [315] V. Guzey and M. Strikman, *Color fluctuation approximation for multiple interactions in leading twist theory of nuclear
11315 shadowing*, Phys. Lett. **B687** (2010) 167–173, arXiv:0908.1149 [hep-ph].
- 11316 [316] K. J. Eskola, V. J. Kolhinen, and C. A. Salgado, *The scale dependent nuclear effects in parton distributions for
11317 practical applications*, Eur. Phys. J. **C9** (1999) 61–68, arXiv:hep-ph/9807297.
- 11318 [317] H. Paukkunen and C. A. Salgado, *Compatibility of neutrino DIS data and global analyses of parton distribution
11319 functions*, JHEP **07** (2010) 032, arXiv:1004.3140 [hep-ph].
- 11320 [318] A. Accardi et al., *Hard probes in heavy ion collisions at the LHC: Jet physics*, arXiv:hep-ph/0310274.
- 11321 [319] M. Bedjidian et al., *Hard probes in heavy ion collisions at the LHC: Heavy flavor physics*, arXiv:hep-ph/0311048.
- 11322 [320] M. Gyulassy and L. McLerran, *New forms of QCD matter discovered at RHIC*, Nucl. Phys. **A750** (2005) 30–63,
11323 arXiv:nucl-th/0405013.
- 11324 [321] D. G. d’Enterria, *Quark-gluon matter*, J. Phys. **G34** (2007) S53–S82, arXiv:nucl-ex/0611012.

- 11325 [322] T. Lappi, *Initial conditions of heavy ion collisions and high energy factorization*, Acta Phys. Polon. **B40** (2009)
11326 1997–2012, arXiv:0904.1670 [hep-ph].
- 11327 [323] A. Accardi, F. Arleo, W. K. Brooks, D. D’Enterria, and V. Muccifora, *Parton Propagation and Fragmentation in QCD*
11328 *Matter*, Riv. Nuovo Cim. **032** (2010) 439–553, arXiv:0907.3534 [nucl-th].
- 11329 [324] ALICE Collaboration, K. Aamodt et al., *Suppression of Charged Particle Production at Large Transverse Momentum*
11330 *in Central Pb–Pb Collisions at $\sqrt{s_{NN}} = 2.76$ TeV*, Phys.Lett. **B696** (2011) 30–39, arXiv:1012.1004 [nucl-ex]. *
11331 Temporary entry *.
- 11332 [325] CMS Collaboration, S. Chatrchyan et al., *Study of high- p_T charged particle suppression in PbPb compared to pp*
11333 *collisions at $\sqrt{s_{NN}}=2.76$ TeV*, arXiv:1202.2554 [nucl-ex].
- 11334 [326] Atlas Collaboration, G. Aad et al., *Observation of a Centrality-Dependent Dijet Asymmetry in Lead-Lead Collisions at*
11335 *$\sqrt{s(NN)}=2.76$ TeV with the ATLAS Detector at the LHC*, Phys.Rev.Lett. **105** (2010) 252303, arXiv:1011.6182
11336 [hep-ex]. * Temporary entry *.
- 11337 [327] CMS Collaboration, S. Chatrchyan et al., *Observation and studies of jet quenching in PbPb collisions at*
11338 *nucleon-nucleon center-of-mass energy = 2.76 TeV*, Phys.Rev. **C84** (2011) 024906, arXiv:1102.1957 [nucl-ex].
- 11339 [328] CMS Collaboration, *Jet momentum dependence of jet quenching in PbPb collisions at $\sqrt{s_{NN}}=2.76$ TeV*,
11340 arXiv:1202.5022 [nucl-ex].
- 11341 [329] NNPDF Collaboration, R. D. Ball et al., *Precision determination of electroweak parameters and the strange content of*
11342 *the proton from neutrino deep-inelastic scattering*, Nucl. Phys. **B823** (2009) 195–233, arXiv:0906.1958 [hep-ph].
- 11343 [330] K. Golec-Biernat and A. M. Stasto, *F_L proton structure function from the unified DGLAP/BFKL approach*, Phys.
11344 Rev. **D80** (2009) 014006, arXiv:0905.1321 [hep-ph].
- 11345 [331] J. L. Albacete, N. Armesto, J. G. Milhano, and C. A. Salgado, *Non-linear QCD meets data: A global analysis of lepton-*
11346 *proton scattering with running coupling BK evolution*, Phys. Rev. **D80** (2009) 034031, arXiv:0902.1112 [hep-ph].
- 11347 [332] The NNPDF Collaboration, R. D. Ball et al., *Reweighting NNPDFs: the W lepton asymmetry*, Nucl.Phys. **B849** (2011)
11348 112–143, arXiv:1012.0836 [hep-ph].
- 11349 [333] NNPDF Collaboration, R. D. Ball et al., *A determination of parton distributions with faithful uncertainty estimation*,
11350 Nucl. Phys. **B809** (2009) 1–63, arXiv:0808.1231 [hep-ph].
- 11351 [334] J. Jowett. Private communication.
- 11352 [335] N. Armesto, *A simple model for nuclear structure functions at small x in the dipole picture*, Eur. Phys. J. **C26** (2002)
11353 35–43, arXiv:hep-ph/0206017.
- 11354 [336] PHENIX Collaboration, S. S. Adler et al., *Centrality dependence of pi0 and eta production at large transverse*
11355 *momentum in $s(NN)^{1/2} = 200$ -GeV d + Au collisions*, Phys. Rev. Lett. **98** (2007) 172302,
11356 arXiv:nucl-ex/0610036.
- 11357 [337] S. J. Brodsky, I. Schmidt, and J.-J. Yang, *Nuclear antishadowing in neutrino deep inelastic scattering*, Phys.Rev. **D70**
11358 (2004) 116003, arXiv:hep-ph/0409279 [hep-ph].
- 11359 [338] E. R. Cazaroto, F. Carvalho, V. P. Goncalves, and F. S. Navarra, *Constraining the nuclear gluon distribution in eA*
11360 *processes at RHIC*, Phys. Lett. **B669** (2008) 331–336, arXiv:0804.2507 [hep-ph].
- 11361 [339] N. Armesto, H. Paukkunen, C. A. Salgado, and K. Tywoniuk, *Nuclear effects on the longitudinal structure function at*
11362 *small x*, Phys.Lett. **B694** (2010) 38–43, arXiv:1005.2035 [hep-ph].
- 11363 [340] A. Bruni, X. Janssen, and P. Marage, *Exclusive Vector Meson Production and Deeply Virtual Compton Scattering at*
11364 *HERA*, Proceedings of the HERA-LHC Workshops, 2006-8, eds. Jung, de Roeck, DESY-PROC-2009-02 (2009) 427,
11365 2009.
- 11366 [341] A. D. Martin, C. Nockles, M. G. Ryskin, and T. Teubner, *Small x gluon from exclusive J/psi production*, Phys. Lett.
11367 **B662** (2008) 252–258, arXiv:0709.4406 [hep-ph].
- 11368 [342] A. Caldwell and H. Kowalski, *Investigating the gluonic structure of nuclei via J/psi scattering*, Phys. Rev. **C81** (2010)
11369 025203.
- 11370 [343] S. Munier, A. M. Stasto, and A. H. Mueller, *Impact parameter dependent S-matrix for dipole proton scattering from*
11371 *diffractive meson electroproduction*, Nucl. Phys. **B603** (2001) 427–445, arXiv:hep-ph/0102291.
- 11372 [344] K. Goeke, M. V. Polyakov, and M. Vanderhaeghen, *Hard Exclusive Reactions and the Structure of Hadrons*, Prog. Part.
11373 Nucl. Phys. **47** (2001) 401–515, arXiv:hep-ph/0106012.
- 11374 [345] M. Diehl, *Generalized parton distributions*, Phys. Rept. **388** (2003) 41–277, arXiv:hep-ph/0307382.
- 11375 [346] S. J. Brodsky, L. Frankfurt, J. F. Gunion, A. H. Mueller, and M. Strikman, *Diffractive leptonproduction of vector mesons*
11376 *in QCD*, Phys. Rev. **D50** (1994) 3134–3144, arXiv:hep-ph/9402283.
- 11377 [347] J. C. Collins, L. Frankfurt, and M. Strikman, *Factorization for hard exclusive electroproduction of mesons in QCD*,
11378 Phys. Rev. **D56** (1997) 2982–3006, arXiv:hep-ph/9611433.

- 11379 [348] M. Diehl, *Generalized parton distributions with helicity flip*, Eur.Phys.J. **C19** (2001) 485–492, arXiv:hep-ph/0101335
11380 [hep-ph].
- 11381 [349] A. Efremov and A. Radyushkin, *Factorization and Asymptotical Behavior of Pion Form-Factor in QCD*, Phys.Lett.
11382 **B94** (1980) 245–250.
- 11383 [350] G. Lepage and S. J. Brodsky, *Exclusive Processes in Perturbative Quantum Chromodynamics*, Phys.Rev. **D22** (1980)
11384 2157.
- 11385 [351] A. V. Belitsky, A. Freund, and D. Mueller, *NLO evolution kernels for skewed transversity distributions*, Phys.Lett.
11386 **B493** (2000) 341–349, arXiv:hep-ph/0008005 [hep-ph].
- 11387 [352] A. Radyushkin, *Double distributions and evolution equations*, Phys.Rev. **D59** (1999) 014030, arXiv:hep-ph/9805342
11388 [hep-ph].
- 11389 [353] A. Radyushkin, *Symmetries and structure of skewed and double distributions*, Phys.Lett. **B449** (1999) 81–88,
11390 arXiv:hep-ph/9810466 [hep-ph].
- 11391 [354] A. Martin, C. Nockles, M. Ryskin, A. Shuvaev, and T. Teubner, *Generalised parton distributions at small x* ,
11392 Eur.Phys.J. **C63** (2009) 57–67.
- 11393 [355] K. Kumericki and D. Mueller, *Deeply virtual Compton scattering at small $x(B)$ and the access to the GPD H* ,
11394 Nucl.Phys. **B841** (2010) 1–58, arXiv:0904.0458 [hep-ph].
- 11395 [356] M. Burkardt, *Impact parameter dependent parton distributions and off-forward parton distributions for $\zeta \rightarrow 0$* ,
11396 Phys. Rev. **D62** (2000) 071503, arXiv:hep-ph/0005108.
- 11397 [357] M. Diehl, *Generalized parton distributions in impact parameter space*, Eur.Phys.J. **C25** (2002) 223–232,
11398 arXiv:hep-ph/0205208 [hep-ph].
- 11399 [358] J. P. Ralston and B. Pire, *Femtophotography of protons to nuclei with deeply virtual Compton scattering*, Phys.Rev.
11400 **D66** (2002) 111501, arXiv:hep-ph/0110075 [hep-ph].
- 11401 [359] T. Rogers, V. Guzey, M. Strikman, and X. Zu, *Determining the proximity of $\gamma^* N$ scattering to the black body
11402 limit using DIS and J/ψ production*, Phys. Rev. **D69** (2004) 074011, arXiv:hep-ph/0309099.
- 11403 [360] H. Kowalski, T. Lappi, and R. Venugopalan, *Nuclear enhancement of universal dynamics of high parton densities*,
11404 Phys. Rev. Lett. **100** (2008) 022303, arXiv:0705.3047 [hep-ph].
- 11405 [361] L. Frankfurt, M. Strikman, and C. Weiss, *Dijet production as a centrality trigger for pp collisions at CERN LHC*,
11406 Phys. Rev. **D69** (2004) 114010, arXiv:hep-ph/0311231.
- 11407 [362] H1 Collaboration, F. D. Aaron et al., *Diffraction Dijet Photoproduction in ep Collisions at HERA*, Eur. Phys. J. **C70**
11408 (2010) 15–37, arXiv:1006.0946 [hep-ex].
- 11409 [363] L. Frankfurt, C. E. Hyde, M. Strikman, and C. Weiss, *Generalized parton distributions and rapidity gap survival in
11410 exclusive diffractive pp scattering*, Phys. Rev. **D75** (2007) 054009, arXiv:hep-ph/0608271.
- 11411 [364] M. Deile et al., *13th International Conference on Elastic and Diffractive Scattering (Blois Workshop) - Moving
11412 Forward into the LHC Era*, arXiv:1002.3527 [hep-ph].
- 11413 [365] ZEUS Collaboration, S. Chekanov et al., *Exclusive electroproduction of J/ψ mesons at HERA*, Nucl. Phys. **B695**
11414 (2004) 3–37, arXiv:hep-ex/0404008.
- 11415 [366] H1 Collaboration, A. Aktas et al., *Elastic J/ψ production at HERA*, Eur. Phys. J. **C46** (2006) 585–603,
11416 arXiv:hep-ex/0510016.
- 11417 [367] H1 Collaboration, F. D. Aaron et al., *Measurement of Deeply Virtual Compton Scattering and its t -dependence at
11418 HERA*, Phys. Lett. **B659** (2008) 796–806, arXiv:0709.4114 [hep-ex].
- 11419 [368] ZEUS Collaboration, S. Chekanov et al., *A measurement of the Q^2 , W and t dependences of deeply virtual Compton
11420 scattering at HERA*, JHEP **05** (2009) 108, arXiv:0812.2517 [hep-ex].
- 11421 [369] C. Marquet and B. Wu, *Exclusive vs. diffractive vector meson production in DIS at small x or off nuclei*,
11422 arXiv:0908.4180 [hep-ph].
- 11423 [370] T. Lappi and H. Mantysaari, *Incoherent diffractive J/ψ -production in high energy nuclear DIS*, Phys.Rev. **C83** (2011)
11424 065202, arXiv:1011.1988 [hep-ph].
- 11425 [371] W. Horowitz, *Measuring the Gluon Density in $e + A$ Collisions: KLN CGC, DGLAP Glauber, or Neither?*,
11426 arXiv:1102.5058 [hep-ph]. * Temporary entry *.
- 11427 [372] L. Frankfurt, M. Strikman, D. Treleani, and C. Weiss, *Evidence for color fluctuations in the nucleon in high-energy
11428 scattering*, Phys. Rev. Lett. **101** (2008) 202003, arXiv:0808.0182 [hep-ph].
- 11429 [373] J. Bartels, K. J. Golec-Biernat, and K. Peters, *On the dipole picture in the nonforward direction*, Acta Phys. Polon.
11430 **B34** (2003) 3051–3068, arXiv:hep-ph/0301192.
- 11431 [374] C. Marquet, R. B. Peschanski, and G. Soyez, *Exclusive vector meson production at HERA from QCD with saturation*,
11432 Phys.Rev. **D76** (2007) 034011, arXiv:hep-ph/0702171 [HEP-PH].

- 11433 [375] M. G. Ryskin, *Diffractional J / psi electroproduction in LLA QCD*, Z. Phys. **C57** (1993) 89–92.
- 11434 [376] P. Newman, *Low x and Diffractional Physics at a Large Hadron electron Collider*, . In Proceedings of the 13th
11435 International (Blois) Conference on Elastic and Diffractional Scattering, EDS'09, CERN, 2009, p182.
- 11436 [377] B. List and A. Mastroberardino, *DIFVIM: A Monte Carlo generator for diffractional processes in ep scattering*,
11437 Proceedings of the Workshop on Monte Carlo Generators for HERA Physics, DESY-PROC-1992-02 (1999) 396, 1999.
- 11438 [378] J. R. Forshaw, R. Sandapen, and G. Shaw, *Colour dipoles and rho, Phi electroproduction*, Phys. Rev. **D69** (2004)
11439 094013, [arXiv:hep-ph/0312172](#).
- 11440 [379] ZEUS Collaboration, S. Chekanov et al., *Exclusive photoproduction of J/psi mesons at HERA*, Eur. Phys. J. **C24**
11441 (2002) 345–360, [arXiv:hep-ex/0201043](#).
- 11442 [380] ZEUS Collaboration, J. Breitweg et al., *Measurement of elastic Upsilon photoproduction at HERA*, Phys. Lett. **B437**
11443 (1998) 432–444, [arXiv:hep-ex/9807020](#).
- 11444 [381] H1 Collaboration, C. Adloff et al., *Elastic photoproduction of J/psi and Upsilon mesons at HERA*, Phys. Lett. **B483**
11445 (2000) 23–35, [arXiv:hep-ex/0003020](#).
- 11446 [382] ZEUS Collaboration, S. Chekanov et al., *Exclusive photoproduction of Upsilon mesons at HERA*, Phys. Lett. **B680**
11447 (2009) 4–12, [arXiv:0903.4205 \[hep-ex\]](#).
- 11448 [383] B. E. Cox, J. R. Forshaw, and R. Sandapen, *Diffractional Upsilon production at the LHC*, JHEP **06** (2009) 034,
11449 [arXiv:0905.0102 \[hep-ph\]](#).
- 11450 [384] E. Perez, L. Schoeffel, and L. Favart, *MILOU: A Monte-Carlo for deeply virtual Compton scattering*,
11451 [arXiv:hep-ph/0411389 \[hep-ph\]](#).
- 11452 [385] L. Frankfurt, A. Freund, and M. Strikman, *Diffractional exclusive photoproduction in DIS at HERA*, Phys.Rev. **D58**
11453 (1998) 114001, [arXiv:hep-ph/9710356 \[hep-ph\]](#).
- 11454 [386] H1 Collaboration, F. Aaron et al., *Deeply Virtual Compton Scattering and its Beam Charge Asymmetry in e+-*
11455 *Collisions at HERA*, Phys.Lett. **B681** (2009) 391–399, [arXiv:arXiv:0907.5289 \[hep-ex\]](#).
- 11456 [387] M. Diehl, T. Gousset, and B. Pire, *Exclusive electroproduction of vector mesons and transversity distributions*,
11457 Phys.Rev. **D59** (1999) 034023, [arXiv:hep-ph/9808479 \[hep-ph\]](#).
- 11458 [388] J. C. Collins and M. Diehl, *Transversity distribution does not contribute to hard exclusive electroproduction of mesons*,
11459 Phys.Rev. **D61** (2000) 114015, [arXiv:hep-ph/9907498 \[hep-ph\]](#).
- 11460 [389] D. Ivanov, B. Pire, L. Szymanowski, and O. Teryaev, *Probing chiral odd GPD's in diffractional electroproduction of two*
11461 *vector mesons*, Phys.Lett. **B550** (2002) 65–76, [arXiv:hep-ph/0209300 \[hep-ph\]](#).
- 11462 [390] R. Enberg, B. Pire, and L. Szymanowski, *Transversity GPD in photo- and electroproduction of two vector mesons*,
11463 Eur.Phys.J. **C47** (2006) 87–94, [arXiv:hep-ph/0601138 \[hep-ph\]](#).
- 11464 [391] Fermilab Tagged Photon Spectrometer, M. D. Sokoloff et al., *An Experimental Study of the alpha-Dependence of J/psi*
11465 *Photoproduction*, Phys. Rev. Lett. **57** (1986) 3003.
- 11466 [392] E665 Collaboration, M. R. Adams et al., *Measurement of nuclear transparencies from exclusive rho0 meson production*
11467 *in muon - nucleus scattering at 470-GeV*, Phys. Rev. Lett. **74** (1995) 1525–1529.
- 11468 [393] L. Frankfurt, V. Guzey, and M. Strikman, *Leading twist nuclear shadowing phenomena in hard processes with nuclei*,
11469 Phys.Rept. **512** (2012) 255–393, [arXiv:1106.2091 \[hep-ph\]](#).
- 11470 [394] B. Nicolescu, *Recent advances in odderon physics*, [arXiv:hep-ph/9911334 \[hep-ph\]](#).
- 11471 [395] C. Ewerz, *The Odderon in quantum chromodynamics*, [arXiv:hep-ph/0306137 \[hep-ph\]](#).
- 11472 [396] J. Bartels, *High-Energy Behavior in a Nonabelian Gauge Theory. 1. T(n,m) in the Leading Log Normal S*
11473 *Approximation*, Nucl.Phys. **B151** (1979) 293.
- 11474 [397] J. Bartels, *High-Energy Behavior in a Nonabelian Gauge Theory. 2. First Corrections to T(n,m) Beyond the Leading*
11475 *LNS Approximation*, Nucl.Phys. **B175** (1980) 365.
- 11476 [398] J. Kwiecinski and M. Praszalowicz, *Three Gluon Integral Equation and Odd c Singlet Regge Singularities in QCD*,
11477 Phys.Lett. **B94** (1980) 413.
- 11478 [399] R. Janik and J. Wosiek, *Solution of the odderon problem*, Phys.Rev.Lett. **82** (1999) 1092–1095, [arXiv:hep-th/9802100](#)
11479 [\[hep-th\]](#).
- 11480 [400] J. Bartels, L. Lipatov, and G. Vacca, *A New odderon solution in perturbative QCD*, Phys.Lett. **B477** (2000) 178–186,
11481 [arXiv:hep-ph/9912423 \[hep-ph\]](#).
- 11482 [401] H1 Collaboration, C. Adloff et al., *Search for odderon induced contributions to exclusive pi0 photoproduction at HERA*,
11483 Phys.Lett. **B544** (2002) 35–43, [arXiv:hep-ex/0206073 \[hep-ex\]](#).
- 11484 [402] J. Czyzewski, J. Kwiecinski, L. Motyka, and M. Sadzikowski, *Exclusive eta(c) photoproduction and electroproduction at*
11485 *HERA as a possible probe of the odderon singularity in QCD*, Phys.Lett. **B398** (1997) 400–406, [arXiv:hep-ph/9611225](#)
11486 [\[hep-ph\]](#).

- 11487 [403] S. J. Brodsky, J. Rathsman, and C. Merino, *Odderon-Pomeron interference*, Phys.Lett. **B461** (1999) 114–122,
11488 [arXiv:hep-ph/9904280 \[hep-ph\]](#).
- 11489 [404] P. Hagler, B. Pire, L. Szymanowski, and O. Teryaev, *Hunting the QCD odderon in hard diffractive electroproduction of*
11490 *two pions*, Phys.Lett. **B535** (2002) 117–126, [arXiv:hep-ph/0202231 \[hep-ph\]](#).
- 11491 [405] I. Ginzburg, I. Ivanov, and N. Nikolaev, *Possible odderon discovery via observation of charge asymmetry in the*
11492 *diffractive $\pi^+ \pi^-$ production at HERA*, Eur.Phys.J.direct **C5** (2003) 02, [arXiv:hep-ph/0207345 \[hep-ph\]](#).
- 11493 [406] P. Hagler, B. Pire, L. Szymanowski, and O. Teryaev, *Pomeron - odderon interference effects in electroproduction of two*
11494 *pions*, Eur.Phys.J. **C26** (2002) 261–270, [arXiv:hep-ph/0207224 \[hep-ph\]](#).
- 11495 [407] M. Diehl, T. Gousset, B. Pire, and O. Teryaev, *Probing partonic structure in $\gamma^* \gamma \rightarrow \pi \pi$ near threshold*,
11496 Phys.Rev.Lett. **81** (1998) 1782–1785, [arXiv:hep-ph/9805380 \[hep-ph\]](#).
- 11497 [408] M. V. Polyakov and C. Weiss, *Two pion light cone distribution amplitudes from the instanton vacuum*, Phys.Rev. **D59**
11498 (1999) 091502, [arXiv:hep-ph/9806390 \[hep-ph\]](#).
- 11499 [409] M. V. Polyakov, *Hard exclusive electroproduction of two pions and their resonances*, Nucl.Phys. **B555** (1999) 231,
11500 [arXiv:hep-ph/9809483 \[hep-ph\]](#).
- 11501 [410] M. Diehl, T. Gousset, and B. Pire, *Exclusive production of pion pairs in $\gamma^* \gamma$ collisions at large Q^{*2}* ,
11502 Phys.Rev. **D62** (2000) 073014, [arXiv:hep-ph/0003233 \[hep-ph\]](#).
- 11503 [411] A. Kaidalov, *Diffractive Production Mechanisms*, Phys.Rept. **50** (1979) 157–226.
- 11504 [412] K. A. Goulianos, *Diffractive Interactions of Hadrons at High-Energies*, Phys. Rept. **101** (1983) 169.
- 11505 [413] G. Ingelman and P. E. Schlein, *Jet Structure in High Mass Diffractive Scattering*, Phys. Lett. **B152** (1985) 256.
- 11506 [414] A. Donnachie and P. V. Landshoff, *Diffractive Deep Inelastic Lepton Scattering*, Phys. Lett. **B191** (1987) 309.
- 11507 [415] G. Wolf, *Review of High Energy Diffraction in Real and Virtual Photon Proton scattering at HERA*, Rept. Prog. Phys.
11508 **73** (2010) 116202, [arXiv:0907.1217 \[hep-ex\]](#).
- 11509 [416] H1 Collaboration, A. Aktas et al., *Diffractive deep-inelastic scattering with a leading proton at HERA*, Eur. Phys. J.
11510 **C48** (2006) 749–766, [arXiv:hep-ex/0606003](#).
- 11511 [417] ZEUS Collaboration, S. Chekanov et al., *Deep inelastic scattering with leading protons or large rapidity gaps at HERA*,
11512 Nucl. Phys. **B816** (2009) 1–61, [arXiv:0812.2003 \[hep-ex\]](#).
- 11513 [418] F. Aaron, C. Alexa, V. Andreev, S. Backovic, A. Baghdasaryan, et al., *Measurement of the cross section for diffractive*
11514 *deep-inelastic scattering with a leading proton at HERA*, Eur.Phys.J. **C71** (2011) 1578, [arXiv:1010.1476 \[hep-ex\]](#).
- 11515 [419] H1 Collaboration, A. Aktas et al., *Measurement and QCD analysis of the diffractive deep- inelastic scattering*
11516 *cross-section at HERA*, Eur. Phys. J. **C48** (2006) 715–748, [arXiv:hep-ex/0606004](#).
- 11517 [420] J. Blumlein and D. Robaschik, *On the scaling violations of diffractive structure functions: Operator approach*, Phys.
11518 Lett. **B517** (2001) 222–232, [arXiv:hep-ph/0106037](#).
- 11519 [421] H1 Collaboration, A. Aktas et al., *Dijet Cross Sections and Parton Densities in Diffractive DIS at HERA*, JHEP **10**
11520 (2007) 042, [arXiv:0708.3217 \[hep-ex\]](#).
- 11521 [422] ZEUS Collaboration, S. Chekanov et al., *A QCD analysis of ZEUS diffractive data*, Nucl. Phys. **B831** (2010) 1–25,
11522 [arXiv:0911.4119 \[hep-ex\]](#).
- 11523 [423] A. D. Martin, M. G. Ryskin, and G. Watt, *Diffractive parton distributions from perturbative QCD*, Eur. Phys. J. **C44**
11524 (2005) 69–85, [arXiv:hep-ph/0504132](#).
- 11525 [424] ZEUS Collaboration, S. Chekanov et al., *Dijet production in diffractive deep inelastic scattering at HERA*, Eur.Phys.J.
11526 **C52** (2007) 813–832, [arXiv:0708.1415 \[hep-ex\]](#).
- 11527 [425] H1 Collaboration, A. Aktas et al., *Tests of QCD factorisation in the diffractive production of dijets in deep-inelastic*
11528 *scattering and photoproduction at HERA*, Eur. Phys. J. **C51** (2007) 549–568, [arXiv:hep-ex/0703022](#).
- 11529 [426] H1, F. D. Aaron et al., *Measurement of Dijet Production in Diffractive Deep- Inelastic Scattering with a Leading*
11530 *Proton at HERA*, [arXiv:1111.0584 \[hep-ex\]](#).
- 11531 [427] H1 Collaboration, A. Aktas et al., *Diffractive open charm production in deep-inelastic scattering and photoproduction*
11532 *at HERA*, Eur. Phys. J. **C50** (2007) 1–20, [arXiv:hep-ex/0610076](#).
- 11533 [428] ZEUS Collaboration, S. Chekanov et al., *Measurement of the open charm contribution to the diffractive proton*
11534 *structure function*, Nucl.Phys. **B672** (2003) 3–35, [arXiv:hep-ex/0307068 \[hep-ex\]](#).
- 11535 [429] The ZEUS Collaboration, S. Chekanov et al., *Diffractive photoproduction of dijets in ep collisions at HERA*,
11536 Eur.Phys.J. **C55** (2008) 177–191, [arXiv:0710.1498 \[hep-ex\]](#).
- 11537 [430] Y. L. Dokshitzer, V. A. Khoze, and T. Sjostrand, *Rapidity gaps in Higgs production*, Phys.Lett. **B274** (1992) 116–121.
- 11538 [431] J. Bjorken, *Rapidity gaps and jets as a new physics signature in very high-energy hadron hadron collisions*, Phys.Rev.
11539 **D47** (1993) 101–113.

- 11540 [432] E. Gotsman, E. Levin, and U. Maor, *Large rapidity gaps in $p p$ collisions*, Phys.Lett. **B309** (1993) 199–204,
11541 [arXiv:hep-ph/9302248 \[hep-ph\]](#).
- 11542 [433] Z. Nagy, *Next-to-leading order calculation of three-jet observables in hadron hadron collision*, Phys. Rev. **D68** (2003)
11543 094002, [arXiv:hep-ph/0307268](#).
- 11544 [434] P. Newman, *Deep Inelastic Scattering at the TeV Energy Scale and the LHeC Project*, Nucl. Phys. Proc. Suppl. **191**
11545 (2009) 307–319, [arXiv:0902.2292 \[hep-ex\]](#).
- 11546 [435] J. Bartels, J. R. Ellis, H. Kowalski, and M. Wusthoff, *An analysis of diffraction in deep-inelastic scattering*, Eur. Phys.
11547 J. **C7** (1999) 443–458, [arXiv:hep-ph/9803497](#).
- 11548 [436] H1 Collaboration, F. e. a. Aaron, *Measurement of the Diffractive Longitudinal Structure Function F_L^D at HERA*,
11549 [arXiv:1107.3420 \[hep-ex\]](#). * Temporary entry *.
- 11550 [437] H1 Collaboration, F. D. Aaron et al., *Measurement of Leading Neutron Production in Deep- Inelastic Scattering at*
11551 *HERA*, Eur. Phys. J. **C68** (2010) 381–399, [arXiv:1001.0532 \[hep-ex\]](#).
- 11552 [438] G. Watt and H. Kowalski, *Impact parameter dependent colour glass condensate dipole model*, Phys. Rev. **D78** (2008)
11553 014016, [arXiv:0712.2670 \[hep-ph\]](#).
- 11554 [439] V. A. Abramovsky, V. N. Gribov, and O. V. Kancheli, *Character of inclusive spectra and fluctuations produced in*
11555 *inelastic processes by multi-pomeron exchange*, Yad. Fiz. **18** (1973) 595–616.
- 11556 [440] L. Frankfurt and M. Strikman, *Diffractive at HERA, color opacity and nuclear shadowing*, Eur. Phys. J. **A5** (1999)
11557 293–306, [arXiv:hep-ph/9812322](#).
- 11558 [441] L. Frankfurt, V. Guzey, and M. Strikman, *Leading twist nuclear shadowing: A user's guide*, Phys. Rev. **D71** (2005)
11559 054001, [arXiv:hep-ph/0303022](#).
- 11560 [442] H. Abramowicz, L. Frankfurt, and M. Strikman, *Interplay of hard and soft physics in small x deep inelastic processes*,
11561 ECONF **C940808** (1994) 033, [arXiv:hep-ph/9503437](#).
- 11562 [443] N. Armesto, A. Capella, A. Kaidalov, J. Lopez-Albacete, and C. Salgado, *Nuclear structure functions at small x from*
11563 *inelastic shadowing and diffraction*, Eur.Phys.J. **C29** (2003) 531–540, [arXiv:hep-ph/0304119 \[hep-ph\]](#).
- 11564 [444] K. Tywoniuk, I. Arsene, L. Bravina, A. Kaidalov, and E. Zabrodin, *Gluon shadowing in the Glauber-Gribov model at*
11565 *HERA*, Phys. Lett. **B657** (2007) 170–175, [arXiv:0705.1596 \[hep-ph\]](#).
- 11566 [445] L. Frankfurt, V. Guzey, and M. Strikman, *Leading twist coherent diffraction on nuclei in deep inelastic scattering at*
11567 *small x and nuclear shadowing*, Phys. Lett. **B586** (2004) 41–52, [arXiv:hep-ph/0308189](#).
- 11568 [446] C. Marquet, *A Unified description of diffractive deep inelastic scattering with saturation*, Phys.Rev. **D76** (2007)
11569 094017, [arXiv:0706.2682 \[hep-ph\]](#).
- 11570 [447] H. Kowalski, T. Lappi, C. Marquet, and R. Venugopalan, *Nuclear enhancement and suppression of diffractive structure*
11571 *functions at high energies*, Phys. Rev. **C78** (2008) 045201, [arXiv:0805.4071 \[hep-ph\]](#).
- 11572 [448] N. N. Nikolaev, B. Zakharov, and V. Zoller, *Unusual effects of diffraction dissociation for multiproduction in deep*
11573 *inelastic scattering on nuclei*, Z.Phys. **A351** (1995) 435–446.
- 11574 [449] J. Collins and H. Jung, *Need for fully unintegrated parton densities*, [arXiv:hep-ph/0508280](#).
- 11575 [450] J. C. Collins and D. E. Soper, *Back-To-Back Jets in QCD*, Nucl. Phys. **B193** (1981) 381.
- 11576 [451] J. C. Collins and D. E. Soper, *Parton Distribution and Decay Functions*, Nucl. Phys. **B194** (1982) 445.
- 11577 [452] J. C. Collins, *What exactly is a parton density?*, Acta Phys. Polon. **B34** (2003) 3103, [arXiv:hep-ph/0304122](#).
- 11578 [453] J. Collins, *Rapidity divergences and valid definitions of parton densities*, PoS **LC2008** (2008) 028, [arXiv:0808.2665](#)
11579 [\[hep-ph\]](#).
- 11580 [454] X.-d. Ji, J.-p. Ma, and F. Yuan, *QCD factorization for semi-inclusive deep-inelastic scattering at low transverse*
11581 *momentum*, Phys. Rev. **D71** (2005) 034005, [arXiv:hep-ph/0404183](#).
- 11582 [455] M. Ciafaloni, *Coherence Effects in Initial Jets at Small q^{*2} / s* , Nucl. Phys. **B296** (1988) 49.
- 11583 [456] S. Catani, F. Fiorani, and G. Marchesini, *QCD Coherence in Initial State Radiation*, Phys.Lett. **B234** (1990) 339.
- 11584 [457] S. Catani, F. Fiorani, and G. Marchesini, *Small x Behavior of Initial State Radiation in Perturbative QCD*, Nucl.Phys.
11585 **B336** (1990) 18.
- 11586 [458] G. Marchesini, *QCD coherence in the structure function and associated distributions at small x* , Nucl.Phys. **B445**
11587 (1995) 49–80, [arXiv:hep-ph/9412327 \[hep-ph\]](#).
- 11588 [459] I. Balitsky, *High-energy QCD and Wilson lines*, [arXiv:hep-ph/0101042](#).
- 11589 [460] J. C. Collins, *Foundations of Perturbative QCD*. Cambridge University Press, Cambridge, 2011.
- 11590 [461] S. Aybat and T. C. Rogers, *TMD Parton Distribution and Fragmentation Functions with QCD Evolution*, Phys.Rev.
11591 **D83** (2011) 114042, [arXiv:1101.5057 \[hep-ph\]](#).

- 11592 [462] J. C. Collins and A. Metz, *Universality of soft and collinear factors in hard- scattering factorization*, Phys. Rev. Lett. 11593 **93** (2004) 252001, [arXiv:hep-ph/0408249](#).
- 11594 [463] F. Landry, R. Brock, P. M. Nadolsky, and C. P. Yuan, *Tevatron Run-1 Z boson data and Collins-Soper-Sterman resummation formalism*, Phys. Rev. **D67** (2003) 073016, [arXiv:hep-ph/0212159](#).
- 11596 [464] J. C. Collins, D. E. Soper, and G. F. Sterman, *Transverse Momentum Distribution in Drell-Yan Pair and W and Z Boson Production*, Nucl. Phys. **B250** (1985) 199.
- 11598 [465] C. Marquet, B.-W. Xiao, and F. Yuan, *Semi-inclusive Deep Inelastic Scattering at small x*, Phys. Lett. **B682** (2009) 207–211, [arXiv:0906.1454 \[hep-ph\]](#).
- 11600 [466] F. Dominguez, B.-W. Xiao, and F. Yuan, *kt-factorization for Hard Processes in Nuclei*, Phys. Rev. Lett. **106** (2011) 022301, [arXiv:1009.2141 \[hep-ph\]](#).
- 11602 [467] H1 Collaboration, A. Aktas et al., *Inclusive dijet production at low Bjorken-x in deep inelastic scattering*, Eur. Phys. J. **C33** (2004) 477–493, [arXiv:hep-ex/0310019](#).
- 11604 [468] A. J. Askew, D. Graudenz, J. Kwiecinski, and A. D. Martin, *Dijet production at HERA as a probe of BFKL dynamics*, Phys. Lett. **B338** (1994) 92–97, [arXiv:hep-ph/9407337](#).
- 11606 [469] J. Kwiecinski, A. D. Martin, and A. M. Stasto, *Predictions for dijet production in DIS using small x dynamics*, Phys. Lett. **B459** (1999) 644–648, [arXiv:hep-ph/9904402](#).
- 11608 [470] A. Szczurek, N. N. Nikolaev, W. Schafer, and J. Speth, *Mapping the proton unintegrated gluon distribution in dijets correlations in real and virtual photoproduction at HERA*, Phys. Lett. **B500** (2001) 254–262, [arXiv:hep-ph/0011281](#).
- 11610 [471] M. Hansson and H. Jung, *Towards precision determination of uPDFs*, [arXiv:0707.4276 \[hep-ph\]](#).
- 11611 [472] F. Hautmann and H. Jung, *Angular correlations in multi-jet final states from kt- dependent parton showers*, JHEP **10** (2008) 113, [arXiv:0805.1049 \[hep-ph\]](#).
- 11613 [473] J. Bartels, C. Ewerz, H. Lotter, and M. Wusthoff, *Azimuthal distribution of quark - anti-quark jets in DIS diffractive dissociation*, Phys.Lett. **B386** (1996) 389–396, [arXiv:hep-ph/9605356 \[hep-ph\]](#).
- 11615 [474] J. Bartels, H. Jung, and M. Wusthoff, *Quark - anti-quark gluon jets in DIS diffractive dissociation*, Eur.Phys.J. **C11** (1999) 111–125, [arXiv:hep-ph/9903265 \[hep-ph\]](#).
- 11617 [475] L. Lonnblad, *ARIADNE version 4: A Program for simulation of QCD cascades implementing the color dipole model*, Comput.Phys.Commun. **71** (1992) 15–31.
- 11619 [476] H. Jung et al., *The CCFM Monte Carlo generator CASCADE 2.2.0*, Eur. Phys. J. **C70** (2010) 1237–1249, [arXiv:1008.0152 \[hep-ph\]](#).
- 11621 [477] F. Dominguez, C. Marquet, B.-W. Xiao, and F. Yuan, *Universality of Unintegrated Gluon Distributions at small x*, Phys.Rev. **D83** (2011) 105005, [arXiv:1101.0715 \[hep-ph\]](#).
- 11623 [478] A. H. Mueller, *Parton distributions at very small x values*, Nucl. Phys. Proc. Suppl. **18C** (1991) 125–132.
- 11624 [479] A. H. Mueller, *Jets at LEP and HERA*, J. Phys. **G17** (1991) 1443–1454.
- 11625 [480] H1 Collaboration, S. Aid et al., *Transverse energy and forward jet production in the low x regime at HERA*, Phys. Lett. **B356** (1995) 118–128, [arXiv:hep-ex/9506012](#).
- 11627 [481] H1 Collaboration, C. Adloff et al., *Forward jet and particle production at HERA*, Nucl. Phys. **B538** (1999) 3–22, [arXiv:hep-ex/9809028](#).
- 11629 [482] H1 Collaboration, A. Aktas et al., *Forward jet production in deep inelastic scattering at HERA*, Eur. Phys. J. **C46** (2006) 27–42, [arXiv:hep-ex/0508055](#).
- 11631 [483] ZEUS Collaboration, J. Breitweg et al., *Forward jet production in deep inelastic scattering at HERA*, Eur. Phys. J. **C6** (1999) 239–252, [arXiv:hep-ex/9805016](#).
- 11633 [484] ZEUS Collaboration, J. Breitweg et al., *Measurement of the $E(T,jet)^{**2}/Q^{**2}$ dependence of forward- jet production at HERA*, Phys. Lett. **B474** (2000) 223–233, [arXiv:hep-ex/9910043](#).
- 11635 [485] ZEUS Collaboration, S. Chekanov et al., *Forward jet production in deep inelastic e p scattering and low-x parton dynamics at HERA*, Phys. Lett. **B632** (2006) 13–26, [arXiv:hep-ex/0502029](#).
- 11637 [486] J. Kwiecinski, S. C. Lang, and A. D. Martin, *Single particle spectra in deep inelastic scattering as a probe of small x dynamics*, Eur. Phys. J. **C6** (1999) 671–680, [arXiv:hep-ph/9707240](#).
- 11639 [487] J. Kwiecinski, A. D. Martin, and J. J. Outhwaite, *Small x QCD effects in DIS with a forward jet or a forward π^0* , Eur. Phys. J. **C9** (1999) 611–622, [arXiv:hep-ph/9903439](#).
- 11641 [488] G. Bottazzi, G. Marchesini, G. P. Salam, and M. Scorletti, *Small-x one-particle-inclusive quantities in the CCFM approach*, JHEP **12** (1998) 011, [arXiv:hep-ph/9810546](#).
- 11643 [489] H. Jung, *CCFM prediction on forward jets and F2: Parton level predictions and a new hadron level Monte Carlo generator CASCADE*, [arXiv:hep-ph/9908497](#).

- 11645 [490] H. Jung, *CCFM prediction for F_2 and forward jets at HERA*, Nucl. Phys. Proc. Suppl. **79** (1999) 429–431,
11646 arXiv:hep-ph/9905554.
- 11647 [491] H. Jung and G. P. Salam, *Hadronic final state predictions from CCFM: The hadron- level Monte Carlo generator*
11648 *CASCADE*, Eur. Phys. J. **C19** (2001) 351–360, arXiv:hep-ph/0012143.
- 11649 [492] O. Kepka, C. Royon, C. Marquet, and R. B. Peschanski, *Next-leading BFKL effects in forward-jet production at HERA*,
11650 Phys. Lett. **B655** (2007) 236–240, arXiv:hep-ph/0609299.
- 11651 [493] J. Bartels, V. Del Duca, and M. Wusthoff, *Azimuthal dependence of forward jet production in DIS in the high-energy*
11652 *limit*, Z.Phys. **C76** (1997) 75–79, arXiv:hep-ph/9610450 [hep-ph].
- 11653 [494] A. Sabio Vera and F. Schwennsen, *Azimuthal decorrelation of forward jets in Deep Inelastic Scattering*, Phys. Rev.
11654 **D77** (2008) 014001, arXiv:0708.0549 [hep-ph].
- 11655 [495] J. Kwiecinski, A. D. Martin, P. J. Sutton, and K. J. Golec-Biernat, *QCD predictions for the transverse energy flow in*
11656 *deep inelastic scattering in the HERA small x regime*, Phys. Rev. **D50** (1994) 217–225, arXiv:hep-ph/9403292.
- 11657 [496] K. J. Golec-Biernat, J. Kwiecinski, A. D. Martin, and P. J. Sutton, *Transverse energy flow at HERA*, Phys. Lett. **B335**
11658 (1994) 220–225, arXiv:hep-ph/9405400.
- 11659 [497] N. H. Brook et al., *A comparison of deep inelastic scattering Monte Carlo event generators to HERA data*,
11660 arXiv:hep-ex/9912053.
- 11661 [498] G. P. Salam and G. Soyez, *A practical Seedless Infrared-Safe Cone jet algorithm*, JHEP **05** (2007) 086,
11662 arXiv:0704.0292 [hep-ph].
- 11663 [499] Y. L. Dokshitzer, V. A. Khoze, A. H. Mueller, and S. I. Troyan, *Basics of perturbative QCD*, . Editions Frontieres 1991,
11664 274p.
- 11665 [500] D. de Florian, R. Sassot, and M. Stratmann, *Global analysis of fragmentation functions for pions and kaons and their*
11666 *uncertainties*, Phys.Rev. **D75** (2007) 114010, arXiv:hep-ph/0703242 [HEP-PH].
- 11667 [501] D. de Florian, R. Sassot, and M. Stratmann, *Global analysis of fragmentation functions for protons and charged*
11668 *hadrons*, Phys.Rev. **D76** (2007) 074033, arXiv:0707.1506 [hep-ph].
- 11669 [502] A. Daleo, D. de Florian, and R. Sassot, *$O(\alpha(s)^{**2})$ QCD corrections to the electroproduction of hadrons with high*
11670 *transverse momentum*, Phys. Rev. **D71** (2005) 034013, arXiv:hep-ph/0411212.
- 11671 [503] R. Sassot, M. Stratmann, and P. Zurita, *Fragmentations Functions in Nuclear Media*, Phys. Rev. **D81** (2010) 054001,
11672 arXiv:0912.1311 [hep-ph].
- 11673 [504] H1 Collaboration, A. Aktas et al., *Forward π^0 production and associated transverse energy flow in deep-inelastic*
11674 *scattering at HERA*, Eur.Phys.J. **C36** (2004) 441–452, arXiv:hep-ex/0404009 [hep-ex].
- 11675 [505] F. Arleo, *Quenching of hadron spectra in DIS on nuclear targets*, Eur.Phys.J. **C30** (2003) 213–221,
11676 arXiv:hep-ph/0306235 [hep-ph].
- 11677 [506] C. A. Salgado and U. A. Wiedemann, *Calculating quenching weights*, Phys.Rev. **D68** (2003) 014008,
11678 arXiv:hep-ph/0302184 [hep-ph].
- 11679 [507] HERMES Collaboration, A. Airapetian et al., *Hadronization in semi-inclusive deep-inelastic scattering on nuclei*,
11680 Nucl.Phys. **B780** (2007) 1–27.
- 11681 [508] A. M. Stasto, *Physics of ultrahigh energy neutrinos*, Int. J. Mod. Phys. **A19** (2004) 317–340, arXiv:astro-ph/0310636.
- 11682 [509] J. K. Becker, *High-energy neutrinos in the context of multimessenger physics*, Phys. Rept. **458** (2008) 173–246,
11683 arXiv:0710.1557 [astro-ph].
- 11684 [510] E. Zas, *Neutrino Detection with Inclined Air Showers*, New J. Phys. **7** (2005) 130, arXiv:astro-ph/0504610.
- 11685 [511] N. Armesto, C. Merino, G. Parente, and E. Zas, *Charged Current Neutrino Cross Section and Tau Energy Loss at*
11686 *Ultra-High Energies*, Phys. Rev. **D77** (2008) 013001, arXiv:0709.4461 [hep-ph].
- 11687 [512] J. A. Bagger and M. E. Peskin, *Exotic processes in high-energy ep collisions*, Phys. Rev. **D31** (1985) 2211.
- 11688 [513] R. J. Cashmore et al., *Exotic phenomena in high-energy ep collisions*, Phys. Rept. **122** (1985) 275–386.
- 11689 [514] G. Jarlskog, (Ed.) and D. Rein, (Ed.), *ECFA Large Hadron Collider Workshop, Aachen, Germany, 4-9 Oct 1990:*
11690 *Proceedings.1*, . CERN-90-10-V-1.
- 11691 [515] G. Kopp, D. Schaile, M. Spira, and P. M. Zerwas, *Bounds on radii and magnetic dipole moments of quarks and leptons*
11692 *from LEP, SLC and HERA*, Z. Phys. **C65** (1995) 545–550, arXiv:hep-ph/9409457.
- 11693 [516] A. F. Zarnecki, *Leptoquarks and Contact Interactions at LeHC*, arXiv:0809.2917 [hep-ph].
- 11694 [517] The ATLAS Collaboration, *Search for New Phenomena in Dijet Mass and Angular Distributions using 4.8 fb⁻¹ of pp*
11695 *Collisions at $\sqrt{s} = 7$ TeV collected by the ATLAS Detector*, ATLAS-CONF-2012-038.
- 11696 [518] E. Eichten, K. D. Lane, and M. E. Peskin, *New Tests for Quark and Lepton Substructure*, Phys. Rev. Lett. **50** (1983)
11697 811–814.
- 11698 [519] R. Ruckl, *Probing lepton and quark substructure in polarized $e^+ N$ scattering*, Nucl. Phys. **B234** (1984) 91.

- 11699 [520] P. Haberl, F. Schrempp, and H. U. Martyn, *Contact interactions and new heavy bosons at HERA: A Model*
11700 *independent analysis*, . In *Hamburg 1991, Proceedings, Physics at HERA, vol. 2* 1133-1148. (see HIGH ENERGY
11701 PHYSICS INDEX 30 (1992) No. 12988).
- 11702 [521] T. G. Rizzo, *Indirect Searches for Z-prime-like Resonances at the LHC*, JHEP **0908** (2009) 082, arXiv:0904.2534
11703 [hep-ph].
- 11704 [522] A. F. Zarnecki, *Global analysis of eeqq contact interactions and future prospects for high-energy physics*, Eur. Phys. J.
11705 **C11** (1999) 539–557, arXiv:hep-ph/9904334.
- 11706 [523] C. T. Hill and E. H. Simmons, *Strong dynamics and electroweak symmetry breaking*, Phys. Rept. **381** (2003) 235–402,
11707 arXiv:hep-ph/0203079.
- 11708 [524] W. Buchmuller, R. Ruckl, and D. Wyler, *Leptoquarks in lepton quark collisions*, Phys. Lett. **B191** (1987) 442–448.
- 11709 [525] B. Schrempp, *Leptoquarks and leptogluons at HERA: Theoretical perspectives*, . In *Hamburg 1991, Proceedings,
11710 Physics at HERA, vol. 2* 1034-1042. (see HIGH ENERGY PHYSICS INDEX 30 (1992) No. 12988).
- 11711 [526] S. Davidson, D. C. Bailey, and B. A. Campbell, *Model independent constraints on leptoquarks from rare processes*, Z.
11712 Phys. **C61** (1994) 613–644, arXiv:hep-ph/9309310.
- 11713 [527] M. Leurer, *A Comprehensive study of leptoquark bounds*, Phys. Rev. **D49** (1994) 333–342, arXiv:hep-ph/9309266.
- 11714 [528] A. Belyaev, C. Leroy, R. Mehdiyev, and A. Pukhov, *Leptoquark single and pair production at LHC with*
11715 *CalcHEP/CompHEP in the complete model*, JHEP **09** (2005) 005, arXiv:hep-ph/0502067.
- 11716 [529] ATLAS Collaboration, G. Aad et al., *Search for first generation scalar leptoquarks in pp collisions at $\sqrt{s}=7$ TeV with*
11717 *the ATLAS detector*, Phys.Lett. **B709** (2012) 158–176, arXiv:1112.4828 [hep-ex].
- 11718 [530] D0 Collaboration, V. M. Abazov et al., *Search for pair production of first-generation leptoquarks in p pbar collisions at*
11719 *$\sqrt{s}=1.96$ TeV*, Phys. Lett. **B681** (2009) 224–232, arXiv:0907.1048 [hep-ex].
- 11720 [531] CMS Collaboration, S. Chatrchyan et al., *Search for First Generation Scalar Leptoquarks in the $e\nu jj$ channel in pp*
11721 *collisions at $\sqrt{s} = 7$ TeV*, arXiv:1105.5237 [hep-ex]. * Temporary entry *.
- 11722 [532] A. Belyaev and A. Pukhov, *private implementation of the leptoquark model*, .
- 11723 [533] A. Pukhov, *Calcchep 2.3: MSSM, structure functions, event generation, 1, and generation of matrix elements for other*
11724 *packages*, arXiv:hep-ph/0412191.
- 11725 [534] S. Ovin, X. Rouby, and V. Lemaitre, *Delphes, a framework for fast simulation of a generic collider experiment*,
11726 arXiv:0903.2225 [hep-ph].
- 11727 [535] H. Harari, *A Schematic Model of Quarks and Leptons*, Phys. Lett. **B86** (1979) 83.
- 11728 [536] H. Fritzsch and G. Mandelbaum, *Weak Interactions as Manifestations of the Substructure of Leptons and Quarks*,
11729 Phys. Lett. **B102** (1981) 319.
- 11730 [537] O. W. Greenberg and J. Sucher, *A Quantum Structure Dynamic Model of Quarks, Leptons, Weak Vector Bosons, and*
11731 *Higgs Mesons*, Phys. Lett. **B99** (1981) 339.
- 11732 [538] R. Barbieri, R. N. Mohapatra, and A. Masiero, *Compositeness and a Left-Right Symmetric Electroweak Model Without*
11733 *Broken Gauge Interactions*, Phys. Lett. **B105** (1981) 369–374.
- 11734 [539] U. Baur and K. H. Streng, *Colored lepton mass bounds from p anti-p collider data*, Phys. Lett. **B162** (1985) 387.
- 11735 [540] A. Celikel, M. Kantar, and S. Sultansoy, *A search for sextet quarks and leptogluons at the LHC*, Phys. Lett. **B443**
11736 (1998) 359–364.
- 11737 [541] S. S. M. Sahin and S. Turkoz, *Resonant production of color octet electrons at the LHeC*, . CERN-LHeC-Note-2010-015
11738 PHY.
- 11739 [542] H. Harari, *Composite models for quarks and leptons*, Phys. Rept. **104** (1984) 159.
- 11740 [543] E. Sauvan and N. Trinh, *Single production of excited fermions at LHeC*, . CERN-LHeC-Note-2010-011 PHY.
- 11741 [544] A. K. Ciftci, R. Ciftci, and S. Sultansoy, *Production of the Fourth SM Family Fermions at the Large Hadron Electron*
11742 *Collider*, . CERN-LHeC-Note-2010-016 PHY.
- 11743 [545] O. J. P. Eboli, S. M. Lietti, and P. Mathews, *Excited leptons at the CERN Large Hadron Collider*, Phys. Rev. **D65**
11744 (2002) 075003, arXiv:hep-ph/0111001.
- 11745 [546] H1 Collaboration, F. D. Aaron et al., *Search for Excited Electrons in ep Collisions at HERA*, Phys. Lett. **B666** (2008)
11746 131–139, arXiv:0805.4530 [hep-ex].
- 11747 [547] H1 Collaboration, F. D. Aaron et al., *A Search for Excited Neutrinos in e-p Collisions at HERA*, Phys. Lett. **B663**
11748 (2008) 382–389, arXiv:0802.1858 [hep-ex].
- 11749 [548] H1 Collaboration, F. D. Aaron et al., *Search for Excited Quarks in ep Collisions at HERA*, Phys. Lett. **B678** (2009)
11750 335–343, arXiv:0904.3392 [hep-ex].
- 11751 [549] OPAL Collaboration, G. Abbiendi et al., *Search for charged excited leptons in $e^+ e^-$ collisions at $s^{*}(1/2) = 183\text{-}GeV$*
11752 *- 209-GeV*, Phys. Lett. **B544** (2002) 57–72, arXiv:hep-ex/0206061.

- 11753 [550] DELPHI Collaboration, J. Abdallah et al., *Determination of the $e^+e^- \rightarrow \gamma\gamma$ cross-section at*
11754 *LEP 2*, Eur. Phys. J. **C37** (2004) 405–419, [arXiv:hep-ex/0409058](#).
- 11755 [551] D0 Collaboration, V. M. Abazov et al., *Search for excited electrons in $p\bar{p}$ collisions at $\sqrt{s} = 1.96$ -TeV*, Phys. Rev. **D77**
11756 (2008) 091102, [arXiv:0801.0877 \[hep-ex\]](#).
- 11757 [552] K. Hagiwara, D. Zeppenfeld, and S. Komamiya, *Excited Lepton Production at LEP and HERA*, Z. Phys. **C29** (1985)
11758 115.
- 11759 [553] F. Boudjema, A. Djouadi, and J. L. Kneur, *Excited fermions at e^+e^- and eP colliders*, Z. Phys. **C57** (1993) 425–450.
- 11760 [554] U. Baur, M. Spira, and P. M. Zerwas, *Excited quark and lepton production at hadron colliders*, Phys. Rev. **D42** (1990)
11761 815–824.
- 11762 [555] T. Kohler, *Exotic processes at HERA: The Event generator COMPOS*, . In *Hamburg 1991, Proceedings, Physics at
11763 HERA, vol. 3* 1526-1541. (see HIGH ENERGY PHYSICS INDEX 30 (1992) No. 12988).
- 11764 [556] C. Berger and P. Kandel, *A new generator for wide angle bremsstrahlung*, . Prepared for Workshop on Monte Carlo
11765 Generators for HERA Physics (Plenary Starting Meeting), Hamburg, Germany, 27-30 Apr 1998.
- 11766 [557] ATLAS Collaboration, G. Aad et al., *Search for excited leptons in proton-proton collisions at $\sqrt{s} = 7$ TeV with the*
11767 *ATLAS detector*, Phys.Rev. **D85** (2012) 072003, [arXiv:1201.3293 \[hep-ex\]](#). Long author list - awaiting processing.
- 11768 [558] CMS Collaboration, S. Chatrchyan et al., *A search for excited leptons in pp Collisions at $\sqrt{s} = 7$ TeV*, Phys.Lett.
11769 **B704** (2011) 143–162, [arXiv:1107.1773 \[hep-ex\]](#).
- 11770 [559] J. A. Aguilar-Saavedra, *A minimal set of top anomalous couplings*, Nucl. Phys. **B812** (2009) 181–204, [arXiv:0811.3842](#)
11771 [\[hep-ph\]](#).
- 11772 [560] ATLAS Collaboration, G. Aad et al., *Expected Performance of the ATLAS Experiment - Detector, Trigger and*
11773 *Physics*, [arXiv:0901.0512 \[hep-ex\]](#).
- 11774 [561] *ATLAS detector and physics performance. Technical design report. Vol. 2*, . CERN-LHCC-99-15.
- 11775 [562] T. Han, K. Whisnant, B. L. Young, and X. Zhang, *Searching for $t \rightarrow c g$ at the Fermilab Tevatron*, Phys. Lett. **B385**
11776 (1996) 311–316, [arXiv:hep-ph/9606231](#).
- 11777 [563] E. Malkawi and T. M. P. Tait, *Top-Charm Strong Flavour-Changing Neutral Currents at the Tevatron*, Phys. Rev. **D54**
11778 (1996) 5758–5762, [arXiv:hep-ph/9511337](#).
- 11779 [564] T. M. P. Tait and C. P. Yuan, *Anomalous t - c - g coupling: The connection between single top production and top decay*,
11780 Phys. Rev. **D55** (1997) 7300–7301, [arXiv:hep-ph/9611244](#).
- 11781 [565] T. Han, M. Hosch, K. Whisnant, B.-L. Young, and X. Zhang, *Single top quark production via FCNC couplings at*
11782 *hadron colliders*, Phys. Rev. **D58** (1998) 073008, [arXiv:hep-ph/9806486](#).
- 11783 [566] T. M. P. Tait and C. P. Yuan, *Single top quark production as a window to physics beyond the standard model*, Phys.
11784 Rev. **D63** (2001) 014018, [arXiv:hep-ph/0007298](#).
- 11785 [567] J. J. Liu, C. S. Li, L. L. Yang, and L. G. Jin, *Single top quark production via SUSY-QCD FCNC couplings at the*
11786 *CERN LHC in the unconstrained MSSM*, Nucl. Phys. **B705** (2005) 3–32, [arXiv:hep-ph/0404099](#).
- 11787 [568] J. J. Liu, C. S. Li, L. L. Yang, and L. G. Jin, *Next-to-leading order QCD corrections to the direct top quark production*
11788 *via model-independent FCNC couplings at hadron colliders*, Phys. Rev. **D72** (2005) 074018, [arXiv:hep-ph/0508016](#).
- 11789 [569] J.-j. Cao, G.-l. Liu, J. M. Yang, and H.-j. Zhang, *Top-quark FCNC productions at LHC in topcolor-assisted technicolor*
11790 *model*, Phys. Rev. **D76** (2007) 014004, [arXiv:hep-ph/0703308](#).
- 11791 [570] J. J. Cao et al., *SUSY-induced FCNC top-quark processes at the Large Hadron Collider*, Phys. Rev. **D75** (2007)
11792 075021, [arXiv:hep-ph/0702264](#).
- 11793 [571] P. M. Ferreira, R. B. Guedes, and R. Santos, *Combined effects of strong and electroweak FCNC effective operators in*
11794 *top quark physics at the CERN LHC*, Phys. Rev. **D77** (2008) 114008, [arXiv:0802.2075 \[hep-ph\]](#).
- 11795 [572] J. M. Yang, *Probing New Physics from Top Quark Processes at LHC: A Mini Review*, Int. J. Mod. Phys. **A23** (2008)
11796 3343, [arXiv:0801.0210 \[hep-ph\]](#).
- 11797 [573] X.-F. Han, L. Wang, and J. M. Yang, *Top quark FCNC decays and productions at LHC in littlest Higgs model with*
11798 *T -parity*, [arXiv:0903.5491 \[hep-ph\]](#).
- 11799 [574] J. Cao, Z. Heng, L. Wu, and J. M. Yang, *R -parity violating effects in top quark FCNC productions at LHC*, Phys. Rev.
11800 **D79** (2009) 054003, [arXiv:0812.1698 \[hep-ph\]](#).
- 11801 [575] V. F. Obraztsov, S. R. Slabospitsky, and O. P. Yushchenko, *Search for anomalous top quark interaction at LEP-2*
11802 *collider*, Phys. Lett. **B426** (1998) 393–402, [arXiv:hep-ph/9712394](#).
- 11803 [576] T. Han and J. L. Hewett, *Top charm associated production in high-energy e^+e^- collisions*, Phys. Rev. **D60** (1999)
11804 074015, [arXiv:hep-ph/9811237](#).
- 11805 [577] J.-j. Cao, Z.-h. Xiong, and J. M. Yang, *SUSY-induced top quark FCNC processes at linear colliders*, Nucl. Phys. **B651**
11806 (2003) 87–105, [arXiv:hep-ph/0208035](#).

- 11807 [578] J. A. Aguilar-Saavedra, *Top flavor-changing neutral interactions: Theoretical expectations and experimental detection*, Acta Phys. Polon. **B35** (2004) 2695–2710, [arXiv:hep-ph/0409342](#).
- 11808
- 11809 [579] A. T. Alan and A. Senol, *Single top production at HERA and THERA*, Europhys. Lett. **59** (2002) 669–673, [arXiv:hep-ph/0202119](#).
- 11810
- 11811 [580] A. A. Ashimova and S. R. Slabospitsky, *The Constraint on FCNC Coupling of the Top Quark with a Gluon from ep Collisions*, Phys. Lett. **B668** (2008) 282–285, [arXiv:hep-ph/0604119](#).
- 11812
- 11813 [581] H1 Collaboration, F. D. Aaron et al., *Search for Single Top Quark Production at HERA*, Phys. Lett. **B678** (2009) 450–458, [arXiv:0904.3876 \[hep-ex\]](#).
- 11814
- 11815 [582] O. Cakir and S. A. Cetin, *Anomalous single top quark production at the CERN LHC*, J. Phys. **G31** (2005) N1–N8.
- 11816 [583] G. A. Moortgat-Pick et al., *The role of polarized positrons and electrons in revealing fundamental interactions at the linear collider*, Phys. Rept. **460** (2008) 131–243, [arXiv:hep-ph/0507011](#).
- 11817
- 11818 [584] G. Brandt, *Single Top production*, talk given at the 1st CERN-ECFA-NuPECC Workshop on the LHeC, Divonne-les-Bains, France, 1-3 September 2008.
- 11819
- 11820 [585] I. T. Cakir, O. Cakir, and S. Sultansoy, *Anomalous Single Top Production at the Large Hadron electron Collider Based gamma p Collider*, Phys. Lett. **B685** (2010) 170–173, [arXiv:0911.4194 \[hep-ph\]](#).
- 11821
- 11822 [586] CMS Collaboration, G. L. Bayatian et al., *CMS technical design report, volume II: Physics performance*, J. Phys. **G34** (2007) 995–1579.
- 11823
- 11824 [587] O. Cakir, *Anomalous production of top quarks at CLIC + LHC based γp colliders*, J. Phys. **G29** (2003) 1181–1192, [arXiv:hep-ph/0301116](#).
- 11825
- 11826 [588] R. Ciftci, *Production of Excited Quark at γp Collider Based on the Large Hadron Electron Collider*, . CERN-LHeC-Note-2010-017 PHY.
- 11827
- 11828 [589] O. Çakır and M. Şahin, *Diquarks in γp Collisions at LHeC*, . CERN-LHeC-Note-2010-012 PHY.
- 11829 [590] CMS Collaboration, V. Khachatryan et al., *Search for Dijet Resonances in 7 TeV pp Collisions at CMS*, Phys. Rev. Lett. **105** (2010) 211801, [arXiv:1010.0203 \[hep-ex\]](#).
- 11830
- 11831 [591] A. Atre, M. Carena, T. Han, and J. Santiago, *Heavy Quarks Above the Top at the Tevatron*, Phys. Rev. **D79** (2009) 054018, [arXiv:0806.3966 \[hep-ph\]](#).
- 11832
- 11833 [592] A. Atre, G. Azuelos, M. Carena, T. Han, E. Ozcan, et al., *Model-Independent Searches for New Quarks at the LHC*, JHEP **1108** (2011) 080, [arXiv:1102.1987 \[hep-ph\]](#).
- 11834
- 11835 [593] O. Cakir, *Single Production of Fourth Family Quarks at LHeC*, . CERN-LHeC-Note-2010-013 PHY.
- 11836 [594] The ATLAS Collaboration, *An update to the combined search for the Standard Model Higgs boson with the ATLAS detector at the LHC using up to 4.9 fb⁻¹ of pp collision data at $\sqrt{s} = 7$ TeV*, ATLAS-CONF-2012-019.
- 11837
- 11838 [595] The CMS Collaboration, *Combined results of searches for a Higgs boson in the context of the standard model and beyond-standard models*, CMS-PAS-HIG-12-008.
- 11839
- 11840 [596] M. Dührssen, *Measurement of Higgs boson parameters at the LHC*, Czech. J. Phys. **55** (2005) B145–B152.
- 11841 [597] J. M. Butterworth, A. R. Davison, M. Rubin, and G. P. Salam, *Jet substructure as a new Higgs search channel at the LHC*, Phys. Rev. Lett. **100** (2008) 242001, [arXiv:0802.2470 \[hep-ph\]](#).
- 11842
- 11843 [598] T. Han and B. Mellado, *Higgs Boson Searches and the H_bbar Coupling at the LHeC*, Phys. Rev. **D82** (2010) 016009, [arXiv:0909.2460 \[hep-ph\]](#).
- 11844
- 11845 [599] B. Jager, *Next-to-leading order QCD corrections to Higgs production at a future lepton-proton collider*, Phys.Rev. **D81** (2010) 054018, [arXiv:1001.3789 \[hep-ph\]](#).
- 11846
- 11847 [600] J. Blumlein, G. van Oldenborgh, and R. Ruckl, *QCD and QED corrections to Higgs boson production in charged current e p scattering*, Nucl.Phys. **B395** (1993) 35–59, [arXiv:hep-ph/9209219 \[hep-ph\]](#).
- 11848
- 11849 [601] J. Alwall et al., *MadGraph/MadEvent v4: The New Web Generation*, JHEP **09** (2007) 028, [arXiv:0706.2334 \[hep-ph\]](#).
- 11850 [602] PGS. <http://www.physics.ucdavis.edu/~conway/research/software/pgs/pgs4-general.htm>.
- 11851 [603] M. Duehrssen, *Study of Higgs bosons in the WW final state and development of a fast calorimeter simulation for the ATLAS experiment*, CERN-THESIS-2010-061.
- 11852
- 11853 [604] T. Plehn, D. L. Rainwater, and D. Zeppenfeld, *Determining the structure of Higgs couplings at the LHC*, Phys. Rev. Lett. **88** (2002) 051801, [arXiv:hep-ph/0105325](#).
- 11854
- 11855 [605] S. S. Biswal, R. M. Godbole, B. Mellado, and S. Raychaudhuri, *Azimuthal Angle Probe of Anomalous HWW Couplings at the LHeC*, [arXiv:1203.6285 \[hep-ph\]](#). LateX2e, 9 pages, 3 eps figures.
- 11856
- 11857 [606] T. L. Team, *LEP Design Report, Vol.III, LEP2*, CERN-AC/96-01-LEP2 (1996).
- 11858 [607] K. Hirata and E. Keil, *Barycentre motion of beams due to beam-beam interaction in asymmetric ring colliders*, Nuclear Instruments and Methods in Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment **292** (1990) no. 1, 156 – 168.
- 11859
- 11860 <http://www.sciencedirect.com/science/article/B6TJM-470F1H3-M/2/ff1b42fa7c847256a9e6c3245d3335d5>.
- 11861

- 11862 [608] S. Myers, *Overlap Knock-Out Resonances with Colliding Bunched Beams in the CERN ISR*, Nuclear Science, IEEE
11863 Transactions on **26** (1979) 3574–3576.
- 11864 [609] J. Jowett, *Summary of the main parameters for the ring-ring option*, LHeC Workshop 2008, Divonne-les-Bains, France
11865 (2008) . <http://indico.cern.ch/contributionDisplay.py?contribId=44&sessionId=18&confId=31463>.
- 11866 [610] J. Jowett, *Ions in 2012*, Chamonix Workshop 2012 (2012) .
11867 <https://indico.cern.ch/conferenceOtherViews.py?view=standard&confId=164089>.
- 11868 [611] W. Kriens, *Neue Kontrollen für die Frequenzsteuerung und Synchronisation bei Hera p*, September, 2000.
11869 **HERA-Seminar in Grömitz**.
- 11870 [612] *Private Communication with Sylvain Weisz*, .
- 11871 [613] Miriam Fitterer and Anke-Susanne Mueller (KIT, Karlsruhe) and Oliver Sim Bruening and Helmut Burkhardt and
11872 Bernhard Johannes Holzer and John M. Jowett (CERN, Geneva) and Max Klein (The University of Liverpool,
11873 Liverpool), *LHeC Ring-Ring Lattice*, IPAC'12 (2012) .
- 11874 [614] CERN-AC/96-01. <http://cdsweb.cern.ch/record/314187>. LEP Design Report. Vol. 3. LEP 2.
- 11875 [615] U. Schneekloth, *Boundary Conditions for the Interaction Region Design*, talk given at the 1st CERN-ECFA-NuPECC
11876 Workshop on the LHeC, Divonne-les-Bains, France, 1-3 September 2008.
- 11877 [616] M. Bieler, E. Gianfelice-Wendt, G. Hoffstaetter, B. Holzer, S. Levonian, et al., *Recent and past experiences with*
11878 *beam-beam effects at HERA*, . Workshop On Beam-Beam Effects In Large Hadron Colliders.
- 11879 [617] F. Zimmermann, R. Brinkmann, J. Feikes, S. Herb, A. Piwinski, et al., *First experience with the asymmetric beam-beam*
11880 *interaction in the 1991 luminosity runs of HERA*, .
- 11881 [618] J. Rossbach and R. Brinkmann, *HERA Straight Sections for Head-On Electron-Proton Interactions*, IEEE
11882 Trans.Nucl.Sci. **32** (1985) 1647–1649.
- 11883 [619] e. Schneekloth, U., *The HERA luminosity upgrade*, .
- 11884 [620] T. Abe, K. Akai, M. Akemoto, A. Akiyama, M. Arinaga, et al., *Compensation of the Crossing Angle with Crab Cavities*
11885 *at KEKB*, Conf.Proc. **C070625** (2007) 27, [arXiv:0706.3248](https://arxiv.org/abs/0706.3248) [physics.ins-det].
- 11886 [621] A. Verdier, *Alignment optics for LHC*, LHC Project Note 325 (2003) .
- 11887 [622] R. Appleby, *IRSYN*, (2010) .
- 11888 [623] S. Russenschuck, *Magnet Options for Q1 and Q2 (Ring-Ring and Linac-Ring)*, 3rd CERN-ECFA-NuPECC Workshop
11889 on the LHeC (2010) .
- 11890 [624] N. Bernard, *Analytic Method to Calculate the Power Produced by Synchrotron Radiation in a Quadrupole Magnet*,
11891 CERN LHeC Note 2 (2010) .
- 11892 [625] H. Wiedemann, *Synchrotron Radiation*, Springer-Verlag Berlin Heidelberg (2003) .
- 11893 [626] I. B. et al., *Study of beam-induced backgrounds in the ZEUS detector from 2002 HERA running*, (2002) .
- 11894 [627] S. Russenschuck, *Private Communication*, (2010) .
- 11895 [628] E. Young, S. Henderson, R. Littauer, B. McDaniel, T. Pelaia, et al., *Collisions of Resonantly Coupled Round Beams at*
11896 *the Cornell Electron Positron Storage Ring (CESR)*, .
- 11897 [629] D. Brandt, W. Herr, M. Meddahi, and A. Verdier, *Is LEP beam-beam limited at its highest energy?*, .
- 11898 [630] R. e. a. Alemany, *Head-on beam-beam tune shifts with high brightness beams in the LHC*, **CERN-ATS-Note-2011-029** MD.
- 11899 [631] M. Meddahi, *Effets faisceau-faisceau dans le collisionneur proton-antiproton du SPS*, . PhD Thesis, Universite de Paris
11900 VII.
- 11901 [632] M. Bassetti and G. Erskine, *Closed Expression for the electrical field of a two-dimensional Gaussian charge*,
11902 **CERN-ISR-TH/80-06**.
- 11903 [633] R. e. a. Alemany, *Test of Luminosity leveling with separated collisions* , **CERN-ATS-Note-2011-028** MD.
- 11904 [634] *LHC beam-beam studies webpage*. <http://lhc-beam-beam.web.cern.ch/lhc-beam-beam/>.
- 11905 [635] J. Jowett, *Heavy Ions in 2011 and Beyond*, . Chamonix 2011 Workshop on LHC Performance, Chamonix, France,
11906 CERN-ATS-2011-005.
- 11907 [636] E. Benedikt, M., E. Collier, P., E. Mertens, V., E. Poole, J., and E. Schindl, K., *LHC Design Report. 3. The LHC*
11908 *injector chain*, . CERN-2004-003-V-3.
- 11909 [637] E. Bruning, Oliver S., E. Collier, P., E. Lebrun, P., E. Myers, S., E. Ostojic, R., et al., *LHC Design Report. 1. The LHC*
11910 *Main Ring*, . CERN-2004-003-V-1.
- 11911 [638] J. e. a. Stovall, *On the Feasibility of Accelerating Deuterons in Linac4*, CERN-sLHC-Project-Note-0032 (2011) .
- 11912 [639] C. Hill, D. Kuchler, R. Scrivens, and F. Wenander, *Studies on ECR4 for the CERN ion program*, Rev.Sci.Instrum. **73**
11913 (2002) 564–566.

- 11914 [640] D. Barber and G. Ripken in *Handbook of Accelerator Physics and Engineering*, A. Chao and M. Tigner, eds. World
11915 Scientific, first ed., 2006. third printing.
- 11916 [641] D. Barber et al., *Several articles*, in *Proc. ICFA Workshop on Quantum Aspects of Beam Physics*. World Scientific,
11917 Monterey, CA, USA, 1999.
- 11918 [642] A. Sokolov and I. Ternov Sov. Phys. Dokl. **8** (1964) no. 12, 1203.
- 11919 [643] J. Jackson, *Classical Electrodynamics*. Wiley & Sons, third ed., 1998.
- 11920 [644] Y. Derbenev and A. Kondratenko Sov. Phys. JETP **37** (1973) 968.
- 11921 [645] S. Mane Phys. Rev. **A36** (1987) 105–130.
- 11922 [646] G. Hoffstätter, M. Vogt, and D. Barber Phys. Rev. ST Accel. Beams **11** (1999) no. 2, 114001.
- 11923 [647] D. Barber, G. Hoffstätter, and M. Vogt in *Proc. 14th Int. Spin Physics Symp.* AIP Conf. Proc. 570 (2001), 2000.
- 11924 [648] V. Baier and V. Katkov Sov. Phys. JETP **25** (1967) 944.
- 11925 [649] V. Baier, V. Katkov, and V. Strakhovenko Sov. Phys. JETP **31** (1970) 908.
- 11926 [650] R. Assmann et al. in *Proc. Part. Accel. Conf.*, p. 2999 and page 3002. New York, NY, USA, 1999.
- 11927 [651] D. Barber et al. Phys. Lett. **343B** (1995) 436.
- 11928 [652] S. Mane Nucl.Inst.Meth. **A292** (1990) 52.
- 11929 [653] S. Mane Nucl.Inst.Meth. **A321** (1992) 21.
- 11930 [654] D. Barber. SLICKTRACK is the extended version of SLICK [655] which includes Monte-Carlo spin-orbit tracking using
11931 the mathematical structures of SLICK.
- 11932 [655] D. Barber. SLICK is a thick lens version of SLIM [640] by D.P. Barber using the formalism of [917].
- 11933 [656] Y. Derbenev and H. Grote Tech. Rep. SL/Note 95-37, CERN, 1995.
- 11934 [657] B. Montague Physics Reports **113** (1984) .
- 11935 [658] D. Forkel-Wirth, *Radioprotection issues after 20 years of LHC operation*, . EUCARD-HE-LHC'10 AccNet
11936 miniworkshop on the HE-LHC, Valetta, Malta, 2010, tbp.
- 11937 [659] *LHC data base LHCLJ-3U0014*, .
- 11938 [660] *LHC data base LHCLJ-3U0012*, .
- 11939 [661] *LHC-LJ-EC-0002*, .
- 11940 [662] P. Bandyopadhyay and C. Segre, *Mucal on the web*. <http://www.csrri.iit.edu/mucal.html>.
- 11941 [663] K. Wittenburg, *The PIN-diode beam loss monitor system at HERA*, . AIP Conference Proceedings Volume 546, 9th
11942 Beam Instrumentation Workshop, Boston, MA, USA.
- 11943 [664] K. Aulenbacher, B. Aune, J. Aysto, J. Baldy, e. Burkhardt, H., et al., *ELFE at CERN: Conceptual design report*, .
- 11944 [665] D. Brandt and A. Hofmann, *Does a high Q(s) raise the maximum intensity to be accumulated in LEP?*, .
- 11945 [666] <http://www-conf.slac.stanford.edu/facetusers/spring2010/Instrument.asp>. Nominal FACET Beam Parameters,
11946 Spring 2010 User workshop.
- 11947 [667] CERN-LEP/TH/83-29. <http://cdsweb.cern.ch/record/98881>. LEP Design Report. Vol. 1. The LEP Injector Chain.
- 11948 [668] CERN-LEP/84-01. <http://cdsweb.cern.ch/record/102083>. LEP Design Report. Vol. 2. The LEP Main Ring.
- 11949 [669] A. Akay, H. Karadeniz, and S. Sultansoy, *Review of Linac-Ring Type Collider Proposals*, Int. Journal of Modern
11950 Physics A **25** (2010) 4589–4602.
- 11951 [670] F. Ruggiero and F. Zimmermann, *Luminosity Optimization near the Beam-Beam Limit by Increasing Bunch Length or
11952 Crossing Angle*, PRST-AB **5** (2002) 061101.
- 11953 [671] F. Zimmermann et al., *Linac-LHC ep Collider Options*, Proc. EPAC'08 Genoa (2008) 2847–2849.
- 11954 [672] D. Schulte, *LHeC Ring-Linac Lattice and Beam Dynamics*, 3rd CERN-ECFA-NuPECC LHeC Workshop
11955 Chavannes-de-Bogis, December 2010 (2010) .
- 11956 [673] F. Zimmermann, K. Thompson, and R. Helm, *Electron-Electron Luminosity in the Next Linear Collider*,
11957 Int. J. Mod. Phys. A **13** (1998) 2443–2454.
- 11958 [674] H. Braun et al., *CLIC 2008 Parameters*, CLIC-Note-764 (2008) .
- 11959 [675] H. Aksakal, A. K. Ciftci, Z. Nergiz, D. Schulte, and F. Zimmermann, *Conversion efficiency and luminosity for gamma
11960 proton colliders based on the LHC-CLIC or LHC-ILC QCD Explorer scheme*, Nucl. Instrum. Meth. **A576** (2007)
11961 287–293, arXiv:hep-ex/0612041.
- 11962 [676] N. Phinney, N. Toge, and N. Walker, *LC Reference Design Report Volume 3 - Accelerator*, (2007) , arXiv:0712.2361
11963 [physics.acc-ph].
- 11964 [677] F. Gerigk et al., *Conceptual Design of the SPL II*, CERN-2006-006 (2006) .

- 11965 [678] C. Mayes and G. Hoffstaetter, *Cornell Energy Recovery Linac Lattice and Layout*, Proc. IPAC'10 Kyoto (2010) .
- 11966 [679] V. Litvinenko, *Future Electron-Hadron Colliders*, Proc. IPAC'10 Kyoto (2010) .
- 11967 [680] G. Neil, *Free Electron Lasers from THz to X-rays*, Invited Talk at UPHUK4, Bodrum, Turkey, 30 August 2010 (2010) .
- 11968 [681] Linnecar, T. and Tückmantel, J., *Private communication*, 28 May 2008, (2008) .
- 11969 [682] O. Napoly, *Private communication*, 6th EuCARD Steering Meeting, Malta, 12–13 October 2010., (2010) .
- 11970 [683] E. Ciapala, *RF for the LHeC*, 3rd CERN-ECFA-NuPECC LHeC Workshop Chavannes-de-Bogis, December 2010 (2010)
11971 .
- 11972 [684] J. Tuckmantel, , Comment at 2nd RFTech meeting, PSI, Villigen, 2–3 December 2010 (2010) .
- 11973 [685] V. Litvinenko and I. Ben-Zvi, *Private communications*, (2010) .
- 11974 [686] I. Ben-Zvi, *Private communications*, 16 November 2010, (2010) .
- 11975 [687] D. Tommasini, *RR+RL Magnets*, 3rd CERN-ECFA-NuPECC LHeC Workshop Chavannes-de-Bogis, December 2010
11976 (2010) .
- 11977 [688] J. Skrabacz, *Optimizing Cost and Minimizing Energy Loss in the Recirculating Race-Track Design of the LHeC
11978 Electron Linac*, CERN-AB-Note-2008-043 (2008) .
- 11979 [689] A. Bogacz, *LHeC Recirculator with Energy Recovery – Beam Optics Choices*, JLAB-TN-10-040 (2010) .
- 11980 [690] D. Schulte and F. Zimmermann, *Private discussions*, (2010) .
- 11981 [691] D. Schulte, *Private communication*, (2010) .
- 11982 [692] D. Schulte and F. Zimmermann, *QCD Explorer Based on LHC and CLIC-1*, Proc. EPAC'04, Lucerne,
11983 CERN-AB-2004-079, and CLIC Note 608 (2004) .
- 11984 [693] K. Ohmi, R. Calaga, W. Hofle, R. Tomas, and F. Zimmermann, *Beam-Beam Effects with External Noise in LHC*,
11985 Proc. PAC07, Albuquerque (2007) 1496.
- 11986 [694] F. Zimmermann et al., *First Bunch Length Studies in the SLC South Final Focus*, Proc. EPAC 1998 Stockholm (1998)
11987 487.
- 11988 [695] C. Adolphsen et al., *Pulse-to-Pulse Stability Issues at the SLC*, Proc. IEEE PAC 1995 Dallas (1995) .
- 11989 [696] P. Chen and K. Yokoya, *Disruption Effects from the Interaction of Round $e+e-$ Beams*, Phys. Rev. D **38** (1988) 987.
- 11990 [697] M. Yamamoto, M. and Kuwahara, *Superlattice Photocathode Development for Low Emittance*, Photocathode Physics for
11991 Photoinjectors Workshop, BNL, October 2010 (2010) .
- 11992 [698] I. Bailey, *A Helical Undulator Based Positron Source for the International Linear Collider*, Proc. PoS HEP2005 (2006)
11993 368.
- 11994 [699] S. Araki et al., *Conceptual Design of a Polarised Positron Source Based on Laser Compton Scattering*,
11995 CARE/ELAN-Document-2005-013, CLIC Note 639, KEK Preprint 2005-60, LAL 05-94 (2005) , physics/0509016.
- 11996 [700] F. Zimmermann et al., *Stacking Simulations for Compton Positron Sources of Future Linear Colliders*, Proc. PAC'09
11997 Vancouver (2009) .
- 11998 [701] V. Litvinenko, *Recirculating Linac*, 2nd CERN-ECFA-NuPECC workshop on LHeC, Divonne-les-Bains (2009) .
- 11999 [702] I. Ginzburg, G. Kotkin, V. Serbo, and V. Telnov, *Colliding γe and $\gamma\gamma$ Beams Based on the Single Pass Accelerators (of
12000 VLEPP Type)*, Nucl. Instr. & Meth. **205** (1983) 47.
- 12001 [703] H. Burkhardt and V. Telnov, *CLIC 3-TeV Photon Collider Options*, CERN-SL-2002-013-AP, CLIC-Note-508 (2002) .
- 12002 [704] T. N. D. Group, *NLC Zeroth-Order Design Report for the Next Linear Collider, Appendix B*, LBNL-5424, SLAC-474,
12003 Appendix B (1996) .
- 12004 [705] V. Telnov, *Principles of Photon Colliders*, NIM A **355** (1995) 3–18.
- 12005 [706] Klemz, G. and Mönig, K. and Will, I. , *Design Study of an Optical Cavity for a Future Photon-Collider at ILC*, NIM A
12006 **564** (2006) 212.
- 12007 [707] H. Aksakal, Z. Nergiz, et al., *γp Option for LHeC*, Draft Note, October 2010 (2010) .
- 12008 [708] K. Yokoya, *CAIN: A Computer Simulation Code for the Interaction of Electron, Positron, Gamma Beams and Strong
12009 Lasers*, available at <http://lcdev.kek.jp/yokoya/CAIN> (2010) .
- 12010 [709] C. Johnstone, *Local chromaticity correction of the LHC*, PAC97 (1997) .
- 12011 [710] S. Fartoukh, *Optics Challenges and Solutions for the LHC Insertion Upgrade Phase I*, LHC Project Report 0038
12012 (2010) .
- 12013 [711] S. Fartoukh, *Towards the LHC Upgrade using the LHC well-characterized technology*, LHC Project Report 0049 (2010) .
- 12014 [712] P. Raimondi and A. Seryi, *A Novel final focus design for future linear colliders*, Phys. Rev. Lett. **86** (2001) 3779.

- 12015 [713] J. A. et al, *Local Chromatic Correction Scheme and Crab-waist Collisions for an Ultra-low beta* at the LHC*,
12016 Proc. IPAC2012, New Orleans, MOPPC002 (2012) .
- 12017 [714] A. Gaddi, *Passive isolation*, Presented in IWLC 2010 (2010) .
- 12018 [715] J. Abelleira, R. Tomás, S. Russenschuck, F. Zimmermann, and B. N., *Design Status of the Linac-Ring Interaction
12019 Region*, Proc. IPAC2011 San Sebastian (2011) 2796.
- 12020 [716] J. Abelleira, H. García, R. Tomás, and F. Zimmermann, *Final-Focus optics for the LHeC electron beamline*,
12021 Proc. IPAC2012 New Orleans (2012) .
- 12022 [717] R. Tomas, *MAPCLASS: A Code to Optimize High Order Aberrations*, CERN AB-Note-2006-017 (ABP) (2010) .
- 12023 [718] D. Schulte, *Beam-Beam Simulations with GUINEA-PIG*, ICAP98 (1998) .
- 12024 [719] A. Bogacz, *LHeC Recirculator with Energy Recovery Beam Optics Choices*, CERN-LHeC-Note-2010-009 ACC,
12025 JLAB-TN-10-040 (2010) .
- 12026 [720] Y. Hao, K. D., V. Litvinenko, V. Ptitsyn, D. Trbojevic, and N. Tsoupas, *ERL Option for LHeC*,
12027 CERN-LHeC-Note-2010-010 ACC (2010) .
- 12028 [721] D. Schulte, *Multi-bunch calculations in the CLIC main linac*, PAC2009 Vancouver (2009) .
- 12029 [722] D. Schulte, *Simulation package based on PLACET*, Proceedings PAC01, Chicago (2001) .
- 12030 [723] *International Linear Collider Reference Design Report*, ILC-Report-2007-001 (2007) .
- 12031 [724] I. Bazarov and G. Hoffstaetter, *Multi-pass Beam-breakup: Theory and Calculation*, EPAC2004 Lucerne (2004) .
- 12032 [725] D. Schulte, , to be published .
- 12033 [726] M. Schuh, , private communication .
- 12034 [727] F. Zimmermann, J. Byrd, A. Chao, S. Heifets, M. Minty, T. Raubenheimer, J. Seeman, S. G., and J. Thomson,
12035 *Experiments on the fast beam-ion instability at the ALS*, Report SLAC-PUB-7617 (1997) .
- 12036 [728] G. Hoffstaetter and M. Liepe, , NIM A **557** (2006) 205–212.
- 12037 [729] N. Hilleret, *Private communication*, .
- 12038 [730] B. Holzer, *Private communication*, .
- 12039 [731] V. Baglin, *Private communication*, .
- 12040 [732] M. Ehrlichmann and G. Hoffstaetter, *Collimating Touschek Particles in an Energy Recovery Linear Accelerator*,
12041 Proc. PAC09 Vancouver (2009) .
- 12042 [733] Y. Miyahara, *A New Formula For The Lifetime Of A Round Beam Caused By The Touschek Effect In An Electron
12043 Storage Ring*, Jap. J. Appl. Phys. **24** (1985) L742.
- 12044 [734] A. Piwinski, *Private communication*, (2000) .
- 12045 [735] L. Thomas, , Phil. Mag, **3** (1927) 1.
- 12046 [736] I. Alekseev et al., *Design Manual - Polarized Proton Collider at RHIC*, Nucl. Inst. and Meth. A **499** (2003) 392.
- 12047 [737] V. Ptitsin, *Symmetric Designs for Helical Spin Rotators at RHIC*, AGS/RHIC/SN No. 5 (1996) .
- 12048 [738] M. Woods, *The Scanning Compton polarimeter for the SLD experiment*, SLAC-PUB-7319 (1996) .
- 12049 [739] *Topical Meeting on Positrons for the LHeC, May 2011*. <http://cern.ch/lhec>.
- 12050 [740] L. R. et al, *The CLIC Electron and Positron Polarized Sources*, . In *XIIIth International Workshop on Polarized
12051 Sources (PST2009)*, Ferrara, Italy.
- 12052 [741] E. Bulyak, J. Urakawa, and F. Zimmermann, *Asymmetric laser radiant cooling in storage rings (report mop064)*, .
12053 <http://www.bnl.gov/pac11/>. In *PAC 2011, New York, U.S.A., March 28 – April 1, 2011*.
- 12054 [742] PosiPol collaboration, S. A. et al, *Conceptual Design of a Polarised Positron Source Based on Laser Compton
12055 Scattering*, physics/0509016. In *Proc. 2005 International Linear Collider Physics and Detector Workshop and 2nd
12056 ILC Accelerator Workshop, 14–27 August 2005, Snowmass, Colorado*.
- 12057 [743] PosiPol collaboration, F. Z. et al, *CLIC Polarized Positron Source Based on Laser Compton Scattering*, . In *Proc. 10th
12058 European Particle Accelerator Conference (EPAC 06)*, 26–30 June 2006, Edinburgh, Scotland.
- 12059 [744] PosiPol collaboration, L. R. et al, *The CLIC Positron Source Based on Compton Schemes*, . In *Proc. 23rd Particle
12060 Accelerator Conference (PAC09)*, 4–8 May 2009, Vancouver, British Columbia, Canada.
- 12061 [745] V. Balakin and A. Mikhailichenko, *Conversion System for Obtaining Highly Polarized Electrons and Positrons*,
12062 Novosibirsk INP 79–85.
- 12063 [746] A. Mikhailichenko, *ILC Undulator Based Positron Source, Tests and Simulations*, . In *Proc. 22nd Particle Accelerator
12064 Conference (PAC07)*, 25–29 June 2007, Albuquerque, New Mexico.
- 12065 [747] L. Rinolfi, *LHeC Concepts for Positrons*, . Brainstorming Meeting for an LHeC Positron Source, CERN, 20 May 2011.

- 12066 [748] O. e. a. Dadoun, *Study of an hybrid positron source using channeling for CLIC*, CLIC Note 808.
- 12067 [749] P. Sievers. Private communication.
- 12068 [750] E. Bulyak., *Optimal $\gamma \rightarrow e^+$ conversion target for Compton sources.*, . In report at ALCPG11, Eugene, Oregon U.S.A. 21/03/2011.
- 12070 [751] T. Erber, *High-Energy Electronmagnetic Conversion Processes in Intense Magnetic Fields*, . Reviews of Modern Physics, vol. 38, no. 4.
- 12072 [752] P. Chen and R. Palmer, *Coherent Pair Creation as a positron source for Linear Colliders*, . SLAC-PUB-5966.
- 12073 [753] C. B. et al, *Studies of Nonlinear QED in collisions of 46.6 GeV Electrons with Intense Laser Pulses*, . Phys.Rev.D60:092004.
- 12075 [754] R. Ostojic and T. Taylor, *Conceptual design of a 70 mm aperture quadrupole for the LHC insertions*, . IEEE Transactions on Applied Superconductivity.
- 12077 [755] M. Tawada, H. Nakayama, and K. Satoh, *Special quadrupole magnets for KEKB interaction region*, . Proceedings of EPAC 2000, Vienna.
- 12079 [756] R. Gupta, *Modular Program and Modular Design for LARP Quadrupoles*, . Magnet Note, Superconducting Magnet Division, Brookhaven National Laboratory.
- 12081 [757] S. Russenschuck, *Field computation for accelerator magnets: Analytical and numerical methods for electromagnetic design and optimization*, .
- 12083 [758] J. e. a. Parrell, *High Field Nb₃Sn conductor development at Oxford Superconductor Technology*, . IEEE Transactions on Applied Superconductivity.
- 12085 [759] A. Devred, E. Baynham, M. Chorowski, P. Fabbriatore, E. Garcia-Tabares, et al., *A Strategy for European superconducting accelerator magnet R&D aimed at LHC luminosity upgrade*, .
- 12087 [760] M. Giesch and J. Gourber, *THE BENDING MAGNET SYSTEM OF LEP*, .
- 12088 [761] R. C. D. Tommasini, M. Buzio, *Dipole Magnets for the LHeC Ring-Ring Option*, . MT-22 Marseille, France, Sept. 2011 [accepted for publication IEEE Trans. Appl.].
- 12090 [762] B. S. et al., *Novel Adjustable Permanent Magnet Quadrupoles for the CLIC Drive Beam Decelerator*, . MT-22 Marseille, France, Sept. 2011.
- 12092 [763] *Conceptual design of the SPL II, a high-power superconducting H- linac at CERN*, . CERN (series) 2006-006.
- 12093 [764] F. e. a. Gerigk, *Choice of the optimum beta for the SPL cavities*, . CERN-sLHC-Project-Note-0001.
- 12094 [765] W. Weingarten, *Performance of superconducting cavities as required for the SPL*, . CERN-AB-2008-063.
- 12095 [766] *Some Aspects of 704 MHz Superconducting RF Cavities*. <http://cern.ch/rcalaga/PUBS/THPP0003.pdf>.
- 12096 [767] G. Neil, *Worldwide ERL R&D Overview Including JLAMP, BNL, and Cornell ERLs, Proceedings of LINAC10*. <http://accelconf.web.cern.ch/AccelConf/LINAC2010/papers/tu103.pdf>.
- 12098 [768] F. e. a. Zimmermann, *The Large Hadron-Electron Collider (LHeC) at the LHC*, Proc PAC'09 Vancouver 4233–4235. <http://accelconf.web.cern.ch/AccelConf/PAC2009/papers/fr1pbc05.pdf>.
- 12100 [769] F. e. a. Zimmermann, *Designs for a Linac-Ring LHeC*, Proc. IPAC'10 Kyoto 1611–1613. <http://accelconf.web.cern.ch/AccelConf/IPAC10/papers/tupeb039.pdf>.
- 12102 [770] V. Litvinenko, *Designs for a Linac-Ring LHeC*, 3rd CERN-ECFA-NuPECC LHeC Workshop Chavannes-de-Bogis, December 2010 .
- 12104 [771] R. e. a. Calaga, *in the proceedings of CARE-HHH08, Chavannes-de-Bogis, 2008*, .
- 12105 [772] R. e. a. Calaga, *in the proceeding of the LHC performance workshop 2010, Chamonix, 2010*, .
- 12106 [773] D. Brandt, H. Burkhardt, M. Lamont, S. Myers, and J. Wenninger, *Accelerator physics at LEP*, Rept.Prog.Phys. **63** (2000) 939–1000.
- 12108 [774] B. Dehning, A. Melissinos, F. Perrone, C. Rizzo, and G. von Holtey, *Scattering of high-energy electrons off thermal photons*, Phys.Lett. **B249** (1990) 145–148.
- 12110 [775] C. Yin Vallgren, A. Ashraf, S. Calatroni, P. Chiggiato, P. Costa Pinto, et al., *Low Secondary Electron Yield Carbon Coatings for Electron-cloud Mitigation in Modern Particle Accelerators*, .
- 12112 [776] C. Hauviller, *Development of composite tubes for experimental vacuum chambers of colliders*, .
- 12113 [777] V. Parma and U. Wagner, *SPL Cryogenic System Studies*, CERN Presentation 2008.
- 12114 [778] B. Petersen. Private communication, Bernd Petersen, DESY.
- 12115 [779] S. Claudet, G. Ferlin, F. Miller, and L. Tavian, *1.8 K Refrigeration units for the LHC: Performance Assessment of Pre-series Units*, . ICEC 2004, Beijing.
- 12117 [780] M. Barnes, F. Caspers, L. Ducimetiere, N. Garrel, and T. Kroyer, *The beam screen for the LHC injection kicker magnets*, .

- 12119 [781] E. Carlier, U. Jansson, R. Jung, V. Mertens, S. Peraire, et al., *The LEP beam dumping system*, .
- 12120 [782] R. Appleby, L. Keller, T. W. Markiewicz, A. Seryi, D. Walz, et al., *The International linear collider beam dumps*,
12121 [arXiv:physics/0601103](https://arxiv.org/abs/physics/0601103) [physics].
- 12122 [783] J. Amann, R. Arnold, A. Seryi, D. Walz, K. Kulkarni, et al., *Design of an 18 MW Beam Dump for 500 GeV*
12123 *Electron/Positron Beams at an ILC*, .
- 12124 [784] S. Myers, *LHC: Machine Status and Prospects for the Short, Medium and Long Term*, Invited Plenary Talk at EPS,
12125 **Grenoble**, July 2011.
- 12126 [785] M. Klein, *The High Luminosity Design study for the LHC*, [Https://espace.cern.ch/hl-lhc/default.aspx](https://espace.cern.ch/hl-lhc/default.aspx).
- 12127 [786] E. Ciapala. Private communication, Edmund Ciapala, CERN, BE-RF group.
- 12128 [787] A. Yamamoto. <http://www.fnal.gov/directorate/ILCPAC/ILCPACNov2010/Yamamoto---cavityindustrialization.pdf>.
12129 Talk at ILC-PAC Eugene November 2010.
- 12130 [788] V. Mertens. Private communication, Volker Mertens, CERN, TE-ABT group.
- 12131 [789] J. Osborne. Private communication, John Osborne, CERN, GS-SE group.
- 12132 [790] *The XFEL construction calendar*. <http://www.xfel.eu/projekt/kalender/>.
- 12133 [791] M. Peininger. www.cockcroft.ac.uk/events/CSSA/presentations/Michael%20Peiniger.pdf. Talk at Cockcroft
12134 Institute seminar April 2011.
- 12135 [792] R. Ruber. www.isv.uu.se/~ziemann/teaching/ht10/ESS.pdf. Uppsala University.
- 12136 [793] *LINAC4 Project Page*. <http://linac4-project.web.cern.ch/linac4-project/>.
- 12137 [794] R. Ischebeck. www.cockcroft.ac.uk/events/eslsxvi/proceedings/psixfelischebeck.pdf. Talk given at the Sixteenth
12138 European Synchrotron Light Source workshop, England, Daresbury Laboratory, Crockcroft Institute, November 2008.
- 12139 [795] A. Mazzacane, *The 4th concept detector for the ILC*, Nucl.Instrum.Meth. **A617** (2010) 173–176.
- 12140 [796] M. Klein and R. Yoshida, *Collider Physics at HERA*, Prog.Part.Nucl.Phys. **61** (2008) 343–393, [arXiv:0805.3334](https://arxiv.org/abs/hep-ex/0805.3334)
12141 [hep-ex].
- 12142 [797] e. Pire, Bernard, e. Cirelli, Marco, e. Colas, Paul, e. Djouadi, Abdelhak, e. Lounis, Abdenour, et al., *High energy*
12143 *physics. Proceedings, 35th International Conference, ICHEP 2010, Paris, France, July 22-28, 2010*, .
- 12144 [798] e. Buchmuller, W. and e. Ingelman, G., *Physics at HERA. Proceedings, Workshop, Hamburg, Germany, October 29-30,*
12145 *1991. Vol. 1-3*, .
- 12146 [799] R. Gluckstern, *Uncertainties in track momentum and direction, due to multiple scattering and measurement errors*,
12147 Nucl.Instrum.Meth. **24** (1963) 381–389.
- 12148 [800] M. Regler, W. Mitaroff, M. Valentan, R. Fruhwirth, and R. Hofler, *The 'LiC Detector Toy' program*, J.Phys.Conf.Ser.
12149 **119** (2008) 032034.
- 12150 [801] P. Adragna, C. Alexa, K. Anderson, A. Antonaki, A. Arabidze, et al., *Measurement of pion and proton response and*
12151 *longitudinal shower profiles up to 20 nuclear interaction lengths with the ATLAS tile calorimeter*, Nucl.Instrum.Meth.
12152 **A615** (2010) 158–181.
- 12153 [802] ATLAS Collaboration, G. Aad et al., *The ATLAS Experiment at the CERN Large Hadron Collider*, JINST **3** (2008)
12154 S08003.
- 12155 [803] B. Holzer, *Private communication*, .
- 12156 [804] ATLAS Collaboration, *ATLAS central solenoid: Technical design report*, . Hardcopy at DESY.
- 12157 [805] ATLAS Collaboration, *ATLAS magnet system: Technical design report*, . Hardcopy at DESY.
- 12158 [806] CMS, *the Compact Muon Solenoid. Muon technical design report*, .
- 12159 [807] CMS Collaboration, G. Acquistapace et al., *CMS, the magnet project: Technical design report*, .
- 12160 [808] P. Allport, "Conventional Silicon Pixel/Strip Tracker", talk at 3rd CERN-ECFA-NuPECC Workshop on LHeC,
12161 *Chavannes-de-Bogis, Switzerland, 12. November 2010*, 2010. <http://indico.cern.ch/getFile.py/access?contribId=50&sessionId=9&resId=0&materialId=slides&confId=105142>.
- 12162 [809] E. Koffeman, *Gossip: Gaseous pixels*, Nucl.Instrum.Meth. **A582** (2007) 858–860.
- 12163 [810] H. van der Graaf, "Gossip and GridPix at LHeC", talk at 3rd CERN-ECFA-NuPECC Workshop on LHeC,
12164 *Chavannes-de-Bogis, Switzerland, 12. November 2010*, 2010.
12165 <http://indico.cern.ch/materialDisplay.py?contribId=51&sessionId=9&materialId=slides&confId=105142>.
- 12166 [811] H. van der Graaf, *Gaseous detectors*, Nucl.Instrum.Meth. **A628** (2011) 27–30.
- 12167 [812] R. Horisberger, "Tracking at Phase II, Pixel, Strixel & Strips", *CMS Tracker Week, La Biodola, Isola d'Elba 27. May*
12168 *2010*, 2010.
- 12169 [813] R. Horisberger, "Considerations for future Large Pixel Systems", talk *CMS Pixel Detector Upgrade Workshop, FNAL*
12170 *10. October 2006*, 2006.
- 12171

- 12172 [814] J. Brau, *The Science and Challenges for Future Detector Development in High Energy Physics*, .
- 12173 [815] N. Wermes, "Silicon Pixel Detectors for Tracking", talk at 1st CERN-ECFA Workshop on LHeC, Divonne-les-Bains,
12174 France, 1-3 September 2008, 2008.
12175 <http://indico.cern.ch/contributionDisplay.py?sessionId=19&contribId=63&confId=31463>.
- 12176 [816] ATLAS and CMS Collaborations, N. Hessey, *Overview and electronics needs of ATLAS and CMS high luminosity
12177 upgrades*, . [http:
12178 //indico.cern.ch/getFile.py/access?contribId=140&sessionId=21&resId=0&materialId=paper&confId=21985](http://indico.cern.ch/getFile.py/access?contribId=140&sessionId=21&resId=0&materialId=paper&confId=21985).
- 12179 [817] M. Nessi, "The Detector Upgrade and the Requirements on the Upgrade Scenarios", 2009.
12180 <http://cdsweb.cern.ch/record/1304568>.
- 12181 [818] C. Haber, "Lecture Silicon Detectors: Principles and Technology", talk at TIPP, Chicago, USA, June 2011, 2011.
12182 [https://indico.cern.ch/getFile.py/access?contribId=529&sessionId=25&resId=0&materialId=slides&confId=
12183 102998](https://indico.cern.ch/getFile.py/access?contribId=529&sessionId=25&resId=0&materialId=slides&confId=102998).
- 12184 [819] D. Christian, "Semiconductor Detectors Overview", talk at TIPP, Chicago, USA, June 2011, 2011. [https://indico.
12185 cern.ch/getFile.py/access?contribId=527&sessionId=22&resId=1&materialId=slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=527&sessionId=22&resId=1&materialId=slides&confId=102998).
- 12186 [820] S. Cihanger, "Silicon sensor R&D for an upgraded CMS Tracker in HL-LHC", talk at TIPP, Chicago, USA, June
12187 2011, 2011. [https://indico.cern.ch/getFile.py/access?contribId=107&sessionId=22&resId=0&materialId=
12188 slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=107&sessionId=22&resId=0&materialId=slides&confId=102998).
- 12189 [821] A. Affolder, "Silicon Strip Detectors for the ATLAS sLHC Upgrade", talk at TIPP, Chicago, USA, June 2011, 2011.
12190 [https://indico.cern.ch/getFile.py/access?contribId=31&sessionId=22&resId=1&resmaterialId=slides\
12191 &confId=102998](https://indico.cern.ch/getFile.py/access?contribId=31&sessionId=22&resId=1&resmaterialId=slides&confId=102998).
- 12192 [822] A. Macchiolo, "Performance of Silicon n-in-p Pixel Detectors irradiated up to 5^{15} n_{eq}/cm^2 for the future ATLAS
12193 Upgrades", talk at TIPP, Chicago, USA, June 2011, 2011. [https:
12194 //indico.cern.ch/getFile.py/access?contribId=33&sessionId=22&resId=0&materialId=slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=33&sessionId=22&resId=0&materialId=slides&confId=102998).
- 12195 [823] U. Parzefall, "Silicon for High-Luminosity Tracking Detectors - Recent RD50 Results", talk at TIPP, Chicago, USA,
12196 June 2011, 2011. [https://indico.cern.ch/getFile.py/access?contribId=203&sessionId=22&resId=3\
12197 &materialId=slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=203&sessionId=22&resId=3&materialId=slides&confId=102998).
- 12198 [824] I. Rubinskiy, "An EUDET/AIDA pixel beam telescope for detector development", talk at TIPP, Chicago, USA, June
12199 2011, 2011. [https:
12200 //indico.cern.ch/getFile.py/access?contribId=25&sessionId=22&resId=0&materialId=slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=25&sessionId=22&resId=0&materialId=slides&confId=102998).
- 12201 [825] M. Bomben, "Recent progress of the ATLAS Planar Pixel Sensor R&D Project", talk at TIPP, Chicago, USA, June
12202 2011, 2011. [https://indico.cern.ch/getFile.py/access?contribId=436&sessionId=22&resId=0&materialId=
12203 slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=436&sessionId=22&resId=0&materialId=slides&confId=102998).
- 12204 [826] M. Mikuz, "Diamond for high energy radiation and particle detection", talk at TIPP, Chicago, USA, June 2011, 2011.
12205 [https://indico.cern.ch/getFile.py/access?contribId=463&sessionId=22&resId=1&materialId=slides&confId=
12206 102998](https://indico.cern.ch/getFile.py/access?contribId=463&sessionId=22&resId=1&materialId=slides&confId=102998).
- 12207 [827] A. Mac Raighne, "3D pixel devices; design, production and characterisation in test beams", talk at TIPP, Chicago,
12208 USA, June 2011, 2011. [https://indico.cern.ch/getFile.py/access?contribId=249&sessionId=22&resId=1\
12209 &materialId=slides&confId=102998](https://indico.cern.ch/getFile.py/access?contribId=249&sessionId=22&resId=1&materialId=slides&confId=102998).
- 12210 [828] A. Ferrari, P. Sala, A. Fasso, and J. Ranft, *FLUKA: A multi-particle transport code (Program version 2005)*, .
- 12211 [829] G. Battistoni, S. Muraro, P. R. Sala, F. Cerutti, A. Ferrari, et al., *The FLUKA code: Description and benchmarking*,
12212 AIP Conf.Proc. **896** (2007) 31–49.
- 12213 [830] M. Garcia-Sciveres, "ATLAS pixels for 2017/18", talk at ACES 2011 Workshop, CERN 9. March 2011.
- 12214 [831] K.K.Gan, F.Vasey, T.Weidberg "Lessons Learned and to be Learned from LHC", talk at Joint ATLAS-CMS Working
12215 Group on Opto-Electronics for SLHC, Report from Sub-Group A, Joint ATLAS/CMS NOTE,
12216 ATL-COM-ELEC-2007-001. <https://edms.cern.ch/document/882775/3.8>.
- 12217 [832] A. Bell, E. Castro, R. Hall-Wilton, W. Lange, W. Lohmann, et al., *Fast Beam Conditions Monitor BCM1F for the
12218 CMS Experiment*, Nucl.Instrum.Meth. **A614** (2010) 433–438, [arXiv:0911.2480](https://arxiv.org/abs/0911.2480) [physics.ins-det].
- 12219 [833] L. Fernandez Hernandez, D. Chong, R. Gray, C. Ilgner, A. Macpherson, et al., *Development of a CVD diamond beam
12220 condition monitor for CMS at the Large Hadron Collider*, Nucl.Instrum.Meth. **A552** (2005) 183–188.
- 12221 [834] A. Macpherson, *Beam Condition Monitoring and radiation damage concerns of the experiment*, talk at ICHEP 2010,
12222 Paris, France, .
- 12223 [835] D. Chong, L. Fernandez-Hernando, R. Gray, C. J. Ilgner, A. Oh, et al., *Validation of synthetic diamond for a beam
12224 condition monitor for the Compact Muon Solenoid experiment*, IEEE Trans.Nucl.Sci. **54** (2007) 182–185.
- 12225 [836] D. Green, *How physics defines the LHC environment and detectors*, Int.J.Mod.Phys. **A25** (2010) 1279–1313.
- 12226 [837] J. Freeman, *Innovations for the CMS HCAL*, Int.J.Mod.Phys. **A25** (2010) 2421–2436.

- 12227 [838] L. Mandelli, *The ATLAS electromagnetic calorimeters: Features and performance*, Int.J.Mod.Phys. **A25** (2010)
12228 1739–1760.
- 12229 [839] P. Bloch, *The CMS electromagnetic calorimeter: Crystals and APD productions*, Mod.Phys.Lett. **A25** (2010)
12230 1027–1045.
- 12231 [840] K. Anderson, T. Del Prete, E. Fullana, J. Huston, C. Roda, et al., *TileCal: The hadronic section of the central ATLAS
12232 calorimeter*, Int.J.Mod.Phys. **A25** (2010) 1981–2003.
- 12233 [841] ATLAS Collaboration, A. Airapetian et al., *ATLAS calorimeter performance Technical Design Report*, .
- 12234 [842] H1 Collaboration, A. Babaev, *Performance of the H1 liquid argon calorimeter*, .
- 12235 [843] H1 Collaboration, I. Abt et al., *The H1 detector at HERA*, Nucl.Instrum.Meth. **A386** (1997) 310–347.
- 12236 [844] M. Fleischer, M. Keller, K. Meier, O. Nix, G. Schmidt, et al., *Performance and upgrade of H1 calorimeters: LAr
12237 calorimeter, SpaCal and VLQ*, .
- 12238 [845] C. Issever, *The calibration of the H1 liquid argon calorimeter*, .
- 12239 [846] H1 collaboration, C. Schwanenberger, *The Jet calibration in the H1 liquid argon calorimeter*, arXiv:physics/0209026
12240 [physics].
- 12241 [847] J. Seehafer, *Simulation of hadronic showers in the H1 liquid argon calorimeter with the simulation programs GHEISHA
12242 and CALOR*, .
- 12243 [848] C. Kiesling, A. Dubak, and B. Olivier, *The liquid argon jet trigger of the H1 experiment at HERA*, Nucl.Instrum.Meth.
12244 **A623** (2010) 513–515.
- 12245 [849] ATLAS Electromagnetic Barrel Liquid Argon Calorimeter Group, B. Aubert et al., *Construction, assembly and tests of
12246 the ATLAS electromagnetic barrel calorimeter*, Nucl.Instrum.Meth. **A558** (2006) 388–418.
- 12247 [850] O. Gildemeister, F. Nessi-Tedaldi, and M. Nessi, *An economic concept for a barrel hadron calorimeter with iron
12248 scintillator sampling and WLS-fiber readout*, .
- 12249 [851] I. Golutvin, B. Borgia, F. Carminati, M. Della Negra, S. Giani, et al., *A Silicon hadron calorimeter module operated in
12250 a strong magnetic field with VLSI readout for LHC*, .
- 12251 [852] OPAL Collaboration, B. Anderson et al., *The OPAL silicon - tungsten calorimeter front end electronics*, IEEE
12252 Trans.Nucl.Sci. **41** (1994) 845–852.
- 12253 [853] J. Adams, G. Bashindzhagian, V. Zatsepin, M. Merkin, M. Panasyuk, et al., *The silicon matrix as a charge detector for
12254 the ATIC experiment*, Instrum.Exp.Tech. **44** (2001) 455–461.
- 12255 [854] V. Zatsepin, J. Adams, H. Ahn, G. Bashindzhagian, K. Batkov, et al., *Experience of application of silicon matrix as a
12256 charge detector in the ATIC experiment*, .
- 12257 [855] V. Bonvicini, M. Boezio, E. Haslum, D. Matveev, M. Pearce, et al., *New concepts in silicon calorimetry for space
12258 experiments*, Nucl.Instrum.Meth. **A518** (2004) 186–187.
- 12259 [856] V. Bonvicini, A. Vacchi, V. Dzhordzhadze, R. Seto, E. Kistenev, et al., *Silicon-tungsten calorimeter for the forward
12260 direction in the PHENIX experiment at RHIC*, IEEE Trans.Nucl.Sci. **52** (2005) 874–878.
- 12261 [857] D. Strom "Silicon Tungsten Calorimetry", talk at SLAC Meeting, 8 January 2004, 2004.
- 12262 [858] D. M. Strom, R. Frey, M. Breidenbach, D. Freytag, N. Graf, et al., *Fine grained silicon-tungsten calorimetry for a
12263 linear collider detector*, IEEE Trans.Nucl.Sci. **52** (2005) 868–873.
- 12264 [859] GEANT4 Collaboration, S. Agostinelli et al., *GEANT4: A Simulation toolkit*, Nucl.Instrum.Meth. **A506** (2003)
12265 250–303.
- 12266 [860] A. Kaidalov and K. Ter-Martirosian, *Pomeron as Quark-Gluon Strings and Multiple Hadron Production at SPS
12267 Collider Energies*, .
- 12268 [861] A. Cravero and F. Gianotti, *Uniformity of response and energy resolution of a large scale prototype of the Barrel
12269 Accordion calorimeter*, . ATLAS internal note CAL-NO-33, RD3, Note 54 (1994), (Page 22, Fig.17).
- 12270 [862] Y. Kulchitsky, P. Tsiareshka, and V. Vinogradov, *Electron Energy Resolution of the ATLAS TILECAL Modules with
12271 Fit Filter Method (July 2002 test beam)*, . ATL-TILECAL-PUB-2006-004; ATL-COM-TILECAL-2006-003, Geneva,
12272 CERN, p48, 2006 (Page 29, Fig. 19).
- 12273 [863] ATLAS/Tile Calorimeter Collaboration, I. Efthymiopoulos, *ATLAS barrel hadron calorimeter: The module 0
12274 experience*, .
- 12275 [864] M. Barbi "Calorimetry - 3rd course", talk at TRIUMF Summer Institute, July 2007, 2007.
- 12276 [865] C. Leroy and P. Rancoita, *Physics of cascading shower generation and propagation in matter: Principles of
12277 high-energy, ultrahigh-energy and compensating calorimetry*, Rept.Prog.Phys. **63** (2000) 505–606.
- 12278 [866] G. Barbiellini, G. Cecchet, J. Hemery, F. Lemeilleur, C. Leroy, et al., *Energy resolution and longitudinal shower
12279 development in a Si/ W electromagnatic calorimeter*, Nucl.Instrum.Meth. **A235** (1985) 55.
- 12280 [867] J.-C. Brient and H. Videau, *The Calorimetry at the future e+ e- linear collider*, arXiv:hep-ex/0202004 [hep-ex].

- 12281 [868] V. Morgunov, *Calorimetry design with energy-flow concept (imaging detector for high-energy physics)*, .
- 12282 [869] S. R. Magill, *Innovations in ILC detector design using a particle flow algorithm approach*, New J.Phys. **9** (2007) 409.
- 12283 [870] R. Wigmans, *Recent results from the DREAM project*, J.Phys.Conf.Ser. **160** (2009) 012018.
- 12284 [871] J. Hauptman, *Particle physics experiments at high energy colliders*, .
- 12285 [872] G. Gaudio and R. Wigmans, *Dual-Readout Calorimetry for High-Quality Energy Measurements*, CERN-SPSC-2011-021/SPSC-SR-086/June 2011.
- 12287 [873] G. Mikenberg, *The ATLAS muon spectrometer*, Mod.Phys.Lett. **A25** (2010) 649–667.
- 12288 [874] F. Gasparini, *The CMS muon detector: From the first thoughts to the final design*, Int.J.Mod.Phys. **A25** (2010) 3121–3154.
- 12290 [875] J. Burnens, R. de Oliveira, G. Glonti, O. Pizzirusso, V. Polychronakos, et al., *A spark-resistant bulk-micromegas chamber for high-rate applications*, arXiv:1011.5370 [physics.ins-det]. * Temporary entry *.
- 12291
- 12292 [876] R. Santonico et al., *A new generation of RPCs to be used as muon trigger detectors at the super-LHC*, .
- 12293 <http://indico.cern.ch/materialDisplay.py?contribId=427&sessionId=16&materialId=slides&confId=102998>.
- 12294 [877] B. Bittner, J. Dubbert, S. Horvat, M. Kilgenstein, O. Kortner, et al., *Development of precision muon drift tube detectors for the high-luminosity upgrade of the LHC*, Nucl.Phys.Proc.Suppl. **215** (2011) 143–146.
- 12295
- 12296 [878] N. Amram, G. Bella, Y. Benhammou, M. A. Diaz, E. Duchovni, E. Etzion, A. Hershenhorn, A. Klier, N. Lupu,
- 12297 G. Mikenberg, D. Milstein, Y. Munwes, O. Sasaki, M. Shoa, V. Smakhtin, and U. Volkmann, *Position resolution and*
- 12298 *efficiency measurements with large scale Thin Gap Chambers for the super LHC*, Nuclear Instruments and Methods in
- 12299 Physics Research Section A: Accelerators, Spectrometers, Detectors and Associated Equipment **628** (2011) no. 1, 177 –
- 12300 181. <http://www.sciencedirect.com/science/article/pii/S0168900210015019>. VCI 2010 - Proceedings of the 12th
- 12301 International Vienna Conference on Instrumentation.
- 12302 [879] V. Smakhtin, G. Mikenberg, A. Klier, Y. Rozen, E. Duchovni, E. Kajamovitz, and A. Hershenhorn, *Thin Gap Chamber*
- 12303 *upgrade for SLHC: Position resolution in a test beam*, Nuclear Instruments and Methods in Physics Research Section
- 12304 A: Accelerators, Spectrometers, Detectors and Associated Equipment **598** (2009) no. 1, 196 – 200.
- 12305 <http://www.sciencedirect.com/science/article/pii/S0168900208012242>. Instrumentation for Colliding Beam Physics
- 12306 - Proceedings of the 10th International Conference on Instrumentation for Colliding Beam Physics.
- 12307 [880] Fourth (“4th”) Detector, G. Drobychev et al., *Letter of Intent from the Fourth Detector (“4th”) Collaboration at the*
- 12308 *International Linear Collider*, . <http://www.4thconcept.org/4LoI.pdf>.
- 12309 [881] R. Brun and F. Rademakers, *ROOT - An Object Oriented Data Analysis Framework*, *Proceedings AIHENP’96*
- 12310 *Workshop, Lausanne, Sep. 1996*, Nucl. Inst. & Meth. in Phys. Res. A **389** (1997) 81–86.
- 12311 [882] R. Chytracek, J. McCormick, W. Pokorski, and S. G., *Geometry Description Markup Language for Physics Simulation*
- 12312 *and Analysis Applications*, IEEE Trans. Nucl. Sci. **Vol. 53, Issue: 5, Part 2** 2892–2896.
- 12313 [883] V. V. Serbo, *Status of AIDA and JAS 3*, Nuclear Instruments and Methods in Physics Research Section A:
- 12314 Accelerators, Spectrometers, Detectors and Associated Equipment **502** (2003) no. 2-3, 663 – 665.
- 12315 <http://www.sciencedirect.com/science/article/pii/S0168900203005370>. Proceedings of the VIII International
- 12316 Workshop on Advanced Computing and Analysis Techniques in Physics Research.
- 12317 [884] A. Vasilescu and L. G., *Displacement damage in Silicon for neutrons, protons, pions, and electrons*, .
- 12318 <http://sesam.desy.de/members/gunnar/NIEL-allr.ps>.
- 12319 [885] F. Carminati and A. Morsch, *Simulation in ALICE*, arXiv:physics/0306092 [physics]. On behalf of the ALICE
- 12320 Offline Project.
- 12321 [886] ALICE Collaboration, I. Hrivnacova et al., *The Virtual Monte Carlo*, arXiv:cs/0306005 [cs-se].
- 12322 [887] ALICE Collaboration, I. Gonzalez Caballero, F. Carminati, A. Morsch, and I. Hrivnacova, *ALICE experience with*
- 12323 *GEANT4*, arXiv:physics/0306025 [physics].
- 12324 [888] J. Hauptman, *Particle Identification in 4th*, arXiv:0812.3571 [hep-ex].
- 12325 [889] H1 Collaboration, T. Ahmed et al., *Experimental Study of Hard Photon Radiation Processes at HERA*, Z. Phys. **C66**
- 12326 (1995) 529–542.
- 12327 [890] V. Andreev et al., *The new H1 luminosity system for HERA II*, Nucl. Instrum. Meth. **A494** (2002) 45–50.
- 12328 [891] ZEUS Luminosity Group, J. Andruszkow et al., *Luminosity measurement in the ZEUS experiment*, Acta Phys. Polon.
- 12329 **B32** (2001) 2025–2058.
- 12330 [892] ZEUS Collaboration, S. D. Paganis, *The upgraded luminosity system for the ZEUS experiment*, Int. J. Mod. Phys.
- 12331 **A16S1C** (2001) 1147–1149.
- 12332 [893] G. A. Schuler and H. Spiesberger, *DJANGO: The Interface for the event generators HERACLES and LEPTO*, . In
- 12333 *Hamburg 1991, Proceedings, Physics at HERA, vol. 3* 1419–1432. (see HIGH ENERGY PHYSICS INDEX 30 (1992)
- 12334 No. 12988).

- 12335 [894] A. Courau and P. Kessler, *QED Compton scattering in high-energy electron - proton collisions*, Phys. Rev. **D46** (1992)
12336 117–124.
- 12337 [895] S. Levonian, *H1LUMI - A Fast Simulation Package for the H1 Luminosity System*, . H1 internal note h1-0493-287
12338 (1993); <http://www.desy.de/~levonian/papers/H1lumi.pdf>.
- 12339 [896] R. Brun, M. Caillat, M. Maire, G. N. Patrick, and L. Urban, *The GEANT3 electromagnetic shower program and a
12340 comparison with the EGS3 code*, . CERN-DD/85/1.
- 12341 [897] SLD Collaboration, R. King, *A Precise measurement of the left-right asymmetry of Z boson production at the SLAC
12342 Linear Collider*, Nucl.Phys.Proc.Suppl. **37B** (1994) 23–31.
- 12343 [898] D. Barber, H. Bremer, M. Boge, R. Brinkmann, W. Bruckner, et al., *The HERA polarimeter and the first observation
12344 of electron spin polarization at HERA*, Nucl.Instrum.Meth. **A329** (1993) 79–111.
- 12345 [899] S. Boogert, M. Hildreth, D. Kafer, J. List, K. Monig, et al., *Polarimeters and Energy Spectrometers for the ILC Beam
12346 Delivery System*, JINST **4** (2009) P10015, [arXiv:0904.0122](https://arxiv.org/abs/0904.0122) [[physics.ins-det](#)].
- 12347 [900] S. Baudrand, M. Bouchel, V. Brisson, R. Chiche, M. Jacquet, et al., *A High Precision Fabry-Perot Cavity Polarimeter
12348 at HERA*, JINST **5** (2010) 06005, [arXiv:1005.2741](https://arxiv.org/abs/1005.2741) [[physics.ins-det](#)].
- 12349 [901] M. Beckmann, A. Borisov, S. Brauksiepe, F. Burkart, H. Fischer, et al., *The Longitudinal polarimeter at HERA*,
12350 Nucl.Instrum.Meth. **A479** (2002) 334–348, [arXiv:physics/0009047](https://arxiv.org/abs/physics/0009047) [[physics](#)].
- 12351 [902] V. Brisson, R. Chiche, M. Jacquet, C. Pascaud, V. Soskov, et al., *Per Mill Level Control of the Circular Polarisation of
12352 the Laser Beam for a Fabry-Perot Cavity Polarimeter at HERA*, JINST **5** (2010) 06006, [arXiv:1005.2742](https://arxiv.org/abs/1005.2742)
12353 [[physics.ins-det](#)].
- 12354 [903] ZEUS FNC Group, S. Bhadra et al., *Design and test of a forward neutron calorimeter for the ZEUS experiment*, Nucl.
12355 Instrum. Meth. **A394** (1997) 121–135, [arXiv:hep-ex/9701015](https://arxiv.org/abs/hep-ex/9701015).
- 12356 [904] R. Arnaldi et al., *The Zero Degree Calorimeters for the ALICE Experiment*, Nucl. Instrum. Meth. **A581** (2007)
12357 397–401.
- 12358 [905] ALICE Collaboration, N. De Marco et al., *Commissioning and calibration of the zero degree calorimeters for the ALICE
12359 experiment*, J. Phys. Conf. Ser. **160** (2009) 012060.
- 12360 [906] ATLAS Collaboration, *Zero degree calorimeters for ATLAS*, . CERN-LHCC-2007-01.
- 12361 [907] O. Grachov et al., *Commissioning of the CMS zero degree calorimeter using LHC beam*, [arXiv:1008.1157](https://arxiv.org/abs/1008.1157)
12362 [[physics.ins-det](#)].
- 12363 [908] LHCf Collaboration, O. Adriani et al., *The LHCf detector at the CERN Large Hadron Collider*, JINST **3** (2008) S08006.
- 12364 [909] R. Chechik, A. Breskin, C. Shalem, and D. Mormann, *Thick GEM-like hole multipliers: Properties and possible
12365 applications*, Nucl. Instrum. Meth. **A535** (2004) 303–308, [arXiv:physics/0404119](https://arxiv.org/abs/physics/0404119).
- 12366 [910] V. Inshakov et al., *Development of detector active element based on thgem*, [arXiv:0906.4441](https://arxiv.org/abs/0906.4441) [[physics.ins-det](#)].
- 12367 [911] CMS, O. Grachov et al., *Status of zero degree calorimeter for CMS experiment*, AIP Conf. Proc. **867** (2006) 258–265,
12368 [arXiv:nucl-ex/0608052](https://arxiv.org/abs/nucl-ex/0608052).
- 12369 [912] *RD52 Experiment*, http://greybook.cern.ch/programmes/experiments/r_d/RD52.html.
- 12370 [913] N. Akchurin and R. Wigmans, *Hadron Calorimetry*, Nucl. Instrum. Meth. **A666** (2012) 80–97.
- 12371 [914] R. Wigmans, *private communication*.
- 12372 [915] FP420 R and D Collaboration, M. Albrow et al., *The FP420 R&D Project: Higgs and New Physics with forward
12373 protons at the LHC*, JINST **4** (2009) T10001, [arXiv:0806.0302](https://arxiv.org/abs/0806.0302) [[hep-ex](#)].
- 12374 [916] P. Taels, *Studie van de acceptantie en resolutie van een protonspectrometer bij de LHeC*, . University of Antwerp
12375 Bachelor thesis.
- 12376 [917] H. Mais and G. Ripken Tech. Rep. 83-62, DESY, 1983. Modern notation: replace \bar{n} by \bar{n}_0 .

12377 Chapter 15

12378 Appendix

12379 15.1 Scientific Advisory Committee

- 12380 Guido Altarelli (Roma)
- 12381 Sergio Bertolucci (CERN)
- 12382 Stan Brodsky (SLAC)
- 12383 Allen Caldwell (MPI Muenchen) - Chair
- 12384 Swapan Chattopadhyay (Cockcroft Institute)
- 12385 John Dainton (Liverpool)
- 12386 John Ellis (CERN)
- 12387 Jos Engelen (NWO)
- 12388 Joel Feltesse (Saclay)
- 12389 Roland Garoby (CERN)
- 12390 Rolf Heuer (CERN)
- 12391 Roland Horisberger (PSI)
- 12392 Young-Kee Kim (Fermilab)
- 12393 Aharon Levy (Tel Aviv)
- 12394 Lev Lipatov (St. Petersburg)
- 12395 Karlheinz Meier (Heidelberg)
- 12396 Richard Milner (MIT)
- 12397 Joachim Mnich (DESY)
- 12398 Steve Myers (CERN)
- 12399 Guenther Rosner (Glasgow)
- 12400 Alexander N. Skrinsky (INP Novosibirsk)
- 12401 Anthony Thomas (JLab)
- 12402 Steve Vigdor (Brookhaven)
- 12403 Ferdinand Willeke (Brookhaven)
- 12404 Frank Wilczek (MIT)
- 12405

12406

15.2 Steering Committee

12407 Oliver Bruening(CERN)
12408 John Dainton (Liverpool)
12409 Albert De Roeck (CERN)
12410 Stefano Forte (Milano)
12411 Max Klein (Liverpool) - Chair
12412 Paul Laycock (Liverpool)
12413 Paul Newman (Birmingham)
12414 Emmanuelle Perez (CERN)
12415 Wesley Smith (Wisconsin)
12416 Bernd Surrow (MIT)
12417 Katsuo Tokushuku (KEK)
12418 Urs Wiedemann (CERN)
12419 Frank Zimmermann (CERN)

12420 **15.3 Working Group Convenors**

12421 **Accelerator Design**

12422 Oliver Bruening (CERN)
12423 John Dainton (Liverpool)
12424

12425 **Interaction Region**

12426 Bernhard Holzer(CERN)
12427 Uwe Schneekloth (DESY)
12428 Pierre van Mechelen (Antwerpen)
12429

12430 **Detector Design**

12431 Peter Kostka (DESY)
12432 Alessandro Polini (Bologna)
12433 Rainer Wallny (Zurich)
12434

12435 **New Physics at Large Scales**

12436 Georges Azuelos (Montreal)
12437 Emmanuelle Perez (CERN)
12438 Georg Weiglein (Hamburg)
12439

12440 **Precision QCD and Electroweak**

12441 Olaf Behnke (DESY)
12442 Paolo Gambino (Torino)
12443 Thomas Gehrmann (Zurich)
12444 Claire Gwenlan (Oxford)
12445

12446 **Physics at High Parton Densities**

12447 Néstor Armesto (Santiago de Compostela)
12448 Brian A. Cole (Columbia)
12449 Paul R. Newman (Birmingham)
12450 Anna M. Stasto (PennState)

12451

15.4 CERN Referees

12452

Ring Ring Design

12453

Kurt Huebner (CERN)

12454

Alexander N. Skrinsky (INP Novosibirsk)

12455

Ferdinand Willeke (BNL)

12456

Linac Ring Design

12457

Reinhard Brinkmann (DESY)

12458

Andy Wolski (Cockcroft)

12459

Kaoru Yokoya (KEK)

12460

Energy Recovery

12461

Georg Hoffstaetter (Cornell)

12462

Ilan Ben Zvi (BNL)

12463

Magnets

12464

Neil Marks (Cockcroft)

12465

Martin Wilson (CERN)

12466

Interaction Region

12467

Daniel Pitzl (DESY)

12468

Mike Sullivan (SLAC)

12469

Detector Design

12470

Philippe Bloch (CERN)

12471

Roland Horisberger (PSI)

12472

Installation and Infrastructure

12473

Sylvain Weisz (CERN)

12474

New Physics at Large Scales

12475

Cristinel Diaconu (IN2P3 Marseille)

12476

Gian Giudice (CERN)

12477

Michelangelo Mangano (CERN)

12478

Precision QCD and Electroweak

12479

Guido Altarelli (Roma)

12480

Vladimir Chekelian (MPI Munich)

12481

Alan Martin (Durham)

12482

Physics at High Parton Densities

12483

Alfred Mueller (Columbia)

12484

Raju Venugopalan (BNL)

12485

Michele Arneodo (INFN Torino)