Overall plan view of hybrid prototype cable ass'y
298.000
6.000
4.500
4.500
37.000
69.900
107.000
111.100
117.000
Max flange thickness 30.500
Prototype length 5mm longer than really needed
Longest length = shortest+5mm +2mm tol
Shortest length + 2mm tolerance
Shortest length in plan view
Backplate on foot
Foot
Base
Standard length is baseplate 183 to centre of top connector
Longer length cable +4mm = 187
484.000 * see note
363.900 * see note
NOTE. This drawing shows a plan view of the layout but does not take into account the shortening of the cables by bending. The prototype cables have made overlong by 5mm and the dimensions in this box should be reduced by 10mm least 5mm. For test setups made shorter by at production cables will accommodated between the and the extra cable length base and the dummy card.
Nominal centre of clamp 177.000
Ø 1/8 inch
Ø 1/8 inch
5.500
322.100
277.900
330.400
318.900
213.900
158.900
14.100
3.000
Ø 3.0mm
edge of kapton circuit
85.6mm
85.6mm
60.4mm
25.4
25.4
63.000
7.5mm
7.5mm
Top Insert
Bottom Insert
58.0mm
58.0mm
Substrate 37.6mm R
PCB 34.6mm R
PCB Overlaps substrate by 3mm around cutout
1.0mm from substrate edge
2.0mm from PCB edge
Kapton PCBs overlap substrate by 1mm along this edge
Chamf. 5mm on substrate 3mm on PCB
Holes B - 2mm
Note: Holes A - 3mm, May be opened to 5mm if top hat inserts are required
Carbon fibre substrate REV K5.1
112.5mm
93.0mm
71.0mm
92.000
121.0mm
102.0mm
81.0mm
71.0mm