




A Precision Oscillation and Spectrum Experiment

Nathaniel Bowden

For the PROSPECT collaboration




Applied Antineutrino Physics 2016



Motivation


Directly test the hypothesis of a new oscillation with $\Delta m^2 \sim 1 \text{ eV}^2$,
i.e. oscillation length of few meters

Provide new tests of reactor models by making precision measurements of novel reactor spectra, esp. ^{235}U fuel



Approach to Short Baseline Reactor Measurements

Search for relative shape distortion in identical detector segments at different baselines \rightarrow eliminate reactor model dependence



Research reactors are *generally* preferable:

- Access to shortest baselines
- Often use ^{235}U fuel \rightarrow static fissile inventory
- Compact core dimensions provide greater sensitivity at $\Delta m^2 \sim 1 \text{ eV}^2$

But:


- Limited space for deployment
- Limited overburden
- Possibility of reactor generated background

PROSPECT Experiment Overview

Physics Objectives

1. Search for short-baseline oscillation at distances $<10\text{m}$
2. Precision measurement of ^{235}U reactor $\bar{\nu}_e$ spectrum

One Experiment, 2 Detectors



Phase I

One detector:

movable AD-I, $\sim 7\text{-}12\text{ m}$ baseline

Phase II

Two detectors:

movable AD-I, $\sim 7\text{-}12\text{ m}$ baseline

stationary AD-II, $\sim 15\text{-}19\text{ m}$ baseline


whitepaper, [arXiv:1309.7647](https://arxiv.org/abs/1309.7647)
PROSPECT collaboration

PROSPECT Physics Program
J. Phys. G, 43 113001; [arXiv:1512.02202](https://arxiv.org/abs/1512.02202)
PROSPECT collaboration

- movable detector enables systematic control, background checks, and increased physics reach
- phased approach provides path to greater sensitivity

PROSPECT Physics - Precision Oscillation Experiment

A model independent experimental approach to test for oscillation of eV-scale neutrinos



Phase I = AD-I, 3 years



Phase II = AD-I + AD-II, 3+3 years

Objectives

4 σ test of best fit after 1 year


>3 σ test of favored region after 3 years

5 σ test of allowed region after 3+3 years



PROSPECT Physics - Precision Spectrum Experiment

A precision measurement to address spectral unknowns




Phase I = AD-I only


Objectives

- Measurement of ^{235}U spectrum
- Compare different reactor models
- Compare different reactor cores


Testing ^{235}U $\bar{\nu}_e$ spectrum models



Large improvement on ILL




Different reactor cores






Experimental site: High Flux Isotope Reactor @ORNL

Compact Reactor Core




Power: 85 MW
Fuel: HEU (^{235}U)
Core shape: cylindrical
Size: $h=0.5\text{m}$ $r=0.2\text{m}$
Duty-cycle: 41%



- Established on-site operation
- User facility, easy 24/7 access
- Exterior access at grade
- Full utility access, incl. internet


PROSPECT Phase I Antineutrino Detector



- 3000L of ${}^6\text{Li}$ loaded liquid scintillator
- 10x12 segmented optical array, $\sim 15 \times 15 \times 120 \text{ cm}^3$ segment dimensions
- Double ended PMT readout, light guides, $\sim 4.5\%/\sqrt{E}$ resolution
- Low mass optical separators, minimal dead material
- Full volume calibration access
- Containment vessel, filled in place

Event Detection in PROSPECT AD-1

Event Identification



Prompt signal: 1-10 MeV positron from inverse beta decay (IBD)

Delay signal: ~0.5 MeV signal from neutron capture on ${}^6\text{Li}$

40 μs delayed n capture

inverse beta decay (IBD)
 γ -like prompt, n-like delay


fast neutron background
 recoil-like prompt, capture-like delay
 capture-like prompt, capture-like delay

accidental gamma background
 γ -like prompt, γ -like delay


Background reduction is key challenge

Background reduction through detector design & fiducialization

IBD event in segmented ${}^6\text{LiLS}$ detector



Pulse Shape Discrimination



PROSPECT Detector & Shielding Development

PROSPECT-0.1

Characterize LS

Aug 2014-Spring 2015

5cm length

0.1 liters

LS, $^6\text{LiLS}$



PROSPECT-2


Background studies

Dec 2014 - Aug 2015

12.5 length

1.7 liters

$^6\text{LiLS}$



multi-layer shielding

PROSPECT-20


*Segment characterization
Scintillator studies
Background studies*

Spring/Summer 2015

1m length

23 liters

LS, $^6\text{LiLS}$



local reactor shielding

PROSPECT-50

Baseline design prototype



Spring 2016

1x2 segments

1.2m length

50 liters

$^6\text{LiLS}$



PROSPECT AD-I

Physics measurement



2017

10x12 segments

1.2m length

~3 tons


$^6\text{LiLS}$




Development of PROSPECT Detector Components

Low-Mass Optical Separators

High reflectivity, high rigidity, low mass reflector system developed




- Array formed using 3D printed “pinwheel” spacers
- Chemical compatibility of all materials validated



Component design refined for final production



^6Li -Loaded Liquid Scintillator



- Developed non-toxic, non-flammable formulations based on EJ-309, LAB, Ultima Gold
- EJ-309 selected as baseline

Light Yield

- EJ-309 base: 11500 ph/MeV
- LiLS: 8200 ph/MeV




Excellent PSD performance for neutron capture & heavy recoils

Full-scale production for PROSPECT AD-1 underway

Full Scale Prototyping - PROSPECT20



Validates optical system design

- Li-loaded liquid scintillator
- Reflector panels



Light Yield/ PE Spectra

- Compton edge of ^{60}Co and ^{217}Bi γ -rays and the quenched (n, Li) capture peak from ^{252}Cf neutrons
- light collection: **522 \pm 16 PE/MeV**





Pulse Shape Discrimination

Unloaded LS studies described in 2015 JINST 10 P11004, [arXiv:1508.06575](https://arxiv.org/abs/1508.06575), PROSPECT collaboration

System Prototyping – PROSPECT50

Validates AD-1 component design


- Low-mass Optical Separators
- Support Structure
- PMT modules
- Filling System
- Calibration: LED & γ/n Sources



Mid-Segment LED Calibration




Source Capsule



PMT Modules



Segment Assembly



P-50 Installed in Shield

PROSPECT50 performance as expected based on earlier prototypes


Detailed technical publication forthcoming

Reactor Background Measurement & Shield Design



Shield design based on surveys & multiple onsite prototype deployments

Extensive measurement campaigns (*ongoing*):

- Characterize background field at HFIR
- Emphasize importance of localized shielding of penetrations, pipes, etc




Localized shielding studies



γ -ray intensity variation at HFIR

PROSPECT AD-1 Shielding

- local shielding next to reactor wall
- multi-layer passive shield:
 - water bricks, HDPE, borated HDPE, lead





AD-1 Multi-Layer Shield


Nucl. Instrum. Meth. A806 (2016) 401–419,
[arXiv:1506.03547](https://arxiv.org/abs/1506.03547), PROSPECT Collaboration

Signal to Background Prediction

Prototype systems provide benchmarking of AD-1 Monte Carlo





PROSPECT20 Correlated Background Measurements




Background rejection via:

- Efficient PSD & neutron identification
- Multi-interaction & multi-particle identification
- Fiducialization



S/B better than 1:1 is predicted for PROSPECT AD-1. Rate and shape of residual IBD-like background can be measured during numerous reactor off periods.

PROSPECT Collaboration



Supported by:

prospect.yale.edu



U.S. DEPARTMENT OF
ENERGY

Office of
Science



**HEISING-SIMONS
FOUNDATION**

Conclusion

- New data are required to address the rate and spectrum reactor anomalies
- PROSPECT Phase I will
 - Probe favored region for eV-scale sterile neutrinos at $>3\sigma$ with 3 years of data
 - Measure the ^{235}U $\bar{\nu}_e$ spectrum, addressing the observed spectral deviation, and providing new constraints on reactor antineutrino models complementary to current and future LEU measurements
- The PROSPECT R&D Program has:
 - developed LiLS detector technology that can mitigate reactor- and cosmogenic related backgrounds
 - Deployed multiple detectors at HFIR to validate models and operating procedures and prepare for full-size system deployment
 - Completed validation of system components for full scale production
- Proceeding with construction of the Phase I Antineutrino Detector
 - Ready to proceed with Phase II development
- Data taking expected to commence in 2017