



- NOTES
1. ARTWORK TO BE EMULSION UP POSITIVE.
 2. THIS REVERSE PATTERN TO BE ALIGNED WITH OBVERSE PATTERN (REF DRG NO 119/10033) TO WITHIN 0.05 MM.
 3. ALL COPPER TRACKS TO BE 18 MICRON THICKNESS AND UNTINNED.
 4. TRACK DETAIL INFORMATION AVAILABLE IN EITHER DXF OR HPGL FORMAT FOR MANUFACTURING PURPOSES.
 5. GENERAL DIMENSIONAL TOLERANCES TO APPLY TO EACH OF THE 3 PCB'S.

FOR OBVERSE PCB TRACK DRAWING
REF DRG NO 119/10033.
FOR SLOT MACHINING DETAIL DRAWING
REF DRG NO 119/10035.

WELDING SPEC		-----	
MATERIAL SPEC		FR4	
MATERIAL		0,5 MM THICK 18 MICRON DOUBLE SIDED COPPER CLAD PCB	
TOLERANCES UNLESS OTHERWISE STATED			
LINEAR DIMENSIONS UP TO 100 \pm 0,05 : OVER 100 \pm 0,1			
ANGULAR DIMENSIONS \pm 0,1°			
SCALE		0 500	
1:5			
ALL DIMENSIONS IN mm's UNLESS OTHERWISE STATED			
DRN.	GS	COUNCIL FOR THE CENTRAL LABORATORY OF THE RESEARCH COUNCILS	
DATE.	17/11/98	DARESBUURY LABORATORY	
CKD.	GS	CHESHIRE	
DATE.	17/11/98	TITLE	
CERT.	GS	HI PLANAR CHAMBER	
DATE.	17/11/98	REVERSE PCB TYPE B	
APPD.	GH	DRAWING N°	ISSUE
DATE.	17/11/98	AI-119/10034	B
USED ON		HERA	
CONTRACTORS COMPANY			
CONTRACTORS DRG N°			

A	FIRST ISSUE
B	THICKNESS CHANGED. NOTE 3 ADDED.
C	DATE
D	DATE
E	DATE
F	DATE
G	DATE
H	DATE
I	DATE
J	DATE